Learning from Demonstration with Weakly Supervised Disentanglement

Abstract

Robotic manipulation tasks, such as wiping with a soft sponge, require control from multiple rich sensory modalities. Human-robot interaction, aimed at teaching robots, is difficult in this setting as there is potential for mismatch between human and machine comprehension of the rich data streams. We treat the task of interpretable learning from demonstration as an optimisation problem over a probabilistic generative model. To account for the high-dimensionality of the data, a high-capacity neural network is chosen to represent the model. The latent variables in this model are explicitly aligned with high-level notions and concepts that are manifested in a set of demonstrations. We show that such alignment is best achieved through the use of labels from the end user, in an appropriately restricted vocabulary, in contrast to the conventional approach of the designer picking a prior over the latent variables. Our approach is evaluated in the context of a table-top robot manipulation task performed by a PR2 robot – that of dabbing liquids with a sponge (forcefully pressing a sponge and moving it along a surface). The robot provides visual information, arm joint positions and arm joint efforts. We have made videos of the task and data available - see supplementary materials at: https://sites.google.com/view/weak-label-lfd.

1 Introduction

Learning from Demonstration (LfD) (Argall et al., 2009) is a commonly used paradigm where a potentially imperfect demonstrator desires to teach a robot how to perform a particular task in its environment. Most often this is achieved through a combination of kinaesthetic teaching and supervised learning—imitation learning (Ross et al., 2011). However, such approaches do not allow for elaborations and corrections from the demonstrator to be seamlessly incorporated. As a result new demonstrations are required when either the demonstrator changes the task specification or the agent changes its context—typical scenarios in the context of interactive task learning (Laird et al., 2017). Such problems mainly arise because the demonstrator and the agent reason about the world by using *notions* and mechanisms at *different levels of abstraction*. A *modifiable* LfD setup requires establishing a mapping from the high-level notions humans use—e.g. spatial concepts, different ways of applying force—to the low-level perceptive and control signals robot agents utilise—e.g. joint angles, efforts and camera images. With this in place, any constraints or elaborations from the human operator, must be mapped to a behaviour on the agent's side that is consistent with the semantics of the operator's desires.

Concretely, we need to be able to ground (Vogt, 2002; Harnad, 1990) the specifications and symbols used by the operator in the actions and observations of the agent. Often the actions and the observations of a robot agent can be high-dimensional—high DoF kinematic chains, high image resolution, etc.—making the symbol grounding problem non-trivial. However, the concepts we need to be able to ground lie on a much-lower-dimensional manifold, embedded in the high-dimensional data space (Fefferman et al., 2016). For example, the concept of pressing softly against a surface manifests itself in a data stream associated with the 7 DoF real-valued space of joint efforts, spread across multiple time steps. However, the essence of what differentiates one type of soft press from another nearby concept can be summarised conceptually using a lower dimensional abstract space. The focus of this work is finding a nonlinear mapping (represented as a high-capacity neural model) between such a low-dimensional manifold and the high-dimensional ambient space of cross-modal data. Moreover, we show that, apart from finding such a mapping, we can also shape and refine the low-dimensional

Figure 1: User demos through teleoperation and a variety of modalities **(left)** are used to fit a common low-level disentangled manifold **(middle)** which contributes in an interpretable way to the generative process for new robot behaviour **(right)**.

manifold by imposing specific biases and structures on the neural model's architecture and training regime.

In this paper, we propose a framework which allows human operators to teach a PR2 robot about different spatial and force-related aspects of a robotic manipulation task, using tabletop dabbing as our main example. This task serves as a concrete representative task that incorporates key issues specific to robotics (e.g. continuous actions, forceful interactions, and discrete categorization of these). Numerous other applications require the very same capability. Our main contributions are:

- A learning method which incorporates information from multiple high-dimensional modalities—vision, joint angles, joint efforts—in order to instill a disentangled low-dimensional manifold (Locatello et al., 2019). By using weak expert labels during the optimisation process, the manifold eventually aligns with the human demonstrators' '*common sense*' notions in a natural and controlled way without the need of separate post-hoc interpretation.

- We release a dataset of subjective concepts grounded in multi-modal demonstrations. Using this, we evaluate whether discrete latent variables or continuous latent variables, both shaped by the discrete user labels, better capture the demonstrated continuous notions.

2   IMAGE-CONDITIONED TRAJECTORY & LABEL MODEL

In the task we use to demonstrate our ideas, which is representative of a broad class of robotic manipulation tasks, we want to control **where** and **how** a robot presses against a table-top surface through the use of a user specification defined by a set of coarse labels—e.g. *"press softly and slowly behind the cube in the image"*. In this context, let, $\mathbf{x}$ denote a $K \times T$ dimensional trajectory for K robot joints and a fixed time length T, $\mathbf{y}$ denote a set of discrete labels semantically grouped in N label groups $\mathcal{G} = \{g_1, \ldots, g_N\}$ (equivalent to multi-label classification problem) and $\mathbf{i}$ denote an RGB image[1]. The labels $\mathbf{y}$ describe qualitative properties of $\mathbf{x}$ and $\mathbf{x}$ with respect to $\mathbf{i}$—e.g. `left` dab, `right` dab, `hard` dab, `soft` dab, etc. We aim to model the distribution of demonstrated robot-arm trajectories $\mathbf{x}$ and corresponding user labels $\mathbf{y}$, conditioned on a visual environment context $\mathbf{i}$. This problem is equivalent to that of structured output representation (Walker et al., 2016; Sohn et al., 2015; Bhattacharyya et al., 2018)—finding a one-to-many mapping from $\mathbf{i}$ to $\{\mathbf{x}, \mathbf{y}\}$ (one image can be part of the generation of many robot trajectories and labels). For this we use a conditional generative model, whose latent variables $\mathbf{c} = \{\mathbf{c}_s, \mathbf{c}_e, \mathbf{c}_u\}$ can accommodate the aforementioned mapping—see Figure 2. The *meaning* behind the different types of latent variables—$\mathbf{c}_s, \mathbf{c}_e$ and $\mathbf{c}_u$—is elaborated in section 3.

We want the variability in the trajectory and label data to be concisely captured by $\mathbf{c}$. We choose by design the dimensionality of the latent variables to be much lower than the dimen-

---

[1]What $\mathbf{i}$ actually represents is a lower-dimensional version of the original RGB image $\mathbf{I}$. The parameters of the image encoder are jointly optimised with the parameters of the recognition and decoder networks

sionality of the data. Therefore, $\mathbf{c}$ is forced to represent abstract properties of the robot behaviour which still carry enough information for the behaviour to be usefully generated—absolute notions like speed, effort, length, and relative spatial notions which are grounded with respect to the visual context. Another way to think of $\mathbf{c}$ is as a continuous version of $\mathbf{y}$ which can therefore incorporate nuances of the same label. In the existing literature discrete labels are usually represented as discrete latent variables—e.g. digit classes (Kingma et al., 2014).

However, the discrete labels humans use are a rather crude approximation to the underlying continuous concepts—e.g. we may have the notion for a `soft` and a `softer` dab even though both would be alternatively labelled as `soft`. For this reason we use continuous latent variables, shaped by discrete labels, to represent these subjective concepts.

Figure 2: The lower-dimensional encoding $\mathbf{i}$ of the environment context $\mathbf{I}$ is observed. Conditioned on $\mathbf{i}$ and the latent variables $\mathbf{c}$, sampled from the prior over $\mathbf{c}$, we get a distribution over possible robot trajectories $\mathbf{x}$ and user labels $\mathbf{y}$.

The joint distribution over $\mathbf{x}$ and $\mathbf{y}$, conditioned on $\mathbf{i}$, is modelled according to Eq. 1. A prior of choice—isotropic Gaussian, Uniform, Categorical—is placed over the latent variables $\mathbf{c}$ which are independent of the image.

$$p(\mathbf{x}, \mathbf{y}|\mathbf{i}) = \int p(\mathbf{x}, \mathbf{y}|\mathbf{i}, \mathbf{c})p(\mathbf{c})d\mathbf{c} = \int p(\mathbf{x}|\mathbf{c}, \mathbf{i})p(\mathbf{y}|\mathbf{c})p(\mathbf{c})d\mathbf{c} \qquad (1)$$

We choose to represent the distribution over $\mathbf{x}$ and $\mathbf{y}$ as Gaussian and Multinomial distributions respectively. The parameters of these distributions are defined as nonlinear functions (of the image context and latent variables) which are represented as the weights θ of a neural network p_θ—$\boldsymbol{\mu}_\theta(\cdot)$ is a vector of means, $\boldsymbol{\sigma}_\theta(\cdot)$ is a vector of log variances and $\boldsymbol{\pi}_\theta(\cdot)$ is a vector of probabilities.

$$p_\theta(\mathbf{x}|\mathbf{c}, \mathbf{i}) = \mathcal{N}(\mathbf{x}|\boldsymbol{\mu}_\theta(\mathbf{c}, \mathbf{i}), \boldsymbol{\sigma}_\theta(\mathbf{c}, \mathbf{i})) \quad (2) \qquad\qquad p_\theta(\mathbf{y}|\mathbf{c}) = \mathrm{Cat}(\mathbf{y}|\boldsymbol{\pi}_\theta(\mathbf{c})) \qquad (3)$$

The parameters of p_θ are optimised by maximising the variational lower bound (VLB) of the data distribution—see Eq. 4. We additionally optimise a recognition network q_ϕ, parametrised by ϕ, which acts as an approximation to the posterior of $\mathbf{c}$, also modelled as a Gaussian. The recognition network q_ϕ is used to find good candidates of $\mathbf{c}$, for given $\mathbf{x}$ and $\mathbf{i}$, thus making the optimisation of θ, tractable (Kingma & Welling, 2013). The posterior is conditioned on the environment context as well, since $\mathbf{i}$ and $\mathbf{c}$ are conditionally dependent, once $\mathbf{x}$ is observed (Husmeier, 2005). Intuitively, we want some of the latent variables to represent relative spatial concepts—e.g. `left of` the cube in the image. For such concepts, under the same robot trajectory $\mathbf{x}$ we should get different latent codes, given different contexts $\mathbf{i}$. The omission of $\mathbf{y}$ from q_ϕ means that we might not be able to fully close the gap between the data distribution and its VLB, leading to a less efficient optimisation procedure (due to higher variance). That is mainly owing to the fact that we use weak supervision—only for some demonstrations do we have labels $\mathbf{y}$. The derivation of and commentary on the optimised VLB are provided in the Supplementary Materials.

$$\log p(\mathbf{x}, \mathbf{y}|\mathbf{i}) \geq \mathbb{E}_{q_\phi(\mathbf{c}|\mathbf{x}, \mathbf{i})}(\log p_\theta(\mathbf{x}, \mathbf{y}|\mathbf{c}, \mathbf{i})) -$$
$$D_{KL}(q_\phi(\mathbf{c}|\mathbf{x}, \mathbf{i})||p(\mathbf{c})) \qquad (4) \qquad q_\phi(\mathbf{c}|\mathbf{x}, \mathbf{i}) = \mathcal{N}(\mathbf{c}|\boldsymbol{\mu}_\phi(\mathbf{x}, \mathbf{i}), \boldsymbol{\sigma}_\phi(\mathbf{x}, \mathbf{i})) \quad (5)$$

3 WEAK LABELLING AND USER SPECIFICATION

Interpretability through Weak Labels Even though the latent variables are constrained to be useful both for the tasks of trajectory and label generation, nothing forces them to carry the intuitive absolute and relative notions described in Section 2 in a factorised fashion—e.g. c_1 corresponds to the effort applied when pressing against the table, c_2 corresponds to how quickly the robot presses against the table, etc. Under an optimised model, those notions can be captured in $\mathbf{c}$ but with no guarantee that they will be represented in an **interpretable** way— i.e. $\mathbf{c}$ needs to be **disentangled**. We achieve disentanglement in the latent space by establishing a one-to-one correspondence between a subset of the latent axes—$\mathbf{c}_s, \mathbf{c}_e$—and the concept groups in $\mathcal{G}$ (Hristov et al., 2018). $\mathbf{c}_s$ is opti-

mised to represent spatial notions, $\mathbf{c}_e$—effort-related notions. The rest of the latent dimensions—$\mathbf{c}_u$—encode features in the data which don't align with the semantics of the labels and their concept groups but are still necessary for good trajectory reconstruction (Figure 2). Under these assumptions the label likelihood from Eq. 3 becomes:

$$p_\theta(\mathbf{y}|\{\mathbf{c}_s, \mathbf{c}_e\}) = \prod_j^{|\mathcal{G}|} \mathbf{1}_{\{y_j \neq \emptyset\}} \text{Cat}(y_j|\boldsymbol{\pi}_j(c_j)) \tag{6}$$

Labelling is **weak/restricted** since each demonstration is given just a single label from a single concept group. This is meant to represent a more natural LfD scenario, where the main task of the expert is still to perform a number of demonstrations, rather than to exhaustively annotate each demonstration with relevant labels from all groups. For example, a demonstrator might say *"this is how you press softly"* and proceed to perform the demonstration (as is common, say, in an instructional video). The demonstrated behaviour might also be `slow` and `short` but the demonstrator may not have been explicitly thinking about these notions, hence may not have labelled accordingly. The missing label values are incorporated with an indicator function in Eq. 6.

Condition on User Specification   Apart from being used in the optimisation objective, the weak labels are also used in an additional conditioning step at test time. The generative process we have consists of first sampling values for $\mathbf{c}$ from its prior. These are then passed together with $\mathbf{i}$ through p_θ in order to get distributions over $\mathbf{x}$ and $\mathbf{y}$, from which we can sample. However, we are really interested in being able to incorporate the provided information about the labels $\mathbf{y}$ into the sampling of semantically aligned parts of $\mathbf{c}$. Specifically, we are interested in being able to generate robot behaviours which are consistent with chosen values for $\mathbf{y}$ (what we call a **user specification**). Post-optimising the θ and ϕ parameters, we choose to approximate the posterior over $\mathbf{c}$ for each label l in each concept group j with a set of Gaussian distributions $\mathcal{N}(\boldsymbol{\mu}_{jl}, \boldsymbol{\Sigma}_{jl})$. We use Maximum Likelihood Estimation for $\boldsymbol{\mu}_{jl}$ and $\boldsymbol{\Sigma}_{jl}$ over a set of samples from $\mathbf{c}$. The samples are weighted with the corresponding label likelihood $p_\theta(y_j = l|\boldsymbol{\pi}_j(c_j))$. As a result, the process of generating a trajectory $\mathbf{x} \sim p_\theta(\mathbf{x}|\mathbf{i}, \mathbf{c})$ can be additionally conditioned on an optional user specification $\mathbf{y} = \{y_1, \ldots, y_{|\mathcal{G}|}\}$, through $\mathbf{c}$, in a single-label fashion (Eq. 7) or a compositional fashion (Eq. 8). Pseudo-code for the generation of trajectories for both types of conditioning is provided in the Supplementary Materials.

$$\mathbf{c} \sim p(\mathbf{c}|y_j = l) = \mathcal{N}(\mathbf{c}|\boldsymbol{\mu}_{jl}, \boldsymbol{\Sigma}_{jl}) \tag{7}$$

$$\forall j \in \{1, \ldots, |\mathbf{c}|\}: c_j \sim p(c_j|y_j = l) = \begin{cases} \text{prior}, & \text{if } y_j = \emptyset \text{ or } j > |\mathcal{G}| \\ \mathcal{N}(\mathbf{c}|\boldsymbol{\mu}_{jl}, \boldsymbol{\Sigma}_{jl})_{(j)}, & \text{otherwise} \end{cases} \tag{8}$$

4   METHODOLOGY

In terms of a concrete model architecture, our model is a Conditional Variational Autoencoder (CVAE) (Sohn et al., 2015) with an encoding network q_ϕ and a decoding network p_θ. The parameters of both networks are optimised jointly using methods for amortised variational inference and a stochastic gradient variational bayes estimation (Kingma & Welling, 2013).[2]

Encoding & Decoding Networks   Due to the diversity of modalities that we want to use, q_ϕ is implemented as a combination of 2D convolutions (for the image input), 1D convolutions (for the trajectoy input) and an MLP that brings the the output of the previous two modules to the common concept manifold $\mathbf{c}$. For the decoding network we implement a Temporal Convolutional Network (TCN) (Bai et al., 2018) which operates over the concatenation $\mathbf{h}$ of a single concept embedding $\mathbf{c}$ and a single image encoding $\mathbf{i}$. However, the TCN takes a sequence of length T and transforms it to another sequence of length T, by passing it through a series of dilated convolutions, while $\mathbf{h}$ is equivalent to a sequence of length 1. Thus, we tile the concatenated vector T times and to each instance of that vector $\mathbf{h}_i, i \in \{1, \ldots, T\}$, we attach a time dimension $t_i = \frac{i}{T}$. This broadcasting technique has previously shown to achieve better disentanglement in the latent space both on visual

---

[2]The models are implemented in PyTorch (Adam et al., 2017) and optimised using the Adam optimiser (Kingma & Ba, 2014)

(Watters et al., 2019) and time-dependent data (Noseworthy et al., 2019). We only set up the mean $\boldsymbol{\mu}_\theta$ of the predicted distribution over $\mathbf{x}$ to be a non-linear function of $[\mathbf{h}; \mathbf{t}]$ while $\boldsymbol{\sigma}$ is fixed, for better numerical stability during training. This allows us to use the $L2$ distance—Mean Squared Error (MSE)—between the inferred trajectories μ_θ, acting as a reconstruction, and the ground truth ones.

Label Predictors For each concept group g_j we take values from the corresponding latent axis c_j and pass it through a single linear layer, with a softmax activation function, to predict a probability vector $\boldsymbol{\pi}_j$. Maximising the label likelihood is realised as a Softmax-Cross Entropy (SCE) term in the loss function. Optimising this term gives us better guarantee that the some of the latent axes will be semantically aligned with the notions in the label groups. The fact that some labels might be missing is accounted for with an indication function which calculates $\nabla\theta, \nabla\phi$ with respect to the SCE, only if y_j is present.

Weighted Loss The full loss function that we optimise is presented in Eq. 9. It is composed of three main terms—the trajectory MSE, equivalent to the negative trajectory log likelihood, the label SCE, equivalent to the negative weak label log likelihood and the KL divergence between the fit amortised posterior over $\mathbf{c}$ and its prior. The concrete values of the three coefficients—α, β, γ—are discussed in the Supplementary Materials.

$$\min_{\theta,\phi,\mathbf{w}} \mathcal{L}(\mathbf{x}, \mathbf{y}, \mathbf{I}) = \beta D_{KL}(\underbrace{q_\phi(\mathbf{c}|\mathbf{x},\mathbf{I})}_{\substack{\text{amortised}\\\text{posterior}}} || \underbrace{p_\theta(\mathbf{c})}_{\text{prior}}) + \alpha \mathbb{E}_{q_\phi(\mathbf{c}|\mathbf{x},\mathbf{I})}(\log \underbrace{p_\theta(\mathbf{x}|\mathbf{c},\mathbf{I})}_{\text{MSE}}) + \gamma \sum_i^{|\mathcal{G}|} \underbrace{\mathbf{1}_{\{y_i \neq \emptyset\}} H(c_i \mathbf{w}_i^T, y_i)}_{\text{SCE}}$$

(9)

5 EXPERIMENTS

The models we experiment with include a Variational Autoencoder (Kingma & Welling, 2013) with a Gaussian prior (VAE), an Adversarial Autoencoder (Makhzani et al., 2015) with a Uniform prior (AAE) and a VAE with mixed continuous and categorical latent variables (GS). For the last model, the continuous variables have a Gaussian prior and the categorical variables utilise the Gumbel-Softmax reparametrisation (Jang et al., 2017). For each of the three models we train them while utilising the weak labels—VAE-weak, AAE-weak, GS-weak—and with no label information—VAE, AAE, GS. Whether or not labels are used during training is controlled by setting $\gamma = 0$ in Eq. 9.

The setup used in the experiments consists of a PR2 robot, an HTC Vive controller and headset, and a tabletop with a single object on it—a red cube. Multiple pressing motions on the surface of the table are demonstrated by teleoperating the end effector of the robot. The pose of the end effector, with respect to the robot's torso, is mapped to be the same as the pose of the controller (held by the demonstrator) with respect of the headset (behind the demonstrator in Figure 4).

Data A total of 100 demonstrations were captured from the PR2, consisting of:

- Initial frame of each demonstration: 128x128-pixel Kinect2 image (RGB);
- 7-DoF joint angle positions;
- 7-DoF joint efforts;
- 5 groups of discrete weak labels;

Each demonstration has a single label attached to it. In total we have 4 spatial symbols—where in the image, with respect to the red cube, do we dab—and 6 force-related symbols—how do we dab (Table 1). Figure 3 provides a graphical depiction demonstrating the differences between the different force-relate groupings qualitatively.

spatial (where)	effort (how)
Image + Joint Angles	Joint Efforts
left & right	**soft & hard**
front & behind	**short & long**
	fast & slow

Table 1: All labels and modalities used in the demonstrations.

All trajectories are standardised to be of fixed length—the length of the longest trajectory (240 timesteps)—by padding them with the last value for each channel/joint. Additionally, both the joint positions and efforts are augmented with Gaussian noise or by randomly sliding them leftwards (simulating an earlier start) and padding accordingly. The size of the total dataset after augmentation

Figure 3: Example user-given labels across 6 different demonstrations. Depicted are effort trajectories from the training data for a single robot joint—`shoulder lift joint`—**(a)** and **(b)** designate the maximal exerted effort, **(c)** and **(d)** designate the length for which the maximal effort is maintained, **(e)** and **(f)** designate the time to reach the maximal effort (slope).

is 1000 demonstrations which are split according to a 90-10 training-validation split. The size of the latent space is chosen to be $|\mathbf{c}| = 8$. In the context of the problem formulation in Section 2, $\mathbf{c}_s = \{c_0, c_1\}$, $\mathbf{c}_e = \{c_2, c_3, c_4\}$ and $\mathbf{c}_u = \{c_5, c_6, c_7\}$.

Figure 4: Physical setup for teleoperating a PR2 end-effector through an HTV Vive controller.

Conditioning on a Single Label We use the Gaussian distributions for each label l in each concept group j—$\mathcal{N}(\boldsymbol{\mu}_{jl}, \boldsymbol{\Sigma}_{jl})$—to sample and generate trajectories that are consistent with the meaning of a particular label. For a set of 5 test images, which have not been seen during training, we draw 1000 samples of $\mathbf{c}$ per image for each of the 10 labels. For each label we then judge whether the generated trajectories match the semantics of the corresponding label using a series of manually-designed heuristics, described in the Supplementary Materials. Average accuracy across all images and all samples is reported for each label. For the labels of a spatial nature, for each 7-dimensional (7 DoFs) robot state x_i, $\mathbf{x} = \{x_1, \ldots, x_T\}$, we compute the corresponding end-effector pose p_i through the forward kinematics $\mathbf{K}$ of the robot. Using the camera model of the Kinect2 sensor, each pose p_i is projected in the image we condition on. We report the Mean Absolute Error (MAE) in normalised pixel coordinates between the dab location and the landmark location (in pixel coordinates) for the misclassified trajectories. This gives us a sense of how far from the desired ones the generated samples are. The dab location is inferred as the point in the end-effector pose trajectory with lowest z coordinate. For example, if we have conditioned on the `left` label but some of the sampled trajectories result in a dab to the `right` of the cube in the image, we report *how far* from the true classification of `left` was the robot when it touched the table.

Conditioning on a Composition of Labels Since the concepts we encode in the latent space of the model should be independent of each other they can be composed together—e.g. a trajectory can be simultaneously `hard`, `long` and `fast`. We examine how well is this conceptual independence preserved in the latent space by generating trajectories conditioned on all possible combinations of labels regarding effort, speed and length of press—8 possible combinations in total. We still use the Gaussian distributions for each label in each concept group but only take the values along the relevant latent axis—Eq. 8. To fully close the loop, the trajectories which we sample from the model could further be executed on the physical robot through a hybrid position/force controller (Reibert, 1981). However, such evaluation is beyond the scope of the paper.

6 RESULTS & DISCUSSION

Our experiments demonstrate that the models which utilise weak user labels within our proposed setup can more reliably generate behaviours consistent with a given spatial or force-related user specification, in contrast to baseline models which do not benefit from such information. Moreover,

we find that continuous latent variables better capture the independent continuous notions which underlie the discrete user labels in comparison to discrete latent variables. Below we present quantitative results from the experiments with further qualitative results in the Supplementary Materials.

When conditioning on a single force label—Table 3—the best-performing models are VAE-weak and AAE-weak. In the worse-performing cases—VAE, GS—it would appear that the models suffer from partial mode collapse. For instance, in Table 3, penultimate row, the VAE can not represent `soft` trajectories, most samples are `hard`. Interestingly AAE and AAE-weak perform similarly well. We attribute that to the fact the Uniform prior used does not have a discrete number of modes to which the optimised posterior might potentially collapse. Simultaneously, regardless of their prior, none of the *weak* models suffer from mode collapse, since the label information helps for the corresponding notions to be more distinguishable in the latent space. All models have high accuracy, when conditioned on a spatial label—Table 2. However, GS-weak, VAE-weak and AAE-weak appear to be closer to the true conditioned-on concept when a bad trajectory is generated, as measured by the lower Mean Absolute Error of the image-projected end-effector positions.

	left		right		front		back	
Model	Acc	MAE	Acc	MAE	Acc	MAE	Acc	MAE
GS	0.83 (0.09)	0.052	0.76 (0.22)	0.040	0.85 (0.09)	0.039	0.90 (0.10)	0.060
GS-weak	0.78 (0.16)	**0.034**	**0.92** (0.13)	**0.013**	**0.92** (0.09)	**0.030**	**0.94** (0.06)	**0.028**
AAE	0.84 (0.12)	0.043	0.88 (0.09)	0.043	0.81 (0.15)	0.039	0.97 (0.03)	0.024
AAE-weak	0.84 (0.24)	**0.018**	**0.89** (0.12)	**0.039**	**0.83** (0.19)	**0.030**	**0.98** (0.04)	**0.022**
VAE	0.80 (0.18)	0.026	0.82 (0.19)	0.031	0.86 (0.08)	0.050	0.97 (0.05)	0.029
VAE-weak	**0.95** (0.07)	0.031	**0.87** (0.14)	**0.026**	**0.93** (0.10)	**0.027**	**0.99** (0.02)	**0.018**

Table 2: Accuracy (mean and std deviation; higher mean is better) and MAE (lower is better) for sampled trajectories under all models, conditioned on a fixed spatial label. Bold numbers designate when the weak version of the model (utilising the weak user labels) outperforms the non-weak one.

Model	soft	hard	short	long	slow	fast
GS	0.26 (0.01)	0.96 (0.01)	0.95 (0.00)	0.76 (0.01)	0.92 (0.01)	0.77 (0.01)
GS-weak	**0.84** (0.01)	**0.98** (0.00)	**0.98** (0.00)	0.69 (0.01)	0.88 (0.01)	0.74 (0.02)
AAE	0.98 (0.00)	1.00 (0.00)	1.00 (0.00)	0.75 (0.01)	0.93 (0.01)	0.64 (0.01)
AAE-weak	0.98 (0.00)	0.99 (0.00)	0.99 (0.00)	**0.97** (0.01)	0.84 (0.01)	**0.84** (0.01)
VAE	0.04 (0.01)	0.95 (0.00)	0.96 (0.01)	0.59 (0.01)	0.93 (0.01)	0.52 (0.01)
VAE-weak	**0.92** (0.00)	**1.00** (0.00)	**1.00** (0.00)	**0.90** (0.01)	**0.95** (0.00)	**0.68** (0.01)

Table 3: Accuracy (mean and std deviation) for sampled trajectories under all models, conditioned on a fixed effort label. Bold numbers designate when the weak version of the model (utilising the weak user labels) outperforms the non-weak one.

Figure 5: Accuracy comparison for generated trajectories conditioned on all compositions of binary labels from the three concept groups for effort, length and speed. The models with continuous latent spaces outperform the discrete one as the underlying concepts are continuous themselves.

While single-label conditioning is possible under all models, it is only VAE-weak, AAE-weak and GS-weak which provide a reliable mechanism for *composing* labels from different independent concept groups. That is possible due to the explicit alignment of each concept and its labels with a single latent axis. Trajectory generation is done after conditioning on compositions of labels from the three independent concept groups designating effort—see Table 1 (right column). Specifically, the difference between the sampled latent values for `hard long slow` and `hard long fast`, for example, are only along the axis used to predict `slow` from `fast`—c_4 in this case. If the generated trajectories match their specification (high measured accuracy) then indeed the perturbed axis is aligned with the notion behind the perturbed labels. Results from this experiment are presented in Figure 5. Evidently, the better-performing models are the ones with continuous latent variables. While the VAE-weak and AAE-weak perform equally well for most label combinations, and do manage to encode independent concepts as such (along specific latent axes), the model with the mix of continuous and categorical latent variables (GS-weak) does not match their results. Taking the second row in Table 3 into account, this means that the categorical model (which has more constrained capacity than the VAE-weak and AAE-weak) can capture the data distribution (shows good single-label-conditioning reconstructions) but in an entangled fashion. Namely, going from `slow` to `fast` corresponds to perturbing more than a single latent axis simultaneously. This further supports our initial hypothesis that while discrete, the weak labels only provide a mechanism for shaping the latent representation of what are otherwise continuous phenomena.

7 RELATED WORK

Methods which utilise high-parameter neural models to learn disentangled low-dimensional representation achieve that by either tuning the optimised loss function (Higgins et al., 2017; Chen et al., 2018), imposing crafted priors over the latent space (Chen et al., 2016) or using weak supervision (Hristov et al., 2019; Rasmus et al., 2015). While being able to produce interpretable manifolds, most of these approaches focus on modelling visual data and respectively visually-manifested concepts, with minor exceptions—e.g. modelling motion capture data (Ainsworth et al., 2018). In contrast, we solve a problem involving multiple heterogeneous modalities—vision, forces, joint angles. Moreover, in addition to separating factors of variation in the data, to achieve latent space interpretability, we also deal with the problem of entanglement across modalities—i.e. which factors relate to which data modalities.

Dynamic Movement Primitives (Schaal, 2006) and Probabilistic Movement Primitives (Paraschos et al., 2013) are commonly used to model dynamical systems as 'point-mass attractors with a non-linear forcing term'. However, the resulting control parameters can be high-dimensional and un-intuitive for end-user manipulation. Performing dimensionality reduction (Colomé et al., 2014) or imposing hierarchical priors (Rueckert et al., 2015) are both ideas seen in the literature as a means of making the high-dimensional parameter space more meaningful to the human demonstrator. These have the advantage of yielding a clearer idea of how changes in the optimised parameters result in deterministic changes in the generated behaviours. However, most of these approaches limit themselves to end-effector trajectories, or – at most – making use of visual input (Kober et al., 2008).

Noseworthy et al. (2019) explore disentangling task parameters from manner of execution parameters, in the context of pouring. They utilise an adversarial training regime, which facilitates better separation of the two types of parameters in the latent space. However, it is assumed that the task parameters are known *a priori*. Interpretation of the learned codes is achieved post-training by perturbing latent axis values and qualitatively inspecting generated trajectories (standard evaluation technique for models which are trained unsupervised). We argue that through the use of weak supervision through discrete labels we have finer control over the 'meaning' of latent dimensions.

8 CONCLUSION

We recontextualise the problem of interpretable multi-modal LfD as a problem of formulating a conditional probabilistic model. In the example task of table-top dabbing, we utilise weak discrete labels from the demonstrator to represent abstract notions, manifested in a captured multi-modal robot dataset. Through the use of high-capacity neural models and methods from deep variational

inference, we show how to align some of the latent variables of the formulated probabilistic model with high-level notions implicit in the demonstrations.

REFERENCES

Paszke Adam, Gross Sam, Chintala Soumith, Chanan Gregory, Yang Edward, D Zachary, Lin Zeming, Desmaison Alban, Antiga Luca, and Lerer Adam. Automatic differentiation in pytorch. In *Proceedings of Neural Information Processing Systems*, 2017.

Samuel K. Ainsworth, Nicholas J. Foti, Adrian K. C. Lee, and Emily B. Fox. oi-VAE: Output interpretable VAEs for nonlinear group factor analysis. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 119–128, Stockholmsmässan, Stockholm Sweden, 10–15 Jul 2018. PMLR. URL http://proceedings.mlr.press/v80/ainsworth18a.html.

Brenna D Argall, Sonia Chernova, Manuela Veloso, and Brett Browning. A survey of robot learning from demonstration. *Robotics and autonomous systems*, 57(5):469–483, 2009.

Shaojie Bai, J Zico Kolter, and Vladlen Koltun. An empirical evaluation of generic convolutional and recurrent networks for sequence modeling. *arXiv preprint arXiv:1803.01271*, 2018.

Apratim Bhattacharyya, Bernt Schiele, and Mario Fritz. Accurate and diverse sampling of sequences based on a "best of many" sample objective. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 8485–8493, 2018.

Tian Qi Chen, Xuechen Li, Roger B Grosse, and David K Duvenaud. Isolating sources of disentanglement in variational autoencoders. In *Advances in Neural Information Processing Systems*, pp. 2610–2620, 2018.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *Advances in Neural Information Processing Systems*, pp. 2172–2180, 2016.

Adrià Colomé, Gerhard Neumann, Jan Peters, and Carme Torras. Dimensionality reduction for probabilistic movement primitives. In *2014 IEEE-RAS International Conference on Humanoid Robots*, pp. 794–800. IEEE, 2014.

Charles Fefferman, Sanjoy Mitter, and Hariharan Narayanan. Testing the manifold hypothesis. *Journal of the American Mathematical Society*, 29(4):983–1049, 2016.

Stevan Harnad. The symbol grounding problem. *Physica D: Nonlinear Phenomena*, 42(1-3):335–346, 1990.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. *ICLR*, 2(5):6, 2017.

Yordan Hristov, Alex Lascarides, and Subramanian Ramamoorthy. Interpretable latent spaces for learning from demonstration. In Aude Billard, Anca Dragan, Jan Peters, and Jun Morimoto (eds.), *Proceedings of The 2nd Conference on Robot Learning*, volume 87 of *Proceedings of Machine Learning Research*, pp. 957–968. PMLR, 29–31 Oct 2018. URL http://proceedings.mlr.press/v87/hristov18a.html.

Yordan Hristov, Daniel Angelov, Michael Burke, Alex Lascarides, and Subramanian Ramamoorthy. Disentangled relational representations for explaining and learning from demonstration. In *Conference on Robot Learning (CoRL)*, 2019.

Dirk Husmeier. Introduction to learning bayesian networks from data. In *Probabilistic modeling in bioinformatics and medical informatics*, pp. 17–57. Springer, 2005.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparametrization with gumble-softmax. In *International Conference on Learning Representations (ICLR 2017)*. OpenReview. net, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Durk P Kingma, Shakir Mohamed, Danilo Jimenez Rezende, and Max Welling. Semi-supervised learning with deep generative models. In *Advances in neural information processing systems*, pp. 3581–3589, 2014.

Jens Kober, Betty Mohler, and Jan Peters. Learning perceptual coupling for motor primitives. In *2008 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 834–839. IEEE, 2008.

John E Laird, Kevin Gluck, John Anderson, Kenneth D Forbus, Odest Chadwicke Jenkins, Christian Lebiere, Dario Salvucci, Matthias Scheutz, Andrea Thomaz, Greg Trafton, et al. Interactive task learning. *IEEE Intelligent Systems*, 32(4):6–21, 2017.

Francesco Locatello, Stefan Bauer, Mario Lucic, Gunnar Raetsch, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. In *International Conference on Machine Learning*, pp. 4114–4124, 2019.

Alireza Makhzani, Jonathon Shlens, Navdeep Jaitly, Ian Goodfellow, and Brendan Frey. Adversarial autoencoders. *arXiv preprint arXiv:1511.05644*, 2015.

Michael D. Noseworthy, Rohan Paul, Subhro Roy, Daehyung Park, and Nicholas Roy. Task-conditioned variational autoencoders for learning movement primitives. 2019.

Alexandros Paraschos, Christian Daniel, Jan R Peters, and Gerhard Neumann. Probabilistic movement primitives. In *Advances in neural information processing systems*, pp. 2616–2624, 2013.

Antti Rasmus, Mathias Berglund, Mikko Honkala, Harri Valpola, and Tapani Raiko. Semi-supervised learning with ladder networks. In *Advances in Neural Information Processing Systems*, pp. 3546–3554, 2015.

MH Reibert. Hybrid position/force control of manipulators. *ASME, J. of Dynamic Systems, Measurement, and Control*, 103:2–12, 1981.

Stéphane Ross, Geoffrey Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 627–635, 2011.

Elmar Rueckert, Jan Mundo, Alexandros Paraschos, Jan Peters, and Gerhard Neumann. Extracting low-dimensional control variables for movement primitives. In *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1511–1518. IEEE, 2015.

Stefan Schaal. Dynamic movement primitives-a framework for motor control in humans and humanoid robotics. In *Adaptive motion of animals and machines*, pp. 261–280. Springer, 2006.

Kihyuk Sohn, Honglak Lee, and Xinchen Yan. Learning structured output representation using deep conditional generative models. In *Advances in neural information processing systems*, pp. 3483–3491, 2015.

Paul Vogt. The physical symbol grounding problem. *Cognitive Systems Research*, 3(3):429–457, 2002.

Jacob Walker, Carl Doersch, Abhinav Gupta, and Martial Hebert. An uncertain future: Forecasting from static images using variational autoencoders. In *European Conference on Computer Vision*, pp. 835–851. Springer, 2016.

Nick Watters, Loic Matthey, Chris P Burgess, and Alexander Lerchner. Spatial broadcast decoder: A simple architecture for disentangled representations in vaes. 2019.

A   VARIATIONAL LOWER BOUND DERIVATION

For completeness we include a derivation of the Variational Lower Bound of the data likelihood. The VLB is used as an optimisation objective—Eq. 9. Jensen's inequality becomes an equality when the amortised posterior $q(\mathbf{c}|\mathbf{x}, \mathbf{i})$ matches exactly the true posterior $p(\mathbf{c}|\mathbf{x}, \mathbf{i}, \mathbf{y})$. The posterior we optimise is not conditioned on $\mathbf{y}$, potentially meaning that we might never close the gap between the $\log$ of the data distribution and the VLB, measured by $D_{KL}(q(\mathbf{c}|\mathbf{x}, \mathbf{i})||p(\mathbf{c}|\mathbf{x}, \mathbf{i}, \mathbf{y}))$. However, maximising the VLB still goes in the direction of maximising the data distribution.

$$
\begin{aligned}
\log p(\mathbf{x}, \mathbf{y}|\mathbf{i}) &= \log \int p(\mathbf{x}, \mathbf{y}|\mathbf{i}, \mathbf{c})p(\mathbf{c})d\mathbf{c} \\
&= \log \int p(\mathbf{x}|\mathbf{i}, \mathbf{c})p(\mathbf{y}|\mathbf{c})p(\mathbf{c})d\mathbf{c} \\
&= \log \int \frac{q(\mathbf{c}|\mathbf{x}, \mathbf{i})}{q(\mathbf{c}|\mathbf{x}, \mathbf{i})}p(\mathbf{x}|\mathbf{i}, \mathbf{c})p(\mathbf{y}|\mathbf{c})p(\mathbf{c})d\mathbf{c} \\
&= \log \mathbb{E}_{q(\mathbf{c}|\mathbf{x}, \mathbf{i})} \frac{p(\mathbf{x}|\mathbf{i}, \mathbf{c})p(\mathbf{y}|\mathbf{c})p(\mathbf{c})}{q(\mathbf{c}|\mathbf{x}, \mathbf{i})} \\
&\geq \mathbb{E}_{q(\mathbf{c}|\mathbf{x}, \mathbf{i})} \log \frac{p(\mathbf{x}|\mathbf{i}, \mathbf{c})p(\mathbf{y}|\mathbf{c})p(\mathbf{c})}{q(\mathbf{c}|\mathbf{x}, \mathbf{i})} \quad\quad\quad\quad\quad\quad [\text{Jensen}] \\
&= \mathbb{E}_{q(\mathbf{c}|\mathbf{x}, \mathbf{i})} \log p(\mathbf{x}|\mathbf{i}, \mathbf{c}) + \mathbb{E}_{q(\mathbf{c}|\mathbf{x}, \mathbf{i})} \log p(\mathbf{y}|\mathbf{c}) - \mathbb{E}_{q(\mathbf{c}|\mathbf{x}, \mathbf{i})} \log \frac{q(\mathbf{c}|\mathbf{x}, \mathbf{i})}{p(\mathbf{c})} \\
&= \mathbb{E}_{q(\mathbf{c}|\mathbf{x}, \mathbf{i})} \log p(\mathbf{x}|\mathbf{i}, \mathbf{c}) + \mathbb{E}_{q(\mathbf{c}|\mathbf{x}, \mathbf{i})} \log p(\mathbf{y}|\mathbf{c}) - D_{KL}(q(\mathbf{c}|\mathbf{x}, \mathbf{i})||p(\mathbf{c})) \\
&= -(D_{KL}(q(\mathbf{c}|\mathbf{x}, \mathbf{i})||p(\mathbf{c})) - \mathbb{E}_{q(\mathbf{c}|\mathbf{x}, \mathbf{i})} \log p(\mathbf{x}|\mathbf{i}, \mathbf{c}) - \mathbb{E}_{q(\mathbf{c}|\mathbf{x}, \mathbf{i})} \log p(\mathbf{y}|\mathbf{c})) \\
&= -(\mathcal{L})
\end{aligned}
$$

$$\tag{10}$$

B   LABEL CONDITIONING & EVALUATION HEURISTICS

Algorithms 1 and 2 provide pseudo-code for the trajectory generation procedures described in Section 3. The main difference can be summarised as following—when the generative process is conditioned on a single label l, all 8 dimensions of the latent samples are drawn from a single 8-dimensional Gaussian distribution associated with that label and its concept group—line 2 in Algorithm 1. However, when the process is conditioned on a composition of labels from different groups—a user specification—the sampling procedure differs as $\mathbf{c}$ is iteratively built. For each latent axis c_j, if a label is specified for the concept group aligned with c_j, only the values along the j-th axis are taken of a sample from the corresponding 8-dimensional Gaussian. If no label is given, c_j is sampled from a Standard Normal distribution $\mathcal{N}(0, 1)$ (or the respective prior of choice.

Same applies for latent dimensions which have not been aligned with any concept groups, since $|\mathbf{c}| > |\mathcal{G}|$—lines 2 to 9 in Algorithm 2.

Algorithm 1: Trajectory generation conditioned on a single label

---

Input: Visual Scene image $\mathbf{I}$
Input: Single user label y from concept group g
Input: Image encoder, part of p_θ
Input: Decoder network q_ϕ
Input: set of Gaussian distribution for each label in each concept group:
$\quad\quad K = \{\{\mathcal{N}(\mu_{jl}, \Sigma_{jl})\}, j \in \{1, \ldots, |\mathcal{G}|\}, l \in \{1, \ldots, |g_j|\}$
Output: Generated trajectory $\hat{\mathbf{x}}$ of time length T

1   encode image input $\mathbf{i} \leftarrow p_\theta(\mathbf{I})$;
2   sample latent values $\mathbf{c} \sim \mathcal{N}(\mathbf{c}|\boldsymbol{\mu}_{jl}, \boldsymbol{\Sigma}_{jl})$, such that $j = g, l = y$;
3   concatenate $\mathbf{c}$ and $\mathbf{i}$: $\mathbf{h} \leftarrow [\mathbf{c}; \mathbf{i}]$;
4   tile $\mathbf{h}$ T times;
5   attach a last time dimension $\mathbf{h} = [\mathbf{h}; \mathbf{t}], \mathbf{t} = \{t_1, \ldots, t_T\}, t_i = \frac{i}{T}$;
6   generate trajectory $\hat{\mathbf{x}} \leftarrow q_\phi(\mathbf{x}|\mathbf{h})$;
7   return $\hat{\mathbf{x}}$;

Algorithm 2: Trajectory generation conditioned on a composition of labels

---

Input: Visual Scene image $\mathbf{I}$
Input: User label specification $\mathbf{y} = \{y_1, \ldots, y_{|\mathcal{G}|}\}$, potentially one label for each concept group
Input: Image encoder, part of p_θ
Input: Decoder network q_ϕ
Input: set of Gaussian distribution for each label in each concept group:
$\quad\quad K = \{\mathcal{N}(\mathbf{c}|\boldsymbol{\mu}_{jl}, \boldsymbol{\Sigma}_{jl})\}, j \in \{1, \ldots, |\mathcal{G}|\}, l \in \{1, \ldots, |g_j|\}$
Output: Generated trajectory $\hat{\mathbf{x}}$ of time length T

1   encode image input $\mathbf{i} \leftarrow p_\theta(\mathbf{I})$;
2   init $\mathbf{c} = []$;
3   **for** *each latent dimension $c_j \in \mathbf{c}$* **do**
4   **if** $y_j \neq \emptyset$ *and* $j <= |\mathcal{G}|$ **then**
5   sample $\mathbf{w} \sim \mathcal{N}(\mathbf{w}|\boldsymbol{\mu}_{jl}, \boldsymbol{\Sigma}_{jl})$, such that, $l = y_j$;
6   only take values along the j-th dimension: append $\mathbf{w}[j]$ to $\mathbf{c}$;
7   **else**
8   sample $w \sim \mathcal{N}(w|0, 1)$;
9   append w to $\mathbf{c}$;
10   concatenate $\mathbf{c}$ and $\mathbf{i}$: $\mathbf{h} \leftarrow [\mathbf{c}; \mathbf{i}]$;
11   tile $\mathbf{h}$ T times;
12   attach a last time dimension $\mathbf{h} = [\mathbf{h}; \mathbf{t}], \mathbf{t} = \{t_1, \ldots, t_T\}, t_i = \frac{i}{T}$;
13   generate trajectory $\hat{\mathbf{x}} \leftarrow q_\phi(\mathbf{x}|\mathbf{h})$;
14   return $\hat{\mathbf{x}}$;

The hand-designed heuristics used for reporting accuracy on the the generated trajectories have concrete semantics and values which have been chosen after closely inspecting the captured dataset, the given user labels and the robot configuration during the demonstrations. :

- spatial labels—`left`, `right`, `front`, `behind`—the location of the red object in the scene is extracted using standard computer vision techniques based on color segmentation. The position of the cube is inferred as the center of mass of all red pixels detected. From the overall end-effector trajectory, derived through the robot forward kinematics, the pressing location is chosen as the end-effector position with the lowest z coordinate. That position is then projected into the image plane in order to determine where with respect to the detected object position did the robot touch the table.

- `soft` vs `hard` trajectories - the generated trajectories have normalised values in the range $[-1, 1]$. A `soft` trajectory is considered as such if specific joint efforts are below a particular threshold. More specifically:

- – `shoulder lift joint` efforts are below 0.5.
  - – `upper arm roll joint` effort are above -0.5.
- `short` vs `long` trajectories - the generated trajectories have length of $T = 240$. A `short` trajectory is considered as such if efforts in the range of [max_effort-0.2, max_effort] are maintained for more than 50 time steps. Otherwise the trajectory is deemed `long`. The heuristic operates over the following joints:
  - – shoulder lift joint efforts
  - – upper arm roll joint efforts
- `slow` vs `fast` trajectories - a `slow` trajectory is considered as such if the time it takes to reach maximal joint effort is more than 80 time steps. Otherwise the trajectory is deemed `fast`. The heuristic operates over the following joints:
  - – shoulder lift joint efforts
  - – upper arm roll joint efforts

For resolving robot joint names, please consult Figure 6 below:

- **shoulder panning joint**
- **shoulder lift joint**
- **upper arm roll joint**
- **elbow flex joint**
- **forearm roll joint**

Figure 6: Color-coded robot arm joints and their corresponding names.

C ARCHITECTURE DETAILS

The model architectures are implemented in the PyTorch framework[3] and is visually presented in Figure 7. The image encoder network takes as input a single RGB 128x128 pixel image. The trajectory encoder takes a single 14-dimensional, 240 time-step-long trajectory. Their outputs both feed into an MLP network which, after a series of nonlinear transformations, outputs parameters of a distribution over the latent space **c**. Through the reparametrisation trick Kingma & Welling (2013) we sample values for **c**. Through a residual connection, the output of the image encoder is concatenated to the sampled latent values. The resultant vector is tiled 240 times, extended with a *time* dimension, and fed into a TCN decoder network to produce reconstructions for the original 14-dimensional input trajectories.

Across all experiments, training is performed for a fixed number of 100 epochs using a batch size of 8. The dimensionality of the latent space $|\mathbf{c}| = 8$ across all experiments. The Adam optimizer (Kingma & Ba, 2014) is used through the learning process with the following values for its parameters—($learning rate = 0.001, \beta1 = 0.9, \beta2 = 0.999, eps = 1e - 08, weight decay rate = 0, amsgrad = False$).

---

[3]https://pytorch.org/docs/stable/index.html

Image Encoder
FC (4) $\mathbf{i}$
FC (256)
2D Conv (k=3, p=1, c=64)
2D Conv (k=3, p=1, c=64)
2D Conv (k=3, p=1, c=64)
2D Conv (k=3, p=1, c=32)
2D Conv (k=3, p=1, c=32)
Input Image $\mathbf{I}$ [128 x 128 x 3]

(a) Image Encoder

Trajectory Encoder
FC (32) $\boldsymbol{\tau}$
FC (256)
1D Conv (k=7, p=3); 1D Conv (k=5, p=2); 1D Conv (k=3, p=1) [c=20]
Input Trajectory $\mathbf{x}$ [240 x 14]

(b) Trajectory Encoder

MLP
FC (2x8) $\mu, \log(\sigma)$
FC (32)
FC (32)
Concatenated $[\mathbf{i}; \boldsymbol{\tau}]$[1 x 36]

(c) MLP

TCN Decoder
Temporal Block (dilation=4, k=5, c=14)
Temporal Block (dilation=2, k=5, c=20)
Temporal Block (dilation=1, k=5, c=20)
append time channel $\mathbf{t}$
tile (240, 12)
Concatenated $[\mathbf{i}; \mathbf{c}]$[1 x 12]

(d) TCN Decoder

Table 4: Network architectures used for the reported models. (a) is a 2D convolutional network, (b) is a 1D convolutional network, (c) is a fully-connected MLP network, (d) is a Temporal Convolution Network, made of stacked temporal blocks and dilated convolutions, described in Bai et al. (2018)

For all experiments, the values (unless when set to 0) for the three coefficients from Equation 9 are:

- $\alpha = 1, \beta = 0.1, \gamma = 10$

The values are chosen empirically in a manner such that all the loss terms have similar magnitude and thus none of them overwhelms the gradient updates while training the full model.

D   QUALITATIVE EVALUATION

Figures 8 to 12 present the qualitative results from perturbing in a controlled way the latent space optimised under the VAE-weak model. For figure the first row of plots represents the generated joint angle positions for each of the 7 joints, for each of the 5 drawn samples, the second row—the generated joint efforts—and the third row the corresponding end-effector positions, from the forward robot kinematics, projected in the image plane. As we can see, perturbing c_0 and c_1 corresponds to clear and consistent movement of the end effector (through the generated joint position profiles) while there is not much change in the generated effort profiles—Figures 8 and 9. Simultaneously, we observe the opposite effect in other 3 Figures. Perturbations in c_2 correspond solely changes in the output efforts in the shoulder lift and upper arm rolls joints—Figure 10 (i) and (j). Perturbations in c_3 correspond to changes in length for which the joint efforts are exerted but does not change their magnitude or where they are applied on the table—Figure 11. And finally, perturbations in c_4 correspond to changes on how quickly the maximum efforts are reached - most noticeable in the changing slope of the shoulder lift and upper arm rolls joints—Figure 12 (i) and (j). As a result, we can conclude that the latent dimensions, which we aligned with the semantically grouped weak labels, have indeed captured the notions and concepts which underlie the labels.

Figure 7: Visual schematic of the overall model. Multiple different modalities are encoded to a common latent space c which is used both for reconstructing trajectories x and predicting weak labels y, coming from the demonstrator.

Figure 8: Linearly interpolate c_0 ($\equiv$ from dabbing to the `left` to dabbing to the `right` of the visual landmark in the scene.)

Figure 9: Linearly interpolate c_1 ($\equiv$ from dab to the `front` to dab to the `back` of the visual landmark in the scene.)

Figure 10: Linearly interpolate c_2 ($\equiv$ from dab `hardly` to `softly`)

Figure 11: Linearly interpolate c_3 ($\equiv$ from dabbing for a `long` period of time to dabbing for a `short` period of time)

Figure 12: Linearly interpolate c_4 ($\equiv$ from dabbing `quickly` to dabbing `slowly`)