On the non-universality of deep learning: quantifying the cost of symmetry

Abstract

We prove a general computational lower bound for learning with neural networks trained by noisy gradient descent (GD). Our result applies whenever GD training is equivariant (true for many standard architectures), and quantifies the alignment needed between architectures and data in order for GD to learn. As applications, (i) we characterize the functions that fully-connected networks can weak-learn on the binary hypercube and unit sphere, demonstrating that depth-2 is as powerful as any other depth for this task; (ii) we extend the merged-staircase necessity result for learning with latent low-dimensional structure [ABM22] to beyond the mean-field regime. Our techniques extend to stochastic gradient descent (SGD), for which we show nontrivial hardness results for learning with fully-connected networks, based on cryptographic assumptions.

1 Introduction

Over the last decade, deep learning has made impressive advances in diverse areas including image classification [KSH12], language translation [BCB14], classical board games [SHS+18], and programming [LCC+22]. Neural networks trained with gradient-based optimizers have surpassed classical methods for these tasks, raising the question: can we hope for deep learning methods to eventually replace all other learning algorithms? In other words, is deep learning a universal learning paradigm? Recently, [AS20, AKM+21] proved that in a certain sense the answer is yes: any PAC-learning algorithm [Val84] can be efficiently implemented by a neural network trained by stochastic gradient descent; analogously, any Statistical Query algorithm [Kea98] can be efficiently implemented by a neural network trained by noisy gradient descent. In short, for any learning algorithm one can construct a deep learning architecture capable of efficiently replacing it.

However, there is a catch: the result of [AS20] relies on a carefully crafted neural network architecture, which is capable of emulating arbitrary learning algorithms using handcrafted memory and computation modules. This is far from the architectures which have been shown to be successful in practice. Neural networks in practice do incorporate domain knowledge (e.g., convolutional networks and transformers for image recognition and language processing [LB+95, LKF10], graph neural networks for analyzing graph data [GMS05, BZSL13, VCC+17], and networks specialized for particle physics [BAO+20]), but they have more "regularity" than the architectures of [AS20], in the sense that they do not rely on heterogeneous and carefully assigned initial weights. We therefore refine our question:

Is deep learning with "regular" architectures and initializations a universal learning paradigm?
If not, can we quantify its limitations when architectures and data are not well aligned?

The above question is broad, and we would like an answer that is applicable to a wide range of possible architectures. In order to formalize the problem and develop a general theory, we take an approach

similar to [Ng04, Sha18, LZA21] of understanding deep learning on a certain architecture and initialization through the *equivariance group G* (a.k.a., symmetry group) of the learning algorithm.

Definition 1.1 (G-equivariant algorithm). *A randomized algorithm $\mathcal{A}$ that takes in a data distribution $\mathcal{D} \in \mathcal{P}(\mathcal{X} \times \mathbb{R})$[1] and outputs a function $\mathcal{A}(\mathcal{D}) : \mathcal{X} \to \mathbb{R}$ is said to be G-equivariant if for each $g \in G$*

$$\mathcal{A}(\mathcal{D}) \stackrel{d}{=} \mathcal{A}(g(\mathcal{D})) \circ g. \qquad (G\text{-equivariance})$$

Here g is a group element that acts on the data space $\mathcal{X}$, and so is viewed as a function $g : \mathcal{X} \to \mathcal{X}$, and $g(\mathcal{D})$ is the distribution of $(g(\boldsymbol{x}), y)$, where $(\boldsymbol{x}, y) \sim \mathcal{D}$.

In the case that the algorithm $\mathcal{A}$ is deep learning on the distribution $\mathcal{D}$, the equivariance group depends on the optimizer, the architecture, and the network initialization [Ng04, LZA21].[2]

Examples of G-equivariant algorithms in deep learning   If a deep learning algorithm has a large equivariance group, we think of it as "regular". The equivariance group of deep learning algorithms is nontrivial in many standard cases. For example, SGD training of fully-connected networks with Gaussian initialization is orthogonally-equivariant [Ng04]; and is permutation-equivariant if we add skip connections [HZRS16]. SGD training of convolutional networks is translationally-equivariant if circular convolutions are used [SNPP19], and SGD training of i.i.d.-initialized transformers without positional embeddings is equivariant to permutations of tokens [VSP+17]. Furthermore, [LZA21, Theorem C.1] provides general conditions under which a deep learning algorithm is equivariant.

Summary of this work   We prove computational limitations on the performance of deep learning when the equivariance group of noisy gradient descent (GD) or stochastic gradient descent (SGD) is not the trivial group. Our results show that deep learning with *regular* architectures and initializations is *not universal*, implying a separation with the carefully-crafted initializations and architectures considered in [AS20] (which generically have trivial equivariance group). We first prove a master theorem that implies computational lower bounds for G-equivariant GD. This gives a refined quantification of the alignment needed between architectures and data in order for GD to learn. It also enables two novel applications: (a) characterizing which functions can be weak-learned by fully-connected networks on both the hypercube and the unit sphere; and (b) taking a step towards characterizing which functions on the hypercube with latent low-dimensional structure can be learned. As a second contribution, we demonstrate nontrivial computational hardness results for fully-connected networks with Gaussian initialization trained by SGD, implying that these cannot learn universally, and providing a separation with [AS20]. An informal overview of these contributions is given in Sections 1.2 and 1.3, but first we cover prior work in more detail in Section 1.1.

1.1   Related work

Most prior work on computational lower bounds for deep learning has focused on proving limitations of linear methods (a.k.a. kernel methods). Recently [WLLM19, AL19, KMS20, AL20, Hsu, HSSV21, ABM22] have refined arguments originating in [Bar93] to show that there are problems on which kernel methods provably fail. These results apply to training neural networks in the Neural Tangent Kernel (NTK) regime [JGH18], but do not apply to more general nonlinear training. Furthermore, for specific architectures such as fully-connected architectures [GMMM21, Mis22] and convolutional architectures [MM21], the kernel and random features models at initialization are well understood, yielding stronger lower bounds for training in the NTK regime with these architectures.

For nonlinear training, which is the setting of this paper, considerably less is known. In the context of sample complexity, [Ng04] introduced the idea of studying the equivariance group of SGD, and constructed a distribution on d dimensions with a $\Omega(d)$ versus $O(1)$ sample complexity separation for learning with an SGD-trained, Gaussian-initialized fully-connected architecture versus an arbitrary algorithm. More recently, [LZA21] built on [Ng04] to show a $O(1)$ versus $\Omega(d^2)$ sample-complexity separation between convolutional and fully-connected architectures that are initialized i.i.d. Gaussian and trained by SGD. In this paper, we also analyze the equivariance group of the training algorithm, but with the different focus of proving computational lower bounds.

---

[1]The set of probability distributions on Ω is denoted by $\mathcal{P}(\Omega)$.

[2]Note that the equivariance group of a *training algorithm* should not be confused with the equivariance group of an *architecture* in the context of geometric deep learning [BBCV21].

In the context of computational lower bounds, it is known that networks trained with noisy[3] gradient descent (GD) fall under the Statistical Query (SQ) framework [Kea98], which allows showing computational limitations for GD training based on SQ lower bounds. This has been combined in [AS20, SSS17, MS20, ACHM22] with the permutation symmetry of GD-training of i.i.d. fully-connected networks to prove lower bounds for learning high-degree parities and polynomials. In our work, we show that these arguments can be viewed in the broader context of more general group symmetries, yielding stronger lower bounds than previously known. For stochastic gradient descent (SGD) training, [ABM22] proves a computational limitation for training of two-layer mean-field networks, but their result applies only when SGD converges to the mean-field limit, and does not apply to more general architectures beyond two-layer networks. Finally, most related to our SGD hardness result is [Sha18], which shows limitations of SGD-trained fully-connected networks under a cryptographic assumption. However, the argument of [Sha18] relies on training being equivariant to linear transformations of the data, and therefore it crucially requires that data be whitened or preconditioned. In contrast, our result proving hardness of learning with SGD holds without requiring any preprocessing steps.

We also note that there is recent work showing sample complexity benefits of invariant/equivariant neural network *architectures* [MMM21, EZ21, Ele21, BVB21, Ele22]. In contrast, we study equivariant training *algorithms*. These are distinct concepts: a deep learning algorithm can be G-equivariant, while the neural network architecture is neither G-invariant nor G-equivariant. For example, a fully-connected network is not invariant to orthogonal transformations of the input. However, if we initialize it with Gaussian weights and train with SGD, then the learning algorithm is equivariant to orthogonal transformations of the input (see Proposition 2.5 below).

1.2 Contribution 1: Lower bounds for noisy gradient descent (GD)

We consider the supervised learning setup where we train a neural network $f_{\mathsf{NN}}(\cdot; \boldsymbol{\theta}) : \mathcal{X} \to \mathbb{R}$ parametrized by $\boldsymbol{\theta} \in \mathbb{R}^p$ to minimize the mean-squared error on a data distribution $\mathcal{D} \in \mathcal{P}(\mathcal{X} \times \mathbb{R})$,

$$\ell_{\mathcal{D}}(\boldsymbol{\theta}) = \mathbb{E}_{(\boldsymbol{x}, y) \sim \mathcal{D}}[(y - f_{\mathsf{NN}}(\boldsymbol{x}; \boldsymbol{\theta}))^2]. \tag{1}$$

The noisy Gradient Descent (GD) training algorithm randomly initializes $\boldsymbol{\theta}^0 \sim \mu_{\boldsymbol{\theta}}$ for some initialization distribution $\mu_{\boldsymbol{\theta}} \in \mathcal{P}(\mathbb{R}^p)$, and then iteratively updates the parameters with step size $\eta > 0$ in a direction $\boldsymbol{g}_{\mathcal{D}}(\boldsymbol{\theta}^k)$ approximating the population loss gradient, plus Gaussian noise $\boldsymbol{\xi}^k \sim \mathcal{N}(0, \tau^2 \boldsymbol{I})$,

$$\boldsymbol{\theta}^{k+1} = \boldsymbol{\theta}^k - \eta \boldsymbol{g}_{\mathcal{D}}(\boldsymbol{\theta}^k) + \boldsymbol{\xi}^k. \tag{GD}$$

Up to a constant factor, $\boldsymbol{g}_{\mathcal{D}}(\boldsymbol{\theta})$ is the population loss gradient, except we have clipped the gradients of the network with the projection operator $\Pi_{B(0,R)}$ to lie in the ball $B(0, R) = \{\boldsymbol{z} : \|\boldsymbol{z}\|_2 \leq R\} \subset \mathbb{R}^p$,[4]

$$\boldsymbol{g}_{\mathcal{D}}(\boldsymbol{\theta}) = -\mathbb{E}_{(\boldsymbol{x}, y) \sim \mathcal{D}}[(y - f_{\mathsf{NN}}(\boldsymbol{x}; \boldsymbol{\theta}))(\Pi_{B(0,R)} \nabla_{\boldsymbol{\theta}} f_{\mathsf{NN}}(\boldsymbol{x}; \boldsymbol{\theta}))].$$

Clipping the gradients is often used in practice to avoid instability from exploding gradients (see, e.g., [ZHSJ19] and references within). In our context, clipping ensures that the injected noise $\boldsymbol{\xi}^k$ is on the same scale as the gradient $\nabla_{\boldsymbol{\theta}} f_{\mathsf{NN}}$ of the network and so it controls the gradients' precision. Similarly to the works [AS20, AKM+21, ACHM22], we consider noisy gradient descent training to be efficient if the clipping radius R, step size η, and inverse noise magnitude $1/\tau$ are all polynomially-bounded, since then (GD) can be efficiently implemented using noisy minibatch SGD (assuming bounded residual error).

We prove a general result that certain data distributions cannot be efficiently learned by G-equivariant (GD) training. For our result, we introduce a quantity called the G-alignment:

Definition 1.2 (G-alignment). *Let G be a compact group, let $\mu_{\mathcal{X}} \in \mathcal{P}(\mathcal{X})$ be a distribution over data points, and let $f \in L^2(\mu_{\mathcal{X}})$ be a labeling function. The G-alignment of $(\mu_{\mathcal{X}}, f)$ is:*

$$\mathcal{C}((\mu_{\mathcal{X}}, f); G) = \sup_h \mathbb{E}_{g \sim \mu_G}[\mathbb{E}_{\boldsymbol{x} \sim \mu_{\mathcal{X}}}[f(g(\boldsymbol{x}))h(\boldsymbol{x})]^2],$$

where μ_G is the Haar measure of G and the supremum is over $h \in L^2(\mu_{\mathcal{X}})$ such that $\|h\|^2 = 1$.

---

[3]Here the noise is used to control the gradients' precision as in [AS20, AKM+21].

[4]Note that if f_{NN} is an R-Lipschitz model, then $\boldsymbol{g}_{\mathcal{D}}(\boldsymbol{\theta})$ will simply be the population gradient of the loss.

In our applications, we use tools from representation theory (see e.g., [Kna96]) to evaluate the G-alignment. Using the G-alignment, we can prove a master theorem for lower bounds, stated here informally:

Theorem 1.3 (GD lower bound, informal statement of Theorem 3.1). *Let $\mathcal{D}_f \in \mathcal{P}(\mathcal{X} \times \mathbb{R})$ be the distribution of $(\boldsymbol{x}, f(\boldsymbol{x}))$ for $\boldsymbol{x} \sim \mu_\mathcal{X}$. If $\mu_\mathcal{X}$ is G-invariant and the GD algorithm is G-equivariant on the considered architecture and initialization, and the G-alignment of $(\mu_\mathcal{X}, f)$ is sufficiently small, then the target function f cannot be efficiently learned.*

The first insight behind this theorem can be traced back at least to [Ng04]: if a G-equivariant algorithm can learn the function f by training on the distribution $\mathcal{D}_f$, then for any group element $g \in G$, it can learn $f \circ g$ by training on the distribution $\mathcal{D}_{f \circ g}$. In other words, the algorithm can learn the class of functions $\mathcal{F} = \{f \circ g : g \in g\}$, which can potentially be much larger than just the single function $\{f\}$. Therefore, if we could prove that the class of functions $\mathcal{F}$ cannot be efficiently learned by *any* network with GD, then this would show that f cannot be efficiently learned by any network where GD is G-equivariant.

The second insight of the theorem is to show that if the G-alignment of $(\mu_\mathcal{X}, f)$ is small, then $\mathcal{F}$ cannot be efficiently learned by GD on *any* network. Why does the G-alignment arise? The intuition is that the G-alignment measures the diversity of the functions in $\mathcal{F}$: if the G-alignment of f is large, then there must be some function h that has high correlation with most of the functions in $\mathcal{F}$, and therefore the functions in $\mathcal{F}$ are not very diverse. On the other hand, if the G-alignment is small, then this must mean that there is no h that correlates with most of them, and so $\mathcal{F}$ is very diverse, which can be used to show that it is hard to learn by gradient descent. This type of argument appears in [AS20, ACHM22] in the specific case of Boolean functions and for permutation equivariance; our proof both applies to a more general setting (beyond Boolean functions and permutations) and yields sharper bounds; see Appendix A.3.[5]

While the idea behind Theorem 1.3 is intuitively simple, the theorem is very broadly applicable, to arbitrary compact groups and beyond functions defined on the Boolean hypercube. We demonstrate its power and ease-of-use by deriving two novel applications that are interesting in their own right, and that showcase the limitations of fully-connected networks with standard initializations. We expect that Theorem 1.3 will find further applications in future work.

Application: Characterization of weak-learnability by fully-connected networks   In our first application, we consider weak-learnability: i.e., when can a function be learned non-negligibly better than just outputting the estimate $f_{\mathsf{NN}} \equiv 0$? Using Theorem 1.3, we characterize which functions over the binary hypercube $f : \{+1, -1\}^d \to \mathbb{R}$ and over the sphere $f : \mathbb{S}^{d-1} \to \mathbb{R}$ are efficiently weak-learnable by GD-trained fully-connected networks with i.i.d. symmetric and i.i.d. Gaussian initialization, respectively. The takeaway is that a function $f : \{+1, -1\}^d \to \mathbb{R}$ is weak-learnable if and only if it has a nonnegligible Fourier coefficient of order $O(1)$ or $d - O(1)$. Similarly, a function $f : \mathbb{S}^{d-1} \to \mathbb{R}$ is weak-learnable if and only if it has nonnegligible projection onto the degree-$O(1)$ spherical harmonics. Such functions can be weak-learned by 2-layer fully-connected networks, which shows that adding more depth does not help for weak learning in these settings. This application is presented in Section 3.1.

Application: Evidence for the staircase property   In our second application, we consider learning a target function $f : \{+1, -1\}^d \to \mathbb{R}$ that only depends on the first P coordinates, $f(\boldsymbol{x}) = h(x_1, \ldots, x_P)$. Our regime of interest here is when the function $h : \{+1, -1\}^P \to \mathbb{R}$ remains fixed and the dimension d grows, since this models the situation where a latent low-dimensional space determines the labels in a high-dimensional dataset. Recently, [ABM22] studied SGD-training of mean-field two-layer networks, and gave a near-characterization of which functions can be learned to arbitrary accuracy ϵ in $O_{h,\epsilon}(d)$ samples, in terms of the *merged-staircase property* (MSP). Using Theorem 1.3, we prove that the MSP is necessary for GD-learnability whenever training is permutation-equivariant – and thus applies well beyond the 2-layer mean-field regime – and we also generalize it beyond leaps of size 1. This application is presented in Section 3.2.

---

[5]Our bound can also be interpreted in terms of the Statistical Query framework, as we discuss in Appendix A.4.

1.3 Contribution 2: Hardness for stochastic gradient descent (SGD)

The second part of this paper concerns Stochastic Gradient Descent (SGD) training, which randomly initializes the weights $\boldsymbol{\theta}^0 \sim \mu_{\boldsymbol{\theta}}$, and then iteratively trains the parameters with the following update rule to try to minimize the loss (1):

$$\boldsymbol{\theta}^{k+1} = \boldsymbol{\theta}^k - \eta \nabla_{\boldsymbol{\theta}} (y - f_{\mathsf{NN}}(\boldsymbol{x}_{k+1}; \boldsymbol{\theta}^k))^2, \qquad \text{(SGD)}$$

where $(y_{k+1}, \boldsymbol{x}_{k+1}) \sim \mathcal{D}$ is a fresh sample on each iteration, and $\eta > 0$ is the learning rate.[6]

Proving computational lower bounds for SGD is a notoriously difficult problem [AKM+21], exacerbated by the fact that for general architectures SGD can be used to simulate any polynomial-time learning algorithm [AS20]. However, we demonstrate that one can prove hardness results for SGD training based off of cryptographic assumptions when the training algorithm has a large equivariance group. We demonstrate the *non-universality* of SGD on a standard fully-connected architecture.

Theorem 1.4 (Hardness for SGD, informal statement of Theorem 4.4). *Under the assumption that the Learning Parities with Noise (LPN) problem[7] is hard, fully-connected neural networks with Gaussian initialization trained by SGD cannot learn* $f_{\mathrm{mod}8} : \{+1, -1\}^d \to \{0, \dots, 7\}$,

$$f_{\mathrm{mod}8}(\boldsymbol{x}) \equiv \sum_{i=1}^d x_i \pmod 8,$$

in polynomial time from noisy samples $(\boldsymbol{x}, f_{\mathrm{mod}8}(\boldsymbol{x}) + \xi)$ *where* $\boldsymbol{x} \sim \{+1, -1\}^d$ *and* $\xi \sim \mathcal{N}(0, 1)$.

This result showcases a nontrivial limitation of SGD training based on an average-case reduction from a cryptographic problem. The closest prior result is in [Sha18], which proved hardness of learning with SGD, but required preprocessing the data with a whitening transformation.

The fully-connected architecture and Gaussian initialization are critical: an architecture that outputted $f_{\mathrm{mod}8}(\boldsymbol{x})$ at initialization would trivially achieve zero loss. However, SGD on fully-connected networks with Gaussian-initialized architectures is *sign-flip* equivariant, and we can show that this additional symmetry property makes $f_{\mathrm{mod}8}$ hard to learn. The proof idea is that if a sign-flip equivariant algorithm can learn the function $f_{\mathrm{mod}8}(\boldsymbol{x})$ from noisy samples, then it can learn the function $f_{\mathrm{mod}8}(\boldsymbol{x} \odot \boldsymbol{s})$ from noisy samples, where $\boldsymbol{s} \in \{+1, -1\}^d$ is an a priori unknown sign-flip vector, and $\odot$ denotes elementwise product. However, this latter problem is hard under standard cryptographic assumptions. The theorem follows by contradiction. More details in Section 4.

2 Preliminaries

Notation Let $\mathcal{H}_d = \{+1, -1\}^d$ be the binary hypercube, and $\mathbb{S}^{d-1} = \{\boldsymbol{x} \in \mathbb{R}^d : \|\boldsymbol{x}\|_2 = 1\}$ the unit sphere. The law of a random variable X is $\mathcal{L}(X)$. If S is a finite set, then $X \sim S$ stands for $X \sim \mathrm{Unif}[S]$. Also let $\boldsymbol{x} \sim \mathbb{S}^{d-1}$ denote $\boldsymbol{x}$ drawn from the uniform Haar measure on $\mathbb{S}^{d-1}$. For a set Ω, let $\mathcal{P}(\Omega)$ be the set of distributions on Ω. Let $\odot$ be the elementwise product. For any $\mu_{\mathcal{X}} \in \mathcal{P}(\mathcal{X})$, and group G acting on $\mathcal{X}$, we say $\mu_{\mathcal{X}}$ is G-invariant if $g(\boldsymbol{x}) \stackrel{d}{=} \boldsymbol{x}$ for $\boldsymbol{x} \sim \mu_{\mathcal{X}}$ and any $g \in G$.

2.1 Equivariance of GD and SGD

We define GD and SGD equivariance separately.

Definition 2.1. *Let* $\mathcal{A}^{\mathrm{GD}}$ *be the algorithm that takes in data distribution* $\mathcal{D} \in \mathcal{P}(\mathcal{X} \times \mathbb{R})$, *runs* (GD) *on initialization* $\boldsymbol{\theta}^0 \sim \mu_{\boldsymbol{\theta}}$ *for k steps, and outputs the function* $\mathcal{A}^{\mathrm{GD}}(\mathcal{D}) = f_{\mathsf{NN}}(\cdot; \boldsymbol{\theta}^k)$

We say "($f_{\mathsf{NN}}, \mu_{\boldsymbol{\theta}}$)-GD is G-equivariant" if $\mathcal{A}^{\mathrm{GD}}$ *is G-equivariant in the sense of Definition 1.1.*

Definition 2.2. *Let* $\mathcal{A}^{\mathrm{SGD}}$ *be the algorithm that takes in samples* $(\boldsymbol{x}_i, y_i)_{i \in [n]}$, *runs* (SGD) *on initialization* $\boldsymbol{\theta}^0 \sim \mu_{\boldsymbol{\theta}}$ *for n steps, and outputs* $\mathcal{A}^{\mathrm{SGD}}((\boldsymbol{x}_i, y_i)_{i \in [n]}) = f_{\mathsf{NN}}(\cdot; \boldsymbol{\theta}^k)$.

We say "($f_{\mathsf{NN}}, \mu_{\boldsymbol{\theta}}$)-SGD is G-equivariant" if $\mathcal{A}^{\mathrm{SGD}}((\boldsymbol{x}_i, y_i)_{i \in [n]}) \stackrel{d}{=} \mathcal{A}^{\mathrm{SGD}}((g(\boldsymbol{x}_i), y_i)_{i \in [n]}) \circ g$ *for any $g \in G$, and any samples* $(\boldsymbol{x}_i, y_i)_{i \in [n]}$.

---

[6]For brevity, we focus on one-pass SGD with a single fresh sample per iteration. Our results extend to empirical risk minimization (ERM) setting and to mini-batch SGD, see Remark E.1.

[7]See Section 4 and Appendix D.3 for definitions and discussion on LPN.

2.2 Regularity conditions on networks imply equivariances of GD and SGD

We take the data space $\mathcal{X} \subseteq \mathbb{R}^d$, and consider the following groups that act on $\mathbb{R}^d$.

Definition 2.3. *Define the following groups and actions:*

- *Let $G_{perm} = S_d$ denote the group of permutations on $[d]$. An element $\sigma \in G_{perm}$ acts on $\boldsymbol{x} \in \mathbb{R}^d$ in the standard way: $\sigma(\boldsymbol{x}) = (x_{\sigma(1)}, \ldots, x_{\sigma(d)})$.*

- *Let $G_{\mathrm{sign,perm}}$ denote the group of signed permutations, an element $g = (\boldsymbol{s}, \sigma) \in G_{\mathrm{sign,perm}}$ is given by a sign-flip vector $\boldsymbol{s} \in \mathcal{H}_d$ and a permutation $\sigma \in G_{perm}$. It acts on $\boldsymbol{x} \in \mathbb{R}^d$ by $g(\boldsymbol{x}) = \boldsymbol{s} \odot \sigma(\boldsymbol{x}) = (s_1 x_{\sigma(1)}, \ldots, s_d x_{\sigma(d)})$.[8]*

- *Let $G_{rot} = SO(d) \subseteq GL(d, \mathbb{R})$ denote the rotation group. An element $g \in G_{rot}$ is a rotation matrix that acts on $\boldsymbol{x} \in \mathbb{R}^d$ by matrix multiplication.*

Under mild conditions on the neural network architecture and initialization, GD and SGD training are known to be G_{perm}-, $G_{\mathrm{sign,perm}}$-, or G_{rot}-equivariant [Ng04, LZA21].

Assumption 2.4 (Fully-connected i.i.d. first layer and no skip connections from the input). *We can decompose the parameters as $\boldsymbol{\theta} = (\boldsymbol{W}, \boldsymbol{\psi})$, where $\boldsymbol{W} \in \mathbb{R}^{m \times d}$ is the matrix of the first-layer weights, and there is a function $g_{\mathsf{NN}}(\cdot; \boldsymbol{\psi}) : \mathbb{R}^m \to \mathbb{R}$ such that $f_{\mathsf{NN}}(\boldsymbol{x}; \boldsymbol{\theta}) = g_{\mathsf{NN}}(\boldsymbol{W} \boldsymbol{x}; \boldsymbol{\psi})$. Furthermore, the initialization distribution is $\mu_{\boldsymbol{\theta}} = \mu_{\boldsymbol{W}} \times \mu_{\boldsymbol{\psi}}$, where $\mu_{\boldsymbol{W}} = \mu_w^{\otimes(m \times d)}$ for $\mu_w \in \mathcal{P}(\mathbb{R})$.*

Notice that Assumption 2.4 is satisfied by fully-connected networks with i.i.d. initialization. Under assumptions on μ_w, we obtain equivariances of GD and SGD (see Appendix E for proofs.)

Proposition 2.5 ([Ng04, LZA21]). *Under Assumption 2.4, GD and SGD are G_{perm}-equivariant. If μ_w is sign-flip symmetric, then GD and SGD are $G_{\mathrm{sign,perm}}$-equivariant. If $\mu_w = \mathcal{N}(0, \sigma^2)$ for some σ, then GD and SGD are G_{rot}-equivariant.*

3 Lower bounds for learning with GD

In this section, let $\mathcal{D}(f, \mu_{\mathcal{X}}) \in \mathcal{P}(\mathcal{X} \times \mathbb{R})$ denote the distribution of $(\boldsymbol{x}, f(\boldsymbol{x}))$ where $\boldsymbol{x} \sim \mu_{\mathcal{X}}$.

We give a master theorem for computational lower bounds for learning with G-equivariant GD.

Theorem 3.1 (GD lower bound using G-alignment). *Let G be a compact group, and let $f_{\mathsf{NN}}(\cdot; \boldsymbol{\theta}) : \mathcal{X} \to \mathbb{R}$ be an architecture and $\mu_{\boldsymbol{\theta}} \in \mathcal{P}(\mathbb{R}^p)$ be an initialization such that GD is G-equivariant.*

Fix any G-invariant distribution $\mu_{\mathcal{X}} \in \mathcal{P}(\mathcal{X})$, any label function $f_* \in L^2(\mu_{\mathcal{X}})$, and any baseline function $\alpha \in L^2(\mu_{\mathcal{X}})$ satisfying $\alpha \circ g = \alpha$ for all $g \in G$. Let $\boldsymbol{\theta}^k$ be the random weights after k time-steps of GD training with noise parameter $\tau > 0$, step size $\eta > 0$, and clipping radius $R > 0$ on the distribution $\mathcal{D} = \mathcal{D}(f_*, \mu_{\mathcal{X}})$. Then, for any $\epsilon > 0$,

$$\mathbb{P}_{\boldsymbol{\theta}^k}[\ell_{\mathcal{D}}(\boldsymbol{\theta}^k) \leq \|f_* - \alpha\|_{L^2(\mu_{\mathcal{X}})}^2 - \epsilon] \leq \frac{\eta R \sqrt{k\mathcal{C}}}{2\tau} + \frac{\mathcal{C}}{\epsilon},$$

where $\mathcal{C} = \mathcal{C}((f_* - \alpha, \mu_{\mathcal{X}}); G)$ is the G-alignment of Definition 1.2.

As discussed in Section 1.2, the theorem states that if the G-alignment is very small, then GD training cannot efficiently improve on the trivial loss from outputting α: either the number of steps k, the gradient precision R/τ, or the step size η have to be very large in order to learn. Appendix A shows a generalization of the theorem for learning a class of functions $\mathcal{F} = \{f_1, \ldots, f_m\}$ instead of just a single function f_*. This result goes beyond the lower bound of [AS20] even when G is the trivial group with one element: the main improvement is that Theorem 3.1 proves hardness for learning real-valued functions beyond just Boolean-valued functions. We demonstrate the usefulness of the theorem through two novel applications in Sections 3.1 and 3.2.

3.1 Application: Characterizing weak-learnability by fully-connected networks

In our first application of Theorem 3.1, we consider fully-connected architectures with i.i.d. initialization, and show how to use their training equivariances to characterize what functions they can

---

[8]The group product is $g_1 g_2 = (\boldsymbol{s}_1, \sigma_1)(\boldsymbol{s}_2, \sigma_2) = (\boldsymbol{s}_1 \odot \sigma_1(\boldsymbol{s}_2), \sigma_1 \circ \sigma_2)$.

weak-learn: i.e., for what target functions f_* they can efficiently achieve a non-negligible correlation after training.

Definition 3.2 (Weak learnability). *Let $\{\mu_d\}_{d\in\mathbb{N}}$ be a family of distributions $\mu_d \in \mathcal{P}(\mathcal{X}_d)$, and let $\{f_d\}_{d\in\mathbb{N}}$ be a family of functions $f_d \in L^2(\mu_d)$. Finally, let $\{\tilde{f}_d\}_{d\in\mathbb{N}}$ be a family of estimators, where $\tilde{f}_d$ is a random function in $L^2(\mu_d)$. We say that $\{f_d, \mu_d\}_{d\in\mathbb{N}}$ is "weak-learned" by the family of estimators $\{\tilde{f}_d\}_{d\in\mathbb{N}}$ if there are constants $d_0, C > 0$ such that for all $d > d_0$,*

$$\mathbb{P}_{\tilde{f}_d}[\|f_d - \tilde{f}_d\|^2_{L^2(\mu_d)} \leq \|f_d\|^2_{L^2(\mu_d)} - d^{-C}] \geq 9/10. \tag{2}$$

Here $9/10$ is an arbitrary, large enough constant. In words, weak-learning measures whether the family of estimators $\{\tilde{f}_d\}$ has a non-negligible edge over simply estimating with the identically zero functions $\tilde{f}_d \equiv 0$. We study weak-learnability by GD-trained fully-connected networks.

Definition 3.3. *We say that $\{f_d, \mu_d\}_{d\in\mathbb{N}}$ is efficiently weak-learnable by GD-trained fully-connected networks if there are fully-connected networks and initializations $\{f_{\mathsf{NN},d}, \mu_{\boldsymbol{\theta},d}\}$, and hyperparameters $\{\eta_d, k_d, R_d, \tau_d\}$ such that for some constant $c > 0$,*

- *Hyperparameters are polynomial size: $0 \leq \eta_d, k_d, R_d, 1/\tau_d \leq O(d^c)$;*

- *$\{\tilde{f}_d\}$ weak-learns $\{f_d, \mu_d\}$ in the sense of Definition 3.2, where $\tilde{f}_d = f_{\mathsf{NN}}(\cdot; \boldsymbol{\theta}_d)$ for weights $\boldsymbol{\theta}_d$ that are GD-trained on $\mathcal{D}(f_d, \mu_d)$ for k_d steps with step size η_d, clipping radius R_d, and noise τ_d, starting from initialization $\mu_{\boldsymbol{\theta},d}$.*

If $\mu_{\boldsymbol{\theta},d}$ is i.i.d copies of a symmetric distribution, we say that the fully-connected networks are symmetrically-initialized, and Gaussian-initialized if $\mu_{\boldsymbol{\theta},d}$ is i.i.d. copies of a Gaussian distribution.

3.1.1 Functions on hypercube, fully-connected networks with i.i.d. symmetric initialization

Let us first consider functions on the Boolean hypercube $f : \mathcal{H}_d \to \mathbb{R}$. These can be uniquely written as a multilinear polynomial $f(\boldsymbol{x}) = \sum_{S\subseteq[d]} \hat{f}(S) \prod_{i\in S} x_i$, where $\hat{f}(S)$ are the Fourier coefficients of f [O'D14]. We characterize weak learnability of functions on the hypercube in terms of their Fourier coefficients. The proof is deferred to Appendix B.1.

Theorem 3.4. *Let $\{f_d\}_{d\in\mathbb{N}}$ be a family of functions $f_d : \mathcal{H}_d \to \mathbb{R}$ with $\|f_d\|_{L^2(\mathcal{H}_d)} \leq 1$. Then $\{f_d, \mathcal{H}_d\}$ is efficiently weak-learnable by GD-trained symmetrically-initialized fully-connected networks if and only if there is a constant $C > 0$ such that for each $d \in \mathbb{N}$ there is $S_d \subseteq [d]$ with $|S_d| \leq C$ or $|S_d| \geq d - C$, and $|\hat{f}_d(S_d)| \geq \Omega(d^{-C})$.*

The algorithmic result can be achieved by two-layer fully-connected networks, and relies on random features analysis where each network weight is initialized to 0 with probability $1 - p$, and $+1$ or -1 with equal probability $p/2$.[9] Therefore, for weak learning, two-layer networks are as good as networks of any depth. For the converse impossibility result, we apply Theorem 3.1, recalling that GD is $G_{\mathrm{sign,perm}}$-equivariant by Proposition 2.5, and noting that $G_{\mathrm{sign,perm}}$-alignment is:

Lemma 3.5. *Let $f : \mathcal{H}_d \to \mathbb{R}$. Then $\mathcal{C}((f, \mathcal{H}_d); G_{\mathrm{sign,perm}}) = \max_{k\in[d]} \binom{d}{k}^{-1} \sum_{\substack{S\subseteq[d] \\ |S|=k}} \hat{f}(S)^2$.*

This lemma can be proved via direct manipulation or using the representation theory of $G_{\mathrm{sign,perm}}$. It implies that if the Fourier coefficients of f are negligible for all S s.t. $\min(|S|, d - |S|) \leq O(1)$, then the $G_{\mathrm{sign,perm}}$-alignment of f is negligible and f cannot be learned efficiently. In Appendix B.1.2 we give a concrete example of a function that is not weak-learnable, that was not previously known.

3.1.2 Functions on sphere, fully-connected networks with i.i.d. Gaussian initialization

We now study learning a target function on the unit sphere, $f \in L^2(\mathbb{S}^{d-1})$, where we take the standard Lebesgue measure on $\mathbb{S}^{d-1}$. A key fact in harmonic analysis is that $L^2(\mathbb{S}^{d-1})$ can be written as the direct sum of subspaces spanned by spherical harmonics of each degree: $L^2(\mathbb{S}^{d-1}) = \oplus_{l=0}^{\infty} \mathcal{V}_{d,l}$,

---

[9]Surprisingly, this means that the full parity function $f_*(\boldsymbol{x}) = \prod_{i=1}^d x_i$ can be efficiently learned with such initializations. See Appendix B.

where $\mathcal{V}_{d,l} \subseteq L^2(\mathbb{S}^{d-1})$ is the space of degree-l spherical harmonics (see, e.g., [Hoc12]). Let $P_{\mathcal{V}_{d,l}} : L^2(\mathbb{S}^{d-1}) \to \mathcal{V}_{d,l}$ be the projection operator to the space of degree-l spherical harmonics, which has dimension $\dim(\mathcal{V}_{d,l}) = \frac{2l+d-2}{l}\binom{l+d-3}{l-1}$. In Appendix B.2, we prove the following characterization of when functions on the sphere are weak-learnable.

Theorem 3.6. *Let $\{f_d\}_{d \in \mathbb{N}}$ be a family of functions $f_d : \mathbb{S}^{d-1} \to \mathbb{R}$ with $\|f_d\|_{L^2(\mathbb{S}^{d-1})} \leq 1$. Then $\{f_d, \mathbb{S}^{d-1}\}$ is efficiently weak-learnable by GD-trained Gaussian-initialized fully-connected networks if and only if there is a constant $C > 0$ such that $\sum_{l=0}^{C} \|P_{\mathcal{V}_{d,l}} f_d\|^2 \geq d^{-C}$.*

The algorithmic result can be achieved by two-layer fully-connected networks, and is a consequence of the analysis of the random feature kernel in [GMMM21], which shows that the projection of f_d onto the low-degree spherical harmonics can be efficiently learned. For the impossibility result, we apply Theorem 3.1, noting that GD is G_{rot}-equivariant by Proposition 2.5, and the G_{rot}-alignment is:

Lemma 3.7. *Let $f \in L^2(\mathbb{S}^{d-1})$. Then $\mathcal{C}((f, \mathbb{S}^{d-1}); G_{rot}) = \max_{l \in \mathbb{Z}_{\geq 0}} \|P_{\mathcal{V}_{d,l}} f\|^2 / \dim(\mathcal{V}_{d,l})$.*

The G_{rot}-alignment is computed using the representation theory of G_{rot}. In particular, we use the Schur orthogonality theorem, and the fact that for any degree $l \in \mathbb{Z}_{\geq 0}$ the representation $\Phi_l(g) : \mathcal{V}_{d,l} \to \mathcal{V}_{d,l}$ of G_{rot} given by $\Phi_l(g)f = f \circ g^{-1}$ is irreducible (see, e.g., [Kna96]).

3.2 Application: Extending the merged-staircase property necessity result

In our second application, we study the setting of learning a sparse function on the binary hypercube (a.k.a. a junta) that depends on only $P \leq d$ coordinates of the input $\boldsymbol{x}$, i.e.,

$$f_*(\boldsymbol{x}) = h_*(x_1, \ldots, x_P),$$

where $h_* : \mathcal{H}_P \to \mathbb{R}$. The regime of interest to us is when h_* is fixed and $d \to \infty$, representing a hidden signal in a high-dimensional dataset. This setting was studied by [ABM22], who identified the "merged-staircase property", which we generalize below.

Definition 3.8 (*l*-MSP). *For $l \in \mathbb{Z}_+$ and $h_* : \mathcal{H}_P \to \mathbb{R}$, we say that h_* satisfies the merged staircase property with leap l (i.e., l-MSP) if its set of nonzero Fourier coefficients $\mathcal{S} = \{S : \hat{h}_*(S) \neq \emptyset\}$ can be ordered as $\mathcal{S} = \{S_1, \ldots, S_m\}$ such that for all $i \in [m]$, $|S_i \setminus \cup_{j < i} S_j| \leq l$.*

For example, $h_*(\boldsymbol{x}) = x_1 + x_1 x_2 + x_1 x_2 x_3$ satisfies 1-MSP; $h_*(\boldsymbol{x}) = x_1 x_2 + x_1 x_2 x_3$ satisfies 2-MSP, but not 1-MSP because of the leap required to learn $x_1 x_2$; similarly $h_*(\boldsymbol{x}) = x_1 x_2 x_3 + x_4$ satisfies 3-MSP but not 2-MSP. If h_* satisfies l-MSP for some small l, then the function f_* can be learned greedily in an efficient manner, by iteratively discovering the coordinates on which it depends. In [ABM22] it was proved that the 1-MSP property nearly characterized which sparse functions could be ϵ-learned in $O_{\epsilon, h_*}(d)$ samples by one-pass SGD training in the mean-field regime.

We prove the MSP necessity result for GD training. On the one hand, our necessity result is for a different training algorithm, GD, which injects noise during training. On the other, our result is much more general since it applies whenever GD is permutation-equivariant, which includes training of fully-connected networks and ResNets of any depth (whereas the necessity result of [ABM22] applies only to two-layer architectures in the mean-field regime). We also generalize the result to any leap l.

Theorem 3.9 (*l*-MSP necessity). *Let $f_{\mathsf{NN}}(\cdot; \boldsymbol{\theta}) : \mathcal{H}_d \to \mathbb{R}$ be an architecture and $\mu_{\boldsymbol{\theta}} \in \mathcal{P}(\mathbb{R}^p)$ be an initialization such that GD is G_{perm}-equivariant. Let $\boldsymbol{\theta}^k$ be the random weights after k steps of GD training with noise parameter $\tau > 0$, step size η, and clipping radius R on the distribution $\mathcal{D} = \mathcal{D}(f_*, \mathcal{H}_d)$. Suppose that $f_*(\boldsymbol{x}) = h_*(\boldsymbol{z})$ where $h_* : \mathcal{H}_P \to \mathbb{R}$ does not satisfy l-MSP for some $l \in \mathbb{Z}_+$. Then there are constants $C, \epsilon_0 > 0$ depending on h_* such that $\mathbb{P}_{\boldsymbol{\theta}^k}[\ell_{\mathcal{D}}(\boldsymbol{\theta}^k) \leq \epsilon_0] \leq \frac{C\eta R}{2\tau}\sqrt{\frac{k}{d^{l+1}}} + \frac{C}{d^{l+1}}$.*

The interpretation is that if h_* does not satisfy l-MSP, then to learn f_* to better than ϵ_0 error with constant probability, we need at least $\Omega_{h_*, \epsilon}(d^{l+1})$ steps of (GD) on a network with step size $\eta = O_{h_*, \epsilon}(1)$, clipping radius $R = O_{h_*, \epsilon}(1)$, and noise level $\tau = \Omega_{h_*, \epsilon}(1)$. The proof is deferred to Appendix C. It proceeds by first isolating the "easily-reachable" coordinates $T \subseteq [P]$, and subtracting their contribution from f_*. We then bound G-alignment of the resulting function, where G is the permutation group on $[d] \setminus T$.

4 Hardness for learning with SGD

In this section, for $\gamma > 0$, we let $\mathcal{D}(f, \mu_{\mathcal{X}}, \gamma) \in \mathcal{P}(\mathcal{X} \times \mathbb{R})$ denote the distribution of $(\boldsymbol{x}, f(\boldsymbol{x}) + \xi)$ where $\boldsymbol{x} \sim \mu_{\mathcal{X}}$ and $\xi \sim \mathcal{N}(0, \gamma^2)$ is independent noise.

We show that the equivariance of SGD on certain architectures implies that the function $f_{\mathrm{mod8}} : \mathcal{H}_d \to \{0, \ldots, 7\}$ given by

$$f_{\mathrm{mod8}}(\boldsymbol{x}) \equiv \sum_i x_i \pmod{8} \tag{3}$$

is hard for SGD-trained, i.i.d. symmetrically-initialized fully-connected networks. Our hardness result relies on a cryptographic assumption to prove superpolynomial lower bounds for SGD learning. For any $S \subseteq [d]$, let $\chi_S : \mathcal{H}_d \to \{+1, -1\}$ be the parity function $\chi_S(\boldsymbol{x}) = \prod_{i \in S} x_i$.

Definition 4.1. *The learning parities with Gaussian noise, (d, n, γ)-LPGN, problem is parametrized by $d, n \in \mathbb{Z}_{>0}$ and $\gamma \in \mathbb{R}_{>0}$. An instance $(S, \boldsymbol{q}, (\boldsymbol{x}_i, y_i)_{i \in [n]})$ consists of (i) an unknown subset $S \subseteq [d]$ of size $|S| = \lfloor d/2 \rfloor$, and (ii) a known query vector $\boldsymbol{q} \sim \mathcal{H}_d$, and i.i.d. samples $(\boldsymbol{x}_i, y_i)_{i \in [n]} \sim \mathcal{D}(\chi_S, \mathcal{H}_d, \gamma)$. The task is to return $\chi_S(\boldsymbol{q}) \in \{+1, -1\}$.*[10]

Our cryptographic assumption is that $\mathrm{poly}(d)$-size circuits cannot succeed on LPGN.

Definition 4.2. *Let $\gamma > 0$. We say γ-LPGN is $\mathrm{poly}(d)$-time solvable if there is a sequence of sample sizes $\{n_d\}_{d \in \mathbb{N}}$ and circuits $\{\mathcal{A}_d\}_{d \in \mathbb{N}}$ such that $n_d, \mathrm{size}(\mathcal{A}_d) \leq \mathrm{poly}(d)$, and $\mathcal{A}_d$ solves (d, n_d, γ)-LPGN with success probability at least $9/10$, when inputs are rounded to $\mathrm{poly}(d)$ bits.*

Assumption 4.3. *Fix γ. The γ-LPGN-hardness assumption is: γ-LPGN is not $\mathrm{poly}(d)$-time solvable.*

The LPGN problem is the simply standard Learning Parities with Noise problem (LPN) [BKW03], except with Gaussian noise instead of binary classification noise, and we are also promised that $|S| = \lfloor d/2 \rfloor$. In Appendix D.3, we derive Assumption 4.3 from the standard hardness of LPN. We now state our SGD hardness result.

Theorem 4.4. *Let $\{f_{\mathsf{NN},d}, \mu_{\boldsymbol{\theta},d}\}_{d \in \mathbb{N}}$ be a family of networks and initializations satisfying Assumption 2.4 (fully-connected) with i.i.d. symmetric initialization. Let $\gamma > 0$, and let $\{n_d\}$ be sample sizes such that $(f_{\mathsf{NN},d}, \mu_{\boldsymbol{\theta},d})$-SGD training on n_d samples from $\mathcal{D}(f_{\mathrm{mod8}}, \mathcal{H}_d, \gamma)$ rounded to $\mathrm{poly}(d)$ bits yields parameters $\boldsymbol{\theta}_d$ with*

$$\mathbb{E}_{\boldsymbol{\theta}_d}[\| f_{\mathrm{mod8}} - f_{\mathsf{NN}}(\cdot; \boldsymbol{\theta}_d) \|^2] \leq 0.0001.$$

Then, under $(\gamma/2)$-LPGN hardness, $(f_{\mathsf{NN},d}, \mu_{\boldsymbol{\theta},d})$-SGD on n_d samples cannot run in $\mathrm{poly}(d)$ time.

In order to prove Theorem 4.4, we use the sign-flip equivariance of gradient descent guaranteed by the symmetry in the initialization. A sign-flip equivariant network that learns $f_{\mathrm{mod8}}(\boldsymbol{x})$ from γ-noisy samples, is capable of solving the harder problem of learning $f_{\mathrm{mod8}}(\boldsymbol{x} \odot \boldsymbol{s})$ from γ-noisy samples, where $\boldsymbol{s} \in \mathcal{H}_d$ is an unknown sign-flip vector. However, through an average-case reduction we show that this problem is $(\gamma/2)$-LPGN-hard. Therefore the theorem follows by contradiction.

5 Discussion

The general GD lower bound in Theorem 3.1 and the approach for basing hardness of SGD training on cryptographic assumptions in Theorem 4.4 could be further developed to other settings.

There are limitations of the results to address in future work. First, the GD lower bound requires adding noise to the gradients, which can hinder training. Second, real-world data distributions are typically not invariant to a group of transformations, so the results obtained by this work may not apply. It is open to develop results for distributions that are approximately invariant.

Finally, it is open whether computational lower bounds for SGD/GD training can be shown beyond those implied by equivariance. For example, consider the function $f : \mathcal{H}_d \to \{+1, -1\}$ that computes the "full parity", i.e., the parity of all of the inputs $f(\boldsymbol{x}) = \prod_{i=1}^d x_i$. Past work has empirically shown that SGD on fully-connected networks with Gaussian initialization [SSS17, AS20, NY21] fails to learn this function. Proving this would represent a significant advance, since there is no obvious equivariance that implies that the full parity is hard to learn — in fact we have shown weak-learnability with symmetric $\mathrm{Rad}(1/2)$ initialization, in which case training is $G_{\mathrm{sign,perm}}$-equivariant.

---

[10]More formally, one would express this as a probabilistic promise problem [Ale03].

References

[ABM22]   E. Abbe, E. Boix-Adsera, and T. Misiakiewicz. The merged-staircase property: a necessary and nearly sufficient condition for sgd learning of sparse functions on two-layer neural networks. *arXiv preprint arXiv:2202.08658*, 2022.

[ACHM22] E. Abbe, E. Cornacchia, J. Hązła, and C. Marquis. An initial alignment between neural network and target is needed for gradient descent to learn. *arXiv preprint arXiv:2202.12846*, 2022.

[AKM+21] E. Abbe, P. Kamath, E. Malach, C. Sandon, and N. Srebro. On the power of differentiable learning versus PAC and SQ learning. In *Advances in Neural Information Processing Systems*, volume 34, 2021.

[AL19]   Z. Allen-Zhu and Y. Li. What can resnet learn efficiently, going beyond kernels? *Advances in Neural Information Processing Systems*, 32, 2019.

[AL20]   Z. Allen-Zhu and Y. Li. Backward feature correction: How deep learning performs deep learning. *arXiv preprint arXiv:2001.04413*, 2020.

[Ale03]   M. Alekhnovich. More on average case vs approximation complexity. In *44th Annual IEEE Symposium on Foundations of Computer Science, 2003. Proceedings.*, pages 298–307. IEEE, 2003.

[AS20]   E. Abbe and C. Sandon. Poly-time universality and limitations of deep learning. *arXiv preprint arXiv:2001.02992*, 2020.

[BAO+20] A. Bogatskiy, B. Anderson, J. Offermann, M. Roussi, D. Miller, and R. Kondor. Lorentz group equivariant neural network for particle physics. In *International Conference on Machine Learning*, pages 992–1002. PMLR, 2020.

[Bar93]   A. R. Barron. Universal approximation bounds for superpositions of a sigmoidal function. *IEEE Transactions on Information theory*, 39(3):930–945, 1993.

[BBCV21] M. M. Bronstein, J. Bruna, T. Cohen, and P. Veličković. Geometric deep learning: Grids, groups, graphs, geodesics, and gauges. *arXiv preprint arXiv:2104.13478*, 2021.

[BBH18]   M. Brennan, G. Bresler, and W. Huleihel. Reducibility and computational lower bounds for problems with planted sparse structure. In *Conference On Learning Theory*, pages 48–166. PMLR, 2018.

[BCB14]   D. Bahdanau, K. Cho, and Y. Bengio. Neural machine translation by jointly learning to align and translate. *arXiv preprint arXiv:1409.0473*, 2014.

[BF02]   N. H. Bshouty and V. Feldman. On using extended statistical queries to avoid membership queries. *Journal of Machine Learning Research*, 2(Feb):359–395, 2002.

[BIK90]   S. Ben-David, A. Itai, and E. Kushilevitz. Learning by distances. In *COLT*, pages 232–245, 1990.

[BKW03]   A. Blum, A. Kalai, and H. Wasserman. Noise-tolerant learning, the parity problem, and the statistical query model. *Journal of the ACM (JACM)*, 50(4):506–519, 2003.

[Boi20]   E. Boix-Adsera. Average-case statistical query algorithms, 2020. Report for MDS Lab Internship.

[BVB21]   A. Bietti, L. Venturi, and J. Bruna. On the sample complexity of learning under geometric stability. *Advances in Neural Information Processing Systems*, 34, 2021.

[BZSL13] J. Bruna, W. Zaremba, A. Szlam, and Y. LeCun. Spectral networks and locally connected networks on graphs. *arXiv preprint arXiv:1312.6203*, 2013.

[Ele21]   B. Elesedy. Provably strict generalisation benefit for invariance in kernel methods. *Advances in Neural Information Processing Systems*, 34, 2021.

[Ele22]   B. Elesedy. Group symmetry in pac learning. In *ICLR 2022 Workshop on Geometrical and Topological Representation Learning*, 2022.

[EZ21]   B. Elesedy and S. Zaidi. Provably strict generalisation benefit for equivariant models. In *International Conference on Machine Learning*, pages 2959–2969. PMLR, 2021.

[GMMM21] B. Ghorbani, S. Mei, T. Misiakiewicz, and A. Montanari. Linearized two-layers neural networks in high dimension. *The Annals of Statistics*, 49(2):1029–1054, 2021.

[GMS05]   M. Gori, G. Monfardini, and F. Scarselli. A new model for learning in graph domains. In *Proceedings. 2005 IEEE international joint conference on neural networks*, volume 2, pages 729–734, 2005.

[Hoc12]   H. Hochstadt. *The functions of mathematical physics*. Courier Corporation, 2012.

[HSSV21]   D. Hsu, C. Sanford, R. A. Servedio, and E. Vlatakis-Gkaragkounis. On the approximation power of two-layer networks of random relus. *arXiv preprint arXiv:2102.02336*, 2021.

[Hsu]   D. Hsu. Dimension lower bounds for linear approaches to function approximation.

[HZRS16]   K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[JGH18]   A. Jacot, F. Gabriel, and C. Hongler. Neural tangent kernel: Convergence and generalization in neural networks. *Advances in neural information processing systems*, 31, 2018.

[Kea98]   M. Kearns. Efficient noise-tolerant learning from statistical queries. *Journal of the ACM (JACM)*, 45(6):983–1006, 1998.

[KMS20]   P. Kamath, O. Montasser, and N. Srebro. Approximate is good enough: Probabilistic variants of dimensional and margin complexity. In *Conference on Learning Theory*, pages 2236–2262. PMLR, 2020.

[Kna96]   A. W. Knapp. *Lie groups beyond an introduction*, volume 140. Springer, 1996.

[KSH12]   A. Krizhevsky, I. Sutskever, and G. E. Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25, 2012.

[LB$^+$95] Y. LeCun, Y. Bengio, et al. Convolutional networks for images, speech, and time series. *The handbook of brain theory and neural networks*, 3361(10):1995, 1995.

[LCC$^+$22] Y. Li, D. Choi, J. Chung, N. Kushman, J. Schrittwieser, R. Leblond, T. Eccles, J. Keeling, F. Gimeno, A. D. Lago, et al. Competition-level code generation with alphacode. *arXiv preprint arXiv:2203.07814*, 2022.

[LKF10]   Y. LeCun, K. Kavukcuoglu, and C. Farabet. Convolutional networks and applications in vision. In *Proceedings of 2010 IEEE international symposium on circuits and systems*, pages 253–256. IEEE, 2010.

[LZA21]   Z. Li, Y. Zhang, and S. Arora. Why are convolutional nets more sample-efficient than fully-connected nets? In *International Conference on Learning Representations*, 2021.

[Mis22]   T. Misiakiewicz. Spectrum of inner-product kernel matrices in the polynomial regime and multiple descent phenomenon in kernel ridge regression. *arXiv preprint arXiv:2204.10425*, 2022.

[MM21]   T. Misiakiewicz and S. Mei. Learning with convolution and pooling operations in kernel methods. *arXiv preprint arXiv:2111.08308*, 2021.

[MMM21]   S. Mei, T. Misiakiewicz, and A. Montanari. Learning with invariances in random features and kernel models. In *Conference on Learning Theory*, pages 3351–3418. PMLR, 2021.

[MS20]   E. Malach and S. Shalev-Shwartz. Computational separation between convolutional and fully-connected networks. *arXiv preprint arXiv:2010.01369*, 2020.

[Ng04]   A. Y. Ng. Feature selection, l 1 vs. l 2 regularization, and rotational invariance. In *Proceedings of the twenty-first international conference on Machine learning*, page 78, 2004.

[NY21]   I. Nachum and A. Yehudayoff. On symmetry and initialization for neural networks. In *Latin American Symposium on Theoretical Informatics*, pages 401–412. Springer, 2021.

[O'D14]   R. O'Donnell. *Analysis of boolean functions*. Cambridge University Press, 2014.

[Rey20]   L. Reyzin. Statistical queries and statistical algorithms: Foundations and applications. *arXiv preprint arXiv:2004.00557*, 2020.

[Sha18]   O. Shamir. Distribution-specific hardness of learning neural networks. *The Journal of Machine Learning Research*, 19(1):1135–1163, 2018.

[SHS⁺18]   D. Silver, T. Hubert, J. Schrittwieser, I. Antonoglou, M. Lai, A. Guez, M. Lanctot, L. Sifre, D. Kumaran, T. Graepel, et al. A general reinforcement learning algorithm that masters chess, shogi, and go through self-play. *Science*, 362(6419):1140–1144, 2018.

[SNPP19]   S. Schubert, P. Neubert, J. Pöschmann, and P. Protzel. Circular convolutional neural networks for panoramic images and laser data. In *2019 IEEE Intelligent Vehicles Symposium (IV)*, pages 653–660. IEEE, 2019.

[SSS17]   S. Shalev-Shwartz, O. Shamir, and S. Shammah. Failures of gradient-based deep learning. In *International Conference on Machine Learning*, pages 3067–3075. PMLR, 2017.

[Sta90]   D. Stanton. An introduction to group representations and orthogonal polynomials. In *Orthogonal Polynomials*, pages 419–433. Springer, 1990.

[Val84]   L. G. Valiant. A theory of the learnable. *Communications of the ACM*, 27(11):1134–1142, 1984.

[VCC⁺17]   P. Velickovic, G. Cucurull, A. Casanova, A. Romero, P. Lio, and Y. Bengio. Graph attention networks. *stat*, 1050:20, 2017.

[VSP⁺17]   A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

[WLLM19]   C. Wei, J. D. Lee, Q. Liu, and T. Ma. Regularization matters: Generalization and optimization of neural nets vs their induced kernel. *Advances in Neural Information Processing Systems*, 32, 2019.

[ZHSJ19]   J. Zhang, T. He, S. Sra, and A. Jadbabaie. Why gradient clipping accelerates training: A theoretical justification for adaptivity. *arXiv preprint arXiv:1905.11881*, 2019.