Thinned random measures for sparse graphs with overlapping communities

Abstract

Network models for exchangeable arrays, including most stochastic block models, generate dense graphs with a limited ability to capture many characteristics of real-world social and biological networks. A class of models based on completely random measures like the generalized gamma process (GGP) have recently addressed some of these limitations. We propose a framework for thinning edges from realizations of GGP random graphs that models observed links via nodes' overall propensity to interact, as well as the similarity of node memberships within a large set of latent communities. Our formulation allows us to learn the number of communities from data, and enables efficient Monte Carlo methods that scale linearly with the number of observed edges, and thus (unlike dense block models) sub-quadratically with the number of entities or nodes. We compare to alternative models for both dense and sparse networks, and demonstrate effective recovery of latent community structure for real-world networks with thousands of nodes.

1   Introduction

Given observations of (often binary) relationships Y_{ij} between pairs of nodes or entities (i, j), many relational models [1] seek to uncover an underlying set of communities. Classic stochastic blockmodels [2] generalize mixture models for clustering non-relational data by assigning each entity to one of K communities (clusters). The *infinite relational model* (IRM) [3] instead uses a Dirichlet process prior [4] to partition entities into single communities. While the IRM allows the number of communities to be inferred from data, later work has shown that real-world social networks are better captured by models which allow individuals to participate in multiple communities [5], including applications of the *hierarchical Dirichlet process* (HDP) [6] to relational data [7].

There is an extensive literature on descriptive statistics of biological and social networks [8, 9], including degree distributions, path distances and "small world" phenomena [10], community structures and modularity, and notions of centrality and causality. In particular, sparsity is a ubiquitous phenomenon in real-world networks [8, 9]: as network size grows, the number of edges grows more slowly than the quadratic number of node pairs. However, the IRM and HDP relational models (and a large literature of related models [1]) generate *dense* graphs where the number of edges scales quadratically with the number of nodes. In fact, a classic representation theorem [11, 12] shows that any generative model that regards graphs as exchangeable adjacency matrices, meaning arrays whose distribution is invariant to permutations of node indices, generates dense graphs. Most existing probabilistic network models, which generate an adjacency matrix by sampling edges from independent Bernoulli distributions given latent node-specific parameters, have this limitation.

By representing graphs as a latent process (a completely random measure), Caron and Fox [13] showed that it is possible to formulate generative models that capture the sparsity of real-world networks. Related models, including certain infinite limits of graphs called *graphons*, have been

studied by several authors [14, 15, 16]. However, these models mostly produce homogeneous graphs with sparsity and heavy-tailed degree distributions, but lacking the community structure of real networks. Two notable exceptions are work by Herlau et al. [17] and Todeschini et al. [18] that augment the random-measure models of [13] with variables encoding latent community structure.

In this paper, we propose a novel random graph model that efficiently thins edges from sparse homogeneous graphs to reveal community structure while maintaining sparsity. Unlike [17], we allow entities to have membership in multiple communities. Unlike [18], we allow completely flexible specification of the hierarchical Bayesian prior on latent community memberships; importantly, this enables the network-specific learning of the appropriate number of latent communities. We further develop an efficient Monte Carlo inference algorithm that, unlike nearly all dense block models, scales linearly with the number of observed edges and thus sub-quadratically with the number of entities. Experiments show recovery of communities for networks with thousands of nodes.

2   Background: Stochastic Blockmodels for Dense and Sparse Networks

An undirected binary network with N nodes and E edges may be represented by a symmetric $N \times N$ adjacency matrix Y. If there is an edge (link) between nodes $i \neq j$ then $Y_{ij} = 1$, otherwise $Y_{ij} = 0$.

2.1   Mixed Membership Stochastic Blockmodels

Stochastic blockmodels (SBMs) [2] assume that each node belongs to one of K latent communities, and that the probability of an edge depends on how strongly their communities are connected. The community $c_i \in \{1, \ldots, K\}$ of node i follows a categorical distribution $c_i \overset{\text{ind}}{\sim} \text{Cat}(\beta)$, where $\beta = (\beta_1, \ldots, \beta_K)$ so that β_k is the frequency of community k. Edges are sampled independently as $Y_{ij} \overset{\text{ind}}{\sim} \text{Bernoulli}(\eta_{c_i c_j})$, where $\eta_{k\ell} = \eta_{\ell k}$ is the probability of an edge between nodes in communities k and ℓ. These interaction probabilities are often assigned conjugate beta priors, $\eta_{k\ell} \overset{\text{ind}}{\sim} \text{Beta}(\tau_a, \tau_b)$.

Mixed membership stochastic blockmodels (MMSBs) [5] extend SBMs to allow nodes to be members of multiple communities. Let $\pi_i = (\pi_{i1}, \ldots, \pi_{iK})$ denote a K-dimensional probability vector representing the strength of affiliation of node i to each of K communities. For every pair of nodes (i, j), the communities governing their interaction are sampled as $c_{ij} \overset{\text{ind}}{\sim} \text{Cat}(\pi_i)$, $c_{ji} \overset{\text{ind}}{\sim} \text{Cat}(\pi_j)$. Then, like standard SBMs, edges are sampled independently as $Y_{ij} \overset{\text{ind}}{\sim} \text{Bernoulli}(\eta_{c_{ij} c_{ji}})$. Community memberships are typically assigned a hierarchical prior, such as

$$\pi_i \mid \beta \overset{\text{ind}}{\sim} \text{Dirichlet}(\zeta\beta_1, \ldots, \zeta\beta_K), \qquad \beta \sim \text{Dirichlet}\left(\frac{\gamma}{K}, \ldots, \frac{\gamma}{K}\right). \tag{1}$$

When fitting this model to data, we can treat K as an upper bound to the number of communities (that is, larger than the maximum number of communities that we expect to be necessary to model the network) and fix $\gamma \ll K$. In this way, the hierarchical Dirichlet formulation allows network-specific learning of the number of communities by favoring sparse community frequency vectors $\beta = (\beta_1, \ldots, \beta_K)$ with some elements $\beta_h \approx 0$, $h \in \{1, \ldots, K\}$. The hierarchical Dirichlet process [6, 7] is the limit of this prior as K approaches infinity [19].

2.2   Sparse Network Models via Completely Random Measures

For any fixed community frequencies β and interaction probabilities η, the SBM and MMSB may only generate *dense* graphs where the number of edges scales quadratically with the number of nodes [12]. In contrast, many real-world networks appear to be sparse [9]. Heuristics are often used to fit (mixed membership) SBMs to large but sparse networks, such as fixing (rather than learning) $\eta_{k\ell} = \varepsilon \approx 0$ for $k \neq \ell$; for example Kim et al. [7] fix $\varepsilon = e^{-30}$. We seek to build models that can capture mixed memberships and sparsity simultaneously without needing to rely on such heuristics.

Completely Random Measures.   By representing the graph as a point process on the plane, Caron and Fox [13] showed that it is possible to generate sparse graphs by appropriately choosing the mean measure of the point process. According to their model, for $i \neq j$,

$$Y_{ij} \mid w_i, w_j \overset{\text{ind}}{\sim} \text{Bernoulli}\left(1 - \exp\{-2w_i w_j\}\right), \tag{2}$$

Figure 1: Generation of an adjacency matrix from the GGP model of Caron and Fox [13] (top) and via thinning via our proposed model with $K = 3$ communities (bottom). Rows and columns correspond to nodes in all plots, ordered by decreasing sociability w_i. *Left:* Latent directed multigraphs underlying the observed graphs on the right. The intensity of a cell is proportional to the Poisson rate: $w_i w_j$ for the GGP, and $w_i w_j \sum_{k=1}^{K} \pi_{ik} \pi_{jk}$ for the thinned GGP. Red zeros indicate thinned edges. *Right:* Binary adjacency matrix of the observed graph for the GGP (top) and thinned GGP (bottom) models. For the thinned GGP, edges are colored according to the community that generated it. Gray cells mark nodes whose edges in the latent multigraph were all thinned, and are thus observed under the GGP but unobserved under the thinned GGP. GGP hyperparameters were set as $\sigma = 0.1, \tau = 1, \alpha = 10$, and community memberships were sampled given $\beta = (1/3, 1/3, 1/3), \zeta = 1$.

where $w_i > 0$ represents the *sociability* of node i: nodes with higher w_i have higher probability to interact with other nodes, and hence greater expected degree. Differently from the (mixed membership) SBMs, where all parameters governing nodes' interactions are sampled independently, here nodes' sociabilities are generated altogether using the jumps of a *completely random measure* (CRM) [20]. Each node is also independently associated to a real-valued location ℓ_i uniformly distributed on the real line, and then a set of potential nodes is defined by restricting to sociabilities with a sampled location in the interval $[0, \alpha]$,

$$W_\alpha = \{w_i : \ell_i \in [0, \alpha]\}. \tag{3}$$

Here $\alpha > 0$ controls the (random) number of nodes N_α in the network by determining the size of the interval in which jumps are included. Depending on the distribution of the jumps, the model can capture both sparse and dense graphs. Intuitively, as detailed in Sec. 5.1 of [13], for sparse networks the distribution of the jumps needs to place almost all of its mass near zero.

This model requires CRMs for which the sum $\bar{W}_\alpha = \sum_{i:\ell_i \in [0,\alpha]} w_i$ of the jumps in $[0, \alpha]$ is finite. A simple undirected network is then generated via a binary projection of an underlying directed multigraph, where the total number of edges n_{ij} from node i to node j is independently distributed as

$$n_{ij} \mid w_i, w_j \overset{\text{ind}}{\sim} \text{Poisson}(w_i w_j). \tag{4}$$

An edge is present in the undirected network if there is at least one directed edge in the latent directed multigraph, that is $Y_{ij} = \mathbb{1}(n_{ij} + n_{ji} \geq 1)$ for nodes $i \neq j$. Because the sum of independent Poisson random variables is Poisson, Eq. (4) implies $P(n_{ij} + n_{ji} = 0) = \exp\{-2w_i w_j\}$, from which Eq. (2)

follows. The number N of nodes in the observed network then equals the number N_α of nodes that have at least one edge in the underlying multigraph. This construction of the binary matrix from a multigraph [13] is visualized in Fig. 1.

The sum-property of the Poisson distribution also implies that, given $\bar{W}_\alpha$, the total number of edges $\bar{D}_\alpha$ in the multigraph has a Poisson($\bar{W}_\alpha^2$) distribution. Since n_{ij} has a high probability of being 0 for most node pairs (i, j), it is more efficient to first sample $\bar{D}_\alpha$ and then independently assign each edge to a pair of nodes based on their sociabilities. In more detail, Eq. (4) is equivalent to

$$\bar{D}_\alpha \mid \bar{W}_\alpha \sim \text{Poisson}(\bar{W}_\alpha^2), \quad P(x_{ev} = i \mid W_\alpha) = \frac{w_i}{\bar{W}_\alpha}, \quad n_{ij} = \sum_{e=1}^{\bar{D}_\alpha} \mathbb{1}(x_{e1} = i)\mathbb{1}(x_{e2} = j), \quad (5)$$

where $x_{ev} \in \{1, 2, \dots\}$ for $v = 1, 2$ indicates the nodes sampled for edges $e \in \{1, \dots, \bar{D}_\alpha\}$. Caron and Fox [13] propose the *generalized gamma process* (GGP) [21, 22, 23] as a flexible but tractable CRM for W_α, with parameters $\tau \in (0, \infty)$, and $\sigma \in (-\infty, 0]$ for dense graphs or $\sigma \in (0, 1)$ for sparse graphs. Fig. 2 (black component) provides a visual summary of the generative process underlying the construction of a GGP random graph, using a directed graphical model that highlights the conditional dependencies (and independencies) between its variables. Figure 3a shows a network sampled from the GGP model by means of a node-edge diagram.

Sparse Block Models. A limitation of the framework described above is that it does not model the community (block) structure of the network – a well-recognized feature of complex networks. Herlau et al. [17] generalized the approach in [13] to accommodate both sparse and dense networks with community structure. Specifically, they introduce a latent discrete variable $c_i \in \{1, \dots, K\}$ to indicate the assignment of node i to one of K communities, like in the SBMs. A bivariate CRM incorporates both the sociability weights and a set of parameters, denoted by $\eta_{c_i c_j}$, capturing the interaction strength between two communities c_i and c_j in the underlying multigraph. For their formulation, the total number of edges n_{ij} from node i to node j are independently distributed as $n_{ij} | c_i, c_j, w_i, w_j \overset{\text{ind}}{\sim} \text{Poisson}(\eta_{c_i c_j} w_i w_j)$, and the likelihood from Eq. (2) of the observed nodes is modified as $Y_{ij} \mid c_i, c_j, w_i, w_j \overset{\text{ind}}{\sim} \text{Bernoulli}(1 - e^{-2\eta_{c_i c_j} w_i w_j})$. We refer to this approach as the stochastic block model generalized gamma process (SBM-GGP).

Sparse Mixed Membership. The SBM-GGP models sparse and dense networks with community structure, but does not capture overlapping community structures; it induces networks whose nodes are partitioned into disjoint communities. In follow-up work, Todeschini et al. [18] extended the CRM-based framework discussed above by associating a vector $(w_{i1}, \dots, w_{iK})$ of sociabilities to each node i, to represent different levels of affiliation of nodes to the K latent communities. A node may have high levels of affiliation to more than a community, leading to the formation of edges across multiple communities. The vectors of node sociabilities are distributed according to a compound CRM [24]; specifically, their implementation uses a *compound generalized gamma process* (CGGP). The likelihood function is modified accordingly, by independently sampling undirected edges as $Y_{ij} \mid w_i, w_j \overset{\text{ind}}{\sim} \text{Bernoulli}(1 - \exp\{-2 \sum_{k=1}^{K} w_{ik} w_{jk}\})$. The latent community weights are modeled as $w_{ik} = w_{i0} \psi_{ik}$, where w_{i0} are sampled from a GGP as in Eq. (3), and ψ_{ik} are gamma-distributed random variables $\psi_{ik} \overset{\text{ind}}{\sim} \text{Gamma}(a_k, b_k)$ whose shape a_k and rate b_k may be inferred from data.

As [18] point out, the CGGP model exploits an (unconstrained) non-negative matrix factorization to define the Bernoulli probability link. In the Appendix, we demonstrate that this lack of constraints hampers the ability of the CGGP model to recover the true community structure of the network. Better regularized approaches to non-negative matrix factorization, like the one we propose, may improve the identifiability of latent community structures and network parameters [25].

3   The Thinned CRM Network Model

We now add overlapping community memberships to the GGP network model [13] via vectors of probabilities sampled from a hierarchical Dirichlet distribution. Unlike the formulation of Todeschini et al. [18], our model enables learning the number of communities from data (see Secs. 2.1 and 4). By using probability vectors rather than unconstrained non-negative values to model community memberships, our model provides a regularized approach to inference in the GGP model, which in simulations (Sec. 5.1) provides a substantial increase in community detection accuracy.

Figure 2: Directed graphical model representing the GGP random graphs of Caron and Fox [13] (black), and the additional variables (blue) in our thinned GGP. For GGP hyperparameters that induce sparse graphs ($\sigma > 0$) there is an infinite number of *potential* nodes, with sociabilities w_i and community memberships π_i.

Let each node i have both a sociability parameter w_i from the GGP as in (3), and a vector of probabilities $\pi_i = (\pi_{i1}, \dots, \pi_{iK})$ drawn from a hierarchical Dirichlet distribution as in (1). Moreover, let the number of *potential* edges between nodes i and j in the latent multigraph depend only on their sociabilities, as in (4). For each of the n_{ij} potential edges, node i independently samples a community from $\text{Cat}(\pi_i)$, and node j samples a community from $\text{Cat}(\pi_j)$. If these community assignments match, the edge is retained; otherwise, it is *thinned* (i.e., discarded). See Figs. 1 and 3 for examples.

More formally, let $\dot{n}_{ij}$ be the number of multigraph edges between a pair of nodes i, j that is retained (not thinned). Edges $e \in \{1, \dots, \bar{D}_\alpha\}$ in the GGP multigraph are stochastically thinned as follows:

$$c_{e1} \mid x_{e1}, (\pi_1, \pi_2, \dots) \overset{\text{ind}}{\sim} \text{Cat}(\pi_{x_{e1}}), \qquad c_{e2} \mid x_{e2}, (\pi_1, \pi_2, \dots) \overset{\text{ind}}{\sim} \text{Cat}(\pi_{x_{e2}}), \tag{6}$$

$$\dot{n}_{ij} = \sum_{e=1}^{\bar{D}_\alpha} \mathbb{1}(x_{e1} = i, x_{e2} = j, c_{e1} = c_{e2}), \qquad Y_{ij} = \mathbb{1}\left(\dot{n}_{ij} + \dot{n}_{ji} \geq 1\right). \tag{7}$$

Here $x_{ev} \in \{1, 2, \dots\}$ for $v = 1, 2$ indicate the nodes associated with edge e as in Eq. (5). An edge Y_{ij} is then present in the undirected graph if and only if at least one multigraph edge is not thinned. Equivalently, Eq. (7) implies that the observed undirected graph is a binary projection of the multigraph edges that are *selected*, i.e. retained after the thinning process.

To determine the distribution of Y_{ij}, note that the probability that nodes i and j are assigned to the same community (marginalizing across communities) equals $P(c_{ei} = c_{ej}) = \sum_{k=1}^K \pi_{ik} \pi_{jk}$. Therefore, marginalizing over the latent multigraph, $\dot{n}_{ij} \mid w_i, w_j, \pi_i, \pi_j \overset{\text{ind}}{\sim} \text{Poisson}(w_i w_j \sum_{k=1}^K \pi_{ik} \pi_{jk})$. The likelihood of the observed network thus equals

$$Y_{ij} \mid w_i, w_j \overset{\text{ind}}{\sim} \text{Bernoulli}\left(1 - \exp\left\{-2 w_i w_j \sum_{k=1}^K \pi_{ik} \pi_{jk}\right\}\right). \tag{8}$$

Unlike the MMSB and GGP models, our *thinned generalized gamma process* (TGGP) model favors edges between nodes that have *both* large sociabilities and similar community memberships. The TGGP model is summarized graphically in Fig. 2 and illustrated in Figs. 1, 3, 4a.

4   Monte Carlo Posterior Inference

In our TGGP model, the latent (unthinned) multigraph has a distribution (Eq. (5)) that depends only on the node sociability parameters w_i. The thinning process (Eq. (7)) then depends only on the community membership vectors π_i. As can be deduced from the Markov properties of the directed graphical model in Fig. 2, given these latent multigraphs, the posterior distributions of $(w_1, w_2, \dots)$ and $(\pi_1, \pi_2, \dots)$ are conditionally independent. This design simplifies posterior inference, and in particular allows us to apply Theorem 6 of [13] to derive the posterior of nodes' sociabilities, provided we can condition on the (latent) multigraph. We thus implement a Gibbs sampling strategy for posterior inference where we sample both thinned and retained edges in the latent multigraph, as well as their community assignments, to allow for efficient updates of other variables.

Some steps in the sampler are straightforwardly derived, considering that we can borrow the approach detailed in [13] to update node sociabilities and GGP hyperparameters (see the Appendix for a

(a) Potential edges   (b) Selected edges   (c) Thinned edges

Figure 3: Visualization of networks simulated via a (thinned) GGP with $\alpha = 15, \sigma = 0.2, \tau = 1$. (a) Before thinning, *potential* edges are proposed according to nodes' sociabilities as in [13]. (b) After thinning, *selected* edges have colors (blue/red) corresponding to their assignment to $K = 2$ communities. (c) The *thinned* edges (gray) are those for which the connected nodes were assigned to different communities. In both (b) and (c), node colors represent their true community memberships, where lighter colors indicate more balanced memberships. Node sizes are proportional to betweenness centrality, and layout is determined by Gephi's Force Atlas 2 [26].

detailed outline). However, the implementation of the sampler requires some additional careful development – which we detail below – to sample the latent multigraph, due to the unobserved thinning process. Multigraph sampling is made more computationally efficient via model properties that are unique to sparse, as opposed to dense, stochastic block models. Letting (filled dot) $\dot{n}_{ij}$ denote the number of unthinned (i.e. selected) multigraph edges as in (7), and (empty dot) $\mathring{n}_{ij} = n_{ij} - \dot{n}_{ij}$ denote the number of thinned multigraph edges, we sample the latent multigraph as follows.

Sampling of $\dot{n}_{ij}$: From Eq. (7), there exists an edge in the observed graph if and only if there is at least one unthinned edge between nodes i and j in the latent multigraph. Thus rather than considering each pair i, j, we only need to sample $\dot{n}_{ij}$ when $Y_{ij} = 1$, an operation with cost linear in the number of observed (undirected) edges. Conversely, $Y_{ij} = 0$ implies $\dot{n}_{ij} = \dot{n}_{ji} = 0$. Since there must be at least one unthinned edge when $Y_{ij} = 1$, the posterior follows a *zero-truncated* Poisson distribution:

$$(\dot{n}_{ij} + \dot{n}_{ji}) \mid Y_{ij} = 1, w_i, w_j, \pi_i, \pi_j \sim \text{Zero-Trunc-Poisson}\left(2 w_i w_k \sum_{k=1}^{K} \pi_{ik} \pi_{jk}\right).$$

For each unthinned edge we sample a single community assignment, since by definition these are the edges whose nodes have been assigned to the same communities. We can sample the community assignment of an unthinned edge between i and j easily as a draw from $\text{Cat}(\pi_{i1}\pi_{j1}, \ldots, \pi_{iK}\pi_{jK})$.

Sampling of $\mathring{n}_{ij}$: By construction, since thinned edges are unobserved, all pairs of nodes (i, j) may have edges that are thinned. These edges are auxiliary variables necessary to obtain the full conditional posterior distribution of W_α. Also, to update community memberships and global frequencies, it is necessary to assign every thinned edge to a pair of discordant (non-matching) communities. Thanks to the properties of Poisson processes, we do not need to sample $\mathring{n}_{ij}$ for all the pairs of nodes; we can develop a more efficient sampler that exploits the thinned model construction. We first sample a *proposed* total number of thinned edges $\mathring{N} \sim \text{Poisson}\left(2 \sum_{i,j=1}^{N} w_i w_j\right)$. We then assign each of these independently to a pair of nodes according to their sociabilities as in Eq. (5), and subsequently to a pair of commmunities given the memberships of the assigned nodes as in Eq. (6). Finally, we determine $\mathring{n}_{ij}$ from the number of edges that were assigned to discordant communities.

Sampling unobserved nodes: As illustrated in Figs. 1 and 3, the total number of nodes N_α with at least one edge in the *unthinned* multigraph is likely to be different from the total number of nodes with at least one edge *after* thinning and – as a consequence – from the total number of nodes N in the observed binary graph Y. There is thus some latent number $N_\alpha - N \geq 0$ of nodes whose edges with the observed nodes have all been thinned. In order to learn this number, our MCMC sampler includes an approximate update of N_α according to the mean ratio N_α/N from graphs simulated from the GGP prior given the latest samples of the hyperparameters α, σ, τ. We found that this approximate method leads to convergence of the empirical MCMC-based estimate of N_α across all simulated and

(a) Adjacency Matrix	(b) True Blocks	(c) Estimated, TGGP	(d) Estimated, CGGP [18]

Figure 4: Results on two simulation experiments: a graph generated with the CGGP [18] (top) and a graph simulated with the proposed TGGP (bottom). Column (a) shows the true adjacency matrices, sorting nodes into blocks according to the strongest community membership; (b) shows the relative edge density in the true blocks, sorting blocks by intensity. Columns (c) and (d) show the blocks estimated, respectively, with the TGGP and the CGGP. In both simulations, we generate data setting $\alpha = 250$, $\sigma = 0.1$, $\tau = 1$, and $K = 15$. For the CGGP we set $a_k = 1/K$ and $b_k = 1$; for the TGGP we set $\beta = (1/K, ..., 1/K)$ and $\zeta = 1$. Inference uses the true number of communities for the CGGP, while our TGGP is given a loose upper bound of $K = 50$, $\gamma = 10$, $\zeta = 0.2$. The TGGP closely approximates the true community structure, while the CGGP consistently underestimates the true number of communities.

real data that we considered (see Appendix). Sampling of the thinned edges from these unobserved nodes introduces some additional complications that we efficiently resolve in the Appendix.

Sampling community memberships π_i: Conditioned on the discrete community assignments for edges in the latent multigraph, the node community memberships π_i have closed-form Dirichlet posteriors (see Appendix). Given π, the global community frequencies β may be efficiently resampled using auxiliary-variable methods developed for the hierarchical Dirichlet process [6]. By learning β, the node community memberships π_i become sparse, placing significant probability mass only on a data-dependent subset of the full set of K communities allocated in Eq. (1).

Computational complexity: For a K-community TGGP model of a graph with E observed edges, resampling the latent multigraph requires $\mathcal{O}(EK)$ operations. (The thinned multigraph has fewer edges, and thus its resampling increases costs by a small constant.) Closed-form resampling of community memberships is faster, requiring only $\mathcal{O}(NK)$ operations for an N-node graph. The CGGP model [18] uses Hamiltonian Monte Carlo proposals with similar cost, but empirically the CGGP sampler mixes slower and has inferior performance (see experiments). By exploiting sparse matrices and parallelization, both samplers may be scaled to networks with tens of thousands of nodes; very-large networks may require alternative approximate inference algorithms.

5 Experimental Results

5.1 Simulation

We discuss a simulation study where we investigated the performance of our proposed TGGP model, and the CGGP model of [18], based on simulated data generated from either model.

First, we present the results from a sparse graph with 15 communities, simulated from our TGGP model by setting $\alpha = 250$, $\sigma = 0.1$, $\tau = 1$ for the distribution of node sociabilities and $\gamma = 10$, $\zeta = 0.2$ for the distribution of node community memberships. The adjacency matrix of the resulting simple, undirected graph is shown in Figure 4(a, bottom). Figure 4(b, bottom) sorts the simulated nodes into blocks according to their main membership and plots the density of edges in each block. We see that the simulated graph has a clear block structure.

We then run our MCMC sampler for 50,000 iterations, discarding the first 40,000 samples as burn-in. For our model fitting, we let 50 be the upper bound to the number of communities and we set $\gamma = 10$ and $\zeta = 0.5$ to allow for learning the number of communities. From a qualitative comparison of the (b) and (c) bottom panes in Figure 4, we see that the community memberships recovered from our model are close to the underlying truth. The credible intervals indicate that the posterior distributions of all parameters tend to concentrate around the true values used for simulation (see Appendix for plots). In contrast, the CGGP model [18] struggles to recover the true community structure of the network (Fig. 4(d bottom)), despite being fitted with the number of communities $K = 15$ set to match the truth. We also simulated a graph from the CGGP model of [18] with parameters

Figure 5: Plot of similarity between true and inferred community memberships for networks simulated (*data*) and fitted (*model*) with the TGGP and CGGP [18]. Our TGGP model uniformly achieves higher similarities.

$a_k = 1/K, b_k = 1$ chosen to induce a community membership prior similar to our TGGP. We fit both the CGGP model and the TGGP model to the generated data. When fitting with the CGGP we still set the number of communities equal to the truth ($K = 15$). The results plotted in Fig. 4(d) indicate that the block structures learned by our (misspecified) TGGP model are nevertheless closer to truth than those recovered by the CGGP.

To quantify the superior community recovery of our TGGP model, recall that for each observed node the CGGP estimates a K-dim. positive real vector of community-specific sociabilities $(w_{i1}, \ldots, w_{iK})$, while our TGGP infers a K-dim. probability vector of community memberships $(\pi_{i1}, \ldots, \pi_{iK})$. For quantitative comparison, we standardize true and inferred sociability vectors by dividing each w_{ik} by the sum $\sum_{h=1}^{K} w_{ih}$. Also, since the TGGP model was fitted with K set to an upper-bound of 50 rather than to the true number of communities, when analyzing TGGP results we pad the true vectors of community memberships (for TGGP-simulated data) and sociabilities (for CGGP-simulated data) with zeros. For estimated parameters, community indices are then permuted to maximize similarity with true parameters. Letting ψ_i and $\hat{\psi}_i$ be, respectively, true and inferred community memberships/sociabilities, we define similarity as $1 - \frac{1}{N} \sum_{i=1}^{N} \mathrm{d}(\psi_i, \hat{\psi}_i)$ where the distance is the L1 total variation $\mathrm{d}(\psi_i, \hat{\psi}_i) = \frac{1}{2} \sum_{k=1}^{K} |\psi_{ik} - \hat{\psi}_{ik}|$. Fig. 5 confirms that the TGGP more accurately recovers community memberships for both networks, and for nodes of both high and low degree.

5.2 Real network data

We compare the performance of our TGGP framework for adding overlapping communities to the GGP model with the approaches detailed in Sec. 2.2: the CGGP (sparse with mixed memberships) of [18] and the SBM-GGP model (sparse with single memberships) of [17]. We also compare to more classical models from Sec. 2.1: the SBM (dense with single membership) of [2] and the MMSB (dense with mixed memberships) of [5]. We run 50,000 iterations of the five models' MCMC on four real-world networks; see Appendix for data sources and pre-processing. Each model was fit to fully observed data to learn node-specific parameters (e.g., sociabilities and community memberships) and community-interaction probabilities, using the values from the final MCMC iteration. Two different measures of posterior predictive accuracy were then used to assess the goodness of model fit.

For the first evaluation measure, we randomly selected 5% of the entries equal to 1 in the adjacency matrix and set them to 0. We then compute the probability of being 1 of all entries that are equal to 0 in the modified adjacency matrix to assess how well each model can distinguish the entries that should in fact be 1. This edge-retrieval measure is motivated by common applications of network analysis to recommendation tasks (suggesting which edges that are not observed should be present). Fig. 6 (top) plots recall (proportion of ones recovered) on the horizontal axis, and F-score (geometric mean of recall and precision, which is the proportion of ones correctly predicted among all entries predicted as ones) on the vertical axis. This retrieval task is very challenging because, for sparse networks, the missing edges are a tiny proportion of all zero entries in the modified adjacency matrix.

Figure 6: F-score versus recall for retrieval of missing edges (top), and ROC curves (bottom) for prediction of missing adjacency matrix entries, for four real-world networks of varying sparsity. Our TGGP uniformly outperforms the CGGP [18], SBM-GGP [17], MMSB [5], and SBM [2].

For the second evaluation measure, we randomly obscure 5% of *all* entries in the adjacency matrix to assess how well each model can recover whether an entry is equal to 0 or to 1. Fig. 6 (bottom) plots the receiver operating characteristic (ROC) curves, where false positive rate (number of zeros predicted as ones divided by the number of zeros) is on the horizontal axis, and true positive rate (proportion of ones correctly predicted as ones divided by the number of ones) is on the vertical axis. This second task has been used in many prior papers but is not as hard as the first one, because for a model to score well it suffices to learn small interaction probabilities, since almost all of the randomly selected entries are 0. Fig. 6 shows that our TGGP model does consistently better than all baseline methods for all networks considered, according to both predictive-performance measures.

6 Discussion

We have proposed a framework for the analysis of binary network data that extends the GGP-based model of Caron and Fox [13] by allowing for overlapping community structures, depending both on the overall sociability of the nodes *and* the similarity of their community memberships. The assumed generative model proposes a novel latent multi-graph framework where nodes are allowed to connect within the same or across different communities, but the edges formed across different communities are hidden (thinned) in the projection giving rise to the observed network. With respect to alternative extensions of the original GGP network model [17, 18], our TGGP enables mixed community memberships and facilitates regularization of the latent community distributions for each node, resulting in improved inference and reconstruction of the latent community structures for both simulated and real data. Furthermore, our model formulation allows for learning the number of communities directly from the data, by encouraging inferring a number of non-empty communities potentially smaller than a set upper bound.

The proposed TGGP model is amenable to further extensions. Since our mixed membership allocation framework relies on the well-studied dirichlet-multinomial specification, it is possible to leverage the vast literature on (finite and infinite) hierarchical dirichlet mixture models to capture more complex and heterogeneous network data. It is also possible to include additional node covariates or metadata to guide the allocation of nodes to communities. Finally, distributional and asymptotic properties of our model formulation can be investigated by exploiting recent results in the literature related to finite mixtures and mixtures of finite mixtures [see, e.g., 27, 28, 29, 19].

References

[1] A. Goldenberg, A.X. Zheng, S.E. Fienberg, and E.M. Airoldi. A survey of statistical network models. *Arxiv preprint arXiv:0912.5410*, 2009.

[2] Yuchung J Wang and George Y Wong. Stochastic blockmodels for directed graphs. *Journal of the American Statistical Association*, 82(397):8–19, 1987.

[3] C. Kemp, J. Tenenbaum, T. Griffiths, T. Yamada, and N. Ueda. Learning systems of concepts with an infinite relational model. In *AAAI*, 2006.

[4] D. Blackwell and J. B. MacQueen. Ferguson distributions via Pólya urn schemes. *Annals of Statistics*, 1(2):353–355, 1973.

[5] Edo M Airoldi, David Blei, Stephen Fienberg, and Eric Xing. Mixed membership stochastic blockmodels. *Advances in neural information processing systems*, 21, 2008.

[6] Y. W. Teh, M. I. Jordan, M. J. Beal, and D. M. Blei. Hierarchical Dirichlet processes. *Journal of the American Statistical Association*, 101(476):1566–1581, December 2006.

[7] Dae Il Kim, Prem K Gopalan, David Blei, and Erik Sudderth. Efficient online inference for bayesian nonparametric relational models. *Advances in neural information processing systems*, 26, 2013.

[8] S. H. Strogatz. Exploring complex networks. *Nature*, 410:268–276, March 2001.

[9] Mark E. J. Newman. Networks: An introduction, 2010.

[10] D. J. Watts and S. H. Strogatz. Collective dynamics of 'small–world' networks. *Nature*, 393: 440–442, June 1998.

[11] David J Aldous. Representations for partially exchangeable arrays of random variables. *Journal of Multivariate Analysis*, 11(4):581–598, 1981.

[12] Peter Orbanz and Daniel M Roy. Bayesian models of graphs, arrays and other exchangeable random structures. *IEEE transactions on pattern analysis and machine intelligence*, 37(2): 437–461, 2014.

[13] François Caron and Emily B Fox. Sparse graphs using exchangeable random measures. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 79(5):1295–1366, 2017.

[14] Christian Borgs, Jennifer T Chayes, Henry Cohn, and Nina Holden. Sparse exchangeable graphs and their limits via graphon processes. *arXiv preprint arXiv:1601.07134*, 2016.

[15] Diana Cai, Trevor Campbell, and Tamara Broderick. Edge-exchangeable graphs and sparsity. *Advances in Neural Information Processing Systems*, 29, 2016.

[16] Victor Veitch and Daniel M Roy. Sampling and estimation for (sparse) exchangeable graphs. *The Annals of Statistics*, 47(6):3274–3299, 2019.

[17] Tue Herlau, Mikkel N Schmidt, and Morten Mørup. Completely random measures for modelling block-structured sparse networks. *Advances in Neural Information Processing Systems*, 29, 2016.

[18] Adrien Todeschini, Xenia Miscouridou, and François Caron. Exchangeable random measures for sparse and modular graphs with overlapping communities. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 82(2):487–520, 2020.

[19] Hemant Ishwaran and Mahmoud Zarepour. Dirichlet prior sieves in finite normal mixtures. *Statistica Sinica*, pages 941–963, 2002.

[20] Olav Kallenberg. *Probabilistic symmetries and invariance principles*, volume 9. Springer, 2005.

[21] Philip Hougaard. Survival models for heterogeneous populations derived from stable distributions. *Biometrika*, 73(2):387–396, 1986.

[22] Lancelot F James. Poisson process partition calculus with applications to exchangeable models and bayesian nonparametrics. *arXiv preprint math/0205093*, 2002.

[23] Antonio Lijoi, Ramsés H Mena, and Igor Prünster. Controlling the reinforcement in bayesian non-parametric mixture models. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 69(4):715–740, 2007.

[24] Jim E Griffin and Fabrizio Leisen. Compound random measures and their use in bayesian non-parametrics. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 79(2):525–545, 2017.

[25] Patrik O Hoyer. Non-negative matrix factorization with sparseness constraints. *arXiv [cs.LG]*, 5:1457–1469, 2004.

[26] Mathieu Bastian, Sebastien Heymann, and Mathieu Jacomy. Gephi: an open source software for exploring and manipulating networks. In *Proceedings of the international AAAI conference on web and social media*, volume 3, pages 361–362, 2009.

[27] Sylvia Frühwirth-Schnatter and Gertraud Malsiner-Walli. From here to infinity: sparse finite versus dirichlet process mixtures in model-based clustering. *Advances in Data Analysis and Classification*, 13(1):33–64, 2019.

[28] Jeffrey W. Miller and Matthew T. Harrison. Mixture models with a prior on the number of components. *Journal of the American Statistical Association*, 113(521):340–356, 2018.

[29] Subhashis Ghosal and Aad van der Vaart. *Fundamentals of Nonparametric Bayesian Inference*. Cambridge Series in Statistical and Probabilistic Mathematics. Cambridge University Press, 2017.