BAYESADAPTER: BEING BAYESIAN, INEXPENSIVELY AND ROBUSTLY, VIA BAYEISAN FINE-TUNING

ABSTRACT

Despite their theoretical appealingness, Bayesian neural networks (BNNs) are falling far behind in term of adoption in real-world applications compared to normal NNs, mainly due to their limited scalability in training, and low fidelity in their uncertainty estimates. In this work, we develop a new framework, named *BayesAdapter*, to address these issues and bring Bayesian deep learning to the masses. The core notion of *BayesAdapter* is to adapt pre-trained deterministic NNs to be BNNs via *Bayesian fine-tuning*. We implement *Bayesian fine-tuning* with a plug-and-play instantiation of stochastic variational inference, and propose *exemplar reparameterization* to reduce gradient variance and stabilize the fine-tuning. Together, they enable training BNNs as if one were training deterministic NNs with minimal added overheads. During *Bayesian fine-tuning*, we further propose an uncertainty regularization to supervise and calibrate the uncertainty quantification of learned BNNs at low cost. To empirically evaluate *BayesAdapter*, we conduct extensive experiments on a diverse set of challenging benchmarks, and observe significantly higher training efficiency, better predictive performance, and more calibrated and faithful uncertainty estimates than existing BNNs.

1 INTRODUCTION

Much effort has been devoted to developing flexible and efficient Bayesian deep models to make accurate, robust, and well-calibrated decisions (MacKay, 1992; Neal, 1995; Graves, 2011; Blundell et al., 2015), with Bayesian neural networks (BNNs) as popular examples. The principled uncertainty quantification inside BNNs is critical for realistic decision-making, well evaluated in scenarios ranging from model-based reinforcement learning (Depeweg et al., 2016), active learning (Hernández-Lobato & Adams, 2015), to healthcare (Leibig et al., 2017), and autonomous driving (Kendall & Gal, 2017). BNNs are also known to be capable of resisting over-fitting.

However, there are fundamental obstacles posed in front of the ML practitioners when trying to pushing the limit of BNNs to larger datasets and deeper architectures: (*i*) The scalability of the existing BNNs is generally restrictive owing to the essential difficulties of learning a complex, non-degenerate distribution over parameters in a high-dim. and over-parameterized space (Liu & Wang, 2016; Louizos & Welling, 2017; Sun et al., 2019). (*ii*) The Bayes posteriors learned from scratch are frequently systematically worse than their point-estimate counterparts in terms of predictive performance (Wenzel et al., 2020). (*iii*) It is shown that the BNNs have the potential to assign low (*epistemic*) uncertainty for realistic out-of-distribution (OOD) data, e.g., adversarial examples, rendering their uncertainty estimates unreliable in safety-critical scenarios. (Grosse et al., 2018)

To solve these problems, we establish a scalable workflow, named *BayesAdapter*, to learn more reliable BNNs. In a global view, we unfold the learning of a BNN into two steps: *deterministic pre-training* of the deep neural network (DNN) counterpart of the BNN followed by several-round *Bayesian fine-tuning*. This enables us to learn a principled BNN with slightly more efforts than training a regular DNN, and provides us with the opportunities to embrace qualified off-the-shelf pre-trained DNNs (e.g., those on PyTorch Hub). The converged parameters of the deterministic model serves as a strong start point for *Bayesian fine-tuning*, allowing us to bypass extensive local optimas suffered from by the direct learning of BNN. To render the fine-tuning in the style of training normal NNs, we resort to stochastic variational inference (VI) to update the approximate posterior. We develop optimizers with built-in weight decay for the parameters of the variational to absorb the

Figure 1: The workflow of *BayesAdapter*. We assume a three-layer model for simplicity. We at first pre-train a DNN counterpart of the target BNN via *maximum a posteriori* (MAP) estimation, then transform it to be a BNN by replacing the point-estimate parameters with a diagonal Gaussian centered at them, from which the parameter samples are drawn for computation. After that, we build separate optimizers with built-in weight decay for the Gaussian mean and variance, and perform fine-tuning to fit the data under uncertainty regularization based on autodiff libraries.

regularization effects from the prior, and develop *exemplar reparametrization* to reduce the gradient variance. Moreover, to make the uncertainty estimation of the learned models reliable, we propose to additionally, explicitly regularize the model to behave uncertainly on representative foreseeable OOD data during fine-tuning. This regularization takes the form of a margin loss, and is readily applicable to most of the existing BNNs. Figure 1 depicts the whole framework of *BayesAdapter*. Extensive empirical studies validate the efficiency and effectiveness of our workflow. In summary, our contributions are as follows:

1. We propose a new, two-step framework *BayesAdapter*, composed of *deterministic pre-training* and *Bayesian fine-tuning*, to obtain practical BNNs.
2. We provide an easy-to-use instantiation of stochastic VI, which allows learning a BNN as if training a deterministic NN and frees the users from tedious details of BNN.
3. We augment the fine-tuning with a generally applicable uncertainty regularization term to rectify the predictive uncertainty according to a collection of OOD data.
4. Extensive studies validate that the workflow is scalable, that the delivered BNN models are high-quality, and that the acquired uncertainty quantification is calibrated and transferable.

2 BAYESADAPTER

In this section, we first motivate *BayesAdapter* by establishing the connection between *maximum a posteriori* (MAP) and Bayesian inference. We then describe the proposed procedure *Bayesian fine-tuning*, and a practical and robust implementation of stochastic VI to realize it. Figure 1 illustrates the overall workflow of *BayesAdapter*.

2.1 FROM DNNs TO BNNs

Suppose that we have access to a dataset $\mathcal{D} = \{(\boldsymbol{x}_i, y_i)\}_{i=1}^n$, where $\boldsymbol{x}_i \in \mathbb{R}^d$ and $y_i \in \mathcal{Y}$ denote the data and label, respectively. A DNN model can be fit via MAP following:

$$\max_{\boldsymbol{w}} \frac{1}{n} \sum_i [\log p(y_i|\boldsymbol{x}_i; \boldsymbol{w})] + \frac{1}{n} \log p(\boldsymbol{w}). \tag{1}$$

We use $\boldsymbol{w} \in \mathbb{R}^p$ to notate the high-dimensional model parameters, and $p(y|\boldsymbol{x}; \boldsymbol{w})$ as the predictive distribution associated with the model. The prior term $p(\boldsymbol{w})$, when taking the form of an isotropic Gaussian, reduces to the L2 weight decay regularizer in optimization. Despite the wide adoption, DNNs are known to be prone to over-fitting, generating over-confident predictions, and are unable to convey valuable information on the trustworthiness of their predictions. Naturally, Bayesian neural networks (BNNs) come into the picture to address these limitations.

Typically, a BNN imposes a prior $p(\boldsymbol{w})$ on model parameters, which is put together with the likelihood $p(\mathcal{D}|\boldsymbol{w})$ to infer the posterior $p(\boldsymbol{w}|\mathcal{D})$. Among the wide spectrum of BNN algorithms (MacKay, 1992; Neal, 1995; Graves, 2011; Blundell et al., 2015; Liu & Wang, 2016; Gal & Ghahramani, 2016; Louizos & Welling, 2017), variational BNNs are particularly promising due to their ease of training compared to other BNN variants. Formally, variational BNNs derive a

θ-parameterized varitional distribution $q(\boldsymbol{w}|\boldsymbol{\theta})$ to approximate the true posterior $p(\boldsymbol{w}|\mathcal{D})$, by maximizing the evidence lower bound (ELBO) (scaled by $1/n$):

$$\max_{\boldsymbol{\theta}} \underbrace{\mathbb{E}_{q(\boldsymbol{w}|\boldsymbol{\theta})}\left[\frac{1}{n}\sum_i \log p(y_i|\boldsymbol{x}_i;\boldsymbol{w})\right]}_{\mathcal{L}_{ell}} - \underbrace{\frac{1}{n}D_{\mathrm{KL}}\left(q(\boldsymbol{w}|\boldsymbol{\theta})\|p(\boldsymbol{w})\right)}_{\mathcal{L}_c}. \tag{2}$$

$\mathcal{L}_{\mathrm{ell}}$ refers to the *expected log-likelihood* and $\mathcal{L}_c$ refers to the *complexity loss*. By casting posterior inference into optimization, Eq. (2) makes the training of BNNs more approachable. However, most existing BNNs[1] trained under such a criterion exhibit limitations in scalability and performance (Osawa et al., 2019a; Wenzel et al., 2020) compared to their deterministic counterparts, mainly attributed to the difficult nature of learning high-dimensional distributions than point estimates, and challenges in finding non-degenerated optima of highly nonlinear functions characterized by NNs.

Given that MAP converges to the mode of the Bayesian posterior, it might be plausible to adapt pre-trained deterministic DNNs to be Bayesian economically. Following this hypothesis, we propose to repurpose the converged parameters $\boldsymbol{w}^*$ of MAP, and use it to instantiate $q(\boldsymbol{w}|\boldsymbol{\theta})$ as a Gaussian $\mathcal{N}(\boldsymbol{w};\boldsymbol{\theta})$ with $\boldsymbol{\theta} = (\boldsymbol{\mu}, \boldsymbol{\Sigma})$, where $\boldsymbol{\mu}$ is initialized as $\boldsymbol{w}^*$ and $\boldsymbol{\Sigma} \in \mathbb{R}^{p \times p}$ denotes the covariance. Then, we arrive at a BNN with *posterior predictive*:

$$p(y|\boldsymbol{x}, \mathcal{D}) = \mathbb{E}_{\mathcal{N}(\boldsymbol{w};\boldsymbol{\mu},\boldsymbol{\Sigma})} p(y|\boldsymbol{x};\boldsymbol{w}) \approx \frac{1}{S}\sum_{s=1}^{S} p(y|\boldsymbol{x};\boldsymbol{w}^{(s)}), \text{where } \boldsymbol{w}^{(s)} \sim \mathcal{N}(\boldsymbol{w};\boldsymbol{\mu},\boldsymbol{\Sigma}), s = 1, ..., S. \tag{3}$$

Eq. (3) is also called *Bayes ensemble*, where $\boldsymbol{\mu}$ is perturbed, and the predictions from multiple likely models are assembled. $\boldsymbol{\Sigma}$ controls the magnitude of perturbation. A classic method to generate an informative $\boldsymbol{\Sigma}$ is by Laplace approximation (Bleistein & Handelsman, 1986), but it is more like a postprocessing procedure, lacking the flexibility to jointly adapt the mean and covariance of the Gaussian posterior w.r.t. data, and its naive implementation without strong assumptions may be computationally prohibitive. Instead, we suggest a more practical workflow – that fine-tunes the approximate posterior $\mathcal{N}(\boldsymbol{w};\boldsymbol{\mu},\boldsymbol{\Sigma})$ by maximizing the ELBO with randomly initialized $\boldsymbol{\Sigma}$.

2.2 BAYESIAN FINE-TUNING IN THE STYLE OF FINE-TUNING DNNS

We develop practical learning algorithms under the stochastic VI scheme to fine-tune the imperfect variational posterior, and to cope with contemporary ML frameworks. In the following, we discuss how to deal with each term in Eq. (2). Algorithm 1 gives an overview of *BayesAdapter*.

Complexity loss $\mathcal{L}_c$. Without losing generality, we assume an isotropic Gaussian prior $p(\boldsymbol{w}) = \mathcal{N}(\boldsymbol{w}; \boldsymbol{0}, \sigma_0^2 \mathbf{I})$. Then the complexity loss is derived as:

$$\mathcal{L}_c = -\frac{1}{n}D_{\mathrm{KL}}\left(\mathcal{N}(\boldsymbol{w};\boldsymbol{\mu},\boldsymbol{\Sigma})\|\mathcal{N}(\boldsymbol{w};\boldsymbol{0},\sigma_0^2\mathbf{I})\right) = -\frac{\boldsymbol{\mu}^T\boldsymbol{\mu} + \mathrm{tr}(\boldsymbol{\Sigma})}{2\sigma_0^2 n} + \frac{\log\det\boldsymbol{\Sigma}}{2n} + c, \tag{4}$$

where $\mathtt{tr}$ and $\mathtt{det}$ are matrix trace and determinant, respectively. c is a constant. The gradients of $\mathcal{L}_c$ w.r.t. $\boldsymbol{\mu}$ and $\boldsymbol{\Sigma}$ can be estimated precisely as:

$$\nabla_{\boldsymbol{\mu}}\mathcal{L}_c = -\frac{\boldsymbol{\mu}}{\sigma_0^2 n}, \nabla_{\boldsymbol{\Sigma}}\mathcal{L}_c = \frac{\sigma_0^2\boldsymbol{\Sigma}^{-1} - \mathbf{I}}{2\sigma_0^2 n}. \tag{5}$$

Eq. (5) indicates that $\max_{\boldsymbol{\mu}} \mathcal{L}_c$ amounts to applying a weight decay regularizer with coefficient $\lambda = \frac{1}{\sigma_0^2 n}$ on $\boldsymbol{\mu}$, which can be conveniently optimized by leveraging the built-in weight decay modules in ML frameworks such as TensorFlow (Abadi et al., 2016) or PyTorch (Paszke et al., 2019).

Directly computing $\nabla_{\boldsymbol{\Sigma}}\mathcal{L}_c$ involves matrix inversion. Implementing the posterior as matrix-variate Gaussian is an alternative, while existing algorithms for matrix-variate Gaussian posterior typically exhibit heavy complexity in time or memory, limited compatibility with contemporary NN building block operations (e.g., convolution), and struggle to scale with data-parallel distributed training (Louizos & Welling, 2016; Sun et al., 2017; Osawa et al., 2019b). To simplify the implementation and boost scalability, we assume a fully factorized Gaussian variational by devising $\boldsymbol{\Sigma}$ as $\mathbf{diag}(\exp(2\boldsymbol{\psi}))$, where $\boldsymbol{\psi} \in \mathbb{R}^p$ is the parameter to be optimized along with $\boldsymbol{\mu}$ (i.e., $\boldsymbol{\theta} = (\boldsymbol{\mu}, \boldsymbol{\psi})$). Injecting this into Eq. (5) gets a more concise gradient estimator: $\nabla_{\boldsymbol{\psi}}\mathcal{L}_c = \mathbf{1}/n - \lambda\exp(2\boldsymbol{\psi})$, meaning that $\max_{\boldsymbol{\psi}} \mathcal{L}_c$ adds an exponential weight decay of $\boldsymbol{\psi}$ with coefficient λ, which can be realized by modifying only two lines of code on top of de facto DL frameworks (see Figure 1).

---

[1]We use BNNs equivalently with variational BNNs in the following text when there is no ambiguity.

Algorithm 1: BayesAdapter

Input: normal training set $\mathcal{D}$ in the size of n, OOD training set $\mathcal{D}^\dagger$, weight decay coefficient λ for both the pre-training and the fine-tuning, threshold γ, learning rates $lr_{\boldsymbol{\mu}}$, $lr_{\boldsymbol{\psi}}$, fine-tuning epochs T

1 Pre-train the DNN counterpart of the target BNN on $\mathcal{D}$ by MAP; denote the converged parameters as $\boldsymbol{\mu}$
2 Create randomly initialized parameters $\boldsymbol{\psi}$; make the computation modules be Bayesian (see Figure 2)
3 Build optimizers $\text{opt}_{\boldsymbol{\mu}}$ and $\text{opt}_{\boldsymbol{\psi}}$ (see Figure 1) with learning rate $lr_{\boldsymbol{\mu}}$ and $lr_{\boldsymbol{\psi}}$ for $\boldsymbol{\mu}$ and $\boldsymbol{\psi}$ respectively
4 **for** *epoch = 1, 2, ..., T* **do**
5   **for** *mini-batch $\mathcal{B} = \{(\boldsymbol{x}_i, y_i)\}_{i=1}^{|\mathcal{B}|}$ in $\mathcal{D}$, mini-batch $\mathcal{B}^\dagger = \{\boldsymbol{x}_i^\dagger\}_{i=1}^{|\mathcal{B}^\dagger|}$ in $\mathcal{D}^\dagger$* **do**
6   Build the whole mini-batch $\{\boldsymbol{x}_1, ..., \boldsymbol{x}_\mathcal{B}, \boldsymbol{x}_1^\dagger, ..., \boldsymbol{x}_{|\mathcal{B}^\dagger|}^\dagger, \boldsymbol{x}_1^\dagger, ..., \boldsymbol{x}_{|\mathcal{B}^\dagger|}^\dagger\}$, and feed it into the model
7   Given the predictive distribution and labels $\{y_i\}_{i=1}^{|\mathcal{B}|}$, compute $\mathcal{L}_{ell}^*$ and $\mathcal{L}_{\text{unc}}$
8   Derive the gradients of $\mathcal{L}_{ell}^* + \mathcal{L}_{\text{unc}}$ w.r.t. $\boldsymbol{\mu}$ and $\boldsymbol{\psi}$ via AutoGrad
9   Update the parameters $\boldsymbol{\mu}$ and $\boldsymbol{\psi}$ with optimizers $\text{opt}_{\boldsymbol{\mu}}$ and $\text{opt}_{\boldsymbol{\psi}}$

Expected log-likelihood $\mathcal{L}_{\text{ell}}$. With the complexity loss expressed as weight decay, we now develop efficient ways for calculating the $\mathcal{L}_{\text{ell}}$ at the end of forward pass, and for performing backpropagation afterwards. In particular, we derive a Monte Carlo (MC) estimation of $\mathcal{L}_{ell}$ based on reparameterization (Kingma & Welling, 2013): we sample a p-dimensional Gaussian noise $\boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$, then obtain the sampled parameter for the whole mini-batch $\mathcal{B}$ of data via $\boldsymbol{w} = \boldsymbol{\mu} + \exp(\boldsymbol{\psi})\boldsymbol{\epsilon}$, given which we approximate $\mathcal{L}_{ell}$ with $\mathcal{L}_{ell}' = \frac{1}{|\mathcal{B}|} \sum_{(\boldsymbol{x}_i, y_i) \in \mathcal{B}} \log p(y_i | \boldsymbol{x}_i; \boldsymbol{w})$. The gradients of $\boldsymbol{\mu}$ and $\boldsymbol{\psi}$ can be derived automatically with autodiff libraries, thus the training resembles that of normal DNNs.

However, gradients derived by $\mathcal{L}_{ell}'$ might exhibit high variance, caused by sharing one set of sampled parameters $\boldsymbol{w}$ across all the training instances in $\mathcal{B}$. *Local reparameterization* is proposed to reduce the variance, but it requires at least 2x forward-backward FLOPS than vanilla reparameterization (refer to Kingma et al. (2015) for more details). To mitigate these issues, we propose *exemplar reparametrization* (ER) which samples a separate set of parameter for every exemplar in the minibatch. Formally, for $\forall \boldsymbol{x}_i \in \mathcal{B}$, we draw $\boldsymbol{w}^{(i)} = \boldsymbol{\mu} + \exp(\boldsymbol{\psi})\boldsymbol{\epsilon}^{(i)}$ where $\boldsymbol{\epsilon}^{(i)} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$, and approximate the *expected log-likelihood* by $\mathcal{L}_{ell}^* = \frac{1}{|\mathcal{B}|} \sum_{(\boldsymbol{x}_i, y_i) \in \mathcal{B}} \log p(y_i | \boldsymbol{x}_i; \boldsymbol{w}^{(i)}), i = 1, ..., |\mathcal{B}|$.

We emphasize that, while this approach generates more parameters at training, they are mostly temporary, and the resultant computational FLOPS are provably identical to that of the vanilla reparameterization. The challenge of ER is to cope with nowadays ML frameworks and maintaining computing efficiency, because off-the-shelf computation kernels in autodiff libraries typically assume a batch of instances share a common set of parameters. We present an example in Figure 2 on how the standard `convolution` op can be converted into

```python
# assume shape x: [b, i, h, w]; w, mu, psi: [o, i, k, k]
def DNN_conv(x, w, stride, padding, groups):
    return conv2d(x, w, stride, padding, groups)

def BayesAdapter_conv(x, mu, psi, stride, padding, groups):
    b = x.shape[0]
    # sample a batch of parameters w: [b, o, i, k, k]
    w = mu + exp(psi) * randn(b, *list(mu.shape))
    # reshape w to have shape [b*o, i, k, k]
    w = w.flatten(start_dim=0, end_dim=1)
    # reshape x to have shape [1, b*i, h, w]
    x = x.flatten(start_dim=0, end_dim=1).unsqueeze(0)
    # perform b convs in parallel
    y = conv2d(x, w, stride, padding, groups*b)
    # reshape the result to standard format
    return y.view(b, mu.shape[0], y.shape[2], y.shape[3])
```

Figure 2: The comparison between standard convolution and convolution used in *BayesAdapter*.

its exemplar version without compromising computational efficiency. The key insight here is that multiple exemplar convolutions can be expressed as a group convolution, which can be performed in parallel using a single group convolution kernel, leveraging the optimized implementations provided by various device-propriety kernel backends (e.g. cuDNN (Chetlur et al., 2014)). Other common operators such as matrix multiplication are straightforward to handle (refer to Appendix A).

With this insight, *BayesAdapter* enables to obtain a BNN with only minor computational cost in addition to pre-training, and can immediately benefit from the availability of higher-performance computational kernels (e.g., more powerful group convolution kernel).

3   CALIBRATE THE UNCERTAINTY ESTIMATION

So far we have developed an inexpensive fine-tuning procedure to obtain BNNs from deterministic NNs. While BNNs can offer uncertainty estimates, these uncertainty measures are highly non-smooth due to the non-convexity of NNs – they might exhibit high uncertainty for data from faraway out-of-distribution (OOD) regions, but become vulnerable on OOD samples close to the normal ones (Grosse et al., 2018), rendering BNNs unable to react to potentially harmful inputs. We quantify

this phenomenon in Section 4.2. To address this problem, we next develop methods to further calibrate the uncertainty estimation of naively trained BNNs. Inspired by recent work on OOD detection (Wang et al., 2020; Durall et al., 2020), we propose to additionally incorporate uncertainty regularization on top of the above fine-tuning procedure. The idea is to force BNNs to generate inconsistent predictions for each sample from a cheaply collected OOD sample set, so that they acquire the ability to yield high uncertainty for OOD samples with similar fingerprints.

To achieve this, we start by defining a differentiable uncertainty metric in terms of mutual information, following Smith & Gal (2018):

$$\mathcal{I}(\boldsymbol{w}, y|\boldsymbol{x}, \mathcal{D}) \approx H\left(\frac{1}{S}\sum_{s=1}^{S} p(y|\boldsymbol{x}; \boldsymbol{w}^{(s)})\right) - \frac{1}{S}\sum_{s=1}^{S} H\left(p(y|\boldsymbol{x}; \boldsymbol{w}^{(s)})\right), \text{where } \boldsymbol{w}^{(s)} \sim \mathcal{N}(\boldsymbol{w}; \boldsymbol{\mu}, \boldsymbol{\psi}), s = 1, ..., S, \quad (6)$$

where H is the Shannon entropy. $\mathcal{I}$ highly correlates with softmax variance (Smith & Gal, 2018), and measures the *epistemic uncertainty* which describes uncertainty in the model and can be used to identify OOD instances. Then, assuming access to an OOD dataset $\mathcal{D}^\dagger = \{\boldsymbol{x}_i^\dagger\}_{i=1}^{n^\dagger}$, we enforce the model to behave uncertainly on each of them by optimizing a margin loss with threshold γ:

$$\max_\theta \mathcal{L}_{\text{unc}} = \frac{1}{|\mathcal{B}^\dagger|}\sum_{\boldsymbol{x}_i^\dagger \in \mathcal{B}^\dagger} \min\left(\mathcal{I}(\boldsymbol{w}, y|\boldsymbol{x}_i^\dagger, \mathcal{D}), \gamma\right), \quad (7)$$

where $\mathcal{B}^\dagger$ refers to a mini-batch of OOD data. For efficiency, we adopt $S = 2$ MC samples for estimating $\mathcal{I}(\boldsymbol{w}, y|\boldsymbol{x}_i^\dagger, \mathcal{D})$ in Eq. (7) in the training. While this loss has a seemingly opposite form from the consistency-promoting loss in semi-supervised learning (SSL) (Laine & Aila, 2016), they share the same design philosophy: $\mathcal{L}_{\text{unc}}$ maximizes the prediction inconsistency of OOD instances so as to distinguish them from in-distribution instances, while SSL minimizes the prediction inconsistency of unlabeled data so to classify them without labels. Put it in the context of autonomous driving: if the model is trained on data only containing scenes in regular weather, we can take a small set of scene data of extreme weather, e.g., tornado and sandstorm, to regularize the training following Eq. (7). Then the model will learn to identify these abnormal scenes based on predictive uncertainty, thus can reject to make unreliable decisions in these scenes.

Constructing the OOD dataset $\mathcal{D}^\dagger$ is flexible and application-specific. In discriminative tasks, two types of OOD data of particular concerns are adversarial and fake samples, which can be both collected trivially following procedures described below.

Adversarial samples. Directly generating adversary samples following methods like PGD (Madry et al., 2017) might be expensive. We propose a more cost-effective alternative based on a key observation: given a valid perturbation space $[-\delta_m, \delta_m]^d$ where δ_m is the maximum norm under the l_∞ threat model, we can see that uniform noises $\boldsymbol{\delta} \sim \mathcal{U}(-\delta_m, \delta_m)^d$ radically encompass the adversarial perturbations which usually reside at local optimas. Thus we can add uniformly perturbed samples into uncertainty training to direct the model to behave uncertainly on randomly contaminated data, bypassing the potential cost of generating real adversary samples. The results in Sec 4.2 surprisingly confirm the effectiveness of uniform noise, and imply a strong connection between uniform noise and adversarial one, which deserves a future investigation.

Fake samples. Fake samples can be obtained by utilizing pretrained state-of-the-art GANs (Miyato et al., 2018; Brock et al., 2018), DeepFake (Deepfakes, 2018), and FaceSwap (Faceswap, 2018). We use only 1000 random fake samples for *Bayesian fine-tuning* on diverse benchmarks.

For both, we empirically find the proposed uncertainty regularization is *data efficient* – with only access to a proxy set of adversarial samples and a small set of fake samples, the model can acquire reliable, transferable uncertainty quantification.

4 EXPERIMENTS

Settings We first conduct experiments on CIFAR-10 (Krizhevsky et al., 2009) and ImageNet (Deng et al., 2009) using wide-ResNet-28-10 (Zagoruyko & Komodakis, 2016) and ResNet-50 (He et al., 2016a), respectively. Besides, we train face recognition models on CASIA (Yi et al., 2014) with MobileNetV2 (Sandler et al., 2018), and perform comprehensive evaluation on face verification datasets including LFW (Huang et al., 2008), CPLFW (Zheng & Deng, 2018), CALFW (Zheng et al., 2017), CFP (Sengupta et al., 2016), VGGFace2 (Cao et al., 2018), and AgeDB-30 (Moschoglou et al., 2017). We pre-train DNNs following standard protocols, and perform *Bayesian fine-tuning* for 40, 12, and 16 epochs with weight decay coefficients (i.e., λ) 2e-4, 1e-4, and 5e-4 on these benchmarks

Table 1: Predictive performance comparison on image classification. NLL denotes the negative log-likelihood.

Method	CIFAR-10 (wide-ResNet-28-10)		ImageNet (ResNet-50)		
	TOP1 (%) ↑	NLL ↓	TOP1 (%) ↑	TOP5 (%) ↑	NLL ↓
MAP	96.92	0.1312	76.13	92.86	0.9618
Laplace Approx.	96.41	0.1204	75.89	92.70	0.9739
MC dropout	96.95	0.1151	74.88	92.32	0.9884
SWAG	96.32	0.1122	-	-	-
BNN	97.02	0.0975	75.97	92.95	0.9435
BayesAdapter-	**97.09**	**0.0945**	**76.49**	**93.10**	**0.9337**
BayesAdapter	96.82	0.1004	76.26	92.96	0.9428

Table 2: Accuracy ↑ comparison on open-set face recognition with MobileNetV2 architecture.

Method	LFW	CPLFW	CALFW	CFP-FF	CFP-FP	VGGFace2	AgeDB-30
MAP	98.2%	84.0%	**87.6%**	97.8%	92.7%	91.7%	85.3%
MC dropout	98.2%	83.6%	87.3%	97.8%	92.8%	**92.6%**	**86.0%**
BNN	97.8%	82.4%	85.7%	96.8%	91.4%	90.5%	83.8%
BayesAdapter-	98.4%	**84.4%**	87.3%	97.7%	92.7%	92.3%	85.1%
BayesAdapter	**98.5%**	84.1%	87.4%	**97.9%**	**93.1%**	92.5%	84.8%

respectively. We set threshold $\gamma = 0.75$, initialize ψ uniformly from $[-6, -5]^p$, and use 20-step PGD as validation adversaries. On the three benchmarks, the perturbation budgets δ_m are set 0.031, 16/255, and 16/255, and the fake samples are obtained from SNGAN (Miyato et al., 2018), Big-GAN (Brock et al., 2018), and DeepFake. We perform intensive data augmentation for fake training data with a random strategy including Gaussian blur, JPEG compression, *etc.* We defer more details to Appendix B. We conduct per experiment for 3 times on 8 RTX 2080-Tis and report the average.

Baselines We consider extensive baselines including *MAP*, *Laplace Approximation* with diagonal Fisher information matrix, *MC dropout* which is detailed in Appendix B, *BNN* which is trained from scratch by solving Eq. (2) without uncertainty regularization, and *BayesAdapter-* which is fine-tuned without uncertainty regularization. They are fairly trained as *BayesAdapter*. Another baseline is *SWAG* (Maddox et al., 2019), whose performance is not worse than SGLD (Welling & Teh, 2011), KFAC Laplace (Ritter et al., 2018), and temperature scaling (Guo et al., 2017). We take the results of *SWAG* from its paper due to implementation difficulties.

Metrics We concern (*i*) the *posterior predictive* performance with $S = 100$ MC samples; (*ii*) the average precision (AP) of directly using the uncertainty estimated by Eq. (6) ($S = 20$) to distinguish OOD test samples (labeled 1) from normal test samples (labeled 0). Eq. (6) of the deterministic baseline *MAP* is 0, so we take the predictive entropy as an alternative uncertainty measure for *MAP*.

4.1 PREDICTIVE PERFORMANCE

We report the evaluation of prediction performance, which is of central importance in practice, of *BayesAdapter* as well as the elobrated baselines in Table 1 and 2. As shown, *BayesAdapter-* notably outperforms the *MAP*, especially in aspect of NLL, which reflects the modeling superiority of Bayesian formulation and highlights the practical value of our workflow. *Laplace Approximation* is consistently worse than *MAP*. In all settings, *BNN* is significantly defeated by *BayesAdapter-*, confirming our claim that performing *Bayesian fine-tuning* from the converged deterministic checkpoints is beneficial to bypass the local optimas potentially encountered by direct Bayesian inference. The popular baselines *MC dropout* and *SWAG* exhibit evidently weaker performance on ImageNet and CIFAR-10, respectively, revealing their limited applicability to various data/architectures or strong requirement for intensive hyper-parameter tuning. Also of note that these is no method gaining imperium on face recognition, which perhaps stems from the diversity of these validation sets.

Across these tasks, *BayesAdapter* is slightly less competitive than its regularization-free counterpart *BayesAdapter-*. This is reasonable since such a regularization enforces the model to sacrifice partial capacity to guarantee the fidelity of uncertainty estimates. Nevertheless, *BayesAdapter* is substantially superior to its fine-tuning start point *MAP* and the from-scratch baseline *BNN* in most of the evaluation settings. To interpret the speedup of *BayesAdapter* over *BNN*, assuming deterministic ResNet-50 takes time t for one epoch of training on ImageNet, it is observed that Bayesian ResNet-50 takes around $2.1t$ for one epoch. Then, the *BNN* baseline from scratch will consume $189t$ for 90-epoch training, while *BayesAdapter-* need $t * 90 + 2.1t * 12 = 115.2t$, saving $73.8t$ (around **40%**) training time than *BNN*. In fact, *BayesAdapter* would be a little slower than *BayesAdapter-* due to the traversal over OOD training set, but still much more time-saving than *BNN*.

(a) *BayesAdapter*, CIFAR-10   **(b)** *BayesAdapter-*, CIFAR-10   **(c)** *BayesAdapter*, ImageNet   **(d)** *BayesAdapter-*, ImageNet

Figure 3: The histograms for the mutual information uncertainty of normal data and OOD data given by models trained w/ and w/o uncertainty regularization.

Table 3: Comparison on the quality of uncertainty estimates in terms of average precision (AP) ↑ of uncertainty based binary classification. (CIFAR-10 and ImageNet)

Method	CIFAR-10		ImageNet	
	Adversarial (PGD)	Fake (SNGAN)	Adversarial (PGD)	Fake (BigGAN)
MAP	0.307	0.800	0.308	0.010
Laplace Approx.	0.308	0.800	0.311	0.015
MC dropout	0.308	0.803	0.309	0.012
BNN	0.307	0.799	0.310	0.021
BayesAdapter-	0.307	0.806	0.387	0.013
BayesAdapter	**0.993**	**0.994**	**0.964**	**0.848**

4.2 QUALITY OF UNCERTAINTY ESTIMATES

At first, we study the effects of the proposed uncertainty regularization technique by visualizing the predictive uncertainty of *BayesAdapter* and *BayesAdapter-* on validation data in Figure 3. We can see that on both CIFAR-10 and ImageNet, *BayesAdapter* yields evidently higher uncertainty for OOD data than normal data, while *BayesAdapter-* is on the contrary, which reveals the effectiveness of the proposed uncertainty regularization in calibrating the predictive uncertainty.

Then, we quantitatively assess the quality of the predictive uncertainty of various methods by estimating AP, which reflects if *the model knows what it knows*. As stated, we take adversarial samples crafted by PGD and fake samples from GANs and DeepFake as proxies of harmful OOD data. We report the results in Table 3 and Table 5 in Appendix C. As shown, *Laplace Approximation*, *MC dropout*, *BNN*, and *BayesAdapter-* perform almost fairly bad as *MAP* across the settings, except that *MC dropout* is capable of partially detecting OOD data on face tasks[2]. These results echo our concern on the reliability of the existing BNNs' predictive uncertainty. By contrast, *BayesAdapter*, which is fine-tuned upon *MAP* for only several rounds based on low-cost supervisions, almost achieve perfect results in detecting OOD instances on CIFAR-10 and face recognition, and also detect most of the OOD instances on ImageNet (see Appendix D for some random samples).

4.3 ABLATION STUDY

Model Calibration Model calibration is another important aspect of the uncertainty estimation. Thus, we present the *Expected Calibration Error* (ECE) (Guo et al., 2017) of the studied methods on CIFAR-10 and ImageNet in Table 4. The ECE of *SWAG* on ImageNet is based on ResNet-152 (He et al., 2016b). We can see that the calibration of *BayesAdapter* is on par with the *MC dropout* and *BNN* baselines.

Table 4: Comparison on ECE ↓.

Method	CIFAR-10	ImageNet
MAP	0.0198	0.0373
Laplace Approx.	0.0106	0.0375
MC dropout	0.0119	**0.0152**
SWAG	0.0088	0.0279
BNN	**0.0055**	0.0183
BayesAdapter-	0.0094	0.0159
BayesAdapter	**0.0057**	0.0165

Transferability of uncertainty quantification One may imagine that the uncertainty quantification learned according to specialized OOD data cannot reasonably generalize to other OOD data. To figure out if this situation exists, on one hand, we evaluate the *BayesAdapter* trained on CIFAR-10 on 10000 samples from PGGAN (Karras et al., 2017) whose patterns are unseen during training. We compute their uncertainty and calculate the AP metric, obtaining **0.932**. As comparison, the APs of *MAP*, *Laplace Approx.*, *MC dropout*, *BNN*, *BayesAdapter-* on such data are 0.789, 0.800, 0.792, 0.793, 0.803 respectively. On the other hand, we craft adversarial examples by the fast gradient sign method (FGSM) (Goodfellow et al., 2014) against the ResNet-152 DNN model with 1000 validation images from ImageNet. Then we estimate the AP on these instances, and obtain 0.011, 0.125, 0.027,

---

[2]We speculate this may be related to the position of deploying dropout and leave it for future investigation.

0.202, 0.019, and **0.882** for *MAP*, *Laplace Approximation*, *MC dropout*, *BNN*, *BayesAdapter-*, and *BayesAdapter* respectively. These studies validate the transferability of our uncertainty estimation.

The effectiveness of exemplar reparameterization We build a toy model with only a Bayesian convolutional layer, fixing the model input and target output, and computing the variance of stochastic gradients across 500 runs. We average the gradient variance of μ and ψ over all their coordinates, and observe that standard reparameterization typically introduces more than $100\times$ variance than exemplar reparameterization, despite with the same FLOPS.

The impacts of ensemble number We draw the change of test accuracy w.r.t. the number of MC samples S for estimating Eq. (3) in Figure 4. The model is trained by *BayesAdapter* on ImageNet. The points on the red line represent the individual accuracies of the 100 parameter samples. The yellow dashed line refers to the deterministic inference with only the Gaussian mean. The green line displays the effects of *Bayes ensemble* – the predictive performance increases from $< 74\%$ to $> 76\%$ quickly before seeing 20 parameter samples, and gradually saturate after that. That is why we use 20 samples for estimating uncertainty and crafting adversarial samples.

Figure 4: The change of test accuracy w.r.t. the number of MC samples for estimating Eq. (3).

Uncertainty-based rejective decision In practice, we expect our models can reject to predict for data with relatively large uncertainty, and only care about the data that they are certain about. In this spirit, we sort the validation data of ImageNet w.r.t. the uncertainty provided by *BayesAdapter*, and split them into 10 buckets of equal size. We depict the average accuracy of each bucket in Figure 5. As expected, our BNN is more accurate for instances with smaller uncertainty. Quantitatively, there are 95% instances with uncertainty less than 0.45, and their accuracy is 78.6%; there are 90% instances with uncertainty less than 0.37, and their accuracy is 80.7%; there are 80% instances with uncertainty less than 0.25, and their accuracy is 84.8%.

Figure 5: Comparison on accuracy for instance buckets of equal size but with rising uncertainty.

5   RELATED WORK

Fruitful works have emerged in the BNN community in the last decade (Graves, 2011; Welling & Teh, 2011; Blundell et al., 2015; Kingma & Welling, 2013; Balan et al., 2015; Liu & Wang, 2016; Kendall & Gal, 2017). However, most of the existing works cannot achieve the goal of practicability. For example, Liu & Wang (2016); Louizos & Welling (2016; 2017); Shi et al. (2018); Sun et al. (2019) trade learning efficiency for flexible variational posteriors, leading to restrictive scalability. Khan et al.; Zhang et al.; Osawa et al. build Adam-like optimizers to do variational inference, but their parallel training throughput and compatibility with data augmentation are inferior to SGD. Empirical Bayes methods, e.g., Monte Carlo (MC) dropout (Gal & Ghahramani, 2016), deep ensemble (Lakshminarayanan et al., 2017), and SWAG (Maddox et al., 2019), usually maintain impressive predictive performance, but suffer from degenerated uncertainty estimates (Fort et al., 2019) or expensive training/storage cost. What's worse, the existing works usually evaluate on impractical OOD data (Louizos & Welling, 2017; Pawlowski et al., 2017) to show the promise of Bayesian principle. Instead, we offer a new evaluation standard in this work, which may benefit the following works.

Laplacian approximation (Bleistein & Handelsman, 1986; Ritter et al., 2018) is also known to transform a DNN to be a BNN, but it is inflexible due to its postprocessing nature and some practical but too strong assumptions. Alternatively, *BayesAdapter* works in the style of fine-tuning, which is more natural and economical for deep networks. Bayesian modeling the last layer of a DNN is proposed recently (Kristiadi et al., 2020), and its combination with *BayesAdapter* deserves an investigation.

6   CONCLUSION

In this work, we propose a scalable workflow to learn practical BNNs. Our core nation is simple but inspiring – learning a BNN model by first pre-training its DNN counterpart and then performing *Bayesian fine-tuning*. In this workflow, we develop a plug-and-play instantiation of stochastic VI, and propose advanced implementation techniques to reduce the gradient variance. We also propose a generic uncertainty regularization trick to calibrate the uncertainty quantification given low-cost supervisions. We evaluate *BayesAdapter* in diverse realistic scenarios and see good results.

REFERENCES

Martín Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, et al. Tensorflow: A system for large-scale machine learning. In *12th {USENIX} symposium on operating systems design and implementation ({OSDI} 16)*, pp. 265–283, 2016.

Anoop Korattikara Balan, Vivek Rathod, Kevin P Murphy, and Max Welling. Bayesian dark knowledge. In *Advances in Neural Information Processing Systems*, pp. 3438–3446, 2015.

Norman Bleistein and Richard A Handelsman. *Asymptotic expansions of integrals.* Courier Corporation, 1986.

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural network. In *International Conference on Machine Learning*, pp. 1613–1622, 2015.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale gan training for high fidelity natural image synthesis. *arXiv preprint arXiv:1809.11096*, 2018.

Qiong Cao, Li Shen, Weidi Xie, Omkar M Parkhi, and Andrew Zisserman. Vggface2: A dataset for recognising faces across pose and age. In *2018 13th IEEE International Conference on Automatic Face & Gesture Recognition (FG 2018)*, pp. 67–74. IEEE, 2018.

Sharan Chetlur, Cliff Woolley, Philippe Vandermersch, Jonathan Cohen, John Tran, Bryan Catanzaro, and Evan Shelhamer. cudnn: Efficient primitives for deep learning. *arXiv preprint arXiv:1410.0759*, 2014.

Deepfakes, 2018. https://github.com/deepfakes/faceswap. Accessed: 2018-10-29.

J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. ImageNet: A Large-Scale Hierarchical Image Database. In *CVPR09*, 2009.

Stefan Depeweg, José Miguel Hernández-Lobato, Finale Doshi-Velez, and Steffen Udluft. Learning and policy search in stochastic dynamical systems with Bayesian neural networks. *arXiv preprint arXiv:1605.07127*, 2016.

Ricard Durall, Margret Keuper, and Janis Keuper. Watch your up-convolution: Cnn based generative deep neural networks are failing to reproduce spectral distributions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 7890–7899, 2020.

Faceswap, 2018. https://github.com/MarekKowalski/FaceSwap. Accessed: 2018-10-29.

Stanislav Fort, Huiyi Hu, and Balaji Lakshminarayanan. Deep ensembles: A loss landscape perspective. *arXiv preprint arXiv:1912.02757*, 2019.

Yarin Gal and Zoubin Ghahramani. Dropout as a Bayesian approximation: Representing model uncertainty in deep learning. In *International Conference on Machine Learning*, pp. 1050–1059, 2016.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Alex Graves. Practical variational inference for neural networks. In *Advances in Neural Information Processing Systems*, pp. 2348–2356, 2011.

Kathrin Grosse, David Pfaff, Michael Thomas Smith, and Michael Backes. The limitations of model uncertainty in adversarial settings. *arXiv preprint arXiv:1812.02606*, 2018.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. *arXiv preprint arXiv:1706.04599*, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 770–778, 2016a.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks. In *European Conference on Computer Vision*, pp. 630–645, 2016b.

José Miguel Hernández-Lobato and Ryan Adams. Probabilistic backpropagation for scalable learning of Bayesian neural networks. In *International Conference on Machine Learning*, pp. 1861–1869, 2015.

Gary B Huang, Marwan Mattar, Tamara Berg, and Eric Learned-Miller. Labeled faces in the wild: A database forstudying face recognition in unconstrained environments. 2008.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. *arXiv preprint arXiv:1502.03167*, 2015.

Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of gans for improved quality, stability, and variation. *arXiv preprint arXiv:1710.10196*, 2017.

Alex Kendall and Yarin Gal. What uncertainties do we need in Bayesian deep learning for computer vision? In *Advances in Neural Information Processing Systems*, pp. 5574–5584, 2017.

Mohammad Emtiyaz Khan, Didrik Nielsen, Voot Tangkaratt, Wu Lin, Yarin Gal, and Akash Srivastava. Fast and scalable Bayesian deep learning by weight-perturbation in adam. In *International Conference on Machine Learning*, pp. 2616–2625, 2018.

Diederik P Kingma and Max Welling. Auto-encoding variational Bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Durk P Kingma, Tim Salimans, and Max Welling. Variational dropout and the local reparameterization trick. In *Advances in Neural Information Processing Systems*, pp. 2575–2583, 2015.

Agustinus Kristiadi, Matthias Hein, and Philipp Hennig. Being bayesian, even just a bit, fixes overconfidence in relu networks. *arXiv preprint arXiv:2002.10118*, 2020.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Samuli Laine and Timo Aila. Temporal ensembling for semi-supervised learning. *arXiv preprint arXiv:1610.02242*, 2016.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in Neural Information Processing Systems*, pp. 6402–6413, 2017.

Christian Leibig, Vaneeda Allken, Murat Seçkin Ayhan, Philipp Berens, and Siegfried Wahl. Leveraging uncertainty information from deep neural networks for disease detection. *Scientific Reports*, 7(1):1–14, 2017.

Qiang Liu and Dilin Wang. Stein variational gradient descent: A general purpose Bayesian inference algorithm. In *Advances in Neural Information Processing Systems*, pp. 2378–2386, 2016.

Christos Louizos and Max Welling. Structured and efficient variational deep learning with matrix gaussian posteriors. In *International Conference on Machine Learning*, pp. 1708–1716, 2016.

Christos Louizos and Max Welling. Multiplicative normalizing flows for variational Bayesian neural networks. In *International Conference on Machine Learning*, pp. 2218–2227, 2017.

David JC MacKay. A practical Bayesian framework for backpropagation networks. *Neural Computation*, 4(3):448–472, 1992.

Wesley J Maddox, Pavel Izmailov, Timur Garipov, Dmitry P Vetrov, and Andrew Gordon Wilson. A simple baseline for bayesian uncertainty in deep learning. In *Advances in Neural Information Processing Systems*, pp. 13153–13164, 2019.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. *arXiv preprint arXiv:1802.05957*, 2018.

Stylianos Moschoglou, Athanasios Papaioannou, Christos Sagonas, Jiankang Deng, Irene Kotsia, and Stefanos Zafeiriou. Agedb: the first manually collected, in-the-wild age database. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pp. 51–59, 2017.

Radford M Neal. *Bayesian Learning for Neural Networks*. PhD thesis, University of Toronto, 1995.

Kazuki Osawa, Siddharth Swaroop, Anirudh Jain, Runa Eschenhagen, Richard E Turner, Rio Yokota, and Mohammad Emtiyaz Khan. Practical deep learning with Bayesian principles. *arXiv preprint arXiv:1906.02506*, 2019a.

Kazuki Osawa, Yohei Tsuji, Yuichiro Ueno, Akira Naruse, Rio Yokota, and Satoshi Matsuoka. Large-scale distributed second-order optimization using kronecker-factored approximate curvature for deep convolutional neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 12359–12367, 2019b.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. In *Advances in neural information processing systems*, pp. 8026–8037, 2019.

Nick Pawlowski, Andrew Brock, Matthew CH Lee, Martin Rajchl, and Ben Glocker. Implicit weight uncertainty in neural networks. *arXiv preprint arXiv:1711.01297*, 2017.

Hippolyt Ritter, Aleksandar Botev, and David Barber. A scalable laplace approximation for neural networks. In *6th International Conference on Learning Representations, ICLR 2018-Conference Track Proceedings*, volume 6. International Conference on Representation Learning, 2018.

Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4510–4520, 2018.

Soumyadip Sengupta, Jun-Cheng Chen, Carlos Castillo, Vishal M Patel, Rama Chellappa, and David W Jacobs. Frontal to profile face verification in the wild. In *2016 IEEE Winter Conference on Applications of Computer Vision (WACV)*, pp. 1–9. IEEE, 2016.

Jiaxin Shi, Shengyang Sun, and Jun Zhu. Kernel implicit variational inference. In *International Conference on Learning Representations*, 2018.

Lewis Smith and Yarin Gal. Understanding measures of uncertainty for adversarial example detection. *arXiv preprint arXiv:1803.08533*, 2018.

Shengyang Sun, Changyou Chen, and Lawrence Carin. Learning structured weight uncertainty in Bayesian neural networks. In *International Conference on Artificial Intelligence and Statistics*, pp. 1283–1292, 2017.

Shengyang Sun, Guodong Zhang, Jiaxin Shi, and Roger Grosse. Functional variational Bayesian neural networks. In *International Conference on Learning Representations*, 2019.

Justus Thies, Michael Zollhofer, Marc Stamminger, Christian Theobalt, and Matthias Niebner. Face2face: Real-time face capture and reenactment of rgb videos. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2387–2395, 2016.

Sheng-Yu Wang, Oliver Wang, Richard Zhang, Andrew Owens, and Alexei A Efros. Cnn-generated images are surprisingly easy to spot... for now. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, volume 7, 2020.

Max Welling and Yee W Teh. Bayesian learning via stochastic gradient langevin dynamics. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pp. 681–688, 2011.

Florian Wenzel, Kevin Roth, Bastiaan S Veeling, Jakub Swiatkowski, Linh Tran, Stephan Mandt, Jasper Snoek, Tim Salimans, Rodolphe Jenatton, and Sebastian Nowozin. How good is the bayes posterior in deep neural networks really? *arXiv preprint arXiv:2002.02405*, 2020.

Dong Yi, Zhen Lei, Shengcai Liao, and Stan Z Li. Learning face representation from scratch. *arXiv preprint arXiv:1411.7923*, 2014.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

Guodong Zhang, Shengyang Sun, David Duvenaud, and Roger Grosse. Noisy natural gradient as variational inference. In *International Conference on Machine Learning*, pp. 5847–5856, 2018.

Tianyue Zheng and Weihong Deng. Cross-pose lfw: A database for studying cross-pose face recognition in unconstrained environments. *Beijing University of Posts and Telecommunications, Tech. Rep*, 5, 2018.

Tianyue Zheng, Weihong Deng, and Jiani Hu. Cross-age lfw: A database for studying cross-age face recognition in unconstrained environments. *arXiv preprint arXiv:1708.08197*, 2017.

A   THE EXEMPLAR VERSION OF POPULAR OPERATORS

As introduced in Sec 2.2, the regular convolution can be elegantly converted into an exemplar version by resorting to group convolution. The other popular operators are relatively easy to handle. For example, we substitute the qualified batch matrix multiplication, which is highly optimized in the well-known autodiff libraries, for matrix multiplication. For the affine transformation in batch normalization (Ioffe & Szegedy, 2015), we can at first sample dedicated affine weight and bias for every exemplar in the batch, then perform transformation with these two batches of parameters by just not *broadcasting* on the batch dimension.

B   MORE EXPERIMENTAL DETAILS

We set lr_ψ to decay at 1/4, 1/2, and 3/4 of the total fine-tuning steps from 0.1, and set lr_μ to be the final value of lr_ψ on the CIFAR-10, ImageNet, and face recognition benchmarks. For models on face recognition, we utilize the features before the last FC layer of the MobileNetV2 architecture to conduct feature distance-based face classification in the validation phase, due to the open-set nature of the validation data. The *Bayes ensemble* is similarly achieved by assembling features from multiple runs as the final feature for estimating predictive performance. But we still adopt the output from the last FC layer for uncertainty estimation (i.e., calculating Eq. (6)).

The training perturbation budget is identical to the evaluation budget on CIFAR-10 and ImageNet. But we set the budget of the uniform noise used for training in face tasks to be 1/4 of the evaluation budget to make the models more sensitive to the perturbed data. We adopt PGD for generating adversarial samples in the validation phase. Concretely, we attack the *posterior predictive* objective, i.e., Eq. (3), with $S = 20$ MC samples. On CIFAR-10, we set $\delta_m = 0.031$ and perform PGD for 20 steps with step size at 0.003. On ImageNet and face recognition, we set $\delta_m = 16/255$ and perform PGD for 20 steps with step size at $1/255$.

Regarding the fake data, we craft 1000 fake samples for training and 10000 ones for evaluation with SNGAN (Miyato et al., 2018) on CIFAR-10; we craft 1000 fake samples for training and 1000 ones for evaluation with BigGAN (Brock et al., 2018) on ImageNet; we randomly sample 1000 fake samples for training and 10000 ones for evaluation from DeepFakes (Deepfakes, 2018), FaceSwap (Faceswap, 2018) and Face2Face (Thies et al., 2016) on face recognition.

As for the *MC dropout*, we add dropout-0.3 (0.3 denotes the dropout rate) before the second convolution in the residual blocks in wide-ResNet-28-10, dropout-0.2 after the second and the third convolutions in the bottleneck blocks in ResNet-50, and dropout-0.2 before the last fully connected (FC) layer in MobileNetV2.

C   MORE RESULTS FOR UNCERTAINTY ESTIMATION

We provide the comparison on the quality of uncertainty estimates on face recognition in Table 5. It is an immediate observation that *BayeAdapter* outperforms the extensive baselines significantly, and can detect almost all the OOD instances across the validation datasets. By contrast, *BayeAdapter-*, *MAP*, and *BNN* are similarly unsatisfactory. Surprisingly, *MC dropout* exhibits some capacity to detect adversarial instances and DeepFake ones in the face tasks. Comparing these results with those of *MC dropout* on CIFAR-10 and ImageNet, we speculate that such results may stem from the location of deploying dropout in the architecture, which deserves a future investigation.

D   VISUALIZATION OF SOME OOD DATA

We provide some random samples of the OOD data used for evaluation in Figure 6. Obviously, these samples are pretty realistic and challenging.

Table 5: Comparison on the quality of uncertainty estimates in terms of AP ↑ on face recognition tasks. The upper part is for adversarial instances and the other part is for DeepFake.

Method	LFW	CPLFW	CALFW	CFP_FF	CFP_FP	VGG2_FP	AGEDB_30
MAP	0.191	0.192	0.191	0.211	0.205	0.200	0.199
MC dropout	0.965	0.946	0.959	0.965	0.949	0.954	0.952
BNN	0.399	0.282	0.429	0.390	0.271	0.291	0.327
BayesAdapter-	0.189	0.189	0.189	0.193	0.191	0.191	0.190
BayesAdapter	**0.998**	**0.981**	**0.999**	**0.999**	**0.983**	**0.990**	**0.995**
MAP	0.389	0.456	0.375	0.394	0.454	0.519	0.437
MC dropout	0.846	0.664	0.862	0.874	0.685	0.733	0.785
BNN	0.621	0.399	0.648	0.559	0.355	0.469	0.516
BayesAdapter-	0.273	0.273	0.273	0.251	0.248	0.309	0.275
BayesAdapter	**0.998**	**0.987**	**0.999**	**0.999**	**0.986**	**0.994**	**0.996**

Figure 6: Some random samples of the OOD data used for evaluation. The first row refers to the fake samples from BigGAN on ImageNet. The second row refers to the adversarial examples generated by PGD on ImageNet. The third row refers to the fake samples from DeepFake.