HIVE: HIERARCHICAL VOLUME ENCODING FOR NEURAL IMPLICIT SURFACE RECONSTRUCTION

ABSTRACT

Neural implicit surface reconstruction has become a new trend in reconstructing a detailed 3D shape from images. In previous methods, however, the 3D scene is only encoded by the MLPs which do not have an explicit 3D structure. To better represent 3D shapes, we introduce a volume encoding to explicitly encode the spatial information. We further design hierarchical volumes to encode the scene structures in multiple scales. The high-resolution volumes capture the high-frequency geometry details since spatially varying features could be learned from different 3D points, while the low-resolution volumes enforce the spatial consistency to keep the shape smooth since adjacent locations possess the same low-resolution feature. In addition, we adopt a sparse structure to reduce the memory consumption at high-resolution volumes, and two regularization terms to enhance results smoothness. This hierarchical volume encoding could be appended to any implicit surface reconstruction method as a plug-and-play module, and can generate a smooth and clean reconstruction with more details. Superior performance is demonstrated in DTU, EPFL, and BlendedMVS datasets with significant improvement on the standard metrics. The code of our method will be made public.

1 INTRODUCTION

Surface reconstruction, or image-based modeling (Tan, 2021), from multi-view images is a heavily studied classic task in computer vision. Given multiple images from different views of an object as well as the corresponding camera parameters, this task aims to recover the accurate 3D surface of the target object. Traditional methods (Fuhrmann et al., 2014) usually solve a depth map for each input image and then fuse (Kazhdan et al., 2006) those depth images to build a complete surface model. After the arising of deep networks, many methods try to exploit the neural networks to directly learn the mapping from 2D images to 3D surfaces (Murez et al., 2020; Sun et al., 2021). These learning-based methods skip the intermediate depth map estimation and are highly efficient even on unseen objects and scenes. But they usually only recover coarse scale geometry and miss most of the high frequency surface details.

Recently, many methods (Yariv et al., 2020; Wang et al., 2021; Yariv et al., 2021; Darmon et al., 2022) have achieved highly accurate reconstruction results based on neural implicit surface. These methods represent the 3D shape with an implicit function, such as occupancy (Oechsle et al., 2021)

Image	NeuS	NeuS+Ours

Figure 1: Visualization of normal maps to highlight our advantages in recovering shape details.

or signed distance fields (SDF) (Wang et al., 2021), and then leverage the neural radiance field (NeRF) (Mildenhall et al., 2020) to render the implicit geometry into color images. Thus, the difference between the rendered images and the input images could optimize the neural radiance field as well as the implicit geometry. Strong results have been demonstrated. However, in these methods, the 3D shape is implicitly encoded in the multi-layer perceptrons (MLPs). Although MLPs are compact and memory efficient, they do not have an explicit 3D structure, which may cause difficulties in learning and optimizing the target 3D shape as is observed in mesh and point-cloud processing (Chibane et al., 2020; Peng et al., 2020). Furthermore, it is also known (Sun et al., 2021) that compact MLPs are hard to encode all the geometry details, such that the recovered surface is prone to be over-smooth.

To address this problem, we introduce a volume encoding to facilitate an MLP to encode 3D shapes. We represent the space with a feature volume, where the feature of each voxel encodes the 3D shape information of that location. This structure could directly encode the geometry of each 3D position faithfully and unambiguously. This feature encoding is then fed into an MLP to compute the SDF of an object surface. The neural rendering process is the same as the previous method (Wang et al., 2021), where the rendering loss is leveraged to optimize both the MLP and our volume encoding. To improve the representation capability of our volume encoding, we further adopt multiple volumes of different scales. This hierarchical structure has two advantages. First, the high-resolution feature volume helps to reason high-frequency geometry details, while the low-resolution volume enforces spatial consistency to keep the shape smooth. Secondly, this hierarchical structure allows us to use low-dimensional features in the high-resolution volume, which helps to reduces memory consumption. To further reduce memory consumption, we sparsify high-resolution volumes with the preliminary surface reconstruction computed from low-resolution volumes. We only keep voxels nearby the surface of the preliminary results. Finally, we design two smoothness terms to facilitate the optimization to make the reconstructed shape clean.

In the experiments, we demonstrate that by simply adding the proposed hierarchical volume encoding, the performance of different methods are all improved significantly. Specifically, the error of NeuS (Wang et al., 2021) is reduced by 25% from 0.84 mm to 0.63 mm, the error of VolSDF (Yariv et al., 2021) is reduced by 23% from 0.86 mm to 0.66 mm, and the error of NeuralWarp (Darmon et al., 2022) is reduced by 10% from 0.68 mm to 0.61 mm on the DTU (Jensen et al., 2014) dataset. More than that, the error of NeuralWarp is reduced by 31% on the EPFL (Strecha et al., 2008) dataset with the "full" metric. Figure 1 shows an example from the DTU dataset. The color coded normal map clearly demonstrates our method can significantly boost NeuS (Wang et al., 2021) to recover more geometry details while keeping the surface smooth and clean.

The main contributions of this work are summarized in the following:

• We propose a hierarchical volume encoding, which can significantly boost the performance of neural implicit surface reconstruction as a plug-and-play module.

• The hierarchical volume encoding is further improved by employing a sparse structure which reduces the memory consumption, and by enforcing two regularization terms that keep the reconstructed surface smooth and clean.

• We demonstrate superior performance in three datasets.

2 RELATED WORK

Traditional multi-view surface reconstruction Traditional methods typically follow a long pipeline of structure-from-motion (i.e. camera calibration) (Schönberger & Frahm, 2016), depth map estimation (Barnes et al., 2009), and multi-depth fusion (Kazhdan et al., 2006) to reconstruct surface models from images. Many advanced geometric methods (Jiang et al., 2013; Lhuillier & Quan, 2005; Furukawa & Ponce, 2009; Galliani et al., 2015; Schönberger et al., 2016) have been developed to enhance these different steps in the last two decades.

After the arising of the deep networks, almost all steps in the conventional pipeline have been revolutionized, including feature extraction and matching (DeTone et al., 2018; Sarlin et al., 2020; Tang et al., 2022), structure-from-motion (Ummenhofer et al., 2017; Tang & Tan, 2019), and depth map estimation (Yao et al., 2018; Gu et al., 2020).

Figure 2: Method overview. In the first stage, we compute an initial result use features from volumes with resolution from 2 to 256. In a later stage, we finalize the result use features from sparsified high resolution volumes with a resolution of 512 or 1024.

To skip the intermediate depth map estimation, given multiple images with known camera poses, some methods try to directly regress a volumetric prediction end-to-end like an occupancy volume (Ji et al., 2017) or a TSDF volume (Murez et al., 2020; Sun et al., 2021). While these methods simplify the overall pipeline and can be generalized to unseen objects and scenes, they often only learn to recover coarse scale geometry and miss many surface details.

Implicit surface reconstruction A neural radiance field (NeRF) encodes a 3D scene (Mildenhall et al., 2020) implicitly in a neural network. The network is optimized to match the rendered images to the input images such that it can generate high quality novel view synthesis results. However, since there is no constraint imposed on the 3D geometry, the surface extracted from the implicit network usually has some defects. To address this problem, some methods first represent the 3D shape with an implicit geometry network, like occupancy grid (Niemeyer et al., 2020; Oechsle et al., 2021) or signed distance fields (Yariv et al., 2020; Wang et al., 2021; Yariv et al., 2021; Darmon et al., 2022; Sun et al., 2022; Fu et al., 2022; Yu et al., 2022), and then transfer the output of the geometry network to a density function, with which the radiance network could render color images. In this way, the radiance network as well as the geometry network can be optimized together by matching the rendered and input images. DVR (Niemeyer et al., 2020) is the first to introduce a fully differentiable renderer for implicit neural occupancy functions. Then, IDR (Yariv et al., 2020) adds the normal and the view direction into the surface renderer, which proves their importance in disentangling geometry and appearance. To obtain a better reconstruction, NeuS (Wang et al., 2021) and VolSDF (Yariv et al., 2021) employ the SDF representation with a volume rendering. They model the volume density as a function of the SDF, which provides a useful inductive bias to the geometry learned in the neural volume rendering process. Sparse-NeuS (Long et al., 2022) further tries to perform the implicit reconstruction with only sparse views, and generalizes the network to an unseen scene. To further improve the surface quality, some methods introduce additional information, like the sparse point clouds (Fu et al., 2022) or monocular depth (Yu et al., 2022), to help the reconstruction, which could recover a more detailed shape but with the cost of acquiring the additional information.

In all the above methods, however, the 3D geometry is directly encoded in the MLPs without any explicit 3D spatial information. As observed in (Chibane et al., 2020; Peng et al., 2020), the simple MLP network architecture often leads to learning and optimization difficulties and consequently inaccurate surface reconstruction. To address this problem, we introduce a hierarchical volume encoding to explicitly encode the 3D spatial information, thus our method can reconstruct more surface details.

3 METHODS

3.1 OVERVIEW

The overall framework of our method is illustrated in Figure 2. Given multiple images $\{\mathbf{I}_i\}_{i=1}^N$ of an object and corresponding camera poses, the task is to reconstruct the 3D surface of this object.

Figure 3: A 2D toy example of the hierarchical volume encoding. Left: a single high resolution volume. Features with 3 channels are used to encode two locations p and q. Note it only captures spatial variant features. Right: a hierarchical volume with lower dimensionality. Features have just 1 channel and the memory consumption is much less. The high resolution volume encodes spatial variant features, while the low resolution volume enforces spatial smoothness.

The 3D shape is represented by an implicit SDF network, with which another implicit color network render images using the neural volume rendering. To enhance the representation ability of the spatial information, we add a hierarchical volume encoding as the input of the SDF network, which can embed the 3D space in multiple scales. To save the memory consumption, we also introduce a sparse structure for high-resolution volumes. Finally, two implicit networks as well as the volume encoding are optimized by minimizing the difference between the rendered images and the input images as well as minimizing two regularization terms.

3.2 IMPLICIT SURFACE RECONSTRUCTION BASED ON VOLUME RENDERING

Neural implicit volume rendering is first introduced in (Mildenhall et al., 2020) for novel view rendering and then used in (Wang et al., 2021; Yariv et al., 2021; Darmon et al., 2022) for surface reconstruction. Our method could be added to any of them for better reconstruction. Here we take NeuS (Wang et al., 2021) as an example, which uses two multi-layer perceptrons (MLPs) to serve as two functions for representing an object: one is the SDF network $sdf : \mathbb{R}^3 \to \mathbb{R}$ that maps a spatial position $\mathbf{x} \in \mathbb{R}^3$ to its SDF value of the object surface, and the other one is the color network $c : \mathbb{R}^3 \times \mathbb{S}^2 \to \mathbb{R}$ that maps the spatial point $\mathbf{x}$ and a viewing direction $\mathbf{v} \in \mathbb{S}^2$ to a color value. The surface $\mathcal{S}$ is then represented by the zero-level set of the SDF function as:

$$\mathcal{S} = \{\mathbf{x} \in \mathbb{R}^3 | sdf(\mathbf{x}) = 0\}. \tag{1}$$

To optimize the SDF network, images are rendered from the color network as well as a weighting function computed from the SDF network. The volume rendering function for generating colors is calculated as

$$C(\mathbf{o}, \mathbf{v}) = \int_0^{+\infty} w(t)c(\mathbf{p}(t), \mathbf{v})dt, \tag{2}$$

where w is the weighting function computed by the density from the SDF network.

To make the weighting function unbiased and occlusion-aware, it is calculated as

$$w(t) = T(t)\rho(t), \tag{3}$$

where

$$T(t) = e^{-\int_0^t \rho(u)du}, \tag{4}$$

and

$$\rho(t) = \max(\frac{-\frac{d\Phi_s}{dt}(sdf(\mathbf{p}(t)))}{\Phi_s(sdf(\mathbf{p}(t)))}, 0), \quad \Phi_s(x) = (1 + e^{-sx})^{-1}. \tag{5}$$

3.3 HIERARCHICAL VOLUME ENCODING

Previous methods usually encode all the information of a 3D object in the MLPs. This works well for novel view rendering but has problems in surface reconstruction, because the simple MLP architecture makes learning and optimization inefficient. To address this problem, we build a 3D feature

volume as the input of the MLPs, which explicitly encodes the 3D spatial information. This feature volume can naturally encode the knowledge about the 3D space of the object, while being optimized as well as the MLPs from the rendering loss.

To enhance the representation ability of the encoding, we also employ a hierarchical mechanism, where different scales of the 3D feature volumes are adopted, as is shown in Figure 3. In the experiments, we find a combination of multi-scale volumes works better than a single large-width volume. This is reasonable since in low-resolution volumes, one voxel represent a large space, such that this space can have the same code. The same code could smooth this space and prevent crushing 3D shape, which is important in surface reconstruction.

In a basic setting, we employ eight feature volumes for the 3D space encoding, whose resolutions increase from $2 \times 2 \times 2 \times 4$ to $256 \times 256 \times 256 \times 4$. When a point $\mathbf{x}$ is being rendered, eight features of the corresponding position from these eight volumes are trilinearly interpolated and concatenated to form $\mathcal{F}(\mathbf{x})$, which works as the input of the MLPs. Therefore, the SDF function becomes

$$\mathcal{S} = \{\mathbf{x} \in \mathbb{R}^3 | sdf(\mathcal{F}(\mathbf{x})) = 0\}. \tag{6}$$

3.4 SPARSE HIGH RESOLUTION VOLUME

It is evident that the higher the resolution of the volume is, the more details would be recovered, but a volume larger than $256 \times 256 \times 256$ would consume much more memory. To solve this problem, a multi-stage optimization scheme is adopted with high-resolution sparse volumes. In general, a lot of voxels in a dense volume are unoccupied and invalid. Thus, we could save memory consumption a lot by using the shape reconstructed from the coarse volumes to cull voxels far from the surface in the high-resolution volumes.

Figure 4: Sparse high-resolution volume. The index of -1 fetches the last embedding (in dark gray) in T_e.

To do this, we propose a multi-stage optimization framework. In the first stage, we use the above-mentioned basic structure, where the resolution of the largest volume is 256. After the first stage, we obtain a coarse surface reconstruction $\mathcal{S}_c$. In the second stage, we utilize $\mathcal{S}_c$ to cull unnecessary voxels to obtain the valid voxels $\mathbf{V}_h^{valid}$ in the high-resolution volume. Specifically, we first dilate the surface $\mathcal{S}_c$ to ensure all the valid voxels nearing the surface are included, where several offsets $\mathbf{dv}$ is added to each surface voxel $\mathbf{v}$ in $\mathcal{S}_c$ to get an unduplicated voxel set:

$$\mathbf{V}_h^{valid} = \text{Set}(\{\mathbf{v} + \mathbf{dv} \mid \mathbf{dv} \in \mathbb{Z}^3, ||\mathbf{dv}|| <= r, \mathbf{v} \in \mathcal{S}_c\}). \tag{7}$$

Therefore, we only need to optimize the embeddings in $\mathbf{V}_h^{valid}$ instead of all voxels. Here, we use a simple data structure, an embedding table T_e, to store these embeddings.

Given a floating-point three-dimensional position $\mathbf{x}$, we obtain the surrounding eight integer coordinates through the rounding operation, take out the embedding of these integer points, and then fuse them through trilinear interpolation to serve as the encoding of $\mathbf{x}$. In order to efficiently extract the corresponding embedding from the embedding table T_e, we construct another index table T_i which stores the indexes of T_e. The values in table T_i are all initialized to -1, which corresponds to the last embedding in table T_e. Then, we assign values to table T_i through the $\mathbf{V}_h^{valid}$. Specifically, we first define a mapping function f:

$$f(\mathbf{x}) = x + y * N + z * N^2, \tag{8}$$

where N is the resolution of the volume, and x, y, z are the coordinates of the position $\mathbf{x}$. We utilize f to map each voxel $\mathbf{v}_j$ in $\mathbf{V}_h^{valid}$ to the index in table T_i, and then T_i further converts it to the index j in T_e:

$$T_i(f(\mathbf{x})) = j, \ j = 1...n \tag{9}$$

where n is the number of valid voxels in $\mathbf{V}_h^{valid}$. The length of the embedding table T_e is only $n+1$ ($n \ll N^3$), such that the memory consumption is reduced a lot due to the sparse structure of the high-resolution volumes.

Method	24	37	40	55	63	65	69	83	97	105	106	110	114	118	122	Mean
IDR(Yariv et al., 2020)	1.63	1.87	0.63	0.48	1.04	0.79	0.77	1.33	1.16	0.76	0.67	0.90	0.42	0.51	0.53	0.90
MVSDF(Zhang et al., 2021)	0.83	1.76	0.88	0.44	1.11	0.90	0.75	1.26	1.02	1.35	0.87	0.84	0.34	0.47	0.46	0.88
COLMAP(Schönberger et al., 2016)	0.45	0.91	0.37	0.37	0.90	1.00	0.54	1.22	1.08	0.64	0.48	0.59	0.32	0.45	0.43	0.65
NeRF(Mildenhall et al., 2020)	1.90	1.60	1.85	0.58	2.28	1.27	1.47	1.67	2.05	1.07	0.88	2.53	1.06	1.15	0.96	1.49
UNISURF(Oechsle et al., 2021)	1.32	1.36	1.72	0.44	1.35	0.79	0.80	1.49	1.37	0.89	0.59	1.47	0.46	0.59	0.62	1.02
NeuS(Wang et al., 2021)	1.00	1.37	0.93	0.43	1.10	0.65	0.57	1.48	1.09	0.83	0.52	1.20	0.35	0.49	0.54	0.84
VolSDF(Yariv et al., 2021)	1.14	1.26	0.81	0.49	1.25	0.70	0.72	1.29	1.18	0.70	0.66	1.08	0.42	0.61	0.55	0.86
NeuralWarp(Darmon et al., 2022)	0.49	0.71	0.38	0.38	0.79	0.81	0.82	1.20	1.06	0.68	0.66	0.74	0.41	0.63	0.51	0.68
NeuS+Hash	1.26	1.67	0.84	0.39	1.19	0.78	0.64	1.41	1.24	0.72	0.58	1.49	0.34	0.49	0.52	0.90
NeuS+Ours	**0.41**	0.70	**0.35**	**0.35**	0.85	**0.55**	**0.62**	1.33	1.03	0.67	0.53	0.79	**0.33**	**0.42**	**0.45**	0.63
VolSDF+Ours	0.51	0.77	0.49	0.38	0.75	0.67	0.71	1.16	1.00	**0.63**	0.57	0.89	0.38	0.52	0.48	0.66
NeuralWarp+Ours	0.44	**0.69**	0.36	0.38	**0.63**	0.64	0.69	**1.13**	**0.99**	0.66	**0.51**	**0.61**	0.36	0.53	0.52	**0.61**

Table 1: Quantitative results on the DTU dataset.

3.5 LOSS FUNCTION

We equip three previous methods (Wang et al., 2021; Yariv et al., 2021; Darmon et al., 2022) with our hierarchical volume encoding. To optimize the model, we use the losses in their work without changes, i.e. a rendering loss $\mathcal{L}_{color}$ which minimizes the difference between the rendered colors and input colors, and an Eikonal loss L_{eik} (Gropp et al., 2020) which encourages unit norm of the SDF function gradients. Besides, for NeuralWarp (Darmon et al., 2022), an additional warping color loss $\mathcal{L}_{warp}$ is adopted, which warps views on each other to enforce multi-view photo-consistency.

In addition, we add two additional regularization terms $\mathcal{L}_{tv}$ and $\mathcal{L}_{normal}$ to make the reconstructed surfaces smooth and clean. The total variation (TV) (Rudin & Osher, 1994) regularization is applied to each embedding volume to make adjacent voxels have similar characteristics, in which case the geometry could be more continuous and compact. It is computed as:

$$\mathcal{L}_{tv} = \sum_{m} \sum_{i,j,k} \sqrt{(V_{i+1,j,k} - V_{i,j,k})^2} + \sqrt{(V_{i,j+1,k} - V_{i,j,k})^2} + \sqrt{(V_{i,j,k+1} - V_{i,j,k})^2}, \quad (10)$$

where m is the number of the hierarchical volumes.

Another regularization term $\mathcal{L}_{normal}$ is a smoothness constraint for normal. For each pixel of the image, we calculate the accumulated normal gradients along the marching ray as

$$N_{grad}(\mathbf{o}, \mathbf{v}) = \int_{0}^{+\infty} w(t) n_{grad}(t) dt, \quad (11)$$

where $n_{grad}(t)$ is the gradient of the normal at $\mathbf{p}(t)$ and computed as

$$n_{grad}(t) = \nabla^2 sdf(\mathcal{F}(\mathbf{p}(t))). \quad (12)$$

The normal regularization $\mathcal{L}_{normal}$ is then defined as:

$$\mathcal{L}_{normal} = \frac{1}{N_{pix}} \sum_{pix} ||N_{grad}||_2, \quad (13)$$

where N_{pix} is the number of pixels in one optimization.

Thus, the final loss $\mathcal{L}$ is defined as:

$$\mathcal{L} = \mathcal{L}_{ori} + \lambda_{tv} * \mathcal{L}_{tv} + \lambda_{normal} * \mathcal{L}_{normal}, \quad (14)$$

where $\mathcal{L}_{ori}$ is the original loss of each method, λ_{tv} and λ_{normal} are two weighting factors.

4 EXPERIMENTS

4.1 IMPLEMENTATION DETAILS

This work is implemented in Pytorch and experimented on Nvidia 2080Ti GPUs. The Adam optimizer $(0.9, 0.999)$ is used to update the network weights. The learning rate for the MLPs is set to $5e^{-4}$ and decreased to $1/20$, while the learning rates for the volumes with resolutions of $2, 4, 8, 16, 32, 64, 128, 256, 512, 1024$ are set to $0.01, 0.01, 0.01, 0.01, 0.01, 0.001, 0.001, 1e^{-4}, 1e^{-4}, 1e^{-4}$ and decreased to $1/100$. We adopt a three-stage training strategy by default, and

Figure 5: Visual comparison of the reconstructed meshes.

the number of optimization iterations is set to the same as the original framework. Taking "NeuS + Ours" as an example, there are 300K iterations in total. In the first stage, eight volumes of resolution from $[2^3, 4]$ to $[256^3, 4]$ are employed for 80K-iteration optimization. In the second stage, a sparse volume with the resolution of $[512^3, 4]$ is added for another 20K-iteration optimization. Finally, a sparse volume of $[1024^3, 4]$ is appended for the remaining 200K-iteration optimization. The length of the index tables for the second and the third stages are set to 256^3.

4.2 EVALUATION

For a fair comparison, we follow previous methods to evaluate our method on DTU (Jensen et al., 2014) , EPFL (Strecha et al., 2008) and BlendedMVS (Yao et al., 2020) benchmark. The Chamfer L1 distance is used for evaluating the accuracy of the recovered surfaces. This metric is the average of the accuracy, which measures the distance from the reconstructed surface to the ground-truth surface, and the completeness, which measures the distance in reverse.

We first evaluate our method on the DTU dataset and report the quantitative results in Table 1. We follow previous work (Darmon et al., 2022; Oechsle et al., 2021) to clean the predicted mesh by visibility masks for more reasonable evaluation. As shown in Table 1, the accuracy of previous

Figure 6: Ablation study. (a)Sparse high-res volume. (b)Regularization terms. (c)NeuS+Hash vs. NeuS+Ours.

methods is improved significantly by adding the hierarchical volume encoding. To be specific, the error of NeuS (Wang et al., 2021) is reduced by 25%, from 0.84 to 0.63, while the error of NeuralWarp (Darmon et al., 2022) is reduced by 10%, from 0.68 to 0.61. The reconstructed meshes are shown in Figure 5, from where we can see that the surfaces of our method are smooth and clean, while containing accurate geometry details. For instance, the details of the house in the first scene in Figure 5 are recovered, especially the shape of the windows and the bricks of the roof, which is more remarkable in the normal map in Figure 1.

We then evaluate our method on the EPFL dataset. For a fair comparison, we follow NeuralWarp to use both the "full" chamfer distance and the "center" chamfer distance to evaluate the reconstructed surfaces. The "center" metric only evaluates the center of the scene cropped by a manually defined box, which focuses more on the precision of the reconstruction, while the "full" metric is also influenced by the ground plane and the rarely seen points, which thus also considers the completeness of the recon-

Method	Fountain-P11		Herzjesu-P7		Mean	
	Full	Center	Full	Center	Full	Center
COLMAP	6.47	2.45	**7.95**	2.31	7.21	2.38
UNISURF	26.16	17.72	27.22	13.72	26.69	15.72
MVSDF	6.87	2.26	11.32	2.72	9.10	2.49
VolSDF	12.89	2.99	13.61	4.58	13.25	3.78
NeuS	7.64	2.25	19.03	14.02	13.33	7.79
NeuralWarp	7.77	1.92	8.88	2.03	8.32	1.97
NeuS+Ours	7.39	1.76	11.23	3.69	9.31	2.73
NeualWarp+Ours	**3.31**	**1.73**	8.13	**1.71**	**5.72**	**1.72**

Table 2: Quantitative results on the EPFL dataset.

struction. As shown in Table 2, the performance of each framework is improved significantly by adding our method. Especially, the "full" metric of NeuralWarp is decreased by 31% to 5.72, which is also a 21% improvement compared to COLMAP (Schönberger et al., 2016).

Finally, the evaluation is performed on the BlendedMVS dataset, which contains objects of more complex shapes. As shown in Figure 5, our method can recover more detailed shapes than previous methods. These illustrate that our hierarchical volume encoding can facilitate MLPs to encode more complex shapes and improve the neural implicit surface reconstruction.

4.3 ABLATION STUDY

We choose "NeuS + Ours" to perform extensive ablation studies to validate the proposed method. All the results are reported from the 15 scans of DTU dataset unless otherwise specified.

Hierarchical volume encoding. To study the effectiveness of the hierarchical volume encoding, we equip the basic set of eight volumes to NeuS (Wang et al., 2021) without any other change. As shown in Table 3, the error of the recovered surfaces is significantly reduced from 0.84 to 0.70.

Regularization terms. We also ablate the two smoothness terms to study their effectiveness. As shown in Table 3, they help to further reduce the error metric down to 0.66. Figure 6 (b) shows a visual comparison without (middle) and with (right) the regularization terms. The reconstructed mesh is smoother and more complete with the regularization terms.

Figure 7: Ablation study about the number of the volumes and the resolution combination of volumes.

Sparse high resolution volume. We analyze the effect of the resolution of volumes. As shown in Table 3, sparse high resolution embedding volume (resolution of 1024 here) further improves the accuracy to 0.63. We also visualize the reconstructed surfaces without (left) and with (right) sparse high resolution embedding in Figure 6(a). It is clear that the high-resolution embedding generates more shape details, e.g., clearer facial shapes.

Hierarchical Volume	Regular Terms	Sparse High-Res	Mean
✗	✗	✗	0.84
✓	✗	✗	0.70
✓	✓	✗	0.66
✓	✓	✓	0.63

Table 3: Ablation study on the DTU dataset.

Setup of embedding volumes. To further inspect the effect of different combinations of the volume encoding, we perform two experiments on the volume setups. (1) We study the number of the volumes. We first compare our hierarchical setup to a large volume of $256^3 \times 32$, the number of whose learnable parameters is about 8 times larger than ours. However, its performance is much worse than ours, as is presented in the left of Figure 7. Then we keep the number of feature channels fixed at 32 and increase the volume number. The resolution of the first volume is set to 256, and the resolution of the remaining volumes is decreased by $1/2$ one by one. As shown in Figure 7 left, the accuracy of the reconstructed surface is gradually improved with the arising of the volume number. (2) Next, we study the impact of the low-resolution volume. We keep the resolution of the largest volume fixed at 256, the number of the volumes fixed at 8, and vary the resolution of the smallest volume from 2 to 64. The resolutions of intermediate volumes are sequentially enlarged, and the enlargement factor is $(256/min\_res)^{1/8}$. From the results shown in Figure 7 right, we can see the performance is decreased when the low-resolution volume begins from a larger resolution. This is intuitive because the low-resolution volume enforces spatial smoothness. Starting from a lower resolution helps to enforce smoothness across larger areas.

Layer number of MLPs. Finally, we experiment with the layer number of MLPs in the SDF network to inspect its effect. When only half of the layers are used, the chamfer distance increases to 0.71. More details are included in the appendix.

4.4 COMPARISON TO HASH ENCODING

A similar hierarchical feature encoding is adopted in Instant-NGP (Müller et al., 2022), but the features are stored in a hash table such that the hash collision is inevitable. This may result in cracks of the implicit geometry. We add this hash encoding to the NeuS framework for a comparison. According to the quantitative results in Table 1 and the visual comparison shown in Figure 6(c), the quality of the reconstructed mesh with hash encoding is worse than our method. Especially, there are many cracked areas on the reconstructed surface.

5 CONCLUSION

We propose to explicitly encode the 3D shape surface by hierarchical volumes to facilitate MLPs in neural implicit surface reconstruction methods. The spatially varying features can be obtained from high resolution volume to reason more details for each query 3D point, while the feature from low-resolution volumes could reason spatial consistency to keep shapes smooth. We also design a sparse structure to reduce the memory consumption of high-resolution volumes, and two regularization terms to enhance surface smoothness. Our hierarchical volume encoding could be appended to any implicit surface reconstruction method as a plug-and-play module to significantly boost their performance, which is demonstrated in three datasets.

REFERENCES

Connelly Barnes, Eli Shechtman, Adam Finkelstein, and Dan B Goldman. Patchmatch: A randomized correspondence algorithm for structural image editing. *ACM Transactions on Graphics*, 28 (3):24, 2009.

Julian Chibane, Thiemo Alldieck, and Gerard Pons-Moll. Implicit functions in feature space for 3d shape reconstruction and completion. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2020.

François Darmon, Bénédicte Bascle, Jean-Clément Devaux, Pascal Monasse, and Mathieu Aubry. Improving neural implicit surfaces geometry with patch warping. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 6260–6269, 2022.

Daniel DeTone, Tomasz Malisiewicz, and Andrew Rabinovich. Superpoint: Self-supervised interest point detection and description. In *CVPR*, pp. 224–236, 2018.

Qiancheng Fu, Qingshan Xu, Yew-Soon Ong, and Wenbing Tao. Geo-neus: Geometry-consistent neural implicit surfaces learning for multi-view reconstruction. *arXiv preprint arXiv:2205.15848*, 2022.

Simon Fuhrmann, Fabian Langguth, and M. Goesele. Mve - a multi-view reconstruction environment. In *Proceedings of the Eurographics Workshop on Graphics and Cultural Heritage*, 2014.

Yasutaka Furukawa and Jean Ponce. Accurate, dense, and robust multiview stereopsis. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 32(8):1362–1376, 2009.

Silvano Galliani, Katrin Lasinger, and Konrad Schindler. Massively parallel multiview stereopsis by surface normal diffusion. In *Proceedings of the International Conference on Computer Vision*, pp. 873–881, 2015.

Amos Gropp, Lior Yariv, Niv Haim, Matan Atzmon, and Yaron Lipman. Implicit geometric regularization for learning shapes. In *Proceedings of Machine Learning and Systems 2020*, pp. 3569–3579. 2020.

Xiaodong Gu, Zhiwen Fan, Siyu Zhu, Zuozhuo Dai, Feitong Tan, and Ping Tan. Cascade cost volume for high-resolution multi-view stereo and stereo matching. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2495–2504, 2020.

Rasmus Jensen, Anders Dahl, George Vogiatzis, Engil Tola, and Henrik Aanæs. Large scale multiview stereopsis evaluation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 406–413. IEEE, 2014.

Mengqi Ji, Juergen Gall, Haitian Zheng, Yebin Liu, and Lu Fang. Surfacenet: An end-to-end 3d neural network for multiview stereopsis. In *Proceedings of the International Conference on Computer Vision*, pp. 2307–2315, 2017.

Nianjuan Jiang, Zhaopeng Cui, and Ping Tan. A global linear method for camera pose registration. In *Proceedings of the International Conference on Computer Vision*, 2013.

Michael Kazhdan, Matthew Bolitho, and Hugues Hoppe. Poisson surface reconstruction. In *Proceedings of the fourth Eurographics symposium on Geometry processing*, volume 7, 2006.

Maxime Lhuillier and Long Quan. A quasi-dense approach to surface reconstruction from uncalibrated images. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 27:418 – 433, 2005.

Xiaoxiao Long, Cheng Lin, Peng Wang, Taku Komura, and Wenping Wang. Sparseneus: Fast generalizable neural surface reconstruction from sparse views. *arXiv preprint arXiv:2206.05737*, 2022.

Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. In *Proceedings of the European Conference on Computer Vision*, pp. 405–421, 2020.

Thomas Müller, Alex Evans, Christoph Schied, and Alexander Keller. Instant neural graphics primitives with a multiresolution hash encoding. *ACM Trans. Graph.*, 41(4):102:1–102:15, July 2022. doi: 10.1145/3528223.3530127. URL https://doi.org/10.1145/3528223.3530127.

Zak Murez, Tarrence van As, James Bartolozzi, Ayan Sinha, Vijay Badrinarayanan, and Andrew Rabinovich. Atlas: End-to-end 3d scene reconstruction from posed images. In *Proceedings of the European Conference on Computer Vision*, pp. 414–431. Springer, 2020.

Michael Niemeyer, Lars Mescheder, Michael Oechsle, and Andreas Geiger. Differentiable volumetric rendering: Learning implicit 3d representations without 3d supervision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3504–3515, 2020.

Michael Oechsle, Songyou Peng, and Andreas Geiger. Unisurf: Unifying neural implicit surfaces and radiance fields for multi-view reconstruction. In *Proceedings of the International Conference on Computer Vision*, pp. 5589–5599, 2021.

Songyou Peng, Michael Niemeyer, Lars Mescheder, Marc Pollefeys, and Andreas Geiger. Convolutional occupancy networks. In *Proceedings of the European Conference on Computer Vision*, 2020.

Leonid I Rudin and Stanley Osher. Total variation based image restoration with free local constraints. In *Proceedings of 1st international conference on image processing*, volume 1, pp. 31–35. IEEE, 1994.

Paul-Edouard Sarlin, Daniel DeTone, Tomasz Malisiewicz, and Andrew Rabinovich. Superglue: Learning feature matching with graph neural networks. In *CVPR*, pp. 4938–4947, 2020.

Johannes L Schönberger, Enliang Zheng, Jan-Michael Frahm, and Marc Pollefeys. Pixelwise view selection for unstructured multi-view stereo. In *Proceedings of the European Conference on Computer Vision*, pp. 501–518. Springer, 2016.

Johannes Lutz Schönberger and Jan-Michael Frahm. Structure-from-motion revisited. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

Christoph Strecha, Wolfgang Von Hansen, Luc Van Gool, Pascal Fua, and Ulrich Thoennessen. On benchmarking camera calibration and multi-view stereo for high resolution imagery. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1–8. Ieee, 2008.

Jiaming Sun, Yiming Xie, Linghao Chen, Xiaowei Zhou, and Hujun Bao. Neuralrecon: Real-time coherent 3d reconstruction from monocular video. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 15598–15607, 2021.

Jiaming Sun, Xi Chen, Qianqian Wang, Zhengqi Li, Hadar Averbuch-Elor, Xiaowei Zhou, and Noah Snavely. Neural 3d reconstruction in the wild. In *ACM SIGGRAPH 2022 Conference Proceedings*, pp. 1–9, 2022.

Ping Tan. Image-based modeling. In *Computer Vision: A Reference Guide*, pp. 653–656. Springer, 2021.

Chengzhou Tang and Ping Tan. Ba-net: Dense bundle adjustment network. *ICLR*, 2019.

Shitao Tang, Jiahui Zhang, Siyu Zhu, and Ping Tan. Quadtree attention for vision transformers. *ICLR*, 2022.

Benjamin Ummenhofer, Huizhong Zhou, Jonas Uhrig, Nikolaus Mayer, Eddy Ilg, Alexey Dosovitskiy, and Thomas Brox. Demon: Depth and motion network for learning monocular stereo. In *CVPR*, pp. 5038–5047, 2017.

Peng Wang, Lingjie Liu, Yuan Liu, Christian Theobalt, Taku Komura, and Wenping Wang. Neus: Learning neural implicit surfaces by volume rendering for multi-view reconstruction. *Advances in Neural Information Processing Systems*, 34:27171–27183, 2021.

Yao Yao, Zixin Luo, Shiwei Li, Tian Fang, and Long Quan. Mvsnet: Depth inference for unstructured multi-view stereo. In *Proceedings of the European Conference on Computer Vision*, pp. 767–783, 2018.

Yao Yao, Zixin Luo, Shiwei Li, Jingyang Zhang, Yufan Ren, Lei Zhou, Tian Fang, and Long Quan. Blendedmvs: A large-scale dataset for generalized multi-view stereo networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1790–1799, 2020.

Lior Yariv, Yoni Kasten, Dror Moran, Meirav Galun, Matan Atzmon, Basri Ronen, and Yaron Lipman. Multiview neural surface reconstruction by disentangling geometry and appearance. *Advances in Neural Information Processing Systems*, 33:2492–2502, 2020.

Lior Yariv, Jiatao Gu, Yoni Kasten, and Yaron Lipman. Volume rendering of neural implicit surfaces. *Advances in Neural Information Processing Systems*, 34:4805–4815, 2021.

Zehao Yu, Songyou Peng, Michael Niemeyer, Torsten Sattler, and Andreas Geiger. Monosdf: Exploring monocular geometric cues for neural implicit surface reconstruction. *arXiv preprint arXiv:2206.00665*, 2022.

Jingyang Zhang, Yao Yao, and Long Quan. Learning signed distance field for multi-view surface reconstruction. In *Proceedings of the International Conference on Computer Vision*, pp. 6525–6534, 2021.

A APPENDIX

A.1 DATASETS

DTU (Jensen et al., 2014) is a well-used dataset for multi-view reconstruction, consisting of 124 scans of various objects. The images are obtained from an RGB camera and a structured light scanner mounted on an industrial robot arm. Each scene is captured from 49 or 64 views with a resolution of 1600×1200. For a fair comparison, we follow previous methods and select 15 scenes from DTU for evaluation. BlendedMVS (Yao et al., 2020) is another dataset for multi-view reconstruction composed of 113 scenes including architectures, sculptures, and small objects. Each scene consists of dozens to hundreds of images with a resolution of 768×576. EPFL (Strecha et al., 2008) is a small dataset composed of two outdoor scenes, Fountain and Herzjesu, which contain 11 and 9 high-resolution images, respectively, and the accurate ground truth meshes.

A.2 MORE ABLATION STUDY

Layer number of MLPs We perform experiments on the layer number of MLPs in the SDF network to inspect its effect. As shown in Table 4, the mean chamfer distance decreases with the increase of the layer number of MLPs. NeuS (Wang et al., 2021) adopts 9 layers of MLPs and gets an error of 0.84, while the error of our method already decreases to 0.78 with only 2 layers.

Method	Num.	24	37	40	55	63	65	69	83	97	105	106	110	114	118	122	Mean
NeuS	9	1.00	1.37	0.93	0.43	1.10	0.65	0.57	1.48	1.09	0.83	0.52	1.20	0.35	0.49	0.54	0.84
NeuS+Ours	1	1.59	1.67	0.56	0.94	0.96	0.73	0.97	1.95	1.82	0.95	1.48	1.67	1.73	0.83	0.78	1.24
	2	0.53	0.78	0.73	0.36	0.90	0.66	0.74	1.48	1.10	0.72	0.55	1.59	0.36	0.57	0.64	0.78
	3	0.49	0.75	0.72	0.37	0.87	0.58	0.63	1.34	1.11	0.74	0.49	1.58	0.34	0.42	0.46	0.73
	5	0.51	0.74	0.58	0.36	0.89	0.58	0.66	1.39	1.05	0.78	0.51	1.47	0.36	0.41	0.42	0.71
	9	0.42	0.77	0.38	0.34	0.81	0.61	0.65	1.26	1.10	0.65	0.49	1.60	0.32	0.58	0.51	0.70

Table 4: Quantitative results for the different layer number of MLPs on the DTU dataset.