Learning Generative Vision Transformer with Energy-Based Latent Space for Saliency Prediction

Jing Zhang[1], **Jianwen Xie**[1], **Nick Barnes**[2], **Ping Li**[1]
[1] Cognitive Computing Lab, Baidu Research
[2] The Australian National University
{zjnwpu, jianwen.kenny, pingli98}@gmail.com, nick.barnes@anu.edu.au

Abstract

Vision transformer networks have shown superiority in many computer vision tasks. In this paper, we take a step further by proposing a novel generative vision transformer with latent variables following an informative energy-based prior for salient object detection. Both the vision transformer network and the energy-based prior model are jointly trained via Markov chain Monte Carlo-based maximum likelihood estimation, in which the sampling from the intractable posterior and prior distributions of the latent variables are performed by Langevin dynamics. Further, with the generative vision transformer, we can easily obtain a pixel-wise uncertainty map from an image, which indicates the model confidence in predicting saliency from the image. Different from the existing generative models which define the prior distribution of the latent variables as a simple isotropic Gaussian distribution, our energy-based informative prior can be more expressive to capture the latent space of the data. We apply the proposed generative vision transformer to both RGB and RGB-D image salient object detection tasks. Extensive experimental results show that our framework can achieve not only accurate saliency predictions but also meaningful uncertainty maps that are consistent with the human perception.

1   Introduction

Salient object detection [62, 63, 15, 16, 5, 80, 81] (SOD), which aims at highlighting objects more attentive than the surrounding areas in images, has achieved significant performance improvement with the deep convolutional neural network revolution. Given a set of training images along with their saliency annotations, the conventional SOD models seek to learn a deterministic mapping from image domain to saliency domain.

Two main issues exist in the above conventional deep saliency prediction framework: (i) the convolution operation based on sliding window makes the deep saliency prediction model less effective in modeling the global contrast, which is essential for salient object detection [7]; (ii) the one-to-one deterministic mapping mechanism makes the current frameworks not only impossible to represent the pixel-wise uncertainty in predicting saliency maps, but also hard to handle incomplete data in a weakly supervised scenario [80]. Besides, given an image, the saliency output of a human is subjective, therefore, a stochastic generative model is more natural than a deterministic model for representing saliency prediction. Although [77] introduces a conditional variational autoencoder (CVAE) [54] for RGB-D salient object detection, the potential posterior collapse problem [20] makes the stochastic predictions less effective in generating meaningful uncertainty estimation.

Motivated by the above two issues, we propose a novel framework, the generative vision transformer, for salient object detection, where a vision transformer structure [39] is used as a backbone and latent variables are introduced in designing our generative framework. On the one hand, transformers [58] have proven to be very effective in long-range dependency modeling, and are capable of modeling

various scopes of object context information with the multi-head self-attention module. With such an architecture, we can achieve global context modeling for effective salient object detection. On the other hand, the latent variables account for randomness and uncertainty in modeling the mapping from image domain to saliency domain, and also enable the model to produce stochastic saliency predictions for uncertainty estimation. Therefore, the proposed model is a latent variable transformer.

Nowadays, there are two types of generative models that have been widely used, namely the variational autoencoder (VAE) [29] and the generative adversarial network (GAN) [17], which correspond to two different generative learning strategies to train latent variable models. To train a top-down latent variable generator, the VAE introduces an extra encoder to approximate the intractable posterior distribution of the latent variables, and trains the generator via a perturbation of maximum likelihood; while the GAN introduces a discriminator to distinguish between generated samples and real data, and trains the generator to fool the discriminator. [19, 67] present the third learning strategy, namely alternating back-propagation (ABP), to train the generator with latent variables being directly sampled from the true posterior distribution by using a gradient-based Markov chain Monte Carlo (MCMC) [36], e.g., Langevin dynamics [42, 64, 11]. All the three generative models define the prior distribution of the latent variables as a simple non-informative isotropic Gaussian distribution, which is less expressive in capturing meaningful latent representation of the data.

In this paper, we investigate generative modeling of the vision transformer. We construct a generative model for salient object detection in the form of a top-down conditional latent variable model. Specifically, we propose a generative vision transformer by adding latent variables into the traditional deterministic transformer, and assume the latent variables follow an informative trainable energy-based prior distribution [46, 47]. Following [70], we parameterize the energy function of the energy-based model (EBM) by a deep net. Instead of using variational learning or adversarial learning, we jointly train the parameters of the EBM prior and the transformer network by maximum likelihood estimation (MLE). The MLE algorithm relies on MCMC sampling to evaluate the intractable prior and posterior distributions of the latent variables.

Experimental results on RGB and RGB-D image salient object detection [62, 66, 77, 15] show that the generative framework equipped with the EBM prior and the transformer-based non-linear mapping is powerful in representing the conditional distribution of object saliency given an image, leading to more reasonable uncertainty estimation as shown in Figure 1, where stochastic saliency prediction is provided by a learned model and the visualization of the pixel-wise uncertainty is presented.

Figure 1: An illustration of the stochastic saliency prediction obtained by the proposed generative vision transformer with an EBM prior, as well as the corresponding pixel-wise uncertainty map.

We summarize our main contributions as: (i) we propose a novel top-down generative vision transformer network with an energy-based prior distribution on latent space for salient object detection; (ii) we jointly train the vision transformer network and the energy-based prior model by an MCMC-based maximum likelihood estimation, without relying on any extra assisting network for adversarial learning or variational learning; (iii) We achieve new benchmark results for both RGB and RGB-D image saliency detection, and obtain meaningful uncertainty maps that are highly consistent with human perception for saliency prediction.

2   Related Work

Salient object detection: The main focus of existing deep fully-supervised RGB image based SOD models [65, 40, 37, 66, 62, 59, 79, 63] is achieving structure preserving saliency prediction, either by sophisticated feature aggregation [65, 37, 59], or by auxiliary edge detection [66, 50, 63], or resorting to structure-aware loss functions [40, 62]. With extra depth data, RGB-D SOD models mainly focus on effective multi-modal learning. [51, 77, 5, 25, 85, 82, 15, 26, 49, 84, 57, 78].

Vision Transformer: The breakthroughs of the Transformer networks [58] in natural language processing (NLP) domain have sparked the interest of the computer vision community in developing vision transformer for different computer vision tasks, such as object detection [4, 61, 6], image segmentation [87, 52, 61, 39], object tracking [72, 73], pose estimation [41, 56], etc. Among them, DPT [52] adopts a U-shape structure and uses ViT [10] as encoder to achieve semantic segmentation and monocular depth estimation. Swin [39] presents a hierarchical transformer with a shifted windowing scheme to achieve efficient transformer network with high resolution images as input.

Dense generative models: Two types of generative models have been widely studied, namely VAE [54, 29] and GAN [17]. VAE uses extra encoder to constrain the distribution of the latent variable, and GAN designs a discriminator to distinguish real samples and the generated samples. VAE [29, 54] has been applied to various tasks such as medical image segmentation [3] and ambiguities modeling [30]. For salient object detection, [32] adopted a VAE to model the image background, and separate salient objects from the background through reconstruction residuals. [77, 76] design CVAE based frameworks to model the subjective nature of saliency. The main scenarios of using GAN [17] can be roughly divided into two categories, namely fully-supervised and semi-supervised. The former [18, 31] treats the discriminator as learnable loss function to distinguish model prediction and the ground truth, and the latter [55, 23] uses GAN to explore the contribution of the unlabeled set. ABP [76] has also been used for RGB-D salient object detection to model dataset bias.

3 Generative Transformer with Energy-Based Latent Space

3.1 Model

We formulate the supervised saliency prediction problem as a conditional generative learning problem. Let $\mathbf{I} \in \mathbb{R}^{h \times w \times 3}$ be an observed RGB image, $s \in \mathbb{R}^{h \times w \times 1}$ be the saliency map, and $z \in \mathbb{R}^{1 \times 1 \times d}$ be the d-dimensional vector of latent variables, where $h \times w \gg d$. Consider the following generative model to predict a saliency map s from an image $\mathbf{I}$,

$$s = T_\theta(\mathbf{I}, z) + \epsilon, \quad z \sim p_\alpha(z), \quad \epsilon \sim \mathcal{N}(0, \sigma_\epsilon^2 I), \tag{1}$$

where T_θ is the non-linear mapping process from $[z, \mathbf{I}]$ to s with parameters θ, $p_\alpha(z)$ is the prior distribution with parameters α, and $\epsilon \sim \mathcal{N}(0, \sigma_\epsilon^2 I)$ is the observation residual of saliency with σ_ϵ is given. Due to the stochasticity of the latent variables z, given an image $\mathbf{I}$, its saliency map is also stochastic. Such a probabilistic model is in accord with the uncertainty of the image saliency.

Following [46], the prior $p_\alpha(z)$ is not assumed to be a simple isotropic Gaussian distribution as GAN [17], VAE [29, 54] or ABP [19]. Specifically, it is in the form of the energy-based correction or exponential tilting [70] of an isotropic Gaussian reference distribution $p_0(z) = \mathcal{N}(0, \sigma_z^2 I)$, i.e.,

$$p_\alpha(z) = \frac{1}{Z(\alpha)} \exp\left[-U_\alpha(z)\right] p_0(z) \propto \exp\left[-U_\alpha(z) - \frac{1}{2\sigma_z^2}||z||^2\right], \tag{2}$$

where $\mathcal{E}_\alpha(z) = U_\alpha(z) + \frac{1}{2\sigma_z^2}||z||^2$ is the energy function that maps the latent variables z to a scalar, and $U_\alpha(z)$ is parameterized by a multi-layer perceptron (MLP) with parameters α. σ_z is a hyperparameter. $Z(\alpha) = \int \exp[-U_\alpha(z)]p_0(z)dz$ is the intractable normalizing constant that resolves the requirement for a probability distribution to have a total probability equal to one. $p_\alpha(z)$ is an informative prior in our model and needs to be estimated along with the non-linear mapping T_θ from the training data.

The mapping T_θ is parameterized by an image transformer [39] with self-attention mechanism, which encodes the image $\mathbf{I}$ and then decodes it along with the latent variables z to the saliency map s, thus, $p_\theta(s|\mathbf{I}, z) = \mathcal{N}(T_\theta(\mathbf{I}, z), \sigma_\epsilon^2 I)$. The resulting generative model is a conditional directed graphical model that combines the EBM prior [46] and the vision transformer [39].

3.2 Learning

The generative transformer with an energy-based prior, which is presented in Eq. (1), can be trained via maximum likelihood estimation. For notation simplicity, let $\beta = (\theta, \alpha)$. For the training examples $\{(\mathbf{I}_i, s_i), i = 1, ..., n\}$, the observed-data log-likelihood function is defined as

$$L(\beta) = \sum_{i=1}^{n} \log p_\beta(s_i|\mathbf{I}_i) = \sum_{i=1}^{n} \log\left[\int p_\beta(s_i, z_i|\mathbf{I}_i)dz_i\right] = \sum_{i=1}^{n} \log\left[\int p_\alpha(z_i)p_\theta(s_i|\mathbf{I}_i, z_i)dz_i\right].$$

Maximizing $L(\beta)$ is equivalent to minimizing the Kullback-Leibler (KL) divergence between the model $p_\beta(s|\mathbf{I})$ and the data distribution $p_{\text{data}}(s|\mathbf{I})$. The gradient of $L(\beta)$ can be computed based on

$$\nabla_\beta \log p_\beta(s|\mathbf{I}) = \mathrm{E}_{p_\beta(z|s,\mathbf{I})}\left[\nabla_\beta \log p_\beta(s,z|\mathbf{I})\right] = \mathrm{E}_{p_\beta(z|s,\mathbf{I})}[\nabla_\beta(\log p_\alpha(z) + \log p_\theta(s|\mathbf{I},z))], \quad (3)$$

where the posterior distribution $p_\beta(z|s,\mathbf{I}) = p_\beta(s,z|\mathbf{I})/p_\beta(s|\mathbf{I}) = p_\alpha(z)p_\theta(s|\mathbf{I},z)/p_\beta(s|\mathbf{I})$.

The learning gradient in Eq. (3) can be decomposed into two parts, i.e., the gradient for the energy-based model α

$$\mathrm{E}_{p_\beta(z|s,\mathbf{I})}[\nabla_\alpha \log p_\alpha(z)] = \mathrm{E}_{p_\alpha(z)}[\nabla_\alpha U_\alpha(z)] - \mathrm{E}_{p_\beta(z|s,\mathbf{I})}[\nabla_\alpha U_\alpha(z)], \quad (4)$$

and the gradient for the transformer θ

$$\mathrm{E}_{p_\beta(z|s,\mathbf{I})}[\nabla_\theta \log p_\theta(s|\mathbf{I},z)] = \mathrm{E}_{p_\beta(z|s,\mathbf{I})}\left[\frac{1}{\sigma_\epsilon^2}(s - T_\theta(\mathbf{I},z))\nabla_\theta T_\theta(\mathbf{I},z)\right]. \quad (5)$$

$\nabla_\alpha U_\alpha(z)$ in Eq. (4) and $\nabla_\theta T_\theta(\mathbf{I},z)$ in Eq. (5) can be efficiently computed via back-propagation. Both Eq. (4) and Eq. (5) include intractable expectation terms $\mathrm{E}_p(\cdot)$, which can be approximated by MCMC samples. To be specific, we can use a gradient-based MCMC, e.g., Langevin dynamics, which is initialized with a Gaussian noise distribution p_0, to draw samples from the energy-based prior model $p_\alpha(z) \propto \exp\left[-\mathcal{E}_\alpha(z)\right]$ by iterating

$$z_{t+1} = z_t - \delta\nabla_z\mathcal{E}_\alpha(z_t) + \sqrt{2\delta}e_t, \quad z_0 \sim p_0(z), \quad e_t \sim \mathcal{N}(0,I), \quad (6)$$

and draw samples from the posterior distribution $p_\beta(z|s,\mathbf{I})$ by iterating

$$z_{t+1} = z_t - \delta\left[\nabla_z\mathcal{E}_\alpha(z_t) - \frac{1}{\sigma_\epsilon^2}(s - T_\theta(\mathbf{I},z_t))\nabla_z T_\theta(\mathbf{I},z_t)\right] + \sqrt{2\delta}e_t, \quad z_0 \sim p_0(z), \quad e_t \sim \mathcal{N}(0,I). \quad (7)$$

δ is the Langevin step size and can be specified independently in Eq. (6) and Eq. (7). We use $\{z_i^+\}$ and $\{z_i^-\}$ to denote, respectively, the samples from the posterior distribution $p_\beta(z|s,\mathbf{I})$ and the prior distribution $p_\alpha(z)$. The gradients of α and θ can be computed with $\{(\mathbf{I}_i,s_i)\}$, $\{z_i^+\}$ and $\{z_i^-\}$ by

$$\nabla\alpha = \frac{1}{n}\sum_{i=1}^n[\nabla_\alpha U_\alpha(z_i^-)] - \frac{1}{n}\sum_{i=1}^n\left[\nabla_\alpha U_\alpha(z_i^+)\right], \quad (8)$$

$$\nabla\theta = \frac{1}{n}\sum_{i=1}^n\left[\frac{1}{\sigma_\epsilon^2}(s_i - T_\theta(\mathbf{I}_i,z_i^+))\nabla_\theta T_\theta(\mathbf{I}_i,z_i^+)\right], \quad (9)$$

We can update the parameters with $\nabla\alpha$ and $\nabla\theta$ via the Adam optimizer [28]. We present the full learning and sampling algorithm of our model in Algorithm 1.

Algorithm 1 Maximum likelihood learning algorithm for generative vision transformer with energy-based latent space for saliency prediction

---

Input: (1) Training images $\{\mathbf{I}_i\}_i^n$ with associated saliency maps $\{s_i\}_i^n$; (2) Number of learning iterations M; (3) Numbers of Langevin steps for prior and posterior $\{K^-, K^+\}$; (4) Langevin step sizes for prior and posterior $\{\delta^-, \delta^+\}$; (5) Learning rates for energy-based prior and transformer $\{\xi_\alpha, \xi_\theta\}$; (6) batch size n'.
Output: Parameters θ for the transformer and α for the energy-based prior model
 1: Initialize θ and α
 2: **for** $m \leftarrow 1$ to M **do**
 3:     Sample observed image-saliency pairs $\{(\mathbf{I}_i,s_i)\}_i^{n'}$
 4:     For each $(\mathbf{I}_i,s_i)$, sample the prior $z_i^- \sim p_{\alpha_t}(z)$ using K^- Langevin steps in Eq. (6) with a step size δ^-.
 5:     For each $(\mathbf{I}_i,s_i)$, sample the posterior $z_i^+ \sim p_{\beta_t}(z|s_i,\mathbf{I}_i)$ using K^+ Langevin steps in Eq. (7) with a step size δ^+.
 6:     Update energy-based prior by Adam with the gradient $\nabla\alpha$ computed in Eq. (8) and a learning rate ξ_α.
 7:     Update transformer by Adam with the gradient $\nabla\theta$ computed in Eq. (9) and a learning rate ξ_θ.
 8: **end for**

3.3   Network

Generative vision transformer: We design the generative vision transformer using the Swin transformer [39] backbone as shown in Figure 2, which takes a three-channel image $\mathbf{I}$ and the

latent variables z as input and output a one-channel saliency map $T_\theta(\mathbf{I}, z)$. Two main modules are included in our generative vision transformer, including a "Transformer Encoder" module and a "Feature Aggregation" module. The former takes $\mathbf{I}$ as input and produce a set of feature maps $\{f_l\}_{l=1}^5$ of channel sizes 128, 256, 512, 1024 and 1024, respectively, while the latter takes $\{f_l\}_{l=1}^5$ and the vector of latent variables z as input to generate the saliency prediction s.

Specifically, we first feed each f_l to a 3×3 convolutional layer to reduce the channel dimension to 32, and obtain a new set of feature maps $\{f_l'\}_{l=1}^5$ after channel reduction. Then, we replicate the vector z spatially and perform a channel-wise concatenation with f_5', followed by a 3×3 convolutional layer that seeks to produce a feature map

Figure 2: Generative latent variable vision transformer

F_5 with same number of channels as that of f_5'. Finally, we sequentially concatenate feature maps from high level to low level via feature aggregation, i.e., from $l = 4$ to 1, we compute $F_l = \text{Conv}_{3\times3}(\text{M}(\text{Concat}(f_l', F_{l+1}, ..., F_5)))$, where $\text{Conv}_{3\times3}(\cdot)$ is a 3×3 convolutional layer that reduces the channel dimension to 32, $\text{M}(\cdot)$ is the channel attention module [83], and $\text{Concat}(\cdot)$ is the channel-wise concatenation operation. Note that, we upsample the higher level feature map to the same spatial size as that of the lower level feature map before the concatenation operation. We feed F_1 to a 3×3 convolutional layer to obtain the one-channel saliency map $T_\theta(\mathbf{I}, z)$.

Energy-based prior model: We design an energy-based model for the latent variables by parameterizing the energy function via a multilayer perceptron (MLP), which uses three fully connected layers to map the latent variables z to the energy. The sizes of the feature maps of different layers of the MLP are $C_e, C_e, 1$ respectively, where we set $C_e = 60$ in our experiment. "GELU" [22] activation is used after each fully connected layer except the last one.

3.4 Analysis

Convergence: Theoretically, when the Adam optimizer of $\beta = (\theta, \alpha)$ in the learning algorithm converges to a local minimum, it solves the following estimating equations

$$\nabla\alpha = 0 \quad \Rightarrow \quad \frac{1}{n}\sum_{i=1}^n \text{E}_{p_\beta(z_i|s_i,\mathbf{I}_i)}[\nabla_\alpha U_\alpha(z_i)] - \text{E}_{p_\alpha(z)}[\nabla_\alpha U_\alpha(z)] = 0, \tag{10}$$

$$\nabla\theta = 0 \quad \Rightarrow \quad \frac{1}{n}\sum_{i=1}^n \text{E}_{p_\beta(z_i|s_i,\mathbf{I}_i)}\left[\frac{1}{\sigma_\epsilon^2}(s_i - T_\theta(\mathbf{I}_i, z_i))\nabla_\theta T_\theta(\mathbf{I}_i, z_i)\right] = 0, \tag{11}$$

which are the maximum likelihood estimating equations. However, in practise, the Langevin dynamics in Eq. (8) and Eq. (9) might not converge to the target distributions due to the use of a small number of Langevin steps (i.e., short-run MCMC), the estimating equations in Eq. (10) and Eq. (11) will correspond to a perturbation of the MLE estimating equation according to [43, 44, 46]. The learning algorithm can be justified as a Robbins-Monro [53] algorithm, whose convergence is theoretically sound. Our model can also be trained with an extra encoder as an amortized inference network [29] for $p_\beta(z|s, \mathbf{I})$ and an extra generator as an amortized sampling network [68, 69, 71] for $p_\alpha(z)$. In this work, we prefer to keep our training algorithm simple in order to avoid extra efforts for the design of the auxiliary network architectures. We will study the joint training strategy in our future work.

Accuracy: Compared with the GAN-based generative framework, our model is a likelihood-based generative framework that will not suffer from mode collapse [2]. In comparison with VAE-based generative framework, whose training is also based on likelihood, our MCMC-based maximum likelihood learning algorithm will not encounter the posterior collapse issue that is caused by amortized inference. On the other hand, the variational inference typically relies on an extra inference network for efficient inference of the latent variables given an image and saliency pair, however, the approximate inference might not be able to take the full place of the posterior distribution in practise. To be specific, we use $q_\phi(z|s, \mathbf{I})$ to denote the tractable approximate inference network with parameters ϕ. The variational inference seeks to optimize $\min_\beta \min_\phi \text{KL}(p_{\text{data}}(s|\mathbf{I})q_\phi(z|s, \mathbf{I})||p_\beta(z, s|\mathbf{I}))$, which can be further decomposed into $\min_\beta \min_\phi \text{KL}(p_{\text{data}}(s|\mathbf{I})||p_\beta(s|\mathbf{I})) + \text{KL}(q_\phi(z|s, \mathbf{I})||p_\beta(z|s, \mathbf{I}))$. That is, the variational inference maximizes the conditional data likelihood plus a KL-divergence between the approximate inference network and the posterior distribution. Only when the $\text{KL}(q_\phi(z|s, \mathbf{I})||p_\beta(z|s, \mathbf{I})) \to 0$,

Figure 3: Visual comparison of our model and the state-of-the-art saliency prediction model, the BBSNet [15]. From top to bottom: images, ground truth saliency maps, results of the BBSNet [15] and results obtained by our model.

the variational inference will lead to the MLE solution, which is exactly the objective of our model. However, there might exist a gap between them in practise due to the improper design of the inference network. Our learning algorithm is much simpler and more accurate than amortized inference.

Computational and memory costs analysis: From the learning perspective, due to the iterative Langevin sampling for the posterior and prior distributions of latent variables, our model is more time-consuming for training than generative models with amortized inference, such as VAE, which is roughly 2.4 times faster than ours on RGB image salient object detection. However, for VAE, the inference model is parameterized by another set of parameters, which need to be updated by back-propagation. In our model, the Langevin dynamics is not treated as a model because once the top-down generator is updated in each iteration, the posterior distribution can be derived from the generator. With the posterior distribution, the Langevin sampling is just an optimization-like process to find fair samples in the latent space defined by the posterior distribution. without relying on an extra inference network, our framework is efficient in memory and friendly for network design.

4   Experimental Results

4.1   Setup

Datasets: For RGB SOD, we train models on DUTS training set [60], and test them on five benchmark datasets, including DUTS testing set, ECSSD [74], DUT [75], HKU-IS [33] and PASCAL-S [34]. For RGB-D SOD, we follow the conventional training setting, in which the training set is a combination of 1,485 images from NJU2K dataset [27] and 700 images from NLPR dataset [48]. We test the trained models on NJU2K testing set, NLPR testing set, DES [8], SSB [45] and SIP [14] testing set.

Evaluation Metrics: We adopt four evaluation metrics to measure the performance, including Mean Absolute Error $\mathcal{M}$, Mean F-measure (F_β), Mean E-measure (E_ξ) [13] and S-measure (S_α) [12].

Implementation Details: Our generative transformer is built upon the Swin transformer [39] and uses it as the backbone of the encoder in our model. The Swin backbone can be initialized with the parameters pretrained on ImageNet-1K [9] for classification, and the other parameters of the newly added components, including the decoder part and the MLP of the energy based prior model, will be randomly initialized from the Gaussian distribution $\mathcal{N}(0, 0.01)$. Empirically we set dimension d of the latent variables z as $d = 32$. We set $\sigma_\epsilon = 1$ in Eq.(1) and $\sigma_z = 1$ in Eq.(2). We resize all the images and the saliency maps to the resolution of 384×384 to fit the Swin transformer. The maximum epoch is 50. The initial learning rates are 2.5×10^{-5}. The whole training takes 9 hours with a batch size of 6 on one NVIDIA GTX 2080Ti GPU for each model. During testing, our model can process 15 images per second.

4.2 Performance Comparison

We compare our framework with state-of-the-art RGB SOD models and RGB-D SOD models, and show a comparison of performance in Table 1 and Table 2 respectively, where "VST" is the only transformer based saliency detection model. We observe consistently better performance of the proposed frameworks. Especially for PASCAL-S dataset [34], which contains more than 40% examples with large salient objects, the significant performance gap between our method and the existing solutions demonstrates the effectiveness of our generative framework for saliency prediction. We further show a qualitative comparison between our RGB-D saliency prediction model and the BBSNet [15] in Figure 3. As we can see, our transformer-based framework, with the effective global context modeling, is superior to its competitor in detecting various sizes of salient objects.

Table 1: Performance comparison with benchmark RGB salient object detection models.

Method	DUTS [60]				ECSSD [74]				DUT [75]				HKU-IS [33]				PASCAL-S [34]			
	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$
CPD [65]	.869	.821	.898	.043	.913	.909	.937	.040	.825	.742	.847	.056	.906	.892	.938	.034	.848	.819	.882	.071
SCRN [66]	.885	.833	.900	.040	.920	.910	.933	.041	.837	.749	.847	.056	.916	.894	.935	.034	.869	.833	.892	.063
PoolNet [35]	.887	.840	.910	.037	.919	.913	.938	.038	.831	.748	.848	.054	.919	.903	.945	.030	.865	.835	.896	.065
BASNet [50]	.876	.823	.896	.048	.910	.913	.938	.040	.836	.767	.865	.057	.909	.903	.943	.032	.838	.818	.879	.076
EGNet [86]	.878	.824	.898	.043	.914	.906	.933	.043	.840	.755	.855	.054	.917	.900	.943	.031	.852	.823	.881	.074
F3Net [62]	.888	.852	.920	.035	.919	.921	.943	.036	.839	.766	.864	.053	.917	.910	.952	.028	.861	.835	.898	.062
ITSD [88]	.886	.841	.917	.039	.920	.916	.943	.037	.842	.767	.867	.056	.921	.906	.950	.030	.860	.830	.894	.066
LDF [63]	.892	.861	.925	.034	.919	.923	.943	.036	.839	.770	.865	.052	.920	.913	.953	.028	.860	.856	.901	.063
VST [38]	.896	.842	.918	.037	.932	.911	.943	.034	.850	.771	.869	.058	.928	.903	.950	.030	.873	.832	.900	.067
Ours	**.908**	**.875**	**.942**	**.029**	**.935**	**.935**	**.962**	**.026**	**.858**	**.797**	**.892**	**.051**	**.930**	**.922**	**.964**	**.023**	**.877**	**.855**	**.915**	**.054**

Table 2: Performance comparison with benchmark RGB-D salient object detection models.

Method	NJU2K [27]				SSB [45]				DES [8]				NLPR [48]				SIP [14]			
	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$
BBSNet [15]	.921	.902	.938	.035	.908	.883	.928	.041	.933	.910	.949	.021	.930	.896	.950	.023	.879	.868	.906	.055
BiaNet [84]	.915	.903	.934	.039	.904	.879	.926	.043	.931	.910	.948	.021	.925	.894	.948	.024	.883	.873	.913	.052
CoNet [26]	.911	.903	.944	.036	.896	.877	.939	.040	.906	.880	.939	.026	.900	.859	.937	.030	.868	.855	.915	.054
UCNet [77]	.897	.886	.930	.043	.903	.884	.938	.039	.934	.919	.967	.019	.920	.891	.951	.025	.875	.867	.914	.051
JLDCF [16]	.902	.885	.935	.041	.903	.873	.936	.040	.931	.907	.959	.021	.925	.894	.955	.022	.880	.873	.918	.049
DSA2F [57]	.903	.901	.923	.039	.904	.898	.933	.036	.920	.896	.962	.021	.918	.897	.950	.024	-	-	-	-
VST [38]	.922	.898	.939	.035	.913	.879	.937	.038	.943	.920	.965	.017	.932	.897	.951	.024	.904	.894	.933	.040
Ours	**.929**	**.924**	**.956**	**.028**	**.916**	**.898**	**.950**	**.032**	**.945**	**.928**	**.971**	**.016**	**.938**	**.921**	**.966**	**.018**	**.906**	**.908**	**.940**	**.037**

4.3 Backbone Analysis

To test the performance of the transformer structure proposed in Section 3.3, we compare it with an conventional convolutional backbone for salient object detection. We create the baseline by replacing the Swin encoder in our transformer structure by the ResNet50 [21] encoder and keeping the decoder part, i.e., the "Feature Aggregation" module in Figure 2 unchanged. We first test them without involving latent variables, which means that we train them in a discriminative manner. We use "our-Swin-D" to denote the model using the Swin encoder and "our-Res50-D" to denote the one using the ResNet50 encoder. Model performances in the task of RGB-D saliency detection are shown in Table. 3. We observe "our-Swin-D" outperforms "our-Res50-D", which clearly indicates the effectiveness of the transformer backbone for salient object detection.

Table 3: Analysis of backbone without involving latent variables.

Method	NJU2K [27]				SSB [45]				DES [8]				NLPR [48]				SIP [14]			
	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$
our-Res50-D	.908	.896	.931	.036	.906	.889	.927	.037	.918	.907	.948	.022	.921	.893	.951	.024	.874	.856	.917	.049
our-Swin-D	.919	.923	.947	.032	.914	.897	.943	.033	.931	.919	.959	.022	.933	.912	.951	.022	.897	.899	.931	.041

We further study the influence of different encoder backbones used in the proposed generative saliency prediction framework with an EBM prior. Table 4 and Table 5, respectively, depict the performance comparisons of our frameworks using different backbones in the tasks of RGB and RGB-D salient

Table 4: Performance of different backbones within the proposed model for RGB saliency detection.

Method	DUTS [60]				ECSSD [74]				DUT [75]				HKU-IS [33]				PASCAL-S [34]			
	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$
Ours-Res50	.890	.850	.927	.035	.918	.914	.944	.036	.837	.762	.867	.053	.917	.906	.952	.029	.859	.830	.896	.063
Ours-DPT	.899	.874	.940	.031	.924	.933	.956	.031	.854	.792	.890	.054	.922	.920	.960	.026	.870	.854	.911	.055
Ours-Swin	**.908**	**.875**	**.942**	**.029**	**.935**	**.935**	**.962**	**.026**	**.858**	**.797**	**.892**	**.051**	**.930**	**.922**	**.964**	**.023**	**.877**	**.855**	**.915**	**.054**

Table 5: Performance of different backbones within the proposed model for RGB-D saliency detection.

Method	NJU2K [27]				SSB [45]				DES [8]				NLPR [48]				SIP [14]			
	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$
Ours-Res50	.919	.909	.946	.033	.906	.882	.937	.038	.937	.925	.974	.017	.920	.892	.949	.025	.882	.872	.918	.049
Ours-DPT	.924	.913	.950	.031	.915	.892	.946	.034	.941	.921	.968	.017	.935	.913	.964	.019	.901	.903	.933	.038
Ours-Swin	**.929**	**.924**	**.956**	**.028**	**.916**	**.898**	**.950**	**.032**	**.945**	**.928**	**.971**	**.016**	**.938**	**.921**	**.966**	**.018**	**.906**	**.908**	**.940**	**.037**

object detection. In the context of our generative framework, we compare the ResNet50 encoder backbone and the Swin transformer encoder backbone. We also modify the DPT [52] backbone to adapt to the tasks of RGB and RGB-D salient object detection with our framework. The DPT built on the ViT transformer [10] is originally designed for semantic segmentation and depth estimation. The comparison results verify the effectiveness of the vision transformer used in our generative framework. In particular, our current solution with the Swin transformer encoder backbone can achieve the best performance for saliency prediction. Further, the performance gap between "our-Swin-D" in Table 3 and "our-Swin" in Table 5 indicates the effectiveness of the generative learning with latent space.

4.4 Generative Learning Analysis

Table 6: Performance of different generative models with transformer backbone for saliency detection.

Method	NJU2K [27]				SSB [45]				DES [8]				NLPR [48]				SIP [14]			
	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$	$S_\alpha \uparrow$	$F_\beta \uparrow$	$E_\xi \uparrow$	$\mathcal{M} \downarrow$
ABP	.920	.915	.951	.030	.910	.890	.942	.035	.935	.920	.962	.018	.930	.914	.962	.020	.900	.898	.935	.039
GAN	.928	.922	.954	.030	.913	.892	.941	.033	.940	.924	.969	.018	.934	.915	.961	.021	.901	.904	.937	.039
VAE	.928	.921	.955	.029	.914	.894	.947	.033	.942	.922	.970	.017	.934	.914	.961	.020	.904	.906	.935	.038
Ours	**.929**	**.924**	**.956**	**.028**	**.916**	**.898**	**.950**	**.032**	**.945**	**.928**	**.971**	**.016**	**.938**	**.921**	**.966**	**.018**	**.906**	**.908**	**.940**	**.037**

We compare our framework with other alternative generative solutions in Table 6. The results are reported in the task of RGB-D saliency detection. For fair comparison, we implement an ABP-based model [19], a GAN-based model [17], and a VAE-based model [29, 54] using the same transformer-based generator as ours. The latent variables in these models are still assumed to follow the isotropic Gaussian distribution, as in the original algorithms. For the ABP-based model, we use MCMC-based inference while training, and sample the latent variables directly from the Gaussian distribution during testing. For the GAN-based alternative, we design a fully convolutional discriminator [24] that consists of five 3×3 convolutional layers with a stride of 2 in each layer. The discriminator takes the concatenation of an image and a saliency map as an input, and is trained to distinguish between the predicted saliency map and the ground truth saliency map given an image. The numbers of the output channels of the discriminators are $64, 64, 64, 64$ and 1. For the VAE-based alternative, we introduce an extra encoder as an approximate Gaussian inference model via the reparameterization trick. The encoder consists of four 4×4 convolutional layers with a stride of 2 in each layer and maps the concatenation of an image and a saliency map to feature maps of channel sizes $64, 64, 64$ and 64 sequentially. After that, two fully connected layers are adopted to produce the mean and the standard deviation of the inference model. For all the three alternative generative models, we set the numbers of the dimension of the latent space the same as that in our model, which is $d = 32$. Compared with the deterministic baseline "our-Swin-D" in Table 3, the three generative frameworks achieve better or comparable performance. Especially in DES dataset [8], the alternative generative models achieve a large performance improvement. Our model outperforms all these alternative generative solutions, showing the effectiveness of the EBM prior used in our model.

4.5 Hyperparameter Analysis

The main hyperparameters in our framework include the number of Langevin steps K, the Langevin step size δ, the number of dimensions of the latent space d, and the size of EBM C_e. We have two sets of hyperparameters $\{\delta^-, K^-\}$ and $\{\delta^+, K^+\}$ of Langevin dynamics for sampling from the prior distribution and the posterior distribution, respectively. For the Langevin step size, we find stable model performance with $\delta^- = 0.4 \pm 0.2$ and $\delta^+ = [0.05, 0.3]$, and we set $\delta^- = 0.4$, $\delta^+ = 0.1$ in this paper. For the number of Langevin steps, we empirically set $K^- = K^+ = 5$ to achieve a trade-off between the training efficiency and the model performance, as more Langevin steps will lead to longer training time but more convergent inference results. Additionally, we investigate the influence of the number of latent dimensions by varying $d = \{8, 16, 32, 64\}$, and observe comparable performance among different choices of d. We also investigate the influence of the EBM size by varying $C_e = \{20, 60, 100\}$, and show the results in Table 7. Among those models, we find $C_e = 60$ can provide optimal prediction performance. We set $d = 32$ and $C_e = 60$ in our paper.

Table 7: Influence of the size of the EBM prior model

Method	NJU2K [27] $S_\alpha\uparrow$	$F_\beta\uparrow$	$E_\xi\uparrow$	$\mathcal{M}\downarrow$	SSB [45] $S_\alpha\uparrow$	$F_\beta\uparrow$	$E_\xi\uparrow$	$\mathcal{M}\downarrow$	DES [8] $S_\alpha\uparrow$	$F_\beta\uparrow$	$E_\xi\uparrow$	$\mathcal{M}\downarrow$	NLPR [48] $S_\alpha\uparrow$	$F_\beta\uparrow$	$E_\xi\uparrow$	$\mathcal{M}\downarrow$	SIP [14] $S_\alpha\uparrow$	$F_\beta\uparrow$	$E_\xi\uparrow$	$\mathcal{M}\downarrow$
$C_e = 20$	**.930**	.913	.957	**.026**	**.917**	.898	.950	.030	**.951**	.921	.970	.016	.937	.913	.950	.022	.901	.892	.931	.037
$C_e = 100$	.926	.904	.950	.031	.916	.891	**.952**	.031	.942	**.930**	.970	**.016**	**.939**	.913	.960	.021	.903	.895	.934	**.036**
Ours ($C_e = 60$)	.929	**.924**	**.956**	.028	.916	**.898**	.950	.032	.945	.928	**.971**	**.016**	.938	**.921**	**.966**	**.018**	**.906**	**.908**	**.940**	.037

4.6 Explainability Analysis

As a generative model, our framework is capable of obtaining a meaningful uncertainty map that summarizes the stochastic behavior of the model in performing saliency prediction. The uncertainty in our paper refers to the stochastic property of generating the saliency prediction from an input image, which is captured by the probabilistic model $p_\beta(s|\mathbf{I})$. A generative saliency prediction method can not only provide accurate predictions but also reasonable uncertainty maps that represents "subjective nature" of human visual saliency. In this section, we propose to use the uncertainty map to qualitatively evaluate different generative saliency prediction frameworks. Specifically, we propose to compute the uncertainty map as the variance of multiple saliency predictions produced from the learned probabilistic model. In the experiment, for each input image, we output ten saliency maps by using Langevin sampling from the learned conditional distribution, and compute the variance map (uncertainty) based on the generated predictions.

To quantify the complexity of a color image, we calculate the complexity score by the following way: (i) we first over-segment the image with the SLIC [1] to obtain 200 superpixels, (ii) then we compute the similarity of each superpixel with the others using handcrafted features from [89], which gives us a 200 dimensional contrast based vector, representing the overall image contrast, (iii) we define the complexity of the image as the mean entropy of the contrast vector. The higher the score, the more complicated the image. In general, a reasonable generative saliency prediction model should have more confident predictions on images with simpler backgrounds (i.e., lower complexity scores), and less confident predictions on images with complicated backgrounds (i.e., higher complexity scores).

In Figure 4, we compare the uncertainty maps of different generative models that we have presented in Section 4.4. For each row of Figure 4, we display an input image, which is tagged with a image complexity score, and the associated ground truth saliency map, followed by the predicted saliency maps and the uncertainty maps obtained by the ABP-based model, the GAN-based model, the VAE-based model, and our model, respectively. As shown in Figure 4, the complexity score of each image is consistent with human perception. We observe that the uncertainty maps obtained from the other generative models fail to reflect the difficulties of the images for saliency predictions. For example, the image shown in the first row has a structured foreground (i.e., a temple) and a textured background (i.e., forest), which leads to a large ambiguity of the boundary between the foreground and the background. The uncertainty map obtained by our model indicates a big variance around the boundary region, which demonstrates the explainability and the reasonability of our model. Note that only generative saliency prediction frameworks can provide such an explainability analysis based on the uncertainty maps, which might motivate us to develop generative frameworks for the goal of explainable saliency prediction.

Figure 4: A comparison of uncertainty maps obtained by different generative saliency prediction frameworks for explainability analysis. Each row represents one example, in which we display an image tagged with a complexity score, the corresponding ground truth saliency map, as well as the predicted saliency maps and the uncertainty maps obtained by different generative frameworks.

5   Conclusion and Discussion

In this paper, we study the generative modeling of vision transformer for salient object detection. We start from defining a conditional probability distribution of saliency map given an image by a top-down latent variable generative framework, in which the non-linear mapping from image to saliency map is parameterized by a proposed vision transformer and the prior distribution of the low-dimensional latent space is represented by an energy-based model. Instead of using amortized inference and sampling strategies, we learn the model by the MCMC-based maximum likelihood where Langevin sampling is used to evaluate the intractable posterior and prior distributions of the latent variables for calculating the gradients of the log-likelihood with respect to the model parameters. With the informative energy-based prior and the expressive top-down vision transformer, our model can achieve both accurate predictions and meaningful uncertainty maps that are consistent with human perception.

From the machine learning perspective, our model is a likelihood-based top-down deep conditional generative model, which is neither CGAN nor CVAE, and is trained without relying on any assisting network. The learning algorithm derived from the proposed model is based on MCMC inference for the posterior and MCMC sampling for the prior, which is more natural, principled, and statistically rigorous. Such a framework is not only useful for saliency prediction (Though this is what we target in our paper) but also applicable to a vast of conditional learning scenarios, such as semantic segmentation, image-to-image translation, etc. Thus, the proposed generative model and the learning algorithm are generic and universal.

From the computer vision perspective, our model with a special network design to handle saliency prediction is a new member of the family of saliency prediction methods. Compared with the traditional discriminative saliency prediction methods and the existing generative ones, our generative method not only shows that it is more natural and reasonable to model the saliency prediction as a conditional probability distribution but also demonstrates impressive performances over all RGB and RGB-D benchmarks. As we know, the computer vision community has started to develop vision transformers for classification, segmentation, detection, generation, etc. Our paper is the first generative saliency prediction transformer. Thus, the proposed framework is significantly important for the computer vision community.

References

[1] Radhakrishna Achanta, Appu Shaji, Kevin Smith, Aurélien Lucchi, Pascal Fua, and Sabine Süsstrunk. Slic superpixels. *Technical report, EPFL*, 06 2010.

[2] Sanjeev Arora, Andrej Risteski, and Yi Zhang. Do gans learn the distribution? some theory and empirics. In *International Conference on Learning Representations (ICLR)*, 2018.

[3] Christian F. Baumgartner, Kerem Can Tezcan, Krishna Chaitanya, Andreas M. Hötker, Urs J. Muehlematter, Khoschy Schawkat, Anton S. Becker, Olivio Donati, and Ender Konukoglu. Phiseg: Capturing uncertainty in medical image segmentation. In *The 24th International Conference on Medical Image Computing and Computer Assisted Intervention (MICCAI)*, pages 119–127, 2019.

[4] Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European Conference on Computer Vision (ECCV)*, pages 213–229, 2020.

[5] Hao Chen and Youfu Li. Progressively complementarity-aware fusion network for RGB-D salient object detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3051–3060, 2018.

[6] Shuo Chen, Tan Yu, and Ping Li. Mvt: Multi-view vision transformer for 3d object recognition. In *British Machine Vision Conference (BMVC)*, 2021.

[7] Ming-Ming Cheng, Niloy J. Mitra, Xiaolei Huang, Philip H. S. Torr, and Shi-Min Hu. Global contrast based salient region detection. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 37(3):569–582, 2015.

[8] Yupeng Cheng, Huazhu Fu, Xingxing Wei, Jiangjian Xiao, and Xiaochun Cao. Depth enhanced saliency detection method. In *Proceedings of International Conference on Internet Multimedia Computing and Service*, pages 23–27, 2014.

[9] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 248–255, 2009.

[10] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations (ICLR)*, 2021.

[11] Kumar Avinava Dubey, Sashank J. Reddi, Sinead A. Williamson, Barnabás Póczos, Alexander J. Smola, and Eric P. Xing. Variance reduction in stochastic gradient langevin dynamics. In *Conference on Neural Information Processing Systems (NIPS)*, pages 1154–1162, 2016.

[12] Deng-Ping Fan, Ming-Ming Cheng, Yun Liu, Tao Li, and Ali Borji. Structure-measure: A new way to evaluate foreground maps. In *IEEE International Conference on Computer Vision (ICCV)*, pages 4548–4557, 2017.

[13] Deng-Ping Fan, Cheng Gong, Yang Cao, Bo Ren, Ming-Ming Cheng, and Ali Borji. Enhanced-alignment measure for binary foreground map evaluation. In *International Joint Conference on Artificial Intelligence (IJCAI)*, pages 698–704, 2018.

[14] Deng-Ping Fan, Zheng Lin, Zhao Zhang, Menglong Zhu, and Ming-Ming Cheng. Rethinking RGB-D Salient Object Detection: Models, Datasets, and Large-Scale Benchmarks. *IEEE Transactions on Neural Networks and Learning Systems (TNNLS)*, 2020.

[15] Deng-Ping Fan, Yingjie Zhai, Ali Borji, Jufeng Yang, and Ling Shao. BBS-Net: RGB-D salient object detection with a bifurcated backbone strategy network. In *European Conference on Computer Vision (ECCV)*, pages 275–292, 2020.

[16] Keren Fu, Deng-Ping Fan, Ge-Peng Ji, and Qijun Zhao. JL-DCF: Joint learning and densely-cooperative fusion framework for RGB-D salient object detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3052–3062, 2020.

[17] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Conference on Neural Information Processing Systems (NIPS)*, pages 2672–2680, 2014.

[18] Rick Groenendijk, Sezer Karaoglu, Theo Gevers, and Thomas Mensink. On the benefit of adversarial training for monocular depth estimation. *Computer Vision and Image Understanding*, 190:102848, 2020.

[19] Tian Han, Yang Lu, Song-Chun Zhu, and Ying Nian Wu. Alternating back-propagation for generator network. In *AAAI Conference on Artificial Intelligence (AAAI)*, page 1976–1984, 2017.

[20] Junxian He, Daniel Spokoyny, Graham Neubig, and Taylor Berg-Kirkpatrick. Lagging inference networks and posterior collapse in variational autoencoders. In *International Conference on Learning Representations (ICLR)*, 2019.

[21] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, 2016.

[22] Dan Hendrycks and Kevin Gimpel. Gaussian error linear units (gelus). *arXiv preprint arXiv:1606.08415*, 2016.

[23] W.-C. Hung, Y.-H. Tsai, Y.-T. Liou, Y.-Y. Lin, and M.-H. Yang. Adversarial learning for semi-supervised semantic segmentation. In *British Machine Vision Conference (BMVC)*, 2018.

[24] Wei-Chih Hung, Yi-Hsuan Tsai, Yan-Ting Liou, Yen-Yu Lin, and Ming-Hsuan Yang. Adversarial learning for semi-supervised semantic segmentation. In *British Machine Vision Conference (BMVC)*, 2018.

[25] Wei Ji, Jingjing Li, Shuang Yu, Miao Zhang, Yongri Piao, Shunyu Yao, Qi Bi, Kai Ma, Yefeng Zheng, Huchuan Lu, and Li Cheng. Calibrated rgb-d salient object detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9471–9481, 2021.

[26] Wei Ji, Jingjing Li, Miao Zhang, Yongri Piao, and Huchuan Lu. Accurate RGB-D salient object detection via collaborative learning. In *European Conference on Computer Vision (ECCV)*, 2020.

[27] Ran Ju, Yang Liu, Tongwei Ren, Ling Ge, and Gangshan Wu. Depth-aware salient object detection using anisotropic center-surround difference. *Signal Processing: Image Communication*, 38:115 – 126, 2015.

[28] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun, editors, *International Conference on Learning Representations (ICLR)*, 2015.

[29] Diederik P Kingma and Max Welling. Auto-encoding variational bayes. In *International Conference on Learning Representations (ICLR)*, 2013.

[30] Simon Kohl, Bernardino Romera-Paredes, Clemens Meyer, Jeffrey De Fauw, Joseph R. Ledsam, Klaus Maier-Hein, S. M. Ali Eslami, Danilo Jimenez Rezende, and Olaf Ronneberger. A probabilistic u-net for segmentation of ambiguous images. In *Conference on Neural Information Processing Systems (NeurIPS)*, pages 6965–6975, 2018.

[31] Quang H. Le, Kamal Youcef-Toumi, Dzmitry Tsetserukou, and Ali Jahanian. Gan mask r-cnn:instance semantic segmentation benefits from generative adversarial networks. *arXiv preprint arXiv:2010.13757*, 2020.

[32] Bo Li, Zhengxing Sun, and Yuqi Guo. Supervae: Superpixelwise variational autoencoder for salient object detection. In *AAAI Conference on Artificial Intelligence (AAAI)*, pages 8569–8576, 2019.

[33] Guanbin Li and Yizhou Yu. Visual saliency based on multiscale deep features. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5455–5463, 2015.

[34] Yin Li, Xiaodi Hou, Christof Koch, James M Rehg, and Alan L Yuille. The secrets of salient object segmentation. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 280–287, 2014.

[35] Jiang-Jiang Liu, Qibin Hou, Ming-Ming Cheng, Jiashi Feng, and Jianmin Jiang. A simple pooling-based design for real-time salient object detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

[36] Jun S Liu. *Monte Carlo strategies in scientific computing*. Springer Science & Business Media, 2008.

[37] Nian Liu, Junwei Han, and Ming-Hsuan Yang. Picanet: Learning pixel-wise contextual attention for saliency detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3089–3098, 2018.

[38] Nian Liu, Ni Zhang, Kaiyuan Wan, Ling Shao, and Junwei Han. Visual saliency transformer. In *IEEE International Conference on Computer Vision (ICCV)*, pages 4722–4732, 2021.

[39] Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *IEEE International Conference on Computer Vision (ICCV)*, 2021.

[40] Zhiming Luo, Akshaya Mishra, Andrew Achkar, Justin Eichel, Shaozi Li, and Pierre-Marc Jodoin. Non-local deep features for salient object detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017.

[41] Weian Mao, Yongtao Ge, Chunhua Shen, Zhi Tian, Xinlong Wang, and Zhibin Wang. Tfpose: Direct human pose estimation with transformers. *arXiv preprint arXiv:2103.15320*, 2021.

[42] Radford M Neal et al. Mcmc using hamiltonian dynamics. *Handbook of markov chain monte carlo*, 2(11):2, 2011.

[43] Erik Nijkamp, Mitch Hill, Song-Chun Zhu, and Ying Nian Wu. Learning non-convergent non-persistent short-run MCMC toward energy-based model. In *Conference on Neural Information Processing Systems (NeurIPS)*, pages 5233–5243, 2019.

[44] Erik Nijkamp, Bo Pang, Tian Han, Linqi Zhou, Song-Chun Zhu, and Ying Nian Wu. Learning multi-layer latent variable model via variational optimization of short run mcmc for approximate inference. In *European Conference on Computer Vision (ECCV)*, pages 361–378. Springer, 2020.

[45] Yuzhen Niu, Yujie Geng, Xueqing Li, and Feng Liu. Leveraging stereopsis for saliency analysis. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 454–461, 2012.

[46] Bo Pang, Tian Han, Erik Nijkamp, Song-Chun Zhu, and Ying Nian Wu. Learning latent space energy-based prior model. In *Conference on Neural Information Processing Systems (NeurIPS)*, 2020.

[47] Bo Pang and Ying Nian Wu. Latent space energy-based model of symbol-vector coupling for text generation and classification. In Marina Meila and Tong Zhang, editors, *International Conference on Machine Learning (ICML)*, pages 8359–8370, 2021.

[48] Houwen Peng, Bing Li, Weihua Xiong, Weiming Hu, and Rongrong Ji. RGBD salient object detection: A benchmark and algorithms. In *European Conference on Computer Vision (ECCV)*, pages 92–109, 2014.

[49] Yongri Piao, Wei Ji, Jingjing Li, Miao Zhang, and Huchuan Lu. Depth-induced multi-scale recurrent attention network for saliency detection. In *IEEE International Conference on Computer Vision (ICCV)*, pages 7254–7263, 2019.

[50] Xuebin Qin, Zichen Zhang, Chenyang Huang, Chao Gao, Masood Dehghan, and Martin Jagersand. Basnet: Boundary-aware salient object detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 7479–7489, 2019.

[51] Liangqiong Qu, Shengfeng He, Jiawei Zhang, Jiandong Tian, Yandong Tang, and Qingxiong Yang. RGBD salient object detection via deep fusion. *IEEE Transactions on Image Processing (TIP)*, 26(5):2274–2285, 2017.

[52] René Ranftl, Alexey Bochkovskiy, and Vladlen Koltun. Vision transformers for dense prediction. In *IEEE International Conference on Computer Vision (ICCV)*, pages 12179–12188, 2021.

[53] Herbert Robbins and Sutton Monro. A stochastic approximation method. *The annals of mathematical statistics*, pages 400–407, 1951.

[54] Kihyuk Sohn, Honglak Lee, and Xinchen Yan. Learning structured output representation using deep conditional generative models. In *Conference on Neural Information Processing Systems (NIPS)*, pages 3483–3491, 2015.

[55] Nasim Souly, Concetto Spampinato, and Mubarak Shah. Semi supervised semantic segmentation using generative adversarial network. In *IEEE International Conference on Computer Vision (ICCV)*, pages 5689–5697, 2017.

[56] Lucas Stoffl, Maxime Vidal, and Alexander Mathis. End-to-end trainable multi-instance pose estimation with transformers. *arXiv preprint arXiv:2103.12115*, 2021.

[57] Peng Sun, Wenhu Zhang, Huanyu Wang, Songyuan Li, and Xi Li. Deep rgb-d saliency detection with depth-sensitive attention and automatic multi-modal fusion. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1407–1417, 2021.

[58] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Conference on Neural Information Processing Systems (NIPS)*, pages 5998–6008, 2017.

[59] Bo Wang, Quan Chen, Min Zhou, Zhiqiang Zhang, Xiaogang Jin, and Kun Gai. Progressive feature polishing network for salient object detection. In *AAAI Conference on Artificial Intelligence (AAAI)*, pages 12128–12135, 2020.

[60] Lijun Wang, Huchuan Lu, Yifan Wang, Mengyang Feng, Dong Wang, Baocai Yin, and Xiang Ruan. Learning to detect salient objects with image-level supervision. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 136–145, 2017.

[61] Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, Tong Lu, Ping Luo, and Ling Shao. Pyramid vision transformer: A versatile backbone for dense prediction without convolutions. In *IEEE International Conference on Computer Vision (ICCV)*, pages 568–578, 2021.

[62] Jun Wei, Shuhui Wang, and Qingming Huang. F^{3}net: Fusion, feedback and focus for salient object detection. In *AAAI Conference on Artificial Intelligence (AAAI)*, pages 12321–12328, 2020.

[63] Jun Wei, Shuhui Wang, Zhe Wu, Chi Su, Qingming Huang, and Qi Tian. Label decoupling framework for salient object detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 13025–13034, 2020.

[64] Max Welling and Yee Whye Teh. Bayesian learning via stochastic gradient langevin dynamics. In *International Conference on Machine Learning (ICML)*, pages 681–688, 2011.

[65] Zhe Wu, Li Su, and Qingming Huang. Cascaded partial decoder for fast and accurate salient object detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3902–3911, 2019.

[66] Zhe Wu, Li Su, and Qingming Huang. Stacked cross refinement network for edge-aware salient object detection. In *IEEE International Conference on Computer Vision (ICCV)*, pages 7264–7273, 2019.

[67] Jianwen Xie, Ruiqi Gao, Zilong Zheng, Song-Chun Zhu, and Ying Nian Wu. Learning dynamic generator model by alternating back-propagation through time. In *AAAI Conference on Artificial Intelligence (AAAI)*, pages 5498–5507, 2019.

[68] Jianwen Xie, Yang Lu, Ruiqi Gao, and Ying Nian Wu. Cooperative learning of energy-based model and latent variable model via MCMC teaching. In *AAAI Conference on Artificial Intelligence (AAAI)*, pages 4292–4301, 2018.

[69] Jianwen Xie, Yang Lu, Ruiqi Gao, Song-Chun Zhu, and Ying Nian Wu. Cooperative training of descriptor and generator networks. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 42(1):27–45, 2018.

[70] Jianwen Xie, Yang Lu, Song-Chun Zhu, and Yingnian Wu. A theory of generative convnet. In *International Conference on Machine Learning (ICML)*, pages 2635–2644, 2016.

[71] Jianwen Xie, Zilong Zheng, and Ping Li. Learning energy-based model with variational auto-encoder as amortized sampler. In *AAAI Conference on Artificial Intelligence (AAAI)*, pages 10441–10451, 2021.

[72] Yihong Xu, Yutong Ban, Guillaume Delorme, Chuang Gan, Daniela Rus, and Xavier Alameda-Pineda. Transcenter: Transformers with dense queries for multiple-object tracking. *arXiv preprint arXiv:2103.15145*, 2021.

[73] Bin Yan, Houwen Peng, Jianlong Fu, Dong Wang, and Huchuan Lu. Learning spatio-temporal transformer for visual tracking. In *IEEE International Conference on Computer Vision (ICCV)*, pages 10448–10457, 2021.

[74] Qiong Yan, Li Xu, Jianping Shi, and Jiaya Jia. Hierarchical saliency detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1155–1162, 2013.

[75] Chuan Yang, Lihe Zhang, Huchuan Lu, Xiang Ruan, and Ming-Hsuan Yang. Saliency detection via graph-based manifold ranking. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3166–3173, 2013.

[76] Jing Zhang, Deng-Ping Fan*, Yuchao Dai, Saeed Anwar, Fatemeh Sadat Saleh, Sadegh Aliakbarian, and Nick Barnes. Uncertainty inspired rgb-d saliency detection. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 2021.

[77] Jing Zhang, Deng-Ping Fan, Yuchao Dai, Saeed Anwar, Fatemeh Sadat Saleh, Tong Zhang, and Nick Barnes. Uc-net: Uncertainty inspired rgb-d saliency detection via conditional variational autoencoders. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 8582 – 8591, 2020.

[78] Jing Zhang, Deng-Ping Fan, Yuchao Dai, Xin Yu, Yiran Zhong, Nick Barnes, and Ling Shao. Rgb-d saliency detection via cascaded mutual information minimization. In *IEEE International Conference on Computer Vision (ICCV)*, pages 4338–4347, 2021.

[79] Jing Zhang, Jianwen Xie, and Nick Barnes. Learning noise-aware encoder-decoder from noisy labels by alternating back-propagation for saliency detection. In *European Conference on Computer Vision (ECCV)*, pages 349–366, 2020.

[80] Jing Zhang, Xin Yu, Aixuan Li, Peipei Song, Bowen Liu, and Yuchao Dai. Weakly-supervised salient object detection via scribble annotations. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 12543–12552, 2020.

[81] Miao Zhang, Jingjing Li, Wei Ji, Yongri Piao, and Huchuan Lu. Memory-oriented decoder for light field salient object detection. In *Conference on Neural Information Processing Systems (NeurIPS)*, pages 896–906, 2019.

[82] Miao Zhang, Weisong Ren, Yongri Piao, Zhengkun Rong, and Huchuan Lu. Select, supplement and focus for RGB-D saliency detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3472–3481, 2020.

[83] Yulun Zhang, Kunpeng Li, Kai Li, Lichen Wang, Bineng Zhong, and Yun Fu. Image super-resolution using very deep residual channel attention networks. In *European Conference on Computer Vision (ECCV)*, pages 286–301, 2018.

[84] Zhao Zhang, Zheng Lin, Jun Xu, Wenda Jin, Shao-Ping Lu, and Deng-Ping Fan. Bilateral attention network for RGB-D salient object detection. *IEEE Transactions on Image Processing (TIP)*, 30:1949–1961, 2021.

[85] Jia-Xing Zhao, Yang Cao, Deng-Ping Fan, Ming-Ming Cheng, Xuan-Yi Li, and Le Zhang. Contrast prior and fluid pyramid integration for RGBD salient object detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3927–3936, 2019.

[86] Jia-Xing Zhao, Jiang-Jiang Liu, Deng-Ping Fan, Yang Cao, Jufeng Yang, and Ming-Ming Cheng. Egnet:edge guidance network for salient object detection. In *IEEE International Conference on Computer Vision (ICCV)*, pages 8778–8787, 2019.

[87] Sixiao Zheng, Jiachen Lu, Hengshuang Zhao, Xiatian Zhu, Zekun Luo, Yabiao Wang, Yanwei Fu, Jianfeng Feng, Tao Xiang, Philip HS Torr, and Li Zhang. Rethinking semantic segmentation from a sequence-to-sequence perspective with transformers. *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021.

[88] Huajun Zhou, Xiaohua Xie, Jian-Huang Lai, Zixuan Chen, and Lingxiao Yang. Interactive two-stream decoder for accurate and fast saliency detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9141–9150, 2020.

[89] Wangjiang Zhu, Shuang Liang, Yichen Wei, and Jian Sun. Saliency optimization from robust background detection. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2814–2821, 2014.