On the Tradeoff Between Robustness and Fairness

Xinsong Ma
School of computer science
Wuhan University
maxinsong1018@gmail.com

Zekai Wang
School of computer science
Wuhan University
wzekai99@gmail.com

Weiwei Liu[*]
School of computer science
Wuhan University
liuweiwei863@gmail.com

Abstract

Interestingly, recent experimental results [2, 26] have identified a robust fairness phenomenon in adversarial training (AT), namely that a robust model well-trained by AT exhibits a remarkable disparity of standard accuracy and robust accuracy among different classes compared with natural training. However, the effect of different perturbation radii in AT on robust fairness has not been studied, and one natural question is raised: does a tradeoff exist between average robustness and robust fairness? Our extensive experimental results provide an affirmative answer to this question: with an increasing perturbation radius, stronger AT will lead to a larger class-wise disparity of robust accuracy. Theoretically, we analyze the class-wise performance of adversarially trained linear models with mixture Gaussian distribution. Our theoretical results support our observations. Moreover, our theory shows that adversarial training easily leads to more serious robust fairness issue than natural training. Motivated by theoretical results, we propose a fairly adversarial training (FAT) method to mitigate the tradeoff between average robustness and robust fairness. Experimental results validate the effectiveness of our proposed method.

1 Introduction

Deep neural networks (DNN) have achieved impressive performance on numerous challenging tasks ranging from computer vision [10, 16] and natural language processing [9, 11] to autonomous driving. Despite this success, it turns out that DNN is vulnerable to adversarial examples. In other words, very small and even imperceptible perturbations are sufficient to deceive DNN models, resulting in erroneous predictions [7, 8, 12, 19]. As one of the most popular methods against adversarial examples, adversarial training (AT) can effectively improve model's robustness [17, 21, 24, 29].

Recently, numerous authors [2, 26] have identified an interesting robust fairness phenomenon in AT, specifically that a robust model well-trained by AT exhibits a remarkable disparity of standard accuracy and robust accuracy among different classes compared with natural training. Usually, the performance of a naturally trained model is similar across classes. However, adversarially trained models tend to perform well in some classes and poorly in others, which will lay serious hidden dangers for some applications. For example, an autonomous driving system may achieve a satisfying average robust accuracy for recognizing objects in the road. Nevertheless, this system is robust to the classes of inanimate objects (high robust accuracy) but vulnerable to some important classes

---

[*]Corresponding author

(a) ResNet18   (b) ResNet50   (c) WRN-32-10

Figure 1: The variance of class-wise robust accuracy for Madry using ResNet18, ResNet50 and WRN-32-10 on CIFAR-10. The perturbation radii for AT are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM with testing perturbation radius $\epsilon_{test} = 16/255$.

(a) ResNet18   (b) ResNet50   (c) WRN-32-10

Figure 2: The average robust accuracy for Madry using ResNet18, ResNet50 and WRN-32-10 on CIFAR-10. The perturbation radii for AT are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM with testing perturbation radius $\epsilon_{test} = 16/255$.

such as human (low robust accuracy), which is a "snake" in the grass for drivers and pedestrians in the road. Additionally, in many sensitive fields related to social ethics, it is crucial to ensure that the models have no discriminatory behaviors toward certain classes (groups or populations). It is therefore imperative to conduct in-depth study on the robust fairness issue. Notably, the effect of different perturbation radii in AT on robust fairness has not been studied. When further considering the robust fairness phenomenon in AT, one natural question arises:

> Is there a tradeoff between average robustness and robust fairness; specifically, as the perturbation radius increases, will stronger adversarially trained models lead to a larger class-wise disparity of robust accuracy among different classes?

This paper attempts to provide an understanding of the robust fairness phenomenon in AT and study the tradeoff between average robustness and robust fairness. Following [5, 18], we use the variance of class-wise robust accuracy to quantitatively measure model's robust fairness. Our experimental results in Figures 1 and 2 provide an affirmative answer to this question, suggesting that there is a tradeoff between average robustness and robust fairness: with the increasing perturbation radius, AT is able to improve the average robust accuracy of models over classes, but AT also leads to a larger variance of class-wise robust accuracy. Theoretically, we analyze the class-wise performance of adversarially trained linear models with mixture Gaussian distribution. Our theoretical results support our observations. Moreover, our theory shows that AT easily results in more serious fairness issue compared with natural training. Motivated by our theoretical results, we propose a variance-based regularized method to mitigate the tradeoff between average robustness and robust fairness. Our core contributions can be summarized as:

- We empirically find the relation between the variance of class-wise robust accuracy and perturbation radius in AT, namely that AT with larger perturbation radius will lead to larger variance of class-wise robust accuracy while average robust accuracy is improved, which suggests that there exists a tradeoff between robustness and fairness;

- We theoretically analyze this new phenomenon above and provide a potential explanation for it through linear model with mixture Gaussian distribution. Additionally, we theoretically prove that AT can lead to severer robust fairness issue compared with natural training;

- We propose FAT to mitigate the tradeoff between robustness and fairness, and experimental results validate the effectiveness of our proposed method.

2 Related Work

Adversarial training Madry [17] proposes adversarial training (AT) to improve the robustness of the model against adversarial examples. Some variants of AT have also been presented. For example, [21, 29] propose different regularization terms. [4, 22] add unlabeled data to the training set. [25] propose an algorithm to accelerate training process. A large number of works [6, 14, 23] have studied the tradeoff between robustness and accuracy. Among these, TRADES [29] is one of the most popular methods due to its promising experimental results. We take the two classical methods, Madry and TRADES, as our benchmarks.

Robust fairness Recently, [2, 20, 26] have identified the phenomenon of class-wise disparity of robustness and describe it as a robust fairness problem. [26] point out that AT can lead to larger class-wise disparity of standard accuracy compared with natural training and focus on adversarial training algorithms. Different from [2, 20, 26], this paper focuses on exploring the relation between the perturbation radius in AT and class-wise disparity of robust accuracy, and further studies whether there is a tradeoff between average robust accuracy and class-wise disparity of robust accuracy. We provide an affirmative answer to this question by comprehensive experiments and rigorous theoretical analysis.

3 Notation and Definition

We donote by $\mathcal{X} \subseteq \mathbb{R}^d$ the feature space and $\mathcal{Y} = \{1, 2, 3, \ldots, L\}$ the label space with unknown joint distribution $\mathcal{D}$, and $\mathcal{X}$ has marginal distribution $\mathcal{D}_x$. Let (x, y) be the feature-label pair, where instance $x \in \mathcal{X}$ and label $y \in \mathcal{Y}$. We denote the transpose of vector/matrix by the superscript $'$. Denote by $f_\theta : \mathcal{X} \to \mathcal{Y}$ the classifier (or hypothesis) which is parameterized by $\theta \in \Theta$, where Θ is the parameter space and maps x to a certain label y. For simplicity, we denote $\ell(\theta, x, y) = \ell(f_\theta(x), y)$ where $\ell(\cdot)$ is a certain loss function.

Natural training. Recall that for natural training in the canonical classification setting, the primary goal is to maximize the standard accuracy of models on the unseen examples from the underlying distribution. Concretely, we hope to find the classifier f_{nat} with the smallest natural risk:

$$R_{nat}(f_{nat}) = \min_{\theta \in \Theta} \mathbb{E}_{(x,y)\sim\mathcal{D}} \ell(\theta, x, y).$$

Adversarial training. AT [17, 21, 29] aims to build models that are robust against adversarial examples by solving a robust optimization problem. Specifically, the task of AT is to find the classifier f_{adv} with the smallest adversarial/robust risk:

$$R_{adv}(f_{adv}) = \min_{\theta \in \Theta} \mathbb{E}_{(x,y)\sim\mathcal{D}} [\sup_{z \in \mathcal{U}(x,\epsilon)} \ell(\theta, z, y)]$$

where $\mathcal{U}(x, \epsilon)$ represents the perturbation set. This paper focuses on the set $\mathcal{U}(x, \epsilon) = \{z \in \mathcal{X} : ||z - x||_\infty \leq \epsilon\}$, where $|| \cdot ||_\infty$ is the l_∞-norm. Such type of set is also called l_∞-attack in AT.

4 Empirical Exploration

This section explores the relations between the perturbation radius in AT and the variance of class-wise robust accuracy, and studies whether there is a tradeoff between average robust accuracy and class-wise disparity of robust accuracy through a series of experiments. We use Madry [17] with various perturbation radii $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$ to train ResNet18, ResNet50 [13] and Wide ResNet-32-10 (WRN-32-10) [28] on the CIFAR-10 and CIFAR-100 datasets [15]. The evaluation metrics are the average robust accuracy and the variance of class-wise robust accuracy. The adversarial testing examples are generated by FGSM [12], PGD-20 [17] and C&W [3] with different testing perturbation radii $\epsilon_{test} = \{16/255, 20/255\}$, respectively. The experimental settings(including optimizer, epoch, learning rate and so on) are same as Section 7.1 Here, we present only the experimental results of Madry on CIFAR-10.

Table 1: The average robust accuracy (%) and variance of class-wise robust accuracy (10^{-2}) for Madry using ResNet18, ResNet50 and WRN-32-10 on CIFAR-10. The perturbation radii for AT are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM, PGD-20 and C&W with different testing perturbation radii $\epsilon_{test} = \{16/255, 20/255\}$. We use var and rob.acc to denote the variance of class-wise robust accuracy, and average robust accuracy, respectively.

attack algorithm		FGSM				PGD-20				C&W			
ϵ_{test}		16/255		20/255		16/255		20/255		16/255		20/255	
model	ϵ_{train}	var	rob.acc	var	rob.acc	var	rob.acc	var	rob.acc	var	rob.acc	var	rob.acc
ResNet18	4/255	1.90	29.04	1.31	21.71	0.10	3.54	0.02	1.12	0.11	3.61	0.02	1.05
	8/255	2.34	39.00	1.99	32.13	0.50	11.23	0.16	4.96	0.61	12.14	0.19	5.35
	12/255	3.12	41.99	2.53	35.71	0.98	19.43	0.35	10.03	1.09	19.39	0.42	10.53
	16/255	3.52	42.94	2.99	37.34	1.28	22.50	0.48	12.86	1.38	22.03	0.60	12.65
ResNet50	4/255	1.24	28.89	0.84	21.14	0.07	3.34	0.01	1.13	0.07	3.47	0.01	1.08
	8/255	2.36	37.74	1.81	30.68	0.56	13.13	0.22	6.10	0.68	14.06	0.29	6.90
	12/255	3.15	39.28	2.78	33.95	1.07	20.88	0.38	11.59	1.16	20.19	0.48	11.70
	16/255	3.89	41.26	3.20	35.95	1.54	23.92	0.66	14.44	1.61	22.56	0.75	14.11
WRN-32-10	4/255	2.30	39.21	0.16	5.15	0.16	5.15	0.02	1.79	0.09	3.97	0.01	1.10
	8/255	2.46	40.68	0.93	13.62	0.93	13.62	0.43	7.91	0.74	12.76	0.25	6.58
	12/255	2.58	41.51	0.97	15.95	0.96	15.63	0.48	9.09	0.96	15.69	0.46	8.87
	16/255	2.73	43.36	1.04	17.05	1.04	17.05	0.65	9.87	1.00	17.09	0.53	9.76

The results in Figures 1 and 2 show that with increasing ϵ_{train}, the average robust accuracy for Madry using three neural network models on CIFAR-10 monotonously increases; moreover, their variance of class-wise robust accuracy monotonously increases as well, which leads to severer robust fairness issues. For example, when $\epsilon_{train} = 4/255$, the average robust accuracy and the variance of class-wise robust accuracy are 29.04% and 0.019 respectively for Madry using ResNet18 on CIFAR-10 under FGSM attack. When $\epsilon_{train} = 16/255$, Madry using ResNet18 achieves 42.94% average robust accuracy, while the variance of class-wise robust accuracy of ResNet18 increases to 0.035 on CIFAR-10. Additionally, the detailed testing results in Table 1 reveal that this trend consistently exists under different networks, attack algorithms and testing perturbation radii.

The results of Madry on CIFAR-100 are presented in Appendix A. We also use TRADES [29] with various perturbation radii ϵ_{train} to train ResNet18, ResNet50 and WRN-32-10 on CIFAR-10 and CIFAR-100. These results are presented in Appendix A. From these results, we can observe the same trend above. These observations suggest that the phenomenon in Figure 1, Figure 2 and Table 1 can be generalized to more AT algorithms, model architectures, datasets and adversarial attacks. From the above empirical analysis, we find that higher average robust accuracy is accompanied by a larger variance of class-wise robust accuracy, suggesting that there exists a tradeoff between average robustness and robust fairness.

Table 2: The robust accuracy (%), average robust accuracy (%) and variance of class-wise robust accuracy (10^{-2}) of some classes for Madry using ResNet50 on CIFAR-10. The perturbation radii for AT are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM with testing perturbation radius $\epsilon_{test} = 16/255$. We use var and rob.acc to denote the variance of class-wise robust accuracy, and average robust accuracy, respectively. Moreover, diff means the difference between testing results where ϵ_{train} is $16/255$ and $4/255$, respectively.

ϵ_{train}	cat	deer	horse	ship	var	rob.acc.
4/255	12.0	17.5	39.9	34.2	1.24	28.89
8/255	10.9	16.7	49.6	53.5	2.36	37.74
12/255	8.9	13.7	50.4	60.4	3.15	39.42
16/255	7.8	13.7	51.4	62.4	3.89	41.26
diff	-4.2	-3.8	11.5	28.2	2.65	12.37

Why does AT results in this phenomenon? Table 2 presents the robust accuracy of some classes, average robust accuracy and variance of class-wise robust accuracy for Madry using ResNet50 on CIFAR-10. The results in Table 2 may reveal the underlying rationale for our findings. From Table 2, we can observe that model's robust accuracy on classes "cat" and "deer" is significantly lower than that on classes "horse" and "ship" for various values of ϵ_{train}. Additionally, with the increasing of ϵ_{train}, the robust accuracy of the model on the classes "cat" and "deer" monotonously decreases; while the robust accuracy of the model on classes "horse" and "ship" monotonously increases. This observation indicates that, to further improve the robustness of models, AT prefers to "sacrifice" model's robust accuracy on relatively vulnerable classes (like "cat" and "deer") and pay more atten-

tion to learning the distribution of examples of more robust classes (like 'horse' and "ship"). This preference of AT increases the variance of class-wise robust accuracy and leads to a tradeoff between average robustness and robust fairness, although the average robustness of the model can be improved. The following section presents a theoretical analysis of this phenomenon.

5 Theoretical Analysis

Following [4, 22, 26], we study a concrete mixture Gaussian distribution. Inspired by the results in Table 2, our motivation is to design two classes, "+1" and "−1" and then we analyze the performance of natural training and AT on each class. We begin with the following definition.

Definition 5.1. (Mixture Gaussian Distribution). Let $\mu_+, \mu_- > 0$ be the per-class mean parameter and $\sigma_+, \sigma_- > 0$ be variance parameter of two classes. The $(\mu_+, \mu_-, \sigma_+, \sigma_-)$-Gaussian mixture distribution $\mathcal{D}^*$ can be then defined by the following distribution over $(x, y) \in \mathbb{R}^d \times \{\pm 1\}$:

$$y = \begin{cases} +1, & p = \alpha \\ -1, & p = 1 - \alpha, \end{cases} \quad x \sim \begin{cases} \mathcal{N}\left(\boldsymbol{\mu}_+, \sigma_+^2 I\right) & \text{if } y = +1 \\ \mathcal{N}\left(-\boldsymbol{\mu}_-, \sigma_-^2 I\right) & \text{if } y = -1 \end{cases} \quad (1)$$

where α is the prior probability of class "+1" and $\boldsymbol{\mu}_+ = \mu_+\mathbf{1}, \boldsymbol{\mu}_- = \mu_-\mathbf{1}, \mathbf{1} = \overbrace{(1, \ldots, 1)}^{\text{dim } d}{}', I$ is a d-dimension identity matrix.

In this section, we focus on studying the performance of the linear model on the distribution $\mathcal{D}^*$ as follows:

$$f(x) = \text{sign}\left(\langle w, x \rangle + b\right) \quad (2)$$

where the parameters $w \in \mathbb{R}^d$, $b \in \mathbb{R}$, and sign(t) evaluates to 1 if scalar $t \geq 0$ and to -1 otherwise.

5.1 Naturally Trained Linear Model

In this subsection, we analyze the performance of a naturally trained linear model on distribution $\mathcal{D}^*$. For simplicity, we denote

$$R_{nat}^{+1}(f) = \mathbb{E}_{(x,y)\sim\mathcal{D}^*}(\mathbb{1}(f(x) = -1)|y = +1)$$

$$R_{nat}^{-1}(f) = \mathbb{E}_{(x,y)\sim\mathcal{D}^*}(\mathbb{1}(f(x) = +1)|y = -1)$$

where $\mathbb{1}(\cdot)$ is the indicator function that takes 1 when the statement in the braces is true and 0 otherwise.

Theorem 5.2. *For the naturally trained linear classifier f_{nat} that minimizes the natural risk:*

$$f_{nat}(x) = \arg\min_f \mathbb{E}_{(x,y)\sim\mathcal{D}^*}(\mathbb{1}(f(x) \neq y)), \quad (3)$$

if $\sigma_+ \neq \sigma_-$, the class-wise natural risk can be expressed as follows:

$$R_{nat}^{+1}(f_{nat}) = \Phi\left(\frac{-\eta^* - d\mu_+}{\sqrt{d}\sigma_+}\right) \quad R_{nat}^{-1}(f_{nat}) = \Phi\left(\frac{\eta^* - d\mu_-}{\sqrt{d}\sigma_-}\right) \quad (4)$$

where $\Phi(\cdot)$ is the cumulative distribution function (c.d.f.) of standard Gaussian distribution $\mathcal{N}(0, 1)$ and

$$\eta^* = \frac{A + \sigma_+\sigma_-(\mu_+ + \mu_-)\sqrt{1 + 2K\frac{\sigma_-^2 - \sigma_+^2}{(\mu_+ + \mu_-)^2}}}{\sigma_-^2 - \sigma_+^2}$$

where $A = -d(\mu_+\sigma_-^2 + \mu_-\sigma_+^2)$ and K is a positive constant. If $\sigma_+ = \sigma_- = \sigma$, the class-wise natural risk can be expressed as follows:

$$R_{nat}^{+1}(f_{nat}) = \Phi\left(\frac{-d^2(\mu_+ + \mu_-)^2 - 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)}\right) \quad (5)$$

$$R_{nat}^{-1}(f_{nat}) = \Phi\left(\frac{-d^2(\mu_+ + \mu_-)^2 + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)}\right). \quad (6)$$

A proof of Theorem 5.2 can be found in Appendix B.1. Because $\Phi(\cdot)$ is a monotonously increasing function, Theorem 5.2 shows that if the variances of two classes are same, the naturally trained model performs better on class "+1" than class "−1"; namely:

$$R_{nat}^{+1}(f_{nat}) < R_{nat}^{-1}(f_{nat}).$$

5.2 Adversarially Trained Linear Model

This subsection studies the performance of the adversarially trained linear model on distribution $\mathcal{D}^*$. Without loss of generality, we consider the l_∞-attack in adversarial training and testing. In this case, the perturbation set can be expressed as $\mathcal{U}(x, \epsilon) = \{z : ||z - x||_\infty \leq \epsilon\}$. The radius ϵ of the perturbation set can be used to adjust the level of attack. Obviously, larger ϵ means that adversary can generate stronger adversarial examples which can easily trick the trained model into making incorrect predictions.

We use ϵ_{train} and ϵ_{test} to represent the radius of the perturbation set in the training and testing phases, respectively, and we further assume $\epsilon_{train} \leq \epsilon_{test}$. For simplicity, we denote

$$R_{adv}^{+1}(f) = \mathbb{E}_{(x,y)\sim\mathcal{D}^*}[\sup_{z\in\mathcal{U}(x,\epsilon)} \mathbb{1}(f(z) = -1)|y = +1]$$

$$R_{adv}^{-1}(f) = \mathbb{E}_{(x,y)\sim\mathcal{D}^*}[\sup_{z\in\mathcal{U}(x,\epsilon)} \mathbb{1}(f(z) = +1)|y = -1].$$

Theorem 5.3. *For the adversarial trained linear classifier f_{adv} that minimizes the adversarial risk:*

$$f_{adv}(x) = \arg\min_{f}\mathbb{E}_{(x,y)\sim\mathcal{D}^*}[\sup_{z\in\mathcal{U}(x,\epsilon)} (\mathbb{1}(f(z) \neq y)], \tag{7}$$

if $\sigma_+ \neq \sigma_-$, the class-wise adversarial risk can be expressed as follows:

$$R_{adv}^{+1}(f_{adv}) = \Phi\left(\frac{-\gamma^* - d(\mu_+ - \epsilon_{test})}{\sqrt{d}\sigma_+}\right) \quad R_{adv}^{-1}(f_{adv}) = \Phi\left(\frac{\gamma^* - d(\mu_- - \epsilon_{test})}{\sqrt{d}\sigma_-}\right) \tag{8}$$

where $\Phi(\cdot)$ is the c.d.f. of standard Gaussian distribution $\mathcal{N}(0, 1)$ and

$$\gamma^* = \frac{B + \sigma_+\sigma_-(\mu_+ + \mu_- - 2\epsilon_{train})\sqrt{1 + \frac{2K(\sigma_-^2 - \sigma_+^2)}{(\mu_+ + \mu_- - 2\epsilon_{train})^2}}}{\sigma_-^2 - \sigma_+^2}$$

where $B = -d(\mu_+\sigma_-^2 + \mu_-\sigma_+^2 - \epsilon_{train}(\sigma_+^2 + \sigma_-^2))$ and K is a positive constant. If $\sigma_+ = \sigma_- = \sigma$, the class-wise adversarial risk can be expressed as follows:

$$R_{adv}^{+1}(f_{adv}) = \Phi\left(\frac{-C - 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}\right)$$

$$R_{adv}^{-1}(f_{adv}) = \Phi\left(\frac{-C + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}\right)$$

where $C = d^2(\mu_+ + \mu_- - 2\epsilon_{train})(\mu_+ + \mu_- - 2\epsilon_{test})$.

The proof of Theorem 5.3 can be seen in Appendix B.2. Theorem 5.3 demonstrates that if the variances of two classes are the same, we have

$$R_{adv}^{+1}(f_{adv}) < R_{adv}^{-1}(f_{adv}),$$

which indicates that the examples in class "−1" are more vulnerable than those in class "+1". In the following, we will present our core theoretical results based on Theorems 5.2 and 5.3.

5.3 Tradeoff between Average Robustness and Robust Fairness

Following [5, 18], we use *variance of class-wise robust accuracy* (VCRA) to quantitatively measure the model fairness. The definition of VCRA is presented below.

Definition 5.4. (VCRA). Given a classifier $f : \mathcal{X} \to \mathcal{Y}$ where $\mathcal{Y} = \{1, 2, 3, \dots, L\}$, the variance of class-wise robust accuracy of f is defined as

$$VCRA(f) = \frac{1}{L}\sum_{i=1}^{L}(p_{adv}(i) - \bar{p}_{adv})^2 \tag{9}$$

where $p_{adv}(i) = \mathbb{P}\{\forall z \in \mathcal{U}(x, \epsilon), f(z) = i|y = i\}$ and $\bar{p}_{adv} = \frac{1}{L}\sum_{i=1}^{L} p_{adv}(i)$. Additionally, we have

$$
\begin{aligned}
p_{adv}(i) &= 1 - \mathbb{P}\{\exists z \in \mathcal{U}(x, \epsilon), f(z) \neq i|y = i\} \\
&= 1 - \mathbb{E}_{(x,y)\sim\mathcal{D}}[\sup_{z\in\mathcal{U}(x,\epsilon)} \mathbb{1}(f(z) \neq i)|y = i].
\end{aligned}
\tag{10}
$$

When calculatinng the *variance of class-wise accuracy* of f: $VCA(f)$, we just need to replace $p_{adv}(i)$ with $p(i)$ where $p(i) = \mathbb{P}(f(x) = i|y = i)$. To obtain more concise analytical results, we focus on the situation in which $\sigma_+ \leq \sigma_-$. However, our results can be generalized to other settings under some mild conditions.

Theorem 5.5. *Given an adversarially trained linear model f_{adv} in Equation (7), the variance of class-wise robust accuracy $VCRA(f_{adv})$ is increasing with respect to ϵ_{train} if $\sigma_- \geq \sigma_+$.*

The proof of Theorem 5.5 can be found in Appendix B.3. A large radius ϵ_{test} of the perturbation set $\mathcal{U}(x, \epsilon_{test})$ in the testing phase enables adversary to generate strong adversarial examples that can easily trick the trained model into making wrong predictions. To defend against these adversarial examples, we usually increase the radius ϵ_{train} of $\mathcal{U}(x, \epsilon_{train})(\epsilon_{train} \leq \epsilon_{test})$ to generate strong adversarial examples in the training phase, which has been proved to effectively improve the average robust accuracy of models. However, Theorem 5.5 shows that the variance of the class-wise robust accuracy of the adversarially trained model f_{adv} increases monotonically with respect to the radius ϵ_{train}. In other words, a larger radius ϵ_{train} will lead to a larger variance of class-wise robust accuracy of the adversarially trained model even though the average robust accuracy of the model might be improved. Therefore, there exists a tradeoff between average robust accuracy and robust fairness. This provides an confirmative answer to our question in Section 1 and explains our experimental findings in Section 4. Notably, when perturbation radius $\epsilon_{test} = 0$, Theorem 5.5 suggests that AT($\epsilon_{train} > 0$) results in larger class-wise disparity of standard accuracy compared with natural training($\epsilon_{train} = 0$). Hence, the results in [26] is a special case of Theorem 5.5.

Why does AT lead to this phenomenon? For simplicity, we just consider the situation in which $\sigma_- = \sigma_+$. In this setting, $R_{adv}^{+1}(f_{adv})$ is monotonically decreasing, but $R_{adv}^{-1}(f_{adv})$ is monotonically increasing with respect to ϵ_{train}. Therefore, improving model's average robust accuracy by increasing ϵ_{train} will result in a smaller $R_{adv}^{+1}(f_{adv})$ and larger $R_{adv}^{-1}(f_{adv})$, meaning larger class-wise disparity of robust accuracy. Moreover, the examples in class "-1" are more vulnerable than those in class "$+1$". These analysis suggests that, to further improve average robust accuracy, AT will "sacrifice" model's robust accuracy on relatively vulnerable class "-1" and pay more attention to learning the distribution of examples in more robust class "$+1$", which explains our observations in Table 2. This preference of AT will lead to a tradeoff between average robust accuracy and robust fairness.

Previous works [2, 26] empirically find that a robust model well-trained by AT exhibits a remarkable disparity of standard accuracy and robust accuracy among different classes compared with natural training. We will theoretically prove this phenomeno. First, we give following theoretical result.

Theorem 5.6. *Given an adversarially trained linear model f_{adv} in Equation (7), and suppose $\sigma_+ = \sigma_-$. The variance of class-wise robust accuracy of f_{adv} can be expressed as follows:*

$$
VCRA(f_{adv}) = \frac{1}{\pi d^3} \exp(-\xi^2) \left(\frac{K\sigma}{\mu_+ + \mu_- - 2\epsilon_{train}}\right)^2
$$

where ξ is a constant and K is a positive constant.

The proof of Theorem 5.6 can be found in Appendix B.3.

Theorem 5.7. *Given an adversarially trained linear model f_{adv} in Equation (7) and a naturally trained linear model f_{nat} in Equation (3), and suppose $\sigma_+ = \sigma_-$. If $\epsilon_{train} < \frac{\mu_+ + \mu_-}{e}$ and $\epsilon_{test} < \frac{\mu_+ + \mu_-}{2} - \frac{eK^3\sigma^3}{d^4(\mu_+ + \mu_-)}$, we have*

$$
\frac{VCRA(f_{adv})}{VCRA(f_{nat})} = e^{(\zeta_2^2 - \zeta_1^2)} \left(\frac{\mu_+ + \mu_-}{\mu_+ + \mu_- - 2\epsilon_{train}}\right)^2 \geq 1
$$

where K is a positive constant and ζ_1, ζ_2 are two constants.

The proof of Theorem 5.7 can be found in Appendix B.3. From Theorem 5.7, we can find $VCRA(f_{nat}) < VCRA(f_{adv})$. Similar to Theorem 5.7, we also demonstrate $VCA(f_{nat}) \le VCRA(f_{adv})$ in Theorem B.6 of Appendix B.3. The results of Theorems 5.7 and B.6 suggest that AT easily leads to severer robust fairness issue than natural training.

6 Fairly Adversarial Training

In this section, we will propose a novel fairly adversarial training (FAT) to mitigate the tradeoff between average robustness and robust fairness. The analytical results in Section 5 and Equation (10) show that we can control the variance of class-wise robust accuracy by controlling the variance of class-wise adversarial risk. Theorem 6.1 provide a theoretical guarantee for using the variance of class-wise adversarial risk to trade off average robustness against robust fairness.

Denote $\tilde{\ell}(\theta, x, y) = \sup_{z \in \mathcal{U}(x, \epsilon)} \ell(\theta, z, y)$ and the corresponding empirical adversarial risk $\hat{R}_{adv}(f) = \frac{1}{n} \sum_{i=1}^{n} \tilde{\ell}(\theta, x_i, y_i)$. In addition, we denote the variance of class-wise adversarial risk (VCAR) as

$$\text{VCAR}(f) = \frac{1}{L} \sum_{i=1}^{L} (R_{adv}(f, i) - \bar{R}_{adv}(f))^2$$

where $R_{adv}(f, i) = \mathbb{E}(\tilde{\ell}(\theta, x, y = i))$ and $\bar{R}_{adv}(f) = \frac{1}{L} \sum_{i=1}^{L} R_{adv}(f, i)$.

Theorem 6.1. *Let $(x_1, y_1), (x_2, y_2), \ldots, (x_n, y_n)$ be drawn independent and identically distributed (i.i.d.) from the unknown distribution $\mathcal{D}$. Under appropriate conditions on the loss $\ell(\cdot)$, parameter space Θ, with probability of at least $1 - \delta$, the following holds for all $\theta \in \Theta$:*

$$R_{adv}(f) \le \hat{R}_{adv}(f) + \sqrt{\frac{\text{VCAR}(f) \frac{1}{\delta}}{n}} + \frac{C}{n}$$

The proof of Theorem 6.1 can be found in Appendix B.4. Theorem 6.1 shows that the variance of class-wise adversarial risk can control the robust risk of classifiers and the class-wise disparity of robustness. Inspired by Theorem 6.1, we propose to minimize the following object:

$$\min_{f} [\underbrace{R_{adv}(f)}_{\text{for robustness}} + \underbrace{\lambda \text{VCAR}(f)}_{\text{for disparity}}] \tag{11}$$

where the parameter λ in Equation (11) captures the tradeoff between average robustness and robust fairness.

We use $\hat{R}_{adv}(f, i)$ to estimate $R_{adv}(f, i)$ where $\hat{R}_{adv}(f, i) = \frac{1}{n_i} \sum_{j=1}^{n_i} \tilde{\ell}(\theta, x_j, i)$ and n_i is the number of examples that belong to class i. The estimator of $\text{VCAR}(f)$ can be expressed as follows:

$$\widehat{\text{VCAR}}(f) = \frac{1}{L} \sum_{i=1}^{L} (\hat{R}_{adv}(f, i) - \bar{\hat{R}}_{adv}(f))^2$$

Usually, $\widehat{\text{VCAR}}(f)$ is a biased but consistent estimator of $VCAR(f)$. FAT can thus be formulated as follows:

$$\min_{f} [\hat{R}_{adv}(f) + \lambda \widehat{\text{VCAR}}(f)] \tag{12}$$

7 Experiments

In this section, we present the experimental results to validate the effectiveness of FAT for mitigating the tradeoff between average robustness and robust fairness.

7.1 Experimental Settings

We conduct our experiments on the benchmark datasets CIFAR-10 and CIFAR-100 [15]. Based on ResNet18 [13], we compare our proposed FAT with Madry [17] on two datasets with different

Table 3: The variance of class-wise robust accuracy (10^{-2}) for Madry and FAT using ResNet18 on CIFAR-10. The perturbation radii are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM, PGD-20 and C&W with different testing perturbation radii $\epsilon_{test} = \{16/255, 20/255\}$.

attack algorithm	FGSM				PGD-20				C&W			
ϵ_{test}	16/255		20/255		16/255		20/255		16/255		20/255	
ϵ_{train}	PGD	FAT	PGD	FAT	PGD	FAT	PGD	FAT	PGD	FAC	PDG	FAT
4/255	1.90	1.76	1.31	1.28	0.10	0.07	0.02	0.01	0.11	0.08	0.02	0.01
8/255	2.34	2.18	1.99	1.69	0.50	0.46	0.16	0.12	0.61	0.52	0.19	0.14
12/255	3.12	2.99	2.53	2.47	0.98	0.84	0.35	0.35	1.09	0.90	0.42	0.38
16/255	3.52	3.32	2.99	2.90	1.28	1.06	0.48	0.40	1.38	1.22	0.60	0.51

Table 4: The average robust accuracy (10^{-2}) for Madry and FAT using ResNet18 on CIFAR-10. The perturbation radii are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM, PGD-20 and C&W with different testing perturbation radii $\epsilon_{test} = \{16/255, 20/255\}$. We use **bold** to denote higher robust accuracy.

attack algorithm	FGSM				PGD-20				C&W			
ϵ_{test}	16/255		20/255		16/255		20/255		16/255		20/255	
ϵ_{train}	PGD	FAT	PGD	FAT	PGD	FAT	PGD	FAT	PGD	FAC	PDG	FAT
4/255	29.04	**29.33**	21.74	**22.65**	3.54	3.11	1.12	**1.31**	3.61	3.23	1.05	0.99
8/255	39.00	38.57	32.13	**32.26**	11.23	**11.29**	4.96	**5.26**	12.14	**12.32**	5.35	**5.48**
12/255	41.99	**42.77**	35.71	**36.71**	19.43	**19.74**	10.03	**10.97**	19.39	**19.88**	10.53	**11.48**
16/255	42.97	**43.40**	37.34	**37.98**	22.50	**22.79**	12.86	**13.11**	22.03	**22.21**	12.65	**12.99**

perturbation radii $\epsilon_{train} \in \{4/255, 8/255, 12/255, 16/255\}$. The maximum PGD step and step size are set to 20 and $\epsilon_{train}/10$, respectively. For optimization, we use SGD with 0.9 momentum for 120 epochs. The initial learning rate is set to 0.1 and is divided by 10 at epoch 60 and epoch 80, respectively. The adversarial testing examples are generated by FGSM [12], PGD-20 [17] and C&W [3] with different testing perturbation radii $\epsilon_{test} = \{16/255, 20/255\}$, respectively. Here, we present only the experimental results on CIFAR-10 in Tables 3 and 4. The experiment results of FAT and Madry on CIFAR-100 can be found in Appendix C.1. Besides, the sensitivity analysis of the regularization hyperparameter λ in FAT is presented in Appendix C.2. Our code can be found on GitHub at `https://github.com/wzekai99/FAT`.

7.2 Experimental Results

Under the attack of FGSM, PGD-20 and C&W with different ϵ_{test}, Table 3 presents the variance of class-wise robust accuracy for FAT and Madry using ResNet18 on CIFAR-10. From table 3, we can observe that FAT significantly reduces the variance of class-wise robust accuracy of Madry for various perturbation radii ϵ_{train}. The results from Tables 3 and 4 further show that with increasing ϵ_{train}, the average robust accuracy and the variance of class-wise robust accuracy of FAT increase, which is consistent with our theory in Section 5. However, compared with Madry, FAT consistently obtains smaller variance of class-wise robust accuracy while achieving comparable average robust accuracy on different ϵ_{train} and attack algorithms. For example, with the increasing of ϵ_{train} from $4/255$ to $16/255$, FAT reduces the variance of class-wise robust accuracy of Madry by around 16% under the C&W attack with $\epsilon_{test} = 16/255$. These experimental results suggest that FAT can effectively suppress the growth of variance of class-wise robust accuracy while achieving an competitive average robust accuracy compared with Madry with the increasing of ϵ_{train}. The results of FAT and TRADES in Appendix C.1 also present conclusions consistent with those drawn here. Therefore, FAT can alleviate the robust fairness problem and mitigate the tradeoff between average robustness and robust fairness.

8   Conclusion

In this work, we empirically find that there is a tradeoff between average robustness and robust fairness: higher average robust accuracy of models is accompanied by severer robust fairness issues with the increasing of training perturbation radius. Our theoretical results explain our observations. We then theoretically demonstrate that AT indeed leads to severer robust fairness issue compared with natural training. Moreover, a novel method is proposed to mitigate the tradeoff between average robustness and robust fairness. Our experimental results verify the superiority of our proposals.

Acknowledgements

This work is supported by the National Natural Science Foundation of China under Grant 61976161.

References

[1] Peter L. Bartlett, Olivier Bousquet, and Shahar Mendelson. Local rademacher complexities. *The Annals of Statistics*, 33:1497–1537, 2005.

[2] Philipp Benz, Chaoning Zhang, Adil Karjauv, and In So Kweon. Robustness may be at odds with fairness: An empirical study on class-wise accuracy. *arXiv preprint arXiv:2010.13365*, 2020.

[3] Nicholas Carlini and David A. Wagner. Towards evaluating the robustness of neural networks. In *IEEE Symposium on Security and Privacy(SP)*, pages 39–57, 2017.

[4] Yair Carmon, Aditi Raghunathan, Ludwig Schmidt, John C. Duchi, and Percy Liang. Unlabeled data improves adversarial robustness. In *NeurIPS*, pages 11190–11201, 2019.

[5] Simon Caton and Christian Haas. Fairness in machine learning: A survey. *arXiv preprint arXiv:2010.04053*, 2020.

[6] Edgar Dobriban, Hamed Hassani, David Hong, and Alexander Robey. Provable tradeoffs in adversarially robust classification. *arXiv preprint arXiv:2006.05161*, 2020.

[7] Kevin Eykholt, Ivan Evtimov, Earlence Fernandes, Bo Li, Amir Rahmati, Chaowei Xiao, Atul Prakash, Tadayoshi Kohno, and Dawn Song. Robust physical-world attacks on deep learning visual classification. In *CVPR*, pages 1625–1634, 2018.

[8] Alhussein Fawzi, Omar Fawzi, and Pascal Frossard. Analysis of classifiers' robustness to adversarial perturbations. *Machine Learning*, 107(3):481–508, 2018.

[9] Xiuwen Gong, Jiahui Yang, Dong Yuan, and Wei Bao. Generalized large margin $k$nn for partial label learning. *IEEETransactions on Multimedia*, 24:1055–1066, 2022.

[10] Xiuwen Gong, Dong Yuan, and Wei Bao. Discriminative metric learning for partial label learning. *IEEE Transactions on Neural Networks and Learning Systems*, 2021.

[11] Xiuwen Gong, Dong Yuan, and Wei Bao. Top-k partial label machine. *IEEE Transactions on Neural Networks and Learning Systems*, 2021.

[12] Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *ICLR*, 2015.

[13] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, pages 770–778, 2016.

[14] Adel Javanmard, Mahdi Soltanolkotabi, and Hamed Hassani. Precise tradeoffs in adversarial training for linear regression. In Jacob D. Abernethy and Shivani Agarwal, editors, *COLT*, volume 125, pages 2034–2078, 2020.

[15] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[16] Weiwei Liu, Donna Xu, Ivor W. Tsang, and Wenjie Zhang. Metric learning for multi-output tasks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 41:408–422, 2019.

[17] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *ICLR*, 2018.

[18] Ninareh Mehrabi, Fred Morstatter, Nripsuta Saxena, Kristina Lerman, and Aram Galstyan. A survey on bias and fairness in machine learning. *ACM Computing Surveys*, 54(6):115:1–115:35, 2021.

[19] Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. Deepfool: A simple and accurate method to fool deep neural networks. In *CVPR*, pages 2574–2582, 2016.

[20] Vedant Nanda, Samuel Dooley, Sahil Singla, Soheil Feizi, and John P. Dickerson. Fairness through robustness: Investigating robustness disparity in deep learning. In *FAccT*, pages 466–477, 2021.

[21] Tianyu Pang, Xiao Yang, Yinpeng Dong, Taufik Xu, Jun Zhu, and Hang Su. Boosting adversarial training with hypersphere embedding. In *NeurIPS*, 2020.

[22] Ludwig Schmidt, Shibani Santurkar, Dimitris Tsipras, Kunal Talwar, and Aleksander Madry. Adversarially robust generalization requires more data. In *NeurIPS*, pages 5019–5031, 2018.

[23] Dimitris Tsipras, Shibani Santurkar, Logan Engstrom, Alexander Turner, and Aleksander Madry. Robustness may be at odds with accuracy. In *ICLR*, 2019.

[24] Zekai Wang and Weiwei Liu. Robustness verification for contrastive learning. In *ICML*, volume 162, pages 22865–22883, 2022.

[25] Eric Wong, Leslie Rice, and J. Zico Kolter. Fast is better than free: Revisiting adversarial training. In *ICLR*, 2020.

[26] Han Xu, Xiaorui Liu, Yaxin Li, Anil K. Jain, and Jiliang Tang. To be robust or to be fair: Towards fairness in adversarial training. In *ICML*, volume 139, pages 11492–11501, 2021.

[27] Dong Yin, Kannan Ramchandran, and Peter L. Bartlett. Rademacher complexity for adversarially robust generalization. In *ICML*, volume 97, pages 7085–7094, 2019.

[28] Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

[29] Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric P. Xing, Laurent El Ghaoui, and Michael I. Jordan. Theoretically principled trade-off between robustness and accuracy. In *ICML*, volume 97, pages 7472–7482, 2019.

A   More Experimental Results of Empirical Exploration

In this section, we present more experimental results of our Empirical Exploration 4. From the results in Tables 5, 6 and 7, we can observe a similar phenomenon presented in Section 4, namely that higher average robust accuracy of models is accompanied by larger variance of class-wise robust accuracy(a severer robust fairness issue) with the increasing of perturbation radius ϵ_{train}. In addition, this trend can be consistently observed under different neural networks, attack algorithms and datasets. These observations suggest the existence of a tradeoff between average robustness and robust fairness.

Table 5: The average robust accuracy (%) and variance of class-wise robust accuracy (10^{-2}) for Madry using ResNet18, ResNet50 and WRN-32-10 on CIFAR-100. The perturbation radii for AT are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM, PGD-20 and C&W with different testing perturbation radii $\epsilon_{test} = \{16/255, 20/255\}$. We use var and rob.acc to denote the variance of class-wise robust accuracy, and average robust accuracy, respectively.

attack Algorithm		FGSM				PGD-20				C&W			
ϵ_{test}		16/255		20/255		16/255		20/255		16/255		20/255	
model	ϵ_{train}	var	rob.acc	var	rob.acc	var	rob.acc	var	rob.acc	var	rob.acc	var	rob.acc
ResNet18	4/255	1.25	11.93	0.81	8.01	0.19	1.83	0.05	0.69	0.23	2.15	0.07	0.76
	8/255	1.80	16.52	0.84	12.35	0.60	5.16	0.26	2.65	0.70	5.65	0.33	3.10
	12/255	2.17	18.56	1.60	14.76	0.96	7.81	0.52	4.43	0.97	8.06	0.54	4.58
	16/255	2.32	19.78	1.89	16.26	1.12	8.95	0.65	5.42	1.18	9.03	0.65	5.45
ResNet50	4/255	1.46	13.04	1.02	8.88	0.30	2.75	0.08	1.16	0.35	3.24	0.12	1.41
	8/255	1.80	16.75	1.35	12.67	0.72	6.07	0.38	3.18	0.77	6.58	0.45	3.60
	12/255	2.01	17.53	1.63	14.20	0.99	7.89	0.55	4.75	1.02	8.35	0.61	5.08
	16/255	2.45	19.86	1.90	16.28	1.28	9.87	0.77	6.31	1.30	9.86	0.81	6.46
WRN-32-10	4/255	1.65	15.87	1.18	11.09	0.19	2.36	0.40	0.94	0.22	2.44	0.07	1.02
	8/255	2.22	19.94	1.69	15.55	0.85	6.36	0.64	3.50	0.88	6.66	0.46	3.81
	12/255	2.32	20.52	1.98	17.14	1.19	9.02	0.67	5.27	1.22	9.64	0.67	5.51
	16/255	2.52	21.68	2.03	18.06	1.22	9.69	0.75	6.07	1.28	10.20	0.81	6.29

Table 6: The average robust accuracy (%) and variance of class-wise robust accuracy (10^{-2}) for TRADES using ResNet18, ResNet50 and WRN-32-10 on CIFAR-10. The perturbation radii for AT are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM, PGD-20 and C&W with different testing perturbation radii $\epsilon_{test} = \{16/255, 20/255\}$. We use var and rob.acc to denote the variance of class-wise robust accuracy, and average robust accuracy, respectively.

attack algorithm		FGSM				PGD-20				C&W			
ϵ_{test}		16/255		20/255		16/255		20/255		16/255		20/255	
model	ϵ_{train}	var	rob.acc	var	rob.acc	var	rob.acc	var	rob.acc	var	rob.acc	var	rob.acc
ResNet18	4/255	1.59	32.10	1.15	23.61	0.18	4.9	0.04	1.80	0.19	5.58	0.04	2.07
	8/255	2.48	42.27	2.18	35.37	0.73	16.84	0.25	8.38	0.76	15.74	0.28	7.92
	12/255	2.64	42.74	2.45	37.24	1.48	23.90	0.71	14.68	1.37	20.34	0.62	12.27
	16/255	2.69	43.71	2.50	38.34	1.67	26.11	0.84	16.55	1.55	22.37	0.73	13.48
ResNet50	4/255	1.21	32.57	0.84	24.59	0.14	4.84	0.02	1.74	0.18	5.44	0.03	2.03
	8/255	1.86	43.00	1.60	36.01	0.54	15.34	0.17	6.62	0.65	14.98	0.18	6.56
	12/255	2.55	44.07	2.36	38.64	1.29	23.60	0.46	14.03	1.29	20.78	0.55	12.32
	16/255	2.80	44.87	2.64	40.02	1.55	26.21	0.56	16.84	1.66	23.67	0.79	14.86
WRN-32-10	4/255	1.09	39.67	1.14	33.27	0.66	9.76	0.23	9.76	0.40	7.70	0.08	2.96
	8/255	2.32	44.94	2.16	39.01	1.02	16.68	0.42	16.68	0.97	15.30	0.46	8.45
	12/255	2.41	46.53	2.32	40.58	1.02	18.85	0.47	18.85	1.10	18.56	0.97	9.49
	16/255	2.69	47.58	2.45	42.26	1.39	20.44	0.69	20.44	1.67	19.86	1.42	10.78

B   Proof of Theoretical Results

In this section, we first give the analytical solutions of natural training and adversarial training for linear model on the distribution $\mathcal{D}^*$ in Equation (1). Then, we present our core conclusion that stronger AT can lead to larger variance of class-wise robust accuracy with the increasing of perturbation radius ϵ_{train}. Additionally, we theoretically explain the phenomenon that adversarial training can easily result in severer robust fairness issue compared with natural training.

B.1   Naturally Trained Linear model

Theorem 5.2. *For the naturally trained linear classifier f_{nat} that minimizes the natural risk:*

$$f_{nat}(x) = \arg\min_f \mathbb{E}_{(x,y)\sim\mathcal{D}^*}(\mathbb{1}(f(x) \neq y)), \tag{13}$$

Table 7: The average robust accuracy (%) and variance of class-wise robust accuracy (10^{-2}) for TRADES using ResNet18, ResNet50 and WRN-32-10 on CIFAR-100. The perturbation radii for AT are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM, PGD-20 and C&W with different testing perturbation radii $\epsilon_{test} = \{16/255, 20/255\}$. We use var and rob.acc to denote the variance of class-wise robust accuracy, and average robust accuracy, respectively.

attack Algorithm		FGSM				PGD-20				C&W			
ϵ_{test}		16/255		20/255		16/255		20/255		16/255		20/255	
model	ϵ_{train}	var	rob.acc	var	rob.acc	var	rob.acc	var	rob.acc	var	rob.acc	var	rob.acc
ResNet18	4/255	1.70	16.22	1.24	11.58	0.43	3.91	0.18	1.90	0.42	4.23	0.19	2.03
	8/255	2.42	21.06	1.96	16.91	1.17	9.97	0.65	5.87	1.12	9.04	0.69	5.69
	12/255	2.79	22.17	2.38	18.73	1.73	12.61	1.13	8.81	1.54	10.28	1.02	7.19
	16/255	2.87	22.46	2.56	19.28	1.93	13.26	1.37	9.63	1.65	10.92	1.17	7.74
ResNet50	4/255	1.78	16.76	1.26	12.19	0.56	4.76	0.24	2.37	0.59	5.27	0.28	2.63
	8/255	2.31	21.78	1.87	17.87	1.58	10.00	0.70	5.89	1.18	9.73	0.70	6.02
	12/255	2.67	22.32	2.29	19.01	1.61	12.18	1.00	8.20	1.47	10.80	0.96	7.37
	16/255	2.72	23.78	2.32	20.29	1.68	12.54	1.32	8.51	1.52	11.02	1.06	7.51
WRN-32-10	4/255	1.96	18.74	1.52	14.28	0.66	5.15	0.32	2.71	0.65	5.23	0.30	2.69
	8/255	2.35	21.49	1.98	17.69	1.15	9.21	0.62	5.34	1.13	9.15	0.63	5.31
	12/255	2.56	23.13	2.08	19.19	1.31	10.90	0.80	6.47	1.37	10.85	0.84	6.66
	16/255	2.74	24.15	2.23	20.31	1.41	11.14	0.87	7.11	1.45	11.08	0.88	6.89

if $\sigma_+ \neq \sigma_-$, the class-wise natural risk can be expressed as follows:

$$R_{nat}^{+1}(f_{nat}) = \Phi\left(\frac{-\eta^* - d\mu_+}{\sqrt{d}\sigma_+}\right) \quad R_{nat}^{-1}(f_{nat}) = \Phi\left(\frac{\eta^* - d\mu_-}{\sqrt{d}\sigma_-}\right) \tag{14}$$

where $\Phi(\cdot)$ is the cumulative distribution function (c.d.f.) of standard Gaussian distribution $\mathcal{N}(0, 1)$ and

$$\eta^* = \frac{A + \sigma_+\sigma_-(\mu_+ + \mu_-)\sqrt{1 + 2K\frac{\sigma_-^2 - \sigma_+^2}{(\mu_+ + \mu_-)^2}}}{\sigma_-^2 - \sigma_+^2}$$

where $A = -d(\mu_+\sigma_-^2 + \mu_-\sigma_+^2)$ and K is a positive constant. If $\sigma_+ = \sigma_- = \sigma$, the class-wise natural risk can be expressed as follows:

$$R_{nat}^{+1}(f_{nat}) = \Phi\left(\frac{-d^2(\mu_+ + \mu_-)^2 - 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)}\right) \tag{15}$$

$$R_{nat}^{-1}(f_{nat}) = \Phi\left(\frac{-d^2(\mu_+ + \mu_-)^2 + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)}\right). \tag{16}$$

Proof. For any classifier $f(x)$ in Equation (2), we first calculate its natural risk.

$$R_{nat}(f) = \mathbb{E}_{(x,y)\sim\mathcal{D}^*}(\mathbb{1}(f(x) \neq y)) \tag{17}$$

$$= \mathbb{P}_{(x,y)\sim\mathcal{D}^*}(f(x) \neq y) \tag{18}$$

$$= \mathbb{P}(y = +1) \cdot \mathbb{P}(f(x) = -1|y = +1) + \mathbb{P}(y = -1) \cdot \mathbb{P}(f(x) = +1|y = -1) \tag{19}$$

$$= \alpha \cdot R_{nat}^{+1}(f) + (1 - \alpha) \cdot R_{nat}^{-1}(f) \tag{20}$$

where $\alpha = \mathbb{P}(y = +1)$.

Denote $x = (x_1, x_2, \ldots, x_d)'$ and $w = (w_1, w_2, \ldots, w_d)'$, we explicitly calculate $R_{nat}(f, +1)$

$$R_{nat}^{+1}(f) = \mathbb{P}(f(x) = -1|y = +1) \tag{21}$$

$$= \mathbb{P}(\langle w, x\rangle + b < 0|y = +1) = \mathbb{P}(\sum_{i=1}^{d} w_i x_i + b < 0) \tag{22}$$

where $x_1, x_2, \ldots, x_d$ are i.i.d. random variables from Gaussian distribution $\mathcal{N}(\mu_+, \sigma_+^2)$ according to the definition of $\mathcal{D}^*$ in Equation (1).

Like $R_{nat}^{+1}(f)$, we have

$$R_{nat}^{-1}(f) = \mathbb{P}(\sum_{i=1}^{d} w_i x_i + b > 0)$$

where $x_1, x_2, \ldots, x_d$ are i.i.d. from $\mathcal{N}(-\mu_-, \sigma_-^2)$. Denote $f_{nat}(x) = \langle w^*, x\rangle + b^*$. According to the method of [26], we can proof $w_1^* = w_2^* = \cdots = w_d^*$ by contradiction. Based on the properties of Gaussian distribution,

$R_{nat}^{+1}(f_{nat})$ and $R_{nat}^{-1}(f_{nat})$ can be expressed as follows:

$$R_{nat}^{+1}(f_{nat}) = \mathbb{P}(\sum_{i=1}^{d} w_i^* x_i + b < 0) = \mathbb{P}(w_1^* \sum_{i=1}^{d} x_i + b < 0)$$

$$= \mathbb{P}\left(\frac{w_1^* \sum_{i=1}^{d}(x_i - \mu_+)}{\sqrt{w_1^{*2} \sum_{i=1}^{d} \sigma_+^2}} < \frac{-b - dw_1^* \mu_+}{\sqrt{w_1^{*2} \sum_{i=1}^{d} \sigma_+^2}} \right)$$

$$= \Phi\left(-\frac{b + dw_1^* \mu_+}{\sqrt{d} w_1^* \sigma_+} \right)$$

$$R_{nat}^{-1}(f_{nat}) = \mathbb{P}(\sum_{i=1}^{d} w_i^* x_i + b > 0) = \mathbb{P}(w_1^* \sum_{i=1}^{d} x_i + b > 0)$$

$$= \mathbb{P}\left(\frac{w_1^* \sum_{i=1}^{d}(x_i - \mu_-)}{\sqrt{w_1^{*2} \sum_{i=1}^{d} \sigma_-^2}} > \frac{-b + dw_1^* \mu_-}{\sqrt{w_1^{*2} \sum_{i=1}^{d} \sigma_-^2}} \right)$$

$$= 1 - \Phi\left(\frac{-b + dw_1^* \mu_-}{\sqrt{d} w_1^* \sigma_-} \right)$$

where Φ is c.d.f. of normal Gaussian distribution $\mathcal{N}(0, 1)$. Then, we get

$$R_{nat}(f_{nat}) = \alpha \Phi\left(-\frac{b + dw_1^* \mu_+}{\sqrt{d} w_1^* \sigma_+} \right) + (1 - \alpha) \Phi\left(\frac{b - dw_1^* \mu_-}{\sqrt{d} w_1^* \sigma_-} \right).$$

For simplicity, we denote $\eta^* = \frac{b^*}{w_1^*}$. Then, we will find the optimal η^* which minimize the overall natural risk $R_{nat}(f_{nat})$ by takeing $\frac{dR_{nat}(f_{nat})}{d\eta^*} = 0$. In detail, it is

$$\alpha \frac{1}{\sqrt{2\pi}} \exp(-\frac{1}{2}(\frac{\eta^* + d\mu_+}{\sqrt{d}\sigma_+})^2) \frac{-1}{\sqrt{d}\sigma_+} + (1-\alpha) \frac{1}{\sqrt{2\pi}} \exp(-\frac{1}{2}(\frac{\eta^* - d\mu_-}{\sqrt{d}\sigma_-})^2) \frac{1}{\sqrt{d}\sigma_-} = 0. \quad (23)$$

Simplifying it gives

$$\left(\frac{\eta^* + d\mu_+}{\sigma_+} \right)^2 - \left(\frac{\eta^* - d\mu_-}{\sigma_-} \right)^2 = 2d \log\left(\frac{\alpha\sigma_-}{(1-\alpha)\sigma_+} \right). \quad (24)$$

Denote $K = d \log\left(\frac{\alpha\sigma_-}{(1-\alpha)\sigma_+} \right)$. Without loss of generality, we assume $K > 0$. Then we obtain

$$(\sigma_-^2 - \sigma_+^2)\eta^{*2} + 2d(\mu_+ \sigma_-^2 + \mu_- \sigma_+^2)\eta^* + d^2(\mu_+^2 \sigma_-^2 - \mu_-^2 \sigma_+^2) = 2K\sigma_+^2 \sigma_-^2. \quad (25)$$

Hence, η^* can be expressed as follows:

$$\eta^* = \frac{-d(\mu_+ \sigma_-^2 + \mu_- \sigma_+^2) + \sigma_+ \sigma_- (\mu_+ + \mu_-)\sqrt{1 + 2K\frac{\sigma_-^2 - \sigma_+^2}{(\mu_+ + \mu_-)^2}}}{\sigma_-^2 - \sigma_+^2}. \quad (26)$$

Then class-wise natural risk is

$$R_{nat}^{+1}(f_{nat}) = \Phi\left(-\frac{\eta^* + d\mu_+}{\sqrt{d}\sigma_+} \right)$$

$$R_{nat}^{-1}(f_{nat}) = \Phi\left(\frac{\eta^* - d\mu_-}{\sqrt{d}\sigma_-} \right).$$

In particular, when $\sigma_+ = \sigma_- = \sigma$, then Equation (25) can be simplified as

$$2d(\mu_+ + \mu_-)\eta^* + d^2(\mu_+^2 - \mu_-^2) = 2K\sigma^2. \quad (27)$$

In this case, η^* can be expressed as follows:

$$\eta^* = \frac{-d^2(\mu_+^2 - \mu_-^2) + 2K\sigma^2}{2d(\mu_+ + \mu_-)}. \quad (28)$$

and corresponding class-wise natural risk can be expressed as follows:

$$R_{nat}^{+1}(f_{nat}) = \Phi\left(\frac{-d^2(\mu_+ + \mu_-)^2 - 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)} \right)$$

$$R_{nat}^{-1}(f_{nat}) = \Phi\left(\frac{-d^2(\mu_+ + \mu_-)^2 + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)} \right).$$

$\square$

B.2 Adversarially Trained Linear model

Theorem 5.3. *For the adversarial trained linear classifier f_{adv} that minimizes the adversarial risk:*

$$f_{adv}(x) = \arg\min_{f} \mathbb{E}_{(x,y)\sim\mathcal{D}^*}\Big[\sup_{z\in\mathcal{U}(x,\epsilon)}(\mathbb{1}(f(z)\neq y)\Big], \tag{29}$$

if $\sigma_+ \neq \sigma_-$, the class-wise adversarial risk can be expressed as follows:

$$R_{adv}^{+1}(f_{adv}) = \Phi\left(\frac{-\gamma^* - d(\mu_+ - \epsilon_{test})}{\sqrt{d}\sigma_+}\right) \tag{30}$$

$$R_{adv}^{-1}(f_{adv}) = \Phi\left(\frac{\gamma^* - d(\mu_- - \epsilon_{test})}{\sqrt{d}\sigma_-}\right) \tag{31}$$

where $\Phi(\cdot)$ is the c.d.f. of standard Gaussian distribution $\mathcal{N}(0,\,1)$ and

$$\gamma^* = \frac{B + \sigma_+\sigma_-(\mu_+ + \mu_- - 2\epsilon_{train})\sqrt{1 + \frac{2K(\sigma_-^2 - \sigma_+^2)}{(\mu_+ + \mu_- - 2\epsilon_{train})^2}}}{\sigma_-^2 - \sigma_+^2}$$

where $B = -d(\mu_+\sigma_-^2 + \mu_-\sigma_+^2 - \epsilon_{train}(\sigma_+^2 + \sigma_-^2))$ and K is a positive constant. If $\sigma_+ = \sigma_- = \sigma$, the class-wise adversarial risk can be expressed as follows:

$$R_{adv}^{+1}(f_{adv}) = \Phi\left(\frac{-C - 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}\right)$$

$$R_{adv}^{-1}(f_{adv}) = \Phi\left(\frac{-C + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}\right)$$

where $C = d^2(\mu_+ + \mu_- - 2\epsilon_{train})(\mu_+ + \mu_- - 2\epsilon_{test})$.

Proof. For any classifier $f(x)$ in Equation (2), we first calculate its adversarial risk.

$$R_{adv}(f) = \mathbb{E}_{(x,y)\sim\mathcal{D}^*}\left[\sup_{z\in\mathcal{U}(x,\epsilon)}(\mathbb{1}(f(z)\neq y)\right]$$

$$= \alpha\cdot\mathbb{P}\left(\sup_{z\in\mathcal{U}(x,\epsilon)}\mathbb{1}(f(z)=-1)|y=+1\right) + (1-\alpha)\cdot\mathbb{P}\left(\sup_{z\in\mathcal{U}(x,\epsilon)}\mathbb{1}(f(z)=+1)|y=-1\right)$$

$$= \alpha R_{adv}^{+1}(f) + (1-\alpha)R_{adv}^{-1}(f).$$

Denote $f_{adv}(x) = \langle w^*, x\rangle + b^*$. Similar to Theorem 5.2, we can proof $w_1^* = w_2^* = \cdots = w_d^*$. Then $R_{adv}(f,+1)$ and $R_{adv}(f,-1)$ can be expressed as

$$R_{adv}^{+1}(f_{adv}) = \mathbb{P}(w_1^*\sum_{i=1}^{d}(x_i - \epsilon) + b < 0)$$

$$= \mathbb{P}\left(\frac{w_1^*\sum_{i=1}^{d}(x_i - \mu_+)}{\sqrt{w_1^{*2}\sum_{i=1}^{d}\sigma_+^2}} < \frac{-b - d(\mu_+ - \epsilon)w_1^*}{\sqrt{w_1^{*2}\sum_{i=1}^{d}\sigma_+^2}}\right)$$

$$= \Phi\left(-\frac{b + d(\mu_+ - \epsilon)w_1^*}{\sqrt{d}w_1^*\sigma_+}\right)$$

$$R_{adv}^{-1}(f_{adv}) = \mathbb{P}(w_1^*\sum_{i=1}^{d}(x_i + \epsilon) + b > 0)$$

$$= \mathbb{P}\left(\frac{w_1^*\sum_{i=1}^{d}(x_i + \mu_-)}{\sqrt{w_1^{*2}\sum_{i=1}^{d}\sigma_-^2}} > \frac{-b + d(\mu_- - \epsilon)w_1^*}{\sqrt{w_1^{*2}\sum_{i=1}^{d}\sigma_-^2}}\right)$$

$$= 1 - \Phi\left(\frac{-b + d(\mu_- - \epsilon)w_1^*\mu_-}{\sqrt{d}w_1^*\sigma_-}\right).$$

Then, we get

$$R_{adv}(f_{adv}) = \alpha\Phi\left(-\frac{b + d(\mu_+ - \epsilon)w_1^*}{\sqrt{d}w_1^*\sigma_+}\right) + (1-\alpha)\Phi\left(\frac{b - d(\mu_- - \epsilon)w_1^*\mu_-}{\sqrt{d}w_1^*\sigma_-}\right). \tag{32}$$

We denote by ϵ_{train} and ϵ_{test} perturbation radii in training phase and testing phase, respectively. For simplicity, we denote $\gamma^* = \frac{b^*}{w_1^*}$. Now, we will find the optimal γ^* which minimizes adversarial risk $R_{adv}(f_{f_{adv}})$ by takeing $\frac{dR_{adv}(f_{adv})}{d\gamma^*} = 0$. In detail, it is

$$\frac{\alpha}{\sqrt{2\pi}}\exp(-\frac{1}{2}(\frac{\gamma^* + d(\mu_+ - \epsilon_{train})}{\sqrt{d}\sigma_+})^2)\frac{-1}{\sqrt{d}\sigma_+} + \frac{1-\alpha}{\sqrt{2\pi}}\exp(-\frac{1}{2}(\frac{\gamma^* - d(\mu_- - \epsilon_{train})}{\sqrt{d}\sigma_-})^2)\frac{1}{\sqrt{d}\sigma_-} = 0.$$

Simplifying it gives

$$\left(\frac{\gamma^* + d(\mu_+ - \epsilon_{train})}{\sigma_+}\right)^2 - \left(\frac{\gamma^* - d(\mu_- - \epsilon_{train})}{\sigma_-}\right)^2 = 2d\log\left(\frac{\alpha\sigma_-}{(1-\alpha)\sigma_+}\right) = 2K.$$

Hence, γ^* can be expressed as follows:

$$\gamma^* = \frac{-d(\mu_+\sigma_-^2 + \mu_-\sigma_+^2 - \epsilon_{train}(\sigma_+^2 + \sigma_-^2)) + \sigma_+\sigma_-(\mu_+ + \mu_- - 2\epsilon_{train})\sqrt{1 + 2K\frac{\sigma_-^2 - \sigma_+^2}{(\mu_+ + \mu_- - 2\epsilon_{train})^2}}}{\sigma_-^2 - \sigma_+^2}.$$

Then class-wise robust risk is

$$R_{adv}^{+1}(f_{adv}) = \Phi\left(-\frac{\gamma^* + d(\mu_+ - \epsilon_{test})}{\sqrt{d}\sigma_+}\right)$$

$$R_{adv}^{-1}(f_{adv}) = \Phi\left(\frac{\gamma^* - d(\mu_- - \epsilon_{test})}{\sqrt{d}\sigma_-}\right).$$

In particular, when $\sigma_+ = \sigma_- = \sigma$, then we have

$$\gamma^* = \frac{2K\sigma^2 - d^2((\mu_+ - \epsilon_{train})^2 - (\mu_- - \epsilon_{train})^2)}{2d(\mu_+ + \mu_- - 2\epsilon_{train})} \tag{33}$$

and corresponding robust risk is

$$R_{adv}^{+1}(f_{adv}) = \Phi\left(-\frac{d^2(\mu_+ + \mu_- - 2\epsilon_{train})(\mu_+ + \mu_- - 2\epsilon_{test}) + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}\right)$$

$$R_{adv}^{-1}(f_{adv}) = \Phi\left(\frac{-d^2(\mu_+ + \mu_- - 2\epsilon_{train})(\mu_+ + \mu_- - 2\epsilon_{test}) + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}\right).$$

$\square$

B.3   Tradeoff between Average Robustness and Robust Fairness

Theorem 5.5. *Given an adversarially trained linear model f_{adv} in Equation (7), the variance of class-wise robust accuracy $VCRA(f_{adv})$ is increasing with respect to ϵ_{train} if $\sigma_- \geq \sigma_+$.*

Proof. According to the results of Theorem 5.3, we can get class-wise robust accuracy:

$$p_{adv}(1) = 1 - R_{adv}^{+1}(f_{adv}) \tag{34}$$

$$p_{adv}(-1) = 1 - R_{adv}^{-1}(f_{adv}). \tag{35}$$

Then the variance of class-wise robust accuracy can be expressed as

$$VCRA(f_{adv}) = \text{Var}(p_{adv}(+1), p_{adv}(-1)) \tag{36}$$

$$= \text{Var}\left(1 - R_{adv}^{+1}(f_{adv}), 1 - R_{adv}^{-1}(f_{adv})\right) \tag{37}$$

$$= \text{Var}\left(R_{adv}^{+1}(f_{adv}), R_{adv}^{-1}(f_{adv})\right) \tag{38}$$

$$= \frac{\left(R_{adv}^{+1}(f_{adv}) - R_{adv}^{-1}(f_{adv})\right)^2}{2}. \tag{39}$$

If $\sigma_- \geq \sigma_+$, we can easily verify that $R_{adv}^{+1}(f_{adv})$ is decreasing and $R_{adv}^{-1}(f_{adv})$ is increasing with respect to ϵ_{train} according to Theorem 5.3. Hence, $VCRA(f_{adv})$ is increasing with respect to ϵ_{train}. $\square$

Theorem 5.6. *Given an adversarially trained linear model f_{adv} in Equation (7) and suppose $\sigma_+ = \sigma_-$. The variance of class-wise robust accuracy of f_{adv} can be expressed as follows:*

$$VCRA(f_{adv}) = \frac{1}{\pi d^3}\exp(-\xi^2)\left(\frac{K\sigma}{\mu_+ + \mu_- - 2\epsilon_{train}}\right)^2$$

where ξ is a constant and K is a positive constant.

Proof. According to Lagrange's Mean Value Theorem, there exists some ξ such that

$$R_{adv}^{-1}(f_{adv}) - R_{adv}^{+1}(f_{adv}) \tag{40}$$

$$= \Phi\left(\frac{-d^2(\mu_+ + \mu_- - 2\epsilon_{train})(\mu_+ + \mu_- - 2\epsilon_{test}) + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}\right) \tag{41}$$

$$- \Phi\left(-\frac{d^2(\mu_+ + \mu_- - 2\epsilon_{train})(\mu_+ + \mu_- - 2\epsilon_{test}) + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}\right) \tag{42}$$

$$= \Phi^{'}(\xi)\left(\frac{-C + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})} + \frac{C + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}\right) \tag{43}$$

$$= \frac{1}{\sqrt{2\pi}}\exp(-\frac{\xi^2}{2})\left(\frac{2K\sigma}{d^{3/2}(\mu_+ + \mu_- - 2\epsilon_{train})}\right) \tag{44}$$

where $C = d^2(\mu_+ + \mu_- - 2\epsilon_{train})(\mu_+ + \mu_- - 2\epsilon_{test})$. Therefore, we obtain final expression of variance:

$$VCRA(f_{adv}) = \frac{1}{\pi d^3}\exp(-\xi^2)\left(\frac{K\sigma}{\mu_+ + \mu_- - 2\epsilon_{train}}\right)^2. \tag{45}$$

$\square$

Theorem 5.7. *Given an adversarially trained linear model f_{adv} in Equation (7) and a naturally trained linear model f_{nat} in Equation (3), and suppose $\sigma_+ = \sigma_-$. If $\epsilon_{train} < \frac{\mu_+ + \mu_-}{e}$ and $\epsilon_{test} < \frac{\mu_+ + \mu_-}{2} - \frac{eK^3\sigma^3}{d^4(\mu_+ + \mu_-)}$, we have*

$$\frac{VCRA(f_{adv})}{VCRA(f_{nat})} = \exp(\zeta_2^2 - \zeta_1^2) \cdot \left(\frac{\mu_+ + \mu_-}{\mu_+ + \mu_- - 2\epsilon_{train}}\right)^2 \geq 1$$

where K is a positive constant, ζ_1, ζ_2 are two constants.

Proof. According to Theorem 5.2 and Theorem 5.3, we have

$$R_{adv}^{+1}(f_{nat}) = \Phi\left(-\frac{d^2(\mu_+ + \mu_-)(\mu_+ + \mu_- - 2\epsilon_{test}) + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}\right)$$

$$R_{adv}^{-1}(f_{nat}) = \Phi\left(\frac{-d^2(\mu_+ + \mu_-)(\mu_+ + \mu_- - 2\epsilon_{test}) + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}\right).$$

Denote $C = d^2(\mu_+ + \mu_- - 2\epsilon_{train})(\mu_+ + \mu_- - 2\epsilon_{test})$. Similar to the proof of Theorem 5.6, according to Lagrange Mean Value Theorem, there exits ζ_1 and ζ_2 such that

$$R_{adv}^{-1}(f_{adv}) - R_{adv}^{+1}(f_{adv}) = \frac{1}{\sqrt{2\pi}}\exp(-\frac{\zeta_1^1}{2})\left(\frac{2K\sigma}{d^{3/2}(\mu_+ + \mu_- - 2\epsilon_{train})}\right) \tag{46}$$

and

$$R_{adv}^{-1}(f_{nat}) - R_{adv}^{+1}(f_{nat}) = \frac{1}{\sqrt{2\pi}}\exp(-\frac{\zeta_2^2}{2})\left(\frac{2K\sigma}{d^{3/2}(\mu_+ + \mu_-)}\right) \tag{47}$$

where

$$\zeta_1 \in \left(-\frac{C + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}, \frac{-C + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}\right) \tag{48}$$

$$\zeta_2 \in \left(-\frac{d^2(\mu_+ + \mu_-)(\mu_+ + \mu_- - 2\epsilon_{test}) + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)}, \frac{-d^2(\mu_+ + \mu_-)(\mu_+ + \mu_- - 2\epsilon_{test}) + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)}\right)$$
$$\tag{49}$$

Therefore, we get

$$\frac{VCRA(f_{adv})}{VCRA(f_{nat})} = \frac{\frac{1}{\pi d^3}\exp(-\zeta_1^2)\left(\frac{K\sigma}{d^{3/2}(\mu_+ + \mu_- - 2\epsilon)}\right)^2}{\frac{1}{\pi d^3}\exp(-\zeta_2^2)\left(\frac{K\sigma}{d^{3/2}(\mu_+ + \mu_-)}\right)^2} \tag{50}$$

$$= \exp(\zeta_2^2 - \zeta_1^2) \cdot \left(\frac{\mu_+ + \mu_-}{\mu_+ + \mu_- - 2\epsilon_{train}}\right)^2. \tag{51}$$

If $\epsilon_{train} < \frac{\mu_+ + \mu_-}{e}$ and $\epsilon_{test} < \frac{\mu_+ + \mu_-}{2} - \frac{eK^3\sigma^3}{d^4(\mu_+ + \mu_-)}$, we can get

$$\frac{VCRA(f_{adv})}{VCRA(f_{nat})} \geq \exp\left(\frac{-4K^3\sigma^3}{d^4(\mu_+ + \mu_- - 2\epsilon_{test})(\mu_+ + \mu_- - 2\epsilon_{train})}\right) \cdot \left(\frac{\mu_+ + \mu_-}{\mu_+ + \mu_- - 2\epsilon_{train}}\right)^2 \geq 1.$$
$$\tag{52}$$

$\square$

Theorem B.6. *Given an adversarial trained linear model f_{adv} in Equation (7) and a natural trained linear model f_{nat} in Equation (3),and suppose $\sigma_+ = \sigma_-$. If $\epsilon_{test} < \sqrt{\frac{\mu_+ + \mu_-}{2} - \frac{2K\sigma^2}{d^2(\mu_+ + \mu_-)}}$ and $\epsilon_{train} < \frac{\mu_+ + \mu_-}{2} - \frac{K\sigma}{\epsilon_{test}d^{3/2}}$, we have*

$$\frac{VCRA(f_{adv})}{VCA(f_{nat})} = \exp(\xi_2^2 - \xi_1^2) \cdot \left(\frac{\mu_+ + \mu_-}{\mu_+ + \mu_- - 2\epsilon_{train}}\right)^2 \geq 1$$

where K is a positive constant, ξ_1, ξ_2 are two constants and $\xi_2 < \xi_1 < 0$,

Proof. Under the conditions that $\epsilon_{train} < \frac{\mu_+ + \mu_-}{2} - \frac{K\sigma}{\epsilon_{test}d^{3/2}}$ and $\epsilon_{test} < \sqrt{\frac{\mu_+ + \mu_-}{2} - \frac{2K\sigma^2}{d^2(\mu_+ + \mu_-)}}$, we obtain following relations:

$$-\frac{d^2(\mu_+ + \mu_-)^2 + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)} < \frac{-d^2(\mu_+ + \mu_-)^2 + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)} <$$

$$\frac{-d^2(\mu_+ + \mu_- - 2\epsilon_{train})(\mu_+ + \mu_- - 2\epsilon_{test}) - 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}$$

$$< \frac{-d^2(\mu_+ + \mu_- - 2\epsilon_{train})(\mu_+ + \mu_- - 2\epsilon_{test}) + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})} < 0.$$

Denote $C = d^2(\mu_+ + \mu_- - 2\epsilon_{train})(\mu_+ + \mu_- - 2\epsilon_{test})$. Similar to the proof of Theorem 5.7, according to Lagrange Mean Value Theorem, there exits ξ_1 and ξ_2 such that

$$R_{adv}^{-1}(f_{adv}) - R_{adv}^{+1}(f_{adv}) = \tag{53}$$

$$= \frac{1}{\sqrt{2\pi}} \exp(-\frac{\xi_1^1}{2})\left(\frac{2K\sigma}{d^{3/2}(\mu_+ + \mu_- - 2\epsilon_{train})}\right) \tag{54}$$

and

$$R_{nat}^{-1}(f_{nat}) - R_{nat}^{+1}(f_{nat}) = \tag{55}$$

$$\Phi'(\xi_2)\left(\frac{-d^2(\mu_+ + \mu_-)^2 + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)} + \frac{d^2(\mu_+ + \mu_-)^2 + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)}\right) \tag{56}$$

$$\frac{1}{\sqrt{2\pi}} \exp(-\frac{\xi_2^2}{2})\left(\frac{2K\sigma}{d^{3/2}(\mu_+ + \mu_-)}\right) \tag{57}$$

where

$$\xi_1 \in \left(-\frac{C + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}, \frac{-C + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_- - 2\epsilon_{train})}\right) \tag{58}$$

$$\xi_2 \in \left(-\frac{d^2(\mu_+ + \mu_-)^2 + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)}, \frac{-d^2(\mu_+ + \mu_-)^2 + 2K\sigma^2}{2d^{3/2}\sigma(\mu_+ + \mu_-)}\right) \tag{59}$$

Note that Equation (53) implies $\xi_2 < \xi_1 < 0$ and thus $\xi_1^2 < \xi_2^2$. Then we get

$$\frac{\text{VCRA}(f_{adv})}{\text{VCA}(f_{nat})} = \frac{\frac{1}{\pi d^3}\exp(-\xi_1^2)\left(\frac{K\sigma}{d^{3/2}(\mu_+ + \mu_- - 2\epsilon)}\right)^2}{\frac{1}{\pi d^3}\exp(-\xi_2^2)\left(\frac{K\sigma}{d^{3/2}(\mu_+ + \mu_-)}\right)^2} \tag{60}$$

$$= \exp(\xi_2^2 - \xi_1^2) \cdot \left(\frac{\mu_+ + \mu_-}{\mu_+ + \mu_- - 2\epsilon_{train}}\right)^2 \geq 1. \tag{61}$$

$$\square$$

B.4 Fairly Adversarial Training

Theorem B.7. *[1]. Let (x_1, y_1), (x_2, y_2), ...,(x_n, y_n) be drawn independent and identically distributed (i.i.d.) from the unknown distribution $\mathcal{D}$. Under appropriate conditions on the loss $\ell(\cdot)$, parameter space Θ, with probability of at least $1 - \delta$, the following holds for all $\theta \in \Theta$,*

$$R_{nat}(f) \leq \hat{R}_{nat}(f) + \sqrt{\frac{\text{Var}\,\ell(\theta, x, y)\frac{1}{\delta}}{n}} + \frac{C}{n} \tag{62}$$

where C is a constant, $\hat{R}_{nat}(f) = \frac{1}{n}\sum_{i=1}^n \ell(\theta, x_i, y_i)$ and Var *indicates the variance.*

Theorem 6.1. *Under the conditions of Theorem B.7, with probability of at least $1 - \delta$, the following holds for all $\theta \in \Theta$:*

$$R_{adv}(f) \leq +\hat{R}_{adv}(f) + \sqrt{\frac{\mathrm{VCAR}(f)\frac{1}{\delta}}{n}} + \frac{C}{n}. \tag{63}$$

Proof. For simplicity, we denote $\bar{\ell}(\theta, x, y) = \frac{1}{L}\sum_{j=1}^{L}\ell(\theta, x, i)$. According to the properties of conditional expectation, we have

$$
\begin{aligned}
\mathrm{Var}(\ell(\theta, x, y)) &= \mathbb{E}_{x\sim\mathcal{D}_x}\left(\mathrm{Var}(\ell(\theta, x, y)|x)\right) \\
&= \mathbb{E}_{x\sim\mathcal{D}_x}\left[\frac{1}{L}\sum_{i=1}^{L}(\ell(\theta, x, i) - \bar{\ell}(\theta, x, y))^2\right] \\
&= \frac{1}{L}\sum_{i=1}^{L}\mathbb{E}_{x\sim\mathcal{D}_x}\left[(\ell(\theta, x, i) - \bar{\ell}(\theta, x, y))^2\right].
\end{aligned} \tag{64}
$$

Because squared function is convex, according to Jensen's inequality, we have

$$
\begin{aligned}
\mathbb{E}_{x\sim\mathcal{D}_x}\left[(\ell(\theta, x, i) - \bar{\ell}(\theta, x, y))^2\right] &\leq \left[\mathbb{E}_{x\sim\mathcal{D}_x}(\ell(\theta, x, i) - \bar{\ell}(\theta, x, y))\right]^2 \\
&= \left[\mathbb{E}_{x\sim\mathcal{D}_x}(\ell(\theta, x, i)) - \frac{1}{L}\sum_{j=1}^{L}\mathbb{E}_{x\sim\mathcal{D}_x}\ell(\theta, x, j))\right]^2 \\
&= \left[R(f, i) - \frac{1}{L}\sum_{j=1}^{L}R(f, j)\right]^2.
\end{aligned} \tag{65}
$$

Similar to [27], we replace $\ell(\theta, x, y)$ with $\tilde{\ell}(\theta, x, y)$ in Equation (65). We can then obtain the following inequality:

$$\mathrm{Var}(\tilde{\ell}(\theta, x, y)) \leq \mathrm{VCAR}(f). \tag{66}$$

Combining with Theorem B.7, we get

$$R_{adv}(f) \leq \frac{1}{n}\sum_{i=1}^{n}\tilde{\ell}(\theta, x_i, y_i) + \sqrt{\frac{\mathrm{VCAR}(f)\frac{1}{\delta}}{n}}) + \frac{C}{n}. \tag{67}$$

$\square$

C More Experimental Results in Section 7

C.1 More Experimental Results of FAT

(a) $\epsilon_{train} = 4/255$ (b) $\epsilon_{train} = 8/255$ (c) $\epsilon_{train} = 12/255$ (d) $\epsilon_{train} = 16/255$

Figure 3: The variance of class-wise robust accuracy for our proposed FAT and Madry using ResNet18 on CIFAR-10. The perturbation radius for AT is chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM with testing perturbation radius $\epsilon_{test} = 16/255$.

In Figures 3, 4 and 5, Tables 8, 9, 10 and 11, we present more experimental results to validate the effectiveness of FAT under ResNet18. The implementation details resemble those in Section 7. From the results above, we can make similar observations to these in Section 7. Specifically, compared with Madry and TRADES, FAT obtains smaller variance of class-wise robust accuracy while achieving comparable average robust accuracy.

(a) $\epsilon_{train} = 4/255$ (b) $\epsilon_{train} = 8/255$ (c) $\epsilon_{train} = 12/255$ (d) $\epsilon_{train} = 16/255$

Figure 4: The variance of class-wise robust accuracy for our proposed FAT and Madry using ResNet18 on CIFAR-100. The perturbation radii for AT are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM with testing perturbation radius $\epsilon_{test} = 16/255$.

(a) $\epsilon_{train} = 4/255$ (b) $\epsilon_{train} = 8/255$ (c) $\epsilon_{train} = 12/255$ (d) $\epsilon_{train} = 16/255$

Figure 5: The variance of class-wise robust accuracy for our proposed FAT and TRADES using ResNet18 on CIFAR-10. The perturbation radii for AT are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM with testing perturbation radius $\epsilon_{test} = 16/255$.

Table 8: The variance of class-wise robust accuracy (10^{-2}) for Madry and FAT using ResNet18 on CIFAR-100. The perturbation radii are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM, PGD-20 and C&W with different testing perturbation radii $\epsilon_{test} = \{16/255, 20/255\}$.

attack algorithm	FGSM				PGD-20				C&W			
ϵ_{test}	16/255		20/255		16/255		20/255		16/255		20/255	
ϵ_{train}	PGD	FAT	PGD	FAT	PGD	FAT	PGD	FAT	PGD	FAC	PDG	FAT
4/255	1.25	1.25	0.81	0.79	0.19	0.19	0.05	0.05	0.23	0.22	0.07	0.06
8/255	1.80	1.69	1.31	1.22	0.60	0.57	0.26	0.25	0.70	0.66	0.33	0.31
12/255	2.17	2.04	1.60	1.47	0.96	0.95	0.52	0.44	0.97	0.95	0.54	0.47
16/255	2.32	2.17	1.89	1.77	1.12	1.08	0.65	0.60	1.18	1.09	0.65	0.61

Table 9: The average robust accuracy (10^{-2}) for Madry and FAT using ResNet18 on CIFAR-100. The perturbation radii are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM, PGD-20 and C&W with different testing perturbation radii $\epsilon_{test} = \{16/255, 20/255\}$. We use **bold** to denote higher robust accuracy.

attack algorithm	FGSM				PGD-20				C&W			
ϵ_{test}	16/255		20/255		16/255		20/255		16/255		20/255	
ϵ_{train}	PGD	FAT	PGD	FAT	PGD	FAT	PGD	FAT	PGD	FAC	PDG	FAT
4/255	11.94	11.89	8.01	7.89	1.83	**2.00**	0.69	**0.78**	2.15	2.14	0.76	**0.83**
8/255	16.52	16.41	12.35	11.94	5.16	**5.19**	2.65	2.62	5.65	5.49	3.10	2.87
12/255	18.56	**18.74**	14.76	**14.79**	7.81	**7.82**	4.43	4.26	8.06	8.01	4.58	**4.61**
16/255	19.78	**19.81**	16.26	**16.78**	8.95	**9.01**	5.42	**5.47**	9.03	**9.53**	5.54	**5.62**

Moreover, this finding still holds under various neural networks, attack algorithms and datasets. These observations suggest that FAT can effectively suppress the growth of variance of class-wise robust accuracy while improving average robust accuracy compared with Madry and TRADES. Thus, FAT can mitigate the tradeoff between robustness and robust fairness.

Table 10: The variance of class-wise robust accuracy (10^{-2}) for TRADES and FAT using ResNet18 on CIFAR-10. The perturbation radii are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM, PGD-20 and C&W with different testing perturbation radii $\epsilon_{test} = \{16/255, 20/255\}$.

attack algorithm	FGSM				PGD-20				C&W			
ϵ_{test}	16/255		20/255		16/255		20/255		16/255		20/255	
ϵ_{train}	TRADES	FAT	TRADES	FAT	TRADES	FAT	TRADES	FAT	TRADES	FAC	TRADES	FAT
4/255	1.59	1.50	1.15	1.08	0.18	0.15	0.04	0.03	0.19	0.17	0.04	0.04
8/255	2.48	2.45	2.18	2.09	0.73	0.65	0.25	0.23	0.76	0.76	0.28	0.21
12/255	2.64	2.48	2.45	2.39	1.48	1.46	0.71	0.65	1.37	1.31	0.62	0.59
16/255	2.69	2.64	2.50	2.45	1.67	1.59	0.84	0.73	1.55	1.47	0.73	0.71

Table 11: The average robust accuracy (10^{-2}) for TRADES and FAT using ResNet18 on CIFAR-10. The perturbation radii are chosen from $\epsilon_{train} = \{4/255, 8/255, 12/255, 16/255\}$. The adversarial testing examples are generated by FGSM, PGD-20 and C&W with different testing perturbation radii $\epsilon_{test} = \{16/255, 20/255\}$. We use **bold** to denote higher robust accuracy.

attack algorithm	FGSM				PGD-20				C&W			
ϵ_{test}	16/255		20/255		16/255		20/255		16/255		20/255	
ϵ_{train}	TRADES	FAT	TRADES	FAT	TRADES	FAT	TRADES	FAT	TRADES	FAC	TRADES	FAT
4/255	32.10	**32.79**	23.61	**24.02**	4.9	**5.14**	1.80	**1.93**	5.58	5.56	2.07	2.07
8/255	42.27	**42.69**	35.37	35.37	16.84	**18.54**	8.38	**9.04**	15.74	16.56	7.92	**8.22**
12/255	42.74	**43.32**	37.24	**37.88**	23.90	23.81	14.68	14.22	20.34	**20.71**	12.27	**12.35**
16/255	43.71	**43.98**	38.34	**38.35**	26.11	**26.81**	16.55	**16.66**	22.37	**22.93**	13.48	**13.69**

C.2 Sensitivity of regularization hyperparameter

The regularization parameter λ is an important hyperparameter in our proposed method. We show how the regularization parameter affects the performance of our robust classifiers by numerical experiments on CIFAR-10. From Figure 6, we can observe that as the regularization parameter λ increases, the variance of class-wise robust accuracy decreases; while the average robust accuracy first increases and then decreases. Empirically, when we set the hyperparameter $\lambda = 0.1$, our method is able to learn classifiers with comparable average robust accuracy and smaller variance of class-wise robust accuracy compared with Madry and TRADES.

(a) Madry and FAT   (b) Madry and FAT   (c) TRADES and FAT   (d) TRADES and FAT

Figure 6: Sensitivity of regularization hyperparameter λ on CIRAR-10.