Improving
Zero-shot Generalization in Offline Reinforcement Learning using Generalized Similarity Functions

Abstract

Reinforcement learning (RL) agents are widely used for solving complex sequential decision making tasks, but still exhibit difficulty in generalizing to scenarios not seen during training. While prior online approaches demonstrated that using additional signals beyond the reward function can lead to better generalization capabilities in RL agents, i.e., using self-supervised learning (SSL), they struggle in the offline RL setting, i.e., learning from a static dataset. We show that performance of online algorithms for generalization in RL can be hindered in the offline setting due to poor estimation of similarity between observations. We propose a new theoretically-motivated framework called Generalized Similarity Functions (GSF), which uses contrastive learning to train an offline RL agent to aggregate observations based on the similarity of their expected future behavior, where we quantify this similarity using *generalized value functions*. We show that GSF is general enough to recover existing SSL objectives while also improving zero-shot generalization performance on two pixel-based offline RL benchmarks.

1 Introduction

Reinforcement learning (RL) is a powerful framework for solving complex tasks that require a sequence of decisions. The RL paradigm has allowed for major breakthroughs in various fields, e.g. outperforming humans on video games [Mnih et al., 2015, Schwarzer et al., 2020], controlling stratospheric balloons [Bellemare et al., 2020] and learning reward functions from robot manipulation videos [Chen et al., 2021]. More recently, RL agents have been tested in a generalization setting, i.e. in which training involves a finite number of related tasks sampled from some distribution, with a potentially distinct sampling distribution during test time [Cobbe et al., 2019, Song et al., 2019, Hjelm et al., 2022]. The main issue for designing generalizable agents is the lack of on-policy data from tasks not seen during training: it is impossible to enumerate all variants of a real-world environment during training and hence the agent must extrapolate from a (limited) training task collection onto a broader set of problems. Since the learning agent is given no training data from test-time tasks, this problem is referred to as zero-shot generalization. In our work, we are interested in the problem of zero-shot generalization where the difference between tasks is predominantly due to perceptually distinct observations. An example of this setting is any environment with distractor features [Cobbe et al., 2020, Stone et al., 2021], i.e. features with no dependence on the reward signal nor the agent's decisions. This generalization setting has recently received much attention [Liu et al., 2020a, Agarwal et al., 2021a, Mazoure et al., 2022], due to its particular relevance to real-world scenarios, for example deploying the same autonomous driving agent at day or at night.

Generalization capabilities of an agent can be analyzed through the prism of *representation learning*, under which the agent's current belief about a rich and high-dimensional environment are summarized

in a low-dimensional entity, called a representation. Recent work in online RL has shown that learning state representations with specific properties such as disentanglement [Higgins et al., 2017] or linear separability [Lin et al., 2020] can improve zero-shot generalization performance. Achieving this with limited data (i.e. offline RL) is challenging, since the representation will have a large estimation error over regions of low data coverage. A common solution to mitigate this task-specific overfitting and extracting the most information out of the data consists in introducing auxiliary learning signals other than instantaneous reward [Raileanu and Fergus, 2021]. As we show later in the paper, many such signals already contained in the dataset can be used to further improve generalization performance. For instance, the generalization performance of PPO on Procgen remains limited even when training on 200M frames, while generalization-oriented agents [Raileanu and Fergus, 2021, Mazoure et al., 2022] can outperform it by leveraging additional auxiliary signals. However, a major issue with the aforementioned methods is their exorbitant reliance on online access to the environment, an impractical restriction for real-world scenarios.

In contrast, in many real-world scenarios access to the environment is restricted to an offline, fixed dataset of experience [Ernst et al., 2005, Lange et al., 2012]. A natural limitation for generalization from offline data is that policy improvement is dependent on dataset quality. Specifically, high-dimensional problems such as control from pixels require large amounts of training experience: a standard training of PPO [Schulman et al., 2017] for 25 million frames on Procgen [Cobbe et al., 2020] generates more than 300 Gb of data, an impractical amount of data to share for offline RL research. Improving zero-shot generalization performance from an offline dataset of high-dimensional observations is therefore a hard problem due to limitations on dataset size and quality.

In this work, we are interested in improving zero-shot generalization across a family of Partially-Observable Markov decision processes [POMDPs, Murphy, 2000] in an offline RL setting, i.e. by training agents on a fixed dataset. We hypothesize that in order for an RL agent to be able to generalize across perceptually different POMDPs without adaptation, observations with similar future behavior should be assigned to close representations. We use the generalized value function (GVF) framework [Sutton et al., 2011] to capture future behavior with respect to any instantaneous signal (called cumulant) at a given state. Specifically, the choice of cumulant determines the nature of the behavioral similarity that is induced into state representations. For example, using reward similarity leads to learning bisimulation metrics [Ferns et al., 2004, Li et al., 2006, Castro, 2020, Zhang et al., 2020], while using future state-action visitation counts encourages reward-free behavioral similarity [Misra et al., 2020, Liu et al., 2020a, Agarwal et al., 2021a, Mazoure et al., 2022].

Our main contributions are as follows:

1. We propose Generalized Similarity Functions (GSF), a novel self-supervised learning algorithm for reinforcement learning that aggregates latent representations of observations by their future behavior (or generalized value function).

2. Existing offline RL benchmarks [Fu et al., 2020, Gulcehre et al., 2020] are not well-suited to test zero-shot generalization, and so we devise two new benchmarks: offline Procgen and Distracting Control Suite. The first consists of 5M transitions from 200 related levels of 16 distinct games; the second consists of 1M transitions from 3 variations of 4 distincts tasks.

3. We evaluate performance of GSF and other baseline methods on both benchmarks, and show that GSF outperforms both previous state-of-the-art offline RL and representation learning baselines on the entire distribution of levels.

4. We analyze the theoretical properties of GSF and describe the impact of hyperparameters and cumulant functions on empirical behavior in both offline Procgen and the offline Distracting Suite benchmarks.

2 Related Works

Generalization in reinforcement learning   Generalizing a model's predictions across a variety of unseen, high-dimensional inputs has been extensively studied in the static supervised learning setting [Bartlett, 1998, Triantafillou et al., 2019, Valle-Pérez and Louis, 2020, Liu et al., 2020b]. Generalization in RL has received a lot of attention: extrapolation to unseen rewards [Barreto et al., 2016, Misra et al., 2020], observations [Zhang et al., 2020, Raileanu and Fergus, 2021, Liu et al., 2020a, Agarwal et al., 2021a, Mazoure et al., 2022] and transition dynamics [Ball et al., 2021]. Each

generalization scenario is best solved by their respective set of methods: sufficient exploration [Misra et al., 2020, Agarwal et al., 2020], auxiliary learning signals [Srinivas et al., 2020, Mazoure et al., 2020, Stooke et al., 2021] or data augmentation [Ball et al., 2021, Sinha and Garg, 2021]. Data augmentation is a promising technique, but typically relies on handcrafted domain information, which might not be available *a priori*. In fact, we will show in our experiments that generalization in the offline RL setting is poor even when using such handcrafted data augmentations, without additional representation learning mechanisms. In this work, we posit that representation learning should use instantaneous auxiliary signals in order to prevent overfitting onto a unique signal (e.g. reward across tasks) and improve generalization performance. Theoretical generalization guarantees have only been provided so far for limited scenarios, mostly for bandits [Swaminathan and Joachims, 2015], linear MDPs [Boyan and Moore, 1995, Wang et al., 2021b, Nachum and Yang, 2021] and across reward functions [Castro and Precup, 2010, Barreto et al., 2016, Wang et al., 2021a, Touati and Ollivier, 2021].

Representation learning   For simple POMDPs, near-optimal policies can be found by optimizing for the reward alone. However, more complex settings may require additional auxiliary signals in order to find state abstractions better suited for control. The problem of learning meaningful state representations (or abstractions) for planning and control has been extensively studied previously [Jong and Stone, 2005, Li et al., 2006], but saw real breakthroughs only recently, in particular due to advances in self-supervised learning (SSL). Outside of RL, SSL has achieved spectacular results by closing the gap between unsupervised and supervised learning on certain datasets [Hjelm et al., 2018, Oord et al., 2018, Caron et al., 2020, Grill et al., 2020]. Representation learning, and specifically self-supervised learning, has also been used to achieve state-of-the-art generalization and sample efficiency results in RL on challenging control problems such as data efficient Atari [Schwarzer et al., 2020, 2021], DeepMind Control [Agarwal et al., 2021a] and Procgen [Mazoure et al., 2020, Stooke et al., 2021, Raileanu and Fergus, 2021, Mazoure et al., 2022]. Noteworthy instances of theoretically-motivated representation learning methods for RL include heuristic-guided learning [Cheng et al., 2021], and random Fourier features [Nachum and Yang, 2021].

Offline reinforcement learning   When learning from a static dataset, agents should balance interpolation and extrapolation errors, while ensuring proper diversity of actions (i.e. prevent collapse to most frequent action in the data). Popular offline RL algorithms such as BCQ [Fujimoto et al., 2019], MBS [Liu et al., 2020c], and CQL [Kumar et al., 2020] rely on a behavior regularization loss [Wu et al., 2019] as a tool to control the extrapolation error. Some methods, such as F-BRC [Kostrikov et al., 2021a] are defined only for continuous action spaces while others, such as MOReL [Kidambi et al., 2020] estimate a pessimistic transition model. The major issue with current offline RL algorithms such as CQL is that they are perhaps overly pessimistic for generalization purposes, i.e. CQL and MBS ensure that the policy improvement is well-supported by the batch of data.

3   Problem setting

3.1   Partially-observable Markov decision processes

A (infinite-horizon) partially-observable Markov decision process [POMDP, Murphy, 2000] M is defined by the tuple $M = \langle \mathcal{S}, p_0, \mathcal{A}, p_{\mathcal{S}}, \mathcal{O}, p_{\mathcal{O}}, r, \gamma \rangle$, where $\mathcal{S}$ is a state space, $p_0 = \mathbb{P}[s_0]$ is the starting state distribution, $\mathcal{A}$ is an action space, $p_{\mathcal{S}} = \mathbb{P}[\cdot | s_t, a_t] : \mathcal{S} \times \mathcal{A} \to \Delta(\mathcal{S})$ is a transition function, $\mathcal{O}$ is an observation space, $p_{\mathcal{O}} = \mathbb{P}[\cdot | s_t] : \mathcal{S} \to \Delta(\mathcal{O})$[1] is an observation function, $r : \mathcal{S} \times \mathcal{A} \to [r_{\min}, r_{\max}]$ is a reward function and $\gamma \in [0, 1)$ is a discount factor. The system starts in one of the initial states $s_0 \sim p_0$ with observation $o_0 \sim p_{\mathcal{O}}(\cdot | s_0)$. At every timestep $t = 1, 2, 3, ..$, the agent, parameterized by a policy $\pi : \mathcal{O} \to \Delta(\mathcal{A})$, samples an action $a_t \sim \pi(\cdot | o_t)$. The environment transitions into a next state $s_{t+1} \sim p_{\mathcal{S}}(\cdot | s_t, a_t)$ and emits a reward $r_t = r(s_t, a_t)$ along with a next observation $o_{t+1} \sim p_{\mathcal{O}}(\cdot | s_{t+1})$.

The goal of an RL agent is to maximize the cumulative discounted rewards $\sum_{t=0}^{\infty} \gamma^t r_t$ obtained over the entire episode. Value-based off-policy RL algorithms achieve this by estimating the state-action value function under a target policy π:

$$Q^\pi(s_t, a_t) = \mathbb{E}_{\mathbb{P}_t^\pi}\left[\sum_{k=1}^{\infty} \gamma^k r(s_{t+k}, a_{t+k}) | s_t, a_t\right], \tag{1}$$

---

[1] $\Delta(\mathcal{X})$ denotes the entire set of distributions over the space $\mathcal{X}$.

for $s_t \in \mathcal{S}, a_t \in \mathcal{A}$ and where $\mathbb{P}_t^\pi$ denotes the joint distribution of $\{s_{t+k}, a_{t+k}\}_{k=1}^\infty$ obtained by executing π in the environment.

An important distinction from online RL is that, in the offline RL setting, we assume access to a historical dataset $\mathcal{D}^\mu$ (instead of a simulator) collected by logging experience of the policy, μ, in the form $\{o_{i,t}, a_{i,t}, r_{i,t}\}_{i=1,t=1}^{i=N,t=T}$ where, for practical purposes, the episode is truncated at T timesteps. Furthermore, we assume that the agent can only be trained on a limited collection of POMDPs $\mathcal{M}_{\text{train}} = \{M_i\}_{i=1}^m$, and its performance is evaluated on the set of test POMDPs $\mathcal{M}_{\text{test}}$. We assume that both $\mathcal{M}_{\text{train}}$ and $\mathcal{M}_{\text{test}}$ were sampled from a common task distribution and that every POMDP $M_i \in \mathcal{M} = \mathcal{M}_{\text{train}} \cup \mathcal{M}_{\text{test}}$ shares the same transition dynamics and reward function with $\mathcal{M}$ but has a different observation function $p_{i,\mathcal{O}}$. Importantly, since we perform control from pixels, we are in the POMDP setting [see Yarats et al., 2019] and therefore emphasize the difference between observations o_t and corresponding states s_t throughout the paper.

3.2 Representation learning

Previous works in the RL literature have studied the use of auxiliary signals to improve generalization performance. Among others, Liu et al. [2020a], Agarwal et al. [2021a] define the similarity of two observations to depend on the distance between action sequences rolled out from that observation under their respective optimal policies. They achieve this by finding a latent space $\mathcal{Z} \subseteq \mathcal{S}$ in which the distance $d_{\mathcal{Z}}(z,z')$ for all $z,z' \in \mathcal{Z}$ is equivalent to distance between true latent states $d_{\mathcal{S}}(s,s')$ for all $s,s' \in \mathcal{S}$; the aforementionned works learn $\mathcal{Z}$ by optimizing action-based similarities between observations. In practice, latent space z is decoded from observation o using a latent state decoder $f : \mathcal{O} \to \mathcal{Z}$ from observation o_t. Throughout the paper, we assume that all value functions have a linear form in the latent decoded state, i.e. $Q_\theta(o,a) = \theta_a^\top f_\psi(o) = \theta_a^\top z_\psi$, which agrees with our practical implementation of all algorithms. Within this model family, the ability of an RL agent to correctly decode latent states from unseen observations directly affects its policy, and therefore, its generalization capabilities. In the next section, we discuss why representation learning is important for offline RL, and how existing action-based similarity metrics fail to recover the true latent states for important families of POMDPs.

4 Motivating example

	Level 1					Level 2				
Actions	8	0	11	11	7	13	8	0	8	13
Values	8.20	8.05	8.74	9.06	9.29	8.26	8.30	8.35	8.40	8.55
Value ranks	2	1	3	4	5	1	2	3	4	5

Figure 1: **(a)** Two levels of the Climber game from the Procgen benchmark [Cobbe et al., 2020] with *near-identical* true latent states and *near-identical* value functions but *drastically different* action sequences. **(b)** Four levels of the jumping task [Tachet et al., 2018] where the constant reward signal makes policy similarity more informative than state value similarity.

Multiple recently proposed self-supervised objectives [Liu et al., 2020a, Agarwal et al., 2021a] conjecture that observations $o_1 \in M_1, o_2 \in M_2$ that emit similar future action sequences under optimal policies π_1^*, π_2^* should be decoded into nearby latent states z_1, z_2. While this heuristic can correctly group observations with respect to their true latent state in simple action spaces, it fails to identify similar pairs of trajectories in POMDPs with multiple optimal policies[2]. For instance, two trajectories might visit an identical set of latent states, but have drastically different actions.

Fig. 1a shows one such example: two levels of the Climber game have a near-identical true latent state (see Appendix) and value function (average normalized mean-squared error of 0.0398 across episode), while having very different action sequences from a same PPO policy (average total variation distance of 0.4423 across episode). The problem is especially acute in Procgen, since the PPO policy is high-entropy for some environments (see Fig. 5), i.e. various levels can have multiple drastically different near-optimal policies, and hence fail to properly capture observation similarities.

---

[2]While optimal policies are not guaranteed to be unique, the optimal value function is unique.

In this scenario, assigning observations to a similar latent state by value function similarity would yield a better state representation than reasoning about action similarities. On the other hand, Fig. 1b shows a domain where grouping state representations by action sequences can be optimal. So how do we unify these similarity metrics under a single framework? In the next section, we use this insight to design a general way of improve representation learning through self-supervised learning of discounted future behavior.

5 Method

We propose measuring a generalized notion of future behavior similarity using generalized value functions, as defined by the corresponding cumulant function. The choice of cumulant determines which components of the future trajectory are most relevant for generalization.

Figure 2: Schematic view of GSF : the offline dataset $\mathcal{D}^\mu$ is used to estimate POMDP-specific GVFs wrt some cumulant function c, whose quantiles are then used to label each observation in the dataset.

5.1 Quantifying future behavior with GVFs

An RL agent's future discounted behavior can be quantified not only by its the value function, but other auxiliary signals, for example, by its future observation occupancy measure, known as successor representation [Dayan, 1993, Barreto et al., 2016]. The choice of the signal used during value iteration measures the properties the agent will exhibit in the future, such as accumulated returns, actions, or observation visitation density. See Thm. 1 in the Appendix for the connection between successor features and interpolation error in our method.

Following the work of Sutton et al. [2011], we can broaden the class of value functions to any kind of cumulative discounted signal, as defined by a bounded cumulant function $c : \mathcal{O} \times \mathcal{A} \to \mathbb{R}^d$, s.t. $|c(o,a)| \leq c_{\max}$ for $c_{\max} = \sup_{o,a \in \mathcal{O} \times \mathcal{A}} c(o,a)$. While typically cumulants are scalar-valued functions (e.g. reward), we also make use of the vector-valued case for learning the successor features [Barreto et al., 2016], in which case the norm of $c(o,a)$ is bounded.

Definition 1 (Generalized value function) *Let c be any bounded function over $\mathbb{R}^d$, let $\gamma \in [0,1]$ and μ any policy. The generalized value function is defined, for any timestep $t \geq 1$ and $o_t \in \mathcal{O}$, as*

$$G^\mu(o_t) = \mathbb{E}_{\mathbb{P}_t^\mu}\left[\sum_{k=1}^{\infty} \gamma^k c(o_{t+k}, a_{t+k})|o_t\right]. \tag{2}$$

Since, in our case, we can learn G^μ for each distinct POMDP M_i for the dataset $\mathcal{D}^\mu$, we index the GVF using the POMDP index, i.e. $G_i^\mu = \texttt{LearnGVF}(c, \mathcal{D}^\mu, i)$ (in practice, learning is parallelized).

5.2 Measuring distances between GVFs of different POMDPs

Examining the difference between future behaviors of two observations quantifies the exact amount of expected behavior change between these two observations. Using the GVF framework, we could compute the distance between $o_1 \in M_1$ and $o_2 \in M_2$ by first estimating the latent state with $z = f(o)$ using a latent state decoder f, and then using the following distance as a measure of dissimilarity

$$d_\mu(o_1{}^i, o_2{}^j) = ||G_i^\mu(f(o_1)) - G_j^\mu(f(o_2))||, i,j = 1,... \tag{3}$$

Algorithm 1: LearnGVF($c, \mathcal{D}^\mu, i, \theta^{(0)}, J, \alpha, \gamma$): Offline estimation of GVF $\hat{G}_i^\mu$

Input : Cumulant function c, dataset $\mathcal{D}^\mu$, POMDP label i, initial parameters $\theta^{(0)}$, target parameters $\tilde{\theta}$, latent state decoder f, iterations J, learning rate α, discount γ

1 **for** $j = 1, \ldots, J$ **do**
2     $o, a, o' \sim \mathcal{D}[i]$; // Sample transition from subset corresponding to POMDP i
3     $c \leftarrow c(o, a)$;
4     $o \leftarrow$ random crop(o);
5     $z, z' \leftarrow f(o), f(o')$;
6     $\theta^{(j)} \leftarrow \theta^{(j-1)} - \alpha \nabla_{\theta^{(j-1)}} (G_{\theta^{(j-1)}}(z) - c - \gamma G_{\tilde{\theta}^{(j-1)}}(z'))^2$;
7   Update target parameters $\tilde{\theta}$ with β of online parameters θ;

However, the distance between GVFs from two different POMDPs can have drastically different scales, i.e. $\sup_{o_1, o_2} |G_1^\mu(o_1) - G_2^\mu(o_2)| \leq \frac{c_{1,\max}^\mu + c_{2,\max}^\mu}{1 - \gamma}$, thus making point-wise comparison meaningless. The issue is less acute for cumulants which are homogenous between different POMDPs (e.g. indicator functions for successor representation), and more problematic when the cumulant incorporates a more heterogeneous signal, such as the extrinsic reward function. To avoid this problem, we suggest performing a comparison based on order statistics.

Namely, a robust distance estimate between GVF signals across POMDPs can be obtained by looking at the cumulative distribution function of G_i denoted $F_i(g) = \mathbb{P}[G_i(o_t) \leq g]$ for all $o_t \in \mathcal{O}$. G_i is a deterministic GVF with the set of discontinuity points of measure 0, and as such F_i can be understood through the induced state distribution $\mathbb{P}_t^\mu$ (using continuous mapping theorem from Mann and Wald [1943]). It can be estimated from n independent and identically distributed samples of $\mathcal{D}^\mu$ as

$$\hat{F}_i(g) = \frac{1}{n} \sum_{i=1}^n \mathbb{1}_{G_i < g}, G_i = \texttt{LearnGVF}(c, \mathcal{D}^\mu, i), g \in \left[-\frac{c_{i,\max}}{1-\gamma}, \frac{c_{i,\max}}{1-\gamma} \right] \tag{4}$$

and its inverse, the empirical quantile function [van der Vaart, 1998]

$$\hat{F}_i^{-1}(p) = \inf\left\{ g \in \left[-\frac{c_{i,\max}^\mu}{1-\gamma}, \frac{c_{i,\max}^\mu}{1-\gamma} \right] : p \leq F_i(g) \right\}, \tag{5}$$

for $p \in [0, 1]$. We use the empirical quantile function to partition the range of all GVFs into K quantile bins, i.e. disjoint sets with identical size where the set corresponding to quantile k is defined as $I_i(k) = \{ o \in M_i : F_i^{-1}(\frac{k}{K}) \leq G_i^\mu(o) \leq F_i^{-1}(\frac{k+1}{K}) \}$ and its aggregated version as $I(k) = \cup_{i=1}^m I_i(k)$[3]. Importantly, we augment the dataset $\mathcal{D}^\mu$ with observation-specific labels, which correspond to the index of the quantile bin into which the GVF G of an observation $o \in M_i$ falls into $l_i(o) = \max_k \mathbb{1}_{o \in I_i(k)}$.

These self-supervised labels are then used in a multiclass InfoNCE loss [Oord et al., 2018], which is a variation of metric learning with respect to the quantile distance defined above [Khosla et al., 2020, Song and Ermon, 2020] and this forms the basis of our self-supervised learning objective.

5.3 Self-supervised learning of GSFs

After augmenting the offline dataset with observation labels as described above, we use a simple self-supervised learning procedure to minimize distance in the latent representation space between observations with identical labels.

First, the observation o is encoded using a non-linear encoder $f_\psi : \mathcal{O} \to \mathcal{Z}$ with parameters ψ into a latent state representation $z = f_\psi(o)$[4]. The representation z is then passed into two separate trunks: 1) a linear matrix θ_a which recovers the state-action value function $Q_\theta(o, a) = \theta_a^\top z$, and 2) a non-linear projection network $h_\theta : \mathcal{Z} \to \mathcal{Z}$ with parameters θ_h to obtain a new embedding, used for self-supervised learning. The projection $h_\theta(z)$ is then used used in a multiclass InfoNCE loss [Oord et al., 2018, Song

---

[3] A special case of quantile binning occurs when $K = n$, in which case the auxiliary task is to predict the rank of the GVF associated to a given observation in the current minibatch.

[4] This encoder is different from the one used to evaluate the GVFs.

and Ermon, 2020] where a linear classifier $\mathbf{W} \in \mathbb{R}^{|\mathcal{Z}| \times K}$ aims to correctly predict the observation labels (i.e. quantile bins $k = 1, 2, .., K$) from $h_\theta(z)$, for temperature $\tau > 0$:

$$\ell_{\text{GSF}}(\theta, \psi, \mathbf{W}) = -\mathbb{E}_{o \sim \mathcal{D}^\mu} \left[\sum_{k=1}^K \mathbb{1}_{l(o)=k} \text{LogSoftmax}(\mathbf{W}^\top h_\theta(f_\psi(o))/\tau)_k \right]. \quad (6)$$

5.4 Full Algorithm

Given m training tasks, GSF first learns GVF estimates $G_1^\mu, .., G_2^\mu$ by applying `LearnGVF` to task-specific data from the offline dataset $\mathcal{D}^\mu$. Each data point in $\mathcal{D}^\mu$ is then labeled with the quantile into which its GVF falls. These labels are then used to jointly optimize Eq.6 and a control loss with respect to the encoder parameters. To learn the value function Q_θ, we use CQL [Kumar et al., 2020], which is trained using a linear combination of Q-learning [Watkins and Dayan, 1992, Ernst et al., 2005] and behavior-regularization:

$$\ell_{\text{CQL}}(\theta) = \mathbb{E}_{o,a,r,o' \sim \mathcal{D}^\mu}[(r + \gamma \max_{a' \in \mathcal{A}} Q_{\tilde{\theta}}(o', a') - Q_\theta(o, a))^2] + \lambda \mathbb{E}_{s \sim \mathcal{D}^\mu}[LSE(Q_\theta(o, a)) - \mathbb{E}_{a \sim \mu}[Q_\theta(o, a)]], \quad (7)$$

for $\lambda \geq 0$, $\tilde{\theta}$ target network parameters[5] and LSE being the log-sum-exp operator [6]. For domains with continuous actions, we also decode the Boltzmann policy π from Q_θ.

Fig. 2 provides a schematic view of the algorithm, while Alg. 2 in the Appendix presents the exact learning procedure for GSF as implemented on top of a CQL agent for a discrete action space.

Recovering existing self-supervised objectives The generality of our framework allows it to recover existing objectives such as CSSC and PSEs by carefully designing the cumulant function. Below, we highlight which existing algorithms can be recovered by GSF.

- **Cross-State Self-Constraint [CSSC, Liu et al., 2020a]**: In CSSC, observations o_1, o_2 are considered similar if they have identical future action sequences of length K under some fixed policy; a total of $|\mathcal{A}|^K$ distinct classes are possible. This approach can be approximated in our framework by picking $c(o_t, a_t) = \mathbb{1}_{a_t}(a), \forall a \in \mathcal{A}$. The problem reduces to a $|\mathcal{A}|^{T-t}$-way classification problem for observations of timestep t, which GSF approximates using K quantiles.
- **Policy similarity embedding [PSE, Agarwal et al., 2021a]**: PSEs balance the distance between local optimal behaviors and long-term dependencies in the transitions, notably using d_{TV}. If we consider the space of Boltzmann policies $\pi_{\text{Boltzmann}}$ with respect to a POMDP-specific value function Q, then choosing $c(o_t, a_t) = r(s_t, a_t)$ in GSF will effectively compute the distance between unnormalized policies.

The choice of K induces a bias-variance trade-off How should the number of quantiles K (read labels) be set, and what is the effect of smaller/ larger values of K on the learned representations? Thm. 1 highlights a trade-off when choosing the number of quantile bins empirically.

Theorem 1 *Let G_1, G_2 be generalized value functions with cumulants c_1, c_2 from respective POMDPs M_1, M_2, K be the number of quantile bins, n_1, n_2 the number of sample transitions from each POMDP. Suppose that $\mathbb{P}[\sup_{t=1,2,...}|c_1(o_{1,t}, \mu(o_{1,t})) - c_2(o_{2,t}, \mu(o_{2,t}))| > {(1-\gamma)\varepsilon}/{\gamma}] \leq \delta$. Then, for any $k = 1, 2, .., K$ and $\varepsilon > 0$ the following holds without loss of generality:*

$$\mathbb{P}\left[\sup_{o_1, o_2 \in I(k)} |G_1(o_1) - G_2(o_2)| > 3\varepsilon\right] \leq 2e^{-2n_1\varepsilon^2/4} + \mathbb{P}\left[\sup_{k=1,2,..,K} |\hat{F}_1^{-1}(k+1/K) - \hat{F}_1^{-1}(k/K)| > \varepsilon\right] + p(n_1, K, \varepsilon) + \delta \quad (8)$$

The proof can be found in the Appendix Sec. A.5. For POMDP M_1, the error decreases monotonically with increasing bin number K (second term) but the variance of bin labels depends on the number of sample transitions n_1 (first term). The inter-POMDP error (third term) does not affect the bin assignment. Hence, choosing a large K will amount to pairing states by rankings, but results in high

---

[5]A copy of θ updated solely using an exponential moving average (see Appendix).
[6]https://en.wikipedia.org/wiki/LogSumExp

272 variance, as orderings are estimated from data and each bin will have $n=1$. Setting K too small will
273 group together unrelated observations, inducing high bias.

274 **Limitations** As is the case with all offline RL methods, GSF is limited by the compounding
275 extrapolation error under low data coverage. We hypothesize that wise choices of K and c can mitigate
276 the extrapolation error by learning observation groups with low intra-group variance, but, since they
277 are environment-dependent, searching for an optimal (K,c) pair can be computationally expensive.

6 Experiments

279 Unlike for single task offline RL [Fu et al., 2020], most prior work on zero-shot generalization from
280 offline data either come up with an *ad hoc* solution suiting their needs, e.g. Ball et al. [2021], or assess
281 performance on benchmarks that do not evaluate generalization across observation functions [e.g., Yu
282 et al., 2020]. To accelerate progress in this field, we devised two benchmarks: offline Procgen (discrete
283 actions) and offline Distracting Suite (continuous actions) - two offline RL datasets to directly test
284 for generalization of RL agents across observation functions[7]. Moreover, for a standard comparison,
285 we provide generalization results on the classical online Procgen simulator, comparing PPO to PPO
286 with GSF and PPO with PSE, respectively.

287 **GVF training** In the offline setting, the training dataset is used to learn a set of task-specific GVFs in
288 parallel as follows. First, we project each observation o into a latent representation $z=f_{\psi'}(o)$; we then
289 pass z through a non-linear network $h_{\theta'}: \mathcal{Z} \to \mathbb{R}^{d_c \times m}$ where d_c is the dimensionality of the cumulant
290 function's output. The output of $h_{\theta'}$ is then split into m disjoint chunks, which are in turn used in their
291 respective temporal difference losses ℓ_{TD} in place of value functions. The procedure can be adapted
292 to an online setting via a similar procedure, except that all GVF estimators are trained simultaneously
293 and independently in separate simulators.

294 **Offline Procgen benchmark** We evaluate the proposed approach on an offline version of the
295 Procgen benchmark [Cobbe et al., 2020], which is widely used to evaluate zero-shot generalization
296 across complex visual perturbations. Given a random seed, Procgen supports sampling procedurally
297 generated level configurations for 16 games under various complexity modes: "easy", "hard" and
298 "exploration". More details can be found in Appendix.

299 **Offline Procgen results** We compare the zero-shot performance on the entire distribution of "easy"
300 POMDPs for GSF against that of strong RL and representation learning baselines: behavioral cloning
301 (BC) - to assess the quality of the PPO policy, CQL [Kumar et al., 2020] - the current state-of-the-art
302 on multiple offline benchmarks which balances RL and BC objectives, CURL [Srinivas et al., 2020],
303 CTRL [Mazoure et al., 2022], DeepMDP [Gelada et al., 2019] - which learns a metric closely related
304 to bisimulation across the MDP, Value Prediction Network [VPN, Oh et al., 2017] - which combines
305 model-free and model-based learning of values, observations, next observations, rewards and discounts,
306 Cross-State Self-Constraint [CSSC, Liu et al., 2020a] - which boosts similarity of observations with
307 identical action sequences, as well as Policy Similarity Embeddings [Agarwal et al., 2020], which
308 groups observation representations based on distance in optimal policy space.

309 Fig. 3 shows the performance of all methods over 5 random seeds and all 16 games on the offline
310 Procgen benchmark after 1 million gradient steps. Per-game average scores for all methods can be
311 found in Tab. 2 (Appendix). The scores are standardized per-game using the downstream task's (offline
312 RL) performance, in this case implemented by CQL. It can be seen that GSF performs better than
313 other offline RL and representation learning baselines.

314 Using different cumulant functions can lead to different label assignments and hence different
315 similarity groups. Fig. 3 examines the performance of GSF with respect to 3 cumulants: 1) $r(s_t,a_t)$,
316 rewards s.t. GSF learns the policy's Q^μ-value, 2) $\mathbb{1}_{o_t}(o)$, the successor representation[8] [Dayan, 1993,
317 Barreto et al., 2016] s.t. GSF learns the distribution induced by μ over $\mathcal{D}^\mu$ [Machado et al., 2020]
318 and 3) $\mathbb{1}_{a_t}(a)$, action counts, s.t. GSF learns discounted policy. While rewards and successor feature
319 cumulant choices leads to similar performance, using action-based distance leads to larger variance.

---

[7]They will be open-sourced.

[8]In the continuous observation space, we learn a d-dimensional successor feature vector z_ψ via TD and
compute the quantiles over $||z_\psi||_1$.

Figure 3: Returns on the offline Procgen benchmark [Cobbe et al., 2020] after 1M training steps. Boxplots are constructed over 5 random seeds and all 16 games; each method is normalized by the per-game median CQL performance. White dots represent average of distribution.

Offline Distracting Control Suite results Following the same procedure as for offline Procgen results, we first formed an offline dataset from the challenging Distracting Control Suite [Stone et al., 2021] by saving the replay buffer of Soft Actor-Critic [Haarnoja et al., 2018] trained for 1M frames on 4 environments with 2 different background perturbations. Next, we pre-trained G_1^μ, G_2^μ with action and reward-based cumulants, which were then used in conjunction with CQL to learn a single multi-task policy. Fig 4 shows the online performance of GSF evaluated on 10 background perturbations not seen during training, normalized by per-environment median CQL scores.

Figure 4: Improvement of GSF over CQL with action and reward-based similarity functions aggregated using performance metrics on 3 seeds and 4 environments of the Distracting Control Suite reported as suggested by Agarwal et al. [2021b] with 95% confidence intervals. We can see that using action counts results in higher mean, median and interquartile mean (IQM) statistics and lower optimality gap (i.e. fraction of scores falling under a certain threshold), than when using rewards, or when comparing with the performance of CQL.

The results are consistent with findings of Agarwal et al. [2021a], in that 1) learning policy-based similarity improves generalization capabilities of state representations, and 2) unlike in Procgen, policy-based similarity provides a better learning signal than value-based similarity.

Online Procgen results We additionally compare performance of GSF to that of PPO and PPO with PSEs in the classical online Procgen benchmark [Cobbe et al., 2019]. Figure 8 shows test returns for 20M frames obtained on the entire distribution of easy levels while training on 200 easy levels for PPO, PPO+PSEs [Agarwal et al., 2021a] and our PPO+GSFs. PPO+GSF outperforms or matches both PPO and PPO+PSE on most environments, showing that GSF can be efficiently combined with both offline and online algorithms. See Appendix A.6.1 for detailed results.

7 Discussion

In this work we proposed Generalized Similarity Functions, a novel framework which combines reinforcement learning with representation learning to improve zero-shot generalization performance on challenging, pixel-based control tasks. GSF relies on computing the similarity between observation pairs with respect to any instantaneous accumulated signal, which leads to improved empirical performance on two newly introduced benchmarks, offline Procgen and offline Distracting Suite. Theoretical results suggest that GSF's hyperparameter choice depends on a bias-variance trade-off.

References

A. Agarwal, M. Henaff, S. Kakade, and W. Sun. Pc-pg: Policy cover directed exploration for provable policy gradient learning. *Neural Information Processing Systems*, 2020.

R. Agarwal, M. C. Machado, P. S. Castro, and M. G. Bellemare. Contrastive behavioral similarity embeddings for generalization in reinforcement learning. *arXiv preprint arXiv:2101.05265*, 2021a.

R. Agarwal, M. Schwarzer, P. S. Castro, A. C. Courville, and M. Bellemare. Deep reinforcement learning at the edge of the statistical precipice. *Advances in Neural Information Processing Systems*, 34, 2021b.

P. J. Ball, C. Lu, J. Parker-Holder, and S. Roberts. Augmented world models facilitate zero-shot dynamics generalization from a single offline environment. *International Conference on Machine Learning*, 2021.

A. Barreto, W. Dabney, R. Munos, J. J. Hunt, T. Schaul, H. Van Hasselt, and D. Silver. Successor features for transfer in reinforcement learning. *arXiv preprint arXiv:1606.05312*, 2016.

P. L. Bartlett. The sample complexity of pattern classification with neural networks: the size of the weights is more important than the size of the network. *IEEE transactions on Information Theory*, 44(2):525–536, 1998.

M. G. Bellemare, S. Candido, P. S. Castro, J. Gong, M. C. Machado, S. Moitra, S. S. Ponda, and Z. Wang. Autonomous navigation of stratospheric balloons using reinforcement learning. *Nature*, 588(7836):77–82, 2020.

J. Boyan and A. W. Moore. Generalization in reinforcement learning: Safely approximating the value function. *Advances in neural information processing systems*, pages 369–376, 1995.

M. Caron, I. Misra, J. Mairal, P. Goyal, P. Bojanowski, and A. Joulin. Unsupervised learning of visual features by contrasting cluster assignments. *arXiv preprint arXiv:2006.09882*, 2020.

P. S. Castro. Scalable methods for computing state similarity in deterministic markov decision processes. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 10069–10076, 2020.

P. S. Castro and D. Precup. Using bisimulation for policy transfer in mdps. In *Twenty-Fourth AAAI Conference on Artificial Intelligence*, 2010.

A. S. Chen, S. Nair, and C. Finn. Learning generalizable robotic reward functions from" in-the-wild" human videos. *arXiv preprint arXiv:2103.16817*, 2021.

C.-A. Cheng, A. Kolobov, and A. Swaminathan. Heuristic-guided reinforcement learning. *arXiv preprint arXiv:2106.02757*, 2021.

K. Cobbe, O. Klimov, C. Hesse, T. Kim, and J. Schulman. Quantifying generalization in reinforcement learning. In *International Conference on Machine Learning*, pages 1282–1289. PMLR, 2019.

K. Cobbe, C. Hesse, J. Hilton, and J. Schulman. Leveraging procedural generation to benchmark reinforcement learning. In *International conference on machine learning*, pages 2048–2056. PMLR, 2020.

P. Dayan. Improving generalization for temporal difference learning: The successor representation. *Neural Computation*, 5(4):613–624, 1993.

A. Dvoretzky, J. Kiefer, and J. Wolfowitz. Asymptotic minimax character of the sample distribution function and of the classical multinomial estimator. *The Annals of Mathematical Statistics*, pages 642–669, 1956.

D. Ernst, P. Geurts, and L. Wehenkel. Tree-based batch mode reinforcement learning. *Journal of Machine Learning Research*, 6:503–556, 2005.

L. Espeholt, H. Soyer, R. Munos, K. Simonyan, V. Mnih, T. Ward, Y. Doron, V. Firoiu, T. Harley, I. Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. In *International Conference on Machine Learning*, pages 1407–1416. PMLR, 2018.

N. Ferns, P. Panangaden, and D. Precup. Metrics for finite markov decision processes. In *UAI*, volume 4, pages 162–169, 2004.

J. Fu, A. Kumar, O. Nachum, G. Tucker, and S. Levine. D4rl: Datasets for deep data-driven reinforcement learning, 2020.

S. Fujimoto, D. Meger, and D. Precup. Off-policy deep reinforcement learning without exploration. In *International Conference on Machine Learning*, pages 2052–2062. PMLR, 2019.

C. Gelada, S. Kumar, J. Buckman, O. Nachum, and M. G. Bellemare. Deepmdp: Learning continuous latent space models for representation learning. In *International Conference on Machine Learning*, pages 2170–2179. PMLR, 2019.

J.-B. Grill, F. Strub, F. Altché, C. Tallec, P. H. Richemond, E. Buchatskaya, C. Doersch, B. A. Pires, Z. D. Guo, M. G. Azar, et al. Bootstrap your own latent: A new approach to self-supervised learning. *arXiv preprint arXiv:2006.07733*, 2020.

S. Guadarrama, A. Korattikara, O. Ramirez, P. Castro, E. Holly, S. Fishman, K. Wang, E. Gonina, N. Wu, E. Kokiopoulou, L. Sbaiz, J. Smith, G. Bartók, J. Berent, C. Harris, V. Vanhoucke, and E. Brevdo. TF-Agents: A library for reinforcement learning in tensorflow. https://github.com/tensorflow/agents, 2018. URL https://github.com/tensorflow/agents. [Online; accessed 4-October-2021].

C. Gulcehre, Z. Wang, A. Novikov, T. Le Paine, S. G. Colmenarejo, K. Zolna, R. Agarwal, J. Merel, D. Mankowitz, C. Paduraru, et al. Rl unplugged: Benchmarks for offline reinforcement learning. 2020.

T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pages 1861–1870. PMLR, 2018.

K. He, H. Fan, Y. Wu, S. Xie, and R. Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9729–9738, 2020.

M. Hessel, H. Soyer, L. Espeholt, W. Czarnecki, S. Schmitt, and H. van Hasselt. Multi-task deep reinforcement learning with popart. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 3796–3803, 2019.

I. Higgins, A. Pal, A. Rusu, L. Matthey, C. Burgess, A. Pritzel, M. Botvinick, C. Blundell, and A. Lerchner. Darla: Improving zero-shot transfer in reinforcement learning. In *International Conference on Machine Learning*, pages 1480–1490. PMLR, 2017.

R. D. Hjelm, A. Fedorov, S. Lavoie-Marchildon, K. Grewal, P. Bachman, A. Trischler, and Y. Bengio. Learning deep representations by mutual information estimation and maximization. *arXiv preprint arXiv:1808.06670*, 2018.

R. D. Hjelm, B. Mazoure, F. Golemo, F. Frujeri, M. Jalobeanu, and A. Kolobov. The sandbox environment for generalizable agent research (segar). *arXiv preprint arXiv:2203.10351*, 2022.

N. K. Jong and P. Stone. State abstraction discovery from irrelevant state variables. In *IJCAI*, volume 8, pages 752–757. Citeseer, 2005.

P. Khosla, P. Teterwak, C. Wang, A. Sarna, Y. Tian, P. Isola, A. Maschinot, C. Liu, and D. Krishnan. Supervised contrastive learning. *Neural Information Processing Systems*, 2020.

R. Kidambi, A. Rajeswaran, P. Netrapalli, and T. Joachims. Morel: Model-based offline reinforcement learning. *arXiv preprint arXiv:2005.05951*, 2020.

I. Kostrikov, J. Tompson, R. Fergus, and O. Nachum. Offline reinforcement learning with fisher divergence critic regularization. *arXiv preprint arXiv:2103.08050*, 2021a.

I. Kostrikov, D. Yarats, and R. Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. *International Conference on Learning Representations*, 2021b.

A. Kumar, A. Zhou, G. Tucker, and S. Levine. Conservative q-learning for offline reinforcement learning. *arXiv preprint arXiv:2006.04779*, 2020.

S. Lange, T. Gabel, and M. Riedmiller. Batch reinforcement learning. In *Reinforcement learning*, pages 45–73. Springer, 2012.

L. Li, T. J. Walsh, and M. L. Littman. Towards a unified theory of state abstraction for mdps. *ISAIM*, 4:5, 2006.

Z. Lin, D. Yang, L. Zhao, T. Qin, G. Yang, and T.-Y. Liu. Rd²: Reward decomposition with representation decomposition. *Advances in Neural Information Processing Systems*, 33, 2020.

G. T. Liu, P.-J. Cheng, and G. Lin. Cross-state self-constraint for feature generalization in deep reinforcement learning. 2020a.

L. Liu, W. Hamilton, G. Long, J. Jiang, and H. Larochelle. A universal representation transformer layer for few-shot image classification. *arXiv preprint arXiv:2006.11702*, 2020b.

Y. Liu, A. Swaminathan, A. Agarwal, and E. Brunskill. Provably good batch reinforcement learning without great exploration. *NeurIPS*, 2020c.

M. C. Machado, M. G. Bellemare, and M. Bowling. Count-based exploration with the successor representation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 5125–5133, 2020.

H. B. Mann and A. Wald. On stochastic limit and order relationships. *The Annals of Mathematical Statistics*, 14(3):217–226, 1943.

B. Mazoure, R. T. d. Combes, T. Doan, P. Bachman, and R. D. Hjelm. Deep reinforcement and infomax learning. *Neural Information Processing Systems*, 2020.

B. Mazoure, A. M. Ahmed, P. MacAlpine, R. D. Hjelm, and A. Kolobov. Cross-trajectory representation learning for zero-shot generalization in rl. *International Conference on Learning Representations*, 2022.

D. Misra, M. Henaff, A. Krishnamurthy, and J. Langford. Kinematic state abstraction and provably efficient rich-observation reinforcement learning. In *International conference on machine learning*, pages 6961–6971. PMLR, 2020.

V. Mnih, K. Kavukcuoglu, D. Silver, A. A. Rusu, J. Veness, M. G. Bellemare, A. Graves, M. Riedmiller, A. K. Fidjeland, G. Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

K. P. Murphy. A survey of pomdp solution techniques. *environment*, 2:X3, 2000.

O. Nachum and M. Yang. Provable representation learning for imitation with contrastive fourier features. *Neural Information Processing Systems*, 2021.

J. Oh, S. Singh, and H. Lee. Value prediction network. *arXiv preprint arXiv:1707.03497*, 2017.

A. v. d. Oord, Y. Li, and O. Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

R. Raileanu and R. Fergus. Decoupling value and policy for generalization in reinforcement learning. *International Conference on Machine Learning*, 2021.

J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

M. Schwarzer, A. Anand, R. Goel, R. D. Hjelm, A. Courville, and P. Bachman. Data-efficient reinforcement learning with self-predictive representations. *International Conference on Learning Representations*, 2020.

M. Schwarzer, N. Rajkumar, M. Noukhovitch, A. Anand, L. Charlin, D. Hjelm, P. Bachman, and A. Courville. Pretraining representations for data-efficient reinforcement learning. *arXiv preprint arXiv:2106.04799*, 2021.

S. Sinha and A. Garg. S4rl: Surprisingly simple self-supervision for offline reinforcement learning. *arXiv preprint arXiv:2103.06326*, 2021.

J. Song and S. Ermon. Multi-label contrastive predictive coding. *Neural Information Processing Systems*, 2020.

X. Song, Y. Jiang, S. Tu, Y. Du, and B. Neyshabur. Observational overfitting in reinforcement learning. *International Conference on Learning Representations*, 2019.

A. Srinivas, M. Laskin, and P. Abbeel. Curl: Contrastive unsupervised representations for reinforcement learning. *International Conference on Machine Learning*, 2020.

A. Stone, O. Ramirez, K. Konolige, and R. Jonschkowski. The distracting control suite–a challenging benchmark for reinforcement learning from pixels. *arXiv preprint arXiv:2101.02722*, 2021.

A. Stooke, K. Lee, P. Abbeel, and M. Laskin. Decoupling representation learning from reinforcement learning. In *International Conference on Machine Learning*, pages 9870–9879. PMLR, 2021.

R. S. Sutton, J. Modayil, M. Delp, T. Degris, P. M. Pilarski, A. White, and D. Precup. Horde: A scalable real-time architecture for learning knowledge from unsupervised sensorimotor interaction. In *The 10th International Conference on Autonomous Agents and Multiagent Systems-Volume 2*, pages 761–768, 2011.

A. Swaminathan and T. Joachims. Batch learning from logged bandit feedback through counterfactual risk minimization. *The Journal of Machine Learning Research*, 16(1):1731–1755, 2015.

R. Tachet, P. Bachman, and H. van Seijen. Learning invariances for policy generalization. *arXiv preprint arXiv:1809.02591*, 2018.

A. Touati and Y. Ollivier. Learning one representation to optimize all rewards. *arXiv preprint arXiv:2103.07945*, 2021.

E. Triantafillou, T. Zhu, V. Dumoulin, P. Lamblin, U. Evci, K. Xu, R. Goroshin, C. Gelada, K. Swersky, P.-A. Manzagol, et al. Meta-dataset: A dataset of datasets for learning to learn from few examples. *International Conference on Learning Representations*, 2019.

G. Valle-Pérez and A. A. Louis. Generalization bounds for deep learning. *arXiv preprint arXiv:2012.04115*, 2020.

A. W. van der Vaart. Asymptotic statistics. cambridge series in statistical and probabilistic mathematics, 1998.

R. Wang, Y. Wu, R. Salakhutdinov, and S. M. Kakade. Instabilities of offline rl with pre-trained neural representation. *arXiv preprint arXiv:2103.04947*, 2021a.

Y. Wang, R. Wang, and S. M. Kakade. An exponential lower bound for linearly-realizable mdps with constant suboptimality gap. *arXiv preprint arXiv:2103.12690*, 2021b.

C. J. Watkins and P. Dayan. Q-learning. *Machine learning*, 8(3-4):279–292, 1992.

Y. Wu, G. Tucker, and O. Nachum. Behavior regularized offline reinforcement learning. *arXiv preprint arXiv:1911.11361*, 2019.

D. Yarats, A. Zhang, I. Kostrikov, B. Amos, J. Pineau, and R. Fergus. Improving sample efficiency in model-free reinforcement learning from images. *arXiv preprint arXiv:1910.01741*, 2019.

T. Yu, D. Quillen, Z. He, R. Julian, K. Hausman, C. Finn, and S. Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Conference on Robot Learning*, pages 1094–1100. PMLR, 2020.

A. Zhang, R. McAllister, R. Calandra, Y. Gal, and S. Levine. Learning invariant representations for reinforcement learning without reconstruction. *International Conference on Learning Representations*, 2020.