Near-optimal Distributional Reinforcement Learning towards Risk-sensitive Control

Abstract

We consider finite episodic Markov decision processes aiming at the entropic risk measure (ERM) of return for risk-sensitive control. We identify two properties of the ERM that enable risk-sensitive distributional dynamic programming. We propose two novel distributional reinforcement learning (DRL) algorithms, including a model-free one and a model-based one, that implement optimism through two different schemes. We prove that both of them attain $\tilde{\mathcal{O}}\left(\frac{\exp(|\beta|H)-1}{|\beta|H}H\sqrt{HS^2AT}\right)$ regret upper bound, where S is the number of states, A the number of states, H the time horizon and T the number of total time steps. It matches RSVI2 proposed in [22] with much a simpler regret analysis. To the best of our knowledge, this is the first regret analysis of DRL, which theoretically verifies the efficacy of DRL for risk-sensitive control. Finally, we improve the existing lower bound by proving a tighter bound of $\Omega\left(\frac{\exp(\beta H/6)-1}{\beta H}H\sqrt{SAT}\right)$ for $\beta > 0$ case, which recovers the tight lower bound $\Omega(H\sqrt{SAT})$ in the risk-neutral setting.

1 Introduction

Standard reinforcement learning (RL) [41] seeks to find an optimal policy that maximizes the expectation of return. It is also called risk-neutral RL since the objective is the mean functional of the return distribution. However, in some high-stakes applications including finance [14, 5], medical treatment [21] and operations [15] etc, the decision-maker tends to be risk-sensitive with the goal of maximizing some risk measure of return distribution.

Under risk-neutral setting, DRL [3] has demonstrated its superior performance over traditional methods in some difficult tasks [13, 12]. Different from value-based approaches, it directly learns the whole return distribution instead of value function. Thus, it is natural to apply distributional RL to risk-sensitive control in view of the intrinsic connection between return distribution and risk functionals/measures [12, 40, 30].

Unfortunately, existing works on risk-sensitive control via DRL approaches ([12, 31, 1]) lack regret analysis, which makes it challenging to evaluate and improve the algorithms for the sake of sample-efficiency. In this paper, we try to answer the following question:

Can distributional reinforcement learning attain near-optimal regret for risk-sensitive control?

We answer this question with a positive answer by providing DRL algorithms with the comparable regret upper bounds in contrast to the regret lower bound. We devise two novel DRL algorithms with principled exploration schemes for risk-sensitive control in the tabular MDP setting. In particular, the proposed algorithms implement the principle of optimism in the face of uncertainty (OFU) at the distributional level to balance the exploration-exploitation trade-off. We also provide the first

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

regret analysis of distributional reinforcement learning, which theoretically verifies the efficacy of DRL for risk-sensitive control.

Main contributions. We summarize our main contributions in the following.

1. We build a distributional dynamic programming (DDP) framework under the risk-sensitive setting. To be more specific, we choose the entropic risk measure (ERM) of the return distribution as our objective. We identify two key properties of ERM, including additivity and monotonicity-preserving. It enables us to establish distributional Bellman optimality equation for risk-sensitive control, which is non-trivial as the equation does not hold for general risk measure. Furthermore, the DDP framework is essential to the design of distributional reinforcement learning algorithms.

2. We propose two DRL algorithms that enforce the OFU principle through two different schemes. In particular, we construct the optimistic return distribution by combining the distributional optimism operator with approximate distributional Bellman update. We prove that either of them attains $\tilde{\mathcal{O}}(\frac{\exp(|\beta|H)-1}{|\beta|}H\sqrt{S^2AK})$ regret upper bound, which matches the best existing result of RSVI2 in [22]. It is the first regret analysis of DRL algorithm in the finite episodic MDP in the risk-sensitive setting. It recovers $\tilde{\mathcal{O}}(H\sqrt{HS^2AT})$ regret in the risk-neutral setting. Compared to the work of [22], the algorithm does not involve complicated bonus design, and the analysis are conceptually cleaner and more interpretable.

3. We fill the gaps in the proof of lower bound in [23]. To the best of our knowledge, [23] only implies a lower bound $\Omega(\frac{\exp(|\beta|H/2)-1}{|\beta|}\sqrt{K})$ rather the claimed bound $\Omega(\frac{\exp(|\beta|H/2)-1}{|\beta|}\sqrt{T})$. The resulting lower bound has several limitations: it is independent of S and A since the proof relies on the reduction to the lower bound for two-armed bandits, and it has a polynomial dependency on H that is loose with a $\sqrt{H}$ factor. We overcome these issues by proving a tight lower bound of $\Omega(\frac{\exp(\beta H/6)-1}{\beta H}H\sqrt{SAT})$. Note that the lower bound is also tight in the risk-neutral setting ($\beta \to 0$).

Related work. A rich body of work studies risk-sensitive RL with the ERM [6, 7, 9, 8, 2, 10, 11, 17, 16, 18, 24, 26, 28, 30, 32, 33, 34, 35, 38, 39]. In particular, [27] is the first to introduce the ERM as risk-sensitive objective in MDP. However, they either assume known transition and reward or consider infinite-horizon setting without sample-complexity considerations.

Two works are closely related to ours [23, 22] under precisely the same setting. [23] is the first to study the risk-sensitive episodic MDP, which provides the first algorithms and regret guarantees. Nevertheless, the regret upper bounds contain a dispensable factor of $\exp(|\beta|H^2)$. Additionally, their lower bound proof contains mistakes, and the corrected proof suggests a weaker bound. [22] improves the algorithm by removing the additional $\mathcal{O}(\exp(|\beta|H^2))$ factor. However, the regret analysis is complicated, and the lower bound is not fixed.

A very recent work ([1]) independently proposes a risk-sensitive DDP framework, but their work is fundamentally different from ours. On the one hand, the risk measure considered in [1] is CVaR rather than ERM. On the other hand, they focus on the infinite horizon setting.

2 Preliminaries

Notations. We write $[M : N] \triangleq \{M, M+1, ..., N\}$ and $[N] \triangleq [1 : N]$ for any positive integers $M \leq N$. We adopt the convention that $\sum_{i=n}^{m} a_i \triangleq 0$ if $n > m$ and $\prod_{i=n}^{m} a_i \triangleq 1$ if $n > m$. We use $\mathbb{I}\{\cdot\}$ to denote the indicator function. For any $x \in \mathbb{R}$, we define $[x]^+ \triangleq \max\{x, 0\}$. We define the step function with parameter c as $\psi_c(x) \triangleq \mathbb{I}\{x \geq c\}$. Note that ψ_c represents the CDF of a deterministic variable taking value c. We denote by $\mathscr{D}([a,b])$, $\mathscr{D}_M$ and $\mathscr{D}$ the set of distributions supported on $[a,b]$, $[0,M]$ and the set of all distributions respectively. For a random variable (r.v.) X, we use $\mathbb{E}[X]$ to denote its expectation. For two r.v.s, we denote by $X \perp Y$ if X is independent of Y. We use $\tilde{\mathcal{O}}(\cdot)$ to denote $\mathcal{O}(\cdot)$ omitting logarithmic factors.

Episodic MDP. An episodic MDP is identified by $\mathcal{M} \triangleq (\mathcal{S}, \mathcal{A}, (P_h)_{h \in [H]}, (\mathcal{R}_h)_{h \in [H]}, H)$, where $\mathcal{S}$ is the state space, $\mathcal{A}$ the action space, $P_h : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to [0,1]$ the probability transition kernel at step h, $\mathcal{R}_h : \mathcal{S} \times \mathcal{A} \to \mathscr{D}([0,1])$ the collection of reward distributions at step h and H the length of one episode. The agent interacts with the environment for K episodes. At the beginning of episode k, Nature selects an initial state s_1^k arbitrarily. In step h, the agent takes action a_h^k and observes

84 random reward $R_h^k(s_h^k, a_h^k) \sim \mathcal{R}_h(s_h^k, a_h^k)$ and reaches the next state $s_{h+1}^k \sim P_h(\cdot|s_h^k, a_h^k)$. The
85 episode terminates at $H + 1$ with $R_{H+1}^k = 0$, then the agent proceeds to next episode.

86 For each $(k, h) \in [K] \times [H]$, we denote by $\mathcal{H}_h^k \triangleq (s_1^1, a_1^1, s_2^1, a_2^1, \ldots, s_H^1, a_H^1, \ldots, s_h^k, a_h^k)$ the
87 (random) history up to step h episode k. We define $\mathcal{F}^k \triangleq \mathcal{H}_H^{k-1}$ as the history up to episode
88 $k - 1$. We describe the interaction between the algorithm and MDP in two levels. In the level of
89 episode, we define an algorithm as a sequence of function $\mathscr{A} \triangleq (\mathscr{A}_k)_{k \in [K]}$, each mapping $\mathcal{F}_k$ to a
90 policy $\mathscr{A}_k(\mathcal{F}_k) \in \Pi$. We denote by $\pi^k \triangleq \mathscr{A}_k(\mathcal{F}_k)$ the policy at episode k. In the level of step, a
91 (deterministic) policy π is defined as a sequence of functions $\pi = (\pi_h)_{h \in [H]}$ with $\pi_h : \mathcal{S} \to \Delta(\mathcal{A})$.

92 **Entropic risk measure.** ERM is a well-known risk measure in risk-sensitive decision-making,
93 including mathematical finance [25], Markovian decision processes [2]. The ERM value of a r.v.
94 $X \sim F$ with coefficient $\beta \neq 0$ is defined as

$$U_\beta(X) \triangleq \frac{1}{\beta} \log(\mathbb{E}_{X \sim F}[\exp(\beta X)]) = \frac{1}{\beta} \log\left(\int_{\mathbb{R}} \exp(\beta x) dF(x)\right).$$

95 With slight abuse of notations, we write $U_\beta(F) = U_\beta(X)$ for $X \sim F$. For β with small absolute
96 value, using Taylor's expansion we have

$$U_\beta(X) = \mathbb{E}[X] + \frac{\beta}{2} \mathbb{E}[X^2] + \mathcal{O}(\beta^2).$$

97 Hence for a decision-maker who aims at maximizing the ERM value, she tends to be risk-seeking
98 (favoring high uncertainty in X) if $\beta > 0$ and risk-averse (favoring low uncertainty in X) if $\beta < 0$.
99 $|\beta|$ controls the risk-sensitivity. It exactly recovers mean as the risk-neutral objective when $\beta \to 0$.

3   Risk-sensitive Distributional Dynamic Programming

101 [3], [36] has discussed the *infinite-horizon* distributional dynamic programming in the *risk-neutral*
102 setting, which will be referred to as the classical DDP. There is a big gap between the risk-sensitive
103 MDP and the risk-neutral one. In this section, we establish the novel DDP framework for risk-
104 sensitive control.

105 We start with defining the return for a policy π starting from state-action pair (s, a) at step h

$$Z_h^\pi(s, a) \triangleq \sum_{h'=h}^{H} R_{h'}(s_{h'}, a_{h'}), \; s_h = s, a_{h'} = \pi_{h'}(s_{h'}), s_{h'+1} \sim P_{h'}(\cdot|s_{h'}, a_{h'}).$$

106 Define $Y_h^\pi(s) \triangleq Z_h^\pi(s, \pi_h(s))$. There are three sources of randomness in $Z_h^\pi(s, a)$: the reward
107 $R_h(s, a)$, the transition P^π and the next-state return $Y_{h+1}^\pi(s_{h+1})$. Denote by $\nu_h^\pi(s)$ and $\eta_h^\pi(s, a)$ the
108 cumulative distribution function (CDF) corresponding to $Z_h^\pi(s)$ and $Z_h^\pi(s, a)$ respectively. To the
109 end of risk-sensitive control, we define the action-value function of a policy π at step h as $Q_h^\pi(s, a) \triangleq$
110 $U_\beta(Z_h^\pi(s, a))$, i.e. the ERM value of the return distribution, for each $(s, a, h) \in \mathcal{S} \times \mathcal{A} \times [H]$. The
111 value function is defined as $V_h^\pi(s) \triangleq Q_h^\pi(s, \pi_h(s)) = U_\beta(Y_h^\pi(s))$.

112 We focus on the control setting, in which the goal is to find an optimal policy to maximize the value
113 function, i.e.

$$\pi^* \triangleq \arg \max_{(\pi_1, \ldots, \pi_H) \in \Pi} V_1^{\pi_1 \cdots \pi_H}(s).$$

114 We write $\pi = (\pi_1, \ldots, \pi_H)$ to emphasize that it is a multi-stage maximization problem. Direct search
115 suffers exponential computational complexity. In the risk-neutral case, the *principle of optimality*
116 holds, i.e.,the optimal policy of tail sub-problem is the tail optimal policy [4]. Therein the multi-stage
117 maximization problem can be reduced to a multiple single-stage maximization problem. However,
118 the principle does not always hold for general risk measures. For example, the optimal policy for
119 conditional value at risk may be non-Markovian/history-dependent ([37]).

120 We identify two key properties of ERM, upon which we retain the principle of optimality.

121 **Lemma 1.** *The ERM satisfies the following properties:*

122   • *Additive:* $X \perp Y \Rightarrow U_\beta(X + Y) = U_\beta(X) + U_\beta(Y)$, $\forall X, Y$.

123   • *Monotonicity-preserving:* $\forall F_1, F_2, G \in \mathscr{D}$, $\forall \theta \in [0, 1]$,

$$U_\beta(F_2) \leq U_\beta(F_1) \Rightarrow U_\beta((1 - \theta)F_2 + \theta G) \leq U_\beta((1 - \theta)F_1 + \theta G).$$

124 The proof is given in Appendix A. In particular, the additivity entails that the ERM value of the
125 current return $Z_h^\pi(s, a)$ equals the sum of the immediate value of $R_h(s, a)$ and the value of the
126 future return $Y_h^\pi(s')$, i.e.,

$$U_\beta(Z_h^\pi(s, a)) = U_\beta(R_h(s, a)) + U_\beta(Y_h^\pi(s')).$$

127 The monotonicity-preserving property together with the additivity suggests that the optimal future
128 return $Y_h^*(s')$ consists in the optimal current return $Z_h^*(s, a)$

$$Z_h^*(s, a) = R_h(s, a) + Y_h^*(s').$$

129 These observations implies the principle of optimality.

130 **Proposition 1** (Principle of optimality)**.** *Let $\pi^* = \{\pi_1^*, \pi_2^*, ..., \pi_H^*\}$ be an optimal policy and assume*
131 *when we visit some state s using policy π at time-step h with positive probability. Consider the sub-*
132 *problem defined by the the following maximization problem*

$$\max_{\pi \in \Pi} V_h^\pi(s) = U_\beta(\mathcal{R}_h(s, a)) + U_\beta([P_h \nu_{h+1}^\pi](s, a)).$$

133 *Then the truncated optimal policy $\{\pi_h^*, \pi_{h+1}^*, ..., \pi_H^*\}$ is optimal for this sub-problem.*

134 The proof is given in Appendix D. It further induces the distributional Bellman optimality equation.

135 **Proposition 2** (Distributional Bellman optimality equation)**.** *For arbitrary initial state s_1, the opti-*
136 *mal policy $(\pi_h^*)_{h \in [H]}$ is given by the following backward recursions:*

$$\begin{aligned}
&\nu_{H+1}^*(s) = \psi_0, \ \eta_h^*(s, a) = [P_h \nu_{h+1}^*](s, a) * f_h(\cdot | s, a), \\
&\pi_h^*(s) = \arg\max_{a \in \mathcal{A}} Q_h^*(s, a) = U_\beta(\eta_h^*(s, a)), \nu_h^*(s) = \eta_h^*(s, \pi_h^*(s)).
\end{aligned} \quad (1)$$

137 *Furthermore, the sequence $(\eta_h^*)_{h \in [H]}$ and $(\nu_h^*)_{h \in [H]}$ are the sequence of distributions corresponding*
138 *to the optimal returns at each step.*

139 The proof is given in Appendix D. For simplicity, we define the distributional Bellman operator
140 $\mathcal{B}(P, \mathcal{R}) : \mathscr{D}^{\mathcal{S}} \to \mathscr{D}^{\mathcal{S} \times \mathcal{A}}$ with associated model $(P, \mathcal{R}) = (P(s, a), \mathcal{R}(s, a))_{(s,a) \in \mathcal{S} \times \mathcal{A}}$ as

$$[\mathcal{B}(P, \mathcal{R})\nu](s, a) \triangleq [P\nu](s, a) * f_h(\cdot | s, a), \ \forall (s, a) \in \mathcal{S} \times \mathcal{A}.$$

141 Hence we can rewrite Equation 1 in a compact form:

$$\begin{aligned}
&\nu_{H+1}^*(s) = \psi_0, \ \eta_h^*(s, a) = [\mathcal{B}(P_h, \mathcal{R}_h)\nu_{h+1}^*](s, a), \\
&\pi_h^*(s) = \arg\max_{a \in \mathcal{A}} U_\beta(\eta_h^*(s, a)), \ \nu_h^*(s) = \eta_h^*(s, \pi_h^*(s)), \forall (s, a, h) \in \mathcal{S} \times \mathcal{A} \times [H].
\end{aligned} \quad (2)$$

142 Finally, we define the regret of an algorithm $\mathscr{A}$ interacting with an MDP $\mathcal{M}$ for K episodes as

$$\text{Regret}(\mathscr{A}, \mathcal{M}, K) \triangleq \sum_{k=1}^{K} V_1^*(s_1^k) - V_h^{\pi^k}(s_1^k).$$

143 Note that the regret is a random variable since π^k is a random quantity. We denote by
144 $\mathbb{E}[\text{Regret}(\mathscr{A}, \mathcal{M}, K)]$ the expected regret. We will omit π and $\mathcal{M}$ if it is clear from the context.

145   **4   Algorithm**

146 For a better understanding of the readers, we present our algorithms under the assumption that the
147 reward is *deterministic and known*[1]. The algorithms for the case of random reward are given in

---

[1]The algorithms for random reward enjoy the regret bounds in the same order.

148 Appendix B. We denote by $\{r_h(s,a)\}_{(s,a,h)\in\mathcal{S}\times\mathcal{A}\times[H]}$ the reward functions. For the special case of
149 deterministic reward, the Bellman update in Equation 1 takes the form

$$\eta_h^*(s,a) = [P_h\nu_{h+1}^*](s,a)(\cdot - r_h(s,a)),$$

150 since adding a deterministic reward $r_h(s,a)$ corresponds to shifting the distribution $[P_h\nu_{h+1}^*](s,a)$
151 by an amount of $r_h(s,a)$. We thus define the distributional Bellman operator $\mathcal{B}(P,\mathcal{R}) : \mathscr{D}^{\mathcal{S}} \to$
152 $\mathscr{D}^{\mathcal{S}\times\mathcal{A}}$ with associated model $(P,r) = (P(s,a), r(s,a))_{(s,a)\in\mathcal{S}\times\mathcal{A}}$ as

$$[\mathcal{B}(P,r)\nu](s,a) \triangleq [P\nu](s,a)(\cdot - r_h(s,a)), \ \forall(s,a) \in \mathcal{S}\times\mathcal{A}.$$

153 We propose two DRL algorithms in this section, including a model-free algorithm and a model-based
154 algorithm. We first introduce the **M**odel- **F**ree **R**isk-sensitive **O**ptimistic **D**istribution **I**teration
155 (RODI-MF) in Algorithm 1. For completeness, we introduce some additional notations here. For
156 two CDFs F and G over reals, we define the supremum distance between them $\|F - G\|_\infty \triangleq$
157 $\sup_x |F(x) - G(x)|$. We define the ℓ_1 distance between two probability mass functions (PMFs)
158 P and Q as $\|P - Q\|_1 \triangleq \sum_i |P_i - Q_i|$. We denote by $B_\infty(F,c) := \{G \in \mathscr{D} \| \|G - F\|_p \le c\}$
159 the supremum norm ball centered at F with radius c. With slight abuse of notations, we denote by
160 $B_1(P,c)$ the supremum norm ball centered at P with radius c.

4.1 Algorithm overview

4.1.1 RODI-MF

163 In each episode, the algorithm includes the planning phase (Line 4-12) and the interaction phase
164 (Line 13-17).

165 **Planning phase.** In a high level, the algorithm implements an optimistic version of approximate
166 DDP from step $H + 1$ to step 1 in each episode. In Line (5-7), it performs sample-based Bellman
167 update. To make it clear, we introduce the superscript k to the variables of Algorithm 1 in episode k.
168 For example, η_h^k denotes η_h in episode k. Specifically, for those visited (s,a)s, we claim that Line
169 6 is equivalent to a model-based Bellman update. Denote by $\mathbb{I}_h^k(s,a) \triangleq \mathbb{I}\{(s_h^k, a_h^k) = (s,a)\}$. Fix a
170 (s,a,k,h) such that $N_h^k(s,a) \ge 1$. We denote by $\hat{P}_h^k(\cdot|s,a)$ the empirical transition model

$$\hat{P}_h^k(s'|s,a) = \frac{1}{N_h^k(s,a)} \sum_{\tau \in [k-1]} \mathbb{I}_h^\tau(s,a) \cdot \mathbb{I}\{s_{h+1}^\tau = s'\}.$$

171 Observe that for any $\nu \in \mathscr{D}^{\mathcal{S}}$, we have

$$\left[\hat{P}_h^k\nu\right](s,a) = \sum_{s'\in\mathcal{S}} \hat{P}_h^k(s'|s,a)\nu(s') = \frac{1}{N_h^k(s,a)} \sum_{s'\in\mathcal{S}} \sum_{\tau\in[k-1]} \mathbb{I}_h^\tau(s,a) \cdot \mathbb{I}\{s_{h+1}^\tau = s'\}\nu(s')$$

$$= \frac{1}{N_h^k(s,a)} \sum_{\tau\in[k-1]} \mathbb{I}_h^\tau(s,a) \cdot \sum_{s'\in\mathcal{S}} \mathbb{I}\{s_{h+1}^\tau = s'\}\nu(s_{h+1}^\tau)$$

$$= \frac{1}{N_h^k(s,a)} \sum_{\tau\in[k-1]} \mathbb{I}_h^\tau(s,a)\nu(s_{h+1}^\tau).$$

172 Hence the update formula in Line 6 of Algorithm 1 can be rewritten as

$$\eta_h^k(s,a) = \left[\hat{P}_h^k\nu_{h+1}^k\right](s,a)(\cdot - r_h(s,a)) = \left[\mathcal{B}(\hat{P}_h^k, r_h)\nu_{h+1}^k\right](s,a),$$

173 implying the equivalence to a model-based Bellman update with empirical transition model $\hat{P}_h^k$.
174 Alternatively, the unvisited (s,a) remains to be the return distribution corresponding to the highest
175 possible reward $H + 1 - h$. The algorithm then computes the optimism constants (Line 8) and
176 enforces OFU through the distributional optimism operator c_h^k (Line 9) to obtain the optimistically
177 plausible return distribution η_h^k. The choice of c_h^k will be discussed later. The optimistic return
178 distributions yields the optimistic value function, from which the algorithm generates the greedy
179 policy π_h^k. The policy π_h^k will be used in the interaction phase.

 Interaction phase. In Line (15-16), the agent interacts with the environment using policy π and
updates the counts N_h based on new observations.

Algorithm 1 RODI-MF

1: Input: T and δ
2: Initialize $N_h(\cdot,\cdot) \leftarrow 0$; $\eta_h(\cdot,\cdot), \nu_h(\cdot) \leftarrow \psi_{H+1-h}$ for all $h \in [H]$
3: **for** $k = 1 : K$ **do**
4:      **for** $h = H : 1$ **do**
5:          **if** $N_h(\cdot,\cdot) > 0$ **then**
6:              $\eta_h(\cdot,\cdot) \leftarrow \frac{1}{N_h(\cdot,\cdot)} \sum_{\tau \in [k-1]} \mathbb{I}_h^\tau(\cdot,\cdot) \nu_{h+1}(s_{h+1}^\tau)(\cdot - r_h(\cdot,\cdot))$
7:          **end if**
8:          $c_h(\cdot,\cdot) \leftarrow \sqrt{\frac{2S}{N_h(\cdot,\cdot)\vee 1}\iota}$
9:          $\eta_h(\cdot,\cdot) \leftarrow O_{c_h(\cdot,\cdot)} \eta_h(\cdot,\cdot)$
10:         $\pi_h(\cdot) \leftarrow \arg\max_a U_\beta(\eta_h(\cdot,a))$
11:         $\nu_h(\cdot) \leftarrow \eta_h(\cdot, \pi_h(\cdot))$
12:      **end for**
13:      Receive s_1^k
14:      **for** $h = 1 : H$ **do**
15:          $a_h^k \leftarrow \pi_h(s_h^k)$ and transit to s_{h+1}^k
16:          $N_h(s_h^k, a_h^k) \leftarrow N_h(s_h^k, a_h^k) + 1$
17:      **end for**
18: **end for**

4.1.2 RODI-MB

We introduce the second algorithm **M**odel- **B**ased **R**isk-sensitive **O**ptimistic **D**istribution **I**teration (RODI-MB). Algorithm 2 is a model-based algorithm because it requires to explicitly maintaining the empirical transition model in each episode. However, it can be reduced to a *classical/non-distributional* reinforcement learning algorithm that deals with the one-dimensional values instead of the distributions. It saves the computational complexity and space complexity in another direction. Likewise, the algorithm includes the planning phase (Line 4-10) and the interaction phase (Line 11-15).

Planning phase. Analogous to Algorithm 1, the algorithm also performs approximate DDP together with the OFU principle. First, it applies the distributional optimistic operator to the empirical transition model $\hat{P}_h^k$ to get the optimistic transition model $\tilde{P}_h^k$. Then the algorithm uses $\tilde{P}_h^k$ to execute Bellman update to generate the optimistic return distributions η_h^k. The remaining steps are the same as Algorithm 1.

Interaction phase. In Line (13-14), the agent interacts with the environment using policy π^k and updates the counts N_h^{k+1} and empirical transition model $\hat{P}_h^{k+1}$ based on the new observations.

Algorithm 2 RODI-MB	**Algorithm 3** ROVI
1: Input: T and δ	1: Input: T and δ
2: $N_h^1(\cdot,\cdot) \leftarrow 0$; $\hat{P}_h^1(\cdot,\cdot) \leftarrow \frac{1}{S}\mathbf{1}$ for all $h \in [H]$	2: $N_h^1(\cdot,\cdot) \leftarrow 0$; $\hat{P}_h^1(\cdot,\cdot) \leftarrow \frac{1}{S}\mathbf{1}$ for all $h \in [H]$
3: **for** $k = 1 : K$ **do**	3: **for** $k = 1 : K$ **do**
4: $\nu_{H+1}^k(\cdot) \leftarrow \psi_0$	4: $V_{H+1}^k(\cdot) \leftarrow 1$
5: **for** $h = H : 1$ **do**	5: **for** $h = H : 1$ **do**
6: $\tilde{P}_h^k(\cdot,\cdot) \leftarrow O_{c_h^k(\cdot,\cdot)} \hat{P}_h^k(\cdot,\cdot)$	6: $\tilde{P}_h^k(\cdot,\cdot) \leftarrow O_{c_h^k(\cdot,\cdot)} \hat{P}_h^k(\cdot,\cdot)$
7: $\eta_h^k(\cdot,\cdot) \leftarrow \left[\mathcal{B}\left(\tilde{P}_h^k, r_h\right)\nu_{h+1}^k\right](\cdot,\cdot)$	7: $J_h^k(\cdot,\cdot) \leftarrow e^{\beta r_h(\cdot,\cdot)}\left[\tilde{P}_h^k W_{h+1}^k\right](\cdot,\cdot)$
8: $\pi_h^k(\cdot) \leftarrow \arg\max_a U_\beta(\eta_h^k(\cdot,a))$	8: $W_h^k(\cdot) \leftarrow \max_a J_h^k(\cdot,a)$
9: $\nu_h^k(\cdot) \leftarrow \eta_h^k(\cdot, \pi_h^k(\cdot))$	9: **end for**
10: **end for**	10: Receive s_1^k
11: Receive s_1^k	11: **for** $h = 1 : H$ **do**
12: **for** $h = 1 : H$ **do**	12: $a_h^k \leftarrow \arg\max_a J_h^k(s_h^k, a)$ and transit to s_{h+1}^k
13: $a_h^k \leftarrow \pi_h^k(s_h^k)$ and transit to s_{h+1}^k	
14: Compute $N_h^{k+1}(\cdot,\cdot)$ and $\hat{P}_h^{k+1}(\cdot,\cdot)$	13: Compute $N_h^{k+1}(\cdot,\cdot)$ and $\hat{P}_h^{k+1}(\cdot,\cdot)$
15: **end for**	14: **end for**
16: **end for**	15: **end for**

Equivalence to `ROVI`. **R**isk-sensitive **O**ptimistic **V**alue **I**teration (`ROVI`) is a classical algorithm that deals with the real-valued value function rather than the distribution. It is motivated from the *exponential Bellman equation* proposed by [22]. We define the functional exponential ERM (EERM) E_β as the ERM after the exponential transformation

$$E_\beta(F) \triangleq \exp(\beta(U_\beta(F))) = \int_{\mathbb{R}} \exp(\beta x) dF(x).$$

Define the exponential value functions $W_h(s) \triangleq E_\beta(\nu_h(s))$ and $J_h(s,a) \triangleq E_\beta(\eta_h(s,a))$ for all (s,a,h)s. Applying EERM to Equation 3 yields the exponential Bellman equation

$$
\begin{aligned}
J_h^*(s,a) &= \exp(\beta r_h(s,a))[P_h W_{h+1}^*](s,a), \\
W_h^*(s) &= \text{sign}(\beta) \max_a \text{sign}(\beta) J_h^*(s,a), \ W_{H+1}^*(s) = 1.
\end{aligned}
\tag{3}
$$

To verify the equivalence, it is sufficient to show that J_h^k in Algorithm 3 corresponds to the exponential function of η_h^k in Algorithm 2. Observe that E_β is linear in F, hence it follows that

$$
\begin{aligned}
E_\beta(\eta_h^k(s,a)) &= E_\beta\left(\left[\tilde{P}_h^k \nu_{h+1}^k\right](s,a)(\cdot - r_h(s,a))\right) = \exp(\beta r_h(s,a)) \cdot \left[\tilde{P}_h^k E_\beta(\nu_{h+1}^k)\right](s,a) \\
&= \exp(\beta r_h(s,a)) \left[\tilde{P}_h^k W_{h+1}^k\right](s,a) = J_h^k(s,a).
\end{aligned}
$$

The two algorithms generate the policy sequence in the same way, implying that their trajectories $\mathcal{H}_H^K$ follow the same distribution. The formal statement is given in Appendix D.

4.2 Distributional Optimism

It is common to add a bonus to rewards to ensure optimism in the risk-neutral setting. Specifically, the bonus is closely related to the quantification of uncertainty, which appears in concentration inequalities. Such a definition cannot be easily adapted to the distributional case. We introduce two types of distributional optimism operators, each of which is applied in Algorithm 2 or Algorithm 1.

Distributional optimism for transition model. We consider here the optimism among the space of PMFs. Using the ℓ_1 concentration inequality [42], we get a concentration bound of the empirical PMF of transition model: with probability at least $1 - \delta$,

$$\left\| \widehat{P}_h^k(s,a) - P_h(s,a) \right\|_1 \leq c_h^k(s,a) = \sqrt{\frac{2S}{N_h^k(s,a)} \log \frac{1}{\delta}} = \tilde{\mathcal{O}}\left(\sqrt{\frac{2S}{N_h^k(s,a)}}\right).$$

Notice that we wish to obtain a optimistic transition model $\tilde{P}_h^k(s,a)$ from the empirical one $\widehat{P}_h^k(s,a)$. In particular, the return distribution η_h^k computed from $\tilde{P}_h^k(s,a)$ and the next-state return distribution ν_{h+1}^k should be more optimistic than the optimal one $\eta_h^*(s,a)$ with high probability. To this aim, we define the distributional optimism operator $O_c^1 : \mathscr{D}(\mathcal{S}) \mapsto \mathscr{D}(\mathcal{S})$ with level c and future return $\nu \in \mathscr{D}^{\mathcal{S}}$ as

$$O_c^1\left(\widehat{P}(s,a), \nu\right) \triangleq \arg \max_{P \in B_1(\widehat{P}(s,a),c)} U_\beta([P\nu]).$$

The ERM satisfy an interesting property that enables an efficient approach to perform O_c^1 (see Appendix A). Now consider Algorithm 2. Using the induction, we have

$$
\begin{aligned}
U_\beta\left(\eta_h^k(s,a)\right) = r_h(s,a) + U_\beta\left(\left[\tilde{P}_h^k \nu_{h+1}^k\right][s,a]\right) &\geq r_h(s,a) + U_\beta\left(\left[P_h \nu_{h+1}^k\right][s,a]\right) \\
&\geq r_h(s,a) + U_\beta\left(\left[P_h \nu_{h+1}^*\right][s,a]\right) \\
&= U_\beta(\eta_h^*(s,a)),
\end{aligned}
$$

which verify the optimism of η_h^k over $\eta_h^*(s,a)$.

Distributional optimism for return distribution. For two CDFs F and G, we say that F is more optimistic than G (w.r.t. ERM) if $U_\beta(F) \geq U_\beta(G)$. This reflects the intuition that more optimistic

distribution should own larger ERM value. Following [29], we define the distributional optimism operator $O_c^\infty : \mathscr{D}([a,b]) \mapsto \mathscr{D}([a,b])$ with level $c \in (0,1)$ as

$$(O_c^\infty F)(x) \triangleq [F(x) - c\mathbb{I}_{[a,b)}(x)]^+.$$

The optimistic operation shifts the input distribution F down by at most c over $[a,b)$, and retain the value 1 at b. This ensures $O_c F$ remains in $\mathscr{D}([a,b])$ and dominates all other CDFs in $\mathscr{D}([a,b])$ in the sense that $(O_c^\infty F)(x) \leq G(x)$ for any $G \in B_\infty(F,c)$. Since ERM is monotonic, it holds that

$$U_\beta(O_c^\infty F) \geq U_\beta(G), \ \forall G \in B_\infty(F,c).$$

Hence $O_c^\infty F$ is the most optimistic distribution that resides in the infinity ball $B_\infty(F,c)$. In other words, for any CDF F and G satisfying $\|F - G\|_\infty \leq c$, we have $O_c^\infty G \succeq F$. Informally, for the instances of return distribution, we can apply the distributional optimism operator to the estimated return distribution η_h^k (Line 9 of Algorithm 1) with level c_h^k to ensure $U_\beta(\eta_h^k(s,a)) \geq U_\beta(\eta_h^*(s,a))$, where c_h^k quantifies the level of uncertainty in the transition model estimation, i.e., the transition model estimation error $\left\| \hat{P}_h^k(s,a) - P_h(s,a) \right\|_1$.

5 Regret Analysis

5.1 Regret upper bounds

In a high level, our analysis focus on EERM instead of ERM, which leads to regret upper bounds that matches the tightest result in [22]. We present some technical highlights in the analysis.

Lipschitz continuity and linearity. We identify two important properties of EERM that establishes the regret upper bounds, including the Lipschitz continuity and linearity. Denote by $L_M(\mathrm{T})$ the Lipschitz constant of a functional $\mathrm{T} : \mathscr{D}([0,M]) \to \mathbb{R}$ with respect to the infinity norm $\|\cdot\|_\infty$. Lemma 2 provides a *tight* Lipschitz constant of ERM. The Lipschitz constant relates the difference between distributions to the difference measured by their ERM value.

Lemma 2 (Lipschitz property of EERM). *E_β is Lipschitz continuous with respect to the supremum norm over $\mathscr{D}_M$ with $L_M(E_\beta) = \exp(|\beta|M) - 1$. Moreover, L_M is tight in terms of both $|\beta|$ and M.*

For simplicity, we use L_M to represent the Lipschitz constant of E_β. Notice that $\lim_{\beta \to 0} L_M(E_\beta) = 0$, which coincides with the fact that E_β reduces to the constant 1 as $\beta \to 0$. The linearity is a key property that sharpens the regret bounds. In contrast, analyzing the ERM would yield a regret upper bound with an additional factor of $\exp(\beta H^2)$. ERM is non-linear in the distribution, which could cause a factor of $\exp(|\beta|H)$ in the control of error back-propagation. It would further lead to a compounding factor of $\exp(|\beta|H^2)$ in the regret bound. In summary, the Lipschitz continuity property enables the regret upper bounds of DRL algorithms, and the linearity tightens the bound.

Distributional optimism. Our analysis also reflects the principle of optimism in the face of uncertainty at the distributional level. Specifically, we first define a high probability good event, under which the true return distribution concentrates around the estimated one with a certain confidence radius. Then we apply the distributional optimism operator to obtain the optimistic return distribution and the optimistic ERM value. Hence the regret can be bounded above by the surrogate regret, in which the optimal ERM value is replaced by

$$\mathrm{Regret}(K) = \sum_{k=1}^K \frac{1}{\beta} \log\left(W_1^*(s_1^k)\right) - \frac{1}{\beta} \log\left(W_1^{\pi^k}(s_1^k)\right) \leq \frac{1}{\beta} \sum_{k=1}^K W_1^k(s_1^k) - W_1^{\pi^k}(s_1^k).$$

Distributional analysis vs. non-distributional analysis. This issue arises in the analysis of Algorithm 2/Algorithm 3. Given the equivalence relation, proving the regret bound of either algorithm suffices. Since Algorithm 3 is a classical algorithm, one may consider using the standard analysis that does not involve with distributions. However, we show that this induces a factor of $\frac{1}{|\beta|} \exp(|\beta|H)$, which explodes as $|\beta| \to 0$. We overcome this issue by invoking the distributional analysis, leading to the desired factor of $\frac{1}{|\beta|}(\exp(|\beta|H) - 1)$.

Although we focus on the algorithms for the deterministic reward in the main text, the regret upper bounds presented below also hold for the algorithms for the random reward. Algorithm 4, Algorithm 5 and Algorithm 6 corresponds to Algorithm 1, Algorithm 2 and Algorithm 3 respectively (cf. Appendix B).

Theorem 1 (Regret upper bound of `RODI-MF`)**.** *For any $\delta \in (0, 1)$, with probability $1 - \delta$, the regret of Algorithm 1 under deterministic reward or Algorithm 4 under random reward is bounded as*

$$Regret(\texttt{RODI-MF}, K) \leq \mathcal{O}\left(\frac{1}{|\beta|}L_H H \sqrt{S^2 AK \log(4SAT/\delta)}\right) = \tilde{\mathcal{O}}\left(\frac{\exp(|\beta|H) - 1}{|\beta|} H \sqrt{S^2 AK}\right).$$

The proof is given in Appendix C.

Theorem 2 (Regret upper bound of `RODI-MB/ROVI`)**.** *For any $\delta \in (0, 1)$, with probability $1 - \delta$, the regret of Algorithm 1/Algorithm 3 under deterministic reward or Algorithm 4/Algorithm 6 under random reward is bounded as*

$$Regret(\texttt{RODI-MF}, K) = Regret(\texttt{ROVI}, K) \leq \mathcal{O}(\frac{1}{|\beta|}L_H H \sqrt{S^2 AK \log(4SAT/\delta)})$$
$$= \tilde{\mathcal{O}}\left(\frac{\exp(|\beta|H) - 1}{|\beta|} H \sqrt{S^2 AK}\right).$$

The proof is given in Appendix C. The above results match the best-known results in [22]. In particular, our algorithms attain exponentially improved regret bounds than those of RSVI and RSQ in [23] by removing the factor of $\exp(|\beta|H^2)$. These results also suggest that by choosing $|\beta| = \mathcal{O}(\frac{1}{H})$, our algorithms can achieve polynomial regret bounds as the risk-neutral setting.

5.2 Regret lower bound

The following proposition features a tighter lower bound for ERM for $\beta > 0$, which is motivated from the construction of hard MDP instance in [19]. However, it is not clear whether a similar lower bound holds for $\beta < 0$, so we leave it as a future direction.

Assumption 1. *Assume $S \geq 6, A \geq 2$, and there exists an integer d such that $S = 3 + \frac{A^d - 1}{A - 1}$. We further assume that $H \geq 3d$ and $\bar{H} \triangleq \frac{H}{3} \geq 1$.*

Theorem 3 (Tighter lower bound)**.** *Assume Assumption 1 holds and $\beta > 0$. Let $\bar{L} \triangleq (1 - \frac{1}{A})(S - 3) + \frac{1}{A}$. Then for any algorithm $\mathscr{A}$, there exists an MDP $\mathcal{M}_{\mathscr{A}}$ such that for $K \geq 2 \exp(\beta(H - \bar{H} - d))\bar{H}\bar{L}A$ we have*

$$\mathbb{E}[Regret(\mathscr{A}, \mathcal{M}_{\mathscr{A}}, K)] \geq \frac{1}{72\sqrt{6}} \frac{\exp(\beta H/6) - 1}{\beta H} H \sqrt{SAT}.$$

The proof is given in Appendix C. Theorem 3 recovers the tight lower bound for standard finite MDP in H, S, A and K, which implies that the exponential dependence on $|\beta|$ and H in the regret upper bounds is unavoidable.

6 Conclusion

We propose a risk-sensitive distributional dynamic programming framework. We devise two novel DRL algorithms, including a model-free one and a model-based one, which implement the OFU principle at the distributional level to balance the exploration and exploitation trade-off under the risk-sensitive setting. We prove that both attain near-optimal regret upper bounds compared with our improved lower bound.

There are several promising future directions. The current regret upper bound has an additional factor $\sqrt{HS}$ compared with the lower bound. It might be possible to remove the factor by designing new algorithms or improving the analysis. Besides, it is interesting to extend the DRL algorithm from tabular MDP to linear function approximation setting. Finally, it will be meaningful to investigate whether the DDP framework holds for other risk measures.

References

[1] Mastane Achab and Gergely Neu. Robustness and risk management via distributional dynamic programming. *arXiv preprint arXiv:2112.15430*, 2021.

[2] Nicole Bäuerle and Ulrich Rieder. More risk-sensitive markov decision processes. *Mathematics of Operations Research*, 39(1):105–120, 2014.

[3] Marc G Bellemare, Will Dabney, and Rémi Munos. A distributional perspective on reinforcement learning. In *International Conference on Machine Learning*, pages 449–458. PMLR, 2017.

[4] Dimitri P Bertsekas et al. *Dynamic programming and optimal control: Vol. 1*. Athena scientific Belmont, 2000.

[5] Tomasz R Bielecki, Stanley R Pliska, and Michael Sherris. Risk sensitive asset allocation. *Journal of Economic Dynamics and Control*, 24(8):1145–1177, 2000.

[6] Vivek S Borkar. A sensitivity formula for risk-sensitive cost and the actor–critic algorithm. *Systems & Control Letters*, 44(5):339–346, 2001.

[7] Vivek S Borkar. Q-learning for risk-sensitive control. *Mathematics of operations research*, 27(2):294–311, 2002.

[8] Vivek S Borkar. Learning algorithms for risk-sensitive control. In *Proceedings of the 19th International Symposium on Mathematical Theory of Networks and Systems–MTNS*, volume 5, 2010.

[9] Vivek S Borkar and Sean P Meyn. Risk-sensitive optimal control for markov decision processes with monotone cost. *Mathematics of Operations Research*, 27(1):192–209, 2002.

[10] Rolando Cavazos-Cadena and Daniel Hernández-Hernández. Discounted approximations for risk-sensitive average criteria in markov decision chains with finite state space. *Mathematics of Operations Research*, 36(1):133–146, 2011.

[11] Stefano P Coraluppi and Steven I Marcus. Risk-sensitive, minimax, and mixed risk-neutral/minimax control of markov decision processes. In *Stochastic analysis, control, optimization and applications*, pages 21–40. Springer, 1999.

[12] Will Dabney, Georg Ostrovski, David Silver, and Rémi Munos. Implicit quantile networks for distributional reinforcement learning. In *International conference on machine learning*, pages 1096–1105. PMLR, 2018.

[13] Will Dabney, Mark Rowland, Marc G Bellemare, and Rémi Munos. Distributional reinforcement learning with quantile regression. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

[14] Mark Davis and Sébastien Lleo. Risk-sensitive benchmarked asset management. *Quantitative Finance*, 8(4):415–426, 2008.

[15] Erick Delage and Shie Mannor. Percentile optimization for markov decision processes with parameter uncertainty. *Operations research*, 58(1):203–213, 2010.

[16] Giovanni B Di Masi et al. Infinite horizon risk sensitive control of discrete time markov processes with small risk. *Systems & control letters*, 40(1):15–20, 2000.

[17] Giovanni B Di Masi and Lukasz Stettner. Risk-sensitive control of discrete-time markov processes with infinite horizon. *SIAM Journal on Control and Optimization*, 38(1):61–78, 1999.

[18] Giovanni B Di Masi and Łukasz Stettner. Infinite horizon risk sensitive control of discrete time markov processes under minorization property. *SIAM Journal on Control and Optimization*, 46(1):231–252, 2007.

[19] Omar Darwiche Domingues, Pierre Ménard, Emilie Kaufmann, and Michal Valko. Episodic reinforcement learning in finite mdps: Minimax lower bounds revisited. In *Algorithmic Learning Theory*, pages 578–598. PMLR, 2021.

[20] Richard M Dudley. *Real analysis and probability*. CRC Press, 2018.

[21] Damien Ernst, Guy-Bart Stan, Jorge Goncalves, and Louis Wehenkel. Clinical data based optimal sti strategies for hiv: a reinforcement learning approach. In *Proceedings of the 45th IEEE Conference on Decision and Control*, pages 667–672. IEEE, 2006.

[22] Yingjie Fei, Zhuoran Yang, Yudong Chen, and Zhaoran Wang. Exponential bellman equation and improved regret bounds for risk-sensitive reinforcement learning. *Advances in Neural Information Processing Systems*, 34, 2021.

[23] Yingjie Fei, Zhuoran Yang, Yudong Chen, Zhaoran Wang, and Qiaomin Xie. Risk-sensitive reinforcement learning: Near-optimal risk-sample tradeoff in regret. *arXiv preprint arXiv:2006.13827*, 2020.

[24] Wendell H Fleming and William M McEneaney. Risk-sensitive control on an infinite time horizon. *SIAM Journal on Control and Optimization*, 33(6):1881–1915, 1995.

[25] Hans Föllmer and Alexander Schied. Stochastic finance. In *Stochastic Finance*. de Gruyter, 2016.

[26] Daniel Hernández-Hernández and Steven I Marcus. Risk sensitive control of markov processes in countable state space. *Systems & control letters*, 29(3):147–155, 1996.

[27] Ronald A Howard and James E Matheson. Risk-sensitive markov decision processes. *Management science*, 18(7):356–369, 1972.

[28] Anna Jaśkiewicz. Average optimality for risk-sensitive control with general state space. *The annals of applied probability*, 17(2):654–675, 2007.

[29] Ramtin Keramati, Christoph Dann, Alex Tamkin, and Emma Brunskill. Being optimistic to be conservative: Quickly learning a cvar policy. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 4436–4443, 2020.

[30] Xiaoteng Ma, Li Xia, Zhengyuan Zhou, Jun Yang, and Qianchuan Zhao. Dsac: Distributional soft actor critic for risk-sensitive reinforcement learning. *arXiv preprint arXiv:2004.14547*, 2020.

[31] Yecheng Ma, Dinesh Jayaraman, and Osbert Bastani. Conservative offline distributional reinforcement learning. *Advances in Neural Information Processing Systems*, 34, 2021.

[32] Steven I Marcus, Emmanual Fernández-Gaucherand, Daniel Hernández-Hernandez, Stefano Coraluppi, and Pedram Fard. Risk sensitive markov decision processes. In *Systems and control in the twenty-first century*, pages 263–279. Springer, 1997.

[33] Oliver Mihatsch and Ralph Neuneier. Risk-sensitive reinforcement learning. *Machine learning*, 49(2):267–290, 2002.

[34] Takayuki Osogami. Robustness and risk-sensitivity in markov decision processes. *Advances in Neural Information Processing Systems*, 25:233–241, 2012.

[35] Stephen D Patek. On terminating markov decision processes with a risk-averse objective function. *Automatica*, 37(9):1379–1386, 2001.

[36] Mark Rowland, Marc Bellemare, Will Dabney, Rémi Munos, and Yee Whye Teh. An analysis of categorical distributional reinforcement learning. In *International Conference on Artificial Intelligence and Statistics*, pages 29–37. PMLR, 2018.

[37] Alexander Shapiro, Darinka Dentcheva, and Andrzej Ruszczynski. *Lectures on stochastic programming: modeling and theory*. SIAM, 2021.

[38] Yun Shen, Wilhelm Stannat, and Klaus Obermayer. Risk-sensitive markov control processes. *SIAM Journal on Control and Optimization*, 51(5):3652–3672, 2013.

[39] Yun Shen, Michael J Tobia, Tobias Sommer, and Klaus Obermayer. Risk-sensitive reinforcement learning. *Neural computation*, 26(7):1298–1328, 2014.

[40] Rahul Singh, Qinsheng Zhang, and Yongxin Chen. Improving robustness via risk averse distributional reinforcement learning. In *Learning for Dynamics and Control*, pages 958–968. PMLR, 2020.

[41] Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[42] Tsachy Weissman, Erik Ordentlich, Gadiel Seroussi, Sergio Verdu, and Marcelo J Weinberger. Inequalities for the l1 deviation of the empirical distribution. *Hewlett-Packard Labs, Tech. Rep*, 2003.

Negative Social Impact

This script may provide better guidance for risk-sensitive reinforcement learning community. It would have certain negative social impact if the proposed algorithms are deployed for illegal usage.