DECAP: DECODING CLIP LATENTS FOR ZERO-SHOT CAPTIONING

ABSTRACT

Large-scale pre-trained multi-modal models (e.g., CLIP) demonstrate strong zero-shot transfer capability in many discriminative tasks, e.g., image classification. Their adaptation to zero-shot image-conditioned text generation tasks has drawn increasing interests. Prior arts approach to zero-shot captioning by either utilizing the existing large language models (e.g., GPT-2) or pre-training the encoder-decoder network in an end-to-end manner. However, the large language models may not generate sensible descriptions due to the task discrepancy between captioning and language modeling, while the end-to-end pre-training requires paired data and extensive computational resources. In this work, we propose a simple framework, named DeCap, for zero-shot captioning. We introduce a lightweight visual-aware language decoder. This decoder is both data-efficient and computationally-efficient: 1) it only requires the *text* data for training, easing the burden on the collection of paired data. 2) it does not require end-to-end training. When trained with only the text data, the decoder takes the text embedding extracted from the off-the-shelf CLIP encoder as a prefix embedding. The challenge is that the decoder is trained on the text corpus but at the inference stage, it needs to generate captions based on visual inputs. Though the CLIP text embedding and the visual embedding are correlated, the *modality gap* issue is widely observed in multi-modal contrastive models that prevents us from directly taking the visual embedding as the prefix embedding. We propose a training-free mechanism to reduce the modality gap. We project the visual embedding into the CLIP text embedding space, while the projected embedding retains the information of the visual input. Taking the projected embedding as the prefix embedding, the decoder generates high-quality descriptions that match the visual input. The experiments show that DeCap outperforms other zero-shot captioning methods by a large margin on the typical image captioning benchmarks, i.e., MSCOCO and Flickr30K. On Flickr30K, the zero-shot result is even competitive with fully supervised methods. We apply DeCap to video captioning and achieve state-of-the-art zero-shot performance on MSR-VTT and ActivityNet-Captions.

1 INTRODUCTION

The goal of image captioning is to automatically generate descriptions for given images. Models (Anderson et al., 2018; Lu et al., 2017; Rennie et al., 2017; Zhang et al., 2021; Huang et al., 2021) trained on human-annotated image-text pairs have achieved impressive results on typical image captioning benchmarks. However, due to the small size and limited visual concepts of human-annotated datasets, these models generalize poorly to images in the wild (Agrawal et al., 2019; Tran et al., 2016). In this paper, to reduce the reliance on human-annotated paired data and improve the generalization in real-world captioning scenarios, we focus on zero-shot captioning that does not require human-annotated paired data for training.

Pre-training on web-scale noisy paired data has been demonstrated to be effective in learning robust multi-modal representations (Radford et al., 2021; Jia et al., 2021; Li et al., 2021; Alayrac et al., 2022; Yu et al., 2022a). Changpinyo et al. (2021) and Wang et al. (2021b) use web-scale image-text pairs to train a captioning model and achieve great improvements on MSCOCO (Chen et al., 2015) and NoCaps (Agrawal et al., 2019) through the pretraining-finetuning paradigm. However, these models show limited zero-shot captioning performance on MSCOCO, indicating that these methods

still rely on human-annotated paired data for fine-tuning. Besides, training with the captioning objective on large-scale data is not efficient, e.g., Wang et al. (2021b) pretrain the model on ALIGN (Jia et al., 2021) and Raffel et al. (2020) about 1M steps using 512 TPU v3 chips (Jouppi et al., 2017).

Instead of directly training a captioning model in an end-to-end manner on web-scale image-text pairs, another line of work (Tewel et al., 2022b; Su et al., 2022) achieves zero-shot captioning by combining existing pre-trained models. Specifically, they use a pre-trained contrastive model CLIP (Radford et al., 2021) to guide a pre-trained language model (PLM), i.e., GPT-2 (Radford et al., 2019), to generate sentences that match the given image. However, the inference speed of these methods is slow because each word generation involves a CLIP text encoder forward. Besides, language models pre-trained on diverse documents from webpages do not match well with captioning tasks that aim to describe visual concepts and their relationships in a given image, resulting in limited performance on image captioning benchmarks.

In this paper, we propose a new framework, named DeCap, for zero-shot captioning. We aim to decode sensible visual descriptions from the CLIP multi-modal embedding space. We do not use paired image-text data during the decoder pre-training, but only leverage the text data. This is more flexible and efficient when the alignment between images and texts became more noisy. Our DeCap framework is described below: During **pre-training**, the text decoder is trained from scratch. The goal is to invert the CLIP text encoder, i.e., a sentence is first encoded into an embedding by the CLIP text encoder and later reconstructed by our text decoder. The decoder takes the text embedding obtained from the CLIP text encoder as the prefix embedding. During **zero-shot inference**, the difficulty lies in how to obtain a prefix embedding that can match the input image and be well decoded by the decoder. The modality gap phenomenon (Liang et al., 2022b) is observed in multi-modal contrastive models which prevents us from directly taking the visual embedding as the prefix embedding. Ramesh et al. (2022) use paired data to learn a model to map the text embedding to a corresponding image embedding. Instead of learning a model, we propose a training-free mechanism to project the image embedding into the CLIP text embedding space. Combining the text decoder with the projection mechanism, we generate high-quality descriptions for given images.

Our main contributions are summarized as follows:

(1) We propose a new framework for zero-shot captioning. Our DeCap framework contains a pretrained contrastive model (i.e., CLIP) and a lightweight visual-aware language decoder taking the CLIP embedding as input. Though our decoder is trained only on the text corpus, it can associate both the visual embedding and the text embedding, thanks to the encoded multi-modal correlation in the CLIP embedding space.

(2) We propose a training-free projection mechanism to reduce the *modality gap* in CLIP multi-modal embedding space. We incorporate a simple support memory containing embeddings of the text corpus in the pre-training stage. We project a visual embedding into the CLIP text embedding space via the support memory. Experiments show that our proposed mechanism effectively reduces the modality gap and significantly improves performance.

(3) Extensive experiments demonstrate DeCap can flexibly apply to various captioning scenarios. DeCap outperforms other zero-shot captioning methods by a large margin on image captioning benchmarks MSCOCO and Flickr30k. On Flickr30k, the zero-shot result is competitive with fully supervised methods, significantly narrowing the gap between zero-shot learning and supervised learning. We apply DeCap to video captioning and achieve state-of-the-art zero-shot results on MSR-VTT and ActivityNet-Captions.

2 RELATED WORK

Vision language models pre-trained on Web-scale data have achieved impressive success (Radford et al., 2021; Jia et al., 2021; Yu et al., 2022a). The contrastive model CLIP pre-trained on 400M (image, text) pairs collected from the internet achieves impressive results on most discriminative tasks in a zero-shot manner. Sharma et al. (2018) introduce the Conceptual Captions (CC3M) dataset containing 3.3M (image, text) pairs collected from billions of webpages. CC12M (Sharma et al., 2018) further scales up the noisy paired data to 12M by relaxing the data collection pipeline. Models trained on CC3M/CC12M improve the captioning performance via the pretraining-finetuning

Figure 1: An overview of our framework. Our method is based on a pre-trained contrastive model CLIP containing a text encoder and a visual encoder. We first learn a text decoder to generate sentences conditioned on the CLIP text embedding. At inference, a training-free mechanism is used to project the image embedding into the text embedding space with the help of a support memory. The projected embedding is further decoded by the text decoder.

paradigm, but are limited in zero-shot captioning evaluation. SimVLM (Wang et al., 2021b) further trains a vision-language model on 1.8B weakly aligned image-text pairs (Jia et al., 2021) and 800GB of web crawled documents (Raffel et al., 2020) and achieves state-of-the-art on many benchmarks via fine-tuning on downstream datasets. The benefit of web-scale datasets has been demonstrated in the above work. However, the training cost is also non-negligible, e.g., SimVLM trains the model from scratch for about 1M steps using 512 TPU v3 chips (Jouppi et al., 2017). In this paper, instead of directly training a captioning model on a large-scale Web-collected dataset, we focus on applying the pre-trained contrastive model CLIP to the captioning task in a zero-shot manner.

Another line of work achieves zero-shot captioning by combining existing web-scale pre-trained models. ZeroCap (Tewel et al., 2022b) combines a contrastive model (e.g., CLIP) with a PLM (e.g., GPT-2). In each generation step, they use CLIP to guide GPT-2 towards a desired visual direction via the proposed CLIP loss. Magic (Su et al., 2022) further adapts the PLM to captioning textual domain by fine-tuning the PLM on a captioning-specific text corpus. Socratic Models (Zeng et al., 2022) use a pre-trained VLM (Gu et al., 2021) to generate prompt templates for GPT-3 (Brown et al., 2020) and then use CILP to retrieve the closest description to the image from the generated candidates. Different from the above work relying on PLMs, we train a text decoder from scratch. This decoder takes CLIP text embedding as input to invert the CLIP text encoder. By utilizing the cross-modal embedding space of CLIP, we can further associate the decoder with visual input to achieve zero-shot captioning.

3 METHOD

Our framework is shown in Figure 1. We learn a text decoder to convert the CLIP text encoder (Sec. 3.1). This text decoder allows us to generate sentences based on the CLIP text embedding. At inference, to reduce the modality gap between text embedding space and image embedding space, we propose a training-free mechanism to project the image embedding into the text embedding space (Sec. 3.2.1). We introduce more inference strategies for comparison (Sec. 3.2.2).

3.1 DECODER PRE-TRAINING

Previous approaches (Tewel et al., 2022b; Su et al., 2022; Zeng et al., 2022) employ a pre-trained language model (PLM) to generate diverse sentences for zero-shot captioning. However, PLMs trained on diverse documents from the webpages do not well match with captioning tasks that aim to describe visual concepts and relationships in a given image.

Instead of employing a PLM, we train a text decoder from scratch to invert the CLIP text encoder. Following recent work (Mokady et al., 2021; Wang et al., 2021b), we use a prefix language model

as our decoder. Specifically, given a sentence $t = \{word_1, word_2, ..., word_{|t|}\}$, the prefix language model P_θ learns to reconstruct t conditioned on the text embedding extracted by a fixed CLIP text encoder. We regard the text embedding as a prefix to the caption. Our objective can be described as:

$$\mathcal{L}_{Recons}(\theta) = -\frac{1}{|t|}\sum_{i=1}^{|t|} \log P_\theta(word_i|word_{<i}, E_{text}(t)), \tag{1}$$

where $E_{text}(\cdot)$ means mapping a sentence to a ℓ_2-normalized embedding space via the CLIP text encoder.

This decoder trained with only text data in a self-supervised manner brings two benefits. On the one hand, by adjusting the source of the training data, we can control the style of the generated sentences. To generate task-specific descriptive captions, we train our decoder on text data from human-annotated image descriptions and webly-collected image captions. On the other hand, this text decoder takes CLIP text embedding as the prefix embedding. The CLIP text embedding is optimized to be correlated with the CLIP image embedding, making it possible to associate the text decoder with visual input without any pairwise training.

3.2 INFERENCE STRATEGIES

In Sec. 3.1, we obtain a decoder that can generate descriptions conditioned on the CLIP text embedding. At inference, the question is how to use the decoder to generate descriptions given the CLIP image embedding. Due to the modality gap between CLIP image embedding space and text embedding space, it is impractical to directly take the CLIP image embedding as the prefix embedding. Ramesh et al. (2022) learn a prior model to map the text embedding to a corresponding image embedding. However, this process requires paired data for training. We propose a training-free mechanism to project the image embedding into text embedding space.

3.2.1 PROJECTION-BASED DECODING (PD)

Assuming that the language model P_θ is trained on a given text set $T = \{t_1, t_2, ..., t_N\}$, where N denotes the size of T. To represent the CLIP text embedding space, we maintain a support memory $M = \{\mathbf{m_1}, \mathbf{m_2}, ..., \mathbf{m_N}\}$, where $\mathbf{m_i} = E_{text}(t_i)$. At inference, we aim to generate a caption for a given image I. With the help of the support memory M, we can project the image embedding into the text embedding space. Specifically, given the image embedding $\mathbf{v} = E_{image}(I)$, we first project $\mathbf{v}$ to each text embedding $\mathbf{m_i}$ in M and then perform a weighted combination of all projections. To obtain the weights of these projections, the cosine similarity between $\mathbf{v}$ and $\mathbf{m}$ is calculated, scaled by a temperature parameter τ, and normalized by a softmax function. The combined project vector $\mathbf{v}_{proj}$ is calculated as:

$$\mathbf{v}_{proj} = \sum_{i=1}^{N} w_i * (\mathbf{m}_i^\top \mathbf{v})\mathbf{m}_i = \sum_{i=1}^{N} \frac{\exp((\mathbf{m}_i^\top \mathbf{v})/\tau)}{\sum_{k=1}^{N}\exp((\mathbf{m}_k^\top \mathbf{v})/\tau)} * (\mathbf{m}_i^\top \mathbf{v})\mathbf{m}_i, \tag{2}$$

where w_i is the weight of i-th projection vector. $\mathbf{v}_{proj}$ is a combination of CLIP text embeddings that can be used as the prefix embedding. We denote $P_\theta(\mathbf{x})$ as the auto-regressive process of generating a sentence conditioned on the prefix embedding $\mathbf{x}$. The final output can be generated by $P_\theta(\frac{\mathbf{v}_{proj}}{||\mathbf{v}_{proj}||_2})$.

This projection-based method does not requires any additional training. It performs well across many datasets and is flexible. The projected vector $\mathbf{v}_{proj}$ can absorb the information from text embeddings in the support memory, resulting in diverse and accurate descriptions. On the other hand, the text data used for training and stored in support memory can be different. We can select appropriate text data to construct a new support memory according to the target domain. The image embedding will then be projected into the new text embedding space, which allows DeCap to quickly generalize to new domains without retraining.

3.2.2 DISCUSSION

To investigate the effect of our decoder and the projection-based mechanism, we further introduce the following methods for comparison:

1) CLIPRe. We first consider a simple retrieval-based approach that does not require a decoder. This approach is mentioned in Su et al. (2022). Given the image I and text set $T = \{t_1, t_2, ..., t_n\}$, CLIPRe retrieves the most relevant texts from T based on the image-text similarity measured by CLIP. This process can be formulated as: $\arg\max_{t \in T} sim(E_{image}(I), E_{text}(t))$, where sim denotes the cosine similarity. In all experiments, we use CLIPRe as our baseline, since it can well reflect the zero-shot performance of the original CLIP without the decoder.

2) Visual Decoding (VD). Considering that text embeddings and image embeddings are correlated, a simple approach is to directly use the image embedding as the prefix embedding. We refer to this method as Visual Decoding. This process can be formulated as: $P_\theta(E_{image}(I))$. However, across the experiments, this method does not achieve satisfying results in most scenarios, indicating that there is a modality gap between CLIP image embeddings and text embeddings.

3) Nearest-neighbor Decoding (NND). Another simple method is to use the nearest text embedding as the prefix embedding. Specifically, we first calculate the similarity between the image embedding $E_{image}(I)$ and the text embeddings in M. Then, the nearest text embedding is directly used as the prefix embedding. We refer to this method as Nearest-neighbor Decoding. This process can be formulated as: $P_\theta(\arg\max_{\mathbf{m} \in M} sim(E_{image}(I), \mathbf{m}))$. Ideally, NND and CLIPRe should achieve the same performance, because the decoder learns to recover the origin text conditioned on the text embedding. Interestingly, across our experiments, NND achieves better performance than CLIPRe in most scenarios, suggesting that our decode may generate more descriptive sentences. Moreover, we find that the performance could be further improved by reconstructing a new text corpus using the decoder. More results and discussion are in Appendix B.

4 EXPERIMENTS

We conduct extensive experiments on captioning tasks including zero-shot image captioning, unpaired image captioning and video captioning. We demonstrate that DeCap can efficiently achieve impressive results under different conditions. In Sec. 4.1, we focus on zero-shot image captioning without any human annotation. In Sec. 4.2, we focus on unpaired image captioning where the images and the sentences are treated independently. In Sec. 4.3, we further apply DeCap to video captioning tasks. In Sec. 4.4, we conduct detailed ablation studies for DeCap.

Implementation Details. We employ a frozen pre-trained Vit-B/32 CLIP model. We adopt a 4-layer Transformer (Subramanian et al., 2018) with 4 attention heads as our language model. The size of the hidden state is 768. By default, we use all the text data in the training set to train the language model from scratch with a naive cross-entropy loss. All the text embeddings from the training corpus are stored to the support memory unless specified otherwise. At inference, the temperature τ in Eq. 2 is set to 0.007 in the video captioning experiment, and 0.01 in other experiments. We report the results over four standard captioning evaluation metrics: BLEU@N (Papineni et al., 2002), METEOR (Banerjee & Lavie, 2005), CIDEr (Vedantam et al., 2015), and SPICE (Anderson et al., 2016). Additionally, we use CLIP-S^{Ref} (Hessel et al., 2021) and CLIP-S to measure the text-text similarity and text-image similarity, respectively. The beam search or constrained beam search (Anderson et al., 2017) is **not** used in all our results.

4.1 ZERO-SHOT IMAGE CAPTIONING

In this section, we conduct zero-shot image captioning using webly-collected corpora. Traditional image captioning methods rely on paired human-annotated data for training, which is difficult to obtain and limited in scale and diversity. We consider two webly-collected corpora for DeCap training: (1) **CC3M** (Sharma et al., 2018) contains three million image-description pairs collected from the web. We only use the text descriptions (CC3M-text) for training. We use one million descriptions randomly sampled from the 3M descriptions to construct the support memory. (2) **SS1M** (Feng et al., 2019) is a webly-collected corpus specifically designed for MSCOCO caption. Feng et al. (2019) use the name of the eighty object classes in MSCOCO as keywords to crawl the descriptions from Shutterstock[1], resulting in 2,322,628 distinct image descriptions in total. We reuse this corpus and further remove sentences with more than fifteen words, obtaining 978,662 sentences.

---

[1]https://www.shutterstock.com

Methods	Pre-training stage	MSCOCO				NoCaps val (CIDEr)			
		B@4	M	C	S	In	Near	Out	Overall
Changpinyo et al. (2021)	CC3M	-	-	-	-	29.2	27.5	37.3	29.7
Changpinyo et al. (2021)	CC12M	-	-	-	-	20.7	24.1	41.6	27.1
ZeroCap	CLIP+GPT-2	2.6	11.5	14.6	5.5	-	-	-	-
CLIPRe	CLIP+CC3M-text	4.6	13.3	25.6	9.2	23.3	26.8	36.5	28.2
DeCap	CLIP+CC3M-text	8.6	15.7	41.3	10.9	34.7	35.9	**48.7**	38.3
DeCap	CLIP+SS1M	**9.2**	**17.4**	**50.6**	**13.1**	**41.8**	**41.7**	46.2	**42.6**

Table 1: Zero-shot captioning results on MSCOCO Karpathy-test split and NoCaps validation set. (In: in-domain; Near: near-domain; Out: out-of-domain; B@4: BLEU@4; M: METEOR; C: CIDEr; S: SPICE).

We compare with methods that use webly-collected data for training or directly employ web-scale pre-trained models to achieve image captioning. Changpinyo et al. (2021) train a captioning model on webly-collected paired data and directly transfer to downstream datasets without fine-tuning. ZeroCap (Tewel et al., 2022b) is a training-free zero-shot captioning method leveraging CLIP and GPT-2. DeCap also adopts CLIP but trains a decoder from scratch on a webly-collected corpus. All these methods target for zero-shot image captioning and do not use human-annotated data.

Results. Table 1 shows the zero-shot results on MSCOCO and NoCaps. DeCap achieves a new state-of-the-art on all metrics. On NoCaps, models pre-trained on webly-collected data achieve better out-of-domain results. This is because the webly-collected data contain diverse visual concepts. On MSCOCO, DeCap pretrained on CC3M-text outperforms ZeroCap by 26.7% in CIDEr. DeCap pretrained on SS1M outperforms ZeroCap by 36% in CIDEr. DeCap trained on SS1M achieves better performance than trained on CC3M (CIDEr: 50.6% vs. 41.3%), indicating that the task-specific webly-collected corpus can further improve the performance of downstream datasets.

4.2 UNPAIRED IMAGE CAPTIONING

To explore the potential of DeCap in more captioning scenarios, we consider the unpaired image captioning setting, where the human-annotated image-sentence pairs are treated as unpaired images and sentences. In Sec. 4.2.1, we investigate the in-domain captioning where training data and test data come from the same dataset, but the training data are unpaired. In Sec. 4.2.2, we consider the cross-domain situation where training data and test data come from different distributions.

4.2.1 IN-DOMAIN CAPTIONING

We evaluate the in-domain captioning performance and compare to supervised methods and other unpaired image captioning methods. (1) Supervised methods: **BUTD** (Anderson et al., 2018) is a classic method that uses Faster R-CNN (Ren et al., 2015) to extract visual features; **CLIPCap** (Mokady et al., 2021) and **CLIP-VL** (Shen et al., 2021) are recent approaches employing CLIP as the visual encoder. (2) Unpaired methods: Laina et al. (2019) and Feng et al. (2019) treat the images and captions from MSCOCO training set as unpaired data. (3) (CLIP+GPT2)-based methods: **ZeroCap** (Tewel et al., 2022b), **Magic** (Su et al., 2022) and **ESPER-Style** (Yu et al., 2022b) finetune the GPT-2 on captions from the training set. (4) **ESPER-Free** (Yu et al., 2022b) use reinforcement learning to align multimodal inputs to language model generations. (5) **CLIPRe** is a retrieval-based baseline. (6) Our **DeCap** uses projection-based decoding (PD) by default. We compare it with another two inference strategies introduced in Sec. 3.2. We denote visual decoding as **DeCap-VD** and nearest-neighbor decodign as **DeCap-NND**. Notably, our decoder is trained on the captions from the training set, and text embeddings of all the training captions are maintained in the support memory.

Results. Table 2 shows the results on MSCOCO and Flickr30K. Overall, DeCap outperforms recent zero-shot approaches by a large margin. Especially on Flickr30K, DeCap is competitive with the supervised learning method BUTD, largely narrowing the gap between supervised learning and zero-shot learning. Notably, our DeCap achieves CIDEr of 91.4% on MSCOCO, outperforming Magic Su et al. (2022) by 42.1%. This clearly demonstrates the effectiveness of our DeCap framework. Two conclusions can be drawn: (1) **CLIP provides aligned multi-modal representations for captioning tasks.** Compared to the unpaired methods that use a visual concept detector to construct a multi-modal embedding space, the CLIP-based zero-shot methods could achieve com-

Method	Data			MSCOCO				Flickr30K			
	P.	I.	T.	B@4	M	C	S	B@4	M	C	S
Supervised Methods											
BUTD	✓			36.2	27.0	113.5	20.3	27.3	21.7	56.6	16.0
CLIPCap	✓			33.5	27.5	113.1	21.1	-	-	-	-
VinVL	✓			41.0	31.1	140.9	25.2	-	-	-	-
CLIP-VL	✓			40.2	29.7	134.2	23.8	-	-	-	-
Train on unpaired data. Zero-shot inference on image-text pairs											
Feng et al. (2019)		✓	✓	18.6	17.9	54.9	11.1	-	-	-	-
Laina et al. (2019)		✓	✓	19.3	20.2	61.8	12.9	-	-	-	-
ESPER-Style		✓	✓	21.9	21.9	78.2	-	-	-	-	-
ESPER-Free		✓		6.3	13.3	29.1	-	-	-	-	-
Zerocap*			✓	7.0	15.4	34.5	9.2	5.4	11.8	16.8	6.2
Magic			✓	12.9	17.4	49.3	11.3	6.4	13.1	20.4	7.1
CLIPRe			✓	12.4	20.4	53.4	14.8	9.8	18.2	31.7	12.0
DeCap-VD			✓	5.0	15.5	25.7	9.8	5.8	15.0	13.0	8.2
DeCap-NND			✓	15.3	21.2	62.9	15.8	12.9	17.2	35.2	10.9
DeCap			✓	**24.7**	**25.0**	**91.4**	**18.7**	**21.0**	**21.8**	**56.6**	**15.2**

Table 2: In-domain captioning results on MSCOCO and Flickr30K. "*" denotes results from Su et al. (2022). "P.", "I." and "T." denote paired data, unpaired image data and unpaired text data, respectively.

petitive results using only text data. (2) **Our decoder and the projection mechanism are crucial for a high performance.** Compared to CLIPRe, DeCap-NND further decodes the nearest-neighbor text embeddings resulting in higher performance, indicating that our decoder can generate more descriptive sentences. DeCap-VD achieves limited performance, demonstrating that there is a large modality gap between CLIP image embedding and text embedding, demonstrating the necessity of our projection mechanism.

4.2.2 CROSS-DOMAIN CAPTIONING

We evaluate the following methods on MSCOCO and Flickr30K in the cross-domain setting, where the training data and the testing data are from different datasets. (1) Zhao et al. (2020) generate pseudo image-text pairs for the target domain using a retrieval model trained on the source domain. (2) **Magic** (Su et al., 2022) finetunes GPT-2 on text data from the source domain. (3) **CLIPRe-S** uses text data from the source domain as galleries. (4) **DeCap** trains the decoder on text data from the source domain. (5) **DeCap-TT** trains the decoder on text data from the source domain and uses the captions from target domain as the support memory.

Results. Table 3 shows the results. Unlike the traditional cross-domain method (Zhao et al., 2020) that relies on paired source domain data and requires training on the target domain, recent CLIP-based zero-shot methods only require source domain text data for training. DeCap significantly outperforms CLIP-based methods, e.g., Magic (Su et al., 2022) and CLIPRe-S on both MSCOCO to Flickr30K and Flickr30K to MSCOCO. Moreover, if the text data from target domain is accessible, DeCap-TT significantly improves the captioning performance (e.g., CIDEr is improved from 44.5% to 63.3%) without any additional training. It simply employs text embedding from the target domain as the support memory. These results demonstrate the strong capabilities of DeCap in cross-domain generalization and the effectiveness of our projection-based decoding mechanism.

4.3 VIDEO CAPTIONING

In this section, we apply our method to the video captioning task. We conduct the experiments on MSR-VTT (Xu et al., 2016) and Activity-Captions (Caba Heilbron et al., 2015). **MSR-VTT** is a large-scale dataset for the open domain video captioning that consists of 10,000 video clips. Each video clip is annotated with 20 sentences. **ActivityNet-Captions** is a standard dense video captioning benchmark with 100K sentence for 20k videos. Following Lei et al. (2020), the val set is split into: *ae-val* with 2,460 videos and *ae-test* with 2,457 videos. We use ground-truth temporal proposals following Krishna et al. (2017).

Methods	Data				MSCOCO to Flickr30K				Flickr30K to MSCOCO			
	S.P.	S.T.	T.I.	T.T.	B@4	M	C	S	B@4	M	C	S
Zhao et al. (2020)*	✓	✓	✓	✓	24.1	19.5	52.8	-				
Magic		✓			6.2	12.2	17.5	5.9	5.2	12.5	18.3	5.7
CLIPRe-S		✓			9.8	16.7	30.1	10.3	6.0	16.0	26.5	10.2
DeCap		✓			16.4	18.1	35.9	11.2	12.0	18.1	44.5	10.9
DeCap-TT		✓		✓	17.6	20.3	41.9	13.7	19.8	20.9	63.3	14.0

Table 3: Cross-domain image captioning evaluation. MSCOCO to Flickr30K means MSCOCO is the source dataset and Flickr30K is the target dataset. "*" means using CIDEr optimization (Rennie et al., 2017). ("S.P.": Source paired data; "S.T.": Source text data; "T.I.": Target image data; "T.T.": Target text data).

Methods	Setting	Metrics				
		B@4	M	C	CLIP-S^{Ref}	CLIP-S
MSR-VTT						
VNS-GRU[†] (Chen et al., 2020)	Supervised	45.3	29.9	53.0	0.739	0.626
SemSynAN[†] (Perez-Martin et al., 2021)		46.4	30.4	51.9	0.733	0.619
ZeroCap[†]		2.3	12.9	5.8	0.739	0.710
MAGIC[†]		5.5	13.3	7.4	0.628	0.566
Tewel et al. (2022a)[†]	Zero-shot	3.0	14.6	11.3	0.785	**0.775**
DeCap-CC3M		6.2	14.9	15.0	**0.792**	0.736
DeCap-COCO		**14.7**	**20.4**	**18.6**	0.761	0.697
CLIPRe-MSR	MSR-VTT text only	10.2	18.8	19.9	0.835	0.852
DeCap-MSR		23.0	23.7	34.9	0.823	0.770
Activity-net						
Reasoner (Liang et al., 2022a)	Supervised	12.5	16.4	30.0	-	-
PDVC (Wang et al., 2021a)		11.8	15.9	27.3	-	-
DeCap-CC3M	Zero-shot	0.6	5.3	12.6	0.769	0.817
DeCap-COCO		1.3	6.6	15.1	0.838	0.754
CLIPRe-ACT	ActivityNet-Captions text only	1.4	8.2	15.1	0.830	0.871
DeCap-ACT		2.4	9.4	20.1	0.808	0.797

Table 4: Video captioning evaluation results. "†" denotes the result is borrowed from Tewel et al. (2022a). DeCap-CC3M, DeCap-COCO, DeCap-MSR and DeCap-ACT denote the model is trained on text data from CC3M, MSCOCO, MSR-VTT and Activity-Captions, respectively.

We apply the same DeCap for video captioning. We consider two different sources for training: (1) **Image captions**. We train our decoder on captions from MSCOCO and CC3M, which are collected or annotated for image captioning tasks. This is a zero-shot video captioning problem as DeCap does not use any video-related data for training. (2) **Video captions**. We extract the text annotations in the training set of video captioning datasets.

At inference, we use a pooling mechanism on frame-level features to obtain a video-level feature. Specifically, for each proposal, we directly randomly sample k frames $f_1, f_2, ..., f_k$ from the clip. We use a mean pooling mechanism on the frame-level features extracted by the CLIP image encoder to obtain a video-level feature. In all experiments, k is set to 10.

Results. Table 4 shows the results. DeCap trained on image captions outperforms the recent zero-shot captioning approaches on standard captioning metrics and achieves competitive results on CLIP-S and CLIP-S^{Ref} metrics. Notably, unlike other methods, DeCap does not directly take CLIP visual-text similarity as the optimization objective. Moreover, DeCap trained on video captions can further improve performance. These results demonstrate that DeCap can easily apply to the video captioning task with a simple random sampling strategy and temporal mean pooling mechanism.

4.4 ABLATION STUDY

In this section, we investigate the effect of the size of training data and the size of the support memory. We study the effect of the pretraining-finetuning paradigm under our framework. We conduct the studies on MSCOCO.

The size of training data. A key question is how much text data we need to train the decoder from scratch. To investigate the effect of training data size, we sample different scale data from

Figure 2: Ablation study on the support memory size (**left**) and the training data size (**right**).

Pre-training data	Fine-tuning data	Memory data	CIDEr			
			in	near	out	overall
MSCOCO	-	MSCOCO	65.2	47.8	25.8	45.9
CC3M	-	CC3M	34.7	35.9	**48.7**	38.3
CC3M	MSCOCO	MSCOCO	**72.7**	**61.9**	43.9	58.2
CC3M	-	MSCOCO	70.1	60.4	44.5	**58.6**

Table 5: Results of DeCap on NoCaps validation split. We only use the text data for both pre-training and fine-tuning.

MSCOCO. At inference, we use the same support memory (full training set, 560K captions) for all experiments. The results are in Figure 2 (**left**). Overall, DeCap benefits from large data size. Compared with training on the full set, the CIDEr score drops from 91.4% to 81.5% when using only 1% data (5.6K captions). The result indicates that DeCap is data-efficient. It shows a promising direction in its application in data-limited scenarios.

The size of the support memory. To investigate the effect of support memory size, we first train the language model on the full training set (560K captions). At inference, we randomly sample different ratio text embeddings as the support memory. The results are in Figure **??** (**right**). Overall, DeCap and CLIPRe both benefit from a large support memory. Moreover, when using only 1% data as the support memory, the performance drops slightly (3.8% performance drop in CIDEr). It indicates that we can maintain a relatively small support memory to achieve competitive results with acceptable storage and computation costs.

Pretraining-finetuning. An interesting question is whether DeCap can benefit from the pretraining-finetuning paradigm. Table 5 shows the results on the NoCaps validation split. Notably, we only use text data for training in both pre-training and fine-tuning. Compared to trained on MSCOCO, the model trained on CC3M achieves better performance in the out-of-domain case, improving the CIDEr metric from 25.8% to 48.7%. This is because CC3M covers more diverse classes than MSCOCO. By fine-tuning the pre-trained model on MSCOCO, we find that the overall performance is greatly improved, obtaining an overall CIDEr of 58.2%. It indicates that our method benefits from the pretraining-finetuning paradigm. By directly changing the support memory without fine-tuning, DeCap achieves a comparable performance as fine-tuning. It suggests that our method can be easily adapted to new domains without training, requiring only some text data from new domains.

5 CONCLUSION

We propose a simple framework for zero-shot captioning and introduce a lightweight visual-aware language decoder that is both data-efficient and computationally-efficient. We propose a training-free mechanism to project the visual embedding to text embedding space, significantly reduces the modality gap issue. By combining the decoder with the projection mechanism, we significantly outperform existing zero-shot methods, establishing a new state-of-the-art in MSCOCO, Flickr30K, MSR-VTT and ActivityNet-Captions. In the future, our DeCap framework may be adapted to other zero-shot text generation problems, e.g., visual dialog.

REFERENCES

Harsh Agrawal, Karan Desai, Yufei Wang, Xinlei Chen, Rishabh Jain, Mark Johnson, Dhruv Batra, Devi Parikh, Stefan Lee, and Peter Anderson. Nocaps: Novel object captioning at scale. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 8948–8957, 2019.

Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katie Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. *arXiv preprint arXiv:2204.14198*, 2022.

Peter Anderson, Basura Fernando, Mark Johnson, and Stephen Gould. Spice: Semantic propositional image caption evaluation. In *European conference on computer vision*, pp. 382–398. Springer, 2016.

Peter Anderson, Basura Fernando, Mark Johnson, and Stephen Gould. Guided open vocabulary image captioning with constrained beam search. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pp. 936–945, 2017.

Peter Anderson, Xiaodong He, Chris Buehler, Damien Teney, Mark Johnson, Stephen Gould, and Lei Zhang. Bottom-up and top-down attention for image captioning and visual question answering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 6077–6086, 2018.

Satanjeev Banerjee and Alon Lavie. Meteor: An automatic metric for mt evaluation with improved correlation with human judgments. In *Proceedings of the acl workshop on intrinsic and extrinsic evaluation measures for machine translation and/or summarization*, pp. 65–72, 2005.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

Fabian Caba Heilbron, Victor Escorcia, Bernard Ghanem, and Juan Carlos Niebles. Activitynet: A large-scale video benchmark for human activity understanding. In *Proceedings of the ieee conference on computer vision and pattern recognition*, pp. 961–970, 2015.

Soravit Changpinyo, Piyush Sharma, Nan Ding, and Radu Soricut. Conceptual 12m: Pushing web-scale image-text pre-training to recognize long-tail visual concepts. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3558–3568, 2021.

Haoran Chen, Jianmin Li, and Xiaolin Hu. Delving deeper into the decoder for video captioning. In *ECAI 2020*, pp. 1079–1086. IOS Press, 2020.

Xinlei Chen, Hao Fang, Tsung-Yi Lin, Ramakrishna Vedantam, Saurabh Gupta, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco captions: Data collection and evaluation server. *arXiv preprint arXiv:1504.00325*, 2015.

Yang Feng, Lin Ma, Wei Liu, and Jiebo Luo. Unsupervised image captioning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4125–4134, 2019.

Xiuye Gu, Tsung-Yi Lin, Weicheng Kuo, and Yin Cui. Open-vocabulary object detection via vision and language knowledge distillation. In *International Conference on Learning Representations*, 2021.

Jack Hessel, Ari Holtzman, Maxwell Forbes, Ronan Le Bras, and Yejin Choi. CLIPScore: A reference-free evaluation metric for image captioning. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 7514–7528, November 2021.

Yupan Huang, Hongwei Xue, Bei Liu, and Yutong Lu. Unifying multimodal transformer for bidirectional image and text generation. In *Proceedings of the 29th ACM International Conference on Multimedia*, pp. 1138–1147, 2021.

Chao Jia, Yinfei Yang, Ye Xia, Yi-Ting Chen, Zarana Parekh, Hieu Pham, Quoc Le, Yun-Hsuan Sung, Zhen Li, and Tom Duerig. Scaling up visual and vision-language representation learning with noisy text supervision. In *International Conference on Machine Learning*, pp. 4904–4916. PMLR, 2021.

Norman P Jouppi, Cliff Young, Nishant Patil, David Patterson, Gaurav Agrawal, Raminder Bajwa, Sarah Bates, Suresh Bhatia, Nan Boden, Al Borchers, et al. In-datacenter performance analysis of a tensor processing unit. In *Proceedings of the 44th annual international symposium on computer architecture*, pp. 1–12, 2017.

Ranjay Krishna, Kenji Hata, Frederic Ren, Li Fei-Fei, and Juan Carlos Niebles. Dense-captioning events in videos. In *Proceedings of the IEEE international conference on computer vision*, pp. 706–715, 2017.

Iro Laina, Christian Rupprecht, and Nassir Navab. Towards unsupervised image captioning with shared multimodal embeddings. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 7414–7424, 2019.

Jie Lei, Liwei Wang, Yelong Shen, Dong Yu, Tamara Berg, and Mohit Bansal. Mart: Memory-augmented recurrent transformer for coherent video paragraph captioning. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 2603–2614, 2020.

Junnan Li, Ramprasaath Selvaraju, Akhilesh Gotmare, Shafiq Joty, Caiming Xiong, and Steven Chu Hong Hoi. Align before fuse: Vision and language representation learning with momentum distillation. *Advances in neural information processing systems*, 34:9694–9705, 2021.

Chen Liang, Wenguan Wang, Tianfei Zhou, and Yi Yang. Visual abductive reasoning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 15565–15575, 2022a.

Weixin Liang, Yuhui Zhang, Yongchan Kwon, Serena Yeung, and James Zou. Mind the gap: Understanding the modality gap in multi-modal contrastive representation learning. *arXiv preprint arXiv:2203.02053*, 2022b.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2018.

Jiasen Lu, Caiming Xiong, Devi Parikh, and Richard Socher. Knowing when to look: Adaptive attention via a visual sentinel for image captioning. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 375–383, 2017.

Ron Mokady, Amir Hertz, and Amit H Bermano. Clipcap: Clip prefix for image captioning. *arXiv preprint arXiv:2111.09734*, 2021.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*, pp. 311–318, 2002.

Jesus Perez-Martin, Benjamin Bustos, and Jorge Pérez. Improving video captioning with temporal composition of a visual-syntactic embedding. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 3039–3049, 2021.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pp. 8748–8763. PMLR, 2021.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, Peter J Liu, et al. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21(140):1–67, 2020.

Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 2022.

Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. *Advances in neural information processing systems*, 28, 2015.

Steven J Rennie, Etienne Marcheret, Youssef Mroueh, Jerret Ross, and Vaibhava Goel. Self-critical sequence training for image captioning. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7008–7024, 2017.

Piyush Sharma, Nan Ding, Sebastian Goodman, and Radu Soricut. Conceptual captions: A cleaned, hypernymed, image alt-text dataset for automatic image captioning. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2556–2565, 2018.

Sheng Shen, Liunian Harold Li, Hao Tan, Mohit Bansal, Anna Rohrbach, Kai-Wei Chang, Zhewei Yao, and Kurt Keutzer. How much can clip benefit vision-and-language tasks? In *International Conference on Learning Representations*, 2021.

Yixuan Su, Tian Lan, Yahui Liu, Fangyu Liu, Dani Yogatama, Yan Wang, Lingpeng Kong, and Nigel Collier. Language models can see: Plugging visual controls in text generation. *arXiv preprint arXiv:2205.02655*, 2022.

Sandeep Subramanian, Adam Trischler, Yoshua Bengio, and Christopher J Pal. Learning general purpose distributed sentence representations via large scale multi-task learning. In *International Conference on Learning Representations*, 2018.

Yoad Tewel, Yoav Shalev, Roy Nadler, Idan Schwartz, and Lior Wolf. Zero-shot video captioning with evolving pseudo-tokens. *arXiv preprint arXiv:2207.11100*, 2022a.

Yoad Tewel, Yoav Shalev, Idan Schwartz, and Lior Wolf. Zerocap: Zero-shot image-to-text generation for visual-semantic arithmetic. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 17918–17928, 2022b.

Kenneth Tran, Xiaodong He, Lei Zhang, Jian Sun, Cornelia Carapcea, Chris Thrasher, Chris Buehler, and Chris Sienkiewicz. Rich image captioning in the wild. In *Proceedings of the IEEE conference on computer vision and pattern recognition workshops*, pp. 49–56, 2016.

Ramakrishna Vedantam, C Lawrence Zitnick, and Devi Parikh. Cider: Consensus-based image description evaluation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4566–4575, 2015.

Teng Wang, Ruimao Zhang, Zhichao Lu, Feng Zheng, Ran Cheng, and Ping Luo. End-to-end dense video captioning with parallel decoding. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6847–6857, 2021a.

Zirui Wang, Jiahui Yu, Adams Wei Yu, Zihang Dai, Yulia Tsvetkov, and Yuan Cao. Simvlm: Simple visual language model pretraining with weak supervision. In *International Conference on Learning Representations*, 2021b.

Jun Xu, Tao Mei, Ting Yao, and Yong Rui. Msr-vtt: A large video description dataset for bridging video and language. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 5288–5296, 2016.

Jiahui Yu, Zirui Wang, Vijay Vasudevan, Legg Yeung, Mojtaba Seyedhosseini, and Yonghui Wu. Coca: Contrastive captioners are image-text foundation models. *Transactions on Machine Learning Research*, 2022a. URL https://openreview.net/forum?id=Ee277P3AYC.

Youngjae Yu, Jiwan Chung, Heeseung Yun, Jack Hessel, JaeSung Park, Ximing Lu, Prithviraj Ammanabrolu, Rowan Zellers, Ronan Le Bras, Gunhee Kim, et al. Multimodal knowledge alignment with reinforcement learning. *arXiv preprint arXiv:2205.12630*, 2022b.

Andy Zeng, Adrian Wong, Stefan Welker, Krzysztof Choromanski, Federico Tombari, Aveek Puro-hit, Michael Ryoo, Vikas Sindhwani, Johnny Lee, Vincent Vanhoucke, et al. Socratic models: Composing zero-shot multimodal reasoning with language. *arXiv preprint arXiv:2204.00598*, 2022.

Xuying Zhang, Xiaoshuai Sun, Yunpeng Luo, Jiayi Ji, Yiyi Zhou, Yongjian Wu, Feiyue Huang, and Rongrong Ji. Rstnet: Captioning with adaptive attention on visual and non-visual words. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 15465–15474, 2021.

Wentian Zhao, Xinxiao Wu, and Jiebo Luo. Cross-domain image captioning via cross-modal re-trieval and model adaptation. *IEEE Transactions on Image Processing*, 30:1180–1192, 2020.

A MORE IMPLEMENTATION DETAILS

We employ a frozen pre-trained Vit-B/32 CLIP model as our cross-modal feature extractor. We adopt a lighting 4-layer Transformer (Subramanian et al., 2018) with 4 attention heads as our decoder (hidden state size 768) following the details (Radford et al., 2019). A linear layer is used to project the CLIP embedding from 512 dimension to 768 dimensions, and is trained with the decoder. The training data size and hyper-parameter for different datasets are summarized in Table 6.

	MSCOCO	Flickr30K	CC3M	SS1M	MSR-VTT	Activity-Captions
Training size	560K	30K	3M	978K	140K	37K
Training steps	40K	20K	200K	150K	20K	8K
Warmup steps	2K	2K	2K	2K	2K	1K
Batch size				128		
Learning rate				$1e^{-5}$		
Label smoothing				0.1		
Optimizer			AdamW (Loshchilov & Hutter, 2018) with default hyperparameters			

Table 6: Training data size and hyper-parameter

B DISCUSSION ABOUT THE RECONSTRUCTION

In Sec. 3.2.2, we introduce the CLIPRe and Nearest-neighbor Decoding (NND) method. Given an image and its CLIP image embedding, both CLIPRe and NND first retrieve the most relative text embedding $\mathbf{m_t}$ in the support memory according to the image-text cosine similarity. CLIPRe then adopts the original sentence t of the $\mathbf{m_t}$ as the caption. NND uses the decoder to generate a sentence t^* conditioned on $\mathbf{m_t}$. Ideally, the generated sentence t^* should be the same as the original sentence t, because the decoder learns to reconstruct t conditioned on the $\mathbf{m_t}$. However, according to the experiments in Sec. 4.2.1, we find NND outperforms CLIPRe in most metrics. To figure out the reason, we conduct the following experiments.

We first train our decoder on the MSCOCO training set with Eq. 1. To investigate the effect of the text decoder, we construct a new corpus $T^* = \{t_1^*, t_2^*, ..., t_N^*\}$, where $t^* = P_\theta(E_{text}(t))$, t is the original sentence in MSCOCO training set and t^* is the reconstructed sentence. We adopt this new corpus as the support memory.

Table 7 shows the results. The reconstructed dataset improves the performance of CLIPRe on all metrics, especially on CIDEr, from 53.4 to 63.6 (+10.2). DeCap adopting the new corpus as the support memory could further improve the CIDEr score to 95.1 (+3.7). The result demonstrates that the sentences generated by our method can better describe the images in MSCOCO. We think the reason is that our decoding process has a denoising effect, which can remove some outliers captions in the training set. Another open question here is whether such a denoised dataset can improve the performance of other fully supervised methods. We leave this as our future work.

	B@4	M	C	S
CLIPRe	12.4	20.4	53.4	14.8
CLIPRe-recons	14.9 (+2.5)	21.5 (+1.1)	63.6 (+10.2)	16.2 (+1.4)
DeCap	24.7	25.0	91.4	18.7
DeCap-recons	26.5 (+1.8)	24.9 (-0.1)	95.1 (+3.7)	18.6 (-0.1)

Table 7: Results on MSCOCO Karpathy-test split. CLIPRe-recons and DeCap-recons denote using the reconstructed corpus as the support memory.

C VISUALIZATIONS

We visualize the generated captions of some images from the MSCOCO Karpathy-test split in Figure 3. We show the captions generated by the DeCap model trained on MSCOCO and CC3M. The captions from DeCap-MSCOCO and DeCap-CC3M have visible style differences.

Figure 3: Generated captions for images from the MSCOCO Karpathy-test split. DeCap-MSCOCO and DeCap-CC3M denote DeCap trained on the MSCOCO training set and CC3M training set, respectively.