Implications of Model Indeterminacy for Explanations of Automated Decisions

Abstract

There has been a significant research effort focused on explaining predictive models, for example through post-hoc explainability and recourse methods. Most of the proposed techniques operate upon a single, fixed, predictive model. However, it is well-known that given a dataset and a predictive task, there may be a multiplicity of models that solve the problem (nearly) equally well. In this work, we investigate the implications of this kind of model indeterminacy on the post-hoc explanations of predictive models. We show how it can lead to *explanatory multiplicity*, and we explore the underlying drivers. We show how predictive multiplicity, and the related concept of epistemic uncertainty, are not indicative of explanatory multiplicity. We further illustrate how a set of models showing very similar aggregate performance on a test dataset may show large variations in their local explanations, i.e., for a specific input. We explore these effects for Shapley value based explanations on three risk assessment datasets. Our results indicate that model indeterminacy may have a substantial impact on explanations in practice, leading to inconsistent and even contradicting explanations.

1 Introduction

Data-driven decision making has become a preferred practice within organizations. When the most important outcomes are readily quantifiable, entire decision making processes may even be automated using predictive models fit to historic data. With so much to be gained from accurate predictions, powerful, modern, "black-box" machine learning (ML) models have obvious appeal. Clearly, however, it is understood that deciding whether to deny access to products like insurance and credit should not be taken lightly. Governing regulation may require a justification to be provided in conjunction with a decision, such as one from a set of adverse action codes [32]. Even where such regulation is not required, there is increasing pressure to make automated decisions more transparent [29]. As a result, considerable interest has recently been devoted to explaining ML model decisions. Academics have proposed numerous new techniques [2], new businesses have been assembled to address this need, and regulators have invested significant effort to provide guidance [20].

Thus far, the focus of most machine learning explanation and transparency research has been on a single learned predictive model. However, it is well-known that given a dataset and a predictive task, there may be a multiplicity of models that solve the problem (nearly) equally well[4; 6; 28]. What are the implications of this kind of model indeterminacy for the explanations of automated decisions? It has been shown that a set of models with very similar performance on a test set may still show significant *predictive multiplicity* [19], which is to say, disagreement on individual predictions. Quantifying this kind of model uncertainty in machine learning predictions is the subject of considerable research interest. For instance it is central to work in Bayesian modelling, and to discussions of epistemic uncertainty [16]. But to what extent are *explanations* affected? In practical applications, where the stakes are high, might model indeterminacy jeopardize the trustworthiness of

Figure 1: [Left] An aggregate performance metric like AUROC (black solid line) and a local explanation like a Shapley value (red dot-dash line) depend on a model's predictive function, $f(\boldsymbol{x})$, in different ways. Even if we see low variance in the aggregate performance across a set of models, we may see high variance in the individual local explanations. [Right] Visualizing how model indeterminacy may affect predictive multiplicity (epistemic uncertainty), local feature-based explanations, and recourse separately. Consider a set of approximately equivalent models, and a point in the input space, $\boldsymbol{x}$. The differences we may see in the model output at $\boldsymbol{x}$ are distinct from the differences we may see in their gradients (with respect to $\boldsymbol{x}$). The location of the nearest decision boundary may also change independently.

an automated decision system by undermining transparency efforts? We explore these questions in the context of risk assessment, i.e., insurance and credit applications, focusing on a well-established class of explanation techniques which use Shapley values [7; 18; 21], but our analysis applies to a broader set of systems and methods.

Contributions In this work, we introduce the notion of *explanatory multiplicity*, and study it both analytically and experimentally. We show how a set of models with very similar test-set performance may have large variations in their local explanations (Figure 1 left). We further show how predictive multiplicity, is not required for—or even indicative of—explanatory multiplicity (Figure 1 right). This is because in general, explanation methods are affected not just by the value of the predictive function at a point, but by its shape. We connect this analysis to an existing measure of model uncertainty: epistemic uncertainty [16]. Through experimentation, we explore explanatory multiplicity on three risk assessment datasets. We measure the changes in the decisions and corresponding explanations that users would receive if an automated decision system switched between approximately equivalent models. Our results indicate that model indeterminacy may have a substantial impact on explanations in practice, leading to inconsistent and even contradicting explanations.

2   Setup and related work

Problem setup We consider the situation whereby a user (applicant) is processed by a (partially) automated decision-making system, which ultimately accepts or rejects them. We assume the system is built around a machine learning model that has been trained on relevant historical data. The model makes a prediction which is used in the decision to accept or reject the applicant, possibly in conjunction with other eligibility criteria or human expertise. However, we are concerned with explaining the *model prediction* to the user. The explanation should be *local*, in the sense that it should be specific to the user's input data, rather than describing a *global* property of the model.

Assume we have a dataset of user-data outcome pairs, $D = \{\boldsymbol{x}_i, y_i\}_{i=1}^{N}$, with multi-dimensional input, $\boldsymbol{x} = (x_1, x_2, ..., x_M) \in \mathcal{X}$, and label $y \in \mathcal{Y}$. We denote the set of features (dimensions) of $\mathcal{X}$ as $\mathcal{M} = \{1, 2, ..., M\}$. Let $f(\boldsymbol{x})$ be a predictive function from a set of candidate functions (hypothesis space), $\mathcal{F}$, mapping the users' data, $\mathcal{X}$, to an output prediction score $z \in \mathcal{Z} \subseteq \mathbb{R}$ used in determining their acceptance. A typical scenario may be that $\mathcal{Y} = \{0, 1\}$, with $\mathcal{F}$ modelling the probability $p(y = 1|\boldsymbol{x})$, in which case $\mathcal{Z} = [0, 1]$. We suppose that the system produces *local*, vector-valued explanations, of the form $\boldsymbol{\phi} : (\mathcal{X}; \mathcal{F}) \mapsto \mathbb{R}^M$. This may be a *feature-importance* vector such as the gradient [3], $\nabla_x f$, or those generated by LIME [25] or SHAP [18]. Alternatively, this may be an *action* vector determined by an algorithmic recourse method [30], in which case we further require $(\boldsymbol{\phi}(\boldsymbol{x}; f) + \boldsymbol{x}) \in \mathcal{X}$. In either case, we let $\phi_k(\boldsymbol{x}; f)$ denote the component of the

Evidence (data) & Objectives

Automated Decision System

Figure 2: Model indeterminacy. The model instance that ends up in production is often not fully determined by the data, modelling objectives, and constraints. There is likely to be a set of different models showing nearly indistinguishable validation performance. This is known as the Rashomon effect. Even if the model class, hyperparameters, and optimization method are all specified, randomness in training may lead to substantial functional differences in the final model instance. This known as underspecification. Despite this potential for variability, most existing explanation techniques operate on a single model instance.

explanation relevant to input feature $k \in \mathcal{M}$. We assume there exists a dataset dependent *model selection criteria*, $S_D : \mathcal{F} \mapsto \{0, 1\}$, which filters $\mathcal{F}$ down to a set of *approximately equivalent models*, $\mathcal{R} = \{f \in \mathcal{F} : S_D(f) = 1\}$. For example, the selection criteria may consist of limiting $\mathcal{R}$ to only include models which score above a certain threshold on a aggregate performance metric.

We are interested in the set of possible explanations that could be given to a user across all approximately equivalent models, $\{\phi(\boldsymbol{x}; f) : f \in \mathcal{R}\}$. We are particularly concerned with situations whereby there exist $f, f' \in \mathcal{R}$ such that $\phi_k(\boldsymbol{x}; f) < 0 < \phi_k(\boldsymbol{x}; f')$, as this would constitute *contradicting* explanations. A user processed by f would be explained that feature k contributed positively to their assessment (or should be increased in the case of recourse), but had the same user been processed by f', they would have been explained that feature k contributed negatively to their assessment (or should be decreased).

2.1 Model indeterminacy: Underspecification and the Rashomon effect

Model indeterminacy arises when there are many *approximately equivalent* predictive functions within the hypothesis space. We say that two models are approximately equivalent if, in a given context, we cannot justify why we should use one instead of the other—both would satisfy our model selection criteria. We consider two types of model indeterminacy: *underspecification* as studied by D'Amour et al. [6], and the *Rashomon effect* as originally described by Breiman [4]. They arise in two slightly different commonplace contexts, but each may lead to sets of approximately equivalent models. The relationship between them is depicted in Figure 2. Underspecification arises when the model specification and training set are not enough to fully determine the model parameters. The training set, model class, hyperparameters, and optimization method are fixed, but the intentional use of randomness during training can lead to sets of approximately equivalent model parameters that effectively differ only because of the choice of random seeds. When the Rashomon effect is observed during model development, many models (possibly of different classes) show show approximately equal performance. Choosing which model among them to use in deployment becomes an arbitrary choice, thus this set of best models may be considered approximately equivalent. The Rashomon effect is more general than underspecification, as it does not require the model specification to be held constant. These types of model indeterminacy are very common in practical settings [6; 4].

2.2 Shapley value based explanations

We focus on the class of *local, feature-based* explanations that use Shapley values to attribute importance to the model's input features. It has been shown that explanations satisfy a set of desirable criteria if and only if they are computed using Shapley values [18]. This has put them in the spotlight for regulatory purposes [32; 20]. The core idea of using Shapley values for explanations is to explore all the possible subsets of features that the model could use to make a prediction, $\mathcal{S} \subset \mathcal{M}$, where $\mathcal{M}$ is the set of all input features, and to calculate the average marginal effect that including feature k into $\mathcal{S}$ has on that prediction. There are several related Shapley-based methods, which vary in how they include/exclude features from a prediction. We present a unifying formulation introduced by Merrick and Taly [21]. Let $\boldsymbol{u}(\boldsymbol{x}, \boldsymbol{r}, \mathcal{S})$ be a composite input function, which takes the values of $\boldsymbol{x}$ for all the features in $\mathcal{S} \subset \mathcal{M}$, and otherwise takes the values of $\boldsymbol{r}$, some other reference input. The

Shapley value for feature k given input $\boldsymbol{x}$ can then be written as

$$\phi_k(\boldsymbol{x}; f) = \frac{1}{M} \sum_{\mathcal{S} \subseteq \mathcal{M} \setminus \{k\}} \binom{M-1}{|\mathcal{S}|}^{-1} \mathbb{E}_{R \sim \mathcal{D}_{\mathrm{ref}}} \big[f\left(\boldsymbol{u}\left(\boldsymbol{x}, R, \mathcal{S} \cup \{k\}\right)\right) - f\left(\boldsymbol{u}\left(\boldsymbol{x}, R, \mathcal{S}\right)\right) \big]. \quad (1)$$

The sum is over all subsets of features (excluding feature k), and $|\mathcal{M}| = M$. Each term is the marginal change in the prediction when including feature k, divided by the binomial coefficient $M - 1$ choose $|S|$, and $\mathcal{D}_{\mathrm{ref}}$ is a sensible reference distribution. By simply varying this reference distribution, we can recover several different Shapley-based explanation methods [21], including those used in popular techniques like KernelSHAP [18] and Quantitative Input Influence [7].

2.3 Uncertainty quantification

Model indeterminacy can be examined through the lens of uncertainty quantification. A popular, Bayesian-inspired framework used in this pursuit subdivides uncertainty into two categories: aleatoric and epistemic [14]. Epistemic uncertainty aims to quantify the uncertainty in the model of the data generating process, and thus can be reduced by gathering more data. Aleatoric uncertainty aims to quantify the inherent (irreducible) noise in the data generating process. Kirsch et al. [16] propose that the uncertainty in the prediction at input $\boldsymbol{x}$ of a Bayesian model (with parameters $\boldsymbol{\theta}$) can be decomposed and categorized as

$$\underbrace{\mathbb{H}\left[Y | \boldsymbol{x}, \mathcal{D}\right]}_{\text{predictive}} = \underbrace{\mathbb{I}\left[Y; \boldsymbol{\theta} | \boldsymbol{x}, \mathcal{D}\right]}_{\text{epistemic}} + \underbrace{\mathbb{E}_{p(\boldsymbol{\theta} | \mathcal{D})}\left[\mathbb{H}\left[Y | \boldsymbol{x}, \boldsymbol{\theta}\right]\right]}_{\text{aleatoric}} \quad (2)$$

where $\mathbb{H}\left[Y | x, \mathcal{D}\right]$ is the predictive entropy given the training data $\mathcal{D}$. The mutual information term, $\mathbb{I}\left[Y; \theta | x, \mathcal{D}\right]$, which corresponds to the epistemic uncertainty, can be obtained by subtracting the aleatoric term from the predictive entropy. One can sample from $p(\boldsymbol{\theta} | \mathcal{D})$ by training model instances with different random seeds [23], effectively relying on underspecification to create functional differences between model instances. In this case, the epistemic uncertainty is related to predictive multiplicity because we have high epistemic uncertainty at $\boldsymbol{x}$ when the individual model instances confidently disagree (at $\boldsymbol{x}$).

2.4 Related work

Local explanation methods have already attracted some criticism with regards to their robustness. For example, Alvarez-Melis and Jaakkola [1] have noted a lack of robustness to small perturbations of the input being explained, while Lakkaraju and Bastani [17] show how this can be exploited to generate manipulative explanations. The effect of model indeterminacy on explanations has been explored in a philosophical sense by Hancox-Li [11]. Rudin [26] has argued against relying on post-hoc explanations of black box models in high stakes decision-making altogether. There has also been research into how the Rashomon effect can impact model interpretability. Semenova et al. [28] quantify the Rashomon effect, and differentiate it from existing ideas in the study of model complexity. Fisher et al. [9] consider the Rashomon set of "all well-performing models" within a specified class, and explore the extent to these models are necessarily dependent on any particular feature. They consider a *global* measure of feature importance called model reliance (MR), examining its range over the Rashomon set for each of the individual input features. Dong and Rudin [8] build on this work by characterizing the MR relationship *between* different features within the Rashomon set, using what they call the variable importance cloud (VIC). This set of work is highly relevant to our treatment of explanatory multiplicity, but it does not directly address the popular *local* explanation methods which explain the prediction for a *specific user*, i.e., a specific $\boldsymbol{x}$. These are currently the main candidates for explanations in practice. In contrast, global measures of feature importance like MR are tied to how important a feature is for a model's aggregate performance on a whole dataset.

3 Explanatory multiplicity

We now examine how model indeterminacy can bring about explanatory multiplicity. First consider the relative consistency of a performance metric, e.g., accuracy or AUROC, versus the value of a local explanation across a set of approximately equivalent models, $\{\phi(\boldsymbol{x}; f) : f \in \mathcal{S}\}$. Regardless of the exact methods employed, the local explanation $\phi(\boldsymbol{x}; f)$ will almost certainly depend on f differently

than the aggregate performance metric. Therefore, even if a set of approximately equivalent models show very similar aggregate performance, we should not expect consistency in their individual local explanations. The difference in dependency on f might transform a tight distribution over the performance metric into a wide, possibly multi-modal, distribution over the Shapley value for a feature, $\phi_k(\boldsymbol{x}; f)$. This is illustrated in Figure 1 (left).

Now consider how the form of the predictive function may vary in the region around some input $\boldsymbol{x}$ across the approximately equivalent models. This is illustrated in Figure 1 (right). We focus on how three local characteristics of the predictive function may vary within the set of approximately equivalent models. First, there can be variance in the value of the predictive function $f(\boldsymbol{x})$. Therefore, we may see considerable disagreement at any individual point in the input space. Strong disagreement would drive high epistemic uncertainty, per Equation 2. Second, there can be variance in the gradient, $\nabla_{\boldsymbol{x}} f(\boldsymbol{x})$, (or the discrete equivalent to this quantity if f is not differentiable). The gradient is an indicator of local feature importance. It is used directly in simple explanation techniques [3], and it is closely connected to several others [27], including Shapley-value based methods in linear models. Finally, there can be variance in the position of the nearest decision boundary. This has implications for counterfactual explanations [31] and algorithmic recourse [30]. It is possible that the nearest decision boundary not only moves, but entirely disappears if we switch to another approximately equivalent model. This could nullify the validity of any recourse provided to a user. Importantly, these three characteristics may vary independently. Therefore, while epistemic uncertainty may be a useful construct for indicating when we should expect to see variance in predictions, it is not indicative of when explanations will vary. As we show, our experimental results support this.

Illustrative example To illustrate these effects, we train 200 neural networks (MLPs) on a synthetic dataset ($\boldsymbol{x} \in \mathbb{R}^2$, $y \in \{0, 1\}$). These model instances differ only because of differences in the random seeds used in training. We limit our consideration to the 3% highest-performing model instances, selecting those ranging between 93.3% and 93.6% validation accuracy. This constitutes a set of approximately equivalent models. Because the models differ only in the random seeds, underspecification is the source of model indeterminacy here. We plot the models' output (softmax probability) over a region of the input space in Figure 10 in Appendix E. Their functional forms may change considerably from one model instance to the next, in some cases, causing the nearest counterfactual boundary to shift or even disappear. A single model instance along with the (iid) test set is shown in Figure 3 (left). The predictive multiplicity at each point in that region of the input space is calculated using the epistemic uncertainty in the set of approximately equivalent models (Equation 2 explained below) and is shown in Figure 3 (center). Notice it increases as we move toward regions of the input space for which we have less data. Finally, we compute the mean pairwise cosine similarity of the gradients (with respect to $\boldsymbol{x}$) between models over the same region of the input space, shown in Figure 3 (right). We see that predictive multiplicity is a poor indicator of the similarity of the gradients across approximately equivalent models. For instance, consider the point at the orange star. We have low epistemic uncertainty (corresponding to inter-model agreement in predictions), yet the gradients across the models at this point are very dissimilar (orange arrows).

Analysis in a linear setting In a linear model class, it is possible to determine the precise conditions under which model indeterminacy can lead to contradicting explanations. We present a brief summary of this analysis here, and refer the reader to Appendix C for more details. Consider the case where $\boldsymbol{x} \in \mathbb{R}^M$, $y \in \mathbb{R}$, and $\mathcal{F}$ is the set of ridge regression models of the form $f(\boldsymbol{x}; \boldsymbol{\theta}) = \boldsymbol{\theta}^T \boldsymbol{x}$, with square error loss and ℓ_2 penalty $\alpha > 0$. The Rashomon set of all $\boldsymbol{\theta}$ which parameterize models within ε of the optimal loss, is an ellipsoidal region, Θ_ε, centered at the OLS solution, $\boldsymbol{\theta}^*$. We are interested in circumstances whereby the sign of a Shapley value reverses within this Rashomon set, i.e., $\exists\, \boldsymbol{\theta}, \boldsymbol{\theta}' \in \Theta_\varepsilon$ s.t. $\phi_k(\boldsymbol{x}; \boldsymbol{\theta}) > 0 > \phi_k(\boldsymbol{x}; \boldsymbol{\theta}')$.

It can be shown that the Shapley value of feature k in this ridge regression setting is $\phi_k(\boldsymbol{x}; \boldsymbol{\theta}) = \theta_k x_k$. Since $\boldsymbol{x}$ is fixed for a user, ϕ_k changes sign if and only if θ_k does. In the simple case where the features of $\boldsymbol{x}$ are independent, the ellipsoidal region Θ_ε is axis-aligned. We show that θ_k is bounded in an interval centered at θ_k^*, having width $2(\varepsilon/(\frac{1}{N} \sum_n x_{k,n}^2 + \alpha))^{1/2}$. For a fixed ε relaxation from optimality and regularization coefficient α, the width of this interval decreases with the variance of the feature k. So ϕ_k is a candidate for sign reversal if x_k is a low variance independent feature, and θ_k^* is near zero.

Consider now if features j and k are correlated, with $\mathrm{Cov}(x_j, x_k) > 0$, but all other features are independent. The ellipsoidal region is aligned for all axes $i \notin \{j, k\}$, but in the j, k plane, the

output probability p(y=1|x)   log epistemic uncertainty   gradient cosine similarity

Figure 3: [Left]: Softmax probability of an MLP over a region of the input space. The test set is depicted as purple circles and yellow Xs. [Center]: Epistemic uncertainty over the same region of the input space is computed using a set of approximately equivalent model instances arising from the same training pipeline. [Right]: Mean pairwise cosine similarity of the gradients (w.r.t. the input) between models over the same region of the input space. The orange arrows are the gradients for (a subset of) the individual models at the point indicated by the orange star (left and center).

cross-sectional ellipse is rotated. In this case, we show that θ_k is also bounded in an interval centered at θ_k^*. If we fix ε, α, and the variance of features j and k, we show that the width of this interval increases with $\mathrm{Cov}(x_j, x_k)$. Intuitively, this tells us that problems for which the input features are strongly correlated are more prone to contradicting explanatory multiplicity. However, in complex hypothesis spaces, it is considerably more difficult to analyse explanatory multiplicity theoretically. We instead explore it through experimentation.

4 Experiments

To explore the extent to which model indeterminacy may impact the consistency of explanations in a practical setting, we conduct a series of experiments. We use three different (binary) risk assessment datasets (all available on Kaggle): UCI Credit Card [33], Give Me Some Credit, and Porto Seguro's Safe Driver Prediction. Their details can be found in Appendix B.1. In each case, we let $y = 1$ indicate the "bad" outcome: missed payment, serious delinquency, and insurance claim filed, respectively. We fit predictive models to each of these datasets, and consider their use in an automated decision system that filters out applicants (users) who pose an unacceptably high risk of a bad outcome. We then measure how the predictions and corresponding explanations are affected by the Rashomon effect and underspecification. Our experiments were conducted on a GPU accelerated computing cluster. ML models were written in PyTorch [24], and the analysis used NumPy [12] and Matplotlib [13] [1][2].

Preprocessing and model selection   We first split each dataset into a development and a holdout set (70 / 30), and apply one-hot encoding and standard scaling. We then run a model selection process with three model classes: logistic regression (LR), multi-layer perceptron (MLP), and a tabular ResNet (TRN) recently proposed by Gorishniy et al. [10]. We sweep through a range of hyperparameter settings, trying a total of 408 model-hyperparameter configurations per dataset. For each configuration, we pick a random seed and use it to control a shuffled split of the development dataset into train and validation sets (70 / 30), as well as to control the randomness used in training (optimization). We fit the models using Adam [15] with a patience-based stopping criteria on the validation set. We also up-weight the rare class, creating a balanced loss. We repeat this process with 3 random seeds per configuration, obtaining a total of 1224 model instances per dataset.

Forming sets of approximately equivalent models   To explore the effect of underspecification, we identify the best model-hyperparameter configuration and generate many approximately equivalent model instances from it. We refer to these as *underspecification sets*, and use the area under the AUROC on the validation sets to determined the best model-hyperparameter configuration for each dataset. We then train 100 models instances using that configuration. In the final training, we fix the number of epochs, and use the full development dataset for each. Thus the *only* source of variation between model instances is the random seed controlling initialization and mini-batch order. To

---

[1]These packages are publicly available under BSD-style licenses.

[2]Experimental source code will be made publicly available on GitHub prior to publication.

explore the impact of the Rashomon effect, we simply skim off the top 3% of model instances (36 instances) from the hyperparameter sweep, ranked according to their AUROC performance on their validation sets. We refer to these as *Rashomon effect sets* (as they stray slightly from the definition of a "Rashomon set" by Semenova et al. [28]). These sets include model instances from different model-hyperparameter configurations, and different controlling random seeds. After forming a set of either type, we use the holdout data to ensure that none of the model instances show unusually low performance out-of-sample.

Computing explanations   For each dataset, we consider a subset of 1000 instances from the holdout set. We generate Shapley value explanations on these points for each of the approximately equivalent models. Notice that in Equation 1 there is an expectation over the reference distribution, $R \sim \mathcal{D}$, as well as a sum over all subsets of features in $\mathcal{M}$ which grows as $\mathcal{O}(|\mathcal{M}|!)$. In practice this sum must be approximated for inputs with even a modest number of features, and the expectation is converted to an empirical mean. Fortunately, there has been considerable effort put into developing estimators for Shapley values. In this work we use a simple antithetic sampling approach described in [22]. Importantly, when comparing Shapley-based explanations across models we are careful to use precisely the same set of samples, thereby ensuring that if two models agreed pointwise everywhere in their domains, their explanations would be identical. To limit the already significant computation involved, we use a simple baseline as the distribution, $\mathcal{D}$, in Equation 1. We use a point mass at the mean input, $\mathbb{E}[x]$. In the language of Merrick and Taly [21], this amounts to considering a "single-reference game" using the mean input, thus the explanations contrast the user with the "average applicant".

5   Results

Here we present the results of our experiments. Note that our figures focus on underspecification and the UCI Credit Card dataset; the corresponding figures for the Rashomon effect and other datasets are presented in Appendix D. We tabulate the results of the hyperparameter sweep and set formation in Table 2, in Appendix B.2. The probability that two approximately equivalent models disagree on a user acceptance decision is a function of the decision threshold (risk appetite). With decision thresholds set to a 50% user acceptance rate, disagreement ranges between 4.35–12.7% across our experimental setups. We report more details on the consistency of decisions across a range of user acceptance rates in Appendix D.1.

To quantify the consistency of explanations we consider the top-k (in magnitude) Shapley values explaining a user's predicted risk (of a bad outcome). These correspond to the features which are most significant to the prediction. It is recommended to limit feature-based explanations to a subset of the most important features [25], thus these would be what is shown to the user. If they are positive-valued, they indicate the feature adds to the applicant's predicted risk. If they are negative-valued, they indicate the feature reduces that risk.

Figure 4: Consistency of explanations. We compare the top-k Shapley values across approximately equivalent models for 1000 users in the hold-out set. [Left] Histogram over the probability of inter-model explanation agreement for each user. [Right] Histogram over the probability of inter-model contradiction (sign change) in the top-k Shapley values for each user. [Dataset: UCI Credit Card, Source of indeterminacy: underspecification]

Table 1: Consistency of explanations

	UCI Credit Card		Give Me Credit		P.S.'s Safe Driver	
	top-3	top-5	top-3	top-5	top-3	top-5
Rashomon effect						
Agree (%)	16.48	7.22	33.12	29.91	21.56	7.94
Contradict (%)	46.64	62.73	6.63	19.54	19.21	34.22
Underspecification						
Agree (%)	27.85	11.71	45.92	36.68	51.90	32.26
Contradict (%)	7.96	20.21	3.40	13.52	0.82	2.50

Agreement   We consider the probability that a user is shown the same set of top-k features if the model were switched to another approximately equivalent model. Within the top-k, we require that the sign of the Shapley values be the same, but not their numerical values or relative order. For example, suppose model A has Shapley values $\{\phi_1 : 0.4, \phi_2 : 0.7, \phi_3 : -0.9, \phi_4 : -0.1\}$, but model B has $\{\phi_1 : -0.5, \phi_2 : 0.8, \phi_3 : -0.7, \phi_4 : 0.3\}$. Their top-1 Shapley values disagree: $\{\phi_3\}$ vs. $\{\phi_2\}$, their top-2 Shapley values agree: $\{\phi_2, \phi_3\}$, but their top-3 Shapley values disagree because ϕ_1 does not have the same sign in both models. The results are plotted in a histogram in Figure 4 (left). They are also averaged over 1000 users and reported in the first row of Table 1. In general, we see low levels of agreement. If a user were shown explanations of a prediction they received from two approximately equivalent models, the probability that the top-3 Shapley values agree is less than 52% in all our experimental settings.

Contradiction   We are most concerned about contradicting explanations, as these can be confusing or even harmful for a user. We consider the probability that at least one of the top-k Shapley values would change sign if the model were to be switched to an approximately equivalent one, i.e., with model A, the user is explained that the value of feature-j is a top contributor to the predicted risk, but with approximately equivalent model B, that same value of feature-j is said to reduce their predicted risk. The results are plotted in a histogram in Figure 4 (right). We also average them over 1000 user explanations and report them in the second row of Table 1. The odds of a contradiction vary considerably across the experimental settings. They are remarkably high in some of the Rashomon sets, but roughly an order of magnitude lower in the underspecification sets. Nonetheless, the odds of a contradiction in the top-5 Shapley values is over 13% in five-sixths of our experimental settings, potentially alarming levels in a real-world setting.

Visualizing (in)consistency   Explanations are often reported in a visual form. We explore the visual consistency of the explanations across approximately equivalent models. To do so, we sort users by the mean overlap in their top-5 Shapley values across pairs of approximately equivalent models. High overlap means the models tend to agree. We select a user, then we plot the explanation for each model within an approximately equivalent set as a separate trace. We limit the plot to the features that are in the top-5 for at least one model. An example of such a plot for a (randomly selected) user in the 10th percentile of explanation agreement can be seen in Figure 5 (left). For four of the features, we see contradictions in the explanations across models. It would be explained to the user that this feature was among the top-5 reasons for a decision, but had an approximately equivalent model been used instead, it would be explained that the same feature was having the *opposite* effect on their decision.

Predictive multiplicity vs. explanatory multiplicity   We explore the relationship between predictive multiplicity and explanatory multiplicity. We observe no significant relationship between these two multiplicities across users. The extent to which the approximately equivalent models agree in their predictions for a user is not indicative of the extent to which the explanations agree. There are users with low explanatory agreement and high predictive agreement, and vice versa. To illustrate this, we plot the mean overlap in the top-5 Shapley values vs. the epistemic uncertainty in the associated predictions (computed via Equation 2) for 1000 users. See Figure 5 (right). We may wish to translate explanatory multiplicity into some statement about the uncertainty in an explanation. However, our results suggest that the uncertainty in an explanation needs to be considered differently than the uncertainty in a prediction. Current estimates of epistemic uncertainty do not appear to capture the type of model uncertainty that is relevant for feature-based explanation.

Figure 5: [Left and Center] Visualizing inconsistencies in explanations. Each trace corresponds to one model's explanation: the Shapley values for a subset of the most important features. Notice that "age", "pay_2", "bill_amt3", and "pay_amt4" all cross the 0 line. For some models they would be presented among the top-5 reasons that a decision was made, yet for other approximately equivalent models, they would be explained as having the *opposite* effect on that decision. In the center, we show the models' softmax outputs. The models tend to agree in their predictions, but not in their explanations. [Right] Predictive vs. explanatory multiplicity. Here we illustrate the relationship between predictive multiplicity and explanatory multiplicity. We plot the mean overlap in the top-5 Shapley values vs. the (log) epistemic uncertainty in the predictions for 1000 users in the holdout set. We see no significant correlation. [Dataset: UCI Credit Card, Source of indeterminacy: underspecification]

Analysis Our results indicate that model indeterminacy can lead to substantial inconsistencies in the local explanations of approximately equivalent models, even when models only differ because of underspecification. On the one hand, this may be viewed as a consequence of high fidelity explanations, which ought to show a sensitivity to the fluctuations of the predictive functions. However, when we consider providing these explanations to a user, whether as a justification for a decision, or as information they can act on, the implications are concerning. Without some kind of guarantee about how long a particular model instance will remain in use, the explanations may be of very little value, or even be detrimental to the users. (Additional results in Appendix D.)

6 Discussion

There are notable societal implications to this work. Consider being told that you were denied a loan because you had too many lines of credit, only to learn that—under a trivially different model—you could have been denied on the basis of having too few. How would this affect your trust in the decision-making system? Explanation techniques that use Shapley values have been rigorously motivated, and may represent a substantial operational cost in practice, requiring orders of magnitude more compute than just making a prediction. It is sensible to want them to be robust. We should at least communicate the limits of their robustness to the user, so they understand exactly what is being explained, i.e., we should be explicit about the *scope* of the explanation. We elaborate on this discussion in Appendix A.

There is much to explore in future work. Our theoretical analysis is currently limited to a simple linear class of models. Our experiments are limited to just one form of Shapley value explanations. It would be important to explore the empirical effects of model indeterminacy on other explanation methods including recourse. Ensembles and averaging explanations may serve to increase robustness against the fragility we point out. It may also be helpful to put the effects of model indeterminacy into perspective by comparing them to human decision-makers. Human decisions, and the explanations of those decisions, are also liable to fluctuate arbitrarily. However, our results remind us that just because a decision or explanation was produced by a "data driven" model, does not mean that they are fully determined by the data. We hope our work inspires a focused research effort into developing explanation techniques that are more robust to the trivial or arbitrary model choices that occur in practice.

References

[1] D. Alvarez-Melis and T. S. Jaakkola. On the Robustness of Interpretability Methods. *arXiv preprint arXiv:1806.08049*, 6 2018. URL https://arxiv.org/abs/1806.08049.

[2] P. P. Angelov, E. A. Soares, R. Jiang, N. I. Arnold, and P. M. Atkinson. Explainable artificial intelligence: an analytical review. *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery*, 11(5), 2021. ISSN 19424795. doi: 10.1002/widm.1424.

[3] D. Baehrens, T. Schroeter, S. Harmeling, M. Kawanabe, K. Hansen, and K. R. Müller. How to explain individual classification decisions. *Journal of Machine Learning Research*, 11, 2010. ISSN 15324435.

[4] L. Breiman. Statistical modeling: The two cultures. *Statistical Science*, 16(3):199–215, 2001. ISSN 08834237. doi: 10.1214/ss/1009213726.

[5] L. Breiman. Random forests. *Machine Learning*, 45(1):5–32, 2001. ISSN 08856125. doi: 10.1023/A:1010933404324.

[6] A. D'Amour, K. Heller, D. Moldovan, B. Adlam, B. Alipanahi, A. Beutel, C. Chen, J. Deaton, J. Eisenstein, M. D. Hoffman, F. Hormozdiari, N. Houlsby, S. Hou, G. Jerfel, A. Karthike-salingam, M. Lucic, Y. Ma, C. McLean, D. Mincu, A. Mitani, A. Montanari, Z. Nado, V. Natara-jan, C. Nielson, T. F. Osborne, R. Raman, K. Ramasamy, R. Sayres, J. Schrouf, M. Seneviratne, S. Sequeira, H. Suresh, V. Veitch, M. Vladymyrov, X. Wang, K. Webster, S. Yadlowsky, T. Yun, X. Zhai, and D. Sculley. Underspecification Presents Challenges for Credibility in Modern Machine Learning. 2020. URL http://arxiv.org/abs/2011.03395.

[7] A. Datta, S. Sen, and Y. Zick. Algorithmic Transparency via Quantitative Input Influence: Theory and Experiments with Learning Systems BT - 2016 IEEE Symposium on Security and Privacy, SP 2016, May 23, 2016 - May 25, 2016. *Security and Privacy (SP), 2016 IEEE Symposium on*, pages 598–617, 2016. URL https://www.andrew.cmu.edu/user/danupam/datta-sen-zick-oakland16.pdf%0Ahttp://dx.doi.org/10.1109/SP.2016.42.

[8] J. Dong and C. Rudin. Exploring the cloud of variable importance for the set of all good models. *Nature Machine Intelligence*, 2(12):810–824, 2020. ISSN 25225839. doi: 10.1038/s42256-020-00264-0. URL http://dx.doi.org/10.1038/s42256-020-00264-0.

[9] A. Fisher, C. Rudin, and F. Dominici. All models are wrong, but many are useful: Learning a variable's importance by studying an entire class of prediction models simultaneously. *Journal of Machine Learning Research*, 20:1–81, 2019. ISSN 15337928.

[10] Y. Gorishniy, I. Rubachev, V. Khrulkov, and A. Babenko. Revisiting deep learning models for tabular data. *Advances in Neural Information Processing Systems*, 34, 2021. URL https://arxiv.org/abs/2106.11959.

[11] L. Hancox-Li. Robustness in machine learning explanations: Does it matter? In *FAT* 2020 - Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency*, pages 640–647. Association for Computing Machinery, Inc, 1 2020. ISBN 9781450369367. doi: 10.1145/3351095.3372836.

[12] C. R. Harris, K. J. Millman, S. J. van der Walt, R. Gommers, P. Virtanen, D. Cournapeau, E. Wieser, J. Taylor, S. Berg, N. J. Smith, R. Kern, M. Picus, S. Hoyer, M. H. van Kerkwijk, M. Brett, A. Haldane, J. F. del Río, M. Wiebe, P. Peterson, P. Gérard-Marchant, K. Sheppard, T. Reddy, W. Weckesser, H. Abbasi, C. Gohlke, and T. E. Oliphant. Array programming with NumPy, 2020. ISSN 14764687.

[13] J. D. Hunter. Matplotlib: A 2D graphics environment. *Computing in Science and Engineering*, 9(3), 2007. ISSN 15219615. doi: 10.1109/MCSE.2007.55.

[14] A. Kendall and Y. Gal. What Uncertainties Do We Need in Bayesian Deep Learning for Computer Vision? In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/2650d6089a6d640c5e85b2b88265dc2b-Paper.pdf.

[15] D. P. Kingma and J. L. Ba. Adam: A method for stochastic optimization. In *3rd International Conference on Learning Representations, ICLR 2015 - Conference Track Proceedings*, 2015.

[16] A. Kirsch, J. van Amersfoort, and Y. Gal. BatchBALD: Efficient and Diverse Batch Acqui-sition for Deep Bayesian Active Learning. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/95323660ed2124450caaac2c46b5ed90-Paper.pdf.

[17] H. Lakkaraju and O. Bastani. "how do i fool you?": Manipulating user trust via misleading black box explanations. In *AIES 2020 - Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, 2020. doi: 10.1145/3375627.3375833.

[18] S. M. Lundberg and S. I. Lee. A unified approach to interpreting model predictions. *Advances in Neural Information Processing Systems*, 2017-Decem(Section 2):4766–4775, 2017. ISSN 10495258.

[19] C. T. Marx, F. D. P. Calmon, and B. Ustun. Predictive multiplicity in classification. In *37th International Conference on Machine Learning, ICML 2020*, volume PartF168147-9, 2020. URL https://arxiv.org/abs/1909.06677.

[20] MAS. Veritas Document 3C FEAT Transparency Principles Assessment Methodol-ogy. Technical report, Monetary Authority of Singapore (MAS), 2 2022. URL https://www.mas.gov.sg/-/media/MAS-Media-Library/news/media-releases/2022/Veritas-Document-3C---FEAT-Transparency-Principles-Assessment-Methodology.pdf.

[21] L. Merrick and A. Taly. The Explanation Game: Explaining Machine Learning Models Using Shapley Values. In *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, volume 12279 LNCS, pages 17–38, 2020. ISBN 9783030573201. doi: 10.1007/978-3-030-57321-8{_}2.

[22] R. Mitchell, J. Cooper, E. Frank, and G. Holmes. Sampling Permutations for Shapley Value Estimation. *Journal of Machine Learning Research*, 23(43):1–46, 2022. URL http://jmlr.org/papers/v23/21-0439.html.

[23] J. Mukhoti, A. Kirsch, J. van Amersfoort, P. H. S. Torr, and Y. Gal. Deterministic Neural Networks with Inductive Biases Capture Epistemic and Aleatoric Uncertainty. (iD), 2021. URL http://arxiv.org/abs/2102.11582.

[24] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, A. Desmaison, A. Köpf, E. Yang, Z. DeVito, M. Raison, A. Tejani, S. Chilamkurthy, B. Steiner, L. Fang, J. Bai, and S. Chintala. PyTorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

[25] M. T. Ribeiro, S. Singh, and C. Guestrin. "Why should i trust you?" Explaining the predictions of any classifier. *Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 13-17-Augu:1135–1144, 2016. doi: 10.1145/2939672.2939778.

[26] C. Rudin. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence*, 1(5):206–215, 2019. ISSN 25225839. doi: 10.1038/s42256-019-0048-x. URL http://dx.doi.org/10.1038/s42256-019-0048-x.

[27] S. Samuel, V. Kamakshi, N. Lodhi, and N. Krishnan. Evaluation of Saliency-based Explainability Method, 2 2021. URL https://ui.adsabs.harvard.edu/abs/2021arXiv210612773Z/abstract.

[28] L. Semenova, C. Rudin, and R. Parr. A study in Rashomon curves and volumes: A new perspective on generalization and model simplicity in machine learning. pages 1–64, 2019. URL http://arxiv.org/abs/1908.01755.

[29] A. Smith. Using Artificial Intelligence and Algorithms, 4 2020. URL https://www.ftc.gov/news-events/blogs/business-blog/2020/04/using-artificial-intelligence-algorithms.

[30] B. Ustun, A. Spangher, and Y. Liu. Actionable recourse in linear classification. *FAT* 2019 - Proceedings of the 2019 Conference on Fairness, Accountability, and Transparency*, pages 10–19, 2019. doi: 10.1145/3287560.3287566.

[31] S. Wachter, B. Mittelstadt, and C. Russell. Counterfactual Explanations Without Opening the Black Box: Automated Decisions and the GDPR. *Harvard Journal of Law and Technology*, 31 (2):842–887, 2018. ISSN 1556-5068. doi: 10.2139/ssrn.3063289.

[32] W. Wang, C. Lesner, A. Ran, M. Rukonic, J. Xue, and E. Shiu. Using small business banking data for explainable credit risk scoring. *AAAI 2020 - 34th AAAI Conference on Artificial Intelligence*, pages 13396–13401, 2020. ISSN 2159-5399. doi: 10.1609/aaai.v34i08.7055.

[33] I. C. Yeh and C. h. Lien. The comparisons of data mining techniques for the predictive accuracy of probability of default of credit card clients. *Expert Systems with Applications*, 36(2 PART 1), 2009. ISSN 09574174. doi: 10.1016/j.eswa.2007.12.020.