"Excuse me, may I say something..." CoLabScience, A Proactive AI Assistant for Biomedical Discovery and LLM-Expert Collaborations

Abstract

The integration of Large Language Models (LLMs) into scientific workflows presents exciting opportunities to accelerate biomedical discovery. However, the reactive nature of LLMs, which respond only when prompted, limits their effectiveness in collaborative settings that demand foresight and autonomous engagement. In this study, we introduce CoLabScience, a proactive LLM assistant designed to enhance biomedical collaboration between AI systems and human experts through timely, context-aware interventions. At the core of our method is PULI (*Positive-Unlabeled Learning-to-Intervene*), a novel framework trained with a reinforcement learning objective to determine when and how to intervene in streaming scientific discussions, by leveraging the team's project proposal and long- and short-term conversational memory. To support this work, we introduce BSDD (*Biomedical Streaming Dialogue Dataset*), a new benchmark of simulated research discussion dialogues with intervention points derived from PubMed articles. Experimental results show that PULI significantly outperforms existing baselines in both intervention precision and collaborative task utility, highlighting the potential of proactive LLMs as intelligent scientific assistants.[1]

1 Introduction

Recent developments in large language models (LLMs) have fostered advancements in scientific research, enabling accelerated discovery in biomedical fields (Luo et al., 2022; Ma et al., 2024; Jin et al., 2025). In particular, existing work has explored their potential across tasks such as drug repurposing, disease diagnosis, and clinical question answering (Qi et al., 2024; Zhao et al., 2023; Lu et al., 2024c). Despite these successes, current models primarily function in a reactive paradigm

Figure 1: Comparison of Reactive and Proactive LLMs in Biomedical Collaboration. Traditional reactive LLMs (left) respond only after being prompted, while proactive LLMs (right) monitor ongoing discussions, identify opportunities to contribute domain-relevant insights, and intervene with timely and context-aware suggestions without explicit prompting.

(Shankar and Parameswaran, 2024; Liao et al., 2023; Lu et al., 2024c), responding solely upon explicit prompts from researchers. This interaction mode significantly restricts their effectiveness in collaborative settings, where the absence of proactive interventions can lead to missed critical insights and opportunities (Yang et al., 2025b). In response to these limitations, we propose that LLMs supporting biomedical research should evolve toward proactive engagement: continuously tracking ongoing discussions, understanding emerging contexts, and autonomously identifying appropriate moments for contribution—integrating into the team as an active team member rather than remaining a passive tool. For instance, as illustrated in Figure 1, a traditional reactive LLM (Hassouna et al., 2024; Zhou et al., 2024) responds passively only after being explicitly prompted by the Clinical Physician, whereas a proactive LLM tracks the discussion, identifies timely opportunities to contribute PTEN-relevant insights, and initiates suggestions that facilitate scientific progress without

---

[1] The code, data, and project demo video are provided in the supplementary material and will be made publicly available upon acceptance.

waiting for direct queries.

Motivated by the need for proactive engagement, we present CoLabScience, a novel AI assistant that transforms LLMs from reactive tools to proactive collaborators in biomedical research. At its core lies PULI (*Positive-Unlabeled Learning-to-Intervene*), a framework trained with reinforcement learning to determine when and how to intervene during scientific discussions. To train this model, we constructed BSDD (*Biomedical Streaming Dialogue Dataset*), a collection of simulated scientific dialogues characterized by multiple research roles (e.g., Pharmacologist, Clinical Physician), generated by LLMs with content grounded in PubMed literature (Sayers et al., 2024). To ensure the reliability of LLM-derived labels and mitigate hallucination risk (Huang et al., 2025; Sriramanan et al., 2024), we adopt a sparse labeling strategy in which only the most valuable intervention points are labeled as positive, while all others remain unlabeled (Luo et al., 2021; Kiryo et al., 2017).

By leveraging CoLabScience's coordinator to identify reliable negative interventions from the positive-unlabeled (PU) data, we employ a two-tier approach: training a small *Observer* LLM with Group Relative Policy Optimization (GRPO) (Shao et al., 2024) to determine when to intervene and fine-tuning a large-scale *Presenter* LLM with supervised learning to generate appropriate intervention content. This architecture enables real-time dialogue monitoring via the efficient Observer model, invoking the computationally expensive Presenter model only when an intervention is needed. Reward signals from both models are integrated to train the reinforcement learning coordinator, enabling an end-to-end training loop. By incorporating the project proposal (i.e., project goals, datasets, and background knowledge) and dual-scale conversational memory, in which long-term memory retains critical prior insights and short-term memory captures the evolving conversational context (Hatalis et al., 2023; Zhong et al., 2024), CoLabScience proactively delivers scientifically grounded interventions without requiring explicit prompting.

Our contributions in this paper are threefold and can be summarized as follows:

• We propose CoLabScience, a proactive LLM assistant that supports efficient biomedical research collaboration through context-aware interventions. Unlike reactive LLMs, CoLabScience autonomously determines when and how to intervene during ongoing research discussions by leveraging project context and conversational history.

• We introduce BSDD, a new open benchmark consisting of simulated biomedical research dialogues grounded in PubMed articles and annotated with proactive intervention labels. BSDD provides a valuable resource for training and evaluating future proactive scientific assistants, advancing research in this emerging area.

• We empirically validate CoLabScience's effectiveness through both simulation-based evaluation and human evaluation. The results demonstrate the model's strong generalization ability and robustness across a range of LLM backbones.

2 Related Work

Large Language Models as Scientific Assistants Recent advances in LLMs have shown promise in biomedical research through protein structure prediction, antibiotic discovery, and drug repurposing (Wong et al., 2024; Zambaldi et al., 2024; Jumper et al., 2021; Swanson et al., 2024; Gottweis et al., 2025). Beyond the biomedical domain, systems like Agent Laboratory and AI Scientist (Schmidgall et al., 2025; Lu et al., 2024a) automate research pipelines from hypothesis generation to reporting, while Agentic Reasoning (Wu et al., 2025) enhances multi-step reasoning. However, these approaches operate reactively by responding to queries or following predetermined workflows rather than proactively identifying opportunities to contribute during ongoing discussions. CoLabScience addresses this gap through context-aware intervention mechanisms that enable autonomous engagement in dynamic scientific workflows.

Proactive Capabilities in Large Language Models Recent work explores LLM proactivity through structured prompting, including initiative-taking in collaboration (Zhang et al., 2024a; Lu et al., 2024b), clarification-seeking behaviors (Zhang et al., 2024b; Qian et al., 2024; Liu et al., 2024; Pang et al., 2025; Li et al., 2024), and requesting user support in complex tasks (Wu et al., 2024). VideoLLM-Online (Chen et al., 2024) extends this to multimodal streaming, training models to determine optimal narration timing. However, these approaches rely on hand-crafted prompts and fixed logic, limiting adaptive intervention. In contrast, we introduce a trainable reinforcement learning mechanism that enables context-aware, timing-sensitive proactive decision-making.

3 Methodology

3.1 Preliminary Definitions

We formalize the proactive intervention task based on multi-round scientific dialogues. Let $\mathcal{D} = \{D^1, D^2, \ldots, D^M\}$ denote a collection of independent multi-round dialogues. Each dialogue $D^i = \{d_1^i, d_2^i, \ldots, d_{N_i}^i\}$ consists of N_i rounds generated from a fixed project proposal C^i, which defines the research goal, background knowledge, and relevant datasets. We aggregate all dialogue rounds into a positive-unlabeled (PU) intervention training set:

$$\{d_1, d_2, \ldots, d_N\},$$

where $N = \sum_{i=1}^{M} N_i$ is the total number of candidate rounds. The PU training set contains u unlabeled rounds $U = \{d_1, \ldots, d_u\}$ with unknown intervention necessity, and $(N - u)$ labeled positive rounds $P = \{d_{u+1}, \ldots, d_N\}$.

Based on the PU dataset, our task is to jointly learn (1) when to intervene, using a Observer $\mathcal{H}_\phi$, and (2) how to intervene, using a Presenter $\mathcal{G}_\psi$. To facilitate the training of both LLMs, we introduce a reinforcement learning framework where a coordinator model $\mathcal{F}_\theta$ identifies potential positive and negative samples from the unlabeled data. To enhance understanding and clarity, a summary of notations is provided in Table 1.

Notations	Descriptions
$\mathcal{D} = \{D^1, \ldots, D^M\}$	Set of M multi-round dialogues.
$D^i = \{d_1^i, \ldots, d_{N_i}^i\}$	i-th dialogue with N_i rounds.
C^i	Project proposal context of D^i (goal, background, datasets).
$U = \{d_1, \ldots, d_u\}$	Unlabeled intervention rounds.
$P = \{d_{u+1}, \ldots, d_N\}$	Positive intervention rounds.
d_n	n-th unlabeled intervention round.
$C(d_n)$	Project proposal associated with the original dialogue of d_n.
$\mathcal{M}^L(d_n)$	Long-term memory of d_n.
$\mathcal{M}^S(d_n)$	Short-term memory of d_n.
$\mathcal{M}(d_n)$	Overall contextualized memory.
$\mathcal{F}_\theta$	Coordinator model.
$\mathcal{H}_\phi$	Observer LLM for intervention timing.
$\mathcal{G}_\psi$	Presenter LLM for intervention responses.

Table 1: Notations.

3.2 PULI Mechanism

In this section, we introduce the PULI mechanism, which jointly learns when and how to intervene in multi-round scientific dialogues using a positive-unlabeled dataset. An overview of the framework is shown in Figure 2.

Figure 2: Illustration of PULI framework. The coordinator decides whether to intervene or remain silent for each unlabeled dialogue round. Silent rounds are used as negative samples to update the Observer through GRPO training to learn intervention timing, while intervention rounds augment positive data to refine the Presenter to generate appropriate intervention content. The Observer and Presenter collaboratively provide rewards to optimize the coordinator in an end-to-end training process.

3.2.1 Multi-Round Dialogue State

For each unlabeled intervention round $d_n \in U$ at local dialogue step t, we construct a contextualized memory $\mathcal{M}_t(d_n)$ comprising three components: (1) the project proposal $C(d_n)$, specifying the research goal, background, and data information; (2) a short-term memory $\mathcal{M}_t^S(d_n)$, capturing the current utterance and its two most recent predecessors; (3) a long-term memory $\mathcal{M}_t^L(d_n)$, summarizing accumulated meeting insights up to step t. The memory construction is defined as:

$$\mathcal{M}_t^S(d_n) = \{d_n^{t-2}, d_n^{t-1}, d_n^t\},$$
$$\mathcal{M}_t^L(d_n) = \begin{cases} \emptyset, & \text{if } t = 0, \\ \Gamma\left(\mathcal{M}_{t-1}^L(d_n) \cup \mathcal{M}_{t-1}^S(d_n)\right), & \text{if } t > 0, \end{cases}$$
$$\mathcal{M}_t(d_n) = [C(d_n), \mathcal{M}_t^S(d_n), \mathcal{M}_t^L(d_n)]. \tag{1}$$

For initial steps where $t < 2$, we omit unavailable indices in $\mathcal{M}_t^S(d_n)$, e.g., $\mathcal{M}_0^S(d_n) = \{d_n^0\}$

and $\mathcal{M}_1^S(d_n) = \{d_n^0, d_n^1\}$. This design ensures that the short-term memory is well-formed at all time steps, while the long-term memory recursively compresses earlier rounds via the LLM summarizer $\Gamma(\cdot)$ to prevent excessive memory accumulation.

To obtain the reinforcement learning state, we process the memory input $\mathcal{M}_t(d_n)$ through both the Observer $\mathcal{H}\phi$ and the Presenter $\mathcal{G}_\psi$, and extract their final hidden representations to construct the state embedding S_n:

$$S_n = \text{Concat}\left(\Psi_{\mathcal{H}_\phi}\left(\mathcal{M}_t(d_n)\right), \Omega\left(\Psi_{\mathcal{G}_\psi}\left(\mathcal{M}_t(d_n)\right)\right)\right), \tag{2}$$

where $\Psi_{\mathcal{H}_\phi}(\cdot)$ and $\Psi_{\mathcal{G}_\psi}(\cdot)$ denote the last hidden layer representations of $\mathcal{H}_\phi$ and $\mathcal{G}_\psi$, respectively, and $\text{Concat}(\cdot, \cdot)$ denotes the concatenation operator. To ensure dimensional consistency between the last hidden layer representations of the Observer and Presenter, we introduce a learnable linear projector $\Omega(\cdot)$ that projects $\Psi_{\mathcal{G}_\psi}\left(\mathcal{M}_t(d_n)\right)$ into the same dimension as the $\Psi_{\mathcal{H}_\phi}\left(\mathcal{M}_t(d_n)\right)$. The projector is jointly optimized with the coordinator policy $\mathcal{F}_\theta$ to determine whether to intervene at round d_n.

3.2.2 Silent or Intervene?

To identify potential intervene (positive) and silent (negative) samples from the PU data, the coordinator in our PULI framework formulates a binary decision-making problem. Specifically, for each unlabeled candidate round d_n, the coordinator observes the dialogue state S_n and selects an action $a_n \in \{0, 1\}$, where $a_n = 1$ indicates choosing to intervene, and $a_n = 0$ corresponds to remaining silent.

Formally, we implement the coordinator $\mathcal{F}_\theta$ as a multilayer perceptron (MLP), which takes the state S_n as input and outputs an intervention probability $\mathcal{F}_\theta(S_n)$ ranging from 0 to 1. The MLP uses ReLU activations in hidden layers and a sigmoid function in the output layer to produce probabilistic decisions.

The coordinator's policy function is defined as:

$$\begin{aligned} \pi_\theta(S_n, a_n) &= P_\theta(a_n \mid S_n) \\ &= a_n \cdot \mathcal{F}_\theta(S_n) + (1 - a_n) \cdot (1 - \mathcal{F}_\theta(S_n)), \end{aligned} \tag{3}$$

where $\pi_\theta(S_n, a_n)$ denotes the probability of selecting action a_n given state S_n. This design enables the coordinator $\mathcal{F}_\theta$ to learn to identify reliable negative examples (i.e., rounds to remain silent) from unlabeled intervention candidates, supporting effective policy refinement.

3.2.3 Learning-to-Intervene Reward

At each global training epoch T of PULI, after the coordinator selects a set of negative interventions $\mathcal{N}$, these negative samples are combined with the labeled positive interventions $\mathcal{P}$ from the training dataset to construct a binary supervision signal. The Observer is then trained using GRPO (Shao et al., 2024), where it is rewarded with 1 for correctly identifying a sample's intervention label and 0 otherwise. The model's performance is evaluated on a held-out validation set, and we denote the validation accuracy at epoch T as z^T.

To effectively encourage learning, we compare the current Observer's performance against the best historical performance. Specifically, we define the reward for intervention timing, r^{when}, as:

$$r^{\text{when}} = z^T - x^T, \tag{4}$$

where $x^T = \max(z^0, z^1, \ldots, z^{T-1})$ represents the best validation accuracy achieved in previous epochs, and z^0 corresponds to the Observer trained at initialization by treating all unlabeled instances as negative.

In parallel, the selected positive samples are used to augment the labeled positive intervention set, resulting in an expanded positive set $\mathcal{P}'$. This set is used to train the Presenter via supervised fine-tuning. To evaluate the quality of generated interventions, we compute the ROUGE-1 score of the LLM on held-out validation examples. Let the ROUGE-1 score at epoch T be denoted as l^T. The reward for intervention content quality, r^{how}, is defined as

$$r^{\text{how}} = l^T - h^T, \tag{5}$$

where $h^T = \max(l^0, l^1, \ldots, l^{T-1})$ is the highest validation ROUGE-1 score observed up to epoch $T-1$.

Finally, the total reward r_{total} used to update the coordinator is a weighted combination of the two components:

$$r_{\text{total}} = \lambda \cdot r^{\text{when}} + (1 - \lambda) \cdot r^{\text{how}}, \tag{6}$$

where $\lambda \in [0, 1]$ balances the importance between *when* to intervene and *how* to intervene. In all experiments, we set the default value of $\lambda = 0.6$.

3.3 Model Training

Coordinator Optimization Inspired by (Luo et al., 2021), we train the coordinator $\mathcal{F}_\theta$ using a reinforcement learning objective with the reward

function defined in Equation 6. At each training epoch T, the coordinator observes the dialogue state S_n for each unlabeled round $d_n \in \mathcal{U}$ and samples an action a_n from its policy $\pi_\theta(S_n)$. The resulting action sequence is evaluated using r_{total}, which integrates improvements in both intervention timing and content quality. Given the trajectory $\tau = \{(S_n, a_n)\}_{n=1}^u$ in epoch T, the coordinator's objective is to maximize the expected reward:

$$J(\theta) = \mathbb{E}_{\pi_\theta}\left[r_{\text{total}}^T\right]. \quad (7)$$

We apply the REINFORCE algorithm to compute the policy gradient:

$$\nabla_\theta J(\theta) \approx \sum_{n=1}^u r_{\text{total}}^T \cdot \nabla_\theta \log \pi_\theta(S_n, a_n), \quad (8)$$

and update the coordinator parameters with learning rate η:

$$\theta \leftarrow \theta + \eta \sum_{n=1}^u r_{\text{total}}^T \cdot \nabla_\theta \log \pi_\theta(S_n, a_n), \quad (9)$$

End-to-End Training   The overall training procedure is performed in an end-to-end iterative loop that jointly updates the coordinator, Observer, and Presenter. Initially, the Observer and Presenter are independently pre-trained by treating all unlabeled rounds in $\mathcal{U}$ as negative. The coordinator is randomly initialized.

At each epoch, the coordinator observes each unlabeled dialogue round d_n, encodes its state S_n using the last hidden layer representations from the Observer and Presenter, and samples an action a_n. Rounds selected for intervention ($a_n = 1$) are used to augment the positive set for updating the Presenter, while rounds with $a_n = 0$ are treated as negatives to refine the Observer. After training both LLMs, the resulting changes in Observer accuracy and Presenter ROUGE-1 scores are used to compute the total reward r_{total}^T and update the coordinator via policy gradient. This iterative process continues for a fixed number of epochs, leading to an end-to-end training framework to optimize intervention strategies.

4   Dataset Construction

LLMs have demonstrated strong capability for generating high-quality role-play datasets (Tao et al., 2024; Lim et al., 2024). While biomedical dialogue corpora such as MedDialog (Zeng et al., 2020),

Figure 3: Overview of BSDD dataset generation. Prophet LLM first extracts the project goal and background from PubMed papers. Dialogue-Simulator LLM then generates multi-role scientific dialogues using role-specific prompt templates. Finally, Prophet LLM labels the most goal-divergent dialogue round as a positive intervention point, while other rounds remain unlabeled.

MediTOD (Saley et al., 2024), and MaLP (Zhang et al., 2023) primarily focus on doctor–patient interactions, scientific dialogues among team members remain largely unexplored. Moreover, existing datasets lack annotated intervention labels that allow LLMs to learn proactive engagement. To fill this gap, we build BSDD (*Biomedical Streaming Dialogue Dataset*), a multi-role scientific dialogue dataset grounded in PubMed literature (Sayers et al., 2024). As shown in Figure 3, we employ two specialized LLMs: a Dialogue-Simulator (DS-LLM) and a Prophet (P-LLM).[2]

For each PubMed literature, P-LLM first accesses the complete paper but deliberately extracts only limited information—research goal, background knowledge, and relevant datasets (analogous to a mini-proposal)—while withholding methodological details, experimental procedures, and conclusions from DS-LLM. Using a prompt template set, DS-LLM instantiates four domain-specific roles: *Pharmacologist, Medicinal Chemist, Bioinformatician*, and *Clinical Physician*, each assigned role-specific responsibilities (e.g., the Medicinal Chemist emphasizes compound structure and synthesis). These roles engage in a multi-round team discussion, collaboratively working toward the predefined research objective (e.g., designing a cancer-targeting compound). Each turn is randomly sampled along a temporal timeline to reflect

---

[2]In practice, we deploy GPT o3-mini as the backbone of both DS-LLM and P-LLM. The prompt details and data statistics are provided in Appendix F and Appendix A, respectively.

asynchronous participation. After dialogue generation, P-LLM identifies the round that deviates most from the intended research goal and labels it as a positive intervention point, representing an opportunity for proactive redirection, while other dialogue rounds remain unlabeled. Our motivation to annotate only one high-confidence intervention point per dialogue is driven by the need to reduce annotation noise and mitigate hallucination risks, which are common when LLMs are asked to make multiple fine-grained judgments in a single inference pass (Manakul et al., 2023; Zhou et al., 2022).

To assess dataset quality, six biomedical experts are recruited to evaluate 100 randomly selected dialogues. For positive interventions, experts rate each dialogue on Timing and Quality using a 5-point scale, resulting in average scores of 3.82 and 4.21 and inter-expert Cohen's Kappa coefficients of 0.63 and 0.58, respectively. For negative samples in the validation and test sets, experts indicate binary agreement with non-intervention labels, achieving an 85% agreement rate.[3]

5 Experiments

5.1 Experimental Settings

Our PULI end-to-end training involves three components: a coordinator, an Observer LLM, and a Presenter LLM. The Observer LLM is trained with GRPO (Shao et al., 2024) using AdamW optimizer with learning rate of 1×10^{-6}, and batch size of 8. The Presenter LLM is fine-tuned via supervised learning with LoRA (rank 16, scaling factor $\alpha = 64$). The coordinator is a 6-layer MLP optimized with learning rate of 1×10^{-4}. Experiments are conducted using TRL (von Werra et al., 2020), Transformers (Wolf et al., 2020), PEFT (Mangrulkar et al., 2022), and PyTorch (Paszke et al., 2017) on eight 80GB A100 GPUs.

5.2 Baselines

We compare PULI with several representative baselines, including Standard, Random, Proactive Agent (Lu et al., 2024b), In-context Learning (ICL) (Koike et al., 2024), and vanilla SFT. Standard denotes the original dialogue without any intervention, while Random triggers interventions at arbitrary turns. For Proactive Agent, we follow Lu et al. (2024b) and adapt the system prompt instructions to when and how intervention task. In

ICL, we incorporate few-shot positive and negative samples into the prompt. For vanilla SFT, we fine-tune the Presenter model using only the labeled positive intervention samples from our dataset. We conduct experiments on two LLM families: LLaMA3 (Dubey et al., 2024) and Qwen3 (Yang et al., 2025a). For each family, we pair a small-scale model to determine when to intervene and a Presenter model to generate intervention content, simulating our dual-objective approach to proactive intervention in scientific dialogues. Specifically, we use (LLaMA3.2-1B-Instruct + LLaMA3.1-8B-Instruct) and (Qwen3-0.6B + Qwen3-14B) as the respective backbone combinations.

5.3 Tasks and Metrics

We follow the evaluation protocols of prior proactive agent studies (Lu et al., 2024b; Zhang et al., 2024a) to assess our approach on two tasks:

Intervention Timing Classification We evaluate whether the Observer LLM in PULI can accurately predict the necessity of intervention at each dialogue round. Standard binary classification metrics are reported, including accuracy, precision, recall, and F1-score.

Intervention Content Quality We assess whether applying interventions leads to improved dialogue-level conclusions. For each dialogue, a new conclusion is generated based on the intervention-augmented context and compared against the golden conclusion derived from the corresponding PubMed paper. We report ROUGE-1 and BLEU-1 scores between the generated and golden conclusions. Furthermore, we perform LLM as judge[4] to compare different methods, where GPT-4.1 (OpenAI, 2025) is deployed to select the best among all generated conclusions. Each method receives one win if its output is judged as best. The Win Rate (WR) for method i is computed as:

$$\text{WR}_i = \frac{W_i}{\sum_j W_j}, \tag{10}$$

where W_i denotes the number of dialogues where method i is selected as the best.

5.4 Main Results

We evaluate PULI across multiple LLM backbones and baselines to assess both intervention timing accuracy and content quality. As shown in Table 2, PULI consistently achieves the best performance

---

[3]Details of the human evaluation and scoring criteria for dataset quality are provided in Appendix E.1.

[4]The LLM-as-Judge prompt is detailed in Appendix F.

LLM Backbone (Observer + Presenter)	Method	Intervention Timing Classification (%)				Intervention Content Quality (%)		
		Accuracy	Recall	Precision	F1	ROUGE-1	BLEU-1	WR-Intra
(GPT-4o-mini + GPT-4o)	Standard	50.0	0.0	0.0	0.0	26.2	14.7	14.9
	Random	47.9	26.3	46.3	33.6	29.5	16.4	20.1
	Proactive Agent	62.3	31.7	81.5	45.6	30.7	17.2	28.3
	ICL	**63.8**	**34.1**	**83.8**	**48.5**	**31.3**	**17.5**	**36.7**
(Qwen3-0.6B + Qwen3-14B)	Standard	50.0	0.0	0.0	0.0	25.2	13.8	0.0
	Random	46.7	26.9	44.6	33.5	27.2	14.9	0.0
	Proactive Agent	53.9	14.9	67.6	24.5	27.6	15.5	14.8
	ICL	55.7	16.2	79.4	28.9	29.4	16.3	18.3
	Vanilla SFT	58.6	20.9	85.4	33.7	29.2	15.8	27.1
	PULI (Ours)	**64.1**	**31.2**	**91.0**	**46.4**	**32.4**	**20.1**	**39.8**
(LLaMA3.2-1B-Instruct + LLaMA3.1-8B-Instruct)	Standard	50.0	0.0	0.0	0.0	25.2	13.8	0.0
	Random	47.9	39.5	47.5	43.1	28.5	15.4	5.8
	Proactive Agent	54.5	53.4	68.8	60.2	29.1	15.4	7.5
	ICL	58.4	54.5	59.1	56.7	30.9	17.7	20.8
	Vanilla SFT	61.7	57.5	62.8	60.0	32.5	20.9	26.7
	PULI (Ours)	**67.4**	**61.7**	**69.6**	**65.4**	**33.5**	**21.8**	**39.2**

Table 2: Main results on intervention timing and content quality across different LLM families and intervention methods. **WR-Intra** is the win rate computed by comparing different methods under the same LLM backbone judged by GPT-4.1. The best result is highlighted in **bold**, and the second-best is underlined.

across all metrics and backbones[5]. On the (Qwen3-0.6B + Qwen3-14B) configuration, PULI outperforms strong baselines such as ICL and Vanilla SFT, achieving 64.1% accuracy in intervention timing classification and 32.4% ROUGE-1 in content quality, with a Win Rate of 39.8%. Similarly, on the (LLaMA3.2-1B + LLaMA3.1-8B) setting, PULI attains 67.4% accuracy, 33.5% ROUGE-1, and the highest intra-backbone Win Rate of 39.2%. To further assess cross-model robustness, Figure 4 compares the best-performing method for each backbone using GPT-4.1 as judge. Notably, PULI achieves a Win Rate of 45.8% on LLaMA3 and 35.9% on Qwen3 —both significantly higher than the best-performing method on GPT pair models (ICL: 18.3%). These results indicate that PULI outperforms proprietary models like GPT-4o, despite being trained with significantly fewer parameters.

5.5 Ablation Study

5.5.1 Variants Comparison

We compare PULI with several variants to assess the contribution of each component. As shown in Table 3, **w PN** treats all unlabeled samples as negatives, serving as a naive baseline. **w SFT** and **w DPO** (Rafailov et al., 2023) train the Observer model using supervised fine-tuning and direct pref-

---

[5]Finetuning GPT models is a black-box, we didn't find a way to finetune GPT-4o-mini using GRPO and some results are omitted. However, the results express the power of PULI.

Figure 4: Cross-backbone comparison of the best-performing methods. For each LLM backbone, we select the method with the highest Win Rate score and compare them using GPT-4.1 judgment.

erence optimization, respectively. PULI outperforms all variants on both intervention timing classification and content quality tasks. Among the variants, **w DPO** performs second best, achieving Accuracy of 64.6%, F1 score of 63.1% and Win Rate of 57.5%. These results suggest that combining PU supervision with reward-based coordination improves both timing and content quality.

5.5.2 Impact of λ in the Joint Objective

We conduct an ablation study to investigate the effect of the balancing weight λ used in our

LLM Backbone (Observer + Presenter)	Method	Intervention Timing Classification (%)				Intervention Content Quality (%)		
		Accuracy	Recall	Precision	F1	ROUGE-1	BLEU-1	WR-Intra
(LLaMA-3.2-1B-Instruct + LLaMA-3.1-8B-Instruct)	w PN	57.3	51.2	58.3	54.5	28.7	15.1	4.1
	w SFT	61.9	53.9	64.3	58.6	_31.7_	18.0	6.7
	w DPO	_64.6_	_60.5_	_66.1_	_63.1_	31.5	_18.6_	_31.7_
	PULI	**67.4**	**61.7**	**69.6**	**65.4**	**33.5**	**21.8**	**57.5**

Table 3: Comparison with method variants. **WR-Intra** is the win rate computed by comparing different methods under the same LLM backbone judged by GPT-4.1.

Figure 5: Effect of the balancing weight λ on Observer and Presenter performance.

Method	Timing	Quality	Helpfulness	Average
GPTs	4.36	4.18	4.43	4.32
PULI	**4.65**	**4.35**	**4.60**	**4.53**

Table 4: Human evaluation results comparing PULI (LLaMA3 pair) and ICL (GPT pair) on Timing, Quality, and Helpfulness (1–5 scale).

joint optimization objective for training the Observer and Presenter. LLaMA3 family (Observer: LLaMA-3.2-1B-Instruct, Presenter: LLaMA-3.1-8B-Instruct) is deployed as the PULI backbone LLMs. As shown in Figure 5, smaller values focus more on optimizing the Presenter (intervention generation), while increasing λ prioritizes the Observer's classification performance. We observe that $\lambda = 0.6$ yields the best balance, achieving competitive Observer accuracy (67.4%) and a high ROUGE-1 score (33.5%) for the Presenter. Notably, when λ is too small (e.g., 0.1), the Observer accuracy drops significantly, whereas overly large values lead to a reduction in Presenter quality. These results highlight the importance of balancing the two objectives during training.

5.6 Human Involved Validation

In addition, we conduct human evaluation[6] following the point-wise protocol proposed by Wang et al. (2023). Specifically, two master's-level students with strong biomedical backgrounds and research experience are recruited to assess 100 randomly sampled intervention response pairs (along with meeting and project context), generated by ICL (with GPT pair) and PULI (with LLaMA3 pair).

The evaluators are blinded to the source of each response. Each response is rated along three dimensions, using a 1–5 scale (with 5 indicating the highest): intervention timing (*Timing*), evaluating whether the intervention occurs at an appropriate point in the dialogue; content quality (*Quality*), measuring fluency and informativeness; and overall usefulness for advancing the project objective (*Helpfulness*). As shown in Table 4, PULI outperforms the GPT pair baseline across all dimensions, achieving higher scores in timing (4.65 vs. 4.36), quality (4.35 vs. 4.18), and helpfulness (4.60 vs. 4.43), resulting in a higher overall average (4.53 vs. 4.32).

6 Conclusion & Future Work

We introduce CoLabScience, a proactive AI assistant for biomedical discovery that integrates intervention timing and content generation to elevate human–AI collaboration. CoLabScience leverages a novel PULI framework, combining PU learning with policy coordination, to co-train a low-cost intervention model that decides when to act and an LLM presentation module that optimizes how to communicate. Experiments across diverse LLM backbones demonstrate significant gains in intervention accuracy and content quality, delivering robust generalization in collaborative biomedical research. In future work, we aim to extend PULI to other knowledge-scarce scientific workflows, e.g., law and education, further advancing human–AI synergy in interdisciplinary discovery.

---

[6]Details of the human information and scoring criteria for model evaluation are provided in Appendix E.2.

Limitations

While CoLabScience demonstrates promising results in proactive scientific assistance, we acknowledge several limitations of the current work:

● **Dataset Construction.** Our BSDD dataset relies on LLM-simulated dialogues grounded in PubMed literature. Although we incorporate expert validation, the simulated nature may not fully capture the complexity, nuance, and unpredictability of real-world scientific collaborations. Moreover, our annotation strategy labels only one optimal intervention point per dialogue to reduce noise and annotation cost. Compared with annotating every dialogue round individually—which would incur substantial labeling effort—this sparse labeling scheme greatly simplifies data construction. Nevertheless, given the strong empirical advantages of Positive–Unlabeled (PU) learning, PULI can still learn effectively from sparsely labeled data.

● **Evaluation Scope.** Our experiments are conducted on simulated dialogues, and future work will extend evaluation to actual research team meetings. The generalizability of PULI to real-world scientific discussions—characterized by overlapping turns, informal reasoning, and evolving research objectives—remains an important direction for future research. Real-world deployment would also benefit from small-scale user studies with practicing researchers to assess ecological validity and identify practical deployment challenges.

● **Computational Considerations in Real-world Inference.** While the Observer serves as a lightweight gate to minimize computational overhead, real-world deployment requires integration with automatic speech recognition (ASR) and text-to-speech (TTS) systems for live interaction, which may introduce additional latency—approximately 0.8 seconds per turn in our prototype. Further optimization of the inference pipeline will be needed to ensure seamless real-time intervention.

● **Intervention Design.** Our current intervention formulation focuses on detecting whether a dialogue round diverges from the project goal, misses opportunities to advance progress, or reflects insufficient team coordination. However, real-world interventions can take diverse forms—such as clarifying misunderstandings, fostering collaboration, or reframing research directions. Future work should explore a broader taxonomy of intervention types and contextual factors that determine their appropriateness and timing.

Ethics Statement

All human annotation work in this study is conducted by domain experts who are not co-authors of this paper. The annotation process is coordinated by a Principal Investigator (PI) from a biomedical research institution, who is listed as a co-author but does not directly participate in any annotation tasks. The expert annotators include one medical doctor, three PhD candidates, and two master's-level students in biomedical fields. All annotators are blind to the study's hypotheses and model architecture during the annotation process.

All annotation work is performed during the experts' regular paid working hours as part of their institutional research responsibilities, and no additional compensation is provided beyond their standard employment. The six annotators evaluate 100 randomly sampled dialogues for dataset quality assessment, rating intervention timing and content quality on established scales. For model evaluation, the two master's-level students with biomedical backgrounds assess intervention responses following point-wise evaluation protocols. All experts provide informed consent for their annotations to be used in this research and released with the dataset.

The content annotated consists entirely of simulated scientific dialogues generated from publicly available PubMed literature. No personal, sensitive, or confidential information is involved in the annotation process. All research procedures follow institutional guidelines, and no additional ethics board review is required under the ACL Ethics Policy. The dataset and annotation guidelines will be made publicly available upon publication to support reproducibility and future research in proactive scientific assistance systems.

References

Joya Chen, Zhaoyang Lv, Shiwei Wu, Kevin Qinghong Lin, Chenan Song, Difei Gao, Jia-Wei Liu, Ziteng Gao, Dongxing Mao, and Mike Zheng Shou. 2024. Videollm-online: Online video large language model for streaming video. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 18407–18418.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. 2024. The llama 3 herd of models. *arXiv e-prints*, pages arXiv–2407.

Juraj Gottweis, Wei-Hung Weng, Alexander Daryin, Tao Tu, Anil Palepu, Petar Sirkovic, Artiom Myaskovsky, Felix Weissenberger, Keran Rong, Ryutaro Tanno, et al. 2025. Towards an ai co-scientist. *arXiv preprint arXiv:2502.18864*.

Amine Ben Hassouna, Hana Chaari, and Ines Belhaj. 2024. Llm-agent-umf: Llm-based agent unified modeling framework for seamless integration of multi active/passive core-agents. *arXiv preprint arXiv:2409.11393*.

Kostas Hatalis, Despina Christou, Joshua Myers, Steven Jones, Keith Lambert, Adam Amos-Binks, Zohreh Dannenhauer, and Dustin Dannenhauer. 2023. Memory matters: The need to improve long-term memory in llm-agents. In *Proceedings of the AAAI Symposium Series*, volume 2, pages 277–280.

Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, et al. 2025. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *ACM Transactions on Information Systems*, 43(2):1–55.

Ruofan Jin, Zaixi Zhang, Mengdi Wang, and Le Cong. 2025. Stella: Self-evolving llm agent for biomedical research.

John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. 2021. Highly accurate protein structure prediction with alphafold. *nature*, 596(7873):583–589.

Ryuichi Kiryo, Gang Niu, Marthinus C Du Plessis, and Masashi Sugiyama. 2017. Positive-unlabeled learning with non-negative risk estimator. *Advances in neural information processing systems*, 30.

Ryuto Koike, Masahiro Kaneko, and Naoaki Okazaki. 2024. Outfox: Llm-generated essay detection through in-context learning with adversarially generated examples. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 21258–21266.

Shuyue Stella Li, Vidhisha Balachandran, Shangbin Feng, Jonathan Ilgen, Emma Pierson, Pang Wei Koh, and Yulia Tsvetkov. 2024. Mediq: Question-asking llms for adaptive and reliable medical reasoning. *arXiv e-prints*, pages arXiv–2406.

Lizi Liao, Grace Hui Yang, and Chirag Shah. 2023. Proactive conversational agents in the post-chatgpt world. In *Proceedings of the 46th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 3452–3455.

Jung Hoon Lim, Sunjae Kwon, Zonghai Yao, John P Lalor, and Hong Yu. 2024. Large language model-based role-playing for personalized medical jargon extraction. *arXiv preprint arXiv:2408.05555*.

Tianjian Liu, Hongzheng Zhao, Yuheng Liu, Xingbo Wang, and Zhenhui Peng. 2024. Compeer: A generative conversational agent for proactive peer support. In *Proceedings of the 37th Annual ACM Symposium on User Interface Software and Technology*, pages 1–22.

Chris Lu, Cong Lu, Robert Tjarko Lange, Jakob Foerster, Jeff Clune, and David Ha. 2024a. The ai scientist: Towards fully automated open-ended scientific discovery. *arXiv preprint arXiv:2408.06292*.

Yaxi Lu, Shenzhi Yang, Cheng Qian, Guirong Chen, Qinyu Luo, Yesai Wu, Huadong Wang, Xin Cong, Zhong Zhang, Yankai Lin, et al. 2024b. Proactive agent: Shifting llm agents from reactive responses to active assistance. *arXiv preprint arXiv:2410.12361*.

Zhiyong Lu, Yifan Peng, Trevor Cohen, Marzyeh Ghassemi, Chunhua Weng, and Shubo Tian. 2024c. Large language models in biomedicine and health: current research landscape and future directions. *Journal of the American Medical Informatics Association*, 31(9):1801–1811.

Chuan Luo, Pu Zhao, Chen Chen, Bo Qiao, Chao Du, Hongyu Zhang, Wei Wu, Shaowei Cai, Bing He, Saravanakumar Rajmohan, et al. 2021. Pulns: Positive-unlabeled learning with effective negative sample selector. In *Proceedings of the AAAI conference on artificial intelligence*, volume 35, pages 8784–8792.

Renqian Luo, Liai Sun, Yingce Xia, Tao Qin, Sheng Zhang, Hoifung Poon, and Tie-Yan Liu. 2022. Biogpt: generative pre-trained transformer for biomedical text generation and mining. *Briefings in Bioinformatics*, 23(6).

Tengfei Ma, Xuan Lin, Tianle Li, Chaoyi Li, Long Chen, Peng Zhou, Xibao Cai, Xinyu Yang, Daojian Zeng, Dongsheng Cao, and Xiangxiang Zeng. 2024. Y-mol: A multiscale biomedical knowledge-guided large language model for drug development.

Potsawee Manakul, Adian Liusie, and Mark JF Gales. 2023. Selfcheckgpt: Zero-resource black-box hallucination detection for generative large language models. *arXiv preprint arXiv:2303.08896*.

Sanket Mangrulkar, Kaustubh Somasundaram, and Akhilesh Shrivastava. 2022. Peft: Parameter-efficient fine-tuning. *Hugging Face*. https://github.com/huggingface/peft.

OpenAI. 2025. Gpt-4.1 api documentation. https://platform.openai.com/docs/models/gpt-4.1. Accessed: 2025-05-11.

Jing-Cheng Pang, Heng-Bo Fan, Pengyuan Wang, Jia-Hao Xiao, Nan Tang, Si-Hang Yang, Chengxing Jia, Ming-Kun Xie, Xiang Chen, Sheng-Jun Huang, et al. 2025. Interactive large language models for reliable answering under incomplete context. *Transactions on Machine Learning Research*.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. 2017. Automatic differentiation in pytorch. In *Advances in Neural Information Processing Systems*.

Biqing Qi, Kaiyan Zhang, Kai Tian, Haoxiang Li, Zhang-Ren Chen, Sihang Zeng, Ermo Hua, Hu Jinfang, and Bowen Zhou. 2024. Large language models as biomedical hypothesis generators: a comprehensive evaluation. *arXiv preprint arXiv:2407.08940*.

Cheng Qian, Bingxiang He, Zhong Zhuang, Jia Deng, Yujia Qin, Xin Cong, Zhong Zhang, Jie Zhou, Yankai Lin, Zhiyuan Liu, et al. 2024. Tell me more! towards implicit user intention understanding of language model driven agents. *arXiv preprint arXiv:2402.09205*.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2023. Direct preference optimization: Your language model is secretly a reward model. *Advances in Neural Information Processing Systems*, 36:53728–53741.

Vishal Vivek Saley, Goonjan Saha, Rocktim Jyoti Das, Dinesh Raghu, et al. 2024. Meditod: An english dialogue dataset for medical history taking with comprehensive annotations. *arXiv preprint arXiv:2410.14204*.

Eric W Sayers, Jeff Beck, Evan E Bolton, J Rodney Brister, Jessica Chan, Donald C Comeau, Ryan Connor, Michael DiCuccio, Catherine M Farrell, Michael Feldgarden, et al. 2024. Database resources of the national center for biotechnology information. *Nucleic Acids Research*, 52(D1):D33–D43.

Samuel Schmidgall, Yusheng Su, Ze Wang, Ximeng Sun, Jialian Wu, Xiaodong Yu, Jiang Liu, Zicheng Liu, and Emad Barsoum. 2025. Agent laboratory: Using llm agents as research assistants. *arXiv preprint arXiv:2501.04227*.

Shreya Shankar and Aditya G Parameswaran. 2024. Building reactive large language model pipelines with motion. In *Companion of the 2024 International Conference on Management of Data*, pages 520–523.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Y Wu, et al. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Gaurang Sriramanan, Siddhant Bharti, Vinu Sankar Sadasivan, Shoumik Saha, Priyatham Kattakinda, and Soheil Feizi. 2024. Llm-check: Investigating detection of hallucinations in large language models. *Advances in Neural Information Processing Systems*, 37:34188–34216.

Richard S Sutton, David McAllester, Satinder Singh, and Yishay Mansour. 1999. Policy gradient methods for reinforcement learning with function approximation. *Advances in neural information processing systems*, 12.

Kyle Swanson, Wesley Wu, Nash L Bulaong, John E Pak, and James Zou. 2024. The virtual lab: Ai agents design new sars-cov-2 nanobodies with experimental validation. *bioRxiv*, pages 2024–11.

Yufei Tao, Ameeta Agrawal, Judit Dombi, Tetyana Sydorenko, and Jung In Lee. 2024. Chatgpt roleplay dataset: Analysis of user motives and model naturalness. *arXiv preprint arXiv:2403.18121*.

Leandro von Werra, Younes Belkada, Lewis Tunstall, Edward Beeching, Tristan Thrush, Nathan Lambert, Shengyi Huang, Kashif Rasul, and Quentin Gallouédec. 2020. Trl: Transformer reinforcement learning. https://github.com/huggingface/trl.

Hongru Wang, Rui Wang, Fei Mi, Zezhong Wang, Ruifeng Xu, and Kam-Fai Wong. 2023. Chain-of-thought prompting for responding to in-depth dialogue questions with llm. *arXiv preprint arXiv:2305.11792*.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Remi Louf, Morgan Funtowicz, et al. 2020. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 conference on empirical methods in natural language processing: system demonstrations*, pages 38–45.

Felix Wong, Erica J Zheng, Jacqueline A Valeri, Nina M Donghia, Melis N Anahtar, Satotaka Omori, Alicia Li, Andres Cubillos-Ruiz, Aarti Krishnan, Wengong Jin, et al. 2024. Discovery of a structural class of antibiotics with explainable deep learning. *Nature*, 626(7997):177–185.

Cheng-Kuang Wu, Zhi Rui Tam, Chao-Chung Wu, Chieh-Yen Lin, Hung-yi Lee, and Yun-Nung Chen. 2024. I need help! evaluating llm's ability to ask for users' support: A case study on text-to-sql generation. *arXiv preprint arXiv:2407.14767*.

Junde Wu, Jiayuan Zhu, and Yuyuan Liu. 2025. Agentic reasoning: Reasoning llms with tools for the deep research. *arXiv preprint arXiv:2502.04644*.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. 2025a. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Bufang Yang, Yunqi Guo, Lilin Xu, Zhenyu Yan, Hongkai Chen, Guoliang Xing, and Xiaofan Jiang. 2025b. Socialmind: Llm-based proactive ar social assistive system with human-like perception for in-situ live interactions. *Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies*, 9(1):1–30.

Vinicius Zambaldi, David La, Alexander E Chu, Harshnira Patani, Amy E Danson, Tristan OC Kwan, Thomas Frerix, Rosalia G Schneider, David Saxton, Ashok Thillaisundaram, et al. 2024. De novo design of high-affinity protein binders with alphaproteo. *arXiv preprint arXiv:2409.08022*.

Guangtao Zeng, Wenmian Yang, Zeqian Ju, Yue Yang, Sicheng Wang, Ruisi Zhang, Meng Zhou, Jiaqi Zeng, Xiangyu Dong, Ruoyu Zhang, et al. 2020. Meddialog: Large-scale medical dialogue datasets. In *Proceedings of the 2020 conference on empirical methods in natural language processing (EMNLP)*, pages 9241–9250.

Ceyao Zhang, Kaijie Yang, Siyi Hu, Zihao Wang, Guanghe Li, Yihang Sun, Cheng Zhang, Zhaowei Zhang, Anji Liu, Song-Chun Zhu, et al. 2024a. Proagent: building proactive cooperative agents with large language models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 17591–17599.

Kai Zhang, Yangyang Kang, Fubang Zhao, and Xiaozhong Liu. 2023. Llm-based medical assistant personalization with short-and long-term memory coordination. *arXiv preprint arXiv:2309.11696*.

Xuan Zhang, Yang Deng, Zifeng Ren, See-Kiong Ng, and Tat-Seng Chua. 2024b. Ask-before-plan: Proactive language agents for real-world planning. *arXiv preprint arXiv:2406.12639*.

Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, et al. 2023. A survey of large language models. *arXiv preprint arXiv:2303.18223*, 1(2).

Wanjun Zhong, Lianghong Guo, Qiqi Gao, He Ye, and Yanlin Wang. 2024. Memorybank: Enhancing large language models with long-term memory. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19724–19731.

Denny Zhou, Nathanael Schärli, Le Hou, Jason Wei, Nathan Scales, Xuezhi Wang, Dale Schuurmans, Claire Cui, Olivier Bousquet, Quoc Le, et al. 2022. Least-to-most prompting enables complex reasoning in large language models. *arXiv preprint arXiv:2205.10625*.

Yuyang Zhou, Guang Cheng, Kang Du, and Zihan Chen. 2024. Toward intelligent and secure cloud: Large language model empowered proactive defense. *arXiv preprint arXiv:2412.21051*.

A Data Statistics

We select PubMed papers (Sayers et al., 2024) covering various biomedical topics, including cancer, Alzheimer's disease, and sepsis. To ensure scientific rigor, we filter for papers published between January 1, 2024 and January 1, 2025 that include concrete methodological descriptions, such as experimental design, procedures, and analysis. Since speakers in each dialogue are temporally and randomly sampled, we vary the random seed to generate up to five dialogues per paper using our data construction pipeline.

For each training dialogue, one positive intervention is automatically annotated by our Prophet LLM within the construction pipeline, and four additional rounds are randomly sampled as unlabeled interventions. To evaluate the Observer's ability to detect appropriate intervention timing, we construct validation and test sets where each dialogue includes one positive and one negative round. The positive round corresponds to the effective intervention point, while the negative round is first selected by Prophet LLM as the least likely point requiring intervention, and then verified by human experts. The resulting negative samples achieve an average agreement score of 0.85 with human annotations, ensuring the reliability of evaluation. Detailed statistics of the constructed BSDD (Biomedical Streaming Dialogue Dataset) dataset are provided in Table 5.

Raw Data Statistics of PubMed Papers			
# Cancer Papers		452	
# Alzheimer's Papers		204	
# Sepsis Papers		41	
Generated Data Statistics			
# Generated Dialogue		3,206	
# Avg. Rounds per Dialogue		20	
# Avg. Tokens per Round		378	
Data Split Statistics			
	Train	**Validation**	**Test**
# Dialogues	2,726	240	240
# Sampled Rounds	13,630	480	480
# Positive Rounds	2,726	240	240
# Unlabeled Rounds	10,904	-	-
# Negative Rounds	-	240	240

Table 5: Statistics of the constructed BSDD dataset

Figure 6: Inference pipeline of CoLabScience in real-world scientific collaboration. The Observer monitors ongoing dialogue and determines when to intervene. Upon intervention trigger, the Presenter generates scientific suggestions for the research team.

B CoLabScience in Real-World Scientific Collaboration

The inference workflow of CoLabScience is illustrated in Figure 6. In a live scientific discussion scenario, dialogue audio is first captured and transcribed in real time via a streaming ASR (Automatic Speech Recognition) module. The resulting transcripts are continuously fed into the Observer, which monitors the conversation and makes a binary decision—either to remain *silent* or to *intervene*. If an intervention is triggered, the Presenter LLM is activated to generate scientifically grounded suggestions based on the conversation context. The generated intervention content is then converted into audio via a TTS (Text-to-Speech) system and delivered back into the ongoing dialogue, completing the feedback loop.

This modular inference design enables CoLabScience to function as a proactive AI assistant in real-world biomedical research settings. By separating the decision-making process (Observer) from the content generation (Presenter), the system avoids unnecessary computation and improves responsiveness. Compared to reactive paradigms that invoke large LLMs at every round, our two-stage approach—with a small-scale Observer determining intervention necessity before invoking the full generation model—offers significantly greater inference efficiency. A demonstration of CoLabScience in a real-world streaming environment is available in the supplementary video.

C PULI Algorithm

In this section, we present the details of the end-to-end training procedure of PULI, as illustrated in Algorithm 1.

Algorithm 1 End-to-End Training of PULI Framework

Input: Unlabeled rounds $U = \{d_1, \ldots, d_u\}$, positive rounds $P = \{d_{u+1}, \ldots, d_N\}$; coordinator policy π_θ; Observer $\mathcal{H}_\phi$; Presenter $\mathcal{G}_\psi$; learning rate η; reward trade-off λ; total epochs E
Output: Optimized π_θ, $\mathcal{H}_\phi$, and $\mathcal{G}_\psi$
1: **Pretrain** $\mathcal{H}_\phi$ and $\mathcal{G}_\psi$ by treating all $d_n \in U$ as negative
2: **Initialize** coordinator parameters θ
3: **for** epoch $T = 1$ to E **do**
4:   Initialize selected intervention set $\mathcal{P}^+ \leftarrow \emptyset$ and silent set $\mathcal{N} \leftarrow \emptyset$
5:   **for** each dialogue round $d_n \in U$ **do**
6:     Construct memory $\mathcal{M}(d_n)$ and encode state $S_n = \text{Concat}\left(\Psi_{\mathcal{H}_\phi}(\mathcal{M}(d_n)), \Omega(\Psi_{\mathcal{G}_\psi}(\mathcal{M}(d_n)))\right)$
7:     Sample action $a_n \sim \pi_\theta(S_n)$
8:     **if** $a_n = 1$ **then**
9:       Add d_n to $\mathcal{P}^+$
10:    **else**
11:      Add d_n to $\mathcal{N}$
12:    **end if**
13:   **end for**
14:   Train $\mathcal{H}_\phi$ via GRPO on $\mathcal{P} \cup \mathcal{N}$ and compute reward r^{when}
15:   Fine-tune $\mathcal{G}_\psi$ on $P' = P \cup \mathcal{P}^+$ and compute reward r^{how}
16:   Compute total reward:

$$r_{\text{total}} = \lambda \cdot r^{\text{when}} + (1 - \lambda) \cdot r^{\text{how}}$$

17:   Update coordinator via REINFORCE:

$$\theta \leftarrow \theta + \eta \sum_{n=1}^{u} r_{\text{total}} \cdot \nabla_\theta \log \pi_\theta(S_n, a_n)$$

18: **end for**
19: **Return** Optimized π_θ, $\mathcal{H}_\phi$, $\mathcal{G}_\psi$

D   REINFORCE Policy Gradient Derivation

We follow the standard REINFORCE framework (Sutton et al., 1999) to derive the policy gradient update used in our coordinator optimization.

Let θ denote the parameters of the coordinator policy $\pi_\theta(a \mid S)$. At each training epoch T, the coordinator samples a sequence of actions over unlabeled dialogue rounds $\tau = \{(S_1, a_1), \ldots, (S_u, a_u)\}$, forming a trajectory under its current policy. Given the total reward of the trajectory as a scalar r_{total}^T, the goal is to maximize the expected reward:

$$J(\theta) = \mathbb{E}_{\tau \sim \pi_\theta}\left[r_{\text{total}}^T\right]. \tag{11}$$

The gradient of this expectation can be computed via the score function estimator:

$$\nabla_\theta J(\theta) = \nabla_\theta \mathbb{E}_{\tau \sim \pi_\theta}\left[r_{\text{total}}^T\right] \tag{12}$$

$$= \mathbb{E}_{\tau \sim \pi_\theta}\left[r_{\text{total}}^T \cdot \nabla_\theta \log P_\theta(\tau)\right], \tag{13}$$

where $P_\theta(\tau)$ is the probability of the trajectory under the current policy.

Assuming the trajectory is composed of conditionally independent actions, we can express the trajectory probability as the product of individual decisions:

$$P_\theta(\tau) = \prod_{n=1}^{u} \pi_\theta(a_n \mid S_n), \tag{14}$$

so the log-probability becomes:

$$\log P_\theta(\tau) = \sum_{n=1}^{u} \log \pi_\theta(a_n \mid S_n). \tag{15}$$

Substituting into the gradient, we obtain:

$$\nabla_\theta J(\theta) = \mathbb{E}_{\tau \sim \pi_\theta}\left[r_{\text{total}}^T \cdot \sum_{n=1}^{u} \nabla_\theta \log \pi_\theta(a_n \mid S_n)\right]. \tag{16}$$

In practice, we estimate this gradient using a single-sample Monte Carlo approximation:

$$\nabla_\theta J(\theta) \approx \sum_{n=1}^{u} r_{\text{total}}^T \cdot \nabla_\theta \log \pi_\theta(a_n \mid S_n), \tag{17}$$

which corresponds to the update used in our main training algorithm.

This derivation assumes that the total reward r_{total}^T is obtained after observing the entire trajectory. If intermediate rewards were available per step, the derivation could be generalized using discounted or shaped rewards.

E   Human Annotation Details

E.1   Data Quality Assessment

Human Experts We engage six domain experts with extensive biomedical research experience, including one medical doctor, three PhD candidates, and two master's-level students. All experts conduct their work during regular paid working hours as part of their institutional duties, and are compensated accordingly.

Assessment Metrics To assess dataset quality, experts are asked to annotate the Timing and content Quality of pre-labeled positive interventions identified by Prophet LLM. In addition, for evaluation purpose, we introduce a small set of negative samples into the validation and test sets. These negative rounds are initially identified by the Prophet LLM as having low likelihood of requiring intervention and are subsequently verified by human experts.

The average annotation scores are 3.82 for timing and 4.21 for quality on a 5-point scale (5 being the highest), and the Agreement rate on negative sample identification is 0.85. The detailed assessment rubric is presented in Table 6.

E.2 Human-Involved Model Evaluation

Human Experts Two master's-level students with biomedical backgrounds perform the human evaluation. This task is assigned as part of their regular research assistant responsibilities and is compensated through standard RA funding, consistent with the data annotation setup.

Evaluation Metrics For each predicted intervention round in the dialogue, experts evaluate intervention Timing and Quality using the same rubric as in the data quality assessment. Furthermore, we introduce an additional metric Helpfulness to measure the overall contribution of the intervention to the team's scientific progress. Full definitions of these criteria are provided in Table 7.

Positive Intervention – Timing		
Score	Label	Description
1	Poor Timing	Intervention occurs at an inappropriate moment; disrupts dialogue flow or misses critical context.
2	Weak Timing	Slightly mistimed; not harmful but lacks context awareness.
3	Acceptable Timing	Timing is reasonable and does not mislead, but could be improved.
4	Good Timing	Well-timed intervention that aligns with team's discussion flow.
5	Excellent Timing	Precisely timed to redirect or enhance discussion at a critical moment.
Positive Intervention – Quality		
Score	Label	Description
1	Poor Quality	Intervention is off-topic, incorrect, or lacks relevance.
2	Weak Quality	Information is vague, partially relevant, or lacks clarity.
3	Acceptable Quality	Reasonable relevance; generally informative but not insightful.
4	Good Quality	Clear and useful; provides relevant direction for the team.
5	Excellent Quality	Highly informative, well-reasoned, and clearly advances the team's goal.
Negative Intervention (Only in Validation and Test Data for Evaluation Purpose)		
Label	Description	
Agree	Dialogue is progressing smoothly toward the goal; no intervention needed.	
Disagree	Discussion shows signs of drifting, confusion, or omissions; intervention is warranted.	

Table 6: Data quality scoring form.

Timing		
Score	Label	Description
1	Poor Timing	Intervention occurs at an inappropriate moment; disrupts dialogue flow or misses critical context.
2	Weak Timing	Slightly mistimed; not harmful but lacks context awareness.
3	Acceptable Timing	Timing is reasonable and does not mislead, but could be improved.
4	Good Timing	Well-timed intervention that aligns with team's discussion flow.
5	Excellent Timing	Precisely timed to redirect or enhance discussion at a critical moment.
Quality		
Score	Label	Description
1	Poor Quality	Intervention is off-topic, incorrect, or lacks relevance.
2	Weak Quality	Information is vague, partially relevant, or lacks clarity.
3	Acceptable Quality	Reasonable relevance; generally informative but not insightful.
4	Good Quality	Clear and useful; provides relevant direction for the team.
5	Excellent Quality	Highly informative, well-reasoned, and clearly advances the team's goal.
Helpfulness		
Score	Label	Description
1	Not Helpful	Distracting, misaligned with team needs, possibly harmful.
2	Slightly Helpful	Low impact; repeats known info or barely contributes.
3	Moderately Helpful	Somewhat useful; might inspire ideas but not essential.
4	Helpful	Helps move the discussion forward meaningfully.
5	Very Helpful	Crucially contributes to team progress, solves key problem.

Table 7: Human-involved model evaluation metrics.

F Prompt Details

In this section, we present the detailed prompts used in our work, including dataset construction for generating scientific dialogues and intervention annotations, baseline in-context learning (ICL) setups for model comparison, and LLM-as-judge evaluation prompts for computing win rates.

LLM-as-Judge Prompt

<|im_start|>system
You are an expert scientific evaluator specializing in research conclusion assessment. You will be given a golden standard conclusion of a scientific research paper, followed by multiple candidate conclusions generated by different methods. The golden standard conclusion summarizes the key elements of the research project, including its main experimental design, core findings, and overall scientific significance. It serves as a high-quality reference for evaluating the quality, clarity, and relevance of alternative conclusions.

Your task is to evaluate and rank these candidate conclusions based on the following criteria:
1. Scientific Accuracy & Consistency: How well does the conclusion align with established scientific knowledge and the project's context?
2. Completeness & Comprehensiveness: Does the conclusion adequately address all key aspects mentioned in the original discussion?
3. Clarity & Structure: Is the conclusion well-organized, clearly written, and logically structured?
4. Clinical/Research Relevance: How effectively does the conclusion translate findings into actionable insights for the field?
5. Evidence Integration: How well does the conclusion synthesize and integrate the discussed evidence?
6. Golden Standard Alignment: How closely does the conclusion match the quality and content depth of the golden standard?

You will receive multiple conclusions labeled as "Method A", "Method B", etc. Your task is to determine which method produces the BEST conclusion overall.

CRITICAL INSTRUCTIONS:
- You must output ONLY ONE LETTER corresponding to the best method (A, B, C, D, or E)
- Consider the golden standard as a reference for quality, but evaluate which generated conclusion is objectively best
- Focus on scientific merit and practical value
- If conclusions are very similar in quality, choose based on clarity and completeness
- Do NOT explain your reasoning — output only the single letter of the best method
Example Output: B <|im_end|>

<|im_start|>user

Golden Standard Conclusion:
<golden standard conclusion>

Candidate Conclusions to Evaluate:
<method A>
<method B>
...
<|im_end|>

Positive Intervention Labeling Prompt

<|im_start|>system
You are an AI moderator specializing in research coherence and integrity. You will analyze a multi-turn scientific team discussion and identify the single most critical point where an intervention should be made to help the team stay focused on the research goal.
You should identify and describe the most valuable intervention point in the discussion. Include the following elements in your output:
- "intervention position": After which turn/round this issue was observed. Use the round number (starting from 0). - "issue type": One of ["scientific error", "low collaboration", "scope drift", "missed opportunity"].
- "target members": Role(s) that should be addressed (e.g., ["Medicinal Chemist"]). - "intervention content": A short explanation of why this intervention is helpful for tracking team member contributions and advancing the research project. This should include **constructive suggestions** grounded in the actual dialog, such as pointing out unexplored ideas, prompting clarification, further direction or encouraging collaboration. - "modified dialog": A revised version of the identified turn that improves the discussion focus or productivity.
Additional context: - You may assume access to the uploaded research paper, but do NOT reference its conclusions directly. - Intervene when the team loses focus, fails to act on key cues, misses cross-role collaboration, or drifts from the research goal. - Your goal is not to fix all problems, but to insert one helpful redirection that will facilitate clearer progress and collaboration. - Each part of your output should be clearly written and self-contained. Do not include any external commentary or formatting instructions. <|im_end|>

<|im_start|>user
<project proposal>
<dialogue history>
<|im_end|>

Baseline ICL Prompt

<|im_start|>system
You are an AI moderator specializing in research coherence and integrity. Your task is to analyze a multi-turn scientific team discussion and determine whether the specified round of conversation requires an intervention.
An intervention may be required for one of the following reasons: - "scientific error" - "low collaboration" - "scope drift from project goal" - "missed opportunity"
You will be shown example cases that illustrate both intervention and non-intervention outcomes: <Positive sample: dialogue context + Intervention Content>, <Negative sample: dialogue context + No Need Intervention>
Your response must be one of the following:
- Intervention Content: <brief reason>
- No Need Intervention
<|im_end|>

<|im_start|>user
<dialogue context>
<specified round of interest>
<|im_end|>

Clinical Physician Prompt

<|im_start|>system
You are a Clinical Physician. You are part of an interdisciplinary drug discovery team that just received the project kickoff briefing. You're now engaging in a live strategy meeting with your colleagues.
Your responsibilities:
- Contribute ideas and critiques from your domain perspective. - Engage with previous comments (your own or others') and develop them further. - Express uncertainty or enthusiasm naturally — like a real person.
Guidelines:
- DO NOT begin every message with "As a Clinical Physician...".
- Use first-person natural language — just speak as yourself.
- Respond based on the meeting history so far — don't repeat what's already said.
- Ask questions or challenge others when appropriate.
- Use domain-specific terminology, but focus on clarity.
Example behavior:
- A Clinical Physician might emphasize patient outcomes or trial design feasibility.
Your goal is to make progress in the research planning through scientific reasoning and collaboration — not to summarize or finalize conclusions. <|im_end|>

<|im_start|>user
<project proposal>
<dialogue history>
Clinical Physician:
<|im_end|>

Bioinformatician Prompt

<|im_start|>system
You are a Bioinformatician. You are part of an interdisciplinary drug discovery team that just received the project kickoff briefing. You're now engaging in a live strategy meeting with your colleagues.
Your responsibilities:
- Contribute ideas and critiques from your domain perspective. - Engage with previous comments (your own or others') and develop them further. - Express uncertainty or enthusiasm naturally — like a real person.
Guidelines:
- DO NOT begin every message with "As a Bioinformatician...".
- Use first-person natural language — just speak as yourself.
- Respond based on the meeting history so far — don't repeat what's already said.
- Ask questions or challenge others when appropriate.
- Use domain-specific terminology, but focus on clarity.
Example behavior:
- A Bioinformatician might offer to analyze omics data or suggest in silico approaches.
Your goal is to make progress in the research planning through scientific reasoning and collaboration — not to summarize or finalize conclusions. <|im_end|>

<|im_start|>user
<project proposal>
<dialogue history>
Bioinformatician:
<|im_end|>

Pharmacologist Prompt

<|im_start|>system
You are a Pharmacologist. You are part of an interdisciplinary drug discovery team that just received the project kickoff briefing. You're now engaging in a live strategy meeting with your colleagues.
Your responsibilities:
- Contribute ideas and critiques from your domain perspective. - Engage with previous comments (your own or others') and develop them further. - Express uncertainty or enthusiasm naturally — like a real person.
Guidelines:
- DO NOT begin every message with "As a pharmacologist...".
- Use first-person natural language — just speak as yourself. - Respond based on the meeting history so far — don't repeat what's already said.
- Ask questions or challenge others when appropriate. - Use domain-specific terminology, but focus on clarity.
Example behavior:
- A Pharmacologist might raise concerns about off-target effects or bioavailability.
Your goal is to make progress in the research planning through scientific reasoning and collaboration — not to summarize or finalize conclusions. <|im_end|>

<|im_start|>user
<project proposal>
<dialogue history>
Pharmacologist:
<|im_end|>

Medicinal Chemist Prompt

<|im_start|>system
You are a Medicinal Chemist. You are part of an interdisciplinary drug discovery team that just received the project kickoff briefing. You're now engaging in a live strategy meeting with your colleagues.
Your responsibilities:
- Contribute ideas and critiques from your domain perspective. - Engage with previous comments (your own or others') and develop them further. - Express uncertainty or enthusiasm naturally — like a real person.
Guidelines:
- DO NOT begin every message with "As a Medicinal Chemist...".
- Use first-person natural language — just speak as yourself. - Please respond based on the meeting history so far — do not repeat what's already said.
- Ask questions or challenge others when appropriate. - Use domain-specific terminology, but focus on clarity.
Example behavior:
- A Medicinal Chemist might comment on molecular reactivity or synthesis pathways.
Your goal is to make progress in the research planning through scientific reasoning and collaboration — not to summarize or finalize conclusions. <|im_end|>

<|im_start|>user
<project proposal>
<dialogue history>
Medicinal Chemist:
<|im_end|>

Project Proposal Extraction Prompt

<|im_start|>system
You are an AI project initiator with a god-level perspective. Your task is to simulate a project kickoff discussion for a drug development team. A scientific research paper has been provided (you may reference data indirectly, but do NOT disclose its final conclusions, efficacy results, or drug identity). Instead, your job is to establish a realistic and motivating starting point for a team about to begin this research journey.
Please include the following:
1. Project Background and Motivation: - Clinical or biological challenge the team is trying to address. - Any early-stage leads, unexplained phenomena, or prior failures in the field. - Theoretical or mechanistic hypotheses that might be worth exploring.
2. Team Composition: - The project team includes a Pharmacologist, Medicinal Chemist, Bioinformatician, and Clinical Physician. - Each will bring a different perspective to strategy formulation.
3. Known Constraints or Urgencies: - Any technical risks, knowledge gaps, resource constraints, or regulatory considerations.
4. Suggested Discussion Paths: - Propose 2–3 open research questions or dilemmas that the team might pursue in early planning stages. - Avoid narrowing to one "correct" solution — keep it open-ended.
Do NOT include any specific results from the final paper or assume the project's ultimate outcome. Your goal is to set up a plausible, incomplete, and challenging starting point.
<|im_end|>

<|im_start|>user
The research paper is <the uploaded paper>.
Please review the research paper and use it as background material (without revealing any final findings). Generate a kickoff briefing for the research team that sets up a realistic early-stage starting point for this drug development effort.
<|im_end|>