THE REWARD HYPOTHESIS IS FALSE

ABSTRACT

The *reward hypothesis* is the hypothesis that "all of what we mean by goals and purposes can be well thought of as the maximisation of the expected value of the cumulative sum of a received scalar signal"(Sutton & Barto, 2018). In this paper, we will argue that this hypothesis is false. We will look at three natural classes of reinforcement learning tasks (multi-objective reinforcement learning, risk-averse reinforcement learning, and modal reinforcement learning), and then prove mathematically that these tasks cannot be expressed using any scalar, Markovian reward function. We thus disprove the reward hypothesis by providing many examples of tasks which are both natural and intuitive to describe, but which are nonetheless impossible to express using reward functions. In the process, we provide necessary and sufficient conditions for when a multi-objective reinforcement learning problem can be reduced to ordinary, scalar reward reinforcement learning. We also call attention to a new class of reinforcement learning problems (namely those we call "modal" problems), which have so far not been given any systematic treatment in the reinforcement learning literature.

1 INTRODUCTION

To use reinforcement learning (RL) to solve a task, it is necessary to first encode that task using a reward function, i.e. as a function from *state-action-next-state* triples to reals (Sutton & Barto, 2018). The *reward hypothesis* states that *any* task which a human might reasonably wish an RL agent to complete can be expressed using such a reward function. For many tasks it is very difficult to provide a reward function (Christiano et al., 2017), and a misspecified reward can often lead to behaviour that is both surprising and undesirable (Krakovna et al., 2020b). Nonetheless, the reward hypothesis holds that such a reward function always can be provided *in principle* for any task that a human could formulate. In this paper, we analyse the reward hypothesis mathematically. Moreover, we argue that our results *disprove* the reward hypothesis.

We will examine three classes of tasks, all of which are both intuitive to understand, and useful in practical situations. We will then show that *almost all* tasks in each of these three classes are impossible to express using ordinary reward functions. These classes thus constitute counterexamples to the reward hypothesis. Moreover, we also show that many of these problems *can* be solved effectively with RL, either by providing references to existing literature, or by providing an outline of a possible approach. This rules out the possibility that those problems which cannot be expressed using reward functions also are impossible to learn effectively.

The first class of problems we look at, in Section 2, is the single-policy version of multi-objective RL (MORL). In such a problem, the agent receives multiple reward signals, and the aim is to learn a single policy that achieves an optimal trade-off of those rewards according to some criterion (Roijers et al., 2013; Liu et al., 2015). For example, a single-policy MORL algorithm might attempt to maximise the rewards lexicographically (Skalse et al., 2022b). We will look at the question of which MORL problems can be reduced to ordinary RL, by providing a scalar reward function that induces the same preferences as the original MORL problem. Moreover, we will provide a complete solution to this problem, in the form of necessary and sufficient conditions. We find that this can *only* be done for MORL problems that correspond to a linear weighting of the rewards, which means that it cannot be done for the vast majority of all interesting MORL problems.

The next class of problems we look at, in Section 3, is risks-sensitive RL. There are many contexts where it is desirable to be risk averse. In economics, and related fields, this is often modelled using

utility functions $U : \mathbb{R} \to \mathbb{R}$ which are concave in some underlying quantity. Can the same thing be done with reward functions? Is it possible to take a reward function, and then create a version of that reward function which induces more risk-averse behaviour? We show that the answer is no – none of the standard risk-averse utility functions can be expressed using reward functions. This demonstrates another limitation in the expressive power of Markovian rewards.

The last class of problems we look at, in Section 4, is something we call *modal* tasks. These are tasks where the agent is evaluated not only based on what trajectories it generates, but also based on what it *could have done* along those trajectories. For example, consider the instruction "you should always be *able* to return to the start state". We provide a formalisation of such tasks, argue that there are many situations in which these tasks could be useful, and finally prove that these tasks cannot be formalised using also ordinary reward functions.

In Section 5, we discuss how to solve tasks from each of these classes using RL. We provide references to existing literature, and then sketch both an approach for learning a wide class of MORL problems, and an approach for learning a wide class of modal problems. Finally, in Section 6, we discuss the significance and limitations of our results, together with ways to extend them.

To clarify, this paper concerns the *reward hypothesis*, expressed by Richard Sutton as "all of what we mean by goals and purposes can be well thought of as the maximisation of the expected value of the cumulative sum of a received scalar signal" (Sutton & Barto, 2018). In other words, it is the hypothesis that any natural task can be expressed as a reward signal. This is not to be confused with what is sometimes referred to as the *reward-is-enough hypothesis* (Silver et al., 2021), which says that "the objective of maximising reward is enough to drive behaviour that exhibits most if not all attributes of intelligence that are studied in natural and artificial intelligence, including knowledge, learning, perception, social intelligence, language and generalisation". In other words, this hypothesis says that a system which maximises a reward function with sufficient competence in a sufficiently complex environment naturally would develop general intelligence. This is a distinct claim, which we will not discuss in this paper.

1.1 RELATED WORK

There has been a few recent papers which examine the expressivity of Markovian reward functions. The first of these is the work by Abel et al. (2021), who point to three different ways to formalise the notion of a "task" (namely, as a set of acceptable policies, as an ordering over policies, or as an ordering over trajectories). They then demonstrate that each of these classes contains at least one instance which cannot be expressed using a reward function (by using the fact that the set of all optimal policies forms a convex set, and the fact that the reward function is Markovian). They also provide algorithms which compute reward functions for these types of tasks, by constructing a linear program. We greatly extend their work by providing new results that are significantly stronger.

Another important paper is the work by Vamplew et al. (2022), who argue that there are many important aspects of intelligence which can be captured by MORL, but not by scalar RL. Like them, we also argue that MORL is a genuine extension of scalar RL, but our approach is quite different. They focus on the question of whether MORL or (scalar) RL is a better foundation for the development of general intelligence (considering feasibility, safety, and etc), and they provide qualitative arguments and biological evidence. By contrast, we are more narrowly focused on what incentive structures can be expressed by MORL and scalar RL, and our results are mathematical.

There is also other relevant work that is less strongly related. For example, Icarte et al. (2022) all point out that there are certain tasks which cannot be expressed using Markovian rewards, and propose a way extend their expressivity by augmenting the reward function with an automaton. Similar approaches have also been used by e.g. Hasanbeig et al. (2020); Hammond et al. (2021). Another example is the work by Skalse et al. (2022c), who show that there are certain relationships that are never satisfied by any pair of reward functions. This paper can also be seen as relating to earlier work on characterising what kinds of preference structures can be expressed using utility functions, such as the famous work by von Neumann & Morgenstern (1947), and other work in game theory and in decision theory.

There is a large literature on (the overlapping topics of) single-policy MORL, constrained RL, and risk-sensitive RL. Some notable examples of this work includes Achiam et al. (2017); Chow et al.

(2017); Miryoosefi et al. (2019); Tessler et al. (2019); Skalse et al. (2022b). This existing literature typically focuses on the creation of algorithms for solving particular MORL problems, and has so far not tackled the problem of characterising when MORL problems can be reduced to scalar RL. Modal RL has (to the best of our knowledge) never been discussed explicitly in the literature before. However, it relates to some existing work, such as side-effect avoidance (Krakovna et al., 2018; 2020a; Turner et al., 2020), and the work by Wang et al. (2020).

1.2 PRELIMINARIES

The standard RL setting is formalised using *Markov Decision Processes* (MDPs), which are tuples $\langle \mathcal{S}, \mathcal{A}, \tau, \mu_0, \mathbb{R}, \gamma \rangle$ where $\mathcal{S}$ is a set of states, $\mathcal{A}$ is a set of actions, $\tau : \mathcal{S} \times \mathcal{A} \rightsquigarrow \mathcal{S}$ is a transition function, μ_0 is an initial state distribution over $\mathcal{S}$, $R : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \rightsquigarrow \mathbb{R}$ a reward function, where $R(s, a, s')$ is the reward obtained if the agent moves from state s to s' by taking action a, and $\gamma \in (0, 1)$ is a discount factor. Here, $f : X \rightsquigarrow Y$ denotes a probabilistic mapping f from X to Y. A state is *terminal* if $\tau(s, a) = s$ and $R(s, a, s) = 0$ for all a. A *trajectory* ξ is a path $s_0, a_0, s_1 \ldots$ in an MDP that is possible according to μ_0 and τ. We use G to denote the *trajectory return function*, where $G(\xi) = \sum_{t=0}^{\infty} \gamma^t r_t$. A *policy* is a mapping $\pi : \mathcal{S} \rightsquigarrow \mathcal{A}$, and Π is the set of all policies. Given a policy π, its *value function* $V^\pi : \mathcal{S} \to \mathbb{R}$ is the function where $V^\pi(s)$ is the expected future discounted reward when following π from s, and its *Q-function* $Q^\pi : \mathcal{S} \times \mathcal{A} \to \mathbb{R} = \mathbb{E}_{S' \sim \tau(s,a)}[R(s, a, S') + \gamma \cdot V^\pi(S')]$. The *policy evaluation function* $J : \Pi \to \mathbb{R}$ is $J(\pi) = \mathbb{E}_{S_0 \sim \mu_0}[V^\pi(S_o)]$. If a policy maximises J, then we say that this policy is *optimal*. We denote optimal policies by $\pi^\star$, and their value function and Q-function by $V^\star$ and $Q^\star$. Moreover, given an MDP $\mathcal{M}$, we say that $\mathcal{M}$'s policy order is the ordering $\prec$ on Π induced by $\pi_1 \prec \pi_2 \iff J(\pi_1) < J(\pi_2)$ for all π_1, π_2. For a more comprehensive overview, see Sutton & Barto (2018).

In this paper, we will say that a reward function R is *trivial* if $J(\pi_1) = J(\pi_2)$ for all π_1, π_2. Moreover, we say that R_1 and R_2 are *equivalent* if $J_1(\pi_1) < J_1(\pi_2) \iff J_2(\pi_1) < J_2(\pi_2)$ for all π_1, π_2, and that they are *opposites* if $J_1(\pi_1) < J_1(\pi_2) \iff J_2(\pi_1) > J_2(\pi_2)$. for all π_1, π_2

MORL problems are formalised using *Multi-Objective MDPs* (MOMDPs), which are tuples $\langle \mathcal{S}, \mathcal{A}, \tau, \mu_0, \vec{R}, \gamma \rangle$. The only place where MOMDPs differ from MDPs are $\vec{R}$, which is a function $\vec{R} : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \rightsquigarrow \mathbb{R}^k$ that, for each transition s, a, s', returns k different rewards (for some k). We denote the reward function that returns the i'th component of $\vec{R}$ as R_i, and use $V_i^\pi, Q_i^\pi, J_i, G_i$, etc, to refer to its value functions, Q-functions, evaluation function, return function, etc. Since there may not be any single policy which maximises each component of $\vec{R}$, a MORL problem additionally needs a rule for how to combine and trade off each reward.

2 MULTI-OBJECTIVE REINFORCEMENT LEARNING

In this section, we examine the MORL setting. We first need a general definition of what a single-policy MORL problem is. Recall that a MOMDP $\langle \mathcal{S}, \mathcal{A}, \tau, \mu_0, \vec{R}, \gamma \rangle$ by itself has no one canonical objective to maximise. We therefore introduce the notion of a *MORL objective*:

Definition 1. *A **MORL objective** over k rewards is a function $\mathcal{O}$ that takes k policy evaluation functions $J_1 \ldots J_k$ and returns a (total) ordering $\prec_{\mathcal{O}}$ over the set of all policies Π.*

Given a MOMDP $\mathcal{M} = \langle \mathcal{S}, \mathcal{A}, \tau, \mu_0, \vec{R}, \gamma \rangle$, a MORL objective $\mathcal{O}$ gives us an ordering over Π that tells us when a policy is preferred over another. We use $\prec_{\mathcal{O}}^{\mathcal{M}}$ to denote the policy ordering that is obtained when we apply $\mathcal{O}$ to $\mathcal{M}$'s policy evaluation functions. For the purposes of this paper, we will not need to impose any further requirements on $\prec_{\mathcal{O}}$. For example, we will not insist that $\prec_{\mathcal{O}}$ must have a greatest element in Π, or that $\pi_1 \prec_O \pi_2$ whenever π_2 is a Pareto improvement over π_1, etc, even though a reasonable MORL objective presumably would have these properties. We next give a few examples of some interesting MORL objectives:

Definition 2. *Given $J_1 \ldots J_k$, the **LexMax** objective $\prec_{Lex}$ is given by $\pi_1 \prec_{Lex} \pi_2$ if and only if there is an $i \in \{1 \ldots m\}$ such that $J_i(\pi_1) < J_i(\pi_2)$, and $J_j(\pi_1) = J_j(\pi_2)$ for $j < i$.*

Definition 3. *Given $J_1 \ldots J_k$, the **MaxMin** objective $\prec_{Min}$ is given by $\pi_1 \prec_{Min} \pi_2 \iff \min_i J_i(\pi_1) < \min_i J_i(\pi_2)$.*

Definition 4. *Given $J_1 \ldots J_k$ and some $c_1 \ldots c_m \in \mathbb{R}$, the **MaxSat** objective $\prec_{Sat}$ is given by $\pi_1 \prec_{Sat} \pi_2$ if and only if the number of rewards that satisfy $J_i(\pi_1) \geq c_i$ is larger than the number of rewards that satisfy $J_i(\pi_2) \geq c_i$.*

Definition 5. *Given J_1, J_2 and some $c \in \mathbb{R}$, the **ConSat** objective $\prec_{Con}$ is given by $\pi_1 \prec_{Con} \pi_2$ if and only if either $J_1(\pi_1) < c$ and $J_1(\pi_1) < J_1(\pi_2)$, or if $J_1(\pi_1), J_1(\pi_2) \geq c$ and $J_2(\pi_1) < J_2(\pi_2)$.*

In other words, the LexMax objective has *lexicographic* preferences over $R_1 \ldots R_m$, so that policies are first ordered by their expected discounted R_1-reward, and then policies that obtain the same expected discounted R_1-reward are ordered by their expected discounted R_2-reward, and so on. The MaxMin objective orders policies by their *worst* performance according to any of $R_1 \ldots R_m$ (which could be used to obtain worst-case guarantees). The MaxSat objective only cares about whether a policy reaches a certain *threshold* for each reward, and ranks policies based on how many thresholds they reach. The ConSat objective wants to maximise J_2, but under the constraint that J_1 reaches a certain threshold. These MORL objectives are simply a short list of illustrative examples, demonstrating the flexibility of the framework. A few more examples are given in Appendix D. We next need to define what it means to *reduce* a MORL problem to a (scalar) RL problem:

Definition 6. *A MOMDP $\mathcal{M} = \langle \mathcal{S}, \mathcal{A}, \tau, \mu_0, \vec{R}, \gamma \rangle$ with objective $\mathcal{O}$ is **equivalent** to the MDP $\tilde{\mathcal{M}} = \langle \mathcal{S}, \mathcal{A}, \tau, \mu_0, \tilde{\mathbb{R}}, \gamma \rangle$ if and only if $\tilde{M}$'s policy order is $\prec_{\mathcal{O}}^{\mathcal{M}}$.*

Note that $\tilde{\mathcal{M}}$ must have the same states, actions, transition function, initial state distribution, and discount factor, as $\mathcal{M}$. This definition therefore says that $\mathcal{M}$ with $\mathcal{O}$ is equivalent to $\tilde{\mathcal{M}}$ if $\tilde{\mathcal{M}}$ is given by replacing $\vec{R} = \langle R_1 \ldots R_k \rangle$ with a single reward function $\tilde{R}$, and $\tilde{R}$ induces the same preferences between all policies as $\mathcal{O}(J_1 \ldots J_k)$. We can now derive necessary and sufficient conditions for when a MORL problem can be reduced to a scalar-reward RL problem.

Theorem 1. *If a MOMDP $\mathcal{M} = \langle \mathcal{S}, \mathcal{A}, \tau, \mu_0, \vec{R}, \gamma \rangle$ with objective $\mathcal{O}$ is equivalent to an MDP $\tilde{M} = \langle \mathcal{S}, \mathcal{A}, \tau, \mu_0, \tilde{\mathbb{R}}, \gamma \rangle$, then $\tilde{J}(\pi) = \sum_{i=1}^{k} w_i \cdot J_i(\pi)$ for some $w_1 \ldots w_k \in \mathbb{R}$. Moreover, $\mathcal{M}$ with $\mathcal{O}$ is also equivalent to the MDP with reward $R(s, a, s') = \sum_{i=1}^{k} w_i \cdot R_i(s, a, s')$.*

Proof. Suppose $\mathcal{M}$ with $\mathcal{O}$ is equivalent to an MDP $\tilde{\mathcal{M}} = \langle \mathcal{S}, \mathcal{A}, \tau, \mu_0, \tilde{\mathbb{R}}, \gamma \rangle$. First, let $m : \Pi \to \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$ be the function that maps each policy π to the $|\mathcal{S}||\mathcal{A}|$-dimensional vector where

$$m(\pi)[s, a] = \sum_{t=0}^{\infty} \gamma^t \mathbb{P}_{\xi \sim \pi}(S_t = s, A_t = a).$$

Moreover, for a reward function R, let $\vec{R} \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$ be the $|\mathcal{S}||\mathcal{A}|$-dimensional vector where

$$\vec{R}[s, a] = \mathbb{E}_{S' \sim \tau(s,a)}[R(s, a, S')].$$

Note that we now have that $J(\pi) = m(\pi) \cdot \vec{R}$, for any reward function R. Recall also that multiplication by an $|\mathcal{S}||\mathcal{A}|$-dimensional vector induces a linear function over $\mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$. This means that, for any reward function R, we can express its policy evaluation function $J : \Pi \to \mathbb{R}$ as $L \circ m$, where L is a linear function. In particular, $\tilde{J} = \tilde{L} \circ m$, and $J_i = L_i \circ m$ for each of $R_i \in \vec{R}$.

From the definition of MORL objectives, we have that $\tilde{J}(\pi)$ is a function of $J_1(\pi) \ldots J_k(\pi)$. This, in turn, means that $\tilde{L}(v)$ is a function of $L_1(v) \ldots L_k(v)$, for any $v \in \text{Im}(m)$. Let M be the $(|S||A| \times k)$-dimensional matrix that maps each vector $v \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$ to $\langle L_1(v), \ldots, L_k(v) \rangle$ (in other words, the matrix whose rows are $\vec{R}_1 \ldots \vec{R}_k$). Since $\tilde{L}(v)$ is a function of $L_1(v) \ldots L_k(v)$, we have that $\tilde{L}$ can be expressed as $f \circ M$ for some function f. Since $\tilde{L}$ is a linear function, and since M is a linear transformation, we that f must be a linear function as well. This means that there are $w_1 \ldots w_k \in \mathbb{R}^k$ such that $f(x) = \sum_{i=1}^{k} w_i \cdot x_i$, which implies that $\tilde{L}(v) = \sum_{i=1}^{m} w_i \cdot L_i(v)$, and further that $\tilde{J}(\pi) = \sum_{i=1}^{k} w_i \cdot J_i(\pi)$. This completes the first part.

Next, let $R(s, a, s') = \sum_{i_1}^{k} w_i \cdot R_i(s, a, s')$. Straightforward algebra shows that $J(\pi) = \sum_{i=1}^{k} w_i \cdot J_i(\pi)$. Now, since $J = \tilde{J}$, and since $\mathcal{M}$ with $\mathcal{O}$ is equivalent to $\tilde{\mathcal{M}}$, we have that $\mathcal{M}$ with $\mathcal{O}$ is equivalent to the MDP with reward R. This completes the second part. $\qquad\square$

This theorem effectively tells us that *only linear* MORL objectives can be represented using scalar-reward RL! This imposes a harsh limitation on what kinds of tasks can be encoded using scalar rewards. Theorem 1 also has the following corollary, which is useful for demonstrating when some MORL objective cannot be expressed using scalar reward functions. Given an ordering $\prec$ over Π dependent on some evaluation functions $J_1 \dots J_k$, we say that a function $U : \Pi \to \mathbb{R}$ *represents* $\prec$ if $U(\pi_1) < U(\pi_2) \iff \pi_1 \prec \pi_2$. We say that U is a *linear representation* if $U(\pi) = f(\sum_{i=1}^{k} w_i \cdot J_i(\pi))$ for some $w_1 \dots w_k \in \mathbb{R}$ and some f that is strictly monotonic.

Corollary 1. *If $\mathcal{O}(J_1 \dots J_k)$ has a non-linear representation U, and $\mathcal{M}$ is a MOMDP whose J-functions are $J_1 \dots J_k$, then $\mathcal{M}$ with $\mathcal{O}$ is not equivalent to any MDP.*

Proof. Assume for contradiction that $\mathcal{M}$ with $\mathcal{O}$ is equivalent the MDP $\tilde{\mathcal{M}} = \langle \mathcal{S}, \mathcal{A}, \tau, \mu_0, \tilde{\mathbb{R}}, \gamma \rangle$. Then $\tilde{J}$ represents $\mathcal{O}(J_1 \dots J_k)$, and this in turn means that U must be strictly monotonic in $\tilde{J}$. Moreover, Theorem 1 implies that $\tilde{J} = \sum_{i=0}^{k} w_i \cdot J_i$ for some $w_1 \dots w_k \in \mathbb{R}^k$. However, this contradicts our assumptions. $\square$

Therefore, we can prove that $\mathcal{M}$ with $\mathcal{O}$ is not equivalent to any MDP by finding a non-linear representation of $\prec_{\mathcal{O}}^{\mathcal{M}}$. We will now show that none of the MORL objectives given in Definition 2-5 can be expressed using single-objective RL, except in a few degenerate edge cases.

Theorem 2. *There is no MDP equivalent to $\mathcal{M}$ with `LexMax`, as long as $\mathcal{M}$ has at least two reward functions that are neither trivial, equivalent, or opposites.*

Proof. Suppose $\mathcal{M}$ with `LexMax` is equivalent to $\tilde{\mathcal{M}} = \langle \mathcal{S}, \mathcal{A}, \tau, \mu_0, \tilde{\mathbb{R}}, \gamma \rangle$. Let i be the smallest number such that R_i is non-trivial, and let j be the smallest number greater than i such that R_j is non-trivial, and not equivalent to or opposite of R_i. Then there are π_1, π_2 such that $J_i(\pi_1) = J_i(\pi_2)$ and $J_j(\pi_1) < J_j(\pi_2)$, which means that $\pi_1 \prec_{\text{Lex}}^{\mathcal{M}} \pi_2$. Moreover, since $\tilde{J}$ represents $\prec_{\text{Lex}}^{\mathcal{M}}$, it follows that there are no π, π' such that $J_i(\pi) < J_i(\pi')$ and $\tilde{J}(\pi) > \tilde{J}(\pi')$. Then Theorem 1 in Skalse et al. (2022c) implies that R_i is equivalent to $\tilde{R}$. However, then $\tilde{J}(\pi_1) = \tilde{J}(\pi_2)$, which means that $\tilde{J}$ cannot represent $\prec_{\text{Lex}}^{\mathcal{M}}$. $\square$

Theorem 3. *There is no MDP equivalent to $\mathcal{M}$ with `MaxMin`, unless $\mathcal{M}$ has a reward function R_i such that $J_i(\pi) \leq J_j(\pi)$ for all $j \in \{1 \dots k\}$ and all π.*

Proof. $\mathcal{O}_{\text{Min}}^{\mathcal{M}}$ is represented by the function $U(\pi) = \min_i J_i(\pi)$. Moreover, if $\mathcal{M}$ has no reward function R_i such that $J_i(\pi) \leq J_j(\pi)$ for all $j \in \{1 \dots k\}$ and all π then this representation is non-linear. Corollary 1 then implies that $\mathcal{M}$ with `MaxMin` is not equivalent to any MDP. $\square$

Theorem 4. *There is no MDP equivalent to $\mathcal{M}$ with `MaxSat`, as long as $\mathcal{M}$ has at least one reward R_i where $J_i(\pi_1) < c_i$ and $J_i(\pi_2) \geq c_i$ for some $\pi_1, \pi_2 \in \Pi$.*

Proof. Note that `MaxSat`$(\mathcal{M})$ is represented by the function $U(\pi) = \sum_{i=1}^{k} \mathbb{1}[J_i(\pi) \geq c_i]$, where $\mathbb{1}[J_i(\pi) \geq c_i]$ is the function that is equal to 1 when $J_i(\pi) \geq c_i$, and 0 otherwise. Moreover, U is not strictly monotonic in any function that is linear in $J_1 \dots J_k$. Corollary 1 thus implies that $\mathcal{M}$ with `MaxSat` is not equivalent to any MDP. $\square$

Theorem 5. *There is no MDP equivalent to $\mathcal{M}$ with `ConSat`, unless either R_1 and R_2 are equivalent, or $\max_{\pi} J_1(\pi) \leq c$.*

Proof. $\mathcal{O}_{\text{Con}}^{\mathcal{M}}$ is represented by $U(\pi) = \{J_1(\pi)$ if $J_1(\pi) \leq c$, else $J_2(\pi) - \min_{\pi} J_2(\pi) + c\}$. Moreover, this representation is non-linear, unless either R_1 and R_2 are equivalent, or $\max_{\pi} J_1(\pi) \leq c$. Corollary 1 then implies that $\mathcal{M}$ with `ConSat` is not equivalent to any MDP. $\square$

Theorem 2-5 show that none of the MORL objectives given in Definition 2-5 can be expressed using single-objective RL, except in a few degenerate cases where those MORL objectives are uninteresting. This demonstrates that there is no satisfactory way to reduce MORL problems to scalar-reward RL (and hence that scalar RL is unable to express many natural task specifications).

3 RISK-SENSITIVE REINFORCEMENT LEARNING

The next area we will look at is that of *risk-sensitive* reinforcement learning. An ordinary RL agent tries to maximise the *expectation* of its reward function. However, there are many cases where it is natural to want the agent to be *risk-averse*. In economics, risk-aversion is typically modelled by using utility functions $U(c)$ that are concave in some relevant quantity c (which might be money, for example). A natural question is then whether a similar trick may be used with reward functions? That is, given a reward function R_1 and a concave function f, can we construct a reward function R_2 such that $G_2(\xi) = f(G_1(\xi))$ for all trajectories ξ? We will examine this question.

Some of the most common risk-averse utility functions includes *exponential utility*, *isoelastic utility*, and *quadratic utility*. The exponential utility function is given by $U(c) = -e^{\alpha c}$, where $\alpha > 0$ is a parameter controlling the degree of risk aversion. The isoelastic utility function is given by $U(c) = c^{1-\alpha}$, for $\alpha > 0, \alpha \neq 1$, or by $U(c) = \ln(c)$ (corresponding to the case when $\alpha = 1$). The quadratic utility function is given by $U(c) = c - \alpha c^2$, where $\alpha > 0$. Since this function is decreasing for sufficiently large c, its domain is typically restricted to $(-\infty, 1/2\alpha]$. We will examine each of these, and show that none of them can be expressed using reward functions.

In this section, we will consider the domain of G to be the set of all coherent trajectories, *not* the set of trajectories which are possible under some transition function τ. In other words, we consider the set of all trajectories to be $(\mathcal{S} \times \mathcal{A})^\omega$. The reason for this is that we do not want to presume any prior knowledge of the environment. If we restrict the set of trajectories we consider, then some risk-averse utility functions can become possible to express (consider the case of a tree-shaped MDP, for example). Finally, we will say that R is *constant* if it has a constant value for all s, a, s'.

To prove our results, we will make use of three lemmas. The proofs of these lemmas are fairly long, but not very illuminating, and so we have relegated them to Appendix A.

Lemma 1. *If R is non-constant, then for any state s there exists trajectories $\zeta_1, \zeta_2, \zeta_3$ starting in s such that $G(\zeta_1) \neq G(\zeta_2)$, $G(\zeta_2) \neq G(\zeta_3)$, and $G(\zeta_1) \neq G(\zeta_3)$.*

Lemma 2. *If $G_2(\xi) = f(G_1(\xi))$ for all ξ and some f, then for any transition $\langle s, a, s' \rangle$ and any trajectory ζ starting in s', $R_2(s, a, s') = f(R_1(s, a, s') + \gamma G_1(\zeta)) - \gamma f(G_1(\zeta))$.*

Lemma 3. *For any non-constant reward R_1 and any f that is injective on $\mathrm{range}(G_1)$, if for any $y \in \mathrm{range}(R_1)$ and any $\gamma \in (0, 1)$ there are at most two distinct x_1, x_2 such that $f(y + \gamma x_1) - \gamma f(x_1) = f(y + \gamma x_2) - \gamma f(x_2)$ then there is no reward R_2 such that $G_2(\xi) = f(G_1(\xi))$ for all ξ.*

Using these lemmas, we can now derive our main results:

Theorem 6. *For any non-constant reward function R_1 and any constant $\alpha \neq 0$, there is no reward function R_2 such that $G_2(\xi) = -e^{\alpha G_1(\xi)}$ for all valid trajectories ξ.*

Proof. With $f(x) = -e^{\alpha x}$, the expression in Lemma 3 becomes $-e^{\alpha(y+\gamma x)} + \gamma e^{\alpha x}$. The derivative of this expression with respect to x is $\gamma\alpha(-e^{\alpha(y+\gamma x)} + e^{\alpha x})$, which has only one root when $\gamma \neq 0$ and $\alpha \neq 0$. This means that there can be at most two distinct values x_1, x_2 such that $-e^{\alpha(y+\gamma x_1)} + \gamma e^{\alpha x_1} = -e^{\alpha(y+\gamma x_2)} + \gamma e^{\alpha x_2}$. Since $-e^{\alpha x}$ is injective, we can thus apply Lemma 3, which completes the proof. $\square$

Theorem 7. *For any non-constant reward function R_1 and any constant $\alpha > 0$, $\alpha \neq 1$, there is no reward function R_2 such that $G_2(\xi) = G_1(\xi)^{1-\alpha}$ for all valid trajectories ξ.*

Proof. With $f(x) = x^{1-\alpha}$, the expression in Lemma 3 becomes $(y + \gamma x)^{(1-\alpha)} - \gamma x^{1-\alpha}$. The derivative of this expression with respect to x is $\gamma(\alpha - 1)(x^{-\alpha} - (\gamma x + y)^{-\alpha})$, which has only one root when $\gamma \neq 0$ and $\alpha \notin \{0, 1\}$. This means that there can be at most two distinct values x_1, x_2 such that $(y + \gamma x_1)^{(1-\alpha)} - \gamma x_1^{1-\alpha} = (y + \gamma x_2)^{(1-\alpha)} - \gamma x_2^{1-\alpha}$. Since $x^{1-\alpha}$ is injective, we can thus apply Lemma 3, which completes the proof. $\square$

Theorem 8. *For any non-constant reward function R_1, there is no reward function R_2 such that $G_2(\xi) = \ln(G_1(\xi))$ for all valid trajectories ξ.*

Proof. With $f(x) = \ln(x)$, the expression in Lemma 3 becomes $\ln(y+\gamma x)-\gamma \ln(x)$. The derivative of this expression with respect to x is $\gamma(1/(y + \gamma x) - 1/x)$, which has only one root when $\gamma \neq 0$. Since $\ln(x)$ is injective, we can thus apply Lemma 3, which completes the proof. □

Theorem 9. *For any non-constant reward function R_1 and any $\alpha > 0$ where $\max_\xi G_1(\xi) \leq \frac{1}{2\alpha}$, there is no reward function R_2 such that $G_2(\xi) = G_1(\xi) - \alpha G_1(\xi)^2$ for all ξ.*

Proof. With $f(x) = x - \alpha x^2$, the expression in Lemma 3 becomes $y + \gamma x - \alpha(y + \gamma x)^2$. This is a second-degree polynomial, which means that there can be at most two distinct values x_1, x_2 such that $y + \gamma x_1 - \alpha(y + \gamma x_1)^2 = y + \gamma x_2 - \alpha(y + \gamma x_2)^2$. Moreover, if $\max_\xi G_1(\xi) \leq \frac{1}{2\alpha}$ then $f(x) = x - \alpha x^2$ is injective on $\mathrm{range}(G_1)$. We can thus apply Lemma 3. □

We can thus see that Lemma 3 is quite flexible. It allows us to rule out many modifications to G as impossible, including all the standard risk-averse utility functions. It would be desirable to strengthen these results, and provide necessary and sufficient conditions for when it is possible to construct a reward R_2 such that $G_2(\xi) = f(G_1(\xi))$ for some function f and some (non-constant) reward R_1. We consider this to be an important question for further work.

4 MODAL REINFORCEMENT LEARNING

The final class of tasks we will examine is one which we have decided to refer to as *modal* tasks. Before we give a formal definition of this class, we will first provide some intuition. In analytic philosophy, a distinction is made between *categorical* facts and *modal* facts. In short, categorical facts only concern what is true in actuality, whereas modal facts concern what must be true, could have been true, or cannot be true, etc. For example, it is a categorical fact that the Eiffel Tower is brown, and a modal fact that it *could have had* a different colour. It is (arguably) a categorical fact that the number 3 is prime, and a modal fact that it *could not have been* otherwise. To give another example, there is a difference between stating that *nothing can travel faster than light* and that *nothing does travel faster than light* – the former statement, which is modal, is stronger than the latter, which is categorical. One can further distinguish between different kinds of possibility (e.g. logical vs physical possibility, etc), and discussions about modality also involves topics such as *causality* and *counterfactuals*, etc. A complete treatment of this subject is far beyond the scope of this paper, but for an overview, see e.g. Menzel (2021).

Modality does of course relate to *modal logic*, but it also relates to *temporal logic*. In particular, computational tree logic (CTL), and its extensions, can express many modal statements.

The intuition behind this section is that a reward function always is expressed in terms of categorical facts, whereas many tasks are naturally expressed in terms of modal facts. For example, consider an instruction such as "you should always be *able* to return to the start state". This instruction seems quite reasonable, but it is not obvious how to translate it into a reward function. Note that this instruction is not telling the agent to *actually* return to the start state, it merely says that it should maintain the *ability* to do so. To give a few other examples, consider instructions such as "you should never enter a state from which it is *possible* to quickly enter an unsafe state", "you should always be *able* to press the emergency shutdown button", or "you should never enter a state where you would be *unable* to receive a feedback signal". These instructions all seem very reasonable, and they are expressed in terms of what should be *possible* or *impossible* along the trajectory of the agent, rather than in terms of what in fact occurs along that trajectory. Given this background motivation, we can now give a formal definition of modal tasks:

Definition 7. *Given a set of states $\mathcal{S}$ and a set of actions $\mathcal{A}$, a **modal reward function** $R^\diamond$ is a function $R^\diamond : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \times (\mathcal{S} \times \mathcal{A} \rightsquigarrow \mathcal{S}) \to \mathbb{R}$ which takes two states $s, s' \in \mathcal{S}$, an action $a \in \mathcal{A}$, and a transition function τ over $\mathcal{S}$ and $\mathcal{A}$, and returns a real number.*

$R^\diamond(s, a, s', \tau)$ is the reward that is obtained when transitioning from state s to s' using action a in an environment whose transition function is τ. Here we allow $R^\diamond$ an unrestricted dependence on τ, to make our results as general as possible, even if a practical algorithm for solving modal tasks presumably would require restrictions on what this dependence can look like (see Appendix E). As usual, $R^\diamond$ then induces a Q-function $Q^\diamond$, value function $V^\diamond$, and evaluation function $J^\diamond$, etc. Modal reward functions can be used to express all the instructions we gave above. We say that a

modal reward $R^\diamond$ and an ordinary reward R are *contingently equivalent* given a transition function τ if $J^\diamond$ and J induce the same ordering of policies given τ, and that they are *robustly equivalent* if $J^\diamond$ and J induce the same ordering of policies for all τ. We use $R_\tau^\diamond$ to denote the reward function $R_\tau^\diamond(s, a, s') = R^\diamond(s, a, s', \tau)$. We will also use the following definition:

Definition 8. *A modal reward function $R^\diamond$ is **trivial** if there is a reward function R such that for all τ, R and $R_\tau^\diamond$ have the same policy ordering under τ.*

The intuition here is that a trivial modal reward function does not actually depends on τ in any important sense. Note that this is *not* necessarily to say that $R_\tau^\diamond = R$ for all τ. For example, it could be the case that $R_\tau^\diamond$ is a *scaled* version of R, or that $R_\tau^\diamond$ and R differ by *potential shaping* Ng et al. (1999), or that $R_\tau^\diamond$ is modified in a way such that $\mathbb{E}_{S' \sim \tau(s,a)}[R_\tau^\diamond(s, a, S')] = \mathbb{E}_{S' \sim \tau(s,a)}[R(s, a, S')]$, since none of these differences affect the policy ordering.

Theorem 10. *For any modal reward $R^\diamond$ and any transition function τ, there exists a reward function R that is contingently equivalent to $R^\diamond$ given τ. Moreover, unless $R^\diamond$ is trivial, there is no reward function that is robustly equivalent to $R^\diamond$.*

Proof. This is straightforward. For the first part, simply let $R(s, a, s') = R^\diamond(s, a, s', \tau)$. The second part is immediate from the definition of trivial modal reward functions. $\square$

In other words, every modal task can be expressed with ordinary reward function in each particular environment, but no reward function expresses a (non-trivial) modal task in all environments. Is this enough? We argue that it is not, because the construction of $R_\tau^\diamond$ will invariably be laborious, and require detailed knowledge of the environment. For example, consider the task "you should always be able to return to the start state"; here, constructing $R_\tau^\diamond$ would amount to manually enumerating all the states from which the start state is reachable. This is very much against the spirit of reinforcement learning, where much of the point is that we want to be able to specify tasks which can be pursued in *unknown* environments. In short, a method which requires a model of the environment is arguably not a reinforcement learning method. We thus argue that reward functions are unable to capture modal tasks in a satisfactory way.

One remaining question might be why one would want to express instructions for reinforcement learning agents in terms of modal properties. After all, what benefit is there to the instruction "never enter a state from which it is possible to quickly enter an unsafe state" over the instruction "never enter an unsafe state"? One reason is that the former task might lead to behaviour that is more robust to changes in the environment. For example, if an RL agent is trained in a simulated environment, and deployed in the real world, then it seems like it would be preferable to tell the agent to avoid *risky* states, rather than *unsafe* states, since imperfections in the simulation could lead to an underestimation of the risk involved. Another example is the existing work on avoiding side effects (Krakovna et al., 2018; 2020a; Turner et al., 2020), which it is natural to express in modal terms. This work can be viewed as being aimed at making the behaviour of an RL agent more robust to misspecification of the reward function.

5 Solving "Inexpressible" Tasks

We have pointed to three classes of tasks which cannot be expressed using reward functions (namely multi-objective tasks, risk-sensitive tasks, and modal tasks). A natural next question is whether these tasks *could* be solved using RL, or whether only the tasks which correspond to Markovian reward functions can be effectively learnt? We discuss this issue below.

In short, it is possible to design RL algorithms for tasks in each of these categories. Multi-objective reinforcement learning is well-explored, with many existing algorithms (see Section 1.1). Most of these algorithms are designed to solve a specific MORL objective; for example, Skalse et al. (2022b) solve the LexMax objective, and Tessler et al. (2019) solve the ConSat objective. There is (to the best of our knowledge) not yet any algorithm for the solving e.g. the MaxMin objective, but there is no good reason to believe that such an algorithm could not be made. Similarly, there are existing algorithms for risk-sensitive RL (e.g. Chow et al. (2017)), and even algorithms that solve certain modal tasks (Krakovna et al., 2018; 2020a; Turner et al., 2020; Wang et al., 2020).

It should also be possible to design algorithms which can flexibly solve many different tasks from the classes we have discussed (instead of having to be designed for just one particular task). For example, suppose a MORL objective can be represented by a function $U : \mathbb{R}^k \to \mathbb{R}$, such that $\pi_1 \prec \pi_2$ when $U(J_1(\pi_1) \dots J_k(\pi_1)) < U(J_1(\pi_2) \dots J_k(\pi_2))$, and that U is *differentiable*. We give a few examples of such objectives in Appendix D, including e.g. a "soft" version of MaxMin. With such an objective, if we have a policy π that is differentiable with respect to some parameters θ, then it should be possible to compute the gradient of $U(J_1(\pi) \dots J_k(\pi))$ with respect to θ, and then use a policy gradient method to increase U. This means that it should be possible to design an actor-critic algorithm which can solve any differentiable MORL objective. We consider the development and evaluation of such methods to be a promising direction for further work.

We outline a possible approach for solving a wide class of modal tasks in Appendix E.

6 Discussion

In this paper, we have studied the veracity of the reward hypothesis, by examining the ability of Markovian reward functions to express different kinds of problems. We have looked at three classes of tasks; multi-objective tasks, risk-sensitive tasks, and modal tasks, and found that reward functions are unable to express most of the tasks in each of these three classes. We have also provided necessary and sufficient conditions for when a multi-objective RL problem can be expressed using a single reward function (which, as it turns out, is almost never), and also drawn attention to a class of tasks which have just barely been explored previously (namely modal tasks). Finally, we have also shown that many of these problems still can be solved with RL, and even outlined some methods for how to extend these solutions, which rules out the possibility that only tasks which can be expressed using reward functions can be effectively learnt.

We argue that our results show that the reward hypothesis is false – there are tasks, which are natural to state and intuitive to understand, and which can be solved with RL methods, but which cannot be expressed using scalar Markovian reward functions. A possible response to this is of course that the reward hypothesis is not meant to refer to *Markovian* rewards, and that a reward function which depends on the entire past trajectory (i.e., with the type signature $(\mathcal{S} \times \mathcal{A})^* \times \mathcal{S} \to \mathbb{R}$) can express any tasks. However, this does not seem to be the spirit of the reward hypothesis, given the vast amount of methods, algorithms, and research, that presupposes Markovian rewards.

There are several ways to extend our work. First of all, while we have given many examples of tasks which cannot be formalised using Markovian reward functions, we have not given a general characterisation of what reward functions are or are not able to express. It would be very desirable to have a set of intuitive necessary and sufficient conditions, which exactly describe those policy orderings that can be expressed using reward functions, similar to what the VNM axioms provide in the case of utility functions. We outline some initial steps towards such a characterisation in Appendix B. Note that the VNM axioms themselves cannot be directly applied to RL, see Appendix C. Additionally, it would also be desirable to provide necessary and sufficient conditions for when it is possible to construct a reward R_2 such that $G_2(\xi) = f(G_1(\xi))$ for some function f and some (non-constant) reward R_1, as we discussed at the end of Section 3.

Our work also provides a strong motivation for developing more RL algorithms that can learn tasks which cannot be expressed using Markovian reward functions. There are several ways to to this. In section 5, we outline an approach for learning any differentiable MORL objective using policy gradients, and in Appendix E, we outline an approach for learning a large class of modal tasks. It would also be very interesting to explore more general ways to express RL tasks, and study their expressivity. For example, it would be interesting to know if (and to what extent) MORL tasks can be expressed using reward machines (Icarte et al., 2022), and similar.

References

David Abel, Will Dabney, Anna Harutyunyan, Mark K. Ho, Michael L. Littman, Doina Precup, and Satinder Singh. On the expressivity of markov reward, 2021. URL https://arxiv.org/abs/2111.00876.

Joshua Achiam, David Held, Aviv Tamar, and Pieter Abbeel. Constrained policy optimization. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, ICML'17, pp. 22–31. JMLR.org, 2017.

Yinlam Chow, Mohammad Ghavamzadeh, Lucas Janson, and Marco Pavone. Risk-constrained reinforcement learning with percentile risk criteria. *Journal of Machine Learning Research*, 18(1): 6070–6120, 2017.

Paul Christiano, Jan Leike, Tom B. Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences, 2017. URL `https://arxiv.org/abs/1706.03741`.

L. Hammond, A. Abate, J. Gutierrez, and M. Wooldridge. Multi-agent reinforcement learning with temporal logic specifications. In *Proceedings of the 20th International Conference on Autonomous Agents and MultiAgent Systems*, pp. 583–592, 2021.

M. Hasanbeig, D. Kroening, and A. Abate. Deep reinforcement learning with temporal logics. In *Proceedings of FORMATS, LNCS 12288*, pp. 1–22, 2020.

Rodrigo Toro Icarte, Toryn Q. Klassen, Richard Valenzano, and Sheila A. McIlraith. Reward machines: Exploiting reward function structure in reinforcement learning. *Journal of Artificial Intelligence Research*, 73:173–208, jan 2022. doi: 10.1613/jair.1.12440.

Victoria Krakovna, Laurent Orseau, Ramana Kumar, Miljan Martic, and Shane Legg. Penalizing side effects using stepwise relative reachability, 2018. URL `https://arxiv.org/abs/1806.01186`.

Victoria Krakovna, Laurent Orseau, Richard Ngo, Miljan Martic, and Shane Legg. Avoiding side effects by considering future tasks, 2020a. URL `https://arxiv.org/abs/2010.07877`.

Victoria Krakovna, Jonathan Uesato, Vladimir Mikulik, Matthew Rahtz, Tom Everitt, Ramana Kumar, Zac Kenton, Jan Leike, and Shane Legg. Specification gaming: the flip side of ai ingenuity, Apr 2020b. URL `https://deepmindsafetyresearch.medium.com/specification-gaming-the-flip-side-of-ai-ingenuity-c85bdb0deeb4`.

C. Liu, X. Xu, and D. Hu. Multiobjective reinforcement learning: A comprehensive overview. *IEEE Transactions on Systems, Man, and Cybernetics: Systems*, 45(3):385–398, 2015.

Christopher Menzel. Possible Worlds. In Edward N. Zalta (ed.), *The Stanford Encyclopedia of Philosophy*. Metaphysics Research Lab, Stanford University, Fall 2021 edition, 2021.

Sobhan Miryoosefi, Kianté Brantley, Hal Daumé III, Miroslav Dudík, and Robert E. Schapire. Reinforcement learning with convex constraints. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems*, pp. 14070–14079, 2019.

Andrew Y Ng, Daishi Harada, and Stuart Russell. Policy invariance under reward transformations: Theory and application to reward shaping. In *Proceedings of the Sixteenth International Conference on Machine Learning*, pp. 278–287, Bled, Slovenia, 1999. Morgan Kaufmann Publishers Inc.

D. M. Roijers, P. Vamplew, S. Whiteson, and R. Dazeley. A survey of multi-objective sequential decision-making. *Journal of Artificial Intelligence Research*, 48:67–113, 10 2013. ISSN 1076-9757. doi: 10.1613/jair.3987. URL `http://dx.doi.org/10.1613/jair.3987`.

David Silver, Satinder Singh, Doina Precup, and Richard S. Sutton. Reward is enough. *Artificial Intelligence*, 299:103535, 2021. ISSN 0004-3702. doi: https://doi.org/10.1016/j.artint.2021.103535. URL `https://www.sciencedirect.com/science/article/pii/S0004370221000862`.

Satinder Singh, Tommi Jaakkola, Michael L. Littman, and Csaba Szepesvári. Convergence results for single-step on-policy reinforcement-learning algorithms. *Machine Learning*, 38:287–308, 2000.

Joar Skalse, Matthew Farrugia-Roberts, Stuart Russell, Alessandro Abate, and Adam Gleave. Invariance in policy optimisation and partial identifiability in reward learning, 2022a. URL https://arxiv.org/abs/2203.07475.

Joar Skalse, Lewis Hammond, Charlie Griffin, and Alessandro Abate. Lexicographic multi-objective reinforcement learning. In Lud De Raedt (ed.), *Proceedings of the Thirty-First International Joint Conference on Artificial Intelligence, IJCAI-22*, pp. 3430–3436. International Joint Conferences on Artificial Intelligence Organization, 7 2022b. doi: 10.24963/ijcai.2022/476. URL https://doi.org/10.24963/ijcai.2022/476. Main Track.

Joar Skalse, Niki Howe, Krasheninnikov Dima, and David Krueger. Defining and characterizing reward gaming. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems*, 2022c.

Richard S. Sutton and Andrew G. Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Chen Tessler, Daniel J. Mankowitz, and Shie Mannor. Reward constrained policy optimization. In *Proceedings of the 7th International Conference on Learning Representations*, 2019.

Alex Turner, Neale Ratzlaff, and Prasad Tadepalli. Avoiding side effects in complex environments. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 21406–21415. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/f50a6c02a3fc5a3a5d4d9391f05f3efc-Paper.pdf.

Peter Vamplew, Benjamin J. Smith, Johan Källström, Gabriel Ramos, Roxana Rădulescu, Diederik M. Roijers, Conor F. Hayes, Fredrik Heintz, Patrick Mannion, Pieter J. K. Libin, Richard Dazeley, and Cameron Foale. Scalar reward is not enough: a response to silver, singh, precup and sutton (2021). *Autonomous Agents and Multi-Agent Systems*, 36(2):41, Jul 2022. ISSN 1573-7454. doi: 10.1007/s10458-022-09575-5. URL https://doi.org/10.1007/s10458-022-09575-5.

J. von Neumann and O. Morgenstern. *Theory of games and economic behavior*. Princeton University Press, 1947.

Yu Wang, Nima Roohi, Matthew West, Mahesh Viswanathan, and Geir E. Dullerud. Statistically model checking pctl specifications on markov decision processes via reinforcement learning. In *2020 59th IEEE Conference on Decision and Control (CDC)*, pp. 1392–1397, 2020. doi: 10.1109/CDC42340.2020.9303982.