GENERATING FURRY CARS: DISENTANGLING OBJECT SHAPE & APPEARANCE ACROSS MULTIPLE DOMAINS

ABSTRACT

We consider the novel task of learning disentangled representations of object shape and appearance *across multiple domains* (e.g., dogs and cars). The goal is to learn a generative model that learns an intermediate distribution, which borrows a subset of properties from each domain, enabling the generation of images that did not exist in any domain exclusively. This challenging problem requires an accurate disentanglement of object shape, appearance, and background from each domain, so that the appearance and shape factors from the two domains can be interchanged. We augment an existing approach that can disentangle factors within a single domain but struggles to do so across domains. Our key technical contribution is to represent object appearance with a differentiable histogram of visual features, and to optimize the generator so that two images with the same latent appearance factor but different latent shape factors produce similar histograms. On multiple multi-domain datasets, we demonstrate our method leads to accurate and consistent appearance and shape transfer across domains.

1 INTRODUCTION

Humans possess the incredible ability of being able to combine properties from multiple image distributions to create entirely new visual concepts. For example, Lake et al. (2015) discussed how humans can parse different object parts (e.g., wheels of a car, handle of a lawn mower) and combine them to conceptualize novel object categories (a scooter). Fig. 1 illustrates another example from a different angle; it is easy for us humans to imagine how the brown car would look if it's appearance were borrowed from the blue and red bird. To model a similar ability in machines, a precise disentanglement of shape and appearance features, and the ability to combine them across different domains are needed. In this work, we seek to develop a framework to do just that.

Disentangling the factors of variation in visual data has received significant attention (Chen et al., 2016; Higgins et al., 2017; Denton & Birodkar, 2017; Singh et al., 2019), in particular with advances in generative models (Goodfellow et al., 2014; Radford et al., 2016; Zhang et al., 2018; Karras et al., 2019; Brock et al., 2019). The premise behind learning disentangled representations is that an image can be thought of as a function of, say two independent latent factors, such that each controls only one human interpretable property (e.g., shape vs. appearance). The existence of such representations enables combining latent factors from two different source images to create a new one, which has properties of both. Prior generative modeling work (Hu et al., 2018; Singh et al., 2019; Li et al., 2020) explore a part of this idea, where the space of latent factors being combined is limited to one domain (e.g., combining a sparrow's appearance with a duck's shape within the domain of birds; I_{AA} in Fig. 1), a scenario which we refer to as *intra-domain* disentanglement of latent factors. This work, focusing on shape and appearance as factors, generalizes this idea to *inter-domain* disentanglement: combining latent factors from different domains (e.g., appearance from birds, shape from cars) to create a new breed of images which does not exist in either domain (I_{AB} in Fig. 1).

The key challenge to this problem is that there is no ground-truth distribution for the hybrid visual concept that spans the two domains. Due to this, directly applying a single domain disentangled image generation approach to the multi-domain setting does not work, as the hybrid concept would be considered out of distribution (we provide more analysis in Sec. 3). Despite the lack of ground-truth, as humans, we would deem certain combinations of factors to be better than others. For example, if two domains share object parts (e.g., dog and leopard), we would prefer a transfer of appearance in which local part appearances are preserved. For the ones that don't share object parts (e.g., bird

Figure 1: Each domain can be represented with e.g., a set of object shapes ($X_{A/B}$) and appearances ($Y_{A/B}$). The ability to generate images of the form $I_{AA/BB}$ requires the system to learn *intra*-domain disentanglement (Singh et al., 2019) of latent factors, whereas the ability to generate images of the form I_{AB} (appearance/shape from domain A/B, respectively) requires *inter*-domain disentanglement of factors, which is the goal of this work.

and car), we may prefer a transfer of appearance in which the overall color/texture frequency is preserved (e.g. Fig. 1, I_2 and I_{AB}), which has been found to be useful in object categorization at coarse level in neuroimaging study (Rice et al., 2014). Our work formulates this idea as a training process, where any two images having the same latent appearance are constrained to have similar frequency of those low-level features. These features in turn are *learned* (as opposed to being hand-crafted), using contrastive learning (Hadsell et al., 2006; Chen et al., 2020), to better capture the low-level statistics of the dataset. The net effect is an accurate transfer of appearance, where important details remain consistent across domains in spite of large shape changes. Importantly, we achieve this by only requiring bounding box annotations to help disentangle object from background, without any other labels, including which domain an image comes from.

To our knowledge, our work is the first to attempt combining factors from different data distributions to generate abstract visual concepts (e.g., car with dog's texture). We perform experiments on a variety of multi-modal datasets, and demonstrate our method's effectiveness qualitatively, quantitatively, and through user studies. We believe our work can open up new avenues for art/design; e.g., a customer could visualize how sofas would look with an animal print or a fashion/car designer could create a new space of designs using the appearance from arbitrary objects. Finally, we believe that the task introduced in this work offers better scrutiny of the quality of disentanglement learned by a method: if it succeeds in doing so within a domain but not in the presence of multiple ones, that in essence indicates some form of entanglement of factors with the domain's properties.

2 RELATED WORK

Learning disentangled representations for image generation has been studied in both the supervised (relying on e.g., keypoints and object masks) (Peng et al., 2017; Balakrishnan et al., 2018; Ma et al., 2018) and unsupervised settings (Li et al., 2018; Shu et al., 2018). Recent work disentangle object shape, appearance, pose, and background with only bounding box annotations (Singh et al., 2019; Li et al., 2020). All prior work, however, focus on disentangling and combining factors within a *single* domain (e.g., birds), and cannot be directly extended to the multi-domain setting since hybrid images would be considered out of distribution (i.e., fake). We present a framework that addresses this limitation, and which works equally well in both single and multi-domain settings.

Another potential angle to tackle the task at hand is through style-content disentanglement (Gatys et al., 2015; Johnson et al., 2016; Ulyanov et al., 2016). However, an object's appearance and shape in complex datasets do not necessarily align with those of style and content (e.g., color of background dominating the style rather than object's appearance). Unsupervised image-to-image translation works (Zhu et al., 2017; Kim et al., 2017; Huang et al., 2018; Gonzalez-Garcia et al., 2018) translate an image from domain A to domain B, such that the resulting image preserves the property common to domains A and B (e.g., structure), and property exclusive to B (e.g., appearance/style). However, if the domains don't have anything in common (e.g., cars $\leftrightarrow$ dogs: different structure and appearance), the translated images typically become degenerate, and no longer preserve properties from different domains. In contrast, our method can combine latent factors acros arbitrary

domains that have no part-level correspondences. Moreover, when part-level correspondences do exist (e.g., `dogs` ↔ `tiger`), it combines appearance and shape in a way which preserves them.

3 APPROACH

Given a single dataset consisting of two image domains $\mathcal{A}$ and $\mathcal{B}$ (e.g., dogs and cars), our goal is to learn a generative model of this distribution (with only bounding box annotations and without domain/category/segmentation labels), so that one latent factor (shape) from $\mathcal{A}$ and another factor (appearance) from $\mathcal{B}$ (or vice-versa) can be combined to generate a new out-of-distribution image preserving the respective latent properties from the two domains. Since there is no ground truth for the desired hybrid out-of-distribution images, our key idea is to preserve the frequency of low-level appearance features when transferred from one domain's shape to another domain's shape. To this end, we develop a learnable, differentiable histogram-based representation of object appearance, and optimize the generator so that any two images that are assigned the same latent appearance factor produce similar feature histograms. This leads to the model learning better disentanglement of object shape and appearance, allowing it to create hybrid images that span multiple domains.

We first formalize the desired properties of our model, and then discuss a single domain disentangled image generation base model (Singh et al., 2019) that we build upon. Finally, we explain how our proposed framework can augment the base model to achieve the complete set of desired properties.

3.1 PROBLEM FORMULATION

Combining factors from multiple domains requires learning a disentangled latent representation for *appearance, shape, and background* of an object. This enables each of the latent factor's behavior to remain consistent, irrespective of other factors. For example, we want the latent appearance vector that represents red and blue object color to produce the same appearance (color/texture distribution) regardless of whether it is combined with a bird's shape or a car's shape (I_{AA} and I_{AB} in Fig. 1). Henceforth, we represent shape, appearance, and background of an object as x, y, b respectively, and remaining continuous factors (e.g., object pose) using z.

As shown in Fig. 1, we can interpret domain $\mathcal{A}$ as having an associated set of shapes - $X_{\mathcal{A}}$ (e.g., possible bird shapes), and an associated set of appearances - $Y_{\mathcal{A}}$ (e.g., possible bird appearances). With an analogous interpretation for domain $\mathcal{B}$ (e.g., cars), we formalize the following problems: **(i) Intra-domain disentanglement:** where a method can generate images of the form $I = G(x, y, z, b)$, where $[x, y] \in (X_A \times Y_A)$ ($\times$ denotes Cartesian product). In other words, the task is to combine all possible shapes with possible appearances *within* a domain (e.g., I_{AA}/I_{BB} in Fig. 1). **(ii) Inter-domain disentanglement:** where everything remains the same as intra-domain disentanglement, except that $[x, y] \in (X_{AB} \times Y_{AB})$, where $X_{AB} = (X_A \cup X_B)$ and $Y_{AB} = (Y_A \cup Y_B)$. This is a more general version of the task, where we wish to combine all possible shapes with all possible appearances *across* multiple domains (e.g., I_{AB} in Fig. 1).

3.2 BASE MODEL

We start with an intra-domain disentangled image generation approach, FineGAN (Singh et al., 2019), as our base model. It takes in four latent variables as input: a continuous noise vector $z \sim \mathcal{N}(0, 1)$, and one-hot vectors $x \sim \text{Cat}(K = N_x, p = 1/N_x)$, $y \sim \text{Cat}(K = N_y, p = 1/N_y)$ and $b \sim \text{Cat}(K = N_b, p = 1/N_b)$, where N_x, N_y, and N_b are hyperparameters that represent the number of distinct shapes, appearances, and background to be discovered, respectively. FineGAN takes in these sampled codes, and generates an image in a stagewise manner, where background I_b and foreground I_f are generated separately and stitched together using a generated foreground mask m: $I = m * I_f + (1 - m) * I_b$.

To learn to disentangle object from background, FineGAN relies on bounding box supervision. To learn the desired disentanglement between shape and appearance without any supervision, FineGAN uses information theory to associate each factor to a latent code, and constrains the relationship between the codes to be hierarchical. Specifically, it makes the assumption that $N_x < N_y$; i.e., variety in object shape is less than variety in object appearance, which is generally true for real-world objects (e.g., different duck species have different colors/textures but share the same overall shape). During training, this hierarchy constraint is imposed so that a set of latent appearance codes

Figure 2: The base model (Singh et al., 2019) is capable of performing *intra*-domain disentanglement for four factors of variation. Each block demonstrates the effect of changing one latent code (shown above/below each image), which controls a single factor in the generated image.

y will always be paired with a particular latent shape code x. This ensures that, during training, the shape code representing e.g., a duck's shape does not get paired with the appearance code for e.g., a sparrow's texture to create an unnatural combination (which the discriminator could use to easily classify the generated image as fake, and in turn prevent the model from learning the desired disentanglement). Two types of loss functions are used: adversarial loss L_{abv} (Goodfellow et al., 2014) to enforce realism on the background and final generated image I, and mutual information loss L_{info} (Chen et al., 2016) between (i) x and object shape, (ii) y and object appearance, to help the latent codes gain control over the respective factors. We denote the losses used by the base model (FineGAN in this case) as L_{base}. Fig. 2 summarizes the properties learned by the base model.

3.3 COMBINING FACTORS FROM MULTIPLE DOMAINS

Although the base model can combine shape and appearance within a single domain (Fig. 1 bottom left), it has trouble doing so across different ones, as illustrated in Fig. 3 (b) top, where the same latent appearance code behaves differently when combined with a car's shape (I) versus a bird's shape (I_{pos_2}). The main reason is because hybrid images, which combine e.g., a bird's colors with a car's shape, are non-existent in the real data (i.e., out of distribution). Thus, the model is penalized from learning such a combination via the adversarial loss. For creating hybrid objects within a domain (e.g., combining red sparrow color and seagull shape to create a non-existent red seagull), this is less of a problem, since the base model implicitly learns part semantics as it has to consistently colorize the correct part of an object regardless of its pose (i.e., it learns a pose-equivariant representation of appearance; see Fig. 2 top-left). And since intra-domain objects share part semantics, during test time (in which the adversarial loss no longer plays a role), transferring e.g., a sparrow's appearance to a seagull's shape can still be achieved with some degree of success. However, when the two domains do not share any part semantics (e.g., birds and cars), the model would not know where e.g., the color of a bird's head should go in a car. In other words, when trained in a multi-domain setting, the base model is unable to fully disentangle shape from appearance; i.e., there is still some form of entanglement of shape and appearance tied to each domain.

So, how can we learn better disentanglement between appearance and shape in the multi-domain setting, without any ground truth for hybrid images? Our idea is to preserve the *frequency* of low-level visual concepts (color/texture) as a heuristic when transferring the appearance from one domain to another. Specifically, any two generated images with the same latent appearance code (but different shape codes) should have similar frequency in low-level appearance. To use this idea as part of an optimization process, we need to: (i) define the concepts whose frequency needs to be computed and make its computation differentiable, and (ii) induce the generator to generate hybrid images that preserve the low-level appearance frequency.

Learning a differentiable histogram of low-level features. At a high-level we'd like texture and color frequency to be our low-level feature concepts. However, since it is difficult to know a priori which specific textures/colors would be useful (e.g., a feature representing leopard texture would be useful for shape/appearance disentanglement in `animals` $\leftrightarrow$ `cars`, but might not be for `birds` $\leftrightarrow$ `cars`), we propose to learn them in a data driven way. Specifically, we represent the low-level concepts using a set of learnable filters (Fig. 3(a)), each of which convolves over a generated image to give regions of high correlation. To focus on the object region, we mask out the background using the base model's generated foreground mask, and compute the channel-wise sum of the resulting

Figure 3: **(a)** The process of computing the frequency-based representation. All steps are differentiable, making the representation learnable as part of the optimization process. **(b)** We construct positive samples differently for L_{filter} and L_{hybrid}, whereas negatives remain the same for both.

response maps to get a k-dimensional histogram representation h. This representation approximates the frequency of visual concepts represented by the set of filters (e.g., dog's fur, tiger's texture).

How do we ensure that the histogram h being approximated is of some relevant object feature? The information captured by the filter bank should be such that (i) the same object in different pose/viewpoints has a similar appearance representation, (ii) which in turn should be dissimilar than the representation of any other arbitrary object. We hence train the filter bank using contrastive learning (Bachman et al., 2019; Chen et al., 2020). Specifically, we first construct a batch of N generated images, where each image is of the form $I = G(x_1, y_1, z_1, b_1)$. We then construct another batch, where each image is of the form $I_{pos_1} = G(x_1, y_1, z_2, b_1)$, by only altering the noise vector z, which changes only the object's pose (due to our base model; Fig. 2 top-left). We set each I and corresponding I_{pos_1} pair as positive samples, and all other image pairs as negative samples (Fig. 3(b)). Finally, we use $NT\text{-}Xent$ (Normalized temperature-scaled cross entropy loss (Chen et al., 2020)) for each image I in the batch to learn the filter bank:

$$\ell_i = -\log \frac{\exp\left(\text{sim}\left(h_i, h_j\right)/\tau\right)}{\sum_{k=1}^{2N} \mathbf{1}_{[k \neq i]} \exp\left(\text{sim}\left(h_i, h_k\right)/\tau\right)} \tag{1}$$

where h_i represents the feature histogram of i^{th} image, j and k indexes the positive and negative samples for i, respectively, and τ is the temperature hyperparameter. We refer to the whole loss as $L_{filter} = \sum_{i=1}^{N} \ell_i$, and optimize it by only updating the weights of the filter bank.

Conditioning the generator to generate hybrid images. Now that we have a way to learn meaningful low-level features in a data driven way, we can use them to condition the generator to generate hybrid images. We use an objective similar to L_{filter}, where we use the same $I = G(x_1, y_1, z_1, b_1)$. However, we construct the positive pairs differently: $I_{pos_2} = G(x_2, y_1, z_1, b_1)$, in which the latent shape code x is different than that of I (while all other codes are the same); see Fig. 3(b). We refer to this loss as $L_{hybrid} = \sum_{i=1}^{N} \ell_i$, and optimize only the generator G's parameters. Intuitively, L_{hybrid} pushes the generator to match the frequency of low-level appearance features (e.g., car's color) between the generated images of two arbitrary shaped objects (e.g., car and bird).

The overall loss function of our framework is:

$$\mathcal{L} = L_{base} + L_{hybrid} + L_{filter} \tag{2}$$

where L_{base} induces the properties needed for intra-domain disentanglement, and the combination of L_{filter} and L_{hybrid} helps extend the abilities to learn inter-domain disentanglement of factors. Note that we do not employ the adversarial loss (which is part of L_{base}) on any hybrid images that do not follow our base model's hierarchical code constraints (as described in Sec. 3.2) since those images would be outside the real data distribution.

4 RESULTS

We now compare the proposed framework against several baselines, and study how they fare in terms of disentangling and combining shape/appearance from different domains.

Figure 4: Results using CycleGAN, MUNIT, and AdaIn. When the two domains don't have structural correspondence, the image-to-image translation methods fail to disentangle shape from appearance. AdaIn suffers, as images don't always have a homogeneous style to be extracted from, resulting in misalignment in the definition of object appearance and style.

We use three single domain datasets: CUB (Wah et al., 2011) collection of 200 birds categories. (ii) Stanford Dogs (Khosla et al., 2011) collection of 120 dog categories. (iii) Stanford Cars (Krause et al., 2013) collection of 196 car categories. Using these, we construct three multi-domain settings: (i) birds ↔ cars, (ii) cars ↔ dogs, (iii) dogs ↔ birds, consisting of a total of 396, 316, and 320 object categories, respectively. We also use a multi-domain dataset of animal faces (Liu et al., 2019), comprising 149 carnivorous categories, where each category can be interpreted as a different domain. This forms our fourth multi-domain setting, (iv) animals ↔ animals.

4.1 CAN IMAGE TRANSLATION OR STYLE TRANSFER METHODS SOLVE THIS TASK?

As mentioned in Sec 2, there are existing works which could potentially offer solutions for the task at hand, even with their core objective being different. CycleGAN (Zhu et al., 2017) and MUNIT (Huang et al., 2018) translate images from one domain to another, in a way where the translated images preserve some properties from both the source and target. If the two domains are, say cars↔dogs, can these methods translate a car into an image that combines the car's shape with a dog-like appearance? Fig. 4 shows some translation results: in general, we observe that the translations become degenerate, and don't preserve any interpretable property from the input, i.e., the methods are no longer able to disentangle structure from domain-specific appearance. We also explore AdaIn (Huang & Belongie, 2017), a method capable of transferring *style* between any arbitrary pair of images; see Fig. 4. We notice that the definition of *style* transferred and what we perceive as appearance don't always align, and even then, the method is unable to solely focus on the foreground object when extracting and transferring the style (e.g., bird's blue color bleeds into the background of the car in the first row). Overall, Fig. 4 shows that these methods are not suited for settings involving arbitrary domains, which have no similarity in object shape/appearance.

4.2 COMPARISON TO MULTI-FACTOR DISENTANGLEMENT BASELINES

We next study baselines which disentangle object shape, appearance, pose, and background, and generate images conditioned on the respective latent vectors: **(i) FineGAN** (Singh et al., 2019): base model described in Sec. 3.2; **(ii) Relaxed FineGAN**: an extension of FineGAN, where we relax the hierarchical constraint between shape and appearance codes (so that at least conceptually, hybrid images can be generated during training). For those hybrids, we only optimize L_{info} whereas for the remaining images (generated with code constraints), we optimize the full L_{base}. **(iii) Ours w/o** L_{filter}: our approach using a fixed, randomly initialized filter bank to compute the frequency-based representation; **(iv) Ours**: our final approach. Note that we don't need domain labels to train methods (i)-(iv); but once trained, we can visualize what the different learned shape (x) and appearance (y) latent vectors represent (e.g., x_1 and x_2 might generate a specific bird and car shape, respectively). Hence, for evaluation purposes, we manually create a split of the latent vectors, $[X_A, Y_A]$ and $[X_B, Y_B]$, so that $\forall x \in X_A$, x represents only one domain (e.g., birds' shapes). This way, we can combine latent factors from different domains to study shape/appearance disentanglement.

Figure 5: **FineGAN (top) vs. Ours (bottom)**. The only difference between the 'Output' and 'Shape' image is the latent appearance vector, which is borrowed from the 'Appearance' image. Our outputs preserve the characteristic appearance details much better than FineGAN. More results in Sec. A.6.

We first show qualitative comparisons to FineGAN over different multi-domain datasets in Fig. 5. FineGAN has issues combining factors from different domains, evident through (i) inaccurate appearance transfer (e.g., row 1: only car window color gets transferred to the bird), and (ii) the inability to transfer details beyond rough color (e.g., row 4: the fur texture of the brown dog isn't transferred to the car; row 1: the characteristic leopard texture isn't transferred to the dog). Our method, on the other hand, results in a more holistic transfer of appearance to arbitrary shapes. Upon transferring, it is able to better preserve the (i) color distribution (row 5/6: both the blue and red components get transferred to the car/bird respectively), (ii) other low-level characteristic features (row 8: brown fur gets transferred to the car's body; row 5: leopard's texture is transferred to the dog's face). Focusing on animals $\leftrightarrow$ animals results for FineGAN, we see that the *Shape* images have a tendency to resist appearance change (e.g., the leopard's texture is still preserved in the output image), which indicates there is some entanglement between shape and appearance. This is mainly because unlike our approach, FineGAN does not have an explicit constraint to enforce the same latent appearance code to produce the same low-level visual features regardless of shape. We study this property in more detail in Sec. A.3.

4.2.1 QUANTIFYING SHAPE/APPEARANCE DISENTANGLEMENT

Appearance transfer: In this experiment, we evaluate how well appearance is transferred from one domain to another. For each latent appearance vector y_i, we generate a source $I_s = G(x_i, y_i, b_i, z_i)$ and target image $I_t = G(x_j, y_i, b_i, z_i)$ $(x_i, x_j$ represent shapes from different domains). We segment the foreground pixels using DeepLabv3 (Chen et al., 2017), pre-trained on COCO (Lin et al., 2014). We then evaluate the similarity between the source and target images' foreground appearance by

	birds $\leftrightarrow$ cars		cars $\leftrightarrow$ dogs		dogs $\leftrightarrow$ birds		animals $\leftrightarrow$ animals	
	color	texture	color	texture	color	texture	color	texture
FineGAN (Singh et al., 2019)	0.4295	0.4234	0.3856	0.4006	0.2862	0.3442	0.1914	0.2322
Relaxed FineGAN	0.3121	0.4005	0.3451	0.3912	0.2433	0.3287	0.1214	0.1834
AdaIn (Huang & Belongie, 2017)	0.5619	0.4476	0.5113	0.3956	0.6265	0.3512	0.2447	0.1801
Ours w/o L_{filter}	0.2842	0.3341	0.2289	0.2754	0.2228	0.2744	0.0721	0.0815
Ours	**0.2484**	**0.3057**	**0.2069**	**0.2535**	**0.2009**	**0.2573**	**0.0462**	**0.0695**

Table 1: χ^2-distance between color/texture histograms of source and target images (lower is better). By enforcing similarity in the frequency of low-level features (via $L_{filter} + L_{hybrid}$), our model better retains the color/texture distribution across the source and target compared to alternate baselines.

	Shape disentanglement		AMT results	
	FineGAN	Ours	Ours vs AdaIn	Ours vs FineGAN
birds $\leftrightarrow$ cars	0.831 $\pm$ 0.04	0.861 $\pm$ 0.03	82.56 $\pm$ 3.28	75.04 $\pm$ 4.67
cars $\leftrightarrow$ dogs	0.835 $\pm$ 0.03	0.841 $\pm$ 0.03	85.45 $\pm$ 5.11	83.02 $\pm$ 4.55
dogs $\leftrightarrow$ birds	0.674 $\pm$ 0.10	0.748 $\pm$ 0.08	75.05 $\pm$ 6.89	63.25 7.17 $\pm$
animals $\leftrightarrow$ animals	0.871 $\pm$ 0.06	0.907 $\pm$ 0.02	82.51 $\pm$ 1.85	76.21 $\pm$ 2.12

Table 2: **(Left)** Shape disentanglement results: higher IoU means better shape disentanglement from appearance. **(Right)** AMT experiment results: how often our method is preferred over the baseline.

computing the χ^2-distance between their color and texture histograms (Leung & Malik, 2001) (more details in Sec. A.4.1). Table 1 summarizes the results. As expected based on Figs. 4 and 5, the baselines often have issues accurately transferring the color/texture distribution to an arbitrary shape, resulting in the color/texture histogram for I_s and I_t having low similarity. 'Ours w/o L_{filter}' is a decent baseline, which simply uses random filters to minimize L_{hybrid}. Our final approach, which learns the filters, achieves the best overall performance in retaining the color and texture information.

Shape transfer: We next evaluate how well the object's original shape is retained when appearance from another domain is transferred to it. If shape is accurately disentangled from appearance, then if we generate a stack of images $\{G(x, y_i, z, b)\} \lor y_i \in$ S (arbitrary set of latent appearances), any differences should only be in the foreground appearance (Fig. 2 top right). We therefore compute the standard deviation across the stack, and convert it into a binary mask using an appropriate threshold. If different sets of appearances (S) result in similar masks, that is an indication of shape being controlled only by x. So, we randomly split the available latent vectors into two sets, S_1 and S_2, compute their respective masks, and evaluate the IoU between them (Sec. A.4.2). This is repeated for 10 different random splits of S_1/S_2, giving the score for a latent shape. The final score is averaged over all possible latent shapes. Table 2 (left) summarizes the results: we see that both FineGAN and our method achieve high IoU scores, demonstrating that changes introduced by different appearance vectors are mostly confined within the same region, and hence *don't* change the object shape.

Hybrid images through the eyes of image classifiers: If we look at the last row in Fig. 5, a regular car becomes a car with brown fur. For an image classification network, does this *furry-car* have more dog-like properties, and less of cars'? When compared to the hybrids created by FineGAN, we find our hybrids do indeed exhibit this behavior; see Sec A.5 in Appendix for details.

Perceptual study: Finally, we conduct human studies. Each task shows the results of two methods, one of which is ours and the other is either AdaIn or FineGAN. The result format is same as in Fig. 5, i.e., [Appearance, Shape $\rightarrow$ Output] (Appearance/Shape images are used as Style/Content input for AdaIn). Amazon Mechanical Turkers are asked to select the method which resulted in a better shape/appearance transfer. We generate 250 tasks for each dataset, and gather responses from 5 unique turkers for each task, resulting in 1250 judgements. Table 2 (Right) summarizes the results. Averaged across all datasets, our method gets chosen over AdaIn and FineGAN in 81.39 $\pm$ 3.85% and 74.38 $\pm$ 7.11% of the cases, demonstrating consistent superiority in generating hybrid images.

5 DISCUSSION AND CONCLUSION

The method introduced in this work bridges the gap between learning intra and inter-domain disentanglement, and improves the base model through better appearance transfer between different domains. However, there are some limitations: when the number of domains increase, it becomes less feasible to train models on all combinations of domains ($\binom{n}{2}$), which grows quadratically). Another limitation is that our approach focuses on combining appearance and shape, but cannot combine different parts across domains (e.g., to create centaur). Nonetheless, we believe that we address an important problem, which can also have practical applications in art and design.

REFERENCES

Philip Bachman, R Devon Hjelm, and William Buchwalter. Learning representations by maximizing mutual information across views. *NeurIPS*, 2019.

Guha Balakrishnan, Amy Zhao, Adrian Dalca, Fredo Durand, and John Guttag. Synthesizing images of humans in unseen poses. In *CVPR*, 2018.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale gan training for high fidelity natural image synthesis. In *ICLR*, 2019.

Liang-Chieh Chen, George Papandreou, Florian Schroff, and Hartwig Adam. Rethinking atrous convolution for semantic image segmentation. In *ArXiv*, 2017.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. *ArXiv*, 2020.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *NIPS*, 2016.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009.

Emily L Denton and Vighnesh Birodkar. Unsupervised learning of disentangled representations from video. In *NIPS*, 2017.

Leon A Gatys, Alexander S Ecker, and Matthias Bethge. A neural algorithm of artistic style. *Arxiv*, 2015.

Abel Gonzalez-Garcia, Joost Van De Weijer, and Yoshua Bengio. Image-to-image translation for cross-domain disentanglement. In *NIPS*, 2018.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *NIPS*, 2014.

Raia Hadsell, Sumit Chopra, and Yann LeCun. Dimensionality reduction by learning an invariant mapping. In *CVPR*, 2006.

Irina Higgins, Loïc Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *ICLR*, 2017.

Qiyang Hu, Attila Szabó, Tiziano Portenier, Paolo Favaro, and Matthias Zwicker. Disentangling factors of variation by mixing them. In *CVPR*, 2018.

Xun Huang and Serge Belongie. Arbitrary style transfer in real-time with adaptive instance normalization. In *ICCV*, 2017.

Xun Huang, Serge Belongie, and Jan Kautz. Multimodal unsupervised image-to-image translation. In *ECCV*, 2018.

Justin Johnson, Alexandre Alahi, and Li Fei-Fei. Perceptual losses for real-time style transfer and super-resolution. In *ECCV*, 2016.

Tero Karras, Samuli Lanie, and Timo Aila. A style-based generator architecture for generative adversarial networks. *CVPR*, 2019.

Aditya Khosla, Nityananda Jayadevaprakash, Bangpeng Yao, and Li Fei-Fei. Novel dataset for fine-grained image categorization. In *First Workshop on Fine-Grained Visual Categorization*, 2011.

Taeksoo Kim, Moonsu Cha, Hyunsoo Kim, Jung Kwon Lee, and Jiwon Kim. Learning to discover cross-domain relations with generative adversarial networks. In *ICML*, 2017.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *ICLR*, 2014.

Jonathan Krause, Michael Stark, Jia Deng, and Li Fei-Fei. 3d object representations for fine-grained categorization. In *IEEE Workshop on 3D Representation and Recognition (3dRR-13)*, 2013.

Brendon M. Lake, Ruslan Salakhutdinov, and Josh Tenenbaum. Human-level concept learning through probabilistic program induction. *Science*, 2015.

Thomas Leung and Jitendra Malik. Representing and recognizing the visual appearance of materials using three-dimensional textons. In *IJCV*, 2001.

Yuheng Li, Krishna Kumar Singh, Utkarsh Ojha, and Yong Jae Lee. Mixnmatch: Multifactor disentanglement and encoding for conditional image generation. In *CVPR*, 2020.

Zejian Li, Yongchuan Tang, and Yongxing He. Unsupervised disentangled representation learning with analogical relations. In *IJCAI*, 2018.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C. Lawrence Zitnick. Microsoft coco: Common objects in context. In *ECCV*, 2014.

Ming-Yu Liu, Xun Huamg, Arun Mallya, Tero Karras, Timo Aila, Jaakko Lehtinen, and Jan Kautz. Few-shot unsupervised image-to-image translation. In *ICCV*, 2019.

Liqian Ma, Qianru Sun, Stamatios Georgoulis, Luc Van Gool, Bernt Schiele, and Mario Fritz. Disentangled person image generation. In *CVPR*, 2018.

Xi Peng, Xiang Yu, Kihyuk Sohn, Dimitris N Metaxas, and Manmohan Chandraker. Reconstruction-based disentanglement for pose-invariant face recognition. In *ICCV*, 2017.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. In *ICLR*, 2016.

Grace E. Rice, David M. Watson, Tom Hartley, and Timothy J. Andrews. Low-level image properties of visual objects predict patterns of neural response across category-selective regions of the ventral visual pathway. *The Journal of Neuroscience*, 2014.

Zhixin Shu, Mihir Sahasrabudhe, Riza Alp Güler, Dimitris Samaras, Nikos Paragios, and Iasonas Kokkinos. Deforming autoencoders: Unsupervised disentangling of shape and appearance. In *ECCV*, 2018.

Krishna Kumar Singh, Utkarsh Ojha, and Yong Jae Lee. Finegan: Unsupervised hierarchical disentanglement for fine-grained object generation and discovery. In *CVPR*, 2019.

Dmitry Ulyanov, Vadim Lebedev, Andrea Vedaldi, and Victor Lempitsky. Texture networks: Feed-forward synthesis of textures and stylized images. *ICML*, 2016.

C. Wah, S. Branson, P. Welinder, P. Perona, and S. Belongie. The Caltech-UCSD Birds-200-2011 Dataset. Technical Report CNS-TR-2011-001, 2011.

Han Zhang, Tao Xu, Hongsheng Li, Shaoting Zhang, Xiaogang Wang, Xiaolei Huang, and Dimitris Metaxas. Stackgan++: Realistic image synthesis with stacked generative adversarial networks. *TPAMI*, 2018.

Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. In *ICCV*, 2017.

A APPENDIX

A.1 TRAINING DETAILS

Since we use FineGAN as our base model, the generator and discriminator architecture, as well as hyperparameters like learning rate, optimizer (Adam (Kingma & Welling, 2014)), β_1/β_2 are borrowed from (Singh et al., 2019). We also use the same data preprocessing step, where we crop the images to $1.5 \times$ their available bounding box, so as to have a decent object to image size ratio. We use a batch size of 24 to maximize the usage of two TITAN Xp GPUs per experiment. Apart from the

raw data, FineGAN uses two forms of information to disentangle object pose, shape, appearance and background while modeling an image distribution - (i) bounding box information, so that patches outside it can be used as real background patches to model background on a patch level; (ii) No. of object categories in the dataset. The hierarchy to be discovered needs to be decided beforehand, where the number of children (N_c) are set to be the number of object categories, and the number of parents (N_p) are decided empirically. We set N_c as 400 (200 + 196) for birds $\leftrightarrow$ cars, 320 (196 + 120) for cars $\leftrightarrow$ dogs and 320 (120 + 200) for dogs $\leftrightarrow$ birds. We set $N_p = N_x/10$ for these three datasets. For animals $\leftrightarrow$ animals, we set N_c as 150 (149 categories), and N_p as $N_c/5$.

Upon training FineGAN, the four different latent vectors start to correspond to some properties in the generated images: latent appearance vector, having a one-hot representation, starts capturing the appearance (different indices start generating different appearance details) etc. This way, one can combine the latent shape code which generated duck, latent appearance code which generated yellow bird, to create a yellow duck. For birds $\leftrightarrow$ cars, cars $\leftrightarrow$ dogs, and dogs $\leftrightarrow$ birds, we first train the base model until convergence (600 epochs). This model can disentangle disentangle the four factors within a domain as shown in Fig. 2. Starting from this pre-trained model, we now use our loss objectives L_{filter} and L_{hybrid}, in addition to L_{base} (FineGAN's overall objective), and further train the model to better perform inter-domain disentanglement of factors.

Specifically, in each iteration, we optimize the model using L_{base}, then optimize the generator's weights using L_{hybrid}, and then optimize the filters' weights using L_{filter}. In our experiments, we found that using L_{hybrid} at lesser frequency (1/4th of the time) compared to L_{base}/L_{filter} works better. The second phase of training is performed for about (50k iterations). The two phase training for these three datasets is important, because we observed that directly using the combination of L_{base}, L_{hybrid} and L_{filter} while training from scratch leads to model having some issues with learning intra-domain disentanglement. For the fourth dataset (animals $\leftrightarrow$ animals), however, we directly train from scratch using all three loss components, a setting which actually results in better performance than the two phase one discussed above. This difference could be attributed to the difference in the nature of multi-domain datasets, where birds $\leftrightarrow$ cars has only two domains, the animals $\leftrightarrow$ animals domain effectively has N_p (= 30) domains.

A.2 ABLATION STUDY

We now study different design choices, and visualize their effects in mixing shape/appearance across domains.

Receptive field size of filters: As explained before, we can use more than one layer of filter while computing the frequency-based representation. As shown in Fig. 3 (left), one can have a second layer of filters which take as input the filter bank responses (g), and repeats the same process again. The final frequency based representation will be the concatenation of representation after first and second stage. In our experiment, we always use filters of size 3x3 (unless stated otherwise), stride = 1, padding = 0. The number of filters in the first, second and third layers are 64, 128 and 192 respectively. We experiment with 4 settings - (i) 1 layer of 1x1 filters; (ii) 1 layer of 3x3 filters; (iii) 2 layers of 3x3 filters; and (iv) 3 layers of 3x3 filters. The results are shown in Fig. 6. With setting (i), i.e. 1 layer of 1x1 filters, the only additional constrain introduced by L_{filter} and L_{hybrid} is to ensure consistency in 1x1 regions, i.e. RGB pixel distribution. In other words, this setting could be thought of as enforcing color histogram similarity between source and target images. We observe a similar behavior in the results as well, where it fails to accurately transfer the tiger's texture to other animals' faces, but is able to faithfully transfer the color distribution. Furthermore, the source dog in the second row has two characteristic property; brown patches above the eyes, and a white region in the middle going all the way to the forehead. Transferring this particular appearance doesn't always preserve the properties; e.g. (i) the tiger only has a white patch near the mouth, which doesn't extend towards the forehead, (ii) the brown patches over the eyes are no longer transferred to the tiger's face. In general, we observe that these properties (white patch, texture pattern), which extend beyond color distribution, are better captured with increasing receptive field. Setting (iii) and (iv) result in similar performance, so we choose the setting (iii) (a simpler version) as our final model.

Parameters optimized using L_{hybrid}: We explain in sec. 3.3 that L_{hybrid} is optimized by adjusting the generator weights. However, the base model we use (FineGAN) generates the foreground in

Figure 6: Results of our method with different settings of filters used to approximate frequency-based representation. As the effective receptive field size increases from top-left to bottom right, we notice that the method can better transfer characteristic appearance details.

two stages: the parent stage generating the outline, and the child stage filling in the details. As we will discuss in Sec. A.3, FineGAN sometimes suffers

A.3 RESISTIVITY ISSUE

In Fig. 10, we see that FineGAN shows a *resistance* towards changing the appearance of an animal; e.g. in row 4, the leopard in the target image only borrows a blackish color tone, and most of the signature leopard appearance remains as it is. In contrast, our method is able to comprehensively change the appearance of an animal; e.g. in the same row, leopard can shed its appearance and borrow everything from the tricolored dog, while also preserving any potential correspondence (the resulting animal retains the brown patch above the eye). We study the resistivity property in more detail: for each latent shape vector x_i, we construct a list of images (L) by combining it with all possible latent appearance vectors, keeping the latent noise (z capturing pose) and background vectors the same, i.e. $L = \{G(x_i, y_j, z_i, b_i)\} \vee y_j \in$ **animals** $\leftrightarrow$ **animals**. We then stack the images in L, compute standard deviation across channels separately, and then average to generate a heatmap image. We repeat this process for all the latent shape vectors, and plot the histogram of standard deviation values. Fig. 10 illustrates this process, and compares the heatmap images generated using our approach vs FineGAN. This helps us visualize the *resistance* property, as the heatmap and histogram through FineGAN indicates much lower standard deviation of pixel differences compared to our approach, implying more diversity of visual appearance attainable using our method.

Figure 7: Analysis of the resistance of a model to alter the appearance. Generations using FineGAN don't fully relinquish the appearance, resulting in a low standard deviation for pixel changes across the spatial locations compared to our approach.

Figure 8: Analysis of the resistance of a model to alter the appearance. Generations using FineGAN don't fully relinquish the appearance, resulting in a low standard deviation for pixel changes across the spatial locations compared to our approach.

A.4 SHAPE/APPEARANCE DISENTANGLEMENT

A.4.1 COLOR/TEXTURE HISTOGRAM CONSTRUCTION DETAILS

We first define the process of obtaining the image and texture based cluster centers (codebook), and then detail the process of constructing and comparing the respective histogram representations of two images.

We sample 50,000 pixel (RGB) values randomly from the images belonging to a multi-domain dataset (e.g. **birds** $\leftrightarrow$ **cars**), and perform *k-means* clustering with $k = 50$ to get the color centers. To compute the texture centers, the images in the dataset are first convolved with a MR8 (Leung & Malik, 2001) filter bank, consisting of 38 filters and 8 responses capturing edge, bar and rotationally symmetric features. After this step, the process is similar to computing the color histograms: we sample 50,000 points from the images, each point being 8-dimensional, and cluster them into 50 centers representing the texton codebook. We repeat this process of computing the color and texture clusters for each multi-domain setting separately. For each latent appearance vector y_i, we generate a source image $I_s = G(x_i, y_i, b_i, z_i)$ and a target image $I_t = G(x_j, y_i, b_i, z_i)$ such that x_i, y_i belong to one domain and x_j to another (e.g. x_i/x_j represents bird/car shape). We then use a semantic

Figure 9: Sample binary masks generated on the standard deviation image for different shapes, by applying appropriate threshold

segmentation network (DeepLabv3 (Chen et al., 2017)) pre-trained on MS COCO (Lin et al., 2014) to extract foreground pixels, and compute and compare color/texture based histograms between source and target images. Note that I_t is likely to represent some visual concepts which were never seen by the segmentation network pre-trained on real data (e.g. car with dog's fur in Fig. 5), which could result in unreliable segmentations from the network. We circumvent that by generating an intermediate image $G(x_j, y_j, b_j, z_i)$ such that both the appearance/shape factors belong to the same target domain. We then run the pre-trained segmentation network on this image, and use the predicted foreground locations for I_t (which has the same shape factor, x_j).

A.4.2 Shape disentanglement

As mentioned in Sec. 4.2.1, one can compute the standard deviation image across the stack, apply an appropriate threshold (we use values between 0.1-0.3) to get a binary mask mostly focusing on the foreground, as shown in Fig. 9

A.5 Understanding hybrid images through image classifiers

A high level goal of this work was to create hybrid, out-of-distribution images which do not exist in any domain exclusively. We studied our method's ability to do so in terms of its ability to accurately transfer properties (shape/appearance) across different domains. Orthogonal to this, however, could we use image classification as a proxy to understand *hybridness*? Let us look at one of the results of FineGAN, from Fig. 5 row 4, dogs ↔ cars. The resulting car generated upon transferring the appearance of dog onto a car still looks like a *realistic* car, i.e. could potentially belong to the real dataset of cars.

We posit that our method better transfers the semantics of the dog to a car; consequently, we expect the hybrid car and the dog to be more similar in some semantic feature space using our method, compared to FineGAN. We test this as follows - given an in-domain image (x and y are tied) $I = G(x, y, b, z)$ (real brown dog), we combine its appearance (y) with factors from other domain to create a hybrid image, $I_a = G(x^{'}, y, b^{'}, z)$ (the hybrid car). We pass both these images through an image classifier (we use VGG 16) pretrained on ImageNet Deng et al. (2009), and compute cosine similarity between the feature representation of these two images. A high similarity implies better transfer of semantics, i.e. a better hybrid image. We repeat this experiment for all the in-domain images, and present the averaged results in Table 3 (left); we see that our method consistently achieves higher similarity, especially for cars ↔ dogs and animals ↔ animals.

Analogously, if transferring the dog's appearance did make the car more hybrid, its similarity with the original car should decrease. That is, given the same in-domain image $G(x, y, b, z)$ (original car), we borrow appearance from the other domain $y^{'}$ to create the hybrid image $I_s = G(x, y^{'}, b, z)$. We repeat the previous experiment and get the cosine distance between their feature representation.

	sim(I, I_a)		sim(I, I_s)	
	FineGAN	**Ours**	**FineGAN**	**Ours**
birds ↔ cars	0.2877 ± 0.035	0.3182 ± 0.040	0.6787 ± 0.095	0.5959 ± 0.084
cars ↔ dogs	0.2976 ± 0.095	0.3624 ± 0.136	0.6067 ± 0.157	0.4473 ± 0.110
dogs ↔ birds	0.3669 ± 0.081	0.4209 ± 0.077	0.5315 ± 0.089	0.5081 ± 0.095
animals ↔ animals	0.4618 ± 0.090	0.6375 ± 0.136	0.6850 ± 0.0963	0.4981 ± 0.101

Table 3: Assessing hybrid image properties through image classification. A high dist(I, I_a) score implies better transfer of semantic properties through appearance transfer. A low dist(I, I_s) score implies that appearance transfer on the same shape resulted in a shift away from the original distribution.

Lower similarity implies that the hybrid image *shifted away* from the original image. Averaged results (over all in-domain images) are presented in Table 3 (Right). We again observe that our method gets lower similarity score, implying more shift from a domain towards hybrid distribution.

A.6 QUALITATIVE RESULTS

Figure 10: Each cell block follows `[Appearance, Shape → Output]`. Assorted results from different multi-domain settings using our method.