Robust Neural Posterior Estimation and Statistical Model Criticism

Abstract

Computer simulations have proven a valuable tool for understanding complex phenomena across the sciences. However, the utility of simulators for modelling and forecasting purposes is often restricted by low data quality, as well as practical limits to model fidelity. In order to circumvent these difficulties, we argue that modellers must treat simulators as idealistic representations of the true data generating process, and consequently should thoughtfully consider the risk of *model misspecification*. In this work we revisit neural posterior estimation (NPE), a class of algorithms that enable black-box parameter inference in simulation models, and consider the implication of a simulation-to-reality gap. While recent works have demonstrated reliable performance of these methods, the analyses have been performed using synthetic data generated by the simulator model itself, and have therefore only addressed the well-specified case. In this paper, we find that the presence of misspecification, in contrast, leads to unreliable inference when NPE is used naïvely. As a remedy we argue that principled scientific inquiry with simulators should incorporate a *model criticism* component, to facilitate interpretable identification of misspecification and a *robust inference* component, to fit "wrong but useful" models. We propose robust neural posterior estimation (RNPE), an extension of NPE to simultaneously achieve both these aims, through explicitly modelling the discrepancies between simulations and the observed data. We assess the approach on a range of artificially misspecified examples, and find RNPE performs well across the tasks, whereas naïvely using NPE leads to misleading and erratic posteriors.

1 Introduction

Stochastic simulators have become a ubiquitous modelling tool across the sciences and are regularly applied to some of the most complex and challenging problems of scientific interest, including climate change (see e.g. Randall et al., 2007), particle physics (e.g. Brehmer et al., 2020), and the Covid-19 pandemic (e.g. Ferguson et al., 2020). Simulators implicitly define a likelihood function $p(\boldsymbol{x} \mid \boldsymbol{\theta})$, where $\boldsymbol{x}$ is the simulator output and $\boldsymbol{\theta}$ are the simulator parameters. Although running the simulator to sample from the model is straightforward, the inherent complexity of simulators often makes analytic calculation of the likelihood intractable. As a result, classical inference techniques to find the parameter posterior $p(\boldsymbol{\theta} \mid \boldsymbol{x})$ such as Markov chain Monte Carlo (MCMC) (Metropolis et al., 1953) are infeasible. To overcome this issue, a large family of simulation-based inference (SBI) methods have been developed that allow parameter inference to be performed on arbitrary "black-box" simulators (see Cranmer et al., 2020). Recently, there has been much success applying neural network-based conditional density estimators, such as normalising flows, to approximate the likelihood or posterior (Greenberg et al., 2019; Papamakarios and Murray, 2016; Papamakarios et al., 2019a; Lueckmann

et al., 2021). These approaches are broadly termed neural likelihood estimation (NLE) and neural posterior estimation (NPE).

Figure 1: Overview of the robust neural posterior estimation (RNPE) framework. Through "denoising" the observed data, we can simultaneously perform *model criticism* to identify how the model is misspecified, and perform inference *robust* to model misspecification. See Gaussian example in section 4.2 for details of the experiment.

Despite proving useful across the sciences, SBI methods are not without their limitations. Firstly, even in the ideal case of a well-specified simulator, these methods in practice lead to imperfect and often overconfident posterior approximations (Hermans et al., 2021; Lueckmann et al., 2021). Secondly, SBI methods generally rely on the assumption that the simulator is well-specified, an assumption that is often violated in practice. It is this second issue that forms the focus of this work.

To define misspecification, it is necessary to make a clear distinction between the true data generating process and the simulator: we will write $\boldsymbol{y}_o$ for observed data, following some unknown data generating process with distribution denoted p^*, and we will write $\boldsymbol{x} \sim p(\boldsymbol{x} \mid \boldsymbol{\theta})$ to denote samples from the simulator. In many applications of SBI, summary statistics are used to reduce the dimensionality of the problem. If this is the case, we use $\boldsymbol{x}$ and $\boldsymbol{y}_o$ to denote the simulated and observed summary statistics, rather than the raw data, and treat the raw data as an unobserved latent of the model. The simulator is said to be *misspecified* if the true data generating process does not fall within the family of distributions defined by the simulator, i.e. $p^* \notin \{p(\boldsymbol{x} \mid \boldsymbol{\theta}); \boldsymbol{\theta} \in \Theta\}$. Simulators generally form idealised and simplistic representations of a more complex data generating process, and hence – like all statistical models – will be "wrong" to some extent. This misspecification often results in a discrepancy between simulated and observed data, sometimes termed a "simulation-to-reality gap". Despite this, the general approach in SBI is to learn a posterior approximation $q(\boldsymbol{\theta} \mid \boldsymbol{x})$ (either directly, or via the likelihood), trained using simulated data, $(\boldsymbol{x}, \boldsymbol{\theta}) \sim p(\boldsymbol{x} \mid \boldsymbol{\theta})p(\boldsymbol{\theta})$, and to query it with the observed data, $q(\boldsymbol{\theta} \mid \boldsymbol{x} = \boldsymbol{y}_o)$. This approach is only theoretically justified under the assumption that the simulator is well-specified; relying on this approach for misspecified simulators leads to two issues:

(i) As the posterior approximation $q(\boldsymbol{\theta} \mid \boldsymbol{x})$ is learned using samples from the simulator, this implies that we can only expect it to form a reasonable approximation of $p(\boldsymbol{\theta} \mid \boldsymbol{x})$ for regions well covered by simulations. For misspecified simulators, the observed data $\boldsymbol{y}_o$ may be very unlikely in $p(\boldsymbol{x}) = \int p(\boldsymbol{x}|\boldsymbol{\theta})p(\boldsymbol{\theta})d\boldsymbol{\theta}$, in which case the approximation $q(\boldsymbol{\theta} \mid \boldsymbol{x} = \boldsymbol{y}_o)$ will likely be poor. In some cases, $\boldsymbol{y}_o$ may even fall outside the support of $p(\boldsymbol{x})$, which results in NPE attempting to extrapolate to estimate the undefined posterior.

(ii) It has been demonstrated more generally that Bayesian inference is frequently problematic under misspecification. Even for simple models, misspecification can lead to posterior concentration around "bad" models (Grünwald and Langford, 2007; Grünwald and Van Ommen, 2017) and poorly calibrated credible regions (Kleijn and van der Vaart, 2012; Syring and Martin, 2019). These issues will persist even in the unlikely case that $q(\boldsymbol{\theta} \mid \boldsymbol{x})$ perfectly approximates $p(\boldsymbol{\theta} \mid \boldsymbol{x})$.

We view the ubiquity of model misspecification (to a generally unknown degree), in addition to the lack of principled methods for addressing it, as a major obstacle to further adoption of SBI.

Our contribution. We propose robust neural posterior estimation (RNPE), an SBI framework that incorporates an error model, $p(\boldsymbol{y} \mid \boldsymbol{x})$, to explicitly express our belief that a discrepancy might exist between the data generating process and the simulator. Following ideas from Box (1980), RNPE facilitates principled scientific modelling, allowing iteration between two complementary components: *model criticism*[1] and *robust inference*:

Model Criticism. Model criticism has long been seen as a key component in statistical modelling; it is only through understanding the limitations of a model that principled model development can occur (Box, 1980; Gelman and Shalizi, 2013). The error model provides a means to compare the observed data to simulations, facilitating *automated* and *interpretable* identification of misspecification.

Robust Inference. Even after several rounds of model development and model criticism, the "best" available model will still frequently be misspecified to an appreciable degree. However, it is often still desirable to use "wrong but useful" models for parameter inference and predictions, and hence the inference process should be robust to misspecification. RNPE partitions inference into two steps: *i)* probabilistically "denoising" the observation, thus producing samples consistent with both the error model and simulator; *ii)* performing NPE, using the property of amortisation[2] to ensemble posterior estimates over the denoised data. In this manner, we incorporate the possibility of model misspecification into the Bayesian update, whilst simultaneously bypassing the need to rely on the ability of NPE to generalise well to misspecified observations.

An overview of the RNPE framework can be seen in Fig. 1. We examine the practical value of this approach for *model criticism* and *robust inference* on examples in which we artificially introduce realistic levels of misspecification.

2 Method

2.1 Error Model

As outlined above, we argue that if we are interested in being able to draw trustworthy scientific conclusions, we should ensure the modelling process accommodates both *model criticism* and *robust inference*. To this end, we explicitly account for possible discrepancies between the simulated and observed data by incorporating an "error model" $p(\boldsymbol{y} \mid \boldsymbol{x})$, such that our new assumed generative model is

$$p(\boldsymbol{\theta}, \boldsymbol{x}, \boldsymbol{y}) = p(\boldsymbol{y} \mid \boldsymbol{x})p(\boldsymbol{x} \mid \boldsymbol{\theta})p(\boldsymbol{\theta}), \tag{1}$$

where we assume that the error distribution is independent of the simulator parameters $\boldsymbol{\theta}$. Using the equivalent factorisation $p(\boldsymbol{\theta}, \boldsymbol{x}, \boldsymbol{y}) = p(\boldsymbol{y})p(\boldsymbol{x} \mid \boldsymbol{y})p(\boldsymbol{\theta} \mid \boldsymbol{x})$, and marginalising over $\boldsymbol{x}$ yields

$$p(\boldsymbol{\theta}, \boldsymbol{y}) = p(\boldsymbol{y}) \int p(\boldsymbol{x} \mid \boldsymbol{y})p(\boldsymbol{\theta} \mid \boldsymbol{x}) \, \mathrm{d}\boldsymbol{x}. \tag{2}$$

Dividing by the marginal likelihood $p(\boldsymbol{y})$, we obtain an expression for the parameter posterior

$$p(\boldsymbol{\theta} \mid \boldsymbol{y}) = \int p(\boldsymbol{x} \mid \boldsymbol{y})p(\boldsymbol{\theta} \mid \boldsymbol{x}) \, \mathrm{d}\boldsymbol{x} = \mathbb{E}_{\boldsymbol{x} \sim p(\boldsymbol{x}|\boldsymbol{y})}[p(\boldsymbol{\theta} \mid \boldsymbol{x})]. \tag{3}$$

Equation (3) involves two unknown distributions, $p(\boldsymbol{x} \mid \boldsymbol{y})$ and $p(\boldsymbol{\theta} \mid \boldsymbol{x})$, which we require for inference. The distribution $p(\boldsymbol{\theta} \mid \boldsymbol{x})$ can be approximated by training a normalising flow $q(\boldsymbol{\theta} \mid \boldsymbol{x})$ on simulated data $(\boldsymbol{x}, \boldsymbol{\theta}) \sim p(\boldsymbol{x} \mid \boldsymbol{\theta})p(\boldsymbol{\theta})$, as is done for NPE. To approximately sample from $p(\boldsymbol{x} \mid \boldsymbol{y})$, we first train a normalising flow, $q(\boldsymbol{x})$, fitted to samples from prior predictive distribution of the simulator $\boldsymbol{x} \sim p(\boldsymbol{x})$. Given an error model $p(\boldsymbol{y} \mid \boldsymbol{x})$ specified *a priori*, we can then approximately sample from $p(\boldsymbol{x} \mid \boldsymbol{y})$ using MCMC, as $\hat{p}(\boldsymbol{x} \mid \boldsymbol{y}) \propto p(\boldsymbol{y} \mid \boldsymbol{x})q(\boldsymbol{x})$. With these approximations, we can sample the robust posterior $\hat{p}(\boldsymbol{\theta} \mid \boldsymbol{y})$ by first sampling $\tilde{\boldsymbol{x}} \sim \hat{p}(\boldsymbol{x} \mid \boldsymbol{y})$, then sampling $\tilde{\boldsymbol{\theta}} \sim q(\boldsymbol{\theta} \mid \tilde{\boldsymbol{x}})$,

---

[1]Sometimes also referred to as "model checking", (e.g. Gelman et al., 1995).

[2]Amortisation refers to the ability of a conditional distribution approximation to condition on arbitrary instances of the conditioning variable, rather than being specialised to a particular instance.

discarding the latent variable $\tilde{\boldsymbol{x}}$, where the tilde is used to distinguish from prior samples and simulations. A Monte Carlo approximation of the expectation in Equation (3) can be used to estimate the posterior density $\hat{p}(\boldsymbol{\theta} \mid \boldsymbol{y})$, i.e.

$$\hat{p}(\boldsymbol{\theta} \mid \boldsymbol{y}) \approx \frac{1}{M} \sum_{m=1}^{M} q(\boldsymbol{\theta} \mid \tilde{\boldsymbol{x}}_m), \qquad \tilde{\boldsymbol{x}}_1, \dots, \tilde{\boldsymbol{x}}_M, \stackrel{\text{iid}}{\sim} \hat{p}(\boldsymbol{x} \mid \boldsymbol{y}). \tag{4}$$

We will refer to $\hat{p}(\boldsymbol{x} \mid \boldsymbol{y}_o)$ as the denoised data distribution, as it intuitively finds a compromise between being close to the observed data $\boldsymbol{y}_o$, as measured by the error model $p(\boldsymbol{y} \mid \boldsymbol{x})$, but consistent with the simulator, as measured by $q(\boldsymbol{x})$. This formulation becomes natural when considering the generative model in (1). We are (approximately) reversing the new assumed data generating process whilst propagating uncertainty throughout, first removing the discrepancy between simulations and the observed data by denoising, and then finding the associated simulator parameters. Under this framework, the standard SBI approach can be retrieved as the special case in which $p(\boldsymbol{y} \mid \boldsymbol{x}) = p(\boldsymbol{x} \mid \boldsymbol{y}) = \delta(\boldsymbol{x} - \boldsymbol{y})$, where δ is the Dirac delta distribution, meaning that we revert to assuming no discrepancy between the simulator and data generating process. Pseudo-code for the overall approach is given in Algorithm 1.

Algorithm 1: Robust neural posterior estimation (RNPE)

for i *in* $1 : N$ **do**
1   Sample $\boldsymbol{\theta}_i \sim p(\boldsymbol{\theta})$
2   Simulate $\boldsymbol{x}_i \sim p(\boldsymbol{x} \mid \boldsymbol{\theta})$
end
3 Train $q(\boldsymbol{x})$ on $\{\boldsymbol{x}_i\}_{i=1}^{N}$
4 Train NPE $q(\boldsymbol{\theta} \mid \boldsymbol{x})$ on $\{(\boldsymbol{\theta}_i, \boldsymbol{x}_i)\}_{i=1}^{N}$
5 Sample $\tilde{\boldsymbol{x}}_m \sim q(\boldsymbol{x} \mid \boldsymbol{y}_o) \propto p(\boldsymbol{y}_o \mid \boldsymbol{x}) q(\boldsymbol{x})$, $m = 1, \dots, M$ using MCMC
6 Sample $\tilde{\boldsymbol{\theta}}_m \sim q(\boldsymbol{\theta} \mid \tilde{\boldsymbol{x}}_m)$, $m = 1, \dots, M$
return $\{(\tilde{\boldsymbol{\theta}}_m, \tilde{\boldsymbol{x}}_m)\}_{m=1}^{M}$, samples approximately from $p(\boldsymbol{\theta}, \boldsymbol{x} \mid \boldsymbol{y}_o)$

The idealised nature of simulation models implies that frequently there will be some characteristics of the observed data that are well captured by simulations, and some aspects in which there exists a discrepancy. Using a set of summary statistics for inference, rather than the raw data naturally captures an interpretable, low dimensional and diverse set of characteristics of the simulated and observed data. Because of this, we find that in general, reducing the raw data to summary statistics is advantageous for *model criticism*, as the practitioner can choose summary statistics which align with their belief about important model characteristics, and easily interpret any discrepancies (see Section 4.4). The requirement for domain specific knowledge to develop summary statistics has been alleviated by recent work (e.g. Fearnhead and Prangle, 2012; Chan et al., 2018; Chen et al., 2020), which seek to automatically embed the raw data to summary statistics; however, these embeddings often lack a tangible interpretation. Alternatively, both hand-crafted and automatic summary statistics could be used in tandem. Hereafter, however, we perform *model criticism* and *inference* using hand-crafted summary statistics, such that $\boldsymbol{x}$ and $\boldsymbol{y}_o$ refer to simulated and observed summary statistics, *not* the raw data.

2.2 Spike and Slab

An error model should describe our prior belief over the discrepancy between the data generating process and simulations. Additionally, to facilitate model criticism, it should ideally allow easy assessment of which summary statistics are approximately well-specified and which are misspecified. Inspired by sparsity-inducing priors used in Bayesian regression literature (George and McCulloch, 1993), we use a "spike and slab" error model on each summary statistic

$$\boldsymbol{x} \sim q(\boldsymbol{x}), \tag{5}$$
$$z_j \sim \text{Bernoulli}(\rho), \qquad j = 1, \dots, D \tag{6}$$
$$y_j \mid x_j, z_j = 0 \sim N(x_j, \sigma^2), \qquad j = 1, \dots, D \tag{7}$$
$$y_j \mid x_j, z_j = 1 \sim \text{Cauchy}(x_j, \tau), \qquad j = 1, \dots, D \tag{8}$$

147 where $\boldsymbol{x} \in \mathbb{R}^D$. As the summary statistics have varying scales, we standardise them to have mean
148 zero and variance one. The Bernoulli variables indicate whether the j-th summary statistic is
149 approximately well-specified; we use the probability of $\rho = 0.5$ to express the belief that it is equally
150 likely a summary statistic will be misspecified or well-specified *a priori*. Alternatively, a hyperprior
151 could be considered, but here we do not pursue this idea. When a summary statistic is well-specified
152 (i.e., $z_j = 0$), we take the error distribution to be a tight Gaussian (a spike) centered on x_j, choosing
153 $\sigma = 0.01$ to enforce consistency between the simulator and the observed data for the j-th statistic. In
154 contrast, in the misspecified case (i.e., $z_j = 1$), we take the error model to be the much wider and
155 heavy tailed Cauchy distribution (a slab). Generally, we might expect misspecification to be relatively
156 subtle, but some model inadequacies can lead to catastrophically misspecified summary statistics.
157 We chose the Cauchy scale $\tau = 0.25$, to reflect this, as it places half the mass within ± 0.25 standard
158 deviations of x_j, but the long tails accommodate summary statistics that are very misspecified. By
159 marginalising over $\boldsymbol{z}$, the spike and slab error model can also be written as

$$p(\boldsymbol{y} \mid \boldsymbol{x}) = \prod_{j=1}^{D} \big[(1 - \rho) \cdot p(y_j \mid x_j, z_j = 0) + \rho \cdot p(y_j \mid x_j, z_j = 1) \big], \qquad (9)$$

160 and as such can be viewed as an equally weighted mixture of the Gaussian spike, $p(y_j \mid x_j, z_j = 0)$,
161 and the Cauchy slab, $p(y_j \mid x_j, z_j = 1)$, for each summary statistic. We note that error model
162 hyperparameter tuning approaches could be considered, e.g. a reasonable heuristic would be to
163 choose an error model that is broad enough that the denoised data $\tilde{\boldsymbol{x}}$ tend not to be outliers in $q(\boldsymbol{x})$,
164 compared to simulations[3]. However, we chose to keep the hyperparameters consistent across tasks, to
165 avoid the risk of overfitting and to demonstrate that neither strong prior knowledge on the error model,
166 nor careful hyperparameter tuning is necessary to yield substantial improvements in performance.

167 A key advantage of the spike and slab error model is given by the latent variable $\boldsymbol{z}$. Similar to posterior
168 inclusion probabilities in Bayesian regression, the posterior frequency of $z_j = 1$, $p(z_j = 1 \mid \boldsymbol{y})$, can
169 be used as an indicator of the *posterior misspecification probability* for the j-th summary statistic.
170 By comparing to the prior misspecification probability ρ, we can say that if $p(z_j = 1 \mid \boldsymbol{y}) > \rho$, the
171 model provides evidence of misspecification for the j-th summary statistic, and if $p(z_j = 1 \mid \boldsymbol{y}) < \rho$,
172 it provides evidence it is well-specified (Talbott, 2016). For the purpose of generality, the latent
173 variable $\boldsymbol{z}$ was not included when describing RNPE thus far. However, we can jointly infer the
174 posterior $\hat{p}(\boldsymbol{x}, \boldsymbol{z} \mid \boldsymbol{y})$ in step 5 of algorithm 1, by using an MCMC algorithm that supports sampling
175 both continuous and discrete variables. For this purpose, we used mixed Hamiltonian Monte Carlo
176 (HMC) (Zhou, 2020, 2022) from the NumPyro python package (Phan et al., 2019).

3 Related Work

3.1 Model Criticism in SBI

179 Posterior predictive checks have been widely used in SBI, to compare the predictive samples to the
180 observed data (e.g. Durkan et al., 2020; Greenberg et al., 2019; Papamakarios et al., 2019b). Although
181 this is a form of model criticism, we note a key limitation of this approach is that if discrepancy is
182 discovered, it may not be clear whether this is due to the failure of the inference procedure, or due to
183 simulator misspecification. In general, it may be possible to identify the presence of misspecification
184 using anomaly/novelty detection. One such approach was suggested by Schmitt et al. (2021) in the
185 context of SBI. However, this approach does not facilitate interpreting misspecification, and it is not
186 clear how to extend it to perform robust inference.

187 There are a few related methods that criticise the a posterior estimate by assessing its calibration
188 using simulated data (e.g. Hermans et al., 2021; Prangle et al., 2014; Talts et al., 2018); however,
189 these results are only applicable under the assumption the model is well-specified.

3.2 Robust Inference in SBI

191 Approximate Bayesian computation (ABC) is a family of SBI methods, characterised by their use
192 of rejection sampling alongside a kernel function to compare the simulated and observed data

---

[3]This could for example be assessed by estimating highest density regions of $q(\boldsymbol{x})$, using the density quantile approach from Hyndman (1996)

(Tavaré et al., 1997; Pritchard et al., 1999; Beaumont et al., 2002). The simplest form of ABC uses simulations with $\boldsymbol{\theta} \sim p(\boldsymbol{\theta})$, and accepts parameters with probability proportional to the similarity of the corresponding simulations to the observed data. The use of a kernel is often seen as a necessary evil, as enforcing an exact match between the observed and simulated data generally results in all samples being rejected. However, it has been noted that the kernel function can often be interpreted as specifying an error model distribution $p(\boldsymbol{y} \mid \boldsymbol{x})$ (Wilkinson, 2013). This idea has been expanded using generalised Bayesian inference, in which the kernel is replaced with a loss function (Schmon et al., 2020), which can be chosen to use a robust measure of discrepancy such as the maximum mean discrepancy (MMD) (Chérief-Abdellatif and Alquier, 2020; Frazier et al., 2020a; Park et al., 2015). Similar ideas have also recently been applied by Dellaporta et al. (2022), who adapt non-parametric learning (see Lyddon et al., 2018) to SBI, to approximately sample a posterior which minimises the MMD between the model and data generating process. However, sampling this approximate posterior requires optimizing a non-convex MMD objective.

Synthetic likelihood is an SBI method that uses a Gaussian approximation of the likelihood (Wood, 2010). Frazier and Drovandi (2021) investigated a robust synthetic likelihood algorithm, in which the variance components of the Gaussian likelihood are expanded based on additional free parameters, inferred in a nested MCMC sampling scheme. In the context of the paper, they interpret this approach as "likelihood adjustment"; however, we note this could equivalently be reframed as the addition of an independent Gaussian error model, with a prior on the variances[4].

In contrast to more traditional SBI methods, few solutions have been proposed for performing robust inference with neural SBI methods. Perhaps the most common approach is to augment the model with additional nuisance parameters (e.g. additive noise), to expand the range of values the simulator can reasonably produce (Cranmer et al., 2020). This again can generally be interpreted as a naïve method of incorporating an error model, and does not facilitate *model criticism*.

4 Experiments

We benchmark the performance of RNPE for parameter inference for three misspecified tasks, comparing results to NPE. To reliably assess performance, we repeat the inference procedure with 1000 different observations and ground truth parameter pairs for each misspecified task, and assess the performance based on two metrics: *i)* the log probability of the true parameter vector, $\boldsymbol{\theta}^*$, and *ii)* the posterior coverage properties (see Section 4.3). We further show examples of RNPE on a single observation for each task. Looking at specific examples demonstrates how RNPE can be used in a practical setting to perform model criticism and robust posterior inference. The code required to reproduce all the results from this manuscript is available at REDACTED_FOR_ANONYMITY.

4.1 Setup

For all experiments, we used $N = 50,000$ simulations, with $M = 100,000$ MCMC samples following 20,000 warm up steps. The MCMC chains were initialised using a random simulation, and $z_j = 1$ for $j = 1, \ldots, D$. To build the approximation $q(\boldsymbol{x})$, we used block neural autoregressive flows (De Cao et al., 2020), as we do not require the ability to sample directly from $q(\boldsymbol{x})$. For the approximation of $q(\boldsymbol{\theta} \mid \boldsymbol{x})$, we utilised neural spline flows (Durkan et al., 2019). For all tasks the hyperparameters were kept consistent; information on hyperparameter choices can be found in Appendix A.3.

4.2 Tasks

Detailed descriptions of each task can be found in Appendix A.2.

Gaussian. A simple Gaussian example from Frazier et al. (2020b). The task involves predicting a single parameter μ, using the sample mean and variance of 100 i.i.d. samples drawn from $N(\mu, 1)$, where 1 is the variance of the Gaussian distribution. To artificially produce misspecified observations, the 100 i.i.d. are instead drawn from $N(\mu, 2)$. Despite its simplicity, this task usefully demonstrates that issues with misspecification can arise even in the simplest of models.

---

[4]This results due the fact that the addition of two independent Gaussian variables yields another Gaussian random variable, with covariance equal to the sum of the individual covariance matrices.

SIR. A stochastic model of epidemic spread with a time-varying infection rate. We attempt to infer two parameters, the infection rate β and the recovery rate γ. We draw daily infection counts for a period of 365 days and compute the following summary statistics: 1-3) `Mean`, `Median` and `Max` - the mean, median and maximum number of infections; 4) `Max Day` - the day of occurrence of the maximum number of infections, 5) `Half Day` - the day at which half the total number of infections was reached, and 6) `Autocor` - the mean autocorrelation (lag 1) of infections. To artificially produce misspecified observations, we chose to introduce a small degree of reporting delays, whereby weekend infection counts are reduced by 5%, which are subsequently recouped on the following Monday. Fig. 5 in the appendix shows an example misspecified simulation and a corresponding artificially produced observation.

CS. A marked point process model of cancer and stromal (CS) cell development in 2D-space, in which the locality of a cell relative to unobserved parent cells determines whether it is a cancer or a stromal cell. Similar point process models can be found in Jones-Todd et al. (2019). There are three Poisson rate parameters, corresponding to the cell rate λ_c, the parent rate λ_p and the daughter rate λ_d, where λ_d controls the number of nearest cells to each parent which become cancerous. We used the following summary statistics: 1-2) `N Cancer` and `N Stromal` - the number of cancer and stromal cells; 3-4) `Mean Min Dist` and `Max Min Dist` - the mean and maximum distance from stromal cells to their nearest cancer cell. Summary statistics 3-4 were approximated empirically through sampling 50 stromal cells, as the full distance matrix was too expensive to compute. To artificially produce misspecified observations, cancer cells were removed if they fell too close to the cancer parent, mimicking necrosis that often occurs in core regions of tumours. A plot of an example misspecified simulation and a corresponding artificially produced observation can be found in Fig. 6 in the appendix.

4.3 Performance Metrics

Log probability of θ^*. The mean posterior log probability of the true parameters over multiple observations is an extensively used performance metric (e.g. Papamakarios and Murray, 2016; Hermans et al., 2020; Durkan et al., 2020), and is closely related to the average KL divergence between the true and approximate posteriors (Lueckmann et al., 2021). We found that NPE would occasionally fail catastrophically, placing negligible posterior mass on the true parameters, skewing the mean estimates. Due to this, we instead use box plots to visualise the distribution over the log-probabilities of the true parameters, rather than reporting the mean.

Posterior Coverage. Given a confidence level α and a posterior approximation $\hat{p}(\boldsymbol{\theta} \mid \boldsymbol{y})$, let $\text{HDR}_{\hat{p}(\boldsymbol{\theta}|\boldsymbol{y})}(1 - \alpha)$ represent its $1 - \alpha$ highest posterior density region, i.e. the smallest region that contains at least $100(1 - \alpha)\%$ of the mass of $\hat{p}(\boldsymbol{\theta} \mid \boldsymbol{y})$. The expected posterior coverage is the frequency with which the true parameter value falls within this highest density region

$$\mathbb{E}_{\boldsymbol{\theta}^*, \boldsymbol{y} \sim p(\boldsymbol{\theta}, \boldsymbol{y})} \left[\mathbb{1}\{\boldsymbol{\theta}^* \in \text{HDR}_{\hat{p}(\boldsymbol{\theta}|\boldsymbol{y})}(1 - \alpha)\} \right] \tag{10}$$

where $\mathbb{1}$ is the indicator function. Posterior coverage is useful for assessing whether an inference procedure is likely to yield overconfident or conservative posterior estimates (Hermans et al., 2021). We empirically estimate this expectation, approximating the highest density regions using the density quantile approach outlined in Hyndman (1996), with 10,000 samples from the approximate posterior.

4.4 Results

Overall Performance. When assessing the overall inference performance, we find that RNPE consistently outperforms NPE across all the tasks (Fig. 2). RNPE tends to put higher posterior density on the true parameters $\boldsymbol{\theta}^*$, frequently by several orders of magnitude (note the log scale). Further, RNPE produces posteriors with better coverage properties, being more conservative than NPE across all the tasks (Fig. 2b). NPE has very poor posterior coverage across all the tasks, with misspecification exacerbating the issues found by Hermans et al. (2021) in the well-specified case. It is important to note that having conservative posterior estimates is generally considered preferable to having overconfident posterior estimates. If an algorithm tends to produce overconfident posteriors, it becomes difficult to know whether the inference should be trusted, and trusting the results may lead to drawing erroneous scientific conclusions.

Gaussian. An example for the Gaussian task can be seen in Fig. 1, in which x_1 corresponds to the mean statistic, and x_2 the variance. From observing the posterior misspecification probabilities and

(a) The log-probability of the true parameters $\boldsymbol{\theta}^*$ in the approximate posteriors formed by RNPE and NPE.

(b) The coverage of RNPE and NPE, at different confidence levels. A well-calibrated posterior follows the dotted line, with conservative posteriors lying above the dotted line, and overconfident posteriors falling below the dotted line.

Figure 2: Comparative performance of NPE and RNPE on the three misspecified tasks, using 1000 different observation and true parameter pairs.

the denoised samples, the results clearly identify a discrepancy in which the observed variance statistic is higher than the simulated variance statistics, allowing identification of source of misspecification. As this is a simple example, we can analytically access the true posterior (obtained using the true data generating model). RNPE produces a posterior close to the ground-truth, whereas NPE confidently places most of the posterior mass far from the ground-truth posterior.

SIR. In the SIR model, the observed data were artificially corrupted by mimicking reporting delays over the weekend. With this in mind, we can consider how the *model criticism* aspect of RNPE could facilitate identification of the issue. Fig. 3a shows that most summary statistics are more likely to be well-specified than was believed *a priori*, with the clear exception of the `Autocor` summary statistic, which is inferred to be misspecified. Fig. 3b shows a density plot of the denoised data for the `Autocor` summary statistic, showing that the observed autocorrelation is much lower relative to what would be expected under the model. This may prompt the practitioner to investigate the day-to-day changes in infections, in which case the discontinuities introduced by the reporting delays could be identified. Fig. 3c shows the posteriors for RNPE and NPE. RNPE yields a posterior with far lower variance than NPE, demonstrating an example where it does not achieve robustness simply by producing broader posterior estimates.

Figure 3: The results for an example of the SIR task: a) the inferred posterior misspecification probabilities for each summary statistic; b) density plot for the denoised samples of the autocorrelation summary statistic; c) The posteriors for both NPE and RNPE.

CS. In the CS model, the observed data was corrupted by removing cells in the core regions of tumours, mimicking necrosis (see Fig. 6). This misspecification primarily impacts the `N Cancer` summary statistic (the number of cancer cells). From Figs. 4a,4b, we can see that the results provide evidence that the `N Cancer` statistic is misspecified, with the observed data having fewer cancer

Figure 4: The results for an example of the CS task: a) the inferred posterior misspecification probabilities for each summary statistic; b) density plot for the denoised samples of the `N Cancer` summary statistic; c) a pair plot of the posteriors for both NPE and RNPE.

cells than would be expected if it was generated from the simulator. Once again, alongside domain knowledge, this information points the practitioner to the source of misspecification (necrosis), and hence the model could be adjusted appropriately. For this example, NPE produced an overconfident posterior with little mass on the true parameters, whereas RNPE does not exhibit this issue (Fig. 4c).

5   Conclusions

We described RNPE, an approach that can be applied to any black-box simulator to simultaneously perform *model criticism*, and perform *robust inference*. RNPE is philosophically similar to existing robust SBI approaches for ABC and synthetic likelihood (Wilkinson, 2013; Frazier and Drovandi, 2021). However, this work introduces two novel contributions: *i)* we propose the first strategy for performing robust inference with a neural SBI method, which have advantages in simulation efficiency, flexibility and scaling to high dimensional problems (Lueckmann et al., 2021), and *ii)* we use a spike-and-slab error model to get explicit misspecification probability diagnostics for summary statistics, to facilitate *model criticism*. Here, we restricted focus to extending NPE. In future work it would be interesting to develop robust extensions for other SBI algorithms and to compare results with existing methods. Additionally, it would be beneficial to develop a larger set of realistic misspecified tasks for assessing performance of robust SBI methods, similar to the work by Lueckmann et al. (2021) for the well-specified case.

We demonstrated with three examples, that RNPE consistently outperforms NPE for parameter inference under misspecification, tending to put more posterior mass on the true parameters, whilst also exhibiting better coverage properties. The tasks were designed to mimic levels of misspecification that could be realistically encountered, and hence the poor performance of NPE calls into question its use in practice, particularly when the level of misspecification could be significant. The stark difference in performance highlights, as suggested by Box (1980), that we should not have blind faith that a model is sufficiently accurate, and therefore we must devise methods for performing *model criticism* and *robust inference*. With further research and wider adoption of these principles in SBI, we believe simulators will only become more powerful tools for scientific discovery.

References

Atkeson, A., Kopecky, K., and Zha, T. (2020). Estimating and forecasting disease scenarios for COVID-19 with an SIR model. Technical report, National Bureau of Economic Research.

Beaumont, M. A., Zhang, W., and Balding, D. J. (2002). Approximate Bayesian computation in population genetics. *Genetics*, 162(4):2025–2035.

Bingham, E., Chen, J. P., Jankowiak, M., Obermeyer, F., Pradhan, N., Karaletsos, T., Singh, R., Szerlip, P., Horsfall, P., and Goodman, N. D. (2019). Pyro: Deep universal probabilistic programming. *The Journal of Machine Learning Research*, 20(1):973–978.

Box, G. E. (1980). Sampling and Bayes' inference in scientific modelling and robustness. *Journal of the Royal Statistical Society: Series A (General)*, 143(4):383–404.

Bradbury, J., Frostig, R., Hawkins, P., Johnson, M. J., Leary, C., Maclaurin, D., Necula, G., Paszke, A., VanderPlas, J., Wanderman-Milne, S., and Zhang, Q. (2018). JAX: composable transformations of Python+NumPy programs.

Brehmer, J., Kling, F., Espejo, I., and Cranmer, K. (2020). Madminer: Machine learning-based inference for particle physics. *Computing and Software for Big Science*, 4(1):1–25.

Chan, J., Perrone, V., Spence, J., Jenkins, P., Mathieson, S., and Song, Y. (2018). A likelihood-free inference framework for population genetic data using exchangeable neural networks. *Advances in neural information processing systems*, 31.

Chen, Y., Zhang, D., Gutmann, M., Courville, A., and Zhu, Z. (2020). Neural approximate sufficient statistics for implicit models. *arXiv preprint arXiv:2010.10079*.

Chérief-Abdellatif, B.-E. and Alquier, P. (2020). MMD-Bayes: Robust Bayesian estimation via maximum mean discrepancy. In *Symposium on Advances in Approximate Bayesian Inference*, pages 1–21. PMLR.

Cranmer, K., Brehmer, J., and Louppe, G. (2020). The frontier of simulation-based inference. *Proceedings of the National Academy of Sciences*, 117(48):30055–30062.

De Cao, N., Aziz, W., and Titov, I. (2020). Block neural autoregressive flow. In *Uncertainty in artificial intelligence*, pages 1263–1273. PMLR.

Dellaporta, C., Knoblauch, J., Damoulas, T., and Briol, F.-X. (2022). Robust Bayesian inference for simulator-based models via the MMD posterior bootstrap. In *International Conference on Artificial Intelligence and Statistics*, pages 943–970. PMLR.

Durkan, C., Bekasov, A., Murray, I., and Papamakarios, G. (2019). Neural spline flows. *Advances in neural information processing systems*, 32.

Durkan, C., Murray, I., and Papamakarios, G. (2020). On contrastive learning for likelihood-free inference. In *International Conference on Machine Learning*, pages 2771–2781. PMLR.

Fearnhead, P. and Prangle, D. (2012). Constructing summary statistics for approximate Bayesian computation: semi-automatic approximate Bayesian computation. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 74(3):419–474.

Ferguson, N. M., Laydon, D., Nedjati-Gilani, G., Imai, N., Ainslie, K., Baguelin, M., Bhatia, S., Boonyasiri, A., Cucunubá, Z., Cuomo-Dannenburg, G., et al. (2020). Impact of non-pharmaceutical interventions (NPIs) to reduce covid-19 mortality and healthcare demand.

Frazier, D. T. and Drovandi, C. (2021). Robust approximate Bayesian inference with synthetic likelihood. *Journal of Computational and Graphical Statistics*, 30(4):958–976.

Frazier, D. T., Drovandi, C., and Loaiza-Maya, R. (2020a). Robust approximate Bayesian computation: An adjustment approach. *arXiv preprint arXiv:2008.04099*.

Frazier, D. T., Robert, C. P., and Rousseau, J. (2020b). Model misspecification in approximate Bayesian computation: consequences and diagnostics. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 82(2):421–444.

Gelman, A., Carlin, J. B., Stern, H. S., and Rubin, D. B. (1995). *Bayesian data analysis*. Chapman and Hall/CRC.

Gelman, A. and Shalizi, C. R. (2013). Philosophy and the practice of Bayesian statistics. *British Journal of Mathematical and Statistical Psychology*, 66(1):8–38.

George, E. I. and McCulloch, R. E. (1993). Variable selection via Gibbs sampling. *Journal of the American Statistical Association*, 88(423):881–889.

Greenberg, D., Nonnenmacher, M., and Macke, J. (2019). Automatic posterior transformation for likelihood-free inference. In *International Conference on Machine Learning*, pages 2404–2414. PMLR.

Grünwald, P. and Langford, J. (2007). Suboptimal behavior of Bayes and MDL in classification under misspecification. *Machine Learning*, 66(2):119–149.

Grünwald, P. and Van Ommen, T. (2017). Inconsistency of Bayesian inference for misspecified linear models, and a proposal for repairing it. *Bayesian Analysis*, 12(4):1069–1103.

Hermans, J., Begy, V., and Louppe, G. (2020). Likelihood-free mcmc with amortized approximate ratio estimators. In *International Conference on Machine Learning*, pages 4239–4248. PMLR.

Hermans, J., Delaunoy, A., Rozet, F., Wehenkel, A., and Louppe, G. (2021). Averting a crisis in simulation-based inference. *arXiv preprint arXiv:2110.06581*.

Hyndman, R. J. (1996). Computing and graphing highest density regions. *The American Statistician*, 50(2):120–126.

Jones-Todd, C. M., Caie, P., Illian, J. B., Stevenson, B. C., Savage, A., Harrison, D. J., and Bown, J. L. (2019). Identifying prognostic structural features in tissue sections of colon cancer patients using point pattern analysis. *Statistics in medicine*, 38(8):1421–1441.

Kidger, P. and Garcia, C. (2021). Equinox: neural networks in JAX via callable pytrees and filtered transformations. *arXiv preprint arXiv:2111.00254*.

Kleijn, B. J. and van der Vaart, A. W. (2012). The Bernstein-von-Mises theorem under misspecification. *Electronic Journal of Statistics*, 6:354–381.

Lam, S. K., Pitrou, A., and Seibert, S. (2015). Numba: A LLVM-based python JIT compiler. In *Proceedings of the Second Workshop on the LLVM Compiler Infrastructure in HPC*, pages 1–6.

Lueckmann, J.-M., Boelts, J., Greenberg, D., Goncalves, P., and Macke, J. (2021). Benchmarking simulation-based inference. In *International Conference on Artificial Intelligence and Statistics*, pages 343–351. PMLR.

Lyddon, S., Walker, S., and Holmes, C. C. (2018). Nonparametric learning from Bayesian models with randomized objective functions. *Advances in Neural Information Processing Systems*, 31.

Metropolis, N., Rosenbluth, A. W., Rosenbluth, M. N., Teller, A. H., and Teller, E. (1953). Equation of state calculations by fast computing machines. *The journal of chemical physics*, 21(6):1087–1092.

Papamakarios, G. and Murray, I. (2016). Fast ε-free inference of simulation models with Bayesian conditional density estimation. *Advances in neural information processing systems*, 29.

Papamakarios, G., Nalisnick, E., Rezende, D. J., Mohamed, S., and Lakshminarayanan, B. (2019a). Normalizing flows for probabilistic modeling and inference. *arXiv preprint arXiv:1912.02762*.

Papamakarios, G., Sterratt, D., and Murray, I. (2019b). Sequential neural likelihood: Fast likelihood-free inference with autoregressive flows. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 837–848. PMLR.

Park, M., Jitkrittum, W., and Sejdinovic, D. (2015). K2-ABC: approximate Bayesian computation with kernel embeddings. *arXiv preprint arXiv:1502.02558*.

Perla, J., Sargent, T. J., Stachurski, J., and Rackauckas, C. (2022). Quantitative economics with julia: Modeling shocks in covid 19 with stochastic differential equations.

Phan, D., Pradhan, N., and Jankowiak, M. (2019). Composable effects for flexible and accelerated probabilistic programming in NumPyro. *arXiv preprint arXiv:1912.11554*.

Prangle, D., Blum, M. G., Popovic, G., and Sisson, S. (2014). Diagnostic tools for approximate Bayesian computation using the coverage property. *Australian & New Zealand Journal of Statistics*, 56(4):309–329.

Pritchard, J. K., Seielstad, M. T., Perez-Lezaun, A., and Feldman, M. W. (1999). Population growth of human y chromosomes: a study of y chromosome microsatellites. *Molecular biology and evolution*, 16(12):1791–1798.

Rackauckas, C. and Nie, Q. (2017). Differentialequations. jl–a performant and feature-rich ecosystem for solving differential equations in julia. *Journal of Open Research Software*, 5(1).

Randall, D. A., Wood, R. A., Bony, S., Colman, R., Fichefet, T., Fyfe, J., Kattsov, V., Pitman, A., Shukla, J., Srinivasan, J., et al. (2007). Climate models and their evaluation. In *Climate change 2007: The physical science basis. Contribution of Working Group I to the Fourth Assessment Report of the IPCC (FAR)*, pages 589–662. Cambridge University Press.

Schmitt, M., Bürkner, P.-C., Köthe, U., and Radev, S. T. (2021). Bayesflow can reliably detect model misspecification and posterior errors in amortized Bayesian inference. *arXiv preprint arXiv:2112.08866*.

Schmon, S. M., Cannon, P. W., and Knoblauch, J. (2020). Generalized posteriors in approximate Bayesian computation. *arXiv preprint arXiv:2011.08644*.

Syring, N. and Martin, R. (2019). Calibrating general posterior credible regions. *Biometrika*, 106(2):479–486.

Talbott, W. (2016). Bayesian Epistemology. In Zalta, E. N., editor, *The Stanford Encyclopedia of Philosophy*. Metaphysics Research Lab, Stanford University, Winter 2016 edition.

Talts, S., Betancourt, M., Simpson, D., Vehtari, A., and Gelman, A. (2018). Validating Bayesian inference algorithms with simulation-based calibration. *arXiv preprint arXiv:1804.06788*.

Tavaré, S., Balding, D. J., Griffiths, R. C., and Donnelly, P. (1997). Inferring coalescence times from DNA sequence data. *Genetics*, 145(2):505–518.

Wilkinson, R. D. (2013). Approximate Bayesian computation (ABC) gives exact results under the assumption of model error. *Statistical applications in genetics and molecular biology*, 12(2):129–141.

Wood, S. N. (2010). Statistical inference for noisy nonlinear ecological dynamic systems. *Nature*, 466(7310):1102–1104.

Zhou, G. (2020). Mixed Hamiltonian Monte Carlo for mixed discrete and continuous variables. *Advances in Neural Information Processing Systems*, 33:17094–17104.

Zhou, G. (2022). Metropolis augmented hamiltonian monte carlo. *arXiv preprint arXiv:2201.08044*.