Data Efficacy for Language Model Training

Abstract

Data is fundamental to the training of language models (LM). Recent research has focused on data efficiency, aiming to reduce data scale without compromising model performance. However, data efficacy, which emphasizes improving model performance by optimizing the utilization of training data, remains underexplored. To address this gap, we propose **DELT** (**D**ata **E**fficacy for **LM** **T**raining), a novel method comprising *Folding Ordering (FO)* and *Learnability-Quality Scoring (LQS)*. *FO* mitigates model forgetting and data distribution bias caused by traditional curriculum learning in modern LM training with limited epochs. *LQS* offers robust scoring by considering multiple perspectives to support *FO* ordering. Comprehensive experiments demonstrate that DELT significantly outperforms baselines, including random shuffle and curriculum learning. Moreover, it synergizes with existing data efficiency methods such as KenLM, DSIR, and PDS, amplifying their effectiveness. As a pluggable solution, DELT boosts model performance without altering data scale and model size.

Figure 1: Average result across 8 benchmarks. High performance at the same selection ratio indicates high efficacy, while achieving similar performance with a smaller selection ratio demonstrates high efficiency. Our method excels in both efficacy and efficiency.

1   Introduction

Language models (Ouyang et al., 2022; Achiam et al., 2023; Dubey et al., 2024a) have fundamentally transformed modern computational applications, revolutionizing how machines comprehend, generate, and interact with humans through natural language. Their impact spans diverse tasks, from translation (Hirschberg and Manning, 2015) and sentiment analysis (Gunasekaran, 2023) to complex applications such as automated reasoning (Yu et al., 2024a) and AI agents (Kusal et al., 2022). As central to these capabilities, data is the foundation from which models learn linguistic patterns, structures, and knowledge. Consequently, meticulous data curation is essential for achieving consistently high model performance across applications.

In data curation, two complementary research directions have emerged. Data efficiency focuses on reducing the scale of training data without sacrificing model performance (Albalak et al., 2024; Xie et al., 2023; Gu et al., 2025). In contrast, data efficacy, which is defined as optimizing the utilization of training data to improve model performance, remains relatively unexplored. Standard data efficiency pipelines typically treat retained samples uniformly, presenting them to the model in random order. Data efficacy, however, explores how to exploit these samples more effectively through informed ordering, weighting, or scheduling strategies. While still nascent, its potential is exemplified by curriculum learning (Wang et al., 2021), which presents examples in order from easy to hard.

A critical consideration for modern language models is that the latest generations (OpenAI; Dubey et al., 2024a; Team et al., 2023) are typically trained for only one or a few epochs, rather than many. This shift stems from the immense scale of their training datasets and computational constraints, distinguishing them from earlier models (Cho et al., 2014; Hochreiter and Schmidhuber, 1997) trained over numerous epochs and often suffered from overfitting. This practice aligns with scaling law principles (Kaplan et al., 2020a) and is further supported by QQT (Goyal et al., 2024), which demonstrates that the utility of high-quality data diminishes rapidly under extensive reuse. Therefore, *optimally utilizing training data becomes crucial for maximizing the performance of language models trained in limited epochs.*

Building on these insights, we propose DELT to enhance data efficacy for LM training. This method improves model performance by fully harnessing data value without modifying dataset content or model architecture, making it cost-effective. Specifically, DELT incorporates data ordering and scoring. For data ordering, we introduce Folding Ordering (FO), a method inspired by human learning practices where content with similar distribution is revisited multiple times. Unlike traditional curriculum learning approaches (Campos, 2021) that directly sort data and risk introducing model forgetting (Wang et al., 2021) and data distribution bias in limited-epoch settings, FO significantly mitigates these challenges, particularly for modern language model training scenarios. For data scoring, we present Learnability-Quality Scoring (LQS), which captures sample learnability through dynamic gradient magnitude changes and evaluates sample quality using gradient angle information. By combining these complementary aspects, LQS enables optimized sample organization.

To validate DELT, we incorporate several baseline methods using our LQS and FO for data scoring and ordering. As shown in Figure 1, DELT significantly improves data efficacy in language model training across typical benchmarks. Furthermore, it outperforms existing efficiency methods (Gu et al., 2025; Heafield, 2011) across all selection ratios. The main contributions are:

- We identify the unexplored potential of data efficacy in modern language model training and propose DELT, a novel method that enhances model performance without altering data scale and model size.

- We introduce Folding Ordering (FO) for data ordering and Learnability-Quality Scoring (LQS) for data scoring in DELT to address known issues, like model forgetting, in existing methods.

- We conducted comprehensive experiments on mainstream benchmarks, demonstrating that DELT achieves superior results in both efficacy and efficiency over existing baselines.

Through these contributions, we provide a general method for understanding and applying data efficacy in language model training, paving the way for more effective model development practices.

2 Related work

Data efficiency (Heafield, 2011; Gu et al., 2025; Xie et al., 2023; Albalak et al., 2024) optimizes language models by selecting relevant training data through strategies like data selection (Heafield, 2011; Gu et al., 2025; Yu et al., 2024b; Dai et al.), sampling (Xie et al., 2023), denoising (Zhao et al., 2021; Hu et al., 2021), and deduplication (Abbas et al., 2023; Tirumala et al., 2023). Primarily, these methods make binary retain-or-discard decisions and typically train on retained samples equally.

Data efficacy aims to maximize performance by optimizing training data organization. Prominent approaches include curriculum learning (Campos, 2021; Kim and Lee, 2024; Chang et al., 2021) and annealing (Dubey et al., 2024a). While these methods sort data directly by difficulty or quality, there remains no established paradigm for effectively organizing data in modern language model training. For detailed review of specific methods about data efficiency and efficacy, please see Appendix A.

To conclude, obtaining new public data has become challenging due to stagnant CommonCrawl (Rana, 2010) snapshots and AI-generated content pollution. Consequently, effectively leveraging existing datasets is vital, making data efficacy increasingly crucial as language models scale. Since data efficacy remains underexplored in current training paradigms, we propose a general method, DELT, to address this gap.

3 Method

3.1 Data Ordering

Existing ordering methods usually utilize the random shuffling method to organize training data. Alternatively, some approaches adopt curriculum learning (Campos, 2021; Kim and Lee, 2024), a sorting-based method inspired by the human learning process, where training begins with simpler samples and gradually progresses to more complex ones. Sorting-based methods can improve training efficiency; however, they often face challenges such as model forgetting and data distribution bias, as studied in previous work (Wang et al., 2021) and analyzed in the Appendix 18, which can ultimately degrade performance.

Data ordering, denoted by π, reorganizes the dataset $\mathcal{D}$ into a new dataset $\mathcal{D}'$ with unchanged size. This reorganization is based on a permutation π determined by γ, the scoring result of each data sample in $\mathcal{D}$.

Folding Ordering (FO) is proposed to improve training data efficacy and address the negative influences brought by the direct sorting method. The permutation function of sorting π_{sort}, illustrated in Eq. 1, returns the indices of each sample in γ.

$$\pi_{sort}(\mathcal{D}; \boldsymbol{\gamma}) = \left[x_{\pi(\gamma)_1}, x_{\pi(\gamma)_2}, \cdots, x_{\pi(\gamma)_{|\mathcal{D}|}} \right] \quad (1)$$

The new method reorganizes the dataset by iterating the curriculum learning process multiple times without duplicating data, while preserving a similar content distribution in each circle by folding strategy. The folding layers, defined as L, represent the number of iterations. As demonstrated in the right of Figure 2, the FO method samples sorted data L times without replacement at a fixed interval L.

$$\pi_{fold}(\mathcal{D}; \boldsymbol{\gamma}; L) = \bigcup_{\ell=0}^{L-1} \langle \pi_{sort}(\mathcal{D}; \boldsymbol{\gamma})_i \mid i \in \{j \mid j \equiv \ell \pmod{L}\} \rangle \quad (2)$$

The permutation function of folding π_{fold} is defined in Eq. 2. Folding ordering not only inherits the benefits from direct sorting but also mitigates issues of model forgetting and data distribution bias caused by it.

3.2 Data Scoring

Existing scoring methods typically focus on attributes such as quality (Gu et al., 2025), difficulty (Heafield, 2011), noisiness (Zhao et al., 2021; Hu et al., 2021), or diversity (Abbas et al., 2023; Tirumala et al., 2023) to compute scores for data selection. However, these methods, designed primarily for data selection, often focus solely on how *good* a sample is, while overlooking *where* a sample contributes most effectively within the context of the entire dataset.

Learnability-Quality Scoring (LQS) is introduced to address this limitation and make the scoring process more attentive to the utility of each data sample. By incorporating both *learnability* and *quality*, LQS is not only sensitive to low-quality samples but also better weights the impact of samples during model training. Our method dynam-

(a) Random Shuffle   (b) Ascending Sorting   (c) Folding (Ours)

Figure 2: Illustration of ordering methods. The right one is Folding method, an advanced multi-fold version of the Sorting method. These results are based on 500 random samples from RedPajama.

ically evaluates how each sample contributes to reducing the downstream loss $J(\boldsymbol{\theta})$ by considering its behavior at different training stages, where $\boldsymbol{\theta} \in \mathbb{R}^N$ represents the parameters of the LM and the N is the dimension of the parameter space.

$$\sum \frac{l_{1,t}}{l_{1,t+1}} > \sum \frac{l_{2,t}}{l_{2,t+1}} > \sum \frac{l_{3,t}}{l_{3,t+1}}$$

(a) Learnability Scores: $\mathcal{L}(x_1) > \mathcal{L}(x_2) > \mathcal{L}(x_3)$

$$\sum \cos(\alpha_{1,t}) > \sum \cos(\alpha_{2,t}) > \sum \cos(\alpha_{3,t})$$

(b) Quality Scores: $Q(x_1) > Q(x_2) > Q(x_3)$

Figure 3: Illustration of LQS scoring method. The left part demonstrates the calculation of the learnability score, and the right part depicts the computation of the quality score.

The ***learnability*** of each data sample represents the difficulty change during model training, as illustrated in Figure 3a. For each training step t from 1 to T on the dataset $\mathcal{D} = \{x_n\}_{n=1}^{|\mathcal{D}|}$, the learnability of a sample x_n (the n-th sample in $\mathcal{D}$) is defined as its contribution to reducing the loss over time during training. The learnability is represented as:

$$\mathcal{L}(x_n) = \sum_{t=1}^{T-1} \frac{l_{n,t}}{l_{n,t+1}} = \sum_{t=1}^{T-1} \frac{\|\nabla\ell(x_n, \boldsymbol{\theta}_t)\|}{\|\nabla\ell(x_n, \boldsymbol{\theta}_{t+1})\|}, \quad (3)$$

where $\nabla\ell(x_n, \boldsymbol{\theta}_t)$ denotes the gradient of loss function for sample x_n at training step t, with model parameters $\boldsymbol{\theta}_t$, and $l_{n,t}$ is its magnitude. A high learnability score indicates that the sample significantly reduces the loss in training, particularly if its gradient magnitude is initially high and decreases substantially over time. Such samples are challenging yet beneficial for training, making them more suitable for later stages of training. Conversely, noisy samples or those with unstable gradients yield a low score, enabling their identification and efficient filtering during data selection.

The ***quality*** of each data sample contributes to data efficacy during model training, as depicted in Figure 3b. It is measured by the consistency of $\nabla\ell(x_n, \boldsymbol{\theta}_t)$ with a target vector $\boldsymbol{\lambda}_{t+1}$ in Equation 5, which represents the average gradient of the loss function for all data at training step $t + 1$. The quality score is computed as:

$$Q(x_n) = \sum_{t=1}^{T-1} \cos(\alpha_{n,t}) = \sum_{t=1}^{T-1} \frac{\boldsymbol{\lambda}_{t+1}^\top \nabla\ell(x_n, \boldsymbol{\theta}_t)}{\|\boldsymbol{\lambda}_{t+1}\| \cdot \|\nabla\ell(x_n, \boldsymbol{\theta}_t)\|}, \quad (4)$$

where $\alpha_{n,t}$ is the angle between two vectors. A higher cosine similarity $\cos(\alpha_{n,t})$ indicates that the gradient convergence direction on x_n is more aligned with the target objective $\boldsymbol{\lambda}_{t+1}$, implying

a stronger contribution to reducing the loss $J(\boldsymbol{\theta})$. Following Gu et al. (2025), the target vector $\boldsymbol{\lambda}_t$ is:

$$\boldsymbol{\lambda}_t = \begin{cases} \boldsymbol{\lambda}_{t+1} + \nabla J(\boldsymbol{\theta}_t) - \eta \cdot \nabla^2 L(\boldsymbol{\theta}_t, \boldsymbol{\gamma}) \cdot \boldsymbol{\lambda}_{t+1}, & \text{if } t < T \\ \nabla J(\boldsymbol{\theta}_t), & \text{if } t = T \end{cases} \quad (5)$$

Besides, the ***reliability*** of these scores is directly influenced by the capability of the model checkpoint. Models with stronger capabilities produce more reliable scores. This capability is linked to the target vector, which is calculated as an average across all samples. When the structural parameters of the model remain unchanged, a stronger model shows greater consistency in the gradient directions of all samples concerning the model parameters, resulting in a larger $\nabla J(\boldsymbol{\theta}_t)$ (Equation 5). This corresponds to a greater magnitude of the target vector. Therefore, we use the magnitude of the target vector to directly measure the model's capability, referred to as the reliability score:

$$\text{R}(\boldsymbol{\theta}_{t+1}) = \|\boldsymbol{\lambda}_{t+1}\| \quad (6)$$

Finally, we combine *learnability* and *quality* into a unified function to score data samples. Meanwhile, a stronger model checkpoint will assign more weight to the scores. LQS is expressed as a combination of the sample's learnability-quality score and the model's capabilities.

$$\gamma_n = \text{R}(\boldsymbol{\theta}_{t+1}) \cdot \text{Q}(x_n) \cdot \mathcal{L}(x_n) \quad (7)$$

$$= \sum_{t=1}^{T-1} \|\boldsymbol{\lambda}_{t+1}\| \cdot \frac{\boldsymbol{\lambda}_{t+1}^\top \nabla \ell(x_n, \boldsymbol{\theta}_t)}{\|\boldsymbol{\lambda}_{t+1}\| \cdot \|\nabla \ell(x_n, \boldsymbol{\theta}_t)\|} \cdot \frac{\|\nabla \ell(x_n, \boldsymbol{\theta}_t)\|}{\|\nabla \ell(x_n, \boldsymbol{\theta}_{t+1})\|}$$

$$= \sum_{t=1}^{T-1} \frac{\boldsymbol{\lambda}_{t+1}^\top \nabla \ell(x_n, \boldsymbol{\theta}_t)}{\|\nabla \ell(x_n, \boldsymbol{\theta}_{t+1})\|} \quad (8)$$

For a detailed explanation of the formula, the score vector $\boldsymbol{\gamma}$ is defined as:

$$\boldsymbol{\gamma} = \left\{ \gamma_n \,\middle|\, \gamma_n = \sum_{t=1}^{T-1} \frac{\boldsymbol{\lambda}_{t+1}^\top \nabla \ell(x_n, \boldsymbol{\theta}_t)}{\|\nabla \ell(x_n, \boldsymbol{\theta}_{t+1})\|}, 1 \leq n \leq |\mathcal{D}| \right\} \quad (9)$$

Larger γ_n values indicate samples with higher quality and significant contributions to reducing the downstream loss $J(\boldsymbol{\theta})$, especially when introduced during later training stages. In contrast, lower γ_n values correspond to samples that are easy and less informative, better suited for early-stage training, or potentially noisy, which can be filtered out in data selection settings. Notably, our method calculates LQS on only a small set of data points, using a trained small model for scoring. Consequently, our method requires relatively low computational cost, as discussed in Appendix 4.5.

Our data scoring method follows these steps: **1) Proxy data sampling**. A proxy dataset $\mathcal{D}^{\text{prx}}$ is first uniformly sampled from the pre-training corpus $\mathcal{D}$, serving as a representative subset of the larger corpus. **2) Proxy data annotation.** We apply Eq. 9 to compute data scores for each instance in $\mathcal{D}^{\text{prx}}$, obtaining a set of data samples with scores as ground truth (see Section 3.2). **3) Data scorer training.** The data scorer, typically a small LM, is fine-tuned on the automatically annotated data samples in $\mathcal{D}^{\text{prx}}$ to predict data scores effectively (see Section 3.2). **4) Full data scoring.** The trained data scorer is then applied to regress scores for the entire pre-training corpus $\mathcal{D}$.

Algorithm 1 Proxy Data Annotation

Require: LM learning rate η. Proxy data $\mathcal{D}^{\text{prx}}$. Downstream loss $J(\boldsymbol{\theta})$. Training steps T. $\text{Proj}[\cdot]$ that projects a point in $\mathbb{R}^{|\mathcal{D}|}$ to U. Model initialization $\boldsymbol{\theta}_0$.
Ensure: Data quality scores $\boldsymbol{\gamma}^*$.
  $\boldsymbol{\gamma}^* = [\gamma_1^*, \gamma_2^*, \cdots, \gamma_{|\mathcal{D}|}^*] \leftarrow \left[\frac{1}{|\mathcal{D}^{\text{prx}}|}, \frac{1}{|\mathcal{D}^{\text{prx}}|}, \cdots, \frac{1}{|\mathcal{D}^{\text{prx}}|} \right]$;
  for $t = 0, 1, \cdots, T - 1$ **do**
    $\boldsymbol{\theta}_{t+1} \leftarrow \boldsymbol{\theta}_t - \eta \nabla L(\boldsymbol{\theta}_t, \boldsymbol{\gamma})$
  end for
  $\boldsymbol{\lambda}_T \leftarrow \nabla J(\boldsymbol{\theta}_T)$
  for $t = T - 1, T - 2, \cdots, 1$ **do**
    $\boldsymbol{\lambda}_t^* \leftarrow \boldsymbol{\lambda}_{t+1}^* + \nabla J(\boldsymbol{\theta}_t) - \eta \nabla^2 L(\boldsymbol{\theta}_t, \boldsymbol{\gamma}^*) \boldsymbol{\lambda}_{t+1}^*$ {Eq. 5}
  end for
  for $n = 1, 2, \cdots, |\mathcal{D}|$ **do**
    $\gamma_n^* \leftarrow \gamma_n^* + \alpha \sum_{t=1}^{T-1} \frac{\boldsymbol{\lambda}_{t+1}^{*\top} \nabla l(x_n, \boldsymbol{\theta}_t)}{\|\nabla l(x_n, \boldsymbol{\theta}_{t+1})\|}$ {Eq. 9}
  end for
  $\boldsymbol{\gamma}^* \leftarrow \text{Proj}[\boldsymbol{\gamma}^*]$
  return $\boldsymbol{\gamma}^*$

Proxy Data Annotation. To construct the ground truth scores $\boldsymbol{\gamma}^*$ for $\mathcal{D}^{\text{prx}}$, we are inspired by (Gu et al., 2025) and adopt a bi-level optimization framework (see Algorithm 1) that quantifies the contribution of each data point in $\mathcal{D}^{\text{prx}}$ to the downstream performance. The goal is to determine an optimal score vector $\boldsymbol{\gamma}^* = [\gamma_1^*, \gamma_2^*, \cdots, \gamma_{|\mathcal{D}|}^*]^\top$.

The bi-level optimization consists of two nested loops: 1) a forward loop that simulates the model training process, and 2) a reverse loop that adjusts the scores $\boldsymbol{\gamma}$ based on the model parameters at each training step. Specifically, in the **forward loop**, the model is trained for T steps using gradient descent, where the training loss is weighted by the current scores $\boldsymbol{\gamma}^*$. This process updates the model parameters $\boldsymbol{\theta}_t$ iteratively, producing a trajectory of checkpoints $\boldsymbol{\theta}_t$ from $t = 0$ to $t = T - 1$. In the **reverse loop**, the target vector $\boldsymbol{\lambda}_t^*$ is computed through the training trajectory from $t = T - 1$ to $t = 0$ according to Eq. 5, where $\boldsymbol{\lambda}_t^*$ represents the backward-propagated gradient at step t, $\nabla l(x_n, \boldsymbol{\theta}_t)$ is the gradient of the loss for the n-th data point. After each update, the scores are projected onto the probability simplex to ensure they remain valid probabilities $\text{Proj}[\boldsymbol{\gamma}^*]$.

Data Scorer Training After we obtain the

Table 1: Data efficacy results on different downstream benchmarks. The Random baseline reports average across three seeds (see Appendix E.1 for details). **DELT** means applying LQS for data scoring and FO for data ordering.

(a) Results (%) for 1B-token data across model sizes (160M, 470M, 1B).

	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
				Model size = 160M					
Random	21.27	34.32	27.85	20.25	24.40	55.19	56.93	50.72	36.37 ($\pm$0.19)
DELT	**21.59**	**36.07**	**28.41**	**23.79**	**25.60**	**56.37**	**59.80**	**53.04**	**38.08**
				Model size = 470M					
Random	21.16	34.91	28.11	21.88	23.90	56.07	58.75	50.04	36.85 ($\pm$0.06)
DELT	**22.33**	**35.88**	**28.45**	**23.26**	**26.60**	**57.20**	**60.10**	**52.81**	**38.33**
				Model size = 1B					
Random	20.58	36.12	28.32	23.56	25.00	56.49	60.05	**52.07**	37.77 ($\pm$0.07)
DELT	**22.76**	**37.95**	**29.95**	**26.38**	**26.00**	**58.07**	**60.90**	51.28	**39.17**

(b) Results (%) for 160M model across data sizes (10B, 50B).

	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
				Data size = 10B tokens					
Random	22.82	38.51	30.72	30.40	25.70	57.32	64.90	51.54	40.24 ($\pm$0.03)
DELT	**24.38**	**39.80**	**31.64**	**32.98**	**27.21**	**58.56**	**66.70**	**51.67**	**41.62**
				Data size = 50B tokens					
Random	24.06	**41.88**	32.05	33.79	26.80	58.11	**69.00**	51.93	42.20 ($\pm$0.13)
DELT	**24.65**	41.07	**33.00**	**36.07**	**29.30**	**59.10**	68.40	**52.67**	**43.03**

(c) Results (%) for 50B-token data and 1.7B model (large scale).

	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
				Model size = 1.7B & Data size = 50B tokens					
Random	38.16	48.02	43.62	**25.83**	41.00	68.41	65.70	**68.93**	49.96 ($\pm$0.21)
DELT	**40.30**	**48.17**	**44.37**	25.23	**44.20**	**69.45**	66.30	65.95	**50.50**

scores $\boldsymbol{\gamma}^*$ for $\mathcal{D}^{\mathrm{prx}}$, we then train a small LM, initialized from a pre-trained checkpoint, with a linear head to serve as the data scorer. The scorer is optimized on the proxy dataset $\mathcal{D}^{\mathrm{prx}}$ to fit the ground-truth scores $\boldsymbol{\gamma}$ from Section 3.2. Specifically, each instance $x_n^{\mathrm{prx}} \in \mathcal{D}^{\mathrm{prx}}$ is encoded by averaging the LM's output hidden states along the sequence, producing a feature representation $\overline{\boldsymbol{h}}(x_n^{\mathrm{prx}}, \boldsymbol{\phi}) \in \mathbb{R}^d$, where $\boldsymbol{\phi}$ are the LM parameters and d is the hidden state size. This representation is passed through a linear head, with parameters $\boldsymbol{w} \in \mathbb{R}^d$ and $b \in \mathbb{R}$, to produce a predicted score. The parameters of the LM and linear head are optimized together using the Mean Squared Error (MSE) loss:

$$\mathcal{L}_{\mathrm{MSE}} = \frac{1}{|\mathcal{D}^{\mathrm{prx}}|} \sum_{n=1}^{|\mathcal{D}^{\mathrm{prx}}|} \left(\boldsymbol{w}^\top \overline{\boldsymbol{h}}(x_n^{\mathrm{prx}}, \boldsymbol{\phi}) + b - \gamma_n^* \right)^2, \quad (10)$$

The optimal parameters $\boldsymbol{\phi}^*$, $\boldsymbol{w}^*$, and b^* are obtained by minimizing this loss. Once trained, the data scorer predicts scores for $x_n \in \mathcal{D}$ as $\gamma(x_n) = \boldsymbol{w}^{*\top} \overline{\boldsymbol{h}}(x_n, \boldsymbol{\phi}^*) + b^*$. This process enables the data scorer to generalize from $\mathcal{D}^{\mathrm{prx}}$ to the larger pre-training corpus $\mathcal{D}$ effectively.

4 Experiment

4.1 Experimental Setup

Data. (1) **General data.** We utilize the Redpajama (Weber et al., 2024) sourced from CommonCrawl as $\mathcal{D}$, which offers a relatively balanced knowledge distribution (Xie et al., 2024). The downstream loss $J(\theta)$ for the data scoring model is computed on the LIMA (Zhou et al., 2024), which is a high-quality dataset with 1,030 diverse instruction-response pairs spanning various downstream scenarios. (2) **Math data.** We use the OpenWeb-Math (Paster et al., 2023) as $\mathcal{D}$. The downstream loss $J(\theta)$ is computed on the MiniF2F (Zheng et al., 2021), which is a high-quality dataset consisting of 488 manually formalized mathematical problem statements, spanning multiple domains. (3) **Code data.** We employ The-Stack-v2 dataset (Lozhkov et al., 2024) as $\mathcal{D}$. The downstream loss $J(\theta)$ is computed on the Epicoder-380k (Wang et al., 2025), which is a synthetic dataset with 380k diverse instruction-response pairs spanning multiple code generation scenarios. (4) **Other data.** We also report language modeling loss on

a DCLM (Li et al., 2024) subset to ensure diversity and long-tail knowledge retention. To verify the robustness of data ordering, we further evaluate on FineWeb-Edu (Penedo et al., 2024) (educational value) and QuRating (Wettig et al., 2024) (multi-criteria pairwise signals aggregated via a Bradley–Terry model), which provide precomputed evaluation scores for each sample..

Model. We apply the Mistral (Jiang et al., 2023) architecture for pre-training on general data, and the Qwen3-1.7B (Yang et al., 2025) for post-training in the math and code domain respectively using the official pre-trained weights.

Baselines. We compare our methods with baselines for data scoring and ordering, including: 1) Data scoring: Random (randomly shuffled data order without selection), KenLM (Heafield, 2011), DSIR (Xie et al., 2023), PDS (Gu et al., 2025); 2) Data ordering: Shuffling (Random), Sorting (Curriculum Learning, CL) (Campos, 2021).

For additional details of the experimental setup, such as training and evaluation, see Appendix B.

4.2 Main Results

Data efficacy with different model sizes and data scales (Table 1). We present the evaluation results of the pre-trained LMs on the OLMo (Groeneveld et al., 2024) evaluation benchmarks in Table 1. As shown, DELT consistently outperforms the baselines on most datasets, achieving the best overall performance across models with 160M, 470M, and 1B parameters (Table 1a), as well as across data sizes of 1B, 10B, and 50B tokens (Table 1b). We further validate the superior of our method on a larger model size (1.7B parameters) and a larger data scale (50B tokens). These results show that combining LQS and FO steadily enhances data efficacy in LM training across various model sizes, data scales, and downstream tasks. For more details, see Table 13 in Appendix.

Table 2: Comparison of different data ordering methods on LQS-scored data. CL_{asc} refers to **ascending** sorting by scores (low→high), while CL_{des} denotes **descending** sorting (high→low).

Ordering	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
Random	21.27	34.32	27.85	20.25	24.40	55.19	56.93	50.72	36.37
CL_{des}	20.69	34.72	27.78	21.20	23.10	56.12	58.20	49.11	36.36↓
CL_{asc}	**22.18**	35.40	28.01	23.48	23.80	55.60	56.80	51.07	37.04↑
Folding	21.59	**36.07**	**28.41**	**23.79**	**25.60**	56.37	**59.80**	**53.04**	**38.08**↑

Data efficacy on different data ordering methods (Table 2). Data ordering is a key component of the DELT and plays a significant role in improving data efficacy. To evaluate the performance of different ordering methods and demonstrate the superiority of our proposed FO, we conduct corresponding experiments. The results in Table 2 show that the proposed Folding method shows the most improvement among all the ordering methods. Besides, the ascending sorting improves the result while descending sorting leads to a decline.

Table 3: Comparison of different data scoring methods on FO-ordered data. Results are obtained on the full dataset without using any selection strategy.

Scoring	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
Random	21.27	34.32	27.85	20.25	24.40	55.19	56.93	50.72	36.37
KenLM	20.98	35.00	28.02	22.55	23.90	56.54	58.30	51.36	37.08
DSIR	**23.17**	35.02	**28.73**	22.28	24.87	**57.27**	55.27	51.61	37.28
PDS	21.93	34.81	28.04	22.43	**26.00**	56.42	59.30	50.20	37.39
LQS	21.59	**36.07**	28.41	**23.79**	25.60	56.37	**59.80**	**53.04**	**38.08**

Data efficacy on different data scoring methods (Table 3). Data scoring serves as the foundation for data ordering. To evaluate the performance of different data scoring methods on FO method, we conduct experiments to verify improvement in data efficacy. As shown in the table 3, applying FO led to consistent improvements in all scoring methods compared to the random baseline, with LQS achieving the greatest gains.

Table 4: Comparison of various data scoring and ordering methods across different selection ratios.

Scoring	Ordering	Selection Ratio					
		1.0	0.9	0.8	0.7	0.6	0.5
KenLM	Random	36.37	36.43	35.72	35.31	35.51	34.78
	Folding	37.08	37.22	36.55	36.38	36.16	35.44
DSIR	Random	36.37	36.58	36.11	36.06	35.57	35.36
	Folding	37.13	37.33	36.90	36.70	36.20	36.08
PDS	Random	36.37	36.19	36.24	37.01	36.14	36.03
	Folding	37.39	37.99	37.63	37.78	37.14	36.15
LQS	Random	36.37	37.14	37.03	35.96	35.95	35.36
	Folding	38.08	37.20	37.54	37.58	36.60	36.47

Table 5: Data efficacy of models trained on different domain-specific datasets. For Random, the results are averaged over three random seeds.

Method	Code Domain		Math Domain	
	HumanEval	MBPP	MATH500	MinervaMath
Random	57.93 (±0.60)	52.80 (±0.06)	45.65 (±0.62)	9.28 (±0.45)
DELT	**66.80**	**55.60**	**50.25**	**13.13**

Data efficacy on different data selection ratios (Table 4). To evaluate the performance of our methods across different data selection ratios, we applied FO and LQS under varying selection ratios and compared them with scoring methods from advanced data efficiency baselines. As shown in Table 4, the FO method consistently demonstrates

Table 6: Performance of FO on different data scoring methods with different data source.

	Ordering	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
Fineweb-edu	Random	22.53	35.44	**27.87**	**14.63**	24.40	56.37	53.50	**51.54**	35.78
	Folding	**23.46**	**38.64**	27.71	10.58	**27.60**	**56.47**	**61.70**	50.36	**37.07**
QuRating	Random	22.01	33.42	27.60	**18.20**	**24.40**	56.15	**57.00**	51.22	36.25
	Folding	**23.55**	**34.76**	**28.16**	17.52	24.00	**57.73**	55.80	**53.20**	**36.84**

stable improvements across different scoring methods and selection ratios. For the LQS method, it outperforms other baselines under the random shuffle setting across most selection ratios. The combination of LQS and FO achieves the highest average accuracy of 38.08% when the selection ratio is 1.0 and shows superior performance across most selection ratios. For more details on the performance under different combinations, please refer to Figure 8, Table 14, and Table 15 in Appendix.

Domain Robustness in Post-training (Table 5). To validate the robustness of the DELT, we conduct post-training experiments on datasets of OpenWebMath (Paster et al., 2023) and The-Stack-v2 (Lozhkov et al., 2024) respectively across math and code domains, both of which are sourced from the web data. As shown in Table 5, our method consistently outperforms the baselines across benchmarks in different domains, demonstrating the strong versatility of the DELT under our proposed LQS and FO methods.

Stability on Different Epochs (Figure 5). In addition to one-epoch training, we also evaluate the impact of DELT under a multi-epoch setting. As shown in Figure 5, our method consistently boosts the results of conventional random ordering as the number of epochs increases. While conventional random ordering exhibits fluctuations and slow improvements after the second epoch, our method shows steady progress, showcasing the effectiveness and stability of our method in maintaining superior performance over multiple epochs. For more details, see Table 16 in Appendix.

4.3 Ablation Study

L **in Folding Learning (Figure 6).** We explore the influence of different folding layers L on model performance in Figure 6. As $L > 1$, the performance consistently surpasses that of $L = 1$ (curriculum learning), verifying the benefits brought by folding learning. The average performance initially increases and then gradually declines, peaking at $L = 3$. In the experiments conducted in this paper, L is set to a default value of 3. For more results

Table 7: Test loss extrapolation via Chinchilla Scaling Law (Hoffmann et al., 2022b). We estimate losses where model size N and trained tokens D align with GPT-3 175B, Llama 6.7B, Llama 2 70B, and Llama 3.1 405B. The improvements of data organization remain consistent for these LMs.

	N	D	Random	**DELT**
GPT-3	175B	300B	3.876	**3.865**
Llama	6.7B	1.0T	3.953	**3.901**
Llama 2	70B	2.0T	3.858	**3.835**
Llama 3.1	405B	15T	3.832	**3.826**

and analyses on FO, please refer to Table 17 and Table 18 in the Appendix.

Robustness of folding ordering method. (Table 6) We validate the effectiveness and generality of our FO strategy by applying it to two strong data scoring baselines: Fineweb-edu (Penedo et al., 2024) and QuRating (Wettig et al., 2024).

We directly reuse their open scores on the CommonCrawl subset and randomly sample 1B-tokens for training: we take the score field from Fineweb-edu and the educational_value_average field from QuRating. As shown in Table 6, Applying FO on these scores yields consistent and substantial improvements across evaluations, demonstrating that FO is robust and broadly applicable to diverse data scoring signals.

4.4 Scaling-up Result

To assess the scalability and robustness of our ordering strategies, we evaluate our methods on a 50B-token data corpus across various Mistral model sizes (160M, 470M, 1B, and 1.7B).

Figure 4 illustrates the test loss on the DCLM subset, comparing conventionally pre-trained LMs (random) against those trained on data ordered by DELT. The results show that LMs trained on ordered data constantly achieve better performance across various model sizes.

Table 7 details our extrapolation of test losses using the Chinchilla Scaling Law (Hoffmann et al., 2022b), showing that the gains from ordered data persist even when pre-training recent large LMs such as GPT-3 (Brown et al., 2020) and the Llama

Figure 4: Test losses on the DCLM corpus (Li et al., 2024) across 160M to 1.7B model sizes. The DELT means applying LQS for data scoring and FO for data ordering.

Figure 5: Performance on different epochs.

Figure 6: Influence of the folding layers L.

Table 8: Asymptotic complexity, GPU FLOPs, and actually spent time of different DELT steps.

Step	Complexity	FLOPs ($\times 10^{20}$)	Actual Time
Proxy Data Annotation (LQS)	$O(N_{prx}D + 4MN_{prx}D_{prx})$	0.49	10.2 Hours
Data Scorer Training & Infering (LQS)	$O(3N_{score}D_{prx} + N_{score}D)$	0.063	1.50 Hours
Data Selection & Ordering	$O(D)$	0	1.3 Minutes
LM Training	$O(ND)$	2.8	96 Hours

family (Touvron et al., 2023a,b; Dubey et al., 2024b). More details of the extrapolation are available in the Appendix D. The DCLM corpus is assembled using a complex heuristic-based pipeline and is confirmed to be both diverse and exhaustive in its knowledge representation. Utilizing existing scores from data selection for data organization comes at a negligible cost and introduces a new perspective for enhancing model performance compared to complex curation pipelines.

4.5 LQS Computational Analysis.

We compare the computational complexity of LQS with pre-training in Table 8. Specifically, following Hoffmann et al. (2022a), for an LM with N parameters to be trained on D tokens, we assume the computational FLOPs of a forward and a backward pass are $2ND$ and $4ND$, respectively. We compute the FLOPs and asymptotic complexities of different stages in LQS as follows. **Proxy Data Annotation.** According to Section Appendix E, we first pre-train a proxy LM on D which consumes $6N^{prx}D$ FLOPs. Then, we perform Algorithm 1 in our paper M times on D^{prx} based on the proxy LM. The forward inner loop in Algorithm 1 consumes $6N^{prx}D^{prx}$ FLOPs. The reverse loop can be treated as the "backward" propagation of the forward inner loop as discussed in Appendix E.1, which consumes $2 \times 6N^{prx}D^{prx}$ FLOPs. The update of γ results in one forward and backward pass of the proxy LM on D^{prx}, which consumes $6N^{prx}D^{prx}$ FLOPs. In summary, the asymptotic complexity of proxy data annotation (LQS calculation) is $O(N^{prx}D + 4MN^{prx}D^{prx})$. **Data Scorer Training.** The data scorer with N^{score} is trained on D^{prx} and used to infer data quality scores on D. Therefore, the computation overhead is $6N^{score}D^{prx} + 2N^{score}D$ and the asymptotic complexity is $O(3N^{score}D^{prx} + N^{score}D)$. **Data Selection & Ordering.** Selecting and ordering pre-training corpus requires iterating over D, whose asymptotic complexity is $O(D)$. This process can be done on CPUs and does not require GPU FLOPs. **Language Model Training.** Pre-training an LM with N parameters requires $6ND$ FLOPs, whose asymptotic complexity is $O(ND)$.

Overall, since the parameter size of the LM used for training N, and the data size D, are typically much larger than the parameter size of the data-scoring model N^{score}, and the proxy data size D^{prx}, the *computational cost of model training is significantly higher than that of sample scoring*.

5 Conclusion

To address the underexplored field of data efficacy, we propose DELT, a novel method integrating Learnability-Quality Scoring (LQS) and Folding Ordering (FO). Additionally, DELT optionally incorporates a data selection module to jointly improve data efficiency. Comprehensive experiments demonstrate that our approach consistently outperforms existing baselines. Ultimately, this work highlights the significant potential of data efficacy to improve model performance without increasing data or model scale.

Limitations

Although DELT significantly enhances data efficacy for language model training, the current paradigm is intrinsically designed for text-based modalities, which we plan to address in future work.

Ethics Statement

We ensure transparency by utilizing publicly available data sources and model architectures. We adhere to the licensing terms for both models and datasets, including proper attribution and sharing any modifications or derivative works under compatible terms. While this work focuses on language modalities, further research is necessary for unbiased evaluation in other modalities.

Declaration of LLM Usage

In the preparation of this work, the authors used LLM in order to improve the readability and language of the manuscript. After using this tool, the authors reviewed and edited the content as needed and take full responsibility for the content of the published article.

Acknowledgments

This document has been adapted by Steven Bethard, Ryan Cotterell and Rui Yan from the instructions for earlier ACL and NAACL proceedings, including those for ACL 2019 by Douwe Kiela and Ivan Vulić, NAACL 2019 by Stephanie Lukin and Alla Roskovskaya, ACL 2018 by Shay Cohen, Kevin Gimpel, and Wei Lu, NAACL 2018 by Margaret Mitchell and Stephanie Lukin, BibTEX suggestions for (NA)ACL 2017/2018 from Jason Eisner, ACL 2017 by Dan Gildea and Min-Yen Kan, NAACL 2017 by Margaret Mitchell, ACL 2012 by Maggie Li and Michael White, ACL 2010 by Jing-Shin Chang and Philipp Koehn, ACL 2008 by Johanna D. Moore, Simone Teufel, James Allan, and Sadaoki Furui, ACL 2005 by Hwee Tou Ng and Kemal Oflazer, ACL 2002 by Eugene Charniak and Dekang Lin, and earlier ACL and EACL formats written by several people, including John Chen, Henry S. Thompson and Donald Walker. Additional elements were taken from the formatting instructions of the *International Joint Conference on Artificial Intelligence* and the *Conference on Computer Vision and Pattern Recognition*.

References

Amro Abbas, Kushal Tirumala, Dániel Simig, Surya Ganguli, and Ari S Morcos. 2023. Semdedup: Data-efficient learning at web-scale through semantic deduplication. *arXiv preprint arXiv:2303.09540*.

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, and 1 others. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Alon Albalak, Yanai Elazar, Sang Michael Xie, Shayne Longpre, Nathan Lambert, Xinyi Wang, Niklas Muennighoff, Bairu Hou, Liangming Pan, Haewon Jeong, and 1 others. 2024. A survey on data selection for language models. *arXiv preprint arXiv:2402.16827*.

Aida Amini, Saadia Gabriel, Peter Lin, Rik Koncel-Kedziorski, Yejin Choi, and Hannaneh Hajishirzi. 2019. Mathqa: Towards interpretable math word problem solving with operation-based formalisms. *Preprint*, arXiv:1905.13319.

Mikel Artetxe, Shruti Bhosale, Naman Goyal, Todor Mihaylov, Myle Ott, Sam Shleifer, Xi Victoria Lin, Jingfei Du, Srinivasan Iyer, Ramakanth Pasunuru, and 1 others. 2022. Efficient large scale language modeling with mixtures of experts. In *Proceedings EMNLP*.

Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and 1 others. 2021. Program synthesis with large language models. *arXiv preprint arXiv:2108.07732*.

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. 2009. Curriculum learning. In *Proceedings of the 26th annual international conference on machine learning*, pages 41–48.

Yonatan Bisk, Rowan Zellers, Jianfeng Gao, Yejin Choi, and 1 others. 2020. Piqa: Reasoning about physical commonsense in natural language. In *Proceedings of AAAI*.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, and 1 others. 2020. Language models are few-shot learners. In *Proceedings of NeurIPS*.

Daniel Campos. 2021. Curriculum learning for language modeling. *arXiv preprint arXiv:2108.02170*.

Ernie Chang, Hui-Syuan Yeh, and Vera Demberg. 2021. Does the order of training samples matter? improving neural data-to-text generation with curriculum learning. *arXiv preprint arXiv:2102.03554*.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela

Mishkin, Brooke Chan, Scott Gray, and 39 others. 2021. Evaluating large language models trained on code.

Kyunghyun Cho, Bart Van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. 2014. Learning phrase representations using rnn encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. 2019. BoolQ: Exploring the surprising difficulty of natural yes/no questions. In *Proceedings of NAACL-HLT*.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv:1803.05457v1*.

Yalun Dai, Lingao Xiao, Ivor Tsang, and Yang He. Training-free dataset pruning for instance segmentation. In *The Thirteenth International Conference on Learning Representations*.

Joost CF De Winter, Samuel D Gosling, and Jeff Potter. 2016. Comparing the pearson and spearman correlation coefficients across distributions and sample sizes: A tutorial using simulations and empirical data. *Psychological methods*, 21(3):273.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, and 1 others. 2024a. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, and 1 others. 2024b. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Sachin Goyal, Pratyush Maini, Zachary C Lipton, Aditi Raghunathan, and J Zico Kolter. 2024. Scaling laws for data filtering–data curation cannot be compute agnostic. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 22702–22711.

Dirk Groeneveld, Iz Beltagy, Pete Walsh, Akshita Bhagia, Rodney Kinney, Oyvind Tafjord, Ananya Harsh Jha, Hamish Ivison, Ian Magnusson, Yizhong Wang, and 1 others. 2024. OLMo: Accelerating the science of language models. *arXiv preprint arXiv:2402.00838*.

Yuxian Gu, Li Dong, Hongning Wang, Yaru Hao, Qingxiu Dong, Furu Wei, and Minlie Huang. 2025. Data selection via optimal control for language models. In *The Thirteenth International Conference on Learning Representations*.

Karthick Prasad Gunasekaran. 2023. Exploring sentiment analysis techniques in natural language processing: A comprehensive review. *arXiv preprint arXiv:2305.14842*.

Kenneth Heafield. 2011. KenLM: Faster and smaller language model queries. In *Proceedings of the Sixth Workshop on Statistical Machine Translation*, pages 187–197, Edinburgh, Scotland. Association for Computational Linguistics.

Julia Hirschberg and Christopher D Manning. 2015. Advances in natural language processing. *Science*, 349(6245):261–266.

Sepp Hochreiter and Jürgen Schmidhuber. 1997. Long short-term memory. *Neural computation*, 9(8):1735–1780.

Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, and 1 others. 2022a. Training compute-optimal large language models. *arXiv preprint arXiv:2203.15556*.

Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, and 1 others. 2022b. Training compute-optimal large language models. In *Proceedings of NeurIPS*.

Wei Hu, QiHao Zhao, Yangyu Huang, and Fan Zhang. 2021. P-diff: Learning classifier with noisy labels based on probability difference distributions. In *2020 25th International Conference on Pattern Recognition (ICPR)*, pages 1882–1889. IEEE.

Peter J. Huber. 1992. *Robust Estimation of a Location Parameter*. Springer New York.

Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, and 1 others. 2023. Mistral 7b. *arXiv preprint arXiv:2310.06825*.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. 2020a. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. 2020b. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*.

Jisu Kim and Juhwan Lee. 2024. Strategic data ordering: Enhancing large language model performance through curriculum learning. *arXiv preprint arXiv:2405.07490*.

Sheetal Kusal, Shruti Patil, Jyoti Choudrie, Ketan Kotecha, Sashikala Mishra, and Ajith Abraham. 2022. Ai-based conversational agents: a scoping review from technologies to future directions. *IEEE Access*, 10:92337–92356.

Hector Levesque, Ernest Davis, and Leora Morgenstern. 2012. The winograd schema challenge. In *Proceedings of KR*.

Jeffrey Li, Alex Fang, Georgios Smyrnis, Maor Ivgi, Matt Jordan, Samir Gadre, Hritik Bansal, Etash Guha, Sedrick Keh, Kushal Arora, and 1 others. 2024. DataComp-LM: In search of the next generation of training sets for language models. *arXiv preprint arXiv:2406.11794*.

Dong C Liu and Jorge Nocedal. 1989. On the limited memory bfgs method for large scale optimization. *Mathematical programming*.

Ilya Loshchilov and Frank Hutter. 2019. Decoupled weight decay regularization. In *Proceedings of ICLR*.

Anton Lozhkov, Raymond Li, Loubna Ben Allal, Federico Cassano, Joel Lamy-Poirier, Nouamane Tazi, Ao Tang, Dmytro Pykhtar, Jiawei Liu, Yuxiang Wei, and 1 others. 2024. Starcoder 2 and the stack v2: The next generation. *arXiv preprint arXiv:2402.19173*.

Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. 2018. Can a suit of armor conduct electricity? a new dataset for open book question answering. In *Proceedings of EMNLP*.

OpenAI. hello-gpt-4o. (2024).

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, and 1 others. 2022. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744.

Denis Paperno, Germán Kruszewski, Angeliki Lazaridou, Ngoc-Quan Pham, Raffaella Bernardi, Sandro Pezzelle, Marco Baroni, Gemma Boleda, and Raquel Fernández. 2016. The lambada dataset: Word prediction requiring a broad discourse context. In *Proceedings of ACL*.

Keiran Paster, Marco Dos Santos, Zhangir Azerbayev, and Jimmy Ba. 2023. Openwebmath: An open dataset of high-quality mathematical web text. *Preprint*, arXiv:2310.06786.

Guilherme Penedo, Hynek Kydlíček, Anton Lozhkov, Margaret Mitchell, Colin A Raffel, Leandro Von Werra, Thomas Wolf, and 1 others. 2024. The fineweb datasets: Decanting the web for the finest text data at scale. *Advances in Neural Information Processing Systems*, 37:30811–30849.

Ahad Rana. 2010. Common crawl – building an open web-scale crawl using hadoop.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R. Bowman. 2024. GPQA: A graduate-level google-proof q&a benchmark. In *First Conference on Language Modeling*.

Petru Soviany, Radu Tudor Ionescu, Paolo Rota, and Nicu Sebe. 2022. Curriculum learning: A survey. *International Journal of Computer Vision*, 130(6):1526–1565.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, and 1 others. 2023. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*.

Kushal Tirumala, Daniel Simig, Armen Aghajanyan, and Ari Morcos. 2023. D4: Improving llm pretraining via document de-duplication and diversification. *Advances in Neural Information Processing Systems*, 36:53983–53995.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. 2023a. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, and 1 others. 2023b. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Xin Wang, Yudong Chen, and Wenwu Zhu. 2021. A survey on curriculum learning. *IEEE transactions on pattern analysis and machine intelligence*, 44(9):4555–4576.

Yaoxiang Wang, Haoling Li, Xin Zhang, Jie Wu, Xiao Liu, Wenxiang Hu, Zhongxin Guo, Yangyu Huang, Ying Xin, Yujiu Yang, and 1 others. 2025. Epicoder: Encompassing diversity and complexity in code generation. *arXiv preprint arXiv:2501.04694*.

Maurice Weber, Dan Fu, Quentin Anthony, Yonatan Oren, Shane Adams, Anton Alexandrov, Xiaozhong Lyu, Huu Nguyen, Xiaozhe Yao, Virginia Adams, and 1 others. 2024. Redpajama: an open dataset for training large language models. *Advances in neural information processing systems*, 37:116462–116492.

Johannes Welbl, Nelson F. Liu, and Matt Gardner. 2017. Crowdsourcing multiple choice science questions. In *Proceedings of the 3rd Workshop on Noisy User-generated Text (ACL 2017)*.

Alexander Wettig, Aatmik Gupta, Saumya Malik, and Danqi Chen. 2024. Qurating: Selecting high-quality data for training language models. *arXiv preprint arXiv:2402.09739*.

Sang Michael Xie, Hieu Pham, Xuanyi Dong, Nan Du, Hanxiao Liu, Yifeng Lu, Percy S Liang, Quoc V Le, Tengyu Ma, and Adams Wei Yu. 2024. DoReMi: Optimizing data mixtures speeds up language model pretraining. In *Proceedings of NeurIPS*.

Sang Michael Xie, Shibani Santurkar, Tengyu Ma, and Percy S Liang. 2023. Data selection for language models via importance resampling. *Advances in Neural Information Processing Systems*, 36:34201–34227.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Fei Yu, Hongbo Zhang, Prayag Tiwari, and Benyou Wang. 2024a. Natural language reasoning, a survey. *ACM Computing Surveys*, 56(12):1–39.

Zichun Yu, Spandan Das, and Chenyan Xiong. 2024b. Mates: Model-aware data selection for efficient pre-training with data influence models. *Advances in Neural Information Processing Systems*.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. 2019. Hellaswag: Can a machine really finish your sentence? In *Proceedings of ACL*.

QiHao Zhao, Wei Hu, Yangyu Huang, and Fan Zhang. 2021. P-diff+: Improving learning classifier with noisy labels by noisy negative learning loss. *Neural Networks*, 144:1–10.

Kunhao Zheng, Jesse Michael Han, and Stanislas Polu. 2021. Minif2f: a cross-system benchmark for formal olympiad-level mathematics. *arXiv preprint arXiv:2109.00110*.

Chunting Zhou, Pengfei Liu, Puxin Xu, Srinivasan Iyer, Jiao Sun, Yuning Mao, Xuezhe Ma, Avia Efrat, Ping Yu, Lili Yu, and 1 others. 2024. Lima: Less is more for alignment. In *Proceedings of NeurIPS*.

Appendix

A Related Works

Data efficiency (Heafield, 2011; Gu et al., 2025; Xie et al., 2023; Albalak et al., 2024) focuses on selecting the most relevant data points for inclusion in training dataset and optimizing the performance of the language model. This area includes well-researched strategies such as data selection (Heafield, 2011; Gu et al., 2025; Yu et al., 2024b; Dai et al.), sampling (Xie et al., 2023), denoising (Zhao et al., 2021; Hu et al., 2021), and deduplication (Abbas et al., 2023; Tirumala et al., 2023), all of which aim to select optimal data for efficient model training. The KenLM (Heafield, 2011) trains a fast and small model for perplexity estimation and treats the perplexity as the data difficulty for LM. The PDS (Gu et al., 2025) evaluates the quality of data samples by measuring the consistency of each sample's gradient direction with a reference direction. The DSIR (Xie et al., 2023) develops an importance weight estimator to select a subset of raw data that mirrors the distribution of the target in a specific feature space. The MATES (Yu et al., 2024b) presents a data influence model that continuously adapts to the evolving data preferences of the pre-trained model, selecting the most effective data for the current stage of pre-training. The SemDeDup (Abbas et al., 2023) utilizes embeddings from pre-trained models to identify and remove data pairs that are semantically similar but not exactly identical. All these methods develop strategies to decide whether a sample should be retained or discarded. However, for retained samples, language models train on them equally, without considering differences in criteria.

Data efficacy, distinct from data efficiency, aims to maximize the performance of language models by optimizing the organization of training data. Curriculum learning, as described by Campos (2021), involves starting with simpler examples and progressively tackling more complex ones, aiding in smoother model convergence. Within curriculum learning, Kim and Lee (2024) presents an attention score to determine the prompt difficulty, and Chang et al. (2021) introduces a soft edit distance to measure sample difficulty. Similarly, annealing learning, as outlined by Dubey et al. (2024a), seeks to improve model performance by initially training on a large, noisy dataset and concluding with a small, high-quality dataset. All these methods sort training data directly by difficulty or quality.

However, since limited research on data efficacy, there is no method for effectively organizing data in modern language model training.

To conclude, data is essential for training language models, and numerous large-scale data sources originate from the internet. Nevertheless, obtaining incremental public data has become challenging due to the slow growth of CommonCrawl (Rana, 2010) snapshots and the increasing presence of AI-generated content online. As language models scale up, effectively leveraging existing data sources becomes vital, which makes data efficacy increasingly important in the near future. Despite this, few studies focus on data efficacy in language model training. To address this gap, we propose a general method DELT.

B Additional Experimental Setup

Training. Unless otherwise specified, we pre-train all LMs for one epoch, using a batch size of 512 and a maximum input length of 1,024. For the model, we utilize 160M parameters by default. For pre-training, we randomly select a 1B-token subset from Redpajama by default, while for post-training, we sample a 1B-token subset each from OpenWeb-Math and The-Stack-v2.

Evaluation. For general evaluation, we assess the trained models on a range of standard natural language understanding and reasoning benchmarks, including Hellaswag (HS; Zellers et al., 2019), Winogrande (Wino; Levesque et al., 2012), LAMBADA (LAMB; Paperno et al., 2016), Open-bookQA (OBQA; Mihaylov et al., 2018), ARC-easy/challenge (ARC-e/c; Clark et al., 2018), PIQA (Bisk et al., 2020), SciQ (Welbl et al., 2017), and BoolQ (Clark et al., 2019). For domain-specific tasks, we assess the models on mathematical reasoning and code generation benchmarks. Specifically, for math, we use GPQA Diamond (Rein et al., 2024) and MathQA (Amini et al., 2019), while for code, we use HumanEval (Chen et al., 2021) and MBPP (Austin et al., 2021).

For the code generation benchmarks, we use a 0-shot setting for HumanEval and a 3-shot setting for MBPP. Code generation performance is reported using pass rate@1, which indicates the percentage of first-attempt solutions that pass all associated unit tests (pass@1). For the other benchmarks, the tasks are framed as multiple-choice questions, where the model selects the correct answer by minimizing the normalized loss across all candidate options (acc_norm).

Compute Resources. We train the 160M model on 1B-token datasets using a single NVIDIA A100 40GB GPU. For experiments with the 160M, 470M, and 1B models on 10B and 50B-token datasets, we utilize 8 NVIDIA A100 40GB GPUs. All data scoring steps, including proxy data annotation, scorer training, and data scoring, are performed on a single NVIDIA A100 80GB GPU.

Training Configuration. To create the data scorer, we fine-tune the Fairseq-Dense-125M model (Artetxe et al., 2022) on the solved data weights γ. As described in algorithm 1, we apply a linear transformation to the mean-pooled representations of instances along the sequence length. The hidden state size is set to 768. The optimization of algorithm 1 is performed using the AdamW optimizer (Loshchilov and Hutter, 2019) for 5 epochs, with a learning rate of 1×10^{-4} and a batch size of 512. We train on 90% of the samples and reserve the remaining 10% from $\mathcal{D}^{\mathrm{prx}}$ as a validation set. The checkpoint with the highest Spearman correlation score (De Winter et al., 2016; Gu et al., 2025) on the validation set is selected to infer data quality scores in $\mathcal{D}$.

For LMs training, all models are trained with a batch size of 256 and a maximum input sequence length of 1,024 for one epoch. The AdamW optimizer (Loshchilov and Hutter, 2019) is paired with a cosine learning rate scheduler. The scheduler includes a warm-up phase for the first 2,000 steps, after which the learning rate decays to 10% of its peak value. The model architecture and corresponding learning rates are summarized in Table 9, following the configurations in (Gu et al., 2025).

Model Size	d_{model}	d_{FFN}	n_{layers}	n_{head}	d_{head}	learning rate
160M	768	3,072	12	12	64	6×10^{-4}
470M	1,024	4,096	24	16	64	3×10^{-4}
1B	1,536	6,144	24	16	96	2.5×10^{-4}
1.7B	2,048	8,192	24	16	128	2×10^{-4}

Table 9: Model configurations and corresponding learning rates.

C DELT Paradigm

To lay the foundation for the further development of data efficacy, we propose a paradigm (Figure 7) to enhance **data efficacy** in LM training without modifying the data content $\mathcal{D}$ or the model parameters θ. It currently comprises two components:

- **Data Scoring**: it aims to assign a score for each training sample based on specific criteria, such as quality, difficulty, diversity, and learnability. These scores are then applied to guide data selection and data ordering in subsequent stages.

- **Data Ordering**: it targets at reorganizing the order of training samples in $\mathcal{D}$ (or $\mathcal{D}^{\text{sub}}$) to create $\mathcal{D}'$, such that LMs trained on $\mathcal{D}'$ achieve superior performance. This process focuses on the organization of dataset $\mathcal{D}$ (or $\mathcal{D}^{\text{sub}}$), while it does not change the dataset scale.

In addition, to make the paradigm more general, we also integrate an optional **data selection** module, enabling DELT to seamlessly enhance **data efficiency**. This module selects an optimal subset $\mathcal{D}^{\text{sub}}$ from the dataset $\mathcal{D}$, ensuring that LMs trained on $\mathcal{D}^{\text{sub}}$ achieve the best possible performance. While this process adjusts the size of the dataset $\mathcal{D}$, it does not affect the structure of $\mathcal{D}^{\text{sub}}$.

Figure 7: Paradigm of Data Efficacy for LM training. The blue box represents the paradigm DELT. Both the methods for data scoring and data ordering components in DELT are flexible and can be adjusted, including those outlined in Section 3. Meanwhile, the data selection is an optional component that can further improve data efficiency. Within the proposed DELT, data efficacy and efficiency are seamlessly compatible, working together to optimize language model performance.

Unlike the baseline method, where the language model is trained directly on the raw data $\mathcal{D}$, and the data efficiency methods that use a selected subset $\mathcal{D}^{\text{sub}}$, DELT processes the raw data $\mathcal{D}$ as follows:

Firstly, data scoring, defined as f, assigns a score vector $\boldsymbol{\gamma}$ to the raw data $\mathcal{D}$, where $\boldsymbol{\gamma}$ lies in a $|\mathcal{D}|$-dimensional simplex. Samples with large $\boldsymbol{\gamma}$ are considered good according to their criteria.

$$\boldsymbol{\gamma} = f(\mathcal{D}) = \left[\gamma_1, \gamma_2, \cdots, \gamma_{|\mathcal{D}|}\right]^\top \quad (11)$$

Secondly, the optioned data selection, denoted as f_s, identifies a subset $\mathcal{D}^{\text{sub}}$ from $\mathcal{D}$ based on the scores $\boldsymbol{\gamma}$ by the selection ratio r. The number of samples K to be selected is determined by r. The function $rank$ provides the ranking index of each

element in the set $\boldsymbol{\gamma}$ in ascending order.

$$\mathcal{D}^{\text{sub}} = f_s(\mathcal{D}; \boldsymbol{\gamma}, K) = \{x_k \mid rank(\boldsymbol{\gamma}_k) > |\mathcal{D}| - K \text{ and } 1 \le k \le |\mathcal{D}|\} \quad (12)$$

$$K = \lfloor r \cdot |\mathcal{D}| \rfloor \quad (13)$$

Finally, data ordering, represented by f_o, reorganizes the $\mathcal{D}$ or $\mathcal{D}^{\text{sub}}$ into a new dataset $\mathcal{D}'$ with unchanged size, based on a permutation π determined by $\boldsymbol{\gamma}$. It could be π_{sort} that returns the indices of each element in $\boldsymbol{\gamma}$ after sorting or other functions.

$$\mathcal{D}' = f_o(\mathcal{D}; \boldsymbol{\gamma}) = \left[x_{\pi(\boldsymbol{\gamma})_1}, x_{\pi(\boldsymbol{\gamma})_2}, \cdots, x_{\pi(\boldsymbol{\gamma})_{|\mathcal{D}|}}\right] \quad (14)$$

Compatibility of data efficacy and data efficiency in DELT. As shown in Figure 7, the DELT paradigm can build upon data scoring and data ordering by incorporating data selection to further enhance **data efficiency**. The entire DELT process can be defined as a transformation of the original dataset $\mathcal{D}$ into a reordered dataset $\mathcal{D}'$:

$$\mathcal{D}' = f_o(\boldsymbol{\gamma}_o) \circ f_s(\mathcal{D}; \boldsymbol{\gamma}_s, K), \quad (15)$$

where the symbol $\circ$ denotes functional composition. $\boldsymbol{\gamma}_o$ and $\boldsymbol{\gamma}_s$ are the score vectors for data ordering and data selection, respectively. Since data scoring often requires substantial computation time, both data selection and data ordering in DELT apply a shared score vector for practicality, i.e., $\boldsymbol{\gamma}_o = \boldsymbol{\gamma}_s = \boldsymbol{\gamma}$. This process ensures that the most qualified samples are selected and then optimally ordered, thereby significantly improving model performance in both data efficacy and efficiency.

D Test Loss Extrapolation with the Scaling Law

We extrapolate the test losses on the DCLM corpus (Li et al., 2024) of the conventionally trained and PDS-trained LMs with the Scaling Law (Hoffmann et al., 2022b; Kaplan et al., 2020b). Following Hoffmann et al. (2022b), we consider the scaling law with the following form:

$$L(N, D) = E + \frac{A}{N^\alpha} + \frac{B}{D^\beta}, \quad (16)$$

where N is the model parameters, D is the number of trained tokens, and A, B, E, α, β are constants. We obtain these constants by minimizing the Huber loss: (Huber, 1992):

$$\min_{a,b,e,\alpha,\beta} \sum_{(N_i, D_i, L_i)} \text{Huber}_\delta(\text{LSE}(a - \alpha \log N_i, b - \beta \log D_i, e) - \log L_i), \quad (17)$$

where $\text{LSE}(\cdot)$ is the log-sum-exp operation. The loss is summed over all (N_i, D_i, L_i) tuples, which

are obtained by the test losses of 160M, 470M, 1B, and 1.7B LM during training from 0B to 50B tokens. We record the losses every 2.5B tokens, resulting in a total $4 \times 50B/2.5B = 80$ tuples like (N_i, D_i, L_i). After solving a, b, and e from Eq. 17 , we have $A = \exp(a)$, $B = \exp(b)$, and $E = \exp(e)$.

Hoffmann et al. (2022b) optimizes Eq. 17 using the LBFGS algorithm (Liu and Nocedal, 1989). However, we found this algorithm sensitive to the initialization of the parameters to be optimized. Therefore, we apply a two-stage optimization. Specifically, we first fit the following data scaling curves for $N =$160M, 470M, 1B, and 1.7B with non-linear least squares from `scipy.optimize.curve_fit`[1], which is much more robust to the initialization:

$$L(D) = E'(N) + \frac{B_0(N)}{D^{\beta_0(N)}}, \qquad (18)$$

where $E'(N)$, $B_0(N)$ and $\beta_0(N)$ are the fitted parameters. Then, we fit the following model size scaling curve:

$$E' = E_0 + \frac{A_0}{N^{\alpha_0}}. \qquad (19)$$

We use the constants from Eq. 19 and the average constants from Eq. 18 to compute the initialization for the LBFGS algorithm:

$$
\begin{aligned}
a_0 &= \log A_0, \\
b_0 &= \log \frac{B_0(160\text{M}) + B_0(470\text{M}) + B_0(1\text{B}) + B_0(1.7\text{B})}{4}, \\
\alpha_0 &= \alpha_0, \\
\beta_0 &= \frac{\beta_0(160\text{M}) + \beta_0(470\text{M}) + \beta_0(1\text{B}) + \beta_0(1.7\text{B})}{4}, \\
e_0 &= \log E_0,
\end{aligned}
\qquad (20)
$$

where $a_0, b_0, \alpha_0, \beta_0, e_0$ are the parameter initialization for the LFBGS algorithm to optimize Eq. 17. We set $\delta = 1 \times 10^{-3}$ and learning rate to 0.05 when running LFBGS and obtain the constants in Table 10. We use these constants and Eq. 16 to compute the predicted loss in Table 7.

Goodness of Fit. We evaluate the goodness of fit of the scaling curves with respect to the training token size D and model size N respectively, by computing the correlation coefficient $R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \bar{y})^2}$, where y_i is the ground truth value and $\hat{y}_i$ is the prediction.

---

[1] https://docs.scipy.org/doc/scipy/reference/generated/scipy.optimize.curve_fit.html

Table 10: Scaling law constants by fitting the test losses on the DCLM corpus. E represents the irreducible loss inherent to the dataset.

	A	B	α	β	E
Random	4.82×10^2	5.12×10^3	0.354	0.295	1.693
DELT	4.28×10^2	4.55×10^3	0.359	0.299	1.693

Table 11: Correlations (R^2) of fitting the scaling curves.

	N=160M	N=470M	N=1B	N=1.7B	D=50×10^9
Random	0.992	0.995	0.998	0.997	0.999
DELT	0.993	0.996	0.998	0.997	0.999

Regarding the training token size, to make the original problem a linear regression problem, we convert Eq. 16 into

$$\log\left(L(N, D) - E - \frac{A}{N^\alpha}\right) = \log B - \beta \log D. \qquad (21)$$

Then, we consider $\log\left(l_i - E - \frac{A}{N^\alpha}\right)$ as the ground truth value for regression, where l_i is the observed loss, and $\log B - \beta \log D_i$ as the prediction. For each $N \in [160M, 470M, 1B, 1.7B]$ we compute an R^2 respectively. Similarly, regarding the model size, we convert Eq. 16 into

$$\log\left(L(N, D) - E - \frac{B}{D^\beta}\right) = \log A - \alpha \log N, \qquad (22)$$

to compute the corresponding R^2 that measures its goodness of fit. For simplicity, we only consider the models at the end of training, where $D = 50 \times 10^9$. The results in Table 11 show that the correlations are sufficiently high, suggesting the scaling curve fits the impact from both the data and model sizes very well.

E More Experiments Results

E.1 Robustness to Randomness.

We conduct experiments for the Random baseline using three different seeds (8, 10, and 42) and report the mean results with standard deviations ($\pm$). As shown in Table 12, the performance gains achieved by our method significantly exceed the fluctuations caused by random seeds, further validating the effectiveness of our approach.Additionally, it should be clarified that since our method explicitly determines the data order, it yields deterministic results on the same hardware. Consequently, multi-seed analysis was not performed for our proposed methods.

Data Efficacy across Different Model Sizes and Data Scales on More Methods. (Table 13).

Table 12: Data efficacy results on different downstream benchmarks. The conventional method presents the average result over three random seeds in this and the following tables. DELT (Ours) means applying LQS for data scoring and FO for data ordering within the introduced paradigm.

(a) Results (%) for 1B-token data across model sizes (160M, 470M, 1B).

	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
Model size = 160M									
Conventional	$21.27_{\pm0.30}$	$34.32_{\pm0.83}$	$27.85_{\pm0.15}$	$20.25_{\pm1.70}$	$24.40_{\pm0.19}$	$55.19_{\pm0.16}$	$56.93_{\pm1.06}$	$50.72_{\pm0.84}$	$36.37_{\pm0.19}$
DELT (Ours)	**21.59**	**36.07**	**28.41**	**23.79**	**25.60**	**56.37**	**59.80**	**53.04**	**38.08**
Model size = 470M									
Conventional	$21.16_{\pm0.42}$	$34.91_{\pm0.86}$	$28.11_{\pm0.23}$	$21.88_{\pm0.10}$	$23.90_{\pm1.84}$	$56.07_{\pm0.58}$	$58.75_{\pm0.35}$	$50.04_{\pm1.40}$	$36.85_{\pm0.06}$
DELT (Ours)	**22.33**	**35.88**	**28.45**	**23.26**	**26.60**	**57.20**	**60.10**	**52.81**	**38.33**
Model size = 1B									
Conventional	$20.58_{\pm0.36}$	$36.12_{\pm0.03}$	$28.32_{\pm0.29}$	$23.56_{\pm0.77}$	$25.00_{\pm0.71}$	$56.49_{\pm1.19}$	$60.05_{\pm0.69}$	$\mathbf{52.07}_{\pm0.17}$	$37.77_{\pm0.07}$
DELT (Ours)	**22.76**	**37.95**	**29.95**	**26.38**	**26.00**	**58.07**	**60.90**	51.28	**39.17**

(b) Results (%) for 160M model across data sizes (10B, 50B).

	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
Data size = 10B tokens									
Conventional	$22.82_{\pm0.72}$	$38.51_{\pm0.57}$	$30.72_{\pm0.35}$	$30.40_{\pm0.77}$	$25.70_{\pm0.71}$	$57.32_{\pm0.27}$	$64.90_{\pm0.21}$	$51.54_{\pm0.95}$	$40.24_{\pm0.03}$
DELT (Ours)	**24.38**	**39.80**	**31.64**	**32.98**	**27.21**	**58.56**	**66.70**	**51.67**	**41.62**
Data size = 50B tokens									
Conventional	$24.06_{\pm0.06}$	$\mathbf{41.88}_{\pm0.06}$	$32.05_{\pm0.11}$	$33.79_{\pm2.18}$	$26.80_{\pm0.99}$	$58.11_{\pm0.58}$	$\mathbf{69.00}_{\pm1.06}$	$51.93_{\pm0.50}$	$42.20_{\pm0.13}$
DELT (Ours)	**24.65**	41.07	**33.00**	**36.07**	**29.30**	**59.10**	68.40	**52.67**	**43.03**

(c) Results (%) for 50B-token data and 1.7B model (large scale).

	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
Model size = 1.7B & Data size = 50B tokens									
Conventional	$38.16_{\pm1.09}$	$48.02_{\pm0.18}$	$43.62_{\pm0.47}$	$\mathbf{25.83}_{\pm0.38}$	$41.00_{\pm0.14}$	$68.41_{\pm0.38}$	$65.70_{\pm1.27}$	$\mathbf{68.93}_{\pm1.15}$	$49.96_{\pm0.21}$
DELT (Ours)	**40.30**	**48.17**	**44.37**	25.23	**44.20**	**69.45**	**66.30**	65.95	**50.50**

To supplement Table 1, we provide additional experimental results comparing DELT with data selection methods across different model sizes and data scales. As shown in Table 13, with increasing model parameters and data scales, our proposed DELT demonstrates consistent improvements and outperforms various methods across most benchmarks.

Comparison of Data Efficiency (Table 14). To supplement Table 4, we further highlight the superiority of the DELT framework by comparing it with the data efficiency setting. Table 14 presents the results of different methods applied within the DELT paradigm, all of which significantly outperform the conventional baseline. Notably, regardless of whether data selection is applied, our proposed LQS scoring method achieves the best results. Furthermore, our proposed Folding ordering method consistently provides noticeable improvements across all baseline methods.

Comparison with advanced data selection methods. To supplement Table 4, we presents the results comparing different data scoring methods without data ordering in Table 15. Compared to the results from the conventional pipeline and state-of-the-art data efficiency baselines, the DELT framework, which incorporates both data selection and ordering, consistently demonstrates significant improvements across various method combinations. Notably, our LQS also achieves the best results even in the setting where only data selection is applied.

Data efficiency promotion on existing methods (Figure 8). To supplement Table 4, we further evaluates the data efficiency of the DELT framework by involving the data selection setting in Figure 8. Compared to the random selection baseline (Shuffling), the DELT framework (Sorting and Folding) achieves superior performance across the majority of selection ratios. The results show that the DELT framework is compatible with the data selection method, and the combination further improves their data efficiency.

Stability on Different Epochs. (Table 16) To supplement Figure 5, we further report the detailed results of the proposed DELT across different epochs on various benchmarks. As shown in Table 16, with an increasing number of epochs, our method demonstrates stable improvements across most benchmarks, further highlighting its robustness and generalizability.

Details for L in Folding Learning (Table 17).

Table 13: Efficacy results on different downstream benchmarks. Ours means applying LQS for data scoring and Folding for data ordering within the DELT.

(a) Results (%) for 1B-token data across model sizes (160M, 470M, 1B).

	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
Model size = 160M									
Conventional	21.27	34.32	27.85	20.25	24.40	55.19	56.93	50.72	36.37
KenLM	**21.93**	33.96	28.09	20.69	25.20	54.79	56.20	50.59	36.43
PDS	21.84	35.02	27.61	19.93	24.80	**56.23**	59.00	51.38	37.01
Ours	21.59	**36.07**	**28.41**	23.79	25.60	56.37	**59.80**	53.04	**38.08**
Model size = 470M									
Conventional	21.16	34.91	28.11	21.88	23.90	56.07	58.75	50.04	36.85
KenLM	**22.35**	34.85	28.05	20.51	25.00	55.17	56.60	50.04	36.57
PDS	22.10	33.04	27.84	21.25	24.80	56.96	59.80	51.85	37.23
Ours	22.33	**35.88**	**28.45**	23.26	26.60	57.20	60.10	52.81	**38.33**
Model size = 1B									
Conventional	20.58	36.12	28.32	23.56	25.00	56.49	60.05	52.07	37.77
KenLM	21.67	35.86	28.76	23.46	26.80	56.58	59.00	49.88	37.75
PDS	22.10	35.56	28.20	23.56	26.40	56.37	60.50	50.67	37.92
Ours	**22.76**	**37.95**	**29.95**	26.38	26.00	58.07	60.90	51.28	**39.17**

(b) Results (%) for 160M model across data sizes (10B, 50B).

	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
Data size = 10B tokens									
Conventional	22.82	38.51	30.72	30.40	25.70	57.32	64.90	51.54	40.24
KenLM	22.78	37.92	30.54	29.98	25.60	57.29	66.00	52.80	40.36
PDS	22.70	39.35	30.73	31.85	27.20	56.04	64.90	**52.88**	40.71
Ours	**24.38**	**39.80**	**31.64**	32.98	27.21	58.56	**66.70**	51.67	**41.62**
Data size = 50B tokens									
Conventional	24.06	**41.88**	32.05	33.79	26.80	58.11	**69.00**	51.93	42.20
KenLM	23.74	40.14	32.10	35.13	28.41	58.15	67.52	51.71	42.11
PDS	24.57	41.37	32.44	35.36	29.20	**59.25**	68.10	50.83	42.64
Ours	**24.65**	41.07	**33.00**	36.07	29.30	59.10	68.40	52.67	**43.03**

Table 14: Efficacy results of different DELT implementations. The best scores for each model size are highlighted in **bold**, while the second-best scores are shown in ***italic bold***. The selection methods report the highest scores across all selection ratios.

Pipeline	Scoring	Selection	Ordering	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
Conventional	-	-	-	21.27	34.32	27.85	20.25	24.40	55.19	56.93	50.72	36.37
DELT	KenLM	-	Sorting	21.93	33.96	***28.09***	20.69	25.20	54.79	56.20	50.59	36.43
	KenLM	-	Folding	20.98	35.00	28.02	22.55	23.90	***56.54***	58.30	***51.36***	37.08
	PDS	-	Sorting	***22.44***	34.18	27.98	21.35	25.40	55.28	55.80	49.17	36.45
	PDS	-	Folding	21.93	34.81	28.04	22.43	**26.00**	56.42	**59.30**	50.20	37.40
	LQS	-	Sorting	**23.22**	***35.24***	28.03	***22.79***	24.70	56.85	57.90	51.17	***37.49***
	LQS	-	Folding	21.59	**36.07**	**28.41**	23.79	***25.60***	56.37	**59.80**	53.04	**38.08**
	KenLM	✓	Sorting	21.93	34.68	27.78	19.37	**26.40**	54.95	56.30	***52.96***	36.80
	KenLM	✓	Folding	***22.10***	34.30	27.62	21.56	25.00	56.26	58.10	52.80	37.22
	PDS	✓	Sorting	**22.61**	35.27	***28.08***	19.68	***25.80***	**56.53**	59.60	51.54	37.38
	PDS	✓	Folding	21.66	***36.01***	28.05	24.33	24.10	55.61	**61.70**	52.47	***37.99***
	LQS	✓	Sorting	***22.10***	35.61	28.05	22.53	23.60	55.93	59.60	51.38	37.35
	LQS	✓	Folding	21.59	**36.07**	**28.41**	***23.79***	25.60	***56.37***	**59.80**	53.04	**38.08**

Table 15: Comparison among different data scoring methods. The selection methods report the highest scores across all selection ratios.

Pipeline	Scoring	Selection	Ordering	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
Conventional	-	-	-	21.27	34.32	27.85	20.25	24.40	55.19	56.93	50.72	36.37
Efficiency	KenLM	✓	-	21.42	34.34	27.76	20.84	25.00	56.31	54.30	51.07	36.38
	DSIR	✓	-	**22.69**	34.55	28.26	21.81	24.40	**56.80**	54.80	51.14	36.81
	PDS	✓	-	21.84	35.02	27.61	19.93	24.80	56.23	59.00	51.38	37.01
	LQS (Ours)	✓	-	22.18	34.09	27.80	21.02	25.20	55.98	59.00	51.85	37.14
DELT	LQS (Ours)	✓	Folding	21.59	**36.07**	**28.41**	23.79	**25.60**	56.37	**59.80**	**53.04**	**38.08**

Table 16: Results on OLMo for the different epochs.

Epoch		ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
1	Conventional	21.27	34.32	27.85	20.25	24.40	55.19	56.93	50.72	36.37
	DELT (Ours)	**21.59**	**36.07**	**28.41**	**23.79**	**25.60**	**56.37**	**59.80**	**53.04**	**38.08**
2	Conventional	21.93	36.20	**29.18**	25.93	23.00	**56.86**	**61.20**	50.99	38.16
	DELT (Ours)	**22.35**	**36.41**	28.28	**27.63**	**26.80**	56.47	61.00	**51.22**	**38.77**
3	Conventional	21.35	35.78	28.76	27.14	**26.20**	**56.51**	**62.80**	49.51	38.51
	DELT (Ours)	**22.44**	**36.95**	**29.41**	**29.09**	24.80	56.20	62.30	**51.62**	**39.10**
4	Conventional	21.10	35.99	28.97	27.51	27.20	55.69	61.80	49.28	38.44
	DELT (Ours)	**22.53**	**38.05**	**29.78**	**29.58**	26.40	**57.34**	**63.90**	**51.85**	**39.93**
5	Conventional	20.59	37.55	29.31	28.05	**27.00**	57.11	61.20	**50.54**	38.92
	DELT (Ours)	**22.87**	**38.05**	**30.01**	**30.08**	26.80	**58.16**	**64.10**	49.80	**39.98**

Figure 8: The performance of KenLM (Heafield, 2011) and PDS (Gu et al., 2025) under different data selection ratios, both with and without the DELT. Data efficiency is enhanced when integrated into DELT.

To supplement Figure 6, we provide detailed results for the proposed Folding Learning method with varying values of the parameter L. As shown in Table 17, model performance reaches its peak at $L = 3$ and demonstrates significant advantages across most benchmarks. Notably, compared to traditional Curriculum Learning ($L = 1$), our proposed method ($L > 1$) achieves substantially better performance on all benchmarks.

E.2 Folding Learning Analysis

E.2.1 Data Bias Analysis

Traditional curriculum learning restricts the model to only "easy sample subsets" during early training (Bengio et al., 2009). This high homogeneity may restrict the gradient descent optimization path, causing the model to converge to a difficult-to-escape sharp local minimum (Soviany et al., 2022). To investigate the impact of the FO on data bias, we evaluate its advantages from two perspectives: *semantic diversity* and *difficulty diversity*. Specifically, we define a sliding window of size w (equal to the batch size) and analyze the data within each window.

For semantic diversity, we compute the average pairwise distance of sample features within the window. These features are represented by the penultimate layer embeddings of GPT-3 and the distance is measured using the Euclidean metric. For the diversity of difficulty, we compute the standard deviation of the scores within the window.

As shown in Table 18, compared to the sorting method, the folding strategy significantly enhances the local diversity of the data. This improvement prevents the model from encountering performance bottlenecks caused by overly homogeneous samples within local regions.

E.2.2 Model Forgetting Analysis

Traditional CL starts training from the easiest data bucket (Bengio et al., 2009). This sequential curriculum causes the model to lose contact with previously learned data, leading to the catastrophic forgetting of even simple concepts learned early on (Wang et al., 2021).

To directly monitor the forgetting phenomenon, we designed a layered validation experiment. We track the Perplexity (PPL) on the easiest 10% of the dataset (D_{val_easy}) throughout training. As shown in Figure 9, the PPL of traditional CL (sorting) on D_{val_easy} rapidly drops (initial 30% phase) but then significantly rebounds after entering the "hard" data region (latter 50%), which directly confirms the forgetting of simple samples. For the FO (L=3), PPL drops normally in Fold 1. When simple data is reintroduced in Fold 2, PPL shows a secondary sharp drop (Re-learning). By the end of training (Fold 3), the model maintains an extremely low PPL on D_{val_easy} and exhibits no rebound phenomenon seen in CL.

Figure 9: The LMs' perplexity (PPL) for D_{val_easy}. Results obtained from a 160M Mistral model trained on 1B-token data (Evaluated every 0.1B tokens).

Table 17: Effect of the fold layer L. "$L = -$" denotes the conventional method, representing the average of three random trials. When $L = 1$, the ordering method reduces to curriculum learning.

L	ARC-c	ARC-e	HS	LAMB	OBQA	PIQA	SciQ	Wino	Avg.
-	21.27	34.32	27.85	20.25	24.40	55.19	56.93	50.72	36.37
1	22.18	35.40	28.01	23.48	23.80	55.60	56.80	51.07	37.04
2	21.57	34.26	28.34	23.29	25.80	55.88	58.70	49.80	37.21
3	21.59	**36.07**	**28.41**	**23.79**	25.60	56.37	**59.80**	**53.04**	**38.08**
4	22.83	34.98	28.50	22.35	24.90	**56.67**	59.80	50.10	37.52
5	**22.91**	35.57	28.16	22.85	**26.70**	55.41	57.30	52.08	37.62

Table 18: Effect of the fold layer.

Methods	Semantic	Difficulty
Sorting	0.060	0.0003
Folding	0.067	0.0014

F LQS Analysis

F.1 Visualization of Sample Learnability Scores and Gradients

To empirically validate the relationship between learnability scores and sample characteristics, we visualize the gradient norm dynamics by tracking the gradient norms and learnability scores of the 5 samples across different training stages. Specifically, these samples consist of one hard and one simple high-quality sample (approx. 800–1000 tokens), two long noisy samples (approx. 800–1000 tokens), and one short noisy sample (approx. 30 tokens).

As shown in Figure 10, the learnability score for high-quality samples (driven by gradient reduction) consistently outweighs the variance observed in noisy samples, ensuring that learnable high-quality data is assigned significantly higher scores. Additionally, long noisy samples exhibit a slight decline, the magnitude of which likely correlates with their specific noise levels. In contrast, the gradient norm of the short noisy sample stabilizes at a very early stage, suggesting that it has likely been memorized (overfitted) by the model.

F.2 Samples Scored by LQS

To better illustrate our advantages, we visualized part samples. Specifically, we randomly sampled examples from the top 10% and bottom 10% based on their scores for visualization.

As shown in Table 19 and 20, high-scoring samples are high-quality, complex sentences that are not only challenging but also highly learnable, significantly aiding the model's optimization in later

Figure 10: The gradient normalization results for 5 different data samples. Results obtained from a 160M Mistral model trained on 1B-token data (Evaluated every 0.1B tokens).

stages. In contrast, as shown in Table **??**, low-scoring samples are often noisy and provide little to no benefit for model training, making them ideal candidates for filtering (see Table **??** example 1 and 2). However, some low-scoring samples consist of simple words or short phrases (see Table **??** example 3 and 4), which are beneficial for the model's learning in the early stages.

Examples of Randomly Sampled High-Scoring Data Points (Top 10%)

Example 1

 The precise nature of his doubt is not articulated but he aligns himself with the 17th century dissenters who put personal religious conscience before the unifying demands of the Church. This precipitates the move to the North, and determines the whole narrative arc of the novel. Before we are thrust, along with our central characters, into the smoky North, it is worth lingering a while on this short first stage of the novel. Gaskell does not make a simple thing of the South, as she might have been tempted to do as a clear point of comparison. Instead she offers us two versions of the South, two kinds of imaginings, both of which are then rejected. The drawing-room world of the Shaws, while superficially appealing, is altogether too enervating for the Margaret Hale who is gradually emerging even in these early chapters. Her decided refusal of Lennox is also a refusal of that world. The rural delights of Helstone (in the New Forest) seem initially to offer a simpler, perhaps a truer, version of the South. But that has already been put in doubt by Margaret and Henry Lennox's rather vexed discussion of it. In London, Henry suggests playfully that it is a 'village in a tale', at which Margaret takes umbrage, only to offer instead that it is 'a village in a poem' (11). When Henry arrives bang in the middle of that poem, the scene is set for romance: 'velvety cramoisy roses' (25), pears plucked from the tree and arranged on a plate of beetroot leaf, and the 'crimson and amber foliage' (26) of the deep forest beyond. Yet instead of the completion of the romantic dream, he comes up hard against Margaret's refusal. Indeed she herself comes up hard against it, and looks back at his proposal somewhat wistfully when she is plunged into her father's ferment, and briefly longs for the London/Shaw world where nothing 'called for much decision'. But if Margaret had accepted Henry – no novel. And besides, he can be kept in mind as a possible future plot line. Gaskell is astute enough to know that challenge makes for a more interesting narrative, and as it turns out, decision is something Margaret is rather good at. In the move to the South, she becomes the adult of the household, her mother declining into frailty, her father exhausted by the consequences of his own conscience. Her growth into her own strength of being is the more convincing because she often quails at what is before her. 'But the future must be met, however stern and iron it be.' (55) Thus, after a brief lull and taking of rest at the seaside town of Heston, Margaret and her father make the journey to Milton – the 'North' of the novel – where, as she says playfully, '"I am overpowered by the discovery of my own genius for management."' (57) But the obstacles are real, and the whole family must contend with their much-changed situation: They were settled in Milton, and must endure smoke and fogs for a season; indeed all other life seemed shut out from them by as thick a fog of circumstance. ... At night when Margaret realised this, she felt inclined to sit down in a stupor of despair. The heavy smoky air hung about her bedroom, which occupied the long narrow projection at the back of the house. The window, placed at the side of the oblong, looked to the blank wall of a similar projection, not above ten feet distant. It loomed through the fog like a great barrier to hope. (62) We are almost in the world of George Orwell's The Road to Wigan Pier – a work in fact heavily influenced by nineteenth-century depictions of urban industrialised living conditions. As if to underline their changed life, a letter has come from Edith, full of the delights of married life in Corfu: 'Edith's life seemed like the deep vault of blue sky above her, free – utterly free from fleck or cloud'. (62) This leads Margaret to reflect in turn on how, if she had accepted Lennox's marriage proposal, things might have been different. The omniscient narrative is here able to give much insight into Margaret's inner thoughts, so that we see her working through these difficult ideas and eventually finding herself clearer and happier: 'As she realised what might have been, she grew to be thankful for what was.' (63) If there is a measure of rationalisation in Margaret's logic here – that too is realistic.

Example 2

 For example, signals 116 and 118 may be in-phase (I) and quadrature (Q) baseband components of a signal. In the example of FIG. 1B, signals 116 and 118 undergo a zero crossing as they transition from +1 to -1. Signals 116 and 118 are multiplied by signal 120 or signal 120 phase shifted by 90 degrees. Signal 116 is multiplied by a 0 degree shifted version of signal 120. Signal 118 is multiplied by a 90 degree shifted version of signal 120. Resulting signals 122 and 124 represent time-varying complex carrier signals. Note that signals 122 and 124 have envelopes that vary according to the time-varying amplitudes of signals 116 and 118. Further, signals 122 and 124 both undergo phase reversals at the zero crossings of signals 116 and 118. Signals 122 and 124 are summed to result in signal 126. Signal 126 represents a time-varying complex signal. Signal 126 may represent an example input signal into VPA embodiments of the present invention. Additionally, signals 116 and 118 may represent example input signals into VPA embodiments of the present invention. 1.2) Example Generation of Time-Varying Complex Envelope Signals from Constant Envelope Signals The description in this section generally relates to the operation of step 508 in FIG. 50. FIG. 1C illustrates three examples for the generation of time-varying complex signals from the sum of two or more substantially constant envelope signals. A person skilled in the art will appreciate, however, based on the teachings provided herein that the concepts illustrated in the examples of FIG. 1C can be similarly extended to the case of more than two constant envelope signals. In example 1 of FIG. 1C, constant envelope signals 132 and 134 are input into phase controller 130. Phase controller 130 manipulates phase components of signals 132 and 134 to generate signals 136 and 138, respectively. Signals 136 and 138 represent substantially constant envelope signals, and are summed to generate signal 140. The phasor representation in FIG. 1C, associated with example 1 illustrates signals 136 and 138 as phasors P136 and P138, respectively. Signal 140 is illustrated as phasor P140. In example 1, P136 and P138 are symmetrically phase shifted by an angle ϕ_1 relative to a reference signal assumed to be aligned with the real axis of the phasor representation. Correspondingly, time domain signals 136 and 138 are phase shifted in equal amounts but opposite directions relative to the reference signal. Accordingly, P140, which is the sum of P136 and P138, is in-phase with the reference signal. In example 2 of FIG. 1C, substantially constant envelope signals 132 and 134 are input into phase controller 130. Phase controller 130 manipulates phase components of signals 132 and 134 to generate signals 142 and 144, respectively. Signals 142 and 144 are substantially constant envelope signals, and are summed to generate signal 150. The phasor representation associated with example 2 illustrates signals 142 and 144 as phasors P142 and P144, respectively. Signal 150 is illustrated as phasor P150. In example 2, P142 and P144 are symmetrically phase shifted relative to a reference signal. Accordingly, similar to P140, P150 is also in-phase with the reference signal. P142 and P144, however, are phase shifted by an angle whereby $\phi_2 \neq \phi_1$ relative to the reference signal. P150, as a result, has a different magnitude than P140 of example 1.

Table 19: Examples of Randomly Sampled High-Scoring Data Points (Top 10%).

Examples of Randomly Sampled High-Scoring Data Points (Top 10%)

Example 3

 Then Eddie owned up and said I took the records and my mummy said what did you do with them Eddie and he said I played cards with them that's what I done with them where as everybody was playing cards for tuppence and thrupence and he was playing with the records and our Tommy stood and looked at him, I have never forgotten the expression on Tommy's face. Eddie was about 15 or 16 then. When Eddie left school he successfully applied for a job in the Belfast City Council and I remember everybody being very proud because it was difficult to get a job with the Council back then. My mummy came in one day and said I was talking to the foreman about our Eddie and he said he's a great worker, my mummy was very proud of him. He used to land in for his lunch to my mummy with all the other binmen, she would have to feed them all. He stayed there until 1968 when he began working at boarding up buildings that had been damaged in the Troubles. As a way to earn an extra bit of money for the family he also worked nights as a barman. When Eddie got older he was always very particular about his appearance, he always wore a suit, sometimes with shirt or tee shirt, he was always very spick and span. Eddie smoked but he wasn't a drinker. That's not to say that he didn't try it at the beginning but it wasn't for him, he became a lifelong pioneer and a blood donor. He was also in the Confraternity (which was a sort of prayer group for men) at Clonard Monastery and he loved it; that was his wee place to get away to. He had strong faith. When Eddie was sixteen he met and fell in love with his future wife Marie. Marie was the love of his life and they courted for six years before getting married in 1962. Five years later their first child was born, quickly followed by three more. Eddie and Marie had three sons – Eamon, Patrick and Ciaran, and one daughter – Brenda. When they got married they went to live with Marie's grandmother in Fort Street. But he wanted his own house for himself and Marie and the only way that was going to happen was to get the money together to buy one. My daddy said to him. "look if you're looking extra money to buy a house go and join the TA its only 2 months a year". So he went and joined the Territorial Army and the money he was getting he sent it home to Marie. He wasn't in the TA for very long and had left by the time his first child was born. When Eddie came home things didn't work out the way he wanted about the house and things got too much for him, he ended up with a bit of a breakdown. Eventually they got the money for a house in Iveagh Street it was in a bad state of repair but Eddie and Marie fixed it up and made it their home. He suffered with mental health difficulties a couple of times in the early-mid 1960s but that was well behind him by the time of his death. Eddie just lived for Marie and their kids, he took on a couple of extra jobs, working as a bar man and doing a bit of painting and decorating. He was always ready and willing to drop everything and do something for you. It was just an ordinary family life and he just loved Marie, he idolised her and she could do no wrong in his eyes. All he had time for was work, home and the confraternity. When he did have free time he liked fishing and clay pigeon shooting. He was content with what he had and he was in his own wee orbit that he owned his house, and provided for his kids he was just happy to be a husband and a daddy. On payday he would give Marie his unopened pay packet, she would then buy him his cigarettes for the week. Not too many men did that in those days. Eddie was strict in a way too with the kids, I remember Eddie coming to visit me with Ciaran, I had a rocking horse in the living room and Ciaran wanted on it and Eddie said no you're not going over it doesn't belong to you, and I looked at Eddie and said let the child go over and get on to the horse I said catch yourself on there is nobody even on it and he went over but he was holding him on it because he maybe would of toppled.

Example 4

 I was interested to see if I would lean closer to earlier poems or later poems since sometimes there can be a significant difference in a poets writing style compared to when they began and ended. Turns ou This.Was.My.Jam Where do I even begin? So the collection is written in reverse chronological- yeah that's right I actually read the introduction to something. I found this particularly interesting because I feel like we often start in the beginning and naturally work our way through their work. I was interested to see if I would lean closer to earlier poems or later poems since sometimes there can be a significant difference in a poets writing style compared to when they began and ended. Turns out I pretty steadily loved it all. I think if I HAD to chose I would lean just slightly closer to the beginning of the collection, but just slightly. That might have a bit of a biases though since Annabelle Leigh is the very first poem we read and it's always been my absolute favorite. Annabelle Leigh aside, I can only imagine what other wonderfully powerful and hauntingly beautiful pieces he could have continued to write had he lived longer. (Internally sobbing) You'll probably notice that there's a lot of reoccurrence with things like the moon, celestial bodies, night, and the evening star- all things I really enjoyed. Also, (and this might quite well be my favorite) Poe has some of the best rhymes. Words that rhymed but weren't your usual rhymes, if you will. For example: departed and brokenhearted, month of June and mystic-moon, dipt in folly and melancholy, Heaven and unforgiven (you gotta twang a little for that one), itself alone and gray tombstone, heart's content and own element. etc. And it doesn't stop there! The the entire language being used is SO GOOD. I'd be reading a poem and then I'd hit a particular line or phrase and just have to a take a moment to say "damn" while the words were absorbed. Some examples of that are "And the silken, sad, uncertain rustling of each purple curtain" (The Raven), I stand amid the roar of a surf-tormented shore (A Dream Within a Dream), With the moon-tints of purple and pearl (Eulalie-A Song), Sound loves to revel in a summer night: Witness the murmur of the gray twilight. (Al Aaraaf Part 2) and "So like you gather in your breath, a portrait taken after death. (Tamberlane) Even the poems that I didn't mark as favorites I still really enjoyed. My least favorite in the collect was Al Aaraaf (both parts), I'm not really sure why I just didn't feel as wow'ed by it. Also, the play that ends the collection I wasn't a huge fan of but I think that just speaks true to the format. Plays are different than poetry. I haven't read any Poe stories for a long time, so I think it would be interesting to see where my enjoyment falls on the prose. But, the poetry is definitely out of the park for me. Something I do find intriguing is that growing up I also thought Poe was just a dark and haunted poet. I think he was in fact haunted, but I don't think (the poetry at least) is as horrific as people usually indicate. In fact, I'm willing to call it beautiful. Beautifully dark, perhaps? Read it, it's perfect. Mateo – Oct 24, 2020 I did not make this image but this is my review I did not make this image but this is my review Stephanie Grosse – Sep 23, 2018 This review has been hidden because it contains spoilers. To view it, click here. Simultaneously mysterious and familiar, like the old friend who suddenly astonishes you with his strangeness or the acquaintance whom you are convinced you must have known since childhood. I very much enjoyed the use of onomatopoeia. You will be hypnotised by the sounds (for example "ee", "em" in the summer dream beneath the tamarind tree). Poe has you forever, in "a dream within a dream" Very memorable.A must read for all poetry lovers. Simultaneously mysterious and familiar, like the old friend who suddenly astonishes you with his strangeness or the acquaintance whom you are convinced you must have known since childhood. I very much enjoyed the use of onomatopoeia.

Table 20: Examples of Randomly Sampled High-Scoring Data Points (Top 10%).

Examples of Randomly Sampled Low-Scoring Data Points (Bottom 10%)

Example 1

XXXXXXXXXX XXXXXXXX XXXXXXXXXX XXXXXXXXX XXXXXXXXXXXXXXX XXXXXXXXXXXXX XXXXXXXXXX XXXXXXXX XXXXXXXX XXXXX XXXXXXXXXXX XXXXX
XXXXXXXXX XXXXXXX XXXXXXX XXXXX XXXXXXXXXXX XXXXXXX XXXX XXX XX XXXXX XXXXXXXXXXX XXXXXXXXXXX XXXXXXXXXXX XXXXXXXXXXXX
XXXXXXXXX XXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXX XXXXX
XXXXXXXX XXXXXXXXXXXXXX XXXXXXXXXXXXXXXX XXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXX XXXXX XXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXX XXXXXXXXXX XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXX Select a country but NOT a region All you need to know about the Indian Defence Forces!

Example 2

XXXXXXXXXX XXXXXXXX XXXXXXXXXX XXXXXXXXX XXXXXXXXXXXXXXX XXXXXXXXXXXXX XXXXXXXXXX XXXXXXXX XXXXXXXX XXXXX XXXXXXXXXXX XXXXX
XXXXXXXXX XXXXXXX XXXXXXX XXXXX XXXXXXXXXXX XXXXXXX XXXX XXX XX XXXXX XXXXXXXXXXX XXXXXXXXXXX XXXXXXXXXXX XXXXXXXXXXXX
XXXXXXXXX XXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXX XXXXX
XXXXXXXX XXXXXXXXXXXXXX XXXXXXXXXXXXXXXX XXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXX XXXXX XXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXX XXXXXXXXXX XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXX Select a country but NOT a region A site focusing on Australian Modelling with galleries, articles
and discussion forums.

Example 3

 USA, Liberia USA, Lithuania, Italy USA, Luxembourg USA, Luxembourg, UK USA, Malaysia USA, Malta, France, UK USA, Malta, UK USA, Mexico
USA, Mexico, Australia USA, Mexico, Australia, Canada USA, Mexico, Canada USA, Mexico, Canada, Germany USA, Mexico, Germany USA, Mexico, Hong
Kong USA, Mexico, Japan USA, Mexico, Spain USA, Mexico, UK USA, Mexico, United Arab Emirates USA, Monaco USA, Monaco, Morocco USA, Morocco USA,
Morocco, Spain, UK USA, Morocco, Switzerland USA, Myanmar USA, Netherlands USA, Netherlands, France USA, Netherlands, Germany, France, Austria
USA, Netherlands, South Africa USA, Netherlands, UK USA, Netherlands, UK, Denmark USA, New Zealand USA, New Zealand, Canada, Israel, Japan,
Nigeria USA, New Zealand, Germany USA, New Zealand, Japan USA, New Zealand, South Africa, UK, Lithuania USA, New Zealand, UK USA, Nicaragua
USA, Nigeria USA, Norway USA, Pakistan USA, Panama, Argentina USA, Panama, Japan, Canada USA, Panama, Mexico USA, Peru USA, Philippines USA,
Philippines, Puerto Rico USA, Philippines, Taiwan, South Korea, China, Canada USA, Poland USA, Poland, Slovenia, Czech Republic, UK USA,
Portugal USA, Portugal, France USA, Puerto Rico USA, Qatar USA, Romania USA, Romania, Canada USA, Romania, France, Italy, Germany USA, Romania,
Germany USA, Romania, Iceland USA, Romania, UK USA, Russia USA, Russia, Hungary USA, Russia, UK USA, Saudi Arabia USA, Senegal USA, Serbia
USA, Serbia, Canada USA, Singapore USA, Singapore, Taiwan USA, Slovakia USA, Slovakia, China USA, South Africa USA, South Africa, Germany USA,
South Africa, India USA, South Africa, Italy USA, South Africa, Zambia, Germany USA, South Korea USA, South Korea, Australia USA, South Korea,
India USA, South Korea, Japan USA, South Korea, Singapore USA, South Korea, Singapore, Russia, Malaysia, Kazakhstan, Taiwan, Hong Kong, Japan,
China, India, Syria, Iran, Egypt, Pakistan USA, South Korea, Spain

---

Example 4

 Phillip L. Horrell v. David Gomez, Warden, No. 20-5306 Ganaa Otgoo v. Illinois, No. 20-5109 Phillip Hartsfield v. Stepanie Dorethy, Warden,
No. 19-1473 Anthony Jackson v. Supreme Court of Illinois, No. 19-8665 David Beverly v. Illinois, No. 19-8502 Lamont Dantzler v. Illinois, No.
19-8448 Joh-ner Taylor Wilson v. Illinois, No. 19-8437 Herbert Burgess v. Illinois, No. 19-8379 Joseph M. Coffman v. Illinois, No. 19-8391
Timothy J. McVay v. Illinois, No. 19-8304 Kenneth Durant v. Frank Lawrence, Warden, No. 19-7967 Seth A. Weaver v. Illinois, No. 19-7823 Lyarron
T. Emers v. Illinois, No. 19-7759 Bethany Austin v. Illinois, No. 19-1029 Anthony Allen v. Illinois, No. 19-7633 Kenin L. Edwards v. Michael L.
Atterberry, et al., No. 19-965 Pablo Rodriguez-Palomino v. Illinois, No. 19-7273 Christopher L. Croom v. Illinois, No. 19-7237 Tony Robinson v.
Illinois, No. 19-7226 Lazaro Zapata v. Illinois, No. 19-7264 Fernando Oliveros v. Illinois, No. 19-7141 Kevin Dameron v. Illinois, No. 19-6945
Peter Gakuba v. Michelle Neese, No. 19-6543 Richard Kalinowski v. Illinois, No. 19-6368 Rafael Alvarado v. Frank Lawrence, Warden, No. 19-6347
Chad M. Cutler v. Illinois, No. 19-6150 Hezekiah Whitfield v. Deanna Brookhart, Warden, No. 19-6051 Lorenzo Davis, Jr. v. Illinois, No. 19-5831
Chadwick N. Barner v. Illinois, No. 19-5655 Charles Donelson v. Q. Tanner, et al., No. 19-5397 Robert Curry v. Illinois, No. 19-5366 Andrew
Condon v. Illinois, No. 19-5349 Keith Talbert v. Illinois, No. 18-9768 Juan Rodriguez v. Illinois, No. 18-9759 Miguel Alcantar v. Illinois,
No. 18-1548 Gregory Rayford v. Illinois, No. 18-9612 Irving Madden v. Michael Melvin, Warden, No. 18-9474 Denzel Pittman v. Illinois, No.
18-9451 Jesus Cotto v. Jacqueline Lashbrook, Warden, No. 18-9116 Pierre Montanez v. Ursula Walowski, No. 18-9101 Russell Frey v. Illinois, No.
18-9120 Peter Gakuba v. Illinois, No. 18-9041 Jose Cobian v. Illinois, No. 18-8963 Derrick Redmond v. Illinois, No. 18-8808 Jennifer N. Nere
v. Illinois, No. 18-8625 Gerald W. Long v. Illinois, No. 18-8577 Willie White v.

Table 21: Examples of Randomly Sampled Low-Scoring Data Points (Bottom 10%).