From Enterprise Knowledge Graphs to Policy-Compliant Agents: Governing Data, Models, and Autonomous Curation

Chris Hokamp[1], Jack Boylan[1], Jerome Bryssinck[1], Deniz Kuey[1] and John Murray[1]

[1]*Quantexa*

Abstract

The governance surface for knowledge graphs in highly regulated domains such as financial crime now extends to model risk management, regulatory obligation traceability, and the guiding and auditing of LLM-backed agent behaviors. Importantly, different usecases for enterprise knowledge graphs require adherence to different policies, so frameworks must be flexible and easy to extend; otherwise, adding compliance harnesses for new policies or regulation can be prohibitively expensive.

In this paper, we describe the governance architecture of the Quantexa Metagraph, an enterprise knowledge graph that encodes its own governance rules as first-class graph content, alongside the domain knowledge those rules govern: regulatory policies decomposed into machine-traversable obligation→control chains; governance and policy ingestion protocols aligned with open standards, and behavioral policies — Agent Instructions and Graph Shapes — that curator agents read from the same graph they write to, under write-mode controls and a per-mutation, agent-attributed audit log. New policies can be curated into the graph, and because agents read their instructions from the graph as well, they can be dynamically configured to follow and obey new or customized policies.

We map these mechanisms onto ODRL, DPV, and SHACL, identifying what existing standards do not yet cover — behavioral governance, graduated trust, and mutation-level audit — and argue that next-generation data governance should treat policies for agents as data in the graph rather than as compliance overlays around it.

Keywords

data governance, knowledge graphs, autonomous agents, ODRL, model risk management, regulatory compliance, provenance

1. Introduction

Knowledge graphs are critical infrastructure in financial services, underpinning entity resolution, risk scoring, and investigative workflows across anti-money-laundering (AML), know-your-customer (KYC), and fraud use cases [1, 2], among others. The recent explosion in AI capabilities has made enterprise knowledge graphs tractable and realistic to use and maintain for many organisations, but the mechanisms for governance of these graphs — who may write what, on what authority, with what audit trail, and in satisfaction of which regulatory obligations — remains underspecified in both the literature and industry practice. This work explores knowledge graphs as a natural solution for the curation and retrieval of policy and governance information, and for modeling and orchestrating the intelligent agents (both humans and AI agents) that interact with the graph.

2. Related Work

The semantic web community has produced mature standards for individual governance concerns. Open Digital Rights Language (ODRL) expresses access- and usage-control policies [3]; because it provides a vocabulary rather than an enforcement engine, organizations apply it by defining profiles that automated systems can interpret, and recent work has moved these policies from descriptive to

NXDG 2026: NeXt-generation Data Governance workshop, co-located with the 22nd International Conference on Semantic Systems (SEMANTiCS 2026), September 15, 2026, Ghent, Belgium

✉ chrishokamp@quantexa.com (C. Hokamp); jackboylan@quantexa.com (J. Boylan); jeromebryssinck@quantexa.com (J. Bryssinck); denizkuey@quantexa.com (D. Kuey); johnmurray@quantexa.com (J. Murray)

enforceable [4, 5] and encoded regulatory instruments themselves as semantic patterns [6]. Data Privacy Vocabulary (DPV) provides machine-readable privacy metadata for GDPR [7] and, since version 2.0, the EU AI Act [8, 9], and SHACL validates graph structure [10]. Additionally, recent work on the AI Risk ontology (AIRO), maps the EU AI act into an ontology designed to aid risk modeling in the context of EU AI regulations [11].

Agent participation changes the governance problem in kind, not only in degree. A policy that is unambiguous in the mind of a compliance officer may be ambiguous under an LLM's interpretation, so behavioral rules cannot simply be written down and assumed to hold; they must be made explicit, attributed, validated structurally where possible, and audited per mutation. At the same time, the semantics of the graph itself are partly emergent; because many usecases require agents to extend the schema as new data arrives (including the ingestion and curation of new policies or user-specific governance protocols), the governance layer must evolve with the llm graph rather than being fixed outside it.

In this paper we describe how these requirements are met in the Quantexa Metagraph, a production enterprise knowledge graph whose architecture is described in detail in a companion paper[1]. Our contributions are:

1. a **regulatory knowledge model** that decomposes regulations into machine-traversable obligation→control→risk-factor chains, connected to the detection logic that implements them (Section 4.1);

2. a **model governance layer** that represents model risk management artifacts required by SR 11-7[2], SS1/23[3], and the EU AI Act as graph entities linked to the components they document (Section 4.2);

3. a **policy-compliant agent architecture** in which autonomous curators operate under behavioural policies stored in the graph they curate, with write-mode controls, structural shape constraints, and a per-mutation, agent-attributed audit log (Section 4.3);

4. an **alignment analysis** mapping these mechanisms onto ODRL, DPV, and SHACL, identifying the governance requirements that current standards do not cover (Section 5).

However, these standards primarily govern *data* — who may access, process, or share it. They do not address the systems that now participate in building the graph: fleets of LLM agents that create entities, assert relationships, and correct data quality autonomously.

3. The Metagraph

The Metagraph is a Wikidata-style [12] enterprise knowledge graph framework: entities and properties are the top-level domain items, and the schema itself is graph content, so new classes and properties can be introduced at runtime without migration. Our internal instantiation of the metagraph currently holds approximately 300,000 triples describing roughly 13,000 entities, spanning solution blueprints for AML, KYC, and fraud use cases, score patterns across risk typologies, platform components, personnel, documentation, and the regulatory and governance content this paper describes. Importantly, the AI agents that interact with the graph, and their instructions, are also stored in the graph. The Quantexa Metagraph is stored in a SPARQL-queryable graph database behind an API gateway that is the sole write path, and is consumed by human users through Model Context Protocol tools [13] inside coding assistants, by a web interface, and by a fleet of autonomous LLM curators, spanning twelve registered task types, that runs continuously.

Three architectural features carry the governance load (Figure 1). First, every mutation passes through a write-ahead log (WAL): an append-only record of the full SPARQL operation, timestamp, target graph, and agent identity, retained in version control and sufficient to reconstruct the store by replay. Second, the gateway enforces hard policy at write time — malformed SPARQL is rejected, a

---

[1]citation to appear on acceptance
[2]https://www.federalreserve.gov/boarddocs/srletters/2011/sr1107.pdf
[3]https://www.bankofengland.co.uk/prudential-regulation/publication/2023/may/model-risk-management-principles-for-banks-ss

collision guard prevents conflicting entity and property creation. Third, agents are governed by content *in* the graph: behavioral instructions and structural shape constraints that curators fetch at startup from the same store they write to. This last loop — agents reading their policies from the artifact they maintain — is the pattern the rest of the paper develops.

Figure 1: Governance architecture of the Metagraph. All writes — human and agent — pass through one gateway and are logged with agent attribution before execution. Behavioural policies (Agent Instructions) and structural constraints (Graph Shapes) are entities in the same store, so the curator fleet reads its governance from the graph it maintains.

4. Governance as Graph Content

4.1. The Regulatory Knowledge Model

Financial institutions must demonstrate that deployed detection logic addresses specific regulatory requirements. To make that demonstration a query rather than a document exercise, the Metagraph decomposes regulations into graph structure: we currently have ingested policies and regulations from 17 regulatory bodies (FATF, MAS, FCA, EBA, FinCEN, and others across nine jurisdictions), 15 regulatory policies, and 37 policy sections, connected through dedicated properties to 12 obligations, 8 control measures, and 8 risk factors. The properties *imposesObligation* (P473), *requiresControl* (P474), *identifiesRiskFactor* (P476), and *riskLevel* (P477) make obligation chains traversable in both directions. For example, for Singapore's MAS Notice 626 [14], decomposed most deeply to date:

```
MAS 626 §8.2 (PEPs)  →P473  apply EDD for PEPs  →P474  {PEP screening;
    source-of-wealth verification; senior-management approval}
```

A compliance officer — or an agent — can ask either "what controls implement this obligation?" or "which obligations does this control satisfy?"

The same pattern connects regulation to detection. A four-property *configuration chain* links each score pattern to its risk typology (P468), required entity types (P469), graph-traversal requirements (P470), and applicable solution blueprints (P471) — 1,668 assertions over the 176 score patterns — so that "which score patterns address trade-based money laundering, require Business entities, and apply to the trade-AML blueprint?" is a single SPARQL query. In practice we find the value of this model is less multi-jurisdictional comparison than *use-case-specific assembly*: given a deployment's blueprint

and jurisdictions, an agent bootstraps the applicable requirement set — obligations, controls, score patterns, thresholds — from the graph instead of re-reading regulatory text. A synthetic simulation layer grounds this model end-to-end: narrative financial-crime scenarios (cross-border layering, trade-based laundering, luxury-asset integration) are mapped to real graph identifiers for typologies, score patterns, and regulatory agencies, providing a testbed for validating that obligation chains support complete compliance narratives without exposing client data.

4.2. Model Governance as Graph Content

Model risk management regimes — SR 11-7 [15] in the US, SS1/23 [16] in the UK, and the horizontal requirements of the EU AI Act [17] — require model cards, validation evidence, and lifecycle documentation. When these artifacts live outside the knowledge graph, they cannot participate in the queries that govern everything else. The Metagraph therefore encodes an internal model-risk-management framework as a 31-entity subgraph: model cards and component software cards, a four-pillar testing framework (technical validation, conceptual soundness, performance evaluation, ongoing monitoring), a six-way classification of AI system artifacts, and red/yellow/green license-risk assessment for third-party assets. A dedicated property (*hasGovernanceDocumentation*, P423) links more than 50 platform components to their governance artifacts, so "which components lack model cards?" and "which model cards claim SR 11-7 compliance?" are queries, not audits. The three regulatory standards are themselves entities, linked to the artifacts they mandate; concepts from the AI Risk Ontology (AIRO) [11] — risk, risk source, consequence, control — are included as alignment points with the wider AI governance vocabulary landscape. The same layer tracks governance documentation across a portfolio of client deployments (global custody and retail banks, a securities-market utility, and professional-services firms), which makes governance maturity across the portfolio itself queryable.

4.3. Policy-Compliant Autonomous Curation

The Metagraph is curated continuously by autonomous LLM agents — twelve registered task types covering discovery, enrichment, deduplication, synchronization, and documentation. Governing them requires attribution, authorization, behavioural constraint, human review where trust is limited, structural compliance, and full auditability. To the best of our knowledge, no existing semantic governance standard addresses this combination.

Four mechanisms do the work.

1. *Write modes*: trusted curators write directly; untrusted or experimental agents operate in `suggest` mode, where assertions become pending suggestions that a human reviewer approves or rejects — approval materializes the triple with full attribution.
2. *Agent Instructions*: behavioral policies are entities in the graph, prioritized (critical / high / normal), categorized, and optionally targeted at specific agent types; agents fetch them at startup via SPARQL and receive them in their system prompts.
3. *Graph Shapes*: SHACL contstraints specify required, optional, and banned properties for key classes, and a per-entity endpoint computes constraint-by-constraint compliance on demand. Shapes themselves are curatable graph citizens rather than external documents.
4. *Audit*: the WAL attributes every mutation to an agent identity; currently authority scores are derived from sources.

5. Alignment with Existing Standards

The mechanisms above map partially onto existing standards. In ODRL terms [3], `direct` write mode is a permission, property and shape-based bans are prohibitions, and `suggest` mode a permission carrying an approval duty; formalizing our write policies as an ODRL profile would make them interoperable with dataspace policy frameworks such as Gaia-X and IDS [18, 19], and enforceable with emerging

ODRL engines [4, 5]. But Agent Instructions exceed ODRL's scope: they govern *how* an agent should behave when permitted to act — which properties to prefer, what to verify before writing — and the authority score implements graduated trust that a binary permission/prohibition model does not express. DPV 2.0's AI Act extension [9] aligns naturally with the model-governance layer (AI system classification, risks, controls), with the difference that the Metagraph operationalizes these concepts in live queries driving blueprint navigation and gap analysis rather than as static annotations. The Graph Shape system is functionally SHACL [10], with two deliberate departures: shapes are first-class entities subject to the same provenance and curation as domain content, and compliance is computed continuously through an API rather than in batch validation runs. Table 1 summarizes the coverage.

Table 1
Governance requirements of agent-curated enterprise KGs versus the scope of existing semantic governance standards (• = covered; ○ = partial; — = out of scope).

Requirement	ODRL	DPV	SHACL	Metagraph mechanism
Data access control	•	○	—	write modes
Privacy metadata	—	•	—	attribution properties
Structural validation	—	—	•	Graph Shapes
Agent behavioural governance	—	—	—	Agent Instructions
Obligation traceability	—	○	—	P473/P474/P476 chains
Model governance artifacts	—	○	—	P423 + framework entities
Per-mutation audit trail	—	—	—	agent-attributed WAL
Graduated trust	—	—	—	authority scoring
Review workflow	○	—	—	suggestion pipeline

6. Discussion

Why in-graph governance. Keeping governance rules, regulatory obligations, model documentation, and agent policies in the graph — rather than in systems around it — yields one query surface: a single SPARQL traversal can run from a regulatory obligation to the score pattern that implements it, the model card that documents that component, and the agent that last curated any of them. It also means governance content is maintained by the same curation machinery as domain content, and that provenance is self-describing in the sense of PROV [20]: "who changed this obligation?" and "what does this agent typically change?" are the same kind of query. Critically, storing the governance framework inside the graph allows straightforward curation and extension of the framework itself, meaning that our design allows us to rapidly ingest new policies and governance documents, and our agents adapt their behavior on the fly to changes in the graph.

Limitations. Agent Instructions are currently natural language interpreted by LLMs, not rules executed by a reasoner; compliance is probabilistic, which is precisely the gap noted in Section 1 — a policy unambiguous to its human author may admit multiple machine interpretations. We mitigate with hard enforcement where rules are expressible in code and shapes where they are structural.

Next steps. The natural continuation is formal alignment: expressing write-mode policy as an ODRL profile with conflict detection over the emerging formal semantics; for example, mapping the model-governance layer onto DPV 2.0's AI Act extension for interoperable compliance reporting; exporting Graph Shapes as standard SHACL while retaining the in-graph representation as authoritative; and formalizing Agent Instructions enough to detect contradictions unambiguously before agents encounter them.

7. Conclusion

Enterprise knowledge graphs in regulated industries need governance that spans data access, regulatory obligation, model documentation, and agent behaviour. The Metagraph demonstrates a working implementation of a holistic, AI-native framework, where policies, obligations, governance artifacts, and behavioral rules as first-class content in the graph they govern, enforced at a single write path with per-mutation attribution.

Declaration on Generative AI

During the preparation of this work, the authors used Claude Code (Anthropic) for drafting assistance and manuscript preparation. The authors contributed all material and take full responsibility for the publication's content.

References

[1] A. Hogan, E. Blomqvist, M. Cochez, C. d'Amato, G. de Melo, C. Gutierrez, S. Kirrane, J. E. Labra Gayo, R. Navigli, S. Neumaier, A.-C. Ngonga Ngomo, A. Polleres, S. M. Rashid, A. Rula, L. Schmelzeisen, J. Sequeda, S. Staab, A. Zimmermann, Knowledge graphs, ACM Computing Surveys 54 (2021) 71:1–71:37. doi:10.1145/3447772.

[2] N. Noy, Y. Gao, A. Jain, A. Narayanan, A. Patterson, J. Taylor, Industry-scale knowledge graphs: Lessons and challenges, Communications of the ACM 62 (2019) 36–43. doi:10.1145/3331166.

[3] R. Iannella, S. Villata, ODRL information model 2.2, W3C Recommendation, 2018. URL: https://www.w3.org/TR/odrl-model/.

[4] A. Cimmino, J. Cano-Benito, R. García-Castro, Open digital rights enforcement framework (ODRE): From descriptive to enforceable policies, Computers & Security 150 (2025) 104282. doi:10.1016/j.cose.2024.104282.

[5] W. Slabbinck, J. A. Rojas Meléndez, B. Esteves, R. Verborgh, P. Colpaert, May the FORCE be with you? A framework for ODRL rule compliance through evaluation, in: Posters, Demos, Workshops, and Tutorials at SEMANTiCS 2025 (NXDG), volume 4064 of *CEUR Workshop Proceedings*, CEUR-WS.org, 2025. URL: https://ceur-ws.org/Vol-4064/.

[6] D. Golpayegani, H. J. Pandit, D. Lewis, Semantic patterns of prohibited AI systems in the EU AI Act, in: Posters, Demos, Workshops, and Tutorials at SEMANTiCS 2025 (NXDG), volume 4064 of *CEUR Workshop Proceedings*, CEUR-WS.org, 2025. URL: https://ceur-ws.org/Vol-4064/.

[7] European Parliament and Council of the European Union, Regulation (EU) 2016/679 — general data protection regulation, Official Journal of the European Union, L 119, 2016.

[8] H. J. Pandit, A. Polleres, B. Bos, R. Brennan, B. Bruegger, F. J. Ekaputra, J. D. Fernández, R. Gachpaz Hamed, E. Kiesling, M. Lizar, E. Schlehahn, S. Steyskal, R. Wenning, Creating a vocabulary for data privacy, in: On the Move to Meaningful Internet Systems: OTM 2019 Conferences (ODBASE), volume 11877 of *Lecture Notes in Computer Science*, Springer, 2019, pp. 714–730. doi:10.1007/978-3-030-33246-4_44.

[9] H. J. Pandit, B. Esteves, G. P. Krog, P. Ryan, D. Golpayegani, J. Flake, Data privacy vocabulary (DPV) — version 2.0, in: The Semantic Web – ISWC 2024, volume 15233 of *Lecture Notes in Computer Science*, Springer, 2024. doi:10.1007/978-3-031-77847-6_10.

[10] H. Knublauch, D. Kontokostas, Shapes constraint language (SHACL), W3C Recommendation, 2017. URL: https://www.w3.org/TR/shacl/.

[11] D. Golpayegani, H. J. Pandit, D. Lewis, AIRO: An ontology for representing AI risks based on the proposed EU AI Act and ISO risk management standards, in: Towards a Knowledge-Aware AI (Proc. SEMANTiCS 2022), IOS Press, 2022. doi:10.3233/SSW220008.

[12] D. Vrandečić, M. Krötzsch, Wikidata: A free collaborative knowledgebase, Communications of the ACM 57 (2014) 78–85. doi:10.1145/2629489.

[13] Anthropic, Model context protocol, Specification, 2024. URL: https://modelcontextprotocol.io/.

[14] Monetary Authority of Singapore, Guidelines to MAS notice 626 on prevention of money laundering and countering the financing of terrorism, 2015. As amended.

[15] Board of Governors of the Federal Reserve System and Office of the Comptroller of the Currency, Supervisory guidance on model risk management, SR Letter 11-7, 2011.

[16] Bank of England Prudential Regulation Authority, Model risk management principles for banks, Supervisory Statement SS1/23, 2023.

[17] European Parliament and Council of the European Union, Regulation (EU) 2024/1689 — artificial intelligence act, Official Journal of the European Union, L series, 2024.

[18] Gaia-X European Association for Data and Cloud, Gaia-x architecture document, Release 22.10, 2022. URL: https://gaia-x.eu/.

[19] B. Otto, S. Steinbuß, A. Teuscher, S. Lohmann, IDS reference architecture model 4, International Data Spaces Association, 2022. URL: https://docs.internationaldataspaces.org/ids-knowledgebase/ids-ram-4.

[20] T. Lebo, S. Sahoo, D. McGuinness, PROV-O: The PROV ontology, W3C Recommendation, 2013. URL: https://www.w3.org/TR/prov-o/.