LOGICAL VIEW ON FAIRNESS OF A BINARY CLASSIFICATION TASK

ABSTRACT

Ethical, Interpretable/Explainable, and Responsible AI are an active area of research and important social initiative. Vendors offer solutions. For instance, Microsoft compiled a platform, Responsible AI. Within the context, challenges of algorithmic fairness and trustworthiness of machine learning are paramount. Furthermore, several authors argue that the emergence of algorithmically infused societies necessitates innovative approaches to measuring feasible information, e.g., collecting data shall follow a trustworthy social theory. In this paper, we show that this approach is heuristic at best.

We prove that, with no regards to data, fairness and trustworthiness are algorithmically undecidable for a basic machine learning task, the binary classification. Therefore, even the approach based on not only improving but fully solving the three usually assumed issues – the insufficient quality of measurements, the complex consequences of (mis)measurements, and the limits of existing social theories – is only heuristics. We show that, effectively, the fairness of a classifier is not even a (version of bias-variance) trade-off inasmuch as it is a logical phenomenon. Namely, we reveal a language L and an $L-$theory T for binary classification task such that the very notion of loss is not expressible in the first-order logic formula in L.

1 INTRODUCTION

Ethical, Interpretable/Explainable, and Responsible AI are an active area of research and important social initiative. Vendors offer solutions. For instance, Microsoft compiled a platform, Responsible AI. Within the context, challenges of algorithmic fairness and trustworthiness of machine learning are paramount. Furthermore, several authors argue that the emergence of algorithmically infused societies necessitates innovative approaches to measuring feasible information, e.g., collecting data shall follow a trustworthy social theory [3]. In this paper, we show that this approach is heuristic at best.

We prove that, with no regards to data, fairness and trustworthiness are algorithmically undecidable for a binary classification task (cf. [4], [5]). Therefore, even the approach based on not only improving but fully solving the three usually assumed issues – the insufficient quality of measurements, the complex consequences of (mis)measurements, and the limits of existing social theories – is only heuristic. We prove that, effectively, the fairness of a binary classifier is not even a trade-off (e.g., a version of bias-variance/complexity etc.) inasmuch as it is a logical phenomenon. Namely, we reveal a language L and $L-$theory T for binary classification task such that the very notion of loss is not expressible in the first-order logic L-formula.

We consider the natural generalization of the binary classifier for the infinite domain.

Out goal is to introduce a purely logical view on loss for a binary classifier on an infinite domain. It is achieved by introducing a general notion of classifier loss based on an observation that any natural loss is a first-order formula in a suitable structure. The latter has a theory T represented by a tuple $\langle L, M \rangle$ where L is a language and M is model for L.

Next, we will show that the resulting first-order theory T admits an extension RG_{ext} on random graph structure such that a notion that a graph has an equal number of connected and unconnected nodes is not expressible in the RG_{ext}-first-order logic. The binary classifiers' structure is isomorphic

(with probability 1) to T. Therefore, if a first-order sentence in one theory is deducible (i.e., can be proved) in that theory, the corresponding sentence is deducible in another.

Then, for two given classifiers, assuming that the classifier loss is a first-order logic formula, $C1 \equiv \langle D, L_{c1} \rangle$ and $C2 \equiv \langle D, L_{c2} \rangle$, we can construct a first-order expression $L_{c1} - L_{c2} = 0$ which is equivalent to an expression that the two classifiers have the same number of connected and unconnected nodes which leads to contradiction. This effectively means that any loss function is not expressible in the RG_{ext}-first-order logic. The rest of the paper is dealing with the proof of these statements. It is interesting to compare this with a general undecidability of identities for wide class of functions in [1].

We conclude with discussion of losses expressible in second and higher logic theory and immediate implications for adopting them on fairness and interpretability. The extended version of the paper contains more information on each of these topics.

1.1 NOTATIONS AND DEFINITIONS

We will try to make this paper self-sufficient and provide all necessary references to the reader who would like to invest more time into the mathematical foundations of machine learning and interpretablity. We would need some information from model theory. We assume that the reader is familiar with the concepts of domain, classifier, and loss as well as the standard body of statistics and probability theory normally used in a supervised machine learning. Notations are natural; $\mathbb{N}$ denotes the set of natural numbers, $\mathbb{Z}$ stands for integers, and $\mathbb{R}$ denotes reals. $\mathbb{R}_+$ would be positive reals. L or l normally stands for a loss unless it is a space which is then defined explicitly. $S \sim D$ means a sample from a distribution D; contextually, D can stand for a domain.
In general, we assume a finite or infinite countable domain. Given a hypotheses space H and domain Z, loss l is a non-negative real function $l : H \times Z \rightarrow \mathbb{R}_+$.

We denote $L_D(h)$ a standard expected loss of a binary classifier $h \in H$ over domain X where H is a hypotheses space, with respect to a probability distribution D; by definition: $L_D(h) = E_{z \sim D}[l_{0-1}(h, z)]$, and, since for 0-1 loss Z ranges over pairs,

$$l_{0-1}(h, (x, y)) = \left\{ \begin{array}{ll} 0 & \text{if} \quad h(x) = y \\ 1 & \text{if} \quad h(x) \neq y \end{array} \right. .$$

We also need some definition from model theory and logic. A filter α on the set of natural numbers N is a collection of sets of natural numbers obeying the following axioms:
1) If $E \subset F \subset \mathbb{N}$ and $E \in \alpha$ then $F \in \alpha$;
2) If $E \in \alpha$ and $F \in \alpha$ then $E \cap F \in \alpha$;
3) Empty set $\emptyset \notin \alpha$.

An ultrafilter α on the natural numbers is a filter which obeys an additional axiom:
If $E \subset \mathbb{N}$ then exactly one E or $\mathbb{N} \backslash E \in \alpha$.
A non-principal ultrafilter α is an ultrafilter that obeys one additional axiom yet:
4) No finite set belongs to α.

It easy to see that non-principal ultrafilters exist. We can start with the filter of cofinite (i.e. complements of finite sets in $\mathbb{N}$), and applying Zorn lemma [3] to embed the filter into an ultrafilter. We call an ultrafilter principal if it is not non-principal. One can prove that every non-principal ultrafilter is of the form $\{E \subset \mathbb{N} | n \in E\}$, where n is a natural number.
One fundamental property of binary classifier $\mu : 2^N \rightarrow \{0, 1\}$, if it maps σ-large sets to 1, and σ-small sets to 0, is that it is a finitely additive probability measure. Moreover, every finitely additive probability measure has this form.

We also are going to use an important tool from model theory that is called ultraproduct $\prod_{i \in I} L_i / U$ where L_i are some algebraic structures indexed by $i \in I$, and U is an ultrafilter.
Algebraic operations on the ultraproduct are defined the same way as in a Cartesian product of L_i and the ultraproduct is a quotient set with respect to relation $\diamond$ which is defined as follows: $x \diamond y$ iff

$\{i \in I | x_i = y_i\} \in U$.

Since we need some notions from lattice theory, we remind the fundamentals of it. Lattice is a partially ordered set in which any two elements have a supremum and an infimum. $Z_l, l \in \mathbb{N}$ is a lattice $(Z_l, \leq)$ if we set $a \wedge b = inf\{a, b\}$ and $a \vee b = sup\{a, b\}$.

Then Z_l is an algebra and a lattice. For a lattice L, we put $\uparrow a = \{b \in L | b \geq a\}$ and $\downarrow a = \{b \in L | b \leq a\}$.

If we fix the domain, then a multi-class classifier, as a structure, is defined (by the lattice isomorphism) by the ordered set of values in Z_l.
$L_D(A)$ denotes a standard 0-1 loss for a binary classifier A.

Finally, we need to touch decidability. Intuitively, it is the situation in first-order logic theory when we can find an effective algorithm that decides whether a well-defined formula for the theory is true (in particular, it does not loop indefinitely – the reason why halting problem is undecidable). The first-order logic is a natural setting for the context, because the second order (and, in general, a higher order) logic only leads to difficulties in any formalization or understanding of interpretability. The celebrated Gödel incompleteness theorem, for instance, deals with the second order formulas.

These definitions are sufficient for our purposes. We need only point out that these fundamental notions normally are essential for a non-standard analysis. However, we deal with a standard context herein and just use them in some proofs.

1.2 RANDOM GRAPH CLASSIFIERS

There is one interesting class of classifiers, similar in nature to binary classifiers, such that its first-order theory is almost for sure decidable (in the sense of probability). This class is associated with random graphs. We would call those the random (binary) classifiers.
The class is defined as follows. Assume that domain is enumerated (countable). Consider a graph with vertex set $\mathbb{N}$ of all natural numbers. Pick a "random" binary classifier A, that is the one that decides on every scoring randomly, with probability $\frac{1}{2}$. [1]. Let RG be the resulting structure.

To decide whether there is an edge between x and y (with $x \neq$ y), we check values $A(x)$ and $A(y)$. If they coincide, then, by definition, there is an edge, otherwise there isn't. Being viewed as a structure, the class of binary classifiers is a bounded lattice in case of a finite domain, and a left bounded lattice in case of infinite domain.
The class of all graphs built this way forms the class of random graphs. We show next that all these graphs are isomorphic (as graphs) with probability 1 (i.e., almost for sure). Namely, consider two disjoint finite subsets of N, X and Y, with respected sizes n and m. Consider now an element $x \in \mathbb{N}$ that is joined to every element of X and no element in Y; we would call that a property P. Given any vertex x, the probability it does not have the property P above is $p = 1 - 2^{-(n+m)}$. So, for m different vertices, the probability that none of them has the desired property is p^m. Clearly, this would converge to zero if n is going to infinity. Thus, at least one $x \in N$ will have the property, with probability 1. Taking into account the fact that there are only countably many disjoint pairs (X, Y) of finite sets in $\mathbb{N} \times \mathbb{N}$, with probability 1, for each pair (X, Y) we can find a vertex that x is joined to every vertex in X and to no vertex in Y. Let $\mathcal{P}$ be that property.

Denote the resulting structure by RG_{ext} defined by the property $\mathcal{P}$. Any binary classifier $C \equiv \langle D, L_c \rangle$ may be viewed as an element in RG where each element of the domain is represented by a pair of vertices in RG. Loss of the classifier C is defined accordingly and becomes a first-order expression in the theory $T \equiv L_{0Ext}$-theory where L_{0Ext} is the extension of basic logical language L_0 extended with the property $\mathcal{P}$.

---

[1]In fact, the very same proof works if, within the context, we assume a ratio $\frac{p}{q}$ where p and q are integer numbers such that $0 \leq \frac{p}{q} \leq 1$.

From that point, we can simply repeat the arguments from [2], Chapter IV.23, pp.645-646 and deduce that the first order theory of random graphs is almost surely decidable, so the first order logic theory of binary classifiers, associated with random graphs, is almost surely decidable too.

In particular, we can consider the extension RG_{ext} for RG with additional property that with probability 1, for every pair (A, B) of disjoint subsets in our domain, there is a vertex v such that v joined to every vertex in A and no vertex in B.

Q.E.D.

Namely, we have the following

Proposition 1.1. *The theory L_{0Ext} of random graph classifiers RG_{ext} is almost surely decidable.*

For completeness, we provide the proof based on an extension in the appendix.

2 MAIN RESULT

2.1 INEXPRESSIBILITY OF FAIRNESS

Let theory T be (as above) the L_{0Ext}-theory of binary classifiers based on structure RG_{ext}. Despite of the fact that the theory is almost surely decidable, once cannot use any first-order expression to compare two binary classifiers. Namely, the following theorem holds:

Theorem 2.1. *Two binary classifiers cannot be compared fairly using any first-order logic expression in T.*

Proof. Assume that the classifier loss is expressible in L_{0Ext}-first-order logic of T. By Marker's theorem for almost sure theory of graphs (e.g., cf. [2], p. 646), the theory T obeys a zero-one law which states that for any L_{0Ext}-sentence ϕ the probability $p_N(\phi)$ tends to zero or tends to 1 as $N \to \inf$. On the other hand, one can see that the probability that a random graph contains $r(\frac{N}{r})$ edges tends to $1/r$ as N tends to infinity for any integer $r > 1$.

Translating this to classifiers in RG_{Ext}, consider any non-trivial classifier. Its loss function then would tend to one or zero as we enumerate the elements of domain. Thus, we witness a contradiction with the fact that the limit is between zero and one. Q.E.D. □

3 UNDECIDABILITY

Theorem 3.1. *Given a domain D, the class of binary classifiers over D (viewed as lower bounded lattices) is (first-order logic) undecidable.*[2]

Proof.
The main idea is to show that the class is not closed under ultraproducts (or Cartesian products). Then, the class is not axiomatizable. As a consequence, being viewed as a structure, it is not decidable.
We first consider the case of finite domain. Strictly speaking, not every binary classifier, viewed as a structure, is a lattice. However, if it is, the immediate observation is that, up to a lattice isomorphism, such binary classifier is bounded. Namely, for a lattice L, $a \in L$ consider set $\uparrow (a) = \{b \in L | b \geq a\}$. A lattice homomorphism $h : M \to L$ is lower bounded if for any $a \in L$, set $h_{-1}(\uparrow (a))$ is either empty or has the least element. A lattice is lower bounded, if any homomorphism from a finitely generated free lattice is lower bounded. Dual definitions are established for the upper bounded lattices.

If lattice is lower and upper bounded, then it is called bounded. Any binary classifier is lower bounded as a lattice if it is representable as a lattice. It is obvious for finite classifiers, since we can view classifier as a lexicographically ordered sequence of pairs $(x_i, y_i), i \in N$ and thus it contains 0 (the

---

[2](Informally, there is no efficient algorithm that decides whether a well-formed formula in the first order logic theory of binary classifiers is true. Therefore, if we try to find an "interpretable" explanation for a phenomenon being explained by a model, then, in general, that explanation may not be possible to formulate in first order logic terms. One may argue that this reduce the very notion of interpretability to heuristics).

Figure 1: Finite Lattice Diagram representation

lowest bound) . Given a finite domain, it also contains 1; any homomorphism preserves 0s and 1s. For an infinite domain D, we assume it can be countably enumerated (thus, the order of the product $D \times D$ is lexicographical). Then, any classifier on such domain is lower bounded, since D, as a lattice, would contain 0.

Any finite lattice L can be identified as a binary classifier $l : L \times L \to \{0, 1\}$ that is associated with the lattice diagram in the following manner. The lattice is represented, up to isomorphism, by its diagram which is a directed graph $G = G(V, E)$ such that for every $v \in V \subset L$ there is no x such that $a > x > c$ for vertices a and c with edge $e(a, c)$ (covering property). The direction of the e is pointing towards a smaller element. Then we simply set classifier l value to 1 for the pair (a, c). If a pair (x, y) is not in the diagram, we set the value to zero. It is not difficult to check that the diagram can be restored from the classifier only one way (cf. figure 1 for the process, l(a,c) →1 and l(c,a) →0).

We need the following result from [6].

Theorem 3.2. *There are finite lower bounded lattices $L_i, i \in I$ for Cauchy filter D such that $\prod_{i \in I} L_i / D$ is not lower bounded.*

The theorem is stated there for just bounded lattices; however, it is valid for lower bounded lattices as well - for completeness, we present the proof in the appendix. To prove our result, theorem 3.1, we only need to notice that, according to the theorem 3.2, the product is a lattice, but it is no longer a binary classifier, that is, there are finite (lower bounded) binary classifiers such that their ultraproduct is not a binary classifier.

Q.E.D.

4 CONCLUSION

An elementary class (or axiomatizable class) consists of all structures satisfying a fixed first-order theory. There are a few limitations of expressiveness of elementary classes. Theorem 3.1 seems to be a reason to move to the second-order logic; however, with higher expressiveness, and some inheritance of the first-order logic properties, there are important negative effects, associated with completeness and compactness theorems.

Discussion One may ask a natural question whether the second-order and higher order logic is more suitable for the modeling the machine learning tasks for formalization of fairness, because the first-order logic has quantifiers' scope "reduced" to elements, rather than sets. Clearly, binary classification task is only useful tool if we can verify the model at the individual level (e.g., the target "malignant/non-malignant" tumor in medicine). Moreover, we would like our formalism be as simple as possible, that is, our expression of boolean target shall refer to individual prediction rather than subset of those, because the problem of defining and selecting the subsets is likely (and, logically, will be) more complex than our task in the first place, at least, for majority of practical problems. By the same token, interpretability requires its scope to be at the individual elements.

In addition, one important consideration is due to formal verification. Many modern verifiers and theorem provers use a higher order logic since they are employ type theory. However, the verification and proving are yet other research domains.

REFERENCES

[1] Richardson, D. (1968) Some unsolvable problems involving elementary functions of a real variable. *Journal of Symbolic Logic* **33**:514-520.

[2] Gowers, T. & Barrow-Green, J. & Leader, I. (2008) *Princeton Companion to Mathematics.* Princeton and Oxford.

[3] Wagner, C. & Strohmaier, M. & Olteanu, A. & Kiciman, I. & Contractor, N. & Eliassi-Rad, T. (2021) Measuring algorithmically infused societies. *Nature* **595**:197-204.

[4] Ben-David, S. & Hrubes, P. & Moran, S. & Shpilka, A. & Yehudayoff, A. (2019) Learnability Can Be Undecidable. *Nature Machine Intelligence* **1**(1):44.

[5] Sehra, S. & Flores, D. & Montanez, G.D. (2021) Undecidability of Underfitting in Learning Algorithms. In *The 2nd International Conference on Computing and Data Science (CONF-CDS 2021).*

[6] Schwidefsky, M.V. (2016) The class of bounded lattices is not axiomatizable. *Algebra and Logic*, **55**(4):327-330.

A APPENDIX

A.1 PROOF OF PROPOSITION 1.1

Theorem A.1. RG_{ext} *is almost surely decidable.*

Proof. This is a completion of the proof sketched in the main text. We aim to construct an extension for the first-order theory such that it is almost for sure decidable. In the main text, we proved that, with probability 1, there is a countably many disjoint pairs (X, Y) of finite sets, for every such pair one can find $x \in X$ that is joined to every vertex in X and to no vertex in B. That extension property formalization is as follows:

(i) $\forall x \forall y \quad x \sim y \rightarrow y \sim x$;
(ii) $\forall x \quad \neg(x \sim x)$;
(iii) $\Phi_{n,m}$ for $n, m \geq 0$

where $\Phi_{n,m}$ is the formula:

$$\forall x_1 ... x_n \quad \forall y_1 ... y_m \wedge_{i=1}^n \wedge_{j=1}^m x_i \neq y_j \rightarrow \exists z((\wedge_{i=1}^n x_i \sim z) \wedge (\wedge_{i=1}^m \neg(y_i \sim z))).$$

Consider the theory T for graph with the extension property (i)-(iii) holds for any pair of disjoint finite set of vertices. By the argumentation above in the main text, with probability 1, random classifiers are models of T.

Moreover, any two countable models of T are isomorphic. The isomorphism can be constructed as follows. Induction. Given model M_1 and M_2, and enumerations $a_0, a_1, ...$ of vertices in M_1 and $b_0, b_1, ...$ of vertices in M_2, let set $f(a_0) = b_0$. For a_1, if a_1 is joined to a_0, find a vertex that is joined to b_0, and in similar way, if not. These are property $\Phi_{1,0}$ and $\Phi_{0,1}$ correspondingly. Selecting alternatively an image for the first a_i that does not yet have an image, and preimage for the first b_j that does not yet have preimage, and a regular case of $\Phi_{i,j}$, we continue by induction.

The theory T is complete. Moreover, there is an algorithm that decides whether any formula or its negation are true in very model of T. That is a simple corollary from the previous considerations. To prove completeness, assume that the opposite is true. Then, by compactness theorem, there are two countable models M_1, M_2 such that a formula is true in M_1, but its negation is true in M_2. This would mean that there are two non-isomorphic models of T which is not the case. Similarly, to prove that there is a deciding algorithm for T, for any formula, one would search the proofs for it or its negation. By completeness theorem (Gödel, Henkin), syntactic and semantic consequence are equivalent for first-order logic, so we will find eventually a proof for the formula or its negation.

To prove almost for sure decidability for random graphs, we only need to notice that T provides the proof for a formula ϕ or its negation. The proofs are finite, so the proof can use only finitely many statements $\Phi_{n,m}$. Thus, there exists $m \in \mathbb{N}$ such that if $M \models \Phi_{m,m}$, then $M \models \phi$. As we saw before, the probability of $M \models \Phi_{m,m}$ tends to 1 when $m \rightarrow 0$, so is the probability of $M \models \phi$. This means that the first order theory of random graphs is almost surely decidable.
Q.E.D.

$\square$

A.2 PROOF OF THEOREM 3.2

Proof.

That statement is the main result of [6]. Following the very construction of [6], we need only to build an ascending chain of elements in the free lattice that its image under natural embedding saves the order of elements.

Next, given a domain, we can identify classifier with an embedding into an inverse limit of finite bounded lattices. More specifically, let X will be a finite set with at least free elements (that is not a real restriction for binary classifier case, because logically multinomial classifier can be split into a sequence of binary ones), and let $F(X)$ be a free lattice generated by X. It is known [8] that $F(X)$ embeds into an inverse limit of finite bounded lattices.

Specifically, there are finite bounded lattices, $L_i, i < \omega$, and surjective lattice homomorphisms $\pi_{ij} : L_j \to L_i, i \leq j < \omega$ such that $\pi_{ii} = Id_{L_i}$ and $\pi_{ik} = \pi_{ij}\pi_{jk}$ for all $i \leq j \leq k < \omega$, and an embedding $\phi : F(X) \to \prod_{i<\omega} L_i$ for which $\pi_i\phi = \pi_{ij}\pi_j\phi$ with any $i \leq j < \omega$ where $\pi_k : \prod_{i<\omega} L_i \to L_k$ is the canonical projection for any $n < \omega$.

Fix a filter Φ over ω, e.g., the filter of all cofinite subsets of ω. Then the map $\xi : F(X) \to \prod_{i<\omega} L_i/\Phi; \xi : a \to \phi(a)/\Phi$ is a lattice homomorphism, by definition. In fact, it is a lattice embedding. Namely, suppose $a \neq b$ in $F(X)$, then we have $\pi_i\phi(a) \neq \pi_i\phi(b)$ for some $i < \omega$. For the inverse limit, it means that $\pi_n\phi(a) \neq \pi_n\phi(b)$ for all $n \geq i$. Immediately, $\xi(a)/\Phi \neq \xi(b)/\Phi$.

Next, consider $t \in F(X)$ and an ascending chain $\{a_i, i < \omega\}$ in $F(X)$. Then $\{\pi_n\phi(a_n)|n < \omega\}/\Phi \leq \xi(t)$ if and only if $a_n \leq t$ for all $n < \omega$.

We will prove now that homomorphism ξ is not lower bounded. It is known (cf. [8], Example 1.24, Whitman) that $F(X)$ contains an infinite ascending chain $\{a_n|n < \omega\}$ which does not have a least upper bound.

Consider $\overline{a} = (\pi_n\phi(a_n)|n < \omega)/\Phi$. Since $1_{F(X)} \in \xi^{-1}(\uparrow \overline{a})$, it follows that the last set is non-empty. Therefore, if we choose an arbitrary element t from the set, we have $\xi(t) \geq \uparrow \overline{a}$. As we saw before, it means we have $t \geq a_n$ for all $n \leq \omega$. Since t is not a least upper bound for the sequence $\{a_n|n < \omega\}$, there exists t_1 such that $t > t_1 \geq a_n$ for all $n < \omega$. As usual, it means that $\xi(t_1) \geq \uparrow \overline{a}$ and thus $t_1 \in \xi^{-1}(\uparrow \overline{a})$. Hence the set $\xi^{-1}(\uparrow \overline{a})$ does not have a least element, i.e., ξ is not lower bounded.

Q.E.D.

One variation of the proof for binary classifiers is based on the following consideration. For finite and countably infinite domains, binary classifier is a distributive lattice over N if we set $\{a \vee b, a \wedge b\} = \{a, b\} \quad \forall a, b$. As is known, for very partial set (poset) C there exists a unique, up to isomorphism, free completed distributed lattice L over C with embedding $\phi : C \to L$ such that for every distributed lattice M, and a monotone function $f : C \to M$ there exists a unique homomorphism f_ϕ that the following diagram is commutative:

$$
\begin{array}{ccc}
C & \xrightarrow{\varphi} & L \\
{\scriptstyle f}\downarrow & & \downarrow{\scriptstyle f_\phi} \\
M & \xrightarrow{id} & M
\end{array}
$$

This allows us to uniquely identify a classifier (as a distributive lattice) with a free distributed lattice embedding; more precisely, with its image under the embedding ϕ. Since L is a free lattice generated by C, it, in turn, embeds into inverse limit of free finite bounded lattices [8].

Next, it is sufficient to prove that there are finite lower bounded lattices the embedding above, that are identified as binary classifiers, that for a non-principal ultrafilter D (e.g. ω), the ultraproduct $\prod_{i \in I} L_i/D$ is not lower bounded.

Then, we can find an infinite chain in the embedding directly, and the rest of the proof is as above.

A.3   FORMAL DEFINITION FOR LANGUAGE L

Let L be a language (an extension of a basic formal logical language, L_0).

Definition   The set of $L-$terms is the smallest set L_t such that contains all constant symbols of L, all variables, and if $t_1, t_2, ..., t_n$ are in L_t then for any n-ary function symbol f, $f(t_1, t_2, ..., t_n)$ is also in L_t. Set L_a of atomic formulas are represented by the properties:
(1) if t_1 and t_2 are terms then $t_1 = t_2$ is in L_a, and
(2) the corresponding n-ary function symbols are also in L_a.

In other words, the set of all formulas in L (expressions, sentences - herein, we use these interchangeably) is the smallest set containing all atomic formulas and closed under logical connectives $\vee$, $\wedge$, $\neg$, $\to$, $\leftrightarrow$, quantifiers $\exists$, $\forall$, equality symbol " $=$ ", parenthesis "(" and ")", and variables.