Intrinsic Control of Variational Beliefs in Dynamic Partially-Observed Visual Environments

Abstract

Humans and animals explore their environment and acquire useful skills even in the absence of clear goals, exhibiting intrinsic motivation. The study of intrinsic motivation in artificial agents is concerned with the following question: what is a good general-purpose objective for an agent? We study this question in dynamic partially-observed environments, and argue that a compact and general learning objective is to minimize the entropy of the agent's state visitation estimated using a latent state-space model. This objective induces an agent to both gather information about its environment, corresponding to reducing uncertainty, and to gain control over its environment, corresponding to reducing the unpredictability of future world states. We instantiate this approach as a deep reinforcement learning agent equipped with a deep variational Bayes filter. We find that our agent learns to discover, represent, and exercise control of dynamic objects in a variety of partially-observed environments sensed with visual observations without extrinsic reward.

1 Introduction

Reinforcement learning offers a framework for learning control policies that maximize a given measure of reward – ideally, rewards that incentivize simple high-level goals, such as survival, accumulating a particular resource, or accomplishing some long-term objective. However, extrinsic rewards may be insufficiently informative to encourage an agent to explore and understand its environment, particularly when the environment is *partially-observed*: when the agent has a limited view of its environment. A generalist agent should instead acquire an understanding of its environment before a specific objective or reward is provided. This goal motivates the study of *self-supervised / unsupervised* reinforcement learning: algorithms that provide the agent with an intrinsically-grounded drive to acquire understanding and control of its environment in the absence of an extrinsic reward signal. Agents trained with intrinsic reward signals might accomplish tasks specified via simple and sparse rewards more quickly, or may acquire broadly useful skills that could be adapted to specific task objectives. Our aim is to design an embodied agent and a general-purpose intrinsic reward signal that leads to the agent controlling partially-observed environments when equipped only with a high-dimensional sensor (camera) and no prior knowledge.

A large body of prior methods for self-supervised reinforcement learning focus on attaining *coverage*, typically through novelty-seeking or skill-discovery objectives; see Hafner et al. [25] for a survey. As argued in prior work [18, 16, 14, 6], a compelling alternative to coverage suited to complex and dynamic environments is to minimize surprise, which incentivizes an agent to control aspects of its environment to achieve homeostasis within it – i.e. constructing and maintaining a niche where it can reliably remain despite external perturbations. We generally expect agents that succeed at minimizing surprise in complex environments to develop similarly complex behaviors; such acquired complex behaviors may be repurposed for other tasks [6]. However, these frameworks do not explicitly address

Figure 1: *Top row:* The environment consists of a large number of objects, some of which (e.g., the goat) move and act in unpredictable ways, and are not observed unless the agent is nearby. *Bottom row:* If the agent maintains a latent state space model of the world, it has uncertain beliefs about unobserved objects, particularly those that are dynamic (like the goat). If the agent reduces the long-horizon average entropy of its beliefs, it will first seek out information (e.g., finding the goat), and then modify the environment to limit the range of states the goat can occupy *even when it is no longer observed*, for example by building a fence around it.

the difficulty of controlling partially-observed environments: if an otherwise complex and chaotic environment contains a "dark room" (small reliable niche), an agent could minimize surprise simply by hiding in this room and refusing to make meaningful observations, thereby failing to explore and control the wider surrounding environment.

Consider Fig. 1, which depicts a partially-observed outdoor environment with various flora (trees, vegetables, and grass), fauna (a goat), weather, and an agent. We will discuss three different intrinsic incentives an agent might adopt in this environment. If the agent's incentive is to (*i*) minimize the entropy of its next observation, it will seek the regions with minimal unpredictable variations in flora, fauna, and weather. This is unsatisfying because it merely requires avoidance, rather than interaction. Let us assume the agent will maintain a model of its *belief* about a learned *latent state* – the agent cannot observe the *true* state, instead it learns a state representation. Further, let us assume the agent maintains a separate model of the visitation of its latent state – we will refer to this distribution as its *latent visitation*. If the agent's incentive is to (*ii*) minimize the entropy of belief (either at every step or at some final step), the agent will gather information and take actions to make the environment predictable: find and observe the changes in flora, fauna, and weather that are predictable and avoid those that aren't. However, once it has taken actions to make the world predictable, this agent is agnostic to future change – it will not resist predictable changes in the environment. Finally, if the agent's incentive is to (*iii*) minimize the entropy of its latent visitation, this will result in categorically different behavior: the agent will seek both to make the world predictable by gathering information about it and *prevent it from changing*. While both the belief and latent visitation entropy minimization objectives are worthwhile intrinsic motivation objectives to study, we speculate that an agent that is adept at preventing its environment from changing will generally learn more complex behaviors.

We present a concise and effective objective for self-supervised reinforcement learning in dynamic partially-observed environments: minimize the entropy of the agent's latent visitation under a latent state-space model learned from exploration. Our method, which we call Believer, results in an agent that learns to seek out and control factors of variation outside of its immediate observations. We instantiate this framework by simultaneously learning a state-space model as a Deep Variational Bayes Filter along with a policy that employs the model's beliefs. Our experiments show that our method learns to represent and control dynamic entities in partially-observed visual environments with *no extrinsic reward signal*, including in several 3D environments.

2   Maxwell's Demon and Belief Entropy

The main concept behind our approach to self-supervised reinforcement learning is that incentivizing an agent to minimize the entropy of its *beliefs* about the world is sufficient to lead it to *both* gather information about the world *and* learn to control aspects of its world. Our approach is partly inspired by a well-known connection between information theory and thermodynamics, which can be illustrated informally by a version of the Maxwell's Demon thought experiment [47, 42]. Imagine a container separated into compartments, as shown in Fig. 2. Both compartments contain gas molecules that bounce off of the walls and each other in a somewhat unpredictable fashion, though short-term

motion of these molecules (between collisions) is predictable. The compartments are separated by a massless door, and the agent (the eponymous "demon") can open or close the door at will to sort the particles.[1] By sorting the particles onto one side, the demon appears to reduce the disorder of the system, as measured by the thermodynamic entropy, S, which increases the energy, F available to do work, as per Helmholtz's free energy relationship, $F = U - TS$. The ability to do work affords the agent *control over the environment*. This apparent violation of the second law of thermodynamics is resolved by accounting for the agent's information processing needed to make decisions [5]. By concentrating the particles into a smaller region, the number of states each particle visits is reduced. Therefore, this illustrates an example environment in which reducing the entropy of the visitation distribution results in an agent gaining the ability to do work. In the same way that Maxwell's demon accumulates free energy via information-gathering and manipulating of its environment, we would expect self-supervised agents guided by belief entropy minimization to accumulate the equivalent of potential energy in their corresponding sequential decision processes, which would lead them to gain control over their environment.

Figure 2: A "demon" gathering information to sort particles, reducing the entropy of the particle configuration.

3 Preliminaries

Our goal in this work will be to design self-supervised reinforcement learning methods in partially observed settings, which can acquire complex behaviors that both gather information and gain control over their environment. To this end, we will formulate the learning problem in the context of a discrete-time partially-observed controlled Markov process, also known as a controlled hidden Markov process (CHMP), which corresponds to a POMDP without a reward function. The CHMP is defined by a state space $\mathcal{S}$ with states $\mathbf{s} \in \mathcal{S}$, action space $\mathcal{A}$ with actions $\mathbf{a} \in \mathcal{A}$, transition dynamics $P(\mathbf{s}_{t+1}|\mathbf{s}_t, \mathbf{a}_t)$, observation space Ω with observations $\mathbf{o} \in \Omega$, and emission distribution $O(\mathbf{o}_t|\mathbf{s}_t)$. The agent is a policy $\pi(\mathbf{a}_t|\mathbf{o}_{\leq t})$. Note that it does *not* observe any states $\mathbf{s}$.

We denote the undiscounted finite-horizon state visitation as $d^\pi(\mathbf{s}) \doteq 1/T \sum_{t=0}^{T-1} \Pr_\pi(\mathbf{s}_t = \mathbf{s})$, where $\Pr_\pi(\mathbf{s}_t = \mathbf{s})$ is the probability that $\mathbf{s}_t = \mathbf{s}$ after executing π for t steps. Using $d^\pi(\mathbf{s})$, we can quantify the average *disorder* of the environment with the Shannon entropy, $H(d^\pi(\mathbf{s}))$. Prior work proposes observational surprise minimization ($\min_\pi - \log \hat{p}(\mathbf{o})$) as an intrinsic control objective [15, 71, 6]; in Berseth et al. [6] (SMiRL), the agent models the state visitation distribution, $d^\pi(\mathbf{s})$ with $\hat{p}(\mathbf{s})$, which it computes by assuming access to $\mathbf{s}$. In environments in which there are natural sources of variation outside of the agent, this incentivizes the SMiRL agent, fully aware of these variations observed through $\mathbf{s}$, to take action to control them. In a partially-observed setting, SMIRL's model becomes $\hat{p}(\mathbf{o})$, which generally will enable the agent to ignore variations that it can prevent from appearing in its observations. We observe this phenomenon in our experiments.

4 Control and Information Gathering via Belief Entropy Minimization

The main question that we tackle in the design of our algorithm is: how can we formulate a general and concise objective function that can enable an RL agent to gain control over its partially-observed environment, in the absence of any user-provided task reward? Consider the following partially-observed "TwoRoom" environment, depicted in Fig. 3. The environment has two rooms: an empty ("dark") room on the left, and a "busy" room on the right, the latter containing two moving particles that move around until the agent "tags" them, which stops their motion. Intuitively, an agent that aims to gather information and gain control of its environment should search for the moving particles to find out where they are. However, it is difficult to observe both particles at the same time. A more effective strategy is to "tag" the particles – then, their position remains fixed, and the agent will know where they are at all times, even when they are not observed. This task can be seen as a simple

---

[1]In Maxwell's original example, the demon sorts the particles into the two chambers based on velocity. Our example is closely related to Szilard's engine [69, 46].

Time

Figure 3: Comparison of several approaches on the TwoRoom environment. The agent, in white, can view a limited area around it, in grey, and can stop particles within its view and darken their color. The vertical wall, in brown, separates particles (blue and green) in the "busy room" (on right) from the "dark room" (on left). *Top:* Our approach seeks out the particles and stops them. *Middle:* The observational surprise minimization method in Berseth et al. [6] leads the agent to frequently hide in the dark room, leaving the particles unstopped. *Bottom:* Latent-state infogain leads the agent to find and observe the particles, but not stop them.

125 analogy for more complex settings that can occur in natural environments, where we might want
126 agents to arrange an environment in an orderly fashion. We can view this task as a rough analogy for
127 a version of the previously-discussed Maxwell's Demon thought experiment.

128 **Representing variability with latent state-space models.** In order for the agent to represent the
129 dynamic components of the environment observed from images, our method involves learning a latent
130 state-space model (LSSM) [73, 39, 30, 45, 22, 48, 74, 72, 41, 10, 23, 49, 59]. We intermittently refer
131 to these dynamic components as "factors of variation" to distinguish the model's representation of
132 variability in the environment (latent state) from the true variability (true state). At timestep t, the
133 LSSM represents the agent's current *belief* as $q_\phi(\mathbf{z}_t|\mathbf{o}_{\leq t}, \mathbf{a}_{\leq t-1})$, where $\mathbf{z}_t$ is the model's latent state.
134 We defer the description of the LSSM learning and architecture to Section 5, and now motivate how
135 we will use the LSSM for constructing an intrinsic control objective.

136 **Belief entropy and latent visitation entropy.** Consider a policy that takes actions to minimize the
137 entropy of the belief $H(q_\phi(\mathbf{z}_t|\mathbf{o}_{\leq t}, \mathbf{a}_{\leq t-1}))$. This corresponds to the agent performing *active state es-*
138 *timation* [12, 75, 38], and is equivalent to taking actions to maximize expected latent-state information
139 gain $I(\mathbf{o}_t, \mathbf{z}_t|\mathbf{o}_{<t}, \mathbf{a}_t)$ [2]. However, active state estimation is satisfied by a policy that simply collects
140 informative observations, as it does not further incentivize actions to "stabilize" the environment
141 by preventing the latent state from changing. Analogous to the standard definition of undiscounted
142 state visitation, consider the undiscounted latent visitation: $d^\pi(\mathbf{z}) \doteq {}^1/_T \sum_{t=0}^{T-1} \Pr_\pi(\mathbf{z}_t = \mathbf{z})$, where
143 $\Pr_\pi(\mathbf{z}_t = \mathbf{z}) = \mathbb{E}_\pi q_\phi(\mathbf{z}_t|\mathbf{o}_{\leq t}, \mathbf{a}_{\leq t-1})$ (the expected belief after executing π for t timesteps). Our
144 goal is to minimize $H(d^\pi(\mathbf{z}))$, as this corresponds to *stabilizing the agent's beliefs*, which incentivizes
145 both reducing uncertainty in each $q_\phi(\mathbf{z}_t|\mathbf{o}_{\leq t}, \mathbf{a}_{\leq t-1})$, as well as constructing a niche such that each
146 $q_\phi(\mathbf{z}_t|\mathbf{o}_{\leq t}, \mathbf{a}_{\leq t-1})$ concentrates probability on the same latent states.

147 **Discovering factors of variation.** In order for belief entropy minimization to incentivize the agent
148 to control entities in the environment, the LSSM's belief must represent the underlying state variables
149 in some way and model their uncertain evolution until either observed or controlled. For example,
150 the demon in the thought experiment in Section 2 would have no incentive to gather the particles if it
151 did not know that they existed. While sufficient random exploration may result in a good-enough
152 LSSM, making this approach generally practical requires a suitable exploration strategy to collect
153 the experience necessary to train an LSSM that represents all of the underlying factors of variation.
154 To this end, we learn a separate exploratory policy to maximize *expected model information gain*,
155 similar to Schmidhuber [61], Houthooft et al. [27], Gheshlaghi Azar et al. [20], Sekar et al. [63].
156 Expected information gain about model parameters $\boldsymbol{\theta}$ is relative to a set of prior experience $\mathcal{D}$ and
157 a partial trajectory $\mathbf{h}_{t-1}$, given as $I(\mathbf{o}_t; \boldsymbol{\theta}|\mathbf{h}_{t-1}, \mathcal{D}) = \mathbb{E}_{\mathbf{o}_t} \text{KL}(p(\boldsymbol{\theta}|\mathbf{o}_t, \mathbf{h}_{t-1}, \mathcal{D}) \| p(\boldsymbol{\theta}|\mathbf{h}_{t-1}, \mathcal{D}))$.
158 Note that model information gain is *distinct* from the information an agent may gather to reduce
159 its belief entropy $H(q_\phi(\mathbf{z}_t|\mathbf{o}_{\leq t}, \mathbf{a}_{\leq t-1}))$ within the current episode. Computing the full model
160 parameter prior $p(\boldsymbol{\theta}|\mathbf{h}_{t-1}, \mathcal{D})$ and posterior $p(\boldsymbol{\theta}|\mathbf{o}_t, \mathbf{h}_{t-1}, \mathcal{D})$ is generally computationally expensive,
161 and also requires evaluating an expectation over observations – instead, we approximate this expected
162 information gain following a method similar to Sekar et al. [63]: we use an ensemble of latent
163 dynamics models, $\mathcal{E} = \{p_{\theta_i}(\mathbf{z}_t|\mathbf{z}_{t-1}, \mathbf{a}_{t-1})\}_{i=1}^K$ to compute the variance of latent states estimated by
164 $q_\phi(\mathbf{z}_t|\mathbf{o}_{\leq t}, \mathbf{a}_{\leq t-1})$. We build the ensemble throughout training using the method of Izmailov et al.
165 [28]. Thus, the exploration reward is given as: $r_e = \text{Var}_{\{\theta_i\}}[\log p_\theta(\mathbf{z}_t|\mathbf{z}_{t-1}, \mathbf{a}_{t-1})|\mathbf{z}_t \sim q_\phi]..$

(a) Latent state-space and visitation models.   (b) Intrinsic rewards.

Figure 4: Figure of latent-state space model and rewards. *Left:* The model observes images, $\mathbf{o}_t$ to inform beliefs about latent states, $q_\phi(\mathbf{z}_t|\mathbf{o}_{\leq t}, \mathbf{a}_{\leq t-1})$, and observes actions to make one-step predictions $p(\mathbf{z}_{t+1}|\mathbf{z}_t, \mathbf{a}_t)$. Each belief is used to update the latent visitation, $\bar{q}_{t'}(\mathbf{z})$. *Right:* The beliefs and latent visitations can be combined into various reward functions. The solid arrows denote directions of belief expansion and contraction incentivized by rewards; the dotted arrows denote directions of belief translation incentivized by rewards.

5 The Believer Algorithm

Now we describe how we implement and combine the various components of our method into a learning algorithm for minimizing belief visitation entropy in CHMPs (reward-less POMDPs). The main components are the latent-state space model, the latent visitation model, and the exploration and control policies.

Latent state-space model.   In our CHMP setting, the agent only has access to partial observations $\mathbf{o}$ of the true state $\mathbf{s}$. In order to estimate a representation of states and beliefs, we employ a sequence-based Variational Autoencoder to learn latent variable belief, dynamics, and emission models. We formulate the variational posterior to be $q_\phi(\mathbf{z}_{1:T}|\mathbf{o}_{1:T}, \mathbf{a}_{1:T}) = \prod_{t=1}^T q_\phi(\mathbf{z}_t|\mathbf{o}_{\leq t}, \mathbf{a}_{\leq t-1})$ and the generative model as $p(\mathbf{z}_{1:T}, \mathbf{o}_{1:T}|\mathbf{a}_{1:T}) = \prod_{t=1}^T p_\theta(\mathbf{o}_t|\mathbf{z}_t)p_\theta(\mathbf{z}_t|\mathbf{z}_{t-1}, \mathbf{a}_{t-1})$. Denoting $\mathbf{h}_t \doteq (\mathbf{o}_{\leq t}, \mathbf{a}_{\leq t-1})$, the log-evidence of the model and its lower-bound are:

$$\log\ p(\mathbf{o}_{1:T}|\mathbf{a}_{1:T-1}) = \log \mathbb{E}_{\mathbf{z}_{1:T} \sim p(\mathbf{z}_{1:T}|\mathbf{a}_{1:T})}\left[\prod_{t=1}^T \log p(\mathbf{o}_t|\mathbf{z}_t)\right]$$

$$\geq \mathcal{L}(\phi, \theta) = \sum_{t=1}^T \mathbb{E}_{q_\phi(\mathbf{z}_t|\mathbf{h}_t)}\left[p_\theta(\mathbf{o}_t|\mathbf{z}_t)\right] - \mathbb{E}_{q_\phi(\mathbf{z}_{t-1}|\mathbf{h}_{t-1})}\left[\mathrm{KL}(q_\phi(\mathbf{z}_t|\mathbf{h}_t)\ ||\ p_\theta(\mathbf{z}_t|\mathbf{z}_{t-1}, \mathbf{a}_{t-1})\right] \quad (1)$$

Given a dataset $\mathcal{D} = \{(\mathbf{o}_{1:T}, \mathbf{a}_{1:T})_i\}_{i=1}^N$, Eq. 1 is used to train the model via $\max_{\phi,\theta} \mathbb{E}_{U(\mathcal{D})}\mathcal{L}(\phi, \theta)$. The focus of our work is not to further develop the performance of LSSMs; our method could be further improved with advances in the particular LSSM employed. In practice, we implemented an LSSM in PyTorch [56] similar to the categorical LSSM architecture described in [24]. In this case, both the belief prior and belief posterior are distributions formed from products of K_1 categorical distributions over K_2 categories: $g(\mathbf{z}; \mathbf{v}) = \prod_{\kappa_1=1}^{K_1} \prod_{\kappa_2=1}^{K_2} \mathbf{v}_{\kappa_1,\kappa_2}^{\mathbf{z}_{\kappa_1,\kappa_2}}$, where the vector of $K_1 \cdot K_2$ parameters, $\mathbf{v}$, is predicted by neural networks: $\mathbf{v}_{\mathrm{posterior}} = \bar{f}_\phi(\mathbf{o}_{\leq t}, \mathbf{a}_t)$ for the posterior, and $\mathbf{v}_{\mathrm{prior}} = f_\theta(\mathbf{o}_{<t}, \mathbf{a}_t)$ for the prior. We found it effective to construct $\bar{f}_\phi$ and f_θ following the distribution-sharing decomposition described in [30, 31, 10], in which the posterior is produced by transforming the parameters of the prior with a measurement update. We implemented the prior as an RNN, and the posterior as an MLP, and defer further details to the supplementary material.

Latent visitation model.   Our agent cannot, in general, evaluate $d^\pi(\mathbf{z})$ or $H(d^\pi(\mathbf{z}))$; at best, it can approximate them. We do so by maintaining a within-episode estimate of $d^\pi(\mathbf{z})$ by constructing a mixture across the belief history samples $\bar{q}_{t'}(\mathbf{z}) = 1/t' \sum_{t=0}^{t'} q_\phi(\mathbf{z}_t|\mathbf{o}_{\leq t}, \mathbf{a}_{\leq t-1})$. This corresponds to a mixture (across time) of single-sample estimates of each $\mathbb{E}_\pi q_\phi(\mathbf{z}_t|\mathbf{o}_{\leq t}, \mathbf{a}_{\leq t-1})$. Given $\bar{q}_{t'}(\mathbf{z})$, we

have an estimate of the visitation of the policy, and we can use this as part or all of the reward signal of the agent. To implement $\bar{q}_{t'}(\mathbf{z})$, we experimented both approximating it by averaging each $\mathbf{v}$ and with recording every belief, and found that simply recording each belief sufficed.

5.1 Belief-based objectives

We now describe several rewards that can be constructed with the LSSM, and how they connect to our main objective. In what follows, we denote $q_\phi(\mathbf{z}_t|\mathbf{o}_{\leq t}, \mathbf{a}_{\leq t-1}) = q_t(\mathbf{z}_t)$ for brevity. While our primary objective is "niche creation" by minimizing the expected surprise of the latent visitation model, we also explore other intrinsic objectives that can be computed in terms of the LSSM and the latent visitation model. These rewards are visualized in Fig. 4.

Certainty. The entropy of the current belief measures the agent's certainty of the latent state, and by extension, about the aspects of the environment captured by the latent. Minimizing the belief entropy increases the agent's certainty. It is agnostic to predictable changes, and penalizes unpredictable changes. We define the *certainty reward* as the negative belief entropy:

$$r_t^c \doteq -\mathrm{H}(q_t(\mathbf{z}_t)) = \mathbb{E}_{q_t(\mathbf{z}_t)}[\log q_t(\mathbf{z}_t)] \tag{2}$$

Niche Creation: Our primary objective is the expected surprise of the latent visitation distribution, which measures how many states the agent believes it could have been in during the episode so far. Minimizing this reduces the number of visited environment states and increases the agent's certainty. We define the *niche creation reward* as the negative cross entropy of the visitation under the belief:

$$r_t^{nc} \doteq -\mathrm{H}(q_t(\mathbf{z}_t), \bar{q}_{t'}(\mathbf{z})) = \mathbb{E}_{q_t(\mathbf{z}_t)}[\log \bar{q}_{t'}(\mathbf{z})]. \tag{3}$$

Niche Expansion. Instead of minimizing the latent visitation entropy altogether, we can add an entropy bonus for the current belief to encourage exploration and thus potentially find a broader niche. The results in bringing the current belief towards the current latent visitation distribution. We define the *niche expansion reward* as the negative KL divergence:

$$r_t^{ne} \doteq -\mathrm{KL}(q_t(\mathbf{z}_t)||\bar{q}_{t'}(\mathbf{z})) = \mathbb{E}_{q_t(\mathbf{z}_t)}[\log \bar{q}_{t'}(\mathbf{z}) - \log q_t(\mathbf{z}_t)]. \tag{4}$$

State Infogain. The latent state information gain (not to be confused with the model information gain described in Section 4) measures how much more certain the belief is compared to its temporal prior. Gaining information does not always coincide with being certain, because an infogain agent may cause chaotic events in the environment with outcomes that it only understands partially. As a result, it has gained more information than standing still but has also become less certain. We define the *infogain reward* as the KL divergence:

$$r_t^i \doteq \mathrm{KL}(q_t(\mathbf{z}_t)||p(\mathbf{z}_t|\mathbf{z}_{t-1}, \mathbf{a}_{t-1})) = \mathbb{E}_{q_t(\mathbf{z}_t)q_{t-1}(\mathbf{z}_{t-1})}[\log q_t(\mathbf{z}_t) - \log p(\mathbf{z}_t|\mathbf{z}_{t-1}, \mathbf{a}_{t-1})]. \tag{5}$$

5.2 Algorithm summary

Conceptual pseudocode for our method is presented in Alg. 1. The algorithm begins by initializing the LSSM, q_ϕ and p_θ, as well as two separate policies: one trained to collect difficult-to-predict data with the exploration objective with rewards defined by r_e, π_e, and one trained to maximize one of the intrinsic control objectives as defined by Eqs. (2) to (5).

We represent each policy $\pi(\mathbf{a}_t|\mathbf{v}_{\mathrm{posterior},t})$ as a two-layer fully-connected MLP with 128 units. Recall that $\mathbf{v}_{\mathrm{posterior}}$ is the vector of posterior parameters, which enables the policy to use the memory represented by the LSSM. We do not back-propagate the policies' losses to the LSSM for simplicity of implementation, although prior work does so in the case of a single policy [41]. Our method is agnostic to the subroutine used to improve the policies. In our implementation, we employ PPO [62].

6 Experiments

Our experiments are designed to answer the following questions: **Q1: Intrinsic control capability**: Does our latent visitation-based self-supervised reward signal cause the agent to stabilize partially-observed visual environments with dynamic entities more effectively than prior self-supervised stabilization objectives? **Q2: Properties of Believer objectives**: What types of emergent behaviors does each belief-based objective described in Section 5.1 evoke?

In order to answer these questions, we identified environments with the following properties **(i):** partial observability, **(ii):** dynamic entities that the agent can affect, and **(iii):** high-dimensional observations.

Algorithm 1 Believer

1: **procedure** BELIEVER(Env; K, M, N, L)
2:   Initialize $\pi_c, \pi_e, q_\phi, p_{\{\theta_i\}_{i=1}^K}, \mathcal{D} \leftarrow \emptyset$.
3:   **for** episode $= 0, \ldots, M$ **do**
4:     $\mathcal{D}_e \leftarrow \text{Collect}(N, \text{Env}, \pi_e); \mathcal{D}_c \leftarrow \text{Collect}(N, \text{Env}, \pi_c); \mathcal{D} \leftarrow \mathcal{D} \cup \mathcal{D}_e \cup \mathcal{D}_c$
5:     `// LSSM fitting step.`
6:     Update q_ϕ, p_θ using SGD on Eq. 1 with $\mathcal{D}$ for L rounds.
7:     Update π_e using SGD on PPO's objective with rewards r_e
8:     `// Intrinsic control optimization step.`
9:     Update π_c using SGD on PPO's objective with rewards defined by one of Eqs. (2) to (5)

Because many standard RL benchmarks do not contain the significant partial-observability that is prevalent in the real world, it is challenging to answer these questions with them. Instead, we create several environments, and employ several existing environments we identified to have these properties. In what follows, we give an overview of the experimental settings and conclusions. We defer comprehensive details to the supplementary material.

6.1 Environments

TwoRoom. As previously described, this environment has two rooms: an empty ("dark") room on the left, and a "busy" room on the right, the latter containing moving particles that move around unless the agent "tags" them, which permanently stops their motion, as shown in Fig. 5. The agent can observe a small area around it, which it receives as an image. In this environment, control corresponds to finding and stopping the particles. The action space is $\mathcal{A} = \{$left, right, up, down, tag, no-op$\}$, and the observation space is normalized RGB-images: $\Omega = [0,1]^{3 \times 30 \times 30}$. An agent that has significant control over this environment should tag particles to reduce the uncertainty over future states. To evaluate policies, we use the average fraction of total particles locked, the average fraction of particles visible, and the discrete true-state visitation entropy of the positions of the particles, $H(d^\pi(s_d))$. We employed two versions of this environment, with details provided in the supplementary material. In the large environment, the agent observes a 5x5 area around it as an image, and the busy room contains 5 particles.

Figure 5: TwoRoom Large Environment.

VizDoom DefendTheCenter. The VizDoom DefendTheCenter environment shown in Fig. 6 is a circular arena in which a stationary agent, equipped with a partial field-of-view of the arena and a weapon, can rotate and shoot encroaching monsters [32]. The action space is $\mathcal{A} = \{$turn left, turn right, shoot$\}$, and the observation space is normalized RGB-images: $\Omega = [0,1]^{3 \times 64 \times 64}$. In this environment, control corresponds to reducing the number of monsters by finding and shooting them. We use the average original environment return, (for which *no policy* has access to during training), the average number of killed monsters at the end of an episode, and the average number of visible monsters to measure the agent's control.

Figure 6: Vizdoom Defend The Center.

OneRoomCapture3D The MiniWorld framework is a customizable 3D environment simulator in which an agent perceives the world through a perspective camera [9]. We used this framework to build the environment in Fig. 7 which an agent and a bouncing box both inhabit a large room; the agent can lock the box to stop it from moving if it is nearby, as well as constrain the motion of the box by standing nearby it. In this environment, control corresponds to finding the box and either trapping it near a wall, or tagging it. The action space is $\mathcal{A} = \{$turn left 20°, turn right 20°, move forward, move backward, tag$\}$, and observation space is normalized RGB-images: $\Omega = [0,1]^{3 \times 64 \times 64}$. We use the average fraction of time the box is captured, the average time the box is visible, and continuous (Gaussian-estimated) true-state visitation entropy of the box's position $H(d^\pi(s_d))$ to measure the agent's ability to reduce entropy of the environment.

Figure 7: One Room Capture 3D.

Figure 8: Visualization of a sequence in the VizDoom DefendTheLine environment. *Row 1:* The image provided to the agent. *Row 2:* The agent's reconstruction of a sample from q. *Row 3:* The agent's one-step image forecast. *Right:* The state infogain signal, $\mathbb{E}_q[\log q - \log p]$. Each colored rectangle identifies a keyframe that corresponds to a colored circle on the infogain plot. The infogain signal measures how much more certain the belief is compared to its temporal prior; when stochastic events happen (monster appears nearby), the signal is high; when the next image is predictable (monster disappears when shot), the signal is low.

Method	TwoRoom Environment			OneRoomCapture3D Environment		
	Obj. Lock↑	Obj. Visible↑	$H(d^\pi(s_d))\downarrow$	Obj. Captured↑	Obj. Visible↑	$H(d^\pi(s_d))\downarrow$
Niche Creation+Infogain	$0.92_{\pm0.01}$	$\mathbf{0.94}_{\pm0.01}$	$0.33_{\pm0.03}$	$\mathbf{0.84}_{\pm0.08}$	$\mathbf{0.88}_{\pm0.02}$	$-0.06_{\pm0.16}$
Niche Expansion, Eq. (4)	$\mathbf{0.95}_{\pm0.00}$	$0.66_{\pm0.03}$	$\mathbf{0.22}_{\pm0.02}$	$0.73_{\pm0.03}$	$0.67_{\pm0.04}$	$\mathbf{-0.96}_{\pm0.21}$
Niche Creation, Eq. (3)	$0.50_{\pm0.05}$	$0.46_{\pm0.05}$	$1.06_{\pm0.09}$	$0.39_{\pm0.04}$	$0.01_{\pm0.00}$	$1.15_{\pm0.16}$
Certainty, Eq. (2)	$0.06_{\pm0.02}$	$0.01_{\pm0.00}$	$1.86_{\pm0.04}$	$0.29_{\pm0.04}$	$0.16_{\pm0.03}$	$0.66_{\pm0.24}$
Infogain, Eq. (5)	$0.00_{\pm0.00}$	$0.55_{\pm0.00}$	$1.95_{\pm0.02}$	$0.57_{\pm0.03}$	$0.54_{\pm0.04}$	$0.97_{\pm0.14}$
SMiRL [6]	$0.25_{\pm0.04}$	$0.27_{\pm0.03}$	$1.52_{\pm0.06}$	$0.46_{\pm0.04}$	$0.20_{\pm0.02}$	$-0.02_{\pm0.28}$
Empowerment [78]	$0.00_{\pm0.00}$	$0.46_{\pm0.03}$	$1.95_{\pm0.03}$	$0.49_{\pm0.04}$	$0.22_{\pm0.02}$	$0.21_{\pm0.25}$
Random policy	$0.61_{\pm0.03}$	$0.28_{\pm0.01}$	$1.19_{\pm0.06}$	$0.54_{\pm0.03}$	$0.16_{\pm0.01}$	$0.12_{\pm0.22}$
Oracle lock policy	$0.98_{\pm0.00}$	$0.91_{\pm0.01}$	$0.13_{\pm0.01}$	$0.95_{\pm0.00}$	$0.96_{\pm0.00}$	$-2.58_{\pm0.23}$

Table 1: Policy evaluation in TwoRoom and OneRoomCapture3D. Means and their standard errors are reported; grey shading denotes a variant of our method, bolding denotes where a method achieves the best mean performance under a metric. We observe that the Niche Expansion and Niche Creation+Infogain objectives lead the agent to seek out and stabilize the dynamic objects substantially more effectively than other methods.

6.2 Comparisons

In order to answer **Q1**, we compare to SMiRL [6] and a recent empowerment method [78] that estimates the current empowerment of the agent from an image. We use the empowerment estimate as a reward signal for training a policy. In order to answer **Q2**, we ensured each environment was instrumented with the aforementioned metrics of visibility and control, and deployed Algorithm 1 separately with each of Eqs. (2) to (5), as well a with simple sum of Eq. (3) and Eq. (5). Finally, we compare to a "random policy" that chooses actions by sampling from a uniform distribution over the action space, as well as an "oracle policy" that has access to privileged information about the environment state in each environment. We perform evaluation at $5e6$ environment steps with 50 policy rollouts per random seed, with 3 random seeds for each method (150 rollouts total).

Our primary results are presented in Tables 1 and 2. We observe the Niche Creation+Infogain and Niche Expansion rewards to yield policies that exhibit a high degree of control over each environment – finding and stopping the moving objects, and finding and shooting the monsters, in the *complete absence of any extrinsic reward signal*. The Infogain-based agent generally seeks out and observes, but does not interfere with, the dynamic objects; the high Visibility metric and low control metrics (Lock, Capture, Kill) in each environment illustrates this. Qualitative results of this phenomenon are illustrated in Fig. 8, in which the infogain signal is high when stochastically-moving monsters are visible, and low when they are not. We observe that in these partially observed environments the method of Berseth et al. [6] tends to learn policies that hide from the dynamic objects in the environment, as indicated by the low control and visibility values of the final policy. Furthermore, we observe the method of Zhao et al. [78] not to exhibit controlling behavior in these partially-observed environments, instead it views the dynamic objects in the TwoRoom and OneRoomCapture3D Environments somewhat more frequently than the random policy. We present videos of all policies in the supplementary material.

7 Related Work

Much of the previous work on learning without extrinsic rewards has been based either on (i) exploration [8, 54, 53], or (ii) some notion of intrinsic control, such as empowerment [35, 50, 31].

Exploration approaches include those that maximize model prediction error or improvement [60, 44, 66, 57], maximize model uncertainty [27, 67, 65, 58, 20], maximize state visitation [4, 19, 70, 26], maximize surprise [60, 1, 68], and employ other novelty-based exploration bonuses [43, 7, 33, 34]. Our method can be combined with prior exploration techniques to aid in optimizing our proposed objective, and in that sense our work is largely orthogonal to prior exploration methods.

Prior works on intrinsic control include empowerment maximization [35, 36, 51], observational surprise minimization [15, 17, 71, 6, 55], and skill discovery [3, 37, 21, 11, 64, 76]. Observational surprise minimization seeks policies that make *observations* predictable and controllable, and is closely connected to entropy minimization, as entropy is defined to be the expected surprise. In Friston et al. [18], the notion of Free Energy Minimization corresponds to minimizing *observational* entropy, and states that the entropy of hidden states in the environment is bounded by the entropy of sensory observations. However, the proof assumes a diffeomorphism to hold between states and observations, which is explicitly violated in CHMPs and any real-world set-

Method	DefendTheCenter Environment		
	Env. Return↑	Monster Kills↑	Visible↑
Niche Creation+Infogain	$1964.4_{\pm 05.42}$	$0.00_{\pm 0.00}$	$\mathbf{1.16}_{\pm 0.005}$
Niche Expansion, Eq. (4)	$\mathbf{2506.4}_{\pm 36.26}$	$\mathbf{28.2}_{\pm 1.50}$	$0.94_{\pm 0.015}$
Niche Creation, Eq. (3)	$2182.2_{\pm 14.12}$	$10.0_{\pm 0.55}$	$0.76_{\pm 0.017}$
Certainty, Eq. (2)	$1958.0_{\pm 35.63}$	$07.2_{\pm 0.73}$	$0.92_{\pm 0.028}$
Infogain, Eq. (5)	$1928.6_{\pm 35.51}$	$00.2_{\pm 00.2}$	$1.15_{\pm 0.008}$
SMiRL [6]	$1918.7_{\pm 53.80}$	$7.58_{\pm 0.15}$	$0.89_{\pm 0.009}$
Empowerment [78]	$2161.8_{\pm 29.06}$	$16.2_{\pm 2.35}$	$0.86_{\pm 0.064}$
Random policy	$2113.8_{\pm 37.60}$	$14.2_{\pm 0.73}$	$0.90_{\pm 0.026}$
Oracle policy	$2550.8_{\pm 55.90}$	$28.0_{\pm 1.52}$	$0.80_{\pm 0.035}$
	TwoRoom-Large Environment		
	Obj. Lock↑	Obj. Visible↑	$H(d^\pi(s_d))\downarrow$
Niche Creation+Infogain	$\mathbf{0.665}_{\pm 0.013}$	$\mathbf{0.501}_{\pm 0.013}$	$\mathbf{2.831}_{\pm 0.083}$
SMiRL [6]	$0.110_{\pm 0.020}$	$0.087_{\pm 0.016}$	$3.417_{\pm 0.022}$
Random policy	$0.271_{\pm 0.024}$	$0.138_{\pm 0.011}$	$3.404_{\pm 0.063}$
Oracle policy	$0.885_{\pm 0.005}$	$0.464_{\pm 0.017}$	$1.016_{\pm 0.043}$

Table 2: Policy evaluation in VizDoom and TwoRoom-Large. Means and their standard errors are reported; grey shading denotes a variant of our method, bolding denotes where a method achieves the best mean performance under a metric. We observe that the Niche Expansion objective in VizDoom and Niche Creation+Infogain objective in TwoRoom-Large lead the agent to seek out and stabilize the dynamic objects substantially more effectively than other methods.

ting, as agents cannot perceive the state of anything outside their egocentric sensory observations. Similarly, empowerment [36, 29, 31, 78] is a measure of the degree of control an agent has over future *observations*, whereas state visitation entropy is a measure of the degree of the control over the *underlying environment state*. Our approach seeks to infer and gain control over a representation of the environment's state, as opposed to the agent's observations. We demonstrate environments where minimizing observational surprise and maximizing empowerment leads to degenerate solutions that ignore important factors of variation, whereas our approach identifies and controls them.

Representation learning methods have been explored in a variety of prior work, including, but not limited to, [40, 73, 30, 13, 52, 77, 22, 41]. Our approach employs a representation learning method to build a latent state-space model [73, 39, 30, 22, 48, 74, 72, 41, 10, 23, 49, 59].

8 Discussion

We presented a method, Believer, for intrinsically motivating an agent to discover, represent, and exercise control of dynamic objects in a partially-observed environments sensed with visual observations. We found that our method approached expert-level performance on several environments and substantially surpassed prior work in its unsupervised control capability. While our experiments represent a proof-of-concept that illustrates how latent state belief entropy minimization can incentivize an agent to both gather information and gain control over its environment, there are a number of exciting future directions. First, our method is inspired by a connection between thermodynamics and information theory, but the treatment of this connection is informal. Formalizing this connection could lead to an improved theoretical understanding of how Believer and other intrinsic motivation methods can lead to desirable behavior, and perhaps allow deriving conditions on environments under which such desirable behaviors would emerge. Second, Believer and other surprise-minimizing intrinsic motivation objectives are designed to work well in complex environments with unpredictable phenomena: a particularly interesting direction for future work is to scale up such methods in order to study the behavior that emerges.

References

[1] J. Achiam and S. Sastry. Surprise-based intrinsic motivation for deep reinforcement learning. *arXiv preprint arXiv:1703.01732*, 2017.

[2] E. H. Aoki, A. Bagchi, P. Mandal, and Y. Boers. A theoretical look at information-driven sensor management criteria. In *14th International Conference on Information Fusion*, pages 1–8. IEEE, 2011.

[3] A. G. Barto, S. Singh, and N. Chentanez. Intrinsically motivated learning of hierarchical collections of skills. In *Proceedings of the 3rd International Conference on Development and Learning*, pages 112–19. Piscataway, NJ, 2004.

[4] M. Bellemare, S. Srinivasan, G. Ostrovski, T. Schaul, D. Saxton, and R. Munos. Unifying count-based exploration and intrinsic motivation. In *Advances in Neural Information Processing Systems*, pages 1471–1479, 2016.

[5] C. H. Bennett. The thermodynamics of computation—a review. *International Journal of Theoretical Physics*, 21(12):905–940, 1982.

[6] G. Berseth, D. Geng, C. M. Devin, N. Rhinehart, C. Finn, D. Jayaraman, and S. Levine. {SM}irl: Surprise minimizing reinforcement learning in unstable environments. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=cPZOyoDloxl.

[7] Y. Burda, H. Edwards, D. Pathak, A. Storkey, T. Darrell, and A. A. Efros. Large-Scale Study of Curiosity-Driven Learning. 2018. URL http://arxiv.org/abs/1808.04355.

[8] N. Chentanez, A. G. Barto, and S. P. Singh. Intrinsically motivated reinforcement learning. In *Advances in neural information processing systems*, pages 1281–1288, 2005.

[9] M. Chevalier-Boisvert. gym-miniworld environment for openai gym. https://github.com/maximecb/gym-miniworld, 2018.

[10] N. Das, M. Karl, P. Becker-Ehmck, and P. van der Smagt. Beta dvbf: Learning state-space models for control from high dimensional observations. *arXiv preprint arXiv:1911.00756*, 2019.

[11] B. Eysenbach, A. Gupta, J. Ibarz, and S. Levine. Diversity is all you need: Learning skills without a reward function. *arXiv preprint arXiv:1802.06070*, 2018.

[12] H. J. S. Feder, J. J. Leonard, and C. M. Smith. Adaptive mobile robot navigation and mapping. *The International Journal of Robotics Research*, 18(7):650–668, 1999.

[13] C. Finn, X. Y. Tan, Y. Duan, T. Darrell, S. Levine, and P. Abbeel. Deep spatial autoencoders for visuomotor learning. In *2016 IEEE International Conference on Robotics and Automation (ICRA)*, pages 512–519. IEEE, 2016.

[14] Z. Fountas, N. Sajid, P. A. Mediano, and K. Friston. Deep active inference agents using monte-carlo methods. *arXiv preprint arXiv:2006.04176*, 2020.

[15] K. Friston. The free-energy principle: a rough guide to the brain? *Trends in cognitive sciences*, 13(7):293–301, 2009.

[16] K. Friston. Life as we know it. *Journal of the Royal Society Interface*, 10(86):20130475, 2013.

[17] K. J. Friston, J. Daunizeau, and S. J. Kiebel. Reinforcement learning or active inference? *PLOS ONE*, 4(7):1–13, 07 2009. doi: 10.1371/journal.pone.0006421. URL https://doi.org/10.1371/journal.pone.0006421.

[18] K. J. Friston, J. Daunizeau, J. Kilner, and S. J. Kiebel. Action and behavior: a free-energy formulation. *Biological cybernetics*, 102(3):227–260, 2010.

[19] J. Fu, J. Co-Reyes, and S. Levine. Ex2: Exploration with exemplar models for deep reinforcement learning. In *Advances in neural information processing systems*, pages 2577–2587, 2017.

[20] M. Gheshlaghi Azar, B. Piot, B. Avila Pires, J.-B. Grill, F. Altché, and R. Munos. World discovery models. *arXiv e-prints*, pages arXiv–1902, 2019.

[21] K. Gregor, D. J. Rezende, and D. Wierstra. Variational intrinsic control. *arXiv preprint arXiv:1611.07507*, 2016.

[22] D. Hafner, T. Lillicrap, I. Fischer, R. Villegas, D. Ha, H. Lee, and J. Davidson. Learning latent dynamics for planning from pixels. *arXiv preprint arXiv:1811.04551*, 2018.

[23] D. Hafner, T. Lillicrap, J. Ba, and M. Norouzi. Dream to control: Learning behaviors by latent imagination. *arXiv preprint arXiv:1912.01603*, 2019.

[24] D. Hafner, T. Lillicrap, M. Norouzi, and J. Ba. Mastering atari with discrete world models. *arXiv preprint arXiv:2010.02193*, 2020.

[25] D. Hafner, P. A. Ortega, J. Ba, T. Parr, K. Friston, and N. Heess. Action and perception as divergence minimization. *arXiv preprint arXiv:2009.01791*, 2020.

[26] E. Hazan, S. Kakade, K. Singh, and A. Van Soest. Provably efficient maximum entropy exploration. In *International Conference on Machine Learning*, pages 2681–2691. PMLR, 2019.

[27] R. Houthooft, X. Chen, Y. Duan, J. Schulman, F. De Turck, and P. Abbeel. VIME: Variational Information Maximizing Exploration. 2016. URL http://arxiv.org/abs/1605.09674.

[28] P. Izmailov, D. Podoprikhin, T. Garipov, D. Vetrov, and A. G. Wilson. Averaging weights leads to wider optima and better generalization. *arXiv preprint arXiv:1803.05407*, 2018.

[29] M. Karl, J. Bayer, and P. van der Smagt. Efficient empowerment. *arXiv preprint arXiv:1509.08455*, 2015.

[30] M. Karl, M. Soelch, J. Bayer, and P. van der Smagt. Deep variational bayes filters: Unsupervised learning of state space models from raw data. *arXiv preprint arXiv:1605.06432*, 2016.

[31] M. Karl, M. Soelch, P. Becker-Ehmck, D. Benbouzid, P. van der Smagt, and J. Bayer. Unsupervised real-time control through variational empowerment. *arXiv preprint arXiv:1710.05101*, 2017.

[32] M. Kempka, M. Wydmuch, G. Runc, J. Toczek, and W. Jaśkowski. Vizdoom: A doom-based ai research platform for visual reinforcement learning. In *2016 IEEE Conference on Computational Intelligence and Games (CIG)*, pages 1–8. IEEE, 2016.

[33] H. Kim, J. Kim, Y. Jeong, S. Levine, and H. O. Song. Emi: Exploration with mutual information. *arXiv preprint arXiv:1810.01176*, 2018.

[34] Y. Kim, W. Nam, H. Kim, J.-H. Kim, and G. Kim. Curiosity-bottleneck: Exploration by distilling task-specific novelty. In *International Conference on Machine Learning*, pages 3379–3388, 2019.

[35] A. S. Klyubin, D. Polani, and C. L. Nehaniv. All else being equal be empowered. In M. S. Capcarrère, A. A. Freitas, P. J. Bentley, C. G. Johnson, and J. Timmis, editors, *Advances in Artificial Life*, pages 744–753, Berlin, Heidelberg, 2005. Springer Berlin Heidelberg. ISBN 978-3-540-31816-3.

[36] A. S. Klyubin, D. Polani, and C. L. Nehaniv. Empowerment: A universal agent-centric measure of control. In *2005 IEEE Congress on Evolutionary Computation*, volume 1, pages 128–135. IEEE, 2005.

[37] G. Konidaris and A. G. Barto. Skill discovery in continuous reinforcement learning domains using skill chaining. In *Advances in neural information processing systems*, pages 1015–1023, 2009.

[38] C. Kreucher, K. Kastella, and A. O. Hero Iii. Sensor management using an active sensing approach. *Signal Processing*, 85(3):607–624, 2005.

[39] R. G. Krishnan, U. Shalit, and D. Sontag. Deep kalman filters. *arXiv preprint arXiv:1511.05121*, 2015.

[40] S. Lange and M. Riedmiller. Deep auto-encoder neural networks in reinforcement learning. In *The 2010 International Joint Conference on Neural Networks (IJCNN)*, pages 1–8. IEEE, 2010.

[41] A. X. Lee, A. Nagabandi, P. Abbeel, and S. Levine. Stochastic latent actor-critic: Deep reinforcement learning with a latent variable model. *arXiv preprint arXiv:1907.00953*, 2019.

[42] H. S. Leff and A. F. Rex. *Maxwell's demon: entropy, information, computing*. Princeton University Press, 2014.

[43] J. Lehman and K. O. Stanley. Abandoning objectives: Evolution through the search for novelty alone. *Evolutionary computation*, 19(2):189–223, 2011.

[44] M. Lopes, T. Lang, M. Toussaint, and P.-Y. Oudeyer. Exploration in model-based reinforcement learning by empirically estimating learning progress. In *Advances in neural information processing systems*, pages 206–214, 2012.

[45] C. J. Maddison, D. Lawson, G. Tucker, N. Heess, M. Norouzi, A. Mnih, A. Doucet, and Y. W. Teh. Filtering variational objectives. *arXiv preprint arXiv:1705.09279*, 2017.

[46] M. Magnasco. Szilard's heat engine. *EPL (Europhysics Letters)*, 33(8):583, 1996.

[47] J. C. Maxwell and P. Pesic. *Theory of heat*. Courier Corporation, 2001.

[48] A. Mirchev, B. Kayalibay, M. Soelch, P. van der Smagt, and J. Bayer. Approximate bayesian inference in spatial environments. *arXiv preprint arXiv:1805.07206*, 2018.

[49] A. Mirchev, B. Kayalibay, P. van der Smagt, and J. Bayer. Variational state-space models for localisation and dense 3d mapping in 6 dof. *arXiv preprint arXiv:2006.10178*, 2020.

[50] S. Mohamed and D. Jimenez Rezende. Variational information maximisation for intrinsically motivated reinforcement learning. In C. Cortes, N. D. Lawrence, D. D. Lee, M. Sugiyama, and R. Garnett, editors, *Advances in Neural Information Processing Systems 28*, pages 2125–2133. Curran Associates, Inc., 2015.

[51] S. Mohamed and D. J. Rezende. Variational information maximisation for intrinsically motivated reinforcement learning. In *Advances in neural information processing systems*, pages 2125–2133, 2015.

[52] A. V. Nair, V. Pong, M. Dalal, S. Bahl, S. Lin, and S. Levine. Visual reinforcement learning with imagined goals. In *Advances in Neural Information Processing Systems*, pages 9191–9200, 2018.

[53] P.-Y. Oudeyer and F. Kaplan. What is intrinsic motivation? a typology of computational approaches. *Frontiers in neurorobotics*, 1:6, 2009.

[54] P.-Y. Oudeyer, F. Kaplan, and V. V. Hafner. Intrinsic motivation systems for autonomous mental development. *IEEE transactions on evolutionary computation*, 11(2):265–286, 2007.

[55] T. Parr and K. J. Friston. Generalised free energy and active inference. *Biological Cybernetics*, 113(5):495–513, Dec 2019. ISSN 1432-0770. doi: 10.1007/s00422-019-00805-w. URL https://doi.org/10.1007/s00422-019-00805-w.

[56] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *arXiv preprint arXiv:1912.01703*, 2019.

[57] D. Pathak, P. Agrawal, A. A. Efros, and T. Darrell. Curiosity-driven Exploration by Self-supervised Prediction. 2017.

[58] D. Pathak, D. Gandhi, and A. Gupta. Self-Supervised Exploration via Disagreement. 2019.

[59] R. Rafailov, T. Yu, A. Rajeswaran, and C. Finn. Offline reinforcement learning from images with latent space models. *Learning for Decision Making and Control (L4DC)*, 2021.

[60] J. Schmidhuber. Curious model-building control systems. In *Proc. international joint conference on neural networks*, pages 1458–1463, 1991.

[61] J. Schmidhuber. Formal theory of creativity, fun, and intrinsic motivation (1990–2010). *IEEE Transactions on Autonomous Mental Development*, 2(3):230–247, 2010.

[62] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[63] R. Sekar, O. Rybkin, K. Daniilidis, P. Abbeel, D. Hafner, and D. Pathak. Planning to explore via self-supervised world models. In *International Conference on Machine Learning*, pages 8583–8592. PMLR, 2020.

[64] A. Sharma, S. Gu, S. Levine, V. Kumar, and K. Hausman. Dynamics-aware unsupervised discovery of skills. *arXiv preprint arXiv:1907.01657*, 2019.

[65] P. Shyam, W. Jaśkowski, and F. Gomez. Model-based active exploration. *arXiv preprint arXiv:1810.12162*, 2018.

[66] B. C. Stadie, S. Levine, and P. Abbeel. Incentivizing exploration in reinforcement learning with deep predictive models. *arXiv preprint arXiv:1507.00814*, 2015.

[67] S. Still and D. Precup. An information-theoretic approach to curiosity-driven reinforcement learning. *Theory in Biosciences*, 131(3):139–148, 2012.

[68] Y. Sun, F. Gomez, and J. Schmidhuber. Planning to be surprised: Optimal bayesian exploration in dynamic environments. In *International Conference on Artificial General Intelligence*, pages 41–51. Springer, 2011.

[69] L. Szilard. Über die entropieverminderung in einem thermodynamischen system bei eingriffen intelligenter wesen. *Zeitschrift für Physik*, 53(11):840–856, 1929.

[70] H. Tang, R. Houthooft, D. Foote, A. Stooke, O. X. Chen, Y. Duan, J. Schulman, F. DeTurck, and P. Abbeel. # exploration: A study of count-based exploration for deep reinforcement learning. In *Advances in neural information processing systems*, pages 2753–2762, 2017.

[71] K. Ueltzhöffer. Deep active inference. *Biological Cybernetics*, 112(6):547–573, 2018.

[72] G. Vezzani, A. Gupta, L. Natale, and P. Abbeel. Learning latent state representation for speeding up exploration. *arXiv preprint arXiv:1905.12621*, 2019.

[73] M. Watter, J. T. Springenberg, J. Boedecker, and M. Riedmiller. Embed to control: A locally linear latent dynamics model for control from raw images. *arXiv preprint arXiv:1506.07365*, 2015.

[74] G. Wayne, C.-C. Hung, D. Amos, M. Mirza, A. Ahuja, A. Grabska-Barwinska, J. Rae, P. Mirowski, J. Z. Leibo, A. Santoro, et al. Unsupervised predictive memory in a goal-directed agent. *arXiv preprint arXiv:1803.10760*, 2018.

[75] J. L. Williams. *Information Theoretic Sensor Management*. PhD thesis, Massachusetts Institute of Technology, 2007.

[76] K. Xu, S. Verma, C. Finn, and S. Levine. Continual learning of control primitives: Skill discovery via reset-games. *arXiv preprint arXiv:2011.05286*, 2020.

[77] M. Zhang, S. Vikram, L. Smith, P. Abbeel, M. J. Johnson, and S. Levine. Solar: Deep structured latent representations for model-based reinforcement learning. *arXiv preprint arXiv:1808.09105*, 2018.

[78] R. Zhao, K. Lu, P. Abbeel, and S. Tiomkin. Efficient empowerment estimation for unsupervised stabilization. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=u2YNJPcQlwq.