# ISOTROPIC CONTEXTUAL REPRESENTATIONS THROUGH VARIATIONAL REGULARIZATION

## ABSTRACT

Contextual language representations achieve state-of-the-art performance across various natural language processing tasks. However, these representations have been shown to suffer from the degeneration problem, i.e. they occupy a narrow cone in the latent space. This problem can be addressed by enforcing isotropy in the latent space. In analogy to variational autoencoders, we suggest applying a token-level variational loss to a Transformer architecture and and optimize the prior distribution's standard deviations as model parameter to increase isotropy. The encoder-decoder architecture allows for learning interpretable embeddings that can be decoded into text again. Extracted features at sentence-level achieve competitive results on benchmark classification tasks, even with a significantly smaller model size.

## 1 INTRODUCTION

Current state-of-the-art models for natural language processing tasks are self-supervised language models based on the Transformer (Vaswani et al., 2017) architecture such as BERT (Devlin et al., 2019) or GPT (Radford et al., 2019). These language models are pretrained on large datasets in an unsupervised manner and subsequently fine-tuned on the target data. The resulting token representations are distributed embeddings and highly contextual (Ethayarajh, 2019). Additional structural properties in the latent space, such as isotropy, are not explicitly enforced. On the contrary, Ethayarajh (2019) have shown that overall, the representations in all layers of these models are anisotropic, i.e. populating only a narrow subspace. This phenomenon is known as representation degeneration (Gao et al., 2019). Cai et al. (2021), though, detect isotropy within clusters of representations.

The performance of contextual representations on target tasks can be improved, if the latent representations overall are isotropic, i.e. distributed across the latent space instead of populating a narrow cone (Ethayarajh, 2019): Gao et al. (2019) improve the performance of a Transformer-based model with increased isotropy by directly optimizing the cosine distance between the latent representations. Wang et al. (2020) suggest to control the singular value distribution of the output representation matrix and Li et al. (2020a) transform the original representation distribution into a Gaussian distribution through normalizing flows to increase the isotropy of the underlying models.

Similar to Gao et al. (2019), we propose to apply a regularizing constraint during training to enforce an isotropic and, even more, complete latent space. A common regularization network is the so-called Variational Autoencoder (VAE) (Kingma & Welling, 2014). VAE networks consist of an encoder that maps given input data not to a point in latent space but a distribution. A VAE's decoder is required to successfully reconstruct the original input from samples of the latent distribution. Thus, the VAE is optimized to reconstruct the given input sequence whilst enforcing the latent distributions to match a given prior distribution.

We propose a Variational Auto-Transformer (VAT), a VAE based on a Transformer architecture, where the variational loss is computed at token level. We show that by enforcing a Gaussian distribution as latent prior, the latent token-level representations become more isotropic in comparison to models such as BERT or GPT. We introduce the prior distribution's standard deviation as model parameter to optimize isotropy and balance the language generation variety against the network's reconstruction ability. Another effect of the VAE is the completeness of the latent space, meaning that every point in latent space can be mapped back, i.e. decoded, to a textual representation. This

allows for text generation through "variational sampling" and other manipulations such as interpolation directly in latent space. While the token-level representations can be used to generate or manipulate text, we also show that sentence-level representations, e.g. obtained through averaging, are suitable for sentence classification tasks.

## 2 BACKGROUND

An autoencoder is a neural network architecture consisting of an encoder $enc$, that maps any input $\boldsymbol{x}$ to a point $\boldsymbol{z}$ in latent space, and a decoder $dec$, such that $\boldsymbol{x} \approx dec(enc(\boldsymbol{x}))$ (Goodfellow et al., 2016). The chosen network architecture defines the families $E$ and $D$ of the encoder and decoder. During training of the autoencoder, the network parameters are optimized to find the optimal $(enc^*, dec^*)$ pair that minimizes a given loss function $L$:

$$(enc^*, dec^*) = \underset{(enc,dec) \in E \times D}{\arg\min} (L) \tag{1}$$

For the standard autoencoder, a reconstruction loss $L = L_{REC}$ is applied:

$$L_{REC} = \|\boldsymbol{x} - dec(enc(\boldsymbol{x}))\| \tag{2}$$

Over-complete autoencoder architectures with many degrees of freedom are prone to a particular form of overfitting: The encoder maps each data point $\boldsymbol{x}$ to an isolated point $\boldsymbol{z}$ in the latent space such that the decoder memorizes the lossless reconstruction of each of these codes. This highly discrete latent space lacks completeness and is of limited use for advanced NLP applications.

### 2.1 VARIATIONAL AUTOENCODER

The variational autoencoder (VAE) (Kingma & Welling, 2014) can be thought of as generative autoencoder. A VAE encodes an input data point as a distribution over the latent space by adding a regularization term to the loss function. The regularization term assesses the Kulback-Leibler divergence between the latent distribution and a standard Gaussian based on their means $\boldsymbol{\mu}$ and covariances $\Sigma$:

$$L_{REG} = -D_{KL}\left[N(\boldsymbol{\mu}, \Sigma), N(\boldsymbol{0}, I)\right] \tag{3}$$

$\boldsymbol{\mu}$ and $\Sigma$ are either estimated using standard point estimators from the encoder outputs, or computed by learned functions such that $\boldsymbol{\mu} = g(\boldsymbol{x})$ and $\Sigma = h(\boldsymbol{x})$ with $g \in G$ and $h \in H$, where $G$ and $H$ are families of network architectures. $G$ and $H$ can contribute to the desired properties of the latent representation by implicitly implementing dimensionality reduction or feature disentangling.

Decoding from the latent representation requires sampling from $\boldsymbol{z} \sim N(\boldsymbol{\mu}, \Sigma)$. In order to enable backpropagation despite this sampling operation, Kingma and Welling (Kingma & Welling, 2014) introduced the reparameterization trick: Instead of sampling from the latent distribution, a random sample $\boldsymbol{\epsilon} \sim N(\boldsymbol{0}, I)$ from a standard Gaussian is drawn and then transformed by the computed mean and covariance $\boldsymbol{z} = \Sigma \cdot \boldsymbol{\epsilon} + \boldsymbol{\mu}$.

The VAE's total loss is the sum of the regularization and reconstruction term:

$$
\begin{aligned}
(enc^*, dec^*) &= \underset{(enc,dec) \in E \times D}{\arg\min} \left(L_{REC} + L_{REG}\right) \\
&= \underset{(enc,dec) \in E \times D}{\arg\min} \left(\|\boldsymbol{x} - dec(\boldsymbol{z})\| - D_{KL}\left[N(\boldsymbol{\mu}, \Sigma), N(\boldsymbol{0}, I)\right]\right)
\end{aligned} \tag{4}
$$

## 3 RELATED WORK

Adding a variational loss to a language model serving as underlying autoencoder has previously been suggested with different model architectures: Gururangan et al. (2019) use MLPs as encoder and

Figure 1: The proposed Variational Auto-Transformer architecture: Mean and covariance for the variational loss (blue, dashed lines) are computed through two independent linear layers. The encoder and decoder (grey, solid lines) architecture is the same as in the original Transformer.

decoder to learn latent vectors from bag-of-words inputs that are used for document classification tasks. Miao et al. (2016) rely on MLPs in a VAE for both document modeling and answer selection. Bowman et al. (2016) apply the variational loss on the last hidden state of a LSTM sequence-to-sequence model and Zhao et al. (2018) use a LSTM-based VAE for dialog generation. Deudon (2018) implements a siamese network architecture based on sentence representations from a VAE with Bi-LSTMs to learn semantic similarity.

Recently, the Transformer architecture has been used in a VAE setting as well: Liu & Liu (2019) add a feed-forward layer to map the encoder outputs to a mean and variance vector which are then upsampled and passed to the decoder followed by an LSTM layer. Fang et al. (2021) compute the mean of the encoder output attentions and estimate mean and variance for the variational loss through dense layers. OPTIMUS (Li et al., 2020b) extends this idea to large-scale language models. The encoder weights are initialized with pre-trained BERT weights, the decoder with those from a pre-trained GPT-2 model. The latent representation of the start token is used as sentence-level representation. All these methods apply $L_{REG}$ on a sentence-level vector and thus enforce isotropy between sentence representations. Capturing long, complex sentences or paragraphs is a challenge with this approach, as the vector representation is restricted to a certain dimensionality independent from the length of the input sequence.

Shu et al. (2020) propose a Transformer-based non-autoregressive model for machine translation, but do not use a Gaussian prior, thus do not enforce an isotropic latent space. A variational autoencoder has not yet been used to generate isotropic token-level representations that allow for direct manipulations in latent space.

## 4 VARIATIONAL AUTO-TRANSFORMER

In our proposed architecture, a Transformer (Vaswani et al., 2017) network is used as autoencoder and extended with a token-level variational loss. The resulting Variational Auto-Transformer (VAT) maps input tokens to context-aware, distributed representations.

Initially proposed for neural machine translation, the Transformer can be used as language model and framed as autoencoder. The set of encoders $E$ and decoders $D$ is defined by the Transformer's characteristic network architecture based on self-attention modules. The encoder maps the input to a latent representation that is then used as attention source in the decoder to predict the next word based on the already produced output. During training, the auto-regressive decoding process is circumvented through teacher forcing, leading to a significant speed-up when compared to recurrent models.

(a) Standard Gaussian $N(\mathbf{0}, \boldsymbol{I})$          (b) Gaussian $N(\mathbf{0}, \mathrm{diag}(0.4))$

Figure 2: Weighted regularization (top) and reconstruction loss (bottom) for train and test data over several epochs for two different Gaussians applied as prior distribution for the regularization term.

In contrast to a classic autoencoder, the Transformer produces token-level latent representations $Z = \{z_1, z_2, \ldots, z_l\}$, $Z \in \mathbb{R}^{l \times d}$, where $l$ is the input sequence length and $d$ is the fixed model dimension. $l$ depends on the length of the input sequence, resulting in representations $Z$ of variable size. The loss function (4) is applied during training of the network. Both, the reconstruction as well as the regularization loss, are thus applied at token level.

Figure 1 illustrates the architecture of the VAT. The output of the encoder is passed to two linear layers in parallel. The linear layers have the same number of input and output nodes and learn a transformation to predict $\boldsymbol{\mu}$ and $\boldsymbol{\sigma}$ for each token. More precisely, we let $\Sigma = \mathrm{diag}\,(\exp \boldsymbol{\sigma})$ where the vector $\boldsymbol{\sigma} = (\sigma_j)_{j=1\ldots d}$ is predicted, so that computing the actual value of $\Sigma$ involves the exponential as a non-linear activation function. The latent representation $Z$ is used as input in the encoder-decoder attention layer of the Transformer's decoder.

### 4.1 SCALING THE REGULARIZATION LOSS

During our experiments, we experienced overfitting on the training data for the reconstruction loss even when weighting the regularization loss according to a logistic annealing function as suggested by Bowman et al. (2016). The learning curves of a corresponding experiment are illustrated in Figure 2a. Additional re-weighting of $L_{REG}$ by a scaling factor $\beta$ similar to the scaling of the beta-VAE (Higgins et al., 2017), but with $\beta < 1$, only had little effect.

Thus, we propose to scale the covariance matrix of the target distribution of $L_{REG}$ instead. This is motivated by the observation that standard Gaussians in $d$-dimensional latent spaces (e.g. $d \geq 128$) will overlap considerably if their mean values are - at the same time - regularized to zero. As a consequence, $L_{REG}$ cannot be minimized by the model without increasing $L_{REC}$ in an undesirable way. Scaling the standard deviation to a too small value, though, might result in peaky distributions, having no regulatory effect and resulting in a trivial reconstruction objective.

We adapt the computation of the regularization loss to incorporate a scaling factor $s$ for the standard deviation as hyperparameter. The closed form of the standard VAE loss function between the data distribution $q$ and a target distribution $p$ is[1]

$$- D_{KL}\left(N(\mu_q, \sigma_q), N(\mu_p, \sigma_p)\right) = \log\left(\frac{\sigma_q}{\sigma_p}\right) - \frac{\sigma_q^2 + (\mu_q - \mu_p)^2}{2\sigma_p^2} + \frac{1}{2} \tag{5}$$

---

[1]Refer to Odaibo (2019) for the derivation of the closed form.

With a target standard deviation $\sigma_p = s \in (0, 1]$ and $\mu_p = 0$, the loss function becomes

$$- D_{KL}\left(N(\mu_q, \sigma_q), N(0, s)\right) = \frac{1}{2}\log(\sigma_q^2) - \frac{\sigma_q^2 + \mu_q^2}{2s^2} - \log(s) + \frac{1}{2} \qquad (6)$$

This results in codes $\boldsymbol{z} = \boldsymbol{\sigma} \cdot \boldsymbol{\epsilon}' + \boldsymbol{\mu}$ being distributed according to a Gaussian with zero mean and a predefined standard deviation, $\boldsymbol{\epsilon}' \sim N(\boldsymbol{0}, \text{diag}(\boldsymbol{s}))$. The optimal balance between $L_{REC}$ and $L_{REG}$ as expressed by the value of $s \in (0, 1]$ is related to the representations' isotropy and will be determined experimentally.

## 5 EXPERIMENTS

The aim of the experiments is to balance the two loss terms. $L_{REC}$ should be low to maintain the reconstruction ability of the network, while a too small scaling value $s$ implies that the VAT essentially behaves as regular AE. At the same time, we want to optimize the isotropy of the latent representations. In order to choose the best setting, we observe both, the resulting loss values and the properties of the latent space in terms of similarity between representations.

Our VAT model architecture is smaller than the original Transformer architecture, as it is not intended for machine translation. The VAT consists of $N = 4$ encoder and decoder layers, respectively, with $H = 8$ attention heads each and a model dimensionality of $d = 128$. A logistic annealing function (Bowman et al., 2016) is applied to weight $L_{REG}$. The VAT is trained on the train split of the WMT19 de-en dataset (Barrault et al., 2019) using English sentences only. WMT19 contains data from the news commentary, Wiki titles, Europarl, ParaCrawl and Common Crawl corpora. The data is tokenized using subword tokenization with a target vocabulary of $2^{15}$ tokens. The full details on model and training parameters are listed in the appendix.

### 5.1 OPTIMAL SCALING PARAMETER

At first, the isotropy of the learned representations $\boldsymbol{z}$ is assessed as a function of the scaling factor $s \in (0, 1]$. Ethayarajh (2019) introduced the notion of isotropy of the latent space as a function of cosine similarity between vector representations of random tokens. In an isotropic latent space, representations of randomly sampled tokens have low cosine similarity and do not cluster in a specific direction but are rather spread across space.

In addition to isotropy, Ethayarajh (2019) introduces the notion of self-similarity and intra-sentence similarity. A high self-similarity, i.e. cosine similarity between representations of the same token in different sentences, indicates that neighboring representations capture similar concepts which contributes to the smoothness of the latent space. Intra-sentence similarity, finally, measures the cosine similarity of tokens occurring in the same sentence to the mean sentence representation, thus being related to contextuality.

In contrast to ELMo (Peters et al., 2018), GPT-2 and BERT, where contextuality is high with respect to the low isotropy in the last layers of the models (Ethayarajh, 2019), we expect a more complete latent space for the VAT and thus high isotropy. The results in Figure 3a are computed for the STS12 datasets Agirre et al. (2012). The average cosine similarity between randomly sampled words is low for smaller $s$ values, suggesting an isotropic latent space with representations distributed across the space. The latent space is most isotropic at $s = 0.4$.

The average self-similarity of tokens greater than $0.6$ suggests a mapping of similar concepts into the same region, indicating smoothness in the latent space. The intra-sentence similarity for $0.5 \geq s \geq 0.1$ is lower than the self-similarity, but still above the similarity of random words. This indicates that contextual information is captured in the representations. Interestingly, for $1 \geq s \geq 0.6$, the token representations seem to "collapse" into an identical representation for all positions in a sequence resulting in an intra-sentence similarity of $1$. Among the words with most context-specific representations are mainly stopwords as they have lowest self-similarity.

In Figure 3b, we report the final loss values after training the models for 3 epochs with different scaling factors $s \in (0, 1]$. Despite the annealing of the regularization loss (Bowman et al., 2016), scaling values $1 \geq s \geq 0.6$ still result in near zero regularization losses and high reconstruction error. The original input cannot be reproduced any more. This phenomenon is referred to as posterior

(a) Cosine similarities of the latent representations of the VAT at the end of the training process denoting the isotropy of the latent space and the contextuality of token representations.

(b) Reconstruction loss, weighted regularization loss and total loss of the VAT at the end of the training process.

Figure 3: Optimizing the scaling factor $s$ with respect to isotropy and loss values.

collapse (Lucas et al., 2019). This collapse also corresponds to the findings from Figure 3a, where the representations within a sentence are identical. Starting from $s = 0.5$, the reconstruction loss drops and only with $s = 0.4$, the reconstruction loss falls below the regularization loss. Values smaller than $s = 0.4$ further decrease the positive effects of regularization and the achievable variety of generated text.

Combining the findings from evaluating the loss and latent space properties in Figure 3, we select $s = 0.4$ as scaling factor for further evaluating the VAT. This value corresponds to good reconstruction ability and isotropic representations which impacts both the generation of text as well as the performance on classification tasks. Also, the learning curves corresponding to $s = 0.4$ exhibit no overfitting any more (see Figure 2b).

## 6 Variational Language Model

During training, the VAT encoder produces variants of the input tokens by drawing from the latent distribution. The VAT decoder has to be able to reproduce the original sequence given variational input. At test time, both approaches are possible: Decoding with the standard deviation set to 0, i.e. $z = \mu$, leads to a deterministic representation and is used for classification tasks. For text generation, decoding $z = \sigma \cdot \epsilon + \mu$ allows to generate variants of the original input sequence which we refer to as variational sampling. Variational language modeling thus refers to the various ways of manipulations and computations in latent space that are possible with the VAT' latent distributions. As examples, we show anecdotal results from variational sampling and interpolation.

Table 1 illustrates the generating capabilities of the VAT. In the second line, the VAT is able to reconstruct the original sequence from the first line. This setting refers to decoding with $z = \mu$. The following lines show exemplary variants of the input sentence obtained by randomizing the latent representations, displaying 12 variational samples. It is interesting that, while mostly maintaining the original sentence structure and original context, variants are found for almost all tokens. This gives an idea of the structure of the latent space and the contextuality of the representations.

We also experimented with latent space interpolation. Given two input sentences that were passed through the VAT encoder, we linearly interpolate the latent representations that were then decoded to produce intermediate sentences. Table 2 illustrates an example interpolation. We note that observing a smooth interpolation trajectory as in the example is not always the case. While we interpolate the latent representation vector, it is still possible that after decoding, the intermediate steps are mapped to the same sentence. This is especially true with increasing size of training data: The more training data, the more contextualized representations for the same word type that are mapped close to each other in latent space will exist.

| **In this class, we will introduce several fundamental concepts.** |
| --- |
| In this class, we will introduce several fundamental concepts. |
| *In this class, we will introduce several fundamental principles.* |
| *In this area, we will introduce several fundamental principles.* |
| *In this process, we will introduce several educational concepts.* |
| *In this class, I will introduce several fundamental principles.* |
| *In this progress, we will introduce private fundamental concepts.* |
| *In this class, we have received several fundamental concepts.* |
| *In this class, we will introduce several public projects.* |
| *In April 2013, we will introduce several fundamental issues.* |
| *In this class, we will find several fundamental principles.* |
| *In one class, she will introduce several fundamental concepts.* |

Table 1: Variational sampling. Example sentence (in **bold**) that was used as input to the VAT, with the decoded mean representation and samples from the latent distribution (in *italics*).

| **I want to talk to you.** |
| --- |
| I want to report. |
| I said: |
| She didn't want to say. |
| **She didn't want to be with him.** |

Table 2: Interpolation. First and last sentence (in **bold**) were given as input to the VAT. Intermediate sentences were obtained by token-wise linear interpolation between the two latent representations. The input sentences are taken from an example in (Bowman et al., 2016).

## 7 SENTENCE REPRESENTATIONS

For the construction of sentence representations, we compare two pooling operations (average, sum). Additionally, the start token ("CLS") representation can be used as embedding for the whole sentence, but this approach has been shown to be inferior to mean pooling in semantic similarity tasks for BERT (Reimers & Gurevych, 2019). We denote the different approaches as VAT-*mean*, VAT-*sum* and VAT-*start*, respectively. We compare our model to the original BERT model (base) and, for a fair comparison in terms of model size, to a smaller variant with similar network dimensions than the VAT. BERT has $L = 12$ encoder layers and the model and representation dimension is $d = 768$. The smaller BERT model[2] (Turc et al., 2019), which we refer to as MiniBERT, has $d = 128$ and $L = 4$, the same size as the VAT. Both BERT and MiniBERT were trained on a much larger collection of datasets (Wikipedia, BookCorpus, CommonCrawl) than the VAT.

The sentence representations are tested using the SentEval (Conneau & Kiela, 2018) toolkit[3]. The toolkit evaluates static sentence representations on two different classes of tasks: semantic similarity and sentence classification tasks. For the semantic similarity tasks, we additionally compare our model to SBERT-NLI (Reimers & Gurevych, 2019) and BERT-flow (Li et al., 2020a) which both were specifically designed to improve BERT's performance on semantic similarity tasks. For those models, results for the base models are reported, where $d = 768$ and $L = 12$.

SBERT-NLI extends a pretrained BERT model with a siamese network architecture specifically targeted to improve sentence comparison tasks. These siamese layers were fine-tuned on natural language inference (NLI) data. SBERT-NLI does not directly optimize the representations' isotropy. BERT-flow is also targeted to improve the pretrained BERT embeddings for semantic similarity tasks through normalizing flows. BERT-flow representations are isotropic as well, but cannot be decoded or "interpreted".

Table 3 lists the correlation values of the different sentence representation methods on the semantic textual similarity (STS) tasks. For each pair of semantically similar sentences, the spearman cor-

---

[2]https://github.com/google-research/bert
[3]https://github.com/facebookresearch/SentEval

|  | STS12 | STS13 | STS14 | STS15 | STS16 | STSb | SICK-R | Average |
|---|---|---|---|---|---|---|---|---|
| *Published in (Reimers & Gurevych, 2019)* | | | | | | | | |
| BERT-*start* | 20.16 | 30.01 | 20.09 | 36.88 | 38.08 | 16.50 | 42.63 | 29.19 |
| BERT-*mean* | 38.78 | 57.98 | 57.98 | 63.15 | 61.06 | 46.35 | 58.40 | 54.81 |
| SBERT-NLI | 70.97 | 76.53 | 73.19 | 79.09 | 74.30 | 77.03 | 72.91 | 74.86 |
| *Published in (Li et al., 2020a)* | | | | | | | | |
| BERT-flow | 63.48 | 72.14 | 68.42 | 73.77 | 75.37 | 70.72 | 63.11 | 69.57 |
| *Our results* | | | | | | | | |
| MiniBERT-*start* | -2.19 | 0.87 | 1.27 | 0.81 | -3.46 | -2.41 | 0.61 | -0.64 |
| MiniBERT-*mean* | -1.14 | -3.83 | 1.63 | 0.21 | 7.25 | -5.3 | -1.73 | -0.42 |
| MiniBERT-*sum* | -0.50 | -1.54 | 0.60 | -0.72 | 0.11 | 1.21 | 1.67 | 0.12 |
| VAT-*start* | 17.45 | 12.10 | 14.74 | 20.09 | 31.14 | 30.70 | 37.15 | 23.34 |
| VAT-*mean* | 45.60 | 45.43 | 52.07 | 55.45 | 58.13 | 50.83 | 47.08 | 50.66 |
| VAT-*sum* | 45.60 | 45.43 | 52.07 | 55.45 | 58.13 | 51.56 | 48.88 | 51.02 |

Table 3: Spearman rank correlation between the cosine similarity of sentence representations and gold label similarity for different semantic textual similarity (STS) tasks without fine-tuning the underlying models to the target data.

relation rank between the cosine of their latent representations and a human-labeled gold standard (between 0 and 5) is computed (no fine-tuning or transfer learning). The correlation of VAT-based sentence representations is on par with BERT-based representations which is surprising given the smaller model architecture and capacity of the VAT. For both VAT and BERT, start token based representations show less correlation than those obtained by average or sum pooling. Representations obtained from the MiniBERT model do not show any correlation at all, indicating that the BERT architecture requires a larger model size. Unsurprisingly, BERT-flow and SBERT-NLI show high correlation and outperform all other models.

The classification tasks included in the SentEval toolkit comprise binary (MR, CR, SST2) and fine-grained (SST5) sentiment or polarity classification tasks, paraphrase detection (MRPC), natural language inference (SICK-E) and question-type classification (TREC) tasks. As paraphrase detection and natural language inference require the comparison of two sentences, the pair of input sentences is concatenated and separated by a special separation token to form a single input vector. For the classification tasks, we compare the performance of the VAT to that of MiniBERT in two ways: in a feature-based approach and in a fine-tuning approach.

Both presented approaches are different from how state-of-the-art models are trained for transfer tasks. Given the smaller model capacity, we do not expect on-par performance, but rather want to better understand the kind of information stored in the representations and the potential that comes with additional classification layers on top of the model. Thus, the comparison to the MiniBERT model serves as baseline.

For the feature-based approach, the sentence representations are extracted from the pretrained models and then passed to a single classification layer trained with an Adam optimizer. Given the results in Table 4 (top), we learn that the sum of the individual token representations is best suited as standalone feature for sentence classification. As VAT-*sum* outperforms VAT-*mean* on all tasks, the dimensions of the latent representations seem to be well disentangled. With the exception of the SST2 task, the start representations yields lowest accuracy values suggesting that the first representations does not capture the full context of a sentence. MiniBERT, which is designed for fine-tuning rather than feature extraction, does not reach the performance of the VAT variants on most tasks with this approach. The difference between MiniBERT and VAT is especially large for the TREC task.

For assessing the performance with a fine-tuning approach, we extend the underlying models by a single non-linear dense classification layer and optimize with Adam. For the VAT, we only reuse the encoder part to access the latent representations $Z$. For each task, we trained for five epochs and selected the best learning rate out of $\left\{3 \cdot 10^{-4}, 1 \cdot 10^{-4}, 5 \cdot 10^{-5}, 3 \cdot 10^{-5}\right\}$ based on the validation set to be used on the test set. Note that the MiniBERT results can differ from the results in the original publication (Turc et al., 2019), as we do not further tune the model or the training process.

|                  | MR        | CR        | SST2      | SST5      | TREC      | MRPC      | SICK-E    |
|------------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| *Feature-based Approach* | | | | | | | |
| MiniBERT-*start* | 50.8/50.1 | 63.9/63.8 | 51.2/49.9 | 27.7/24.6 | 23.7/18.2 | 67.8/66.5 | 56.4/56.7 |
| MiniBERT-*mean*  | 50.9/50.1 | 61.6/60.9 | 53.0/50.3 | 24.4/25.1 | 22.9/18.2 | 65.5/65.9 | 55.6/55.9 |
| MiniBERT-*sum*   | 51.9/49.6 | 62.2/59.7 | 51.4/51.5 | 25.8/23.0 | 23.0/20.8 | 64.8/57.6 | 48.4/49.7 |
| VAT-*start*      | 60.5/59.6 | 63.8/63.8 | **61.6/63.3** | 29.4/29.3 | 35.1/40.4 | 67.5/66.5 | 56.4/56.7 |
| VAT-*mean*       | 61.0/60.2 | 63.9/63.8 | 61.4/60.7 | 30.4/31.0 | 44.1/48.6 | 67.5/66.6 | 59.2/58.5 |
| VAT-*sum*        | **61.2/60.5** | **66.8/65.7** | 61.0/62.6 | **31.5/32.2** | **46.8/54.8** | **69.6/68.5** | **67.8/66.6** |
| *Fine-tuning Approach* | | | | | | | |
| MiniBERT-*start* | 72.8/72.1 | 64.4/61.9 | 80.6/83.2 | 36.7/36.1 | 32.1/38.8 | 68.9/66.5 | 56.4/56.7 |
| MiniBERT-*mean*  | **76.0/75.6** | 73.4/65.6 | **81.0/83.3** | 38.0/37.9 | 72.4/73.2 | 71.8/68.6 | 58.2/58.1 |
| MiniBERT-*sum*   | 73.8/70.7 | 75.4/67.6 | 70.0/81.6 | 35.8/32.8 | 70.8/69.6 | 68.9/63.0 | 57.6/44.3 |
| VAT-*start*      | 74.5/74.6 | 76.3/72.5 | 82.7/82.6 | 37.8/38.6 | 82.7/87.2 | **70.0/69.9** | 61.6/61.3 |
| VAT-*mean*       | 73.8/74.1 | 75.0/72.5 | 81.7/82.4 | **39.9/40.0** | 84.1/85.2 | 68.9/63.7 | **64.2/61.8** |
| VAT-*sum*        | 72.9/73.2 | **78.6/74.5** | **82.6/83.3** | 40.7/39.9 | **84.7/88.2** | 69.7/68.3 | 62.0/60.8 |

Table 4: Dev/test accuracies on the SentEval transfer classification tasks. A single dense layer with nonlinear activation and Adam optimizer is used as classification layer. **Bold** values indicate the best test result for each task in the feature-based and fine-tuning approach.

In Table 4 (bottom), we see a performance leap for all of the models compared to their feature-based results. While VAT-*sum* was performing best for the feature-based approach, the method to produce sentence-level representations is not that decisive for the fine-tuning approach. The differences between *sum*, *mean* and *start* are not as great as for the semantic similarity tasks any more, neither for MiniBERT nor for VAT. It is interesting that MiniBERT is in lead for sentiment classification tasks, whereas VAT shows outstanding performance on the TREC (topic classification) task.

## 8    DISCUSSION AND CONCLUSION

The goal of the proposed VAT model is to obtain isotropic representations mapped to a smooth and complete latent space. The hyperparameter and scaling factor $s$ is directly optimized to meet these criteria. The effect can be seen especially for text generation, where the VAT is able to produce coherent text through manipulations directly in latent space. However, optimizing $L_{REG}$ comes at the cost of $L_{REC}$. Perfect reconstruction of the original input is not possible at all times any more.

Reducing the representations to a single sentence-level vector e.g. by applying pooling preserves contextual information. Semantic similarity tasks demonstrate that the smaller model capacity of the VAT is sufficient to capture semantic information that is on a par with larger BERT architectures. However, models explicitly trained to improve the performance on semantic similarity tasks are out of reach.

The VAT is able to produce more robust standalone sentence-level features when compared with MiniBERT for the feature-based classification approach. However, The VAT outperforms the similar-sized MiniBERT also when being fine-tuned on sentence classification tasks, but is far from the state-of-the-art performance known from BERT-sized models with more sophisticated training procedures. Interestingly, the VAT shows its peak performance for the topic classification task TREC. In our setup, the VAT captures topic-related information even better than sentiment.

Tasks involving the comparison of two sentences (MRPC, SICK-E), represented by a single concatenated vector, cannot be successfully solved by either VAT or MiniBERT. Some model variants (MiniBERT included) only learn to predict the most frequent class. The reason could be the smaller model sizes that are incapable of capturing the information of two concatenated sentences, as especially the VAT was never trained on such a setting. Instead of a concatenated vector, the comparison task could be solved using a siamese network architecture, similar to Deudon (2018).

The comparison to MiniBERT leaves us optimistic that with a larger model and dataset size, the performance on downstream tasks will even improve while still maintaining the desired characteristics of the latent representations. Optimizing the regularization loss at token-level could even allow the training of a multilingual model or a translation model, given sufficient training data.

REPRODUCIBILITY STATEMENT

All data used for training and evaluation of the model are publicly available. The WMT19 dataset was obtained through the tensorflow library at `https://www.tensorflow.org/datasets/catalog/wmt19_translate`, all other datasets are available through the SentEval toolkit at `https://github.com/facebookresearch/SentEval`. The source code for instantiating and training our model as well as for decoding and generating variational samples is made available as supplementary material. Hyperparameters and training settings are described in Section 5 and – in more detail – in Appendix A.

REFERENCES

Eneko Agirre, Daniel Cer, Mona Diab, and Aitor Gonzalez-Agirre. SemEval-2012 Task 6: A Pilot on Semantic Textual Similarity. In *\*SEM 2012: The First Joint Conference on Lexical and Computational Semantics – Volume 2: Proceedings of the Sixth International Workshop on Semantic Evaluation (SemEval 2012)*, pp. 385–393, Montréal, Canada, June 2012. Association for Computational Linguistics.

Loïc Barrault, Ondřej Bojar, Marta Costa-Jussà, Christian Federmann, Mark Fishel, Yvette Graham, Barry Haddow, Matthias Huck, Philipp Koehn, Shervin Malmasi, et al. Findings of the 2019 Conference on Machine Translation (WMT19). In *Proceedings of the Fourth Conference on Machine Translation (Volume 2: Shared Task Papers, Day 1)*, pp. 1–61, 2019.

Samuel R. Bowman, Luke Vilnis, Oriol Vinyals, Andrew Dai, Rafal Jozefowicz, and Samy Bengio. Generating Sentences from a Continuous Space. In *Proceedings of The 20th SIGNLL Conference on Computational Natural Language Learning*, pp. 10–21, Berlin, Germany, August 2016. Association for Computational Linguistics.

Xingyu Cai, Jiaji Huang, Yuchen Bian, and Kenneth Church. Isotropy in the Contextual Embedding Space: Clusters and Manifolds. In *International Conference on Learning Representations*, Online, 2021.

Alexis Conneau and Douwe Kiela. SentEval: An Evaluation Toolkit for Universal Sentence Representations. In *Proceedings of the Eleventh International Conference on Language Resources and Evaluation (LREC 2018)*, Miyazaki, Japan, May 2018. European Language Resources Association (ELRA).

Michel Deudon. Learning Semantic Similarity in a Continuous Space. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics.

Kawin Ethayarajh. How Contextual are Contextualized Word Representations? Comparing the Geometry of BERT, ELMo, and GPT-2 Embeddings. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 55–65, Hong Kong, China, November 2019. Association for Computational Linguistics.

Le Fang, Tao Zeng, Chaochun Liu, Liefeng Bo, Wen Dong, and Changyou Chen. Transformer-based Conditional Variational Autoencoder for Controllable Story Generation. *CoRR, arXiv:2101.00828v1*, 2021.

Jun Gao, Di He, Xu Tan, Tao Qin, Liwei Wang, and Tieyan Liu. Representation Degeneration Problem in Training Natural Language Generation Models. In *International Conference on Learning Representations*, 2019.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT Press, 2016.

Suchin Gururangan, Tam Dang, Dallas Card, and Noah A. Smith. Variational Pretraining for Semi-supervised Text Classification. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 5880–5894, Florence, Italy, July 2019. Association for Computational Linguistics.

Irina Higgins, Loïc Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-VAE: Learning basic visual concepts with a constrained variational framework. In *International Conference on Learning Representations*, Toulon, France, 2017.

Diederik P. Kingma and Max Welling. Auto-Encoding Variational Bayes. In Yoshua Bengio and Yann LeCun (eds.), *International Conference on Learning Representations*, Banff, AB, Canada, 2014.

Alexandre Lacoste, Alexandra Luccioni, Victor Schmidt, and Thomas Dandres. Quantifying the Carbon Emissions of Machine Learning. *CoRR, arXiv:1910.09700*, 2019.

Bohan Li, Hao Zhou, Junxian He, Mingxuan Wang, Yiming Yang, and Lei Li. On the Sentence Embeddings from Pre-trained Language Models. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 9119–9130. Association for Computational Linguistics, November 2020a.

Chunyuan Li, Xiang Gao, Yuan Li, Baolin Peng, Xiujun Li, Yizhe Zhang, and Jianfeng Gao. Optimus: Organizing Sentences via Pre-trained Modeling of a Latent Space. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 4678–4699, Online, November 2020b. Association for Computational Linguistics.

Danyang Liu and Gongshen Liu. A Transformer-Based Variational Autoencoder for Sentence Generation. In *2019 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–7, 2019.

James Lucas, George Tucker, Roger Grosse, and Mohammad Norouzi. Understanding Posterior Collapse in Generative Latent Variable Models. In *International Conference on Learning Representations, DeepGenStruct Workshop*, New Orleans, LA, USA, 2019.

Yishu Miao, Lei Yu, and Phil Blunsom. Neural Variational Inference for Text Processing. In *Proceedings of the 33rd International Conference on Machine Learning - Volume 48*, ICML'16, pp. 1727–1736. JMLR.org, 2016.

Stephen Odaibo. Tutorial: Deriving the Standard Variational Autoencoder (VAE) Loss Function. *CoRR, arXiv:1907.08956*, 2019.

Matthew Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. Deep Contextualized Word Representations. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 2227–2237, New Orleans, Louisiana, June 2018. Association for Computational Linguistics.

Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language Models are Unsupervised Multitask Learners and Better Language Models and Their Implications. OpenAI Blog, 2019.

Nils Reimers and Iryna Gurevych. Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 3982–3992, Hong Kong, China, November 2019. Association for Computational Linguistics.

Raphael Shu, Jason Lee, Hideki Nakayama, and Kyunghyun Cho. Latent-variable Non-autoregressive Neural Machine Translation with Deterministic Inference using a Delta Posterior. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 8846–8853, 2020.

Iulia Turc, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Well-Read Students Learn Better: On the Importance of Pre-training Compact Models. *CoRR,arXiv:1908.08962v2*, 2019.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is All you Need. In *Advances in Neural Information Processing Systems 30*, pp. 5998–6008. Curran Associates, Inc., 2017.

Lingxiao Wang, Jing Huang, Kevin Huang, Ziniu Hu, Guangtao Wang, and Quanquan Gu. Improving Neural Language Generation with Spectrum Control. In *International Conference on Learning Representations*, 2020.

Tiancheng Zhao, Kyusong Lee, and Maxine Eskenazi. Unsupervised Discrete Sentence Representation Learning for Interpretable Neural Dialog Generation. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1098–1107, Melbourne, Australia, July 2018. Association for Computational Linguistics.

# A   APPENDIX

## MODEL DETAILS

The implemented VAT consists of $N = 4$ encoder and decoder layers, respectively, with $H = 8$ attention heads each. The encoder and decoder architecture including the positional embedding is the same as in the original Transformer (Vaswani et al., 2017) and can be seen in Figure 1. The model dimensionality $d = 128$, the dimension in the feed forward layers is $512$. Dropout during training is set to $0.1$. The Noam optimizer Vaswani et al. (2017) operates with $50,000$ warmup steps. A logistic annealing function Bowman et al. (2016) with $50,000$ warmup steps and an initial value of $0.00025$ is applied to weight the regularization term of the loss function.

The VAT is trained on the train split of the WMT19 de-en dataset Barrault et al. (2019) using English sentences only. The data is tokenized using subword tokenization with a target vocabulary of $2^{15}$ tokens. Batch size is set to $128$. Decoded sentences that are presented as results are obtained through beam search with beam size $5$.

## ENERGY CONSUMPTION

Experiments were conducted using a private infrastructure, which has an estimated carbon efficiency of 0.197 kgCO$_2$eq/kWh. A single epoch takes 20 hours of computation on a RTX 2080 Ti (TDP of 250W) GPU. For the training of a VAT model for 3 epochs, total emissions are estimated to be 0.99 kgCO$_2$eq according to the ML impact calculator Lacoste et al. (2019) available at:

`https://mlco2.github.io/impact#compute.`