R4D: Utilizing Reference Objects for Long-Range Distance Estimation

Abstract

Estimating the distance of objects is a safety-critical task for autonomous driving. Focusing on the short-range objects, existing methods and datasets neglect the equally important long-range objects. In this paper, we name this challenging but underexplored task as Long-Range Distance Estimation, and propose two datasets for this task. We then propose R4D, the first framework to accurately estimate the distance of long-range objects by using references with known distances in the scene. Drawing inspiration from human perception, R4D builds a graph by connecting a target object to all references. An edge in the graph encodes the relative distance information between a pair of target and reference objects. An attention module is then used to weigh the importance of reference objects and combine them into one target object distance prediction. Experiments on the two proposed datasets demonstrate the effectiveness and robustness of R4D by showing significant improvements compared to existing baselines.

1 Introduction

Estimating the distances of objects from the vehicle is crucial for several autonomous driving tasks, including lane changing, route planning, speed adjustment, collision avoidance, to name a few. Although existing methods and datasets focus on short-range objects, knowing the distance of long-range objects — objects beyond a typical LiDAR range of ∼80 meters (as shown in Figure 1) — is necessary for freeway driving, heavy-duty truck driving, and wet road driving. Based on the US Department of Transportation (Blanco & Hankey, 2005), on rural highways with a standard speed limit of 65 miles/h, it takes ∼145 meters for a passenger vehicle to come to a complete stop in an emergency, greatly exceeding the typical LiDAR sensing range. The required stopping distance grows significantly with a heavy load truck or in bad road conditions such as snow, ice, or rain. For example, the stopping distance increases from 145 meters to 183 meters and 278 meters for trucking and wet road driving, respec-

Figure 1: Most long-range **vehicles** (target objects) in this view are beyond **LiDAR** range, but are still important for safety. R4D estimates the distance of **target objects** by using **reference objects** with known distances (*e.g.*, LiDAR detections).

tively (Administration, 2016; Blanco & Hankey, 2005). In addition, given that harsh and sudden breaking on freeways is unsafe, it remains critical to estimate the distance of objects beyond the minimum required stopping distance in order to provide enough time for a gradual slow-down or lane change. Therefore, to allow sufficient time for an appropriate reaction and to ensure safety, autonomous driving systems are required to estimate the distance to long-range objects.

We name this critical but underexplored task as *Long-Range Distance Estimation*. Concretely, given the short-range LiDAR signal and the camera image, the distances of long-range objects (beyond LiDAR range) are expected as output. Following conventions, the *distance* is measured between the camera and the object center along the camera's optical axis (Gökçe et al., 2015; Haseeb et al., 2018; Zhu & Fang, 2019). We discuss more about making design choices for our task in the related work. For this new task, we present *pseudo long-range KITTI dataset* and *anonymous internal long-range dataset*. Since KITTI (Geiger et al., 2013) do not provide ground-truth distance for

Figure 2: R4D overall architecture for training and prediction. Target and references are represented as a graph and the embeddings are fed to an attention module to weigh different references and aggregate results into a final distance estimate.

long-range objects, the pseudo long-range KITTI dataset is a derived dataset by removing LiDAR points beyond 40 meters and considering the objects beyond 40 meters as target. More importantly, we build a large scale dataset with annotated *real* long-range objects (from 80 to 300 meters). In summary, with different definition of "long-range" (either beyond 40 or 80 meters), both datasets include LiDAR points, camera images, and distance labels for long-range objects.

Neither LiDAR nor camera alone solves this long-range distance estimation problem to the desired accuracy. Most existing *LiDAR* technologies do not meet long-range sensing requirements. According to the Waymo and KITTI self-driving car datasets, the maximum LiDAR range is only around 80 meters, which falls short of the range required for the aforementioned scenarios. Even though some advanced LiDAR systems claim to achieve a longer sensing range, *e.g.*, Waymo's 5th generation LiDAR system (Jeyachandran, 2020) and Velodyne Alpha Prime^{TM} (VelodyneLidar, 2021) which reach up to 300 meters, LiDAR points are sparse at long-range and, thus, more likely to be occluded. Therefore, LiDAR alone is not enough to cover all safety-critical self-driving car applications.

Cameras, on the other hand, sense objects at a longer range and capture rich semantic information such as object appearance, geometry, and contextual hints. However, they do not, in and of themselves, provide depth information. Classical geometry-based algorithms could estimate the distance of canonical objects (*e.g.*, sedans, trucks) based on their pixel sizes in the camera image (Criminisi et al., 2000; Tuohy et al., 2010; Gökçe et al., 2015; Haseeb et al., 2018; Qi et al., 2019). However, these approaches yield inaccurate results on long-range objects due to errors in size estimation. Appearance-based methods (Song et al., 2020; Zhu & Fang, 2019) give unsatisfactory results on long-range objects. Such methods rely on a single appearance cue to estimate the distance, overlooking context or other relevant signals in the scene. At long-range, objects are visually small thus produce less informative appearance features. Although neither LiDAR nor camera alone can solve this problem, these two signals provide complementary cues for long-range distance estimation.

In this paper, we propose R4D, a method to utilize reference objects with known and accurate distances for long-range distance estimation (R4D). The main motivation behind our approach lies in theories of human perception from cognitive science: humans often estimate the distance of an object relative to other *reference* points or objects (Granrud et al., 1984). Specifically, we train a model to localize a long-range object (*target*) given *references* with known distances. We represent the target object and references as a *graph*. As shown in Figure 2, we define objects as nodes, with edges connecting the target to the reference objects. The reference information is propagated to the long-range target object by extracting target-reference (Tar-Ref) embeddings. R4D then feeds all target-reference embeddings to an attention module which fuses information from different references, by weighing their relative importance and combining them into one distance prediction.

Experiments on the pseudo long-range KITTI and anonymous internal long-range datasets show that R4D significantly improves the distance estimation and achieves state-of-the-art long-range localization results. For example, on the *anonymous internal long-range* dataset, with R4D, the distances of 8.9% more vehicles (from 53.4% to 62.3%) are predicted with a relative distance error below 10%. By conducting experiments on images captured at different times of the day, *e.g.*, train on daytime and test on nighttime images, R4D also shows stronger robustness against domain changes.

To summarize, our contributions are three-fold. (1) We propose a critical but underexplored task Long-Range Distance Estimation. (2) We present two datasets, pseudo long-range KITTI dataset and anonymous internal long-range dataset. To facilitate future research, the datasets will be made publicly available. (3) We develop R4D, the first framework to accurately estimate the distance of long-range objects by using references with known distances.

2 RELATED WORK

In this section, we discuss the related tasks and the detailed design choices of our proposed task.
Monocular distance estimation. Estimating the distance of objects from an RGB image (*i.e.*, monocular distance estimation) is a popular computer vision topic. More than a decade ago, researchers designed geometry-based algorithms to estimate object distances. For example, Tuohy et al. (2010) use inverted perspective mapping (IPM) to convert an image to the bird's eye view for estimating distances. Learning-based methods were later proposed (Qi et al., 2019; Song et al., 2020). For example, SVR (Gökçe et al., 2015) and DisNet (Haseeb et al., 2018) take the pixel height and width of an object as input and estimate object distance by using support vector regression (Drucker et al., 1997) and multi-layer perceptron (MLP). However, such methods are subject to errors in object size estimation (Zhu & Fang, 2019), which can be even more pronounced for long-range objects. Zhu & Fang (2019) developed an end-to-end distance estimator with a Convolutional Neural Network (CNN) feature extractor. Specifically, given an RGB image and object bounding boxes, the model extracts per-object embeddings with a CNN and ROI pooling operator (Girshick, 2015), and then predicts a distance for each object. As previously mentioned, this method relies heavily on object appearance, which is a less informative cue for long-range objects.

Another related research topic is monocular per-pixel depth estimation. Eigen et al. (2014); Garg et al. (2016); Godard et al. (2019); Lee & Kim (2019); Liu et al. (2015); Shu et al. (2020) propose to predict dense depth maps given RGB images. For example, Lee & Kim (2019) generate multi-resolution relative depth maps to construct the final depth map. However, these methods can be resource-intensive and, therefore, difficult to incorporate within a latency-sensitive system such as autonomous driving (Zhu & Fang, 2019). In addition, it is non-trivial to translate a depth map into per-object distance estimates due to occlusions, looseness of bounding boxes, *etc*.

Long-range depth sensing. In addition, other approaches such as stereo cameras and Radar have been used to sense objects at long-range. Stereo camera systems simulate human binocular vision and use multiple cameras to create stereo-pairs and perceive depth (Khamis et al., 2018; Poggi et al., 2019). However, stereo vision systems have a few limitations: they are difficult to calibrate, are sensitive to vibrations (Zhang et al., 2020), and require a special hardware setup. In contrast, R4D does not need special hardware and works with existing sensors present on most autonomous vehicles, such as standalone camera and LiDAR. Radar, on the other hand, uses radio waves to determine the range, angle, and velocity of objects. However, due to its limited angular resolution (Scheiner et al., 2020), it is difficult for Radar to accurately localize long-range objects.

Monocular 3D object detection. Monocular 3D object detection aims to detect all objects in an image by predicting a 3D bounding box for each of them, *e.g.*, MonoPair (Chen et al., 2020). Besides distance (from the target object to the autonomous vehicle), the monocular 3D object detector also predicts object size. For short-range vehicles, both object distance and object size are critical for self-driving tasks, such as route planning, collision avoidance, and lane changing. However, for long-range vehicles, the distance is significantly larger than object size (*e.g.*, 300 meters vs. 2 meters), thus the object size is less critical compared to the distance under the real-world scenario. Moreover, predicting the object size increases the latency and the complexity of the model. *Therefore, our task focuses on estimating the distance of long-range objects.*

Figure 3: The detailed architecture for training and prediction. We use a CNN to extract a feature map from the input image. Given target, reference, and union bounding boxes, an ROIAlign is used to crop their corresponding embeddings from the feature map. Given the center and size of the target and reference boxes, we extract geo-distance embeddings using a MLP. We refer to "Attention & MLP" and its output as the *absolute distance head*, and "Aux MLP" and its output as the *relative distance head*. *Relative heads* are only used during training. Δd_i is the relative distance between the target and the i[th] reference object.

3 METHODOLOGY

Motivated by the observation that humans estimate the distance of an object relative to other references (Granrud et al., 1984), we propose R4D, a method utilizing Reference objects For long-range Distance estimation. References can be any combination of objects or points with known and accurate distances to the autonomous vehicle, such as LiDAR detections, objects detected by other sensors, map features, *etc*. We represent the target object and references as a *graph* shown in the "Raw Inputs" dashed box in Figure 2. The target object and its references are nodes in this graph. Between a pair of target and reference objects, an edge is built to encode their pairwise relationship.

Figure 4: Attention module to fuse target-reference embeddings.

The detailed architecture is illustrated in Figure 3. To model the target-reference pairwise relationship, we propose to extract *union embeddings* and *geo-distance embeddings* which encode visual and geometry relationships, respectively (Section 3.1). Then, inspired by the intuition that reference objects are not equally important, we introduce an attention module in Section 3.2 to selectively aggregate pairwise relationships. Finally, R4D is trained with an auxiliary supervision: the *relative distances* between the target and its references, as explained in Section 3.3.

In our setup, and without loss of generality, we use a monocular camera as the main sensor for detecting long-range target objects, and adopt LiDAR detected short-range objects as references. It is worthy noting that R4D is not specifically designed for LiDAR or monocular images and is readily extended to other sensors and references.

3.1 MODELING PAIRWISE RELATIONSHIPS

As previously mentioned, to better estimate the distance of a target object, we propose to model the pairwise relationships between it and other reference objects. For every pair of reference-target objects, we extract per-object feature embeddings and pairwise embeddings, as shown in Figure 3. In particular, pairwise embeddings include *union* embeddings and *geo-distance* embeddings which provide visual and geometry cues, respectively.

Union embeddings. Visual cues for modeling pairwise relationships should be based on the target object, the reference object, as well as the scene between the two objects. We therefore propose a simple approach to extract feature embeddings from the union bounding box which covers both objects. Figure 3 shows an example of a union bounding box highlighted in green. This is similar to Yao et al. (2018), where union bounding boxes were used to extract features for image captioning.

Geo-distance embeddings. To provide geometry cues, we form an input using the following:

- 2D bounding box *center coordinates* of target and reference objects, and the relative position shift between them.
- 2D bounding box *size* of target and reference objects, and the relative scale between them.
- The *distance of the reference object* as provided by a LiDAR 3D object detector.

We, then, feed this input into a multi-layer perceptron to generate the geo-distance embedding.

Given the target, reference, union, and geo-distance embeddings, we concatenate them to form a final target-reference embedding which models the relationship between a pair of target and reference objects. We analyze and discuss the importance of these embeddings in Section 5.3.

3.2 ATTENTION-BASED INFORMATION AGGREGATION

Pairs of target-reference embeddings should be combined to estimate the distance of a given target object. A simple approach is to average them over all references of the same target object. However, intuitively, and as supported by our experimental results, reference objects are not equally important. For example, a car in the bottom left of the image is potentially less helpful when localizing a faraway car lying in the top right corner of the image.

Figure 5: Data distribution of the anonymous long-range dataset.

Figure 6: An example of our distance augmentation for encouraging learning pairwise relationships.

In order to guide our model to focus on the most important reference objects, we introduce an attention-based module. As shown in Figure 4, we follow VectorNet (Gao et al., 2020) to construct embeddings with local and global information. Specifically, we use MLP and average pooling to extract a global embedding (shown in yellow in Figure 4). The global embedding is, then, concatenated with the original target-reference embeddings (blue in Figure 4). Given these global-local embeddings, the attention module predicts and normalizes importance weights for each reference using a fully connected layer followed by a softmax layer. It, finally, uses these weights to fuse the original target-reference embeddings, in a weighted average manner, resulting in one final embedding.

3.3 RELATIVE DISTANCE SUPERVISION

Predicting the target distance from the target embedding is more straightforward than from other indirect cues such as reference embeddings. To encourage the model to learn the pairwise relationships between target and reference objects, instead of shortcut cues (Geirhos et al., 2020; Li et al., 2021; Wang et al., 2020), we provide additional supervision. The design of this additional supervision is akin to the residual representation, which is widely used for computer vision to help the optimization procedure (Briggs et al., 2000; He et al., 2016; Szeliski, 1990; 2006). Specifically, during the training stage, we add a relative (or residual) distance head for each target-reference embedding. The *relative* distance Δd between the target object and the reference object is given by $\Delta d = d_t - d_r$, where d_t (resp., d_r) is the distance between the camera and the target (resp., reference) object.

4 DATASETS AND EVALUATION METRICS

To evaluate on the new task, long-range distance estimation, we create *pseudo long-range KITTI dataset* and *anonymous internal long-range dataset*. We then introduce the evaluation metrics.

4.1 PSEUDO LONG-RANGE KITTI DATASET

The original KITTI dataset (Geiger et al., 2013) contains RGB images, LiDAR point clouds, as well as 2D and 3D bounding boxes and other per-pixel annotations. With these rich annotations, benchmarks for self-driving tasks have been well developed based on KITTI dataset, including scene flow estimation, depth estimation, detection, and segmentation.

Even though the KITTI dataset provides LiDAR point clouds, it does not provide distance annotations beyond LiDAR range. We hereby present *pseudo long-range KITTI dataset*, which is derived from the original KITTI dataset. By assuming LiDAR has an effective sensing range of 40 meters only, we remove LiDAR points beyond it. The objects lying beyond this effective sensing range are considered as long-range target objects, while the distance of other objects are known and provided as inputs. It is worth noting that there are no overlap between the aforementioned target objects and the objects with known distance. Following the convention (Shi et al., 2019), the original training data is split into two subsets for training and validation, respectively. All the images do not contain long-range objects are removed from the dataset. Finally, the pseudo long-range KITTI dataset contains 2,181 images with 4,233 vehicles and 2,340 images with 4,033 vehicles in the training and validation set, respectively. Although it is easily obtained, this derived dataset is relatively small-scale and more critically does not annotate real long-range objects.

Method	LiDAR	< 5%↑	< 10%↑	< 15%↑	Abs Rel↓	Sq Rel↓	RMSE↓	RMSE$_{\log}$↓
SVR	✗	29.9%	51.6%	65.4%	12.8%	5.43	31.4	0.210
DisNet	✗	31.3%	52.4%	66.5%	12.5%	5.28	31.3	0.207
Zhu & Fang (2019)	✗	31.2%	53.4%	68.7%	11.5%	4.43	29.4	0.187
Zhu & Fang (2019)	✓	34.1%	56.4%	70.5%	11.3%	4.78	31.3	0.194
R4D-NA (**ours**)	✓	35.9%	61.7%	76.4%	10.1%	3.68	27.0	0.168
R4D (**ours**)	✓	**38.5%**	**62.3%**	**77.1%**	**9.8%**	**3.60**	**26.7**	**0.167**

Table 1: Results on the anonymous internal long-range dataset. Compared to Zhu & Fang (2019), R4D achieves performance gains on all evaluation metrics. R4D also outperforms SVR (Gökçe et al., 2015), and DisNet (Haseeb et al., 2018). R4D-NA refers to No-Attention R4D.

4.2 ANONYMOUS INTERNAL LONG-RANGE DATASET

Considering the aforementioned two limitations of the pseudo long-range KITTI dataset, we build a long-range dataset which includes vehicle distances up to 300 meters from the autonomous vehicle. The labels are obtained as follows. First, we create 3D boxes for objects in the LiDAR range. Then, we use Radar derived signals for rough positioning and extend LiDAR boxes to long-range. Due to the low resolution of Radar, labelers use smooth object trajectory constraints to make sure the boxes are consistent over time and space. Finally, given the 3D boxes for long-range objects, we compute their distances to the autonomous vehicle. In total, as shown in Figure 5, we obtain 49,056 training images with 187,938 long-range vehicles, and 3,578 validation images containing 10,483 long-range vehicles. These images span different times of day, including dawn, day, dusk, and night time. Considering its large scale and the real long-range annotations, we use this dataset by default.

4.3 EVALUATION METRICS

We follow the evaluation metrics used in dense depth and per-object distance estimation (Eigen et al., 2014; Liu et al., 2015; Garg et al., 2016; Zhu & Fang, 2019; Shu et al., 2020; Zhang et al., 2020), namely: 1) the percentage of objects with relative distance error below a certain threshold ($< 5\%$↑, $< 10\%$↑, $< 15\%$↑), 2) the absolute relative difference (Abs Rel↓), 3) the squared relative difference (Sq Rel↓), 4) the root of the mean squared error (RMSE↓), and 5) the root of the mean squared error computed from the logs of the predicted and ground-truth distances (RMSE$_{\log}$↓). Specifically, given ground-truth distances d^* and predicted distances d, we compute the metrics as follows:

$$\text{Abs Rel↓} = \text{Average}\left(|d - d^*|/d^*\right), \qquad \text{Sq Rel↓} = \text{Average}\left((d - d^*)^2/d^*\right),$$
$$\text{RMSE↓} = \sqrt{\text{Average}\left((d - d^*)^2\right)}, \qquad \text{RMSE}_{\log}↓ = \sqrt{\text{Average}\left((\log d - \log d^*)^2\right)}. \tag{1}$$

Note that ↑ and ↓ indicate whether a larger or smaller value of the corresponding metric indicates a better performance. We only evaluate performance on long-range objects.

5 EXPERIMENTS

5.1 IMPLEMENTATION DETAILS

We put the detailed design choices in Section A, and here we only introduce a critical component, distance augmentation, during the training stage.

Distance augmentation. Distance augmentation is designed for encouraging R4D to learn from pairwise relationships and prevent it from exclusively using a single cue (namely, the target embeddings). We guide the model to focus more on the relative distance between the reference and

Method	LiDAR	< 5%↑	< 10%↑	< 15%↑	Abs Rel↓	Sq Rel↓	RMSE↓	RMSE$_{\log}$↓
SVR	✗	39.1%	65.9%	79.0%	10.2%	1.38	9.5	0.166
DisNet	✗	37.1%	65.0%	77.7%	10.6%	1.55	10.4	0.181
Zhu & Fang (2019)	✗	39.4%	65.8%	80.2%	8.7%	0.88	7.7	0.131
Zhu & Fang (2019)	✓	41.1%	66.5%	78.0%	8.9%	0.97	8.1	0.136
R4D (**ours**)	✓	**46.3%**	**72.5%**	**83.9%**	**7.5%**	**0.68**	**6.8**	**0.112**

Table 2: Results on the pseudo long-range KITTI dataset. R4D outperforms SVR (Gökçe et al., 2015), DisNet (Haseeb et al., 2018), and Zhu & Fang (2019).

Tgt	Ref	Uni	G-D	$< 5\%\uparrow$	$< 10\%\uparrow$	$< 15\%\uparrow$	Abs Rel$\downarrow$	Sq Rel$\downarrow$	RMSE$\downarrow$	RMSE$_{\log}\downarrow$
✓	✗	✗	✗	31.2%	53.4%	68.7%	11.5%	4.43	29.4	0.187
✓	✓	✗	✗	31.5%	60.8%	75.3%	11.2%	4.30	29.2	0.183
✓	✓	✓	✗	32.5%	55.2%	69.7%	11.2%	4.42	29.7	0.188
✓	✓	✗	✓	36.9%	60.8%	75.3%	10.2%	3.88	27.8	0.175
✓	✓	✓	✓	**38.5%**	**62.3%**	**77.1%**	**9.8%**	**3.60**	**26.7**	**0.167**

Table 3: The target embeddings (Tgt) and the reference embeddings (Ref) alone are not enough for modeling pairwise relationships. The union embeddings (Uni) and geo-distance embeddings (G-D) are also necessary components of R4D.

target objects by emphasizing the correlation between the pairwise embeddings and the distance prediction. Specifically, we keep the relative distance fixed, perturb the reference distance, and expect the model to predict the target distance with the same perturbation. For example, as shown in Figure 6 (a), the relative distance between the target and reference object is 120 meters and given a reference distance of 80 meters, the model should predict a target distance of 200 meters (= 80 meters + 120 meters). As shown in Figure 6 (b), when the provided reference distance is perturbed (by, say, 20 meters), the model should predict 220 meters (= 100 meters + 120 meters) as the target distance, in order to maintain the correct relative distance of 120 meters. This helps the model not overfit to appearance cues provided by the target object and be more robust to slight changes in camera parameters or field-of-view. Similar augmentation techniques have been successfully used to discourage shortcut learning in other deep learning tasks (Li et al., 2021). During training, the distance label perturbation is sampled from a Gaussian distribution $X \sim \mathcal{N}(\mu, \sigma^2)$ with $\mu = 0$ and $\sigma = 200$ (See Section B for details). For the pseudo long-range KITTI dataset, we use $\sigma = 50$.

5.2 LONG-RANGE DISTANCE ESTIMATION

Tables 1 and 2 show the distance estimation results on the anonymous internal long-range and pseudo long-range KITTI datasets. On both datasets, R4D significantly outperforms prior monocular distance estimation solutions. For example, compared to Zhu & Fang (2019), R4D significantly improves the performance on the anonymous internal long-range dataset by 7.3%, 8.9%, and 8.4% on the $< 5\%\uparrow$, $< 10\%\uparrow$, and $< 15\%\uparrow$ metrics, respectively. We observe similar trends on the pseudo long-range KITTI dataset: these improve by 6.9%, 6.7%, and 3.7%, respectively. The improvement is even larger when compared to geometry-based techniques such as SVR (Gökçe et al., 2015) and DisNet (Haseeb et al., 2018). These improvements illustrate the effectiveness of R4D.

Figure 7: Comparison between Zhu & Fang (2019) with and without LiDAR information. We show the Abs Rel$\downarrow$ metric (normalized by the blue bars) for different ground-truth distance ranges. Results show that the simpler way of fusing short-range LiDAR signals marginally improves the performance on objects slightly beyond LiDAR range but hurts very long-range objects.

To further illustrate that R4D effectively uses references in LiDAR range for long-range distance estimation, we design another simple baseline to use LiDAR as a reference. We augment the input camera image (RGB) with a channel containing per-pixel projected LiDAR distance values (D) (shown in Figure 1). Then, given an RGB+D image, and detected bounding boxes, the model predicts a distance value for each target object. We modify the input of our baseline, Zhu & Fang (2019), to include the distance channel (D), in addition to the RGB image. However, as the results shown in Tables 1 and 2 (row 4), this approach achieves similar performance as when the camera image (RGB) is the sole input. Besides, in Figure 7, we show the distance estimation results of R4D as well as Zhu & Fang (2019) with RGB and RGB+D inputs, broken-down over different ground-truth distance ranges. We note that the addition of the LiDAR distance channel only improves the performance of objects slightly beyond LiDAR range, but fails at extrapolating distance values for localizing extremely long-range objects. In contrast, R4D offers consistent performance gains compared to Zhu & Fang (2019) across all distances. This results demonstrates the importance of explicitly modeling object relationships (the strategy of R4D), compared to the simpler baseline which has access to the same LiDAR sensor data.

Method	Abs.	Rel.	#Ref	DA	< 5%↑	< 10%↑	< 15%↑	Abs Rel↓	Sq Rel↓	RMSE↓	RMSE$_{log}$↓
Zhu & Fang (2019)	✓	✗	Zero	✗	32.9%	55.6%	69.9%	11.2%	4.36	29.3	0.187
Zhu & Fang (2019)	✓	✗	Zero	✓	32.3%	54.3%	69.4%	11.4%	4.37	29.2	0.186
R4D-Relative	✗	✓	One	✗	34.4%	58.8%	73.8%	10.6%	4.00	28.1	0.178
R4D-Relative	✗	✓	One	✓	34.9%	57.4%	73.3%	10.6%	3.93	27.8	0.174
R4D-One-Ref	✓	✓	One	✗	37.5%	59.9%	74.3%	10.4%	3.92	27.7	0.176
R4D-One-Ref	✓	✓	One	✓	37.5%	59.5%	73.8%	10.3%	3.87	27.6	0.175
R4D-NoAuxLoss	✓	✗	All	✗	29.9%	52.1%	69.7%	11.6%	4.67	30.4	0.195
R4D-NoAuxLoss	✓	✗	All	✓	**37.9%**	60.9%	74.7%	10.2%	3.88	27.9	0.174
R4D	✓	✓	All	✗	32.0%	54.1%	70.9%	11.1%	4.30	29.3	0.187
R4D	✓	✓	All	✓	37.5%	**63.3%**	**78.6%**	**9.8%**	**3.64**	**26.9**	**0.169**

Table 4: Ablation studies on the proposed pairwise relationship modeling and distance augmentation (DA). Results in this table are slightly different from those in Tables 1 and 3 because, here, we remove images which do not contain any reference objects. This is in order to report results on R4D-Relative, which requires at least one reference object (see Section 5.3 for details).

5.3 ABLATION STUDIES

Attention-based information aggregation. As discussed in Section 3.2, given a fixed target, R4D aggregates all target-reference embeddings using an attention-based module and predicts a weight for each reference. As shown in Table 1, compared to treating all references equally and taking the average of all target-reference embeddings (R4D-NA), the attention module improves the performance across all metrics, *e.g.*, <5%↑ is improved by 2.6%.

In order to inspect the attention module output, we visualize the learnt reference weights. We highlight the reference object with the largest weight in Figure 8. We find that results match our intuition. For example, the most important references usually share the same lane and pose as the target. In addition, the best reference is usually the one closest to the target object.

Efficacy of feature embeddings. In this section, we perform ablation experiments on the proposed feature embeddings (Section 3.1) to show their importance. The first two rows in Table 3 show that, when only using the target and reference embeddings, the performance is sub-optimal. This is likely due to the fact that these embeddings fail to capture pairwise relationships and only encode individual appearance, pose, and geometry information. Incorporating the geo-distance embeddings (row 4) allows the model to learn from the relative position and geometry between target and reference objects, resulting in the largest performance improvement. Finally, adding the union embeddings (row 5), which encode relative appearance cues, further improves the performance (*e.g.*, < 5%↑ improves by 1.6%). Note that the union embeddings are only helpful when used together with the geo-distance embeddings. This is because the union bounding box may include multiple potential objects, and a precise position is critical to pinpoint the reference object location.

Benefits of modeling pairwise relationships. R4D's main performance improvements stem from modeling pairwise relationships between target and reference objects. In this section, we show how incorporating references helps. We study the effect of removing the relative distance supervision (*i.e.*, the "Aux MLP" head in Figure 3) or the absolute distance supervision. When only the relative distance head is enabled, we use its output during inference and the target distance is computed by adding the relative distance to the known reference distance (we exclude images without references).

Figure 8: Visualizing the learnt reference weights. Targets are highlighted in yellow. References with the largest attention weights are highlighted in red. Other references are colored in blue. We observe that the most important references are often close to or in the same lane as the target, and share a similar pose as the target. Best viewed zoomed in. More images are shown in Section F.

Valid. Set	Method	$< 15\%\uparrow$	Abs Rel$\downarrow$	Sq Rel$\downarrow$	RMSE$\downarrow$	RMSE$_{\text{log}}\downarrow$
Day	Zhu & Fang (2019)	72.2%	11.2%	4.52	30.3	0.190
	R4D (**ours**)	77.0% (+4.8%)	9.6% (-1.6%)	3.71 (-0.81)	27.8 (-2.5)	0.171 (-0.019)
Dawn & Dusk	Zhu & Fang (2019)	63.8%	13.6%	6.48	36.4	0.233
	R4D (**ours**)	70.0% (+6.2%)	11.3% (-2.3%)	4.19 (-2.29)	28.5 (-7.9)	0.177 (-0.056)
Night	Zhu & Fang (2019)	36.8%	23.3%	12.5	46.8	0.344
	R4D (**ours**)	49.1% (**+12.3%**)	17.7% (**-5.6%**)	8.2 (**-4.38**)	38.4 (**-8.4**)	0.267 (**-0.077**)

Table 5: Robustness on out-of-distribution data. Both R4D and the baseline (Zhu & Fang, 2019) are trained on daytime images only, and evaluated on three test sets collected during different times of day. The performance improvement of R4D increases when the domain gap is larger.

As shown in Table 4, randomly choosing one reference (row 3) and predicting the distance using relative distance achieves a $< 10\%\uparrow$ of 58.8%, outperforming the baseline (Zhu & Fang, 2019) which directly predicts the absolute distance (row 1 with a $< 10\%\uparrow$ of 55.6%). Combining the absolute and relative heads during training (row 5) further improves the $< 10\%\uparrow$ metric by 4.3% (achieving a $< 10\%\uparrow$ metric of 59.9%). Finally, this improvement is the largest when multiple references are aggregated using the attention module (row 8), resulting in a $< 10\%\uparrow$ of 63.3%.

Distance augmentation. As described in Section 5.1, we propose the distance augmentation strategy to encourage R4D to learn better pairwise relationships during training. Table 4 shows the results from ablation experiments related to distance augmentation. The distance augmentation is only critical for our final model R4D, which (1) includes both absolute and relative distance prediction heads, and (2) considers *multiple* reference objects. Without distance augmentation (row 7), the model does not learn pairwise relationships, and the performance of R4D's absolute distance head drops to the baseline's performance (row 1). In fact, when at most one reference is used during training (Zhu & Fang (2019), R4D-Relative, and R4D-One-Ref), the proposed distance augmentation marginally affects the performance. Our intuition is that the one- or zero-reference cases require less supervision and data diversity due to the simpler input and model structures.

5.4 ROBUSTNESS ON OUT-OF-DISTRIBUTION DATA

For safety-critical applications, such as autonomous driving, the ability to handle out-of-distribution (OOD) data is crucial (Vyas et al., 2018). We expect R4D to be more robust on OOD data because it captures contextual information, in addition to appearance and geometry cues. In contrast, baseline methods (Zhu & Fang, 2019) use a single prediction cue, thus rendering them more sensitive to appearance changes. To validate the robustness on OOD data, we train our model solely on images captured during daytime, but evaluate on three different times of day, namely: daytime, dawn/dusk, and night-time. Specifically, we split the anonymous internal long-range dataset into four disjoint sets: *train-day* (used for training), and *val-day*, *val-dawn&dusk*, *val-night* (used for validation). The results of this experiment are shown in Table 5. Compared to the baseline method (Zhu & Fang, 2019), R4D achieves a larger improvement when the domain gap between the training and validation sets is larger. For example, when evaluating on daytime (small domain gap) and night-time (large domain gap), R4D achieves an Abs Rel$\downarrow$ metric improvement of 1.6% and 5.6%, respectively.

6 CONCLUSION

In this paper, we present an underexplored task, long-range distance estimation, as well as two datasets for it. We then introduced R4D, a novel approach to address this problem. Our method can accurately localize long-range objects using references with known distances in the scene. Experiments on two proposed datasets demonstrate that it significantly outperforms prior solutions and achieves state of the art long-range distance estimation performance. It should also be noted that R4D is not specifically designed for LiDAR or monocular images and is readily extended to other sensors and references, such as features from high-definition maps. It can also be used to incorporate temporal information by fusing past object detections as references, which is a direction we hope to explore to further improve the long-range distance estimation performance.

REFERENCES

Federal Motor Carrier Safety Administration. Long stopping distances, Federal Motor Carrier Safety Administration. https://www.fmcsa.dot.gov/ourroads/long-stopping-distances, 2016. Accessed: Sep-09-2021.

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

Myra Blanco and Jonathan M Hankey. Visual performance during nighttime driving in fog. Technical report, FHWA-HRT-04-137, 2005.

William L Briggs, Van Emden Henson, and Steve F McCormick. *A multigrid tutorial*. SIAM, 2000.

Holger Caesar, Varun Bankiti, Alex H. Lang, Sourabh Vora, Venice Erin Liong, Qiang Xu, Anush Krishnan, Yu Pan, Giancarlo Baldan, and Oscar Beijbom. nuScenes: A multimodal dataset for autonomous driving. *arXiv preprint arXiv:1903.11027*, 2019.

Yongjian Chen, Lei Tai, Kai Sun, and Mingyang Li. Monopair: Monocular 3D object detection using pairwise spatial relationships. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

Antonio Criminisi, Ian Reid, and Andrew Zisserman. Single view metrology. *International Journal of Computer Vision (IJCV)*, 40(2):123–148, 2000.

Harris Drucker, Christopher JC Burges, Linda Kaufman, Alex J Smola, and Vladimir Vapnik. Support vector regression machines. In *Advances in Neural Information Processing Systems (NeurIPS)*, 1997.

David Eigen, Christian Puhrsch, and Rob Fergus. Depth map prediction from a single image using a multi-scale deep network. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2014.

Jiyang Gao, Chen Sun, Hang Zhao, Yi Shen, Dragomir Anguelov, Congcong Li, and Cordelia Schmid. VectorNet: Encoding HD maps and agent dynamics from vectorized representation. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

Ravi Garg, Vijay Kumar Bg, Gustavo Carneiro, and Ian Reid. Unsupervised CNN for single view depth estimation: Geometry to the rescue. In *European Conference on Computer Vision (ECCV)*, 2016.

Andreas Geiger, Philip Lenz, Christoph Stiller, and Raquel Urtasun. Vision meets robotics: The KITTI dataset. *International Journal of Robotics Research (IJRR)*, 2013.

Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel, Matthias Bethge, and Felix A Wichmann. Shortcut learning in deep neural networks. *arXiv preprint arXiv:2004.07780*, 2020.

Ross Girshick. Fast R-CNN. In *International Conference on Computer Vision (ICCV)*, 2015.

Clément Godard, Oisin Mac Aodha, Michael Firman, and Gabriel J Brostow. Digging into self-supervised monocular depth estimation. In *International Conference on Computer Vision (ICCV)*, 2019.

Fatih Gökçe, Göktürk Üçoluk, Erol Şahin, and Sinan Kalkan. Vision-based detection and distance estimation of micro unmanned aerial vehicles. *Sensors*, 15(9):23805–23846, 2015.

Priya Goyal, Piotr Dollár, Ross Girshick, Pieter Noordhuis, Lukasz Wesolowski, Aapo Kyrola, Andrew Tulloch, Yangqing Jia, and Kaiming He. Accurate, large minibatch SGD: Training ImageNet in 1 hour. *arXiv preprint arXiv:1706.02677*, 2017.

Carl E Granrud, Albert Yonas, and Linda Pettersen. A comparison of monocular and binocular depth perception in 5-and 7-month-old infants. *Journal of Experimental Child Psychology*, 38(1):19–32, 1984.

Muhammad Abdul Haseeb, Jianyu Guan, Danijela Ristić-Durrant, and Axel Gräser. DisNet: A novel method for distance estimation from monocular camera. *10th Planning, Perception and Navigation for Intelligent Vehicles (PPNIV18), IROS*, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask R-CNN. In *International Conference on Computer Vision (ICCV)*, 2017.

Peter J Huber. Robust estimation of a location parameter. In *Breakthroughs in statistics*, pp. 492–518. Springer, 1992.

Satish Jeyachandran. Waymo's 5th Generation Self-Driving LiDAR. https://blog.waymo.com/2020/03/introducing-5th-generation-waymo-driver.html, 2020. Accessed: Sep-09-2021.

Sameh Khamis, Sean Fanello, Christoph Rhemann, Adarsh Kowdle, Julien Valentin, and Shahram Izadi. Stereonet: Guided hierarchical refinement for real-time edge-aware depth prediction. In *European Conference on Computer Vision (ECCV)*, 2018.

Jae-Han Lee and Chang-Su Kim. Monocular depth estimation using relative depth maps. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

Peixuan Li, Huaici Zhao, Pengfei Liu, and Feidao Cao. Rtm3d: Real-time monocular 3d detection from object keypoints for autonomous driving. In *European Conference on Computer Vision (ECCV)*, 2020.

Yingwei Li, Qihang Yu, Mingxing Tan, Jieru Mei, Peng Tang, Wei Shen, Alan Yuille, and Cihang Xie. Shape-texture debiased neural network training. In *International Conference on Learning Representations*, 2021.

Fayao Liu, Chunhua Shen, Guosheng Lin, and Ian Reid. Learning depth from single monocular images using deep convolutional neural fields. *IEEE Transactions on Pattern Analysis and Machine Intelligence (PAMI)*, 38(10):2024–2039, 2015.

Zechen Liu, Zizhang Wu, and Roland Tóth. SMOKE: Single-stage monocular 3D object detection via keypoint estimation. In *Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2020.

Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. In *ICLR*, 2017.

Vinod Nair and Geoffrey E Hinton. Rectified linear units improve restricted Boltzmann machines. In *International Conference on Machine Learning (ICML)*, 2010.

Matteo Poggi, Davide Pallotti, Fabio Tosi, and Stefano Mattoccia. Guided stereo matching. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

SH Qi, J Li, ZP Sun, JT Zhang, and Y Sun. Distance estimation of monocular based on vehicle pose information. In *J. Phys., Conf. Ser.*, 2019.

Nicolas Scheiner, Florian Kraus, Fangyin Wei, Buu Phan, Fahim Mannan, Nils Appenrodt, Werner Ritter, Jurgen Dickmann, Klaus Dietmayer, Bernhard Sick, et al. Seeing around street corners: Non-line-of-sight detection and tracking in-the-wild using doppler radar. In *Conference on Computer Vision and Pattern Recognition*, 2020.

Shaoshuai Shi, Xiaogang Wang, and Hongsheng Li. Pointrcnn: 3d object proposal generation and detection from point cloud. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

Chang Shu, Kun Yu, Zhixiang Duan, and Kuiyuan Yang. Feature-metric loss for self-supervised learning of depth and egomotion. In *European Conference on Computer Vision (ECCV)*, 2020.

Z. Song, J. Lu, T. Zhang, and H. Li. End-to-end learning for inter-vehicle distance and relative velocity estimation in adas with a monocular camera. In *International Conference on Robotics and Automation (ICRA)*, 2020.

Richard Szeliski. Fast surface interpolation using hierarchical basis functions. *IEEE Transactions on Pattern Analysis and Machine Intelligence (PAMI)*, 12(6):513–528, 1990.

Richard Szeliski. Locally adapted hierarchical basis preconditioning. *ACM Transactions on Graphics (TOG)*, 25(3):1135–1143, 2006.

S Tuohy, D O'Cualain, E Jones, and M Glavin. Distance determination for an automobile environment using inverse perspective mapping in opencv. In *IET Irish Signals and Systems Conference (ISSC)*, 2010.

VelodyneLidar. Alpha Prime™. https://velodynelidar.com/products/alpha-prime/, 2021. Accessed: Sep-09-2021.

Apoorv Vyas, Nataraj Jammalamadaka, Xia Zhu, Dipankar Das, Bharat Kaul, and Theodore L Willke. Out-of-distribution detection using an ensemble of self supervised leave-out classifiers. In *European Conference on Computer Vision (ECCV)*, 2018.

Weiyao Wang, Du Tran, and Matt Feiszli. What makes training multi-modal classification networks hard? In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

Ting Yao, Yingwei Pan, Yehao Li, and Tao Mei. Exploring visual relationship for image captioning. In *European Conference on Computer Vision (ECCV)*, 2018.

Kai Zhang, Jiaxin Xie, Noah Snavely, and Qifeng Chen. Depth sensing beyond LiDAR range. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

Yin Zhou, Pei Sun, Yu Zhang, Dragomir Anguelov, Jiyang Gao, Tom Ouyang, James Guo, Jiquan Ngiam, and Vijay Vasudevan. End-to-end multi-view fusion for 3D object detection in LiDAR point clouds. In *Conference on Robot Learning*, 2020.

Jing Zhu and Yi Fang. Learning object-specific distance from a monocular image. In *International Conference on Computer Vision (ICCV)*, 2019.

A IMPLEMENTATION DETAILS

We use ResNet-50 (He et al., 2016) followed by an ROIAlign layer (He et al., 2017) to extract target, reference, and union embeddings. We then apply a fully connected layer to each embedding to reduce the feature dimension to 1,024. We use a three-layer perceptron to extract geo-distance embeddings. Each layer contains a single fully connected layer followed by layer normalization (Ba et al., 2016) and ReLU (Nair & Hinton, 2010). For the attention module, we use the two-layer subgraph propagation operation mentioned in VectorNet (Gao et al., 2020) as the Global-Local Embedding Fusion depicted in Figure 4 in the main submission, and replace the max pooling layer with average pooling. The reference objects are detected using a multi-view fusion 3D object detector (Zhou et al., 2020) with 72.1 3D AP (L1). When there is no reference object in an image (0.6% of the images), we disable the relative distance supervision. We use smooth L1 (Huber, 1992) as the loss function (Zhu & Fang, 2019). We train R4D on an 8-core TPU with a total batch size of 32 images for 24 epochs. The learning rate is initially set to 0.0005 and then decays by a factor of 10 at the 16th and 22nd epochs. We warm up (Goyal et al., 2017) the learning rate for 1,800 iterations. We initialize the weights from a ResNet-50 model pretrained on ImageNet (He et al., 2016). For the pseudo long-range KITTI dataset, we train over 150 epochs with an initial learning rate of 0.005 and cosine learning rate decay (Loshchilov & Hutter, 2017).

DistAug	σ	$< 5\%\uparrow$	$< 10\%\uparrow$	$< 15\%\uparrow$	Abs Rel$\downarrow$	Sq Rel$\downarrow$	RMSE$\downarrow$	RMSE$_{\log}\downarrow$
✗	N/A	32.0%	54.1%	70.9%	11.1%	4.30	29.3	0.187
✓	1	32.8%	56.5%	71.9%	11.0%	4.32	29.2	0.186
✓	2	32.6%	54.9%	71.6%	10.9%	4.13	28.7	0.182
✓	5	32.4%	55.0%	71.0%	11.2%	4.44	29.8	0.189
✓	10	33.9%	56.8%	73.3%	10.7%	4.18	29.0	0.183
✓	20	35.7%	58.1%	73.4%	10.3%	3.89	28.0	0.175
✓	50	36.6%	59.5%	75.1%	10.2%	3.91	28.1	0.175
✓	100	34.6%	58.3%	75.0%	10.4%	3.91	28.0	0.176
✓	150	37.5%	62.1%	76.6%	9.9%	**3.61**	**26.8**	**0.167**
✓	200	37.5%	**63.3%**	**78.6%**	**9.8%**	3.64	26.9	0.169
✓	250	**38.3%**	61.0%	75.2%	10.1%	3.79	27.5	0.173
✓	300	37.2%	60.7%	75.6%	10.1%	3.77	27.4	0.171

Table 6: Hyper-parameter sensitivity of distance augmentation.

Method	#Ref	$< 5\%\uparrow$	$< 10\%\uparrow$	$< 15\%\uparrow$	Abs Rel$\downarrow$	Sq Rel$\downarrow$	RMSE$\downarrow$	RMSE$_{\log}\downarrow$	T (ms)$\downarrow$
Zhu & Fang (2019)	0	32.0%	54.1%	70.9%	11.1%	4.30	29.3	0.187	**15.0**
R4D(**ours**)	1	35.0%	60.7%	76.0%	10.4%	3.93	27.9	0.175	15.2
R4D(**ours**)	2	37.0%	62.4%	77.5%	10.0%	3.83	27.7	0.174	15.5
R4D(**ours**)	5	37.2%	63.3%	78.4%	**9.8%**	3.68	27.1	0.170	15.6
R4D(**ours**)	10	37.3%	**63.7%**	78.5%	**9.8%**	3.66	27.0	**0.169**	16.3
R4D(**ours**)	20	37.4%	63.4%	78.5%	**9.8%**	**3.64**	**26.9**	**0.169**	17.0
R4D(**ours**)	50	**37.5%**	63.3%	**78.6%**	**9.8%**	**3.64**	**26.9**	**0.169**	20.3

Table 7: Effect of the maximum number of references (#Ref) on distance estimation performance and inference latency (T).

B HYPER-PARAMETER SENSITIVITY: DISTANCE AUGMENTATION

In this section, we show how the performance of R4D varies with the distance augmentation hyper-parameter σ. In our final model, we perturbed the ground-truth distances of target and reference objects by a Gaussian random variable with distribution $X \sim \mathcal{N}(\mu, \sigma^2)$ with $\mu = 0$ and $\sigma = 200$. In Table 6, we show the performance of our method for different values of σ ranging from 1 to 300. We observe that the proposed distance augmentation consistently improves the performance of R4D for all values of σ. The model reaches its optimal performance when σ is around 200.

C INFERENCE LATENCY AND NUMBER OF REFERENCES

In the main draft, we set the maximum number of references to 50. In this section, we show the performance and inference time of our method when we vary the maximum number of references. We draw two conclusions from the results (in Table 7). First, more references lead to better results. For example, we observe the with a maximum of 2 reference objects, the $< 5\%\uparrow$ metric improves by 2% (from 35.0% to 37.0%) compared to using a single reference object. In addition, when the number of references is large (say, 5), the benefit of using additional reference objects is marginal. For example, we observe that the $< 5\%\uparrow$ metric increases by only 0.3% (from 37.2% to 37.5%) when the maximum number of references is increased from 5 to 50. Finally, and as expected, the latency increases with the number of reference objects. However, this increase is not significant when using a relatively small number of references. For example, when we increase the maximum number of references from 1 to 5, the latency only increases by 0.6 ms, while the $< 10\%\uparrow$ metric improves by 9.2%.

D PSEUDO LONG-RANGE NUSCENES DATASET

We further provide another derived pseudo long-rang dataset, *Pseudo Long-Range nuScenes Dataset*, and the experimental results on it. Although we prove several derived pseudo long-range datasets, we still encourage readers to focus more on our anonymous internal long-range dataset.

Method	LiDAR	< 5%↑	< 10%↑	< 15%↑	Abs Rel↓	Sq Rel↓	RMSE↓	RMSE$_{log}$↓
SVR	✗	33.0%	58.0%	74.0%	10.9%	1.56	10.7	0.166
DisNet	✗	29.5%	58.6%	75.0%	10.7%	1.46	10.5	0.162
Zhu & Fang (2019)	✗	40.3%	66.7%	80.3%	8.4%	0.91	8.6	0.121
Zhu & Fang (2019)	✓	37.7%	63.5%	77.2%	9.2%	1.06	9.2	0.132
R4D (**ours**)	✓	**44.2%**	**71.1%**	**84.6%**	**7.6%**	**0.75**	**7.7**	**0.110**

Table 8: Results on the pseudo long-range nuScenes Dataset. R4D outperforms SVR (Gökçe et al., 2015), DisNet (Haseeb et al., 2018), and Zhu & Fang (2019).

Method	LiDAR	< 5%↑	< 10%↑	< 15%↑	Abs Rel↓	Sq Rel↓	RMSE↓	RMSE$_{log}$↓
SMOKE	✗	42.4%	70.5%	83.3%	10.3%	1.98	10.6	0.145
RTM3D	✗	42.7%	71.1%	**83.9%**	9.8%	1.75	9.9	0.135
R4D (**ours**)	✓	**46.3%**	**72.5%**	**83.9%**	**7.5%**	**0.68**	**6.8**	**0.112**

Table 9: Compare with monocular 3D object detection methods on pseudo long-range KITTI dataset. R4D outperforms SMOKE (Liu et al., 2020), and RTM3D (Li et al., 2020).

The proposed anonymous internal long-range dataset is a large-scale dataset with annotation for *real* long-range objects, which aligns better with the real-world scenario.

To construct pseudo long-range nuScenes dataset, we first export the original nuScenes dataset to KITTI format by the nuScenes offical code[1]. Then we reuse the pipeline that builds the pseudo long-range KITTI dataset. The final pseudo long-range nuScenes dataset includes 18,926 training images with target 59,800 vehicles, and 4,017 validation images with 11,737 target vehicles.

The results are shown in Table 8. R4D outperforms all baselines with a large margin. For example, with R4D, Zhu & Fang (2019) (line 3) improves by 4.4% on the < 10%↑ metric (from 66.7% to 71.1%). By comparing line 3 with line 4, we observe the performance drop when appending the LiDAR points as an additional input channel to Zhu & Fang (2019). This observation also supports our conclusion in the main manuscript, the additional distance channel does not help to improve the distance estimation performance. The observation here is even more obvious, because the original nuScenes dataset only provides relative low resolution (32 beams, while KITTI dataset is 64 beams) LiDAR signals (Caesar et al., 2019).

E COMPARE WITH MONOCULAR 3D OBJECT DETECTORS

In the related work section of the main manuscript, we have discussed the relationship between our proposed task, namely Long-Range Distance Estimation, and monocular 3D object detection. Here, we conduct experiments to compare R4D to monocular 3D detection methods on pseudo long-range KITTI dataset. We associate the detected 3D bounding boxes with 2D ground-truth boxes using a bipartite matching algorithm. The weights of the bipartite graph are the 2D IoUs of ground-truth and detected boxes. In order to compare with our method, we calculate the distance prediction metrics on matched ground-truth and detected box pairs.

As shown in Table 9, R4D outperforms SOTA 3D object detectors on the distance prediction task. For example, on the < 5%↑ metric, R4D improves 3.6% (from 42.7% to 46.3%) compared with previous state-of-the-art monocular 3D object detector RMT3D (Li et al., 2020). This improvement is more significant than the improvement from SMOKE (Liu et al., 2020) to RTM3D (Li et al., 2020) (only improves 0.3% on the < 5%↑ metric) due to R4D utilizing the short-range LiDAR signals. It is also worth noting that R4D does not utilized the techniques proposed in other monocular 3D object detection papers such as multi-task training and strong architectures. Therefore, R4D is complementary to 3D detection methods, and combining it with such methods will further improve the long-range distance estimation performance.

---

[1]https://github.com/nutonomy/nuscenes-devkit/blob/master/python-sdk/nuscenes/scripts/export_kitti.py

Valid. Set	Tgt	Ref	Uni	G-D	DA	< 15%↑	**Abs Rel**↓	Sq Rel↓	RMSE↓	RMSE$_{log}$↓
Day	✓	✗	✗	✗	✗	72.2%	11.2%	4.52	30.3	0.190
	✓	✓	✗	✗	✓	70.2% (-2.0%)	11.2%	4.60 (+0.08)	30.8 (+0.5)	0.191 (+0.001)
	✓	✓	✓	✗	✓	73.1% (+0.9%)	10.3% (-0.9%)	4.03 (-0.49)	28.9 (-1.4)	0.178 (-0.012)
	✓	✓	✓	✓	✗	71.5% (-0.7%)	10.7% (-0.5%)	4.31 (-0.21)	29.8 (-0.5)	0.184 (-0.006)
	✓	✓	✓	✓	✓	77.0% (+4.8%)	9.6% (-1.6%)	3.71 (-0.81)	27.8 (-2.5)	0.171 (-0.019)
Dawn &	✓	✗	✗	✗	✗	63.8%	13.6%	6.48	36.4	0.233
	✓	✓	✗	✗	✓	62.5% (-1.3%)	13.5% (-0.1%)	6.05 (-0.43)	34.7 (-1.7)	0.224 (-0.009)
	✓	✓	✓	✗	✓	64.1% (+0.3%)	13.5% (-0.1%)	6.38 (-0.10)	36.1 (-0.4)	0.231 (-0.002)
	✓	✓	✓	✓	✗	64.3% (+0.5%)	12.8% (-0.8%)	5.41 (-1.07)	33.0 (-3.4)	0.206 (-0.027)
Dusk	✓	✓	✓	✓	✓	70.0% (+6.2%)	11.3% (-2.3%)	4.19 (-2.29)	28.5 (-7.9)	0.177 (-0.056)
Night	✓	✗	✗	✗	✗	36.8%	23.3%	12.5	46.8	0.344
	✓	✓	✗	✗	✓	36.2% (-0.6%)	22.9% (-0.4%)	11.9 (-0.6)	45.7 (-1.1)	0.335 (-0.009)
	✓	✓	✓	✗	✓	36.7% (-0.1%)	22.6% (-0.7%)	12.0 (-0.5)	46.3 (-0.5)	0.340 (-0.004)
	✓	✓	✓	✓	✗	49.1% (+12.3%)	17.5% (-5.8%)	8.2 (-4.3)	38.7 (-8.1)	0.271 (-0.073)
	✓	✓	✓	✓	✓	49.1% (+12.3%)	17.7% (-5.6%)	8.2 (-4.3)	38.4 (-8.4)	0.267 (-0.077)

Table 10: Robustness on out-of-distribution data. All models are trained on daytime images only, and evaluated on three test sets collected during different times of day. We evaluate each components from R4D, *i.e.*, the target embeddings (Tgt), the reference embeddings (Ref), the union embeddings (Uni), the geo-distance embeddings (G-D), and distance augmentation (DA).

F MORE QUALITATIVE EXAMPLES ON ANONYMOUS INTERNAL LONG-RANGE DATASET

We also provide more qualitative examples of the output of the attention module in the supplemental material (please download the zip file). All images are from our proposed anonymous internal long-range dataset. Similar to Figure 8 in the main manuscript, the target objects are highlighted in yellow. References with the largest attention weights are highlighted in red. Other references are colored in blue. As before, we observe that the most important references are often close to or in the same lane as the target, and share a similar pose.

Method	Occlusion	< 5%↑	< 10%↑	< 15%↑	Abs Rel↓	Sq Rel↓	RMSE↓	RMSE$_{log}$↓
Zhu & Fang (2019)	✗	31.2%	53.4%	68.7%	11.5%	4.43	29.4	0.187
Zhu & Fang (2019)	✓	26.2%	44.8%	59.6%	13.8%	5.71	33.0	0.212
R4D (ours)	✗	38.5%	62.3%	77.1%	9.8%	3.60	26.7	0.167
R4D (ours)	✓	29.3%	51.6%	67.5%	11.9%	4.44	29.0	0.184

Table 11: Robustness against occlusion.

G UNDERSTANDING DISTANCE AUGMENTATION

In this section, from a view of optimization, we illustrate that the objective functions of training the baseline model (Zhu & Fang, 2019) are similar when applying or not applying the distance augmentation. Intuitively, since the distance augmentation we used has zero mean ($\mu = 0$ in the Gaussian distribution), the well-trained models predict unbiased distance. Our observation from the first two lines in Table 4 also support our intuition: the performance of the baseline models (Zhu & Fang, 2019) is similar no matter with or without distance augmentation. In the rest part of this section, we explain this intuition with language of mathematics.

When not applying distance augmentation, the goal of the training procedure is to get the optimal network parameters Θ that can minimize the loss function, *i.e.*,

$$\Theta = \arg\min_{\theta} \|f(X;\theta) - Y\|^2, \tag{2}$$

where f is a deep neural network with parameters θ; X is the inputs of the dataset while Y is the distance labels of the dataset. Even though complex loss function can be applied, here we compute the total distance loss over the whole training dataset via L2 norm ($\|\cdot\|^2$) for simplicity.

In contrast, with distance augmentation, the equation about getting the optimal network parameters Θ is

$$\Theta = \arg\min_{\theta} \frac{1}{n} \sum_{i=0}^{n} \|f(X;\theta) - Y_i\|^2, \tag{3}$$

where n is the total number of training epochs, and each $(Y_i)_j$ is sampled independently from Gaussian distribution $N(y_j, \sigma)$, where y_j is the original ground-truth label for j-th input data. Given the optimization objective with and without distance augmentation as equation 3 and equation 2, we argue they are intrinsically same when $n \to \infty$, as shown below.

$$
\begin{aligned}
&\arg\min_{\theta} \frac{1}{n} \sum_{i=0}^{n-1} \|f(X;\theta) - Y_i\|^2 \\
&= \arg\min_{\theta} \frac{1}{n} \sum_{i=0}^{n-1} (\|f(X;\theta)\|^2 - 2\langle f(X;\theta), Y_i\rangle + \|Y_i\|^2) \\
&= \arg\min_{\theta} \frac{1}{n} \sum_{i=0}^{n-1} \|f(X;\theta)\|^2 - 2\Big\langle f(X;\theta), \frac{1}{n}\sum_{i=0}^{n-1} Y_i\Big\rangle + \frac{1}{n}\sum_{i=0}^{n-1} \|Y_i\|^2 \\
&= \arg\min_{\theta} \frac{1}{n} \sum_{i=0}^{n-1} \|f(X;\theta)\|^2 - 2\Big\langle f(X;\theta), \frac{1}{n}\sum_{i=0}^{n-1} Y_i\Big\rangle \\
&= \arg\min_{\theta} \|f(X;\theta)\|^2 - 2\langle f(X;\theta), Y\rangle \\
&= \arg\min_{\theta} \|f(X;\theta)\|^2 - 2\langle f(X;\theta), Y\rangle + \|Y\|^2 \\
&= \arg\min_{\theta} \|f(X;\theta) - Y\|^2
\end{aligned}
\tag{4}
$$

where the first two steps follow from basic algebra, the third step follows from dropping the constant term from $\arg\min$, the forth step follows from Gaussian concentration (n is large), the fifth step follows from adding a constant term.

To summarize, we show that using or not using distance augmentation does not significantly influence the well-trained baseline models (Zhu & Fang, 2019), which is supported by our math proof and the experimental results in Table 4 line 1-2.

H ABLATION STUDIES ON OUT-OF-DISTRIBUTION DATA

In Section 5.4, we demonstrate the robustness of R4D on Out-Of-Distribution data. In this section, we study the impact of each component of our proposed R4D on anonymous internal long-range. The results are shown in Table 10. The observation is similar to our observation on the standard validation set (Section 5.3): each component incurs marginal improvement on model robustness, and only when using all of these components together, a significant improvement can be observed. For example, before applying Geo-distance embedding, the improvement on Night set is only 0.7% Abs Rel↓, while the final R4D model improves 5.6% Abs Rel↓. Another interesting observation is about distance augmentation: the model without distance augmentation does not perform well on the Day Set, but perform as well as the model with distance augmentation on the Night Set. We hypothesis this is because the appearance information for night scene are not discriminative enough, so both models rely more on the geometry information. We will further investigate this in the future.

I ROBUSTNESS AGAINST REFERENCE BOXES PERTURBATION

The goal of this section is to demonstrate how robust R4D is with respect to the noise of the input 2D bounding boxes and the object distance provided by the 3D detector. We conduct ablation studies by perturbing the 2D reference boxes (with a maximum magnitude of 15% of the box size) or the distance of the reference objects (with a maximum magnitude of 15% of the original distance). The

results are shown in Table 12 and Table 13. We found that even with significant noise (*i.e.*, 15%), the performance of our model still significantly outperformed our baseline model (Zhu & Fang, 2019). For example, in Table 13, even though with 15% noises, R4D is still 4.3% < 15%↑ better than the baseline method (Zhu & Fang, 2019).

Method	Noise Level	< 5%↑	< 10%↑	< 15%↑	Abs Rel↓	Sq Rel↓	RMSE↓	RMSE$_{log}$↓
R4D (ours)	0%	38.5%	62.3%	77.1%	9.8%	3.60	26.7	0.167
R4D (ours)	15%	36.7%	59.8%	74.9%	10.2%	3.79	27.4	0.172
Zhu & Fang (2019)	N/A	31.2%	53.4%	68.7%	11.5%	4.43	29.4	0.187

Table 12: Noise on reference input 2D bounding boxes. We perturb the location and the size of reference 2D boxes, and then test the performance of R4D. Although slightly observing performance drop after adding noise, R4D is still better than the baseline method (Zhu & Fang, 2019).

Method	Noise Level	< 5%↑	< 10%↑	< 15%↑	Abs Rel↓	Sq Rel↓	RMSE↓	RMSE$_{log}$↓
R4D (ours)	0%	38.5%	62.3%	77.1%	9.8%	3.60	26.7	0.167
R4D (ours)	15%	37.8%	60.1%	74.2%	10.2%	3.82	27.5	0.172
Zhu & Fang (2019)	N/A	31.2%	53.4%	68.7%	11.5%	4.43	29.4	0.187

Table 13: Noise on object distance provided by the 3D detector. We perturb distance of reference 3D boxes, and then test the performance of R4D. Although slightly observing performance drop after adding noise, R4D is still better than the baseline method (Zhu & Fang, 2019).

Method	LiDAR	< 5%↑	< 10%↑	< 15%↑	Abs Rel↓	Sq Rel↓	RMSE↓	RMSE$_{log}$↓
Zhu & Fang (2019)	✗	31.2%	53.4%	68.7%	11.5%	4.43	29.4	0.187
Zhu & Fang (2019)	✓	34.1%	56.4%	70.5%	11.3%	4.78	31.3	0.194
R4D (ours)	✗	35.1%	60.1%	76.1%	10.4%	3.81	27.2	0.172
R4D (ours)	✓	38.5%	62.3%	77.1%	9.8%	3.60	26.7	0.167

Table 14: Results comparison on the anonymous internal long-range. We compare the baseline (Zhu & Fang, 2019) and R4D with and without LiDAR signals. For R4D, when LiDAR signal is missing, we train a monocular depth estimator (Zhu & Fang, 2019) on the short range objects, and then predict the distance for short-range objects as references.

J   COMPARE WITH BASELINE WITH A PURE IMAGE-BASED SETTING

To demonstrate the potential of the concept of using reference object for depth estimation, in this section, we conduct experiment in a purely image-based setting in which the depth for of the reference object is generated by a monocular depth estimation model. Specifically, we use the monocular method proposed by (Zhu & Fang, 2019) to generate short range distance (with 8.14% absolute relative error for short-range objects).

As shown in Table 14, in a purely image based setting, our model significantly outperforms the baseline models. The results confirms the effectiveness of our purposed reference-based method.