Evolution of Neural Tangent Kernels under Benign and Adversarial Training

Abstract

Two key challenges facing modern deep learning is mitigating deep networks vulnerability to adversarial attacks, and understanding deep learning's generalization capabilities. Towards the first issue, many defense strategies have been developed, with the most common being Adversarial Training (AT). Towards the second challenge, one of the dominant theories that has emerged is the Neural Tangent Kernel (NTK) – a characterization of neural network behavior in the infinite-width limit. In this limit, the kernel is frozen and the underlying feature map is fixed. In finite-widths however, there is evidence that feature learning happens at the earlier stages of the training (kernel learning) before a second phase where the kernel remains fixed (lazy training). While prior work has aimed at studying adversarial vulnerability through the lens of the frozen infinite-width NTK, there is no work which studies adversarial robustness of NTK during training. In this work, we perform an empirical study of the evolution of the NTK under standard and adversarial training, aiming to disambiguate the effect of adversarial training on kernel learning and lazy training. We find under adversarial training, the NTK rapidly converges to a different kernel (and feature map) than standard training. This new kernel provides adversarial robustness, even when non-robust training is performed on top of it. Furthermore, we find that adversarial training on top of a fixed kernel can yield a classifier with 76.1% robust accuracy under PGD attacks with $\varepsilon = 4/255$ on CIFAR-10.

1 Introduction

Modern deep learning, while effective on tackling clean, curated datasets, is often very brittle to domain and distribution shifts [61]. Perhaps the most notorious failure mode of deep learning to domain shifts is adversarial examples [58]: images with small, bounded, perturbations which consistently fool state-of-the-art classifiers. While work has been dedicated to mitigating [22, 15, 39], explaining [21, 31, 29], and harnessing [51, 42, 52] this peculiar behavior, the problem still remains largely open, with the state-of-the-art robust classifiers still falling far behind in benign accuracy compared to standard non-robust networks [15]. Indeed, tackling this idiosyncrasy of deep learning seems almost impossible given that the behavior of deep models under benign data and training is still largely unexplained [10, 47, 48], let alone adversarial training.

The community has tried developed numerous theories on better understanding deep learning [59, 3, 30, 49, 11]. One emerging theory is the notion of deep learning as kernel learners [37, 18, 1]. That is, deep networks trained with gradient descent learn a kernel, whose feature map is embedded in the tangent space of the network outputs with respective to its parameters. After a brief phase of

kernel learning, neural networks behave similar to *lazy learners*, i.e., linear and slow in this neural tangent feature map. This two-stage theory of deep learning has been observed in vision networks such as residual networks [25] used in practice, and has been the subject of much recent empirical [56, 37, 18, 5] and theoretical works [24, 27, 2]. While these reports have verified this theory for benign training, no work has looked at this property at the intersection of adversarial training. To this end, here, we perform the first empirical study of how the neural tangent kernel evolves over the course of adversarial training. In Sec. 3, we present our experimental setup designed to isolate the effect of adversarial training on the two stage of deep learning under the kernel learner theory: 1) kernel learning and 2) linear fitting. By using this framework, we study and show the following:

1. Similar to standard training, adversarial training results in a distinct kernel which quickly converges in the first few epochs of training (Sec. 3) 2. **Adversarial robustness can be inherited from the kernel made from adversarial training**, even when the second stage classifier has **no access to adversarial examples** during training (Sec. 4). 3. Adversarial training is effective on top of the learned kernels given by standard training (in the frozen feature regime), providing a testbed where many of the fixed-feature assumptions present in theoretical works on adversarial training are met, while still providing high practical performance (Sec. 7). 4. Eigenvectors in the learned NTK of networks with adversarial training contained visually interpretable features, while the initial NTK and benign training NTK do not (Sec. 8).

Background and Related Works

Neural Tangent Kernel. Explaining the empirical success of deep learning models from a theoretical stand point is an exciting and active line of research which is still in its infancy. One of the most popular tools for understanding neural network behavior is the neural tangent kernel (NTK) [30, 4]. Under this theory training deep networks with gradient descent in the infinite-width limit corresponds to training training a kernel-based classifier, with the corresponding kernel being the NTK defined as $k_{NTK}(x, x') = \mathbb{E}_{\theta \sim p(\theta)}[\nabla_\theta f(x)^T \nabla_\theta f(x')]$, for parameter distribution $p(\theta)$ and network architecture f_θ. Analogously, training an infinite width Bayesian neural network corresponds to Gaussian process regression using the NNGP kernel [43, 20, 34, 40, 44]. In both these infinite-width limits, the underlying feature space is fixed, determined entirely by the architecture and parameter distribution.

The frozen nature of the kernel stands in contradiction to the ability of deep models to learn useful features and representations. Indeed, it has been shown theoretically, under different limiting assumptions, or with finite-widths, that feature learning does occur, with a time evolving and data-dependent kernel, $k_t(x, x') = \nabla_{\theta_t} f_{\theta_t}(x)^T \nabla_{\theta_t} f_{\theta_t}(x')$, with time dependent network parameters θ_t [62, 24, 27, 2]. This learned NTK aligns itself with dataset labels to accelerate training and improve generalization. Empirical evidence supports this, with works finding that this meta-kernel evolves quickly within the early stages of network training, before stabilizing [37, 18, 5, 56]. In this new setting, there exists two stages in deep network training: 1) *kernel learning* and 2) *linear fitting*. In the first stage, the kernel rapidly evolves to align with the dataset's features and labels, while in the second phase, the kernel changes only minimally and the network behaves linearly in the NTK feature map $\phi(x) = \nabla_{\theta'} f_{\theta'}(x)\Big|_{\theta' = \theta_t}$, a regime sometimes referred to as *lazy training* [14, 35].

Adversarial Examples and adversarial training. Adversarial examples present one the of the most infamous failure modes of deep learning [58]. These are images within bounded pertur-bations of naturally occurring images which consistently fool deep networks over a wide ar-ray of architectures [41]. There is much literature dedicated to designing techniques for secur-ing networks against these attacks[22, 39, 15, 23, 33, 64, 46, 13]. In this work, we focus on adversarial training with iterated projected gradient descent (PGD), which seeks to minimize $\mathcal{L}_{\text{rob}} = \mathbb{E}_{x,y \sim p(x,y)}\left[\max_{x' \sim B_\epsilon(x)} \mathcal{L}_{\text{standard}}(x', y)\right]$. That is, minimizing the worst case loss of samples in a small neighborhood around training examples, where the inner maximization is computed during training using iterated PGD [22, 39].

From a theoretical standpoint, much work has been devoted to explaining the causes of adversarial vulnerability and the limitations of adversarial robustness. Popular theories include the notion of there existing "robust and non-robust features" present in data [29, 61], adversarial examples being an outcome of high dimensional geometry [21, 31, 54], an outcome of stochastic gradient descent (SGD) [55], and many more [11]. Based on the NTK theory, there has been work studying the presence of adversarial examples under the NTK and NNGP kernels [19, 6, 12, 45, 7]. Recently, NTK theory has been use to generate attack methods for deep networks [60, 63]. Adversarial examples have been shown to arise in simplified linear classification settings [53, 29], which readily transfer to the NTK settings as the NTK classifier is linear in its underlying feature representation. However, these reports on the adversarial vulnerability of NTK and NNGP kernels has been focused solely on the infinite-width limit of these kernels, with no literature on the adversarial robustness of the learned and data-dependent NTK that is present in practical networks.

2 Experimental setup

Definitions and problem setup. We first define the necessary objects and terminologies for our experimental setup. Our scheme follows closely that of [18]; however, we consider the additional dimension of adversarial robustness in addition to benign accuracy. First, we define the parameter dependent empirical NTK: $k_{ENTK,\theta}(x, x') = \nabla_\theta f_\theta(x)^T \nabla_\theta f_\theta(x')$. In the case where $\theta = \theta(t)$, where $\theta(t)$ refers the parameters of the network after training for t epochs, we use the shorthand $k_t = k_{ENTK,\theta(t)}$. Next, we define three training dynamics. **1) Standard** dynamics as $f_{standard,\theta} = f_\theta(t)$, that is, network behavior with no modifications. **2) Linearized** (also referred to as lazy) dynamics around epoch t: $f_{lin,\theta,t}(x) = f_{\theta_t}(x) + (\theta - \theta_t)^T \nabla_{\theta'} f_{\theta'}(x)\Big|_{\theta'=\theta_t}$. I.e. linearized training dynamics corresponds to performing a first-order taylor expansion of the network parameters around a point θ_t. We refer to f_{θ_t} as the parent network, and t the spawn epoch. Note that in linearized dynamics, the underlying feature map $\phi(x) = \nabla_{\theta'} f_{\theta'}(x)\Big|_{\theta'=\theta_t}$, and the corresponding kernel is fixed. Fort et al. [18] studied this regime and showed that in practice, deep networks training with SGD undergo two stages in training, in which the first phase was chaotic with a rapid changing kernel until some relatively early epoch t, and the second stage behaves like linear training about θ_t. **3) Centered linear** training (or centered for short): where we subtract the parent network's output [26, 36, 38]: $f_{centered,\theta,t}(x) = (\theta - \theta_t)^T \nabla_{\theta'} f_{\theta'}(x)\Big|_{\theta'=\theta_t}$. This corresponds to linear training, with the zeroth order term removed. Now the output is strictly dependent on the difference between θ and θ_t, and the contribution of the first t epochs is only through how it modifies the feature map. Studying this setting lets us isolate the properties of the learned kernel k_t, without worrying about its contribution from earlier. Efficient implementation of both these linearized versions is done using forward mode differentiation in the JAX library [8].

Experimental design We follow closely that of [18], where we train networks in two distance stages with an added dimension of adversarial training. Additional details are available in Appendix. *Stage 1: Standard dynamics.* We train Resnet18s on CIFAR-10 or CIFAR-100 [32] for t epochs either using benign data (i.e. no data modification), or adversarial training, for $0 \leq t \leq 100$. *Stage 2: Linearized dynamics.* Following stage 1, we take the parent network from stage 1 and train for an additional 100 epochs with either linearized or centered linearized training dynamics. Note that for centered training, after stage 1, the networks will output entirely zeros, as the zeroth order term has no effect, so the classifier does not have a "warm start." In this stage, we train using **benign** data, with no adversarial training. Additionally, we freeze the batchnorm running mean and standard deviation parameters after stage 1, as allowing these to change would implicitly change the feature map $\phi(x) = \nabla_{\theta'} f_{\theta'}(x)\Big|_{\theta'=\theta_t}$.

3 Evolution of the NTK under standard and adversarial training

First, we look at the evolution of the kernel under different training conditions. To do this, we calculate the empirical NTK on a random subset of 500 class-balanced training points on CIFAR-10 and CIFAR-100 for resnets trained for 100 epochs SGD under standard dynamics with either

Figure 1: Evolution of the Neural Tangent Kernel under benign and adversarial training on Resnet-18s on CIFAR-100 (Top row) and CIFAR-10 (Bottom Row). Networks are either trained with for 100 epochs with benign or adversarial training, or 50 of benign followed by 50 epochs of adversarial training (50/50). From left to right, we plot the kernel velocity, kernel distance to the final kernel, effective rank, and mean kernel specialization of the resulting kernels. (n=3)

benign training or adversarial training. We also consider a third scenario where we perform benign training for 50 epochs then change to adversarial training for the remaining 50 epochs so we have an additional control point of the effect of adversarial training. For networks with multiple outputs, the kernel matrix is a rank-four tensor in $\mathbb{R}^{C \times C \times N \times N}$ with C being the class count and N being the dataset size. The calculation for these entries is given by $k_{c,c'}(x, x') = \nabla_\theta f_\theta^c(x)^T \nabla_\theta f_\theta^{c'}(x')$, and the resulting subclass kernel matrix $K_{c,c'} \in \mathbb{R}^{N \times N}$. Unless otherwise stated, for the statistics we present, we calculate the trace kernel, the average of the diagonal elements of the class-specific matrix: $\bar{K} = \frac{1}{C} \sum_{c=1}^{C} K_{c,c}$.

Firstly, we look at the kernel distance between neighboring epochs. This kernel distance is given by: $S(K_1, K_2) = 1 - \frac{\text{Tr}(K_1^T K_2)}{||K_1||_F ||K_2||_F}$, which equals to 0 iff $K_1 = K_2$. The kernel velocity is given by $\frac{dS}{dt}$, which we approximate as a finite difference between neighboring epochs (See fig. 1a). We also consider the kernel distance from the current epoch to the kernel at the end of training (fig. 1b). From these metrics we see that both for benign and adversarial training, the kernel converges within 30 epochs to close to the final kernel, in accordance with the results in Fort et al. [18]. This suggests that after these few epochs, the underlying feature set is fixed and the remainder of training is spent performing linear classification on this feature set. Surprisingly, adversarial training also quickly converges, albeit to a different kernel whose underlying feature set is more robust (as we will see in later sections). In the third setting, we observe a small spike in kernel velocity at epoch 50 when we swap from standard to adversarial training. The change is small compared to the initial rapid kernel evolution, suggesting that the standard training kernel is more similar to the adversarial kernel than it is to the initial NTK. Likewise, when we plot the kernel distance to the final kernel, both models nearly converge after epoch 40, while in the third setting the model stabilizes at the standard training kernel before changing to the adversarial kernel after 50 epochs.

The third metric we compute is the effective rank of the kernel matrix [50]. This measures the dispersion of the matrix over its eigenvectors, and is given by: erank(K) $= \exp(- \sum_{i=1}^{N} p_i \log p_i)$, With $p_i = \frac{\lambda_i}{\sum_{i=1}^{N} \lambda_i}$ with λ_i being the eigenvalues of the kernel matrix K. This value is bounded between 1 when the matrix has one dominant direction and N when all eigenvalues are equal. Previous work has shown that deeper networks are bias towards low effective rank (of the conjugate kernel) at initialization [28]. Alternatively, the effective rank could be interpreted as the complexity of dataset under the kernel, and existing work has shown that robust classifiers require more model

Figure 2: Performance of standard, linearized and centered training based on kernels made from benign or standard training on CIFAR-100 (top row) and CIFAR-100 (bottom row). Solid lines indicate benign accuracy while dashed lines indicate adversarial accuracy. Under standard or linearized dynamics with benign training (left), networks have little to no robust accuracy, but the networks learn kernels with robust features over time, as centered training gains robustness as the kernel evolves. Centered training also sees a robustness gain over adversarial training (center) at the cost of some benign accuracy. For linearized dynamics, the relative magnitude of the first-order component sharply peaks in early epochs before decaying to 0 as the spawn network full trains (right).

163 capacity [11, 53], although it is unclear the precise relationship between the effective rank notion of
164 complexity and those given in prior work relating to adversarial robustness.

165 As a fourth metric, we consider the mean kernel specialization. As discusses earlier, for multi-classed
166 outputs, the full NTK is a $4D$ tensor in $\mathbb{R}^{C \times C \times N \times N}$ with C class-specific kernels corresponding to the
167 diagonal entries of the first two dimensions. Over training, it has been observed that these individual
168 class-specific kernels specialize to align themselves with their classes [56]. The kernel specialization,
169 defined as: $\text{KSM}(c, c') = \frac{A(K^{c,c}, y_{c'} y_{c'}^T)}{C^{-1} \Sigma_{d=1}^{C} A(K^{d,d}, y_{c'} y_{c'}^T)}$, where $A(K^{c,c}, y_{c'} y_{c'}^T) = 1 - S(K^{c,c}, y_{c'} y_{c'}^T)$, i.e.
170 the cosine similarity of the kernel matrix and the one-hot class labels. Intuitively, this compares how
171 aligned class c specific kernel is to the labels of class c' compared to other class kernels. This quantity
172 is bounded between 0 and C and higher diagonal entries (when $c = c'$), indicate higher specialization.
173 We define the mean kernel specialization as $C^{-1}\Sigma_{c=1}^{C} \text{KSM}(c, c)$, i.e. the average of diagonal entries
174 of the KSM matrix. We calculate this for only CIFAR-10, as computing all 100 class-specific kernels
175 for CIFAR-100 is too costly. From fig. 1d, where we see that adversarial training is associated with a
176 lower mean kernel specialization, we take away that adversarial training promotes features which are
177 more broadly shared between classes, although this needs further investigations which will be the
178 focus of our continued effort.

4 Performance of Linearized and Centered Training

180 Next we look at the performance of linearized and centered training, where we vary the spawn epoch
181 at which we begin stage 2 training, i.e. the epoch t described in Sec. 3. We then plot the benign and
182 adversarial performance of the classifier after stage 2 training, in comparison with the performance
183 at the end of stage 1 training in fig. 2 for CIFAR-10 and CIFAR-100. We show the results when
184 either stage 1 is performed with benign training or adversarial training. Additionally, for the case
185 of linearized training, we plot the relative magnitude of the zeroth order and first order terms in the
186 linearization dynamics equation. Specifically, let $f_0 = f_{\theta_t}(x)$ and $\Delta f = (\theta - \theta_t)^T \nabla_{\theta'} f_{\theta'}(x)\big|_{\theta' = \theta_t}$.
187 We plot the relative magnitude of the two components, given by $\frac{\Delta f^T \Delta f}{f_0^T f_0}$, averaged over the test set.

188 The most surprising observation is that centered training gains significant robustness over standard
189 and linearized training dynamics, both in adversarial and benign training. Because centered training
190 does include the zeroth order term in its predictions, all the robustness given by centered training is
191 **inherited entirely through the learned NTK**, and not through adversarial training (as we perform
192 benign training in stage 2). This lends credence to the "robust feature" hypothesis given in Ilyas

Figure 3: Adversarial transferability of standard, linearized and centered networks to fully trained networks with either benign or adversarial training on CIFAR-10 and CIFAR-100. (n=3)

et al. [29], however, now what matters is not necessarily what features are present in the data, but what features the networks learns in its kernel. On the final adversarial kernel, centered training brings about a 3.7% adversarial accuracy gain over standard adversarial training on CIFAR-10, going from $51.77 \pm 0.80\%$ to $55.46 \pm 1.79\%$. Similar improvements are also seen on CIFAR-100 with an improvement from $24.42 \pm 0.14\%$ to 27.35 ± 0.41. At around epoch 10, the centered network reaches $62.09 \pm 1.76\%$ robust accuracy on CIFAR-10, an over 10% performance gain.

Equally surprising is that that even under benign training, the network learns a robust kernel over time, with centered training reaching $41.41 \pm 9.75\%$ after epoch 100 for CIFAR-10 and 14.16 ± 1.03 for CIFAR-100. Despite this, the neural network under standard dynamics still sees no adversarial accuracy, suggesting that the contribution from the robust learned kernel is minor compared to the contribution of the non-robust kernels which are present early in training. Roughly speaking, the final networks outputs could be written as the integral over time of instantaneous kernel-dependent functions [16]. We can verify that the contribution of the kernel at later epochs is small by the relative magnitude plots in fig. 2c, which shows that first-order additional term of linearized dynamics becomes very minor by epoch 30, meaning that the network has essentially fully fit the dataset, at which point the learned kernel reaches it maximum robustness (as seen by the centered plots). We observe that the learned kernel only gains robustness over time, but its robustness stagnates as kernel velocity slows down. Linearized training sees a peak in the relative magnitude of first to zeroth order components around epoch 10-15, coinciding with the small bump in robustness for the benign training kernel under linearized training, and for the adversarial training kernel a peak in accuracy in benign and adversarial settings for linearized and centered training. We conjecture that this bump in relative magnitude correlates with the stage transition between kernel learning and linear fitting, where the kernel is well aligned with the data, but the network has not yet fully fit the training data, causing the first order component to contain the majority of the data fit.

5 Adversarial Transferability of Linearized Dynamics

We next study the differences between standard and linearized dynamics from the perspective of adversarial transferability, specifically, how well do adversarial examples generated with one dynamics transfer to models with other dynamics? From the experiments described in Sec. 3, we have a set of classifiers with standard, linearized, and centered dynamics: $\{f_{\text{stan},t}\}, \{f_{\text{lin},t}\}, \{f_{\text{cen},t}\}$ for $0 \le t \le 100$. For each of these classifiers, we generated adversarial examples on the test set with L_∞ PGD (details provided in Appendix), $\{\hat{X}_{\text{stan},t}\}, \{\hat{X}_{\text{lin},t}\}, \{\hat{X}_{\text{cen},t}\}$. To see how these adversarial examples compare to those generated by a network with standard dynamics, we then evaluated the accuracy of $f_{\text{stan},t=100}$ on these adversarial examples: $\text{Acc}_{\text{stan},t=100}^{(\cdot),t'} = \mathbb{E}_{x,y \sim \hat{X}_{(\cdot),t'}}[\mathbb{I}(y = f_{\text{stan},t=100}(x))]$.

We then define the adversarial transferability as: $\tau_{(\cdot),t'} = \dfrac{\text{Acc}_{\text{stan},t=100}^{b} - \text{Acc}_{\text{stan},t=100}^{(\cdot),t'}}{\text{Acc}_{\text{stan},t=100}^{b} - \text{Acc}_{\text{stan},t=100}^{\text{stan},t=100}}$, where

$\text{Acc}_{\text{stan},t=100}^{b}$ is the accuracy of the standard dynamics classifier with a benign test set. This metric measures the relative effectiveness of adversarial examples generated by another network to adversarial examples generated by the network itself. Values of $\tau = 1$ mean that the adversarial examples perform just as well as adversarial examples generated by the classifier itself, while $\tau = 0$ would imply that adversarial examples do not transfer whatsoever.

We plot these for CIFAR-10 and CIFAR-100 trained Resnet-18s with either benign or adversarial training in fig. 3. Comparing the plots of benign training and adversarial training, we see that in both cases, the adversarial examples of standard and linearized dynamics transfer similarly well to the

Table 1: Performance of stage 2 network training with a parent network trained with adversarial training for 10 epochs on CIFAR-10. η = learning rates. (n=3)

	Frozen Batchnorm				Standard Batchnorm		
	Parent Network	Centering	SGD $\eta = 0.0001$	SGD $\eta = 0.01$	Centering	SGD $\eta = 0.0001$	SGD $\eta = 0.01$
Benign Accuracy	78.33 ± 1.07	48.73 ± 1.52	81.73 ± 0.76	82.21 ± 0.96	30.80 ± 9.76	52.46 ± 18.47	43.22 ± 17.72
Adversarial Accuracy	48.73 ± 1.52	62.09 ± 1.76	44.99 ± 0.75	44.39 ± 1.23	19.45 ± 6.21	20.91 ± 8.69	14.28 ± 5.92
Kernel Distance	-	0 ± 0	0.0140 ± 0.0009	0.0290 ± 0.0042	0.0012 ± 0.0001	0.0228 ± 0.0061	0.0624 ± 0.0151

full trained network. In contrast, the adversarial examples made by centered training are far less effective, suggesting that the feature set used by the kernel does not necessarily correspond to the same feature set used by a fully trained network. For standard training, the adversarial transferability plots rise much more quickly than for adversarial training, suggesting that features from early kernels are used more in the final model than for adversarial training, as seen by the slower initial rise of the standard and linearized training in fig. 3b and fig. 3d. As seen earlier, centered training on earlier NTK kernels provide little robust accuracy, suggesting that some of the lack of robustness of fully trained networks could be due to the contribution of these early kernels. For standard training, the adversarial transferability of fully trained networks rises sharply in the first 15 epochs then slowly decays over time. This suggests that the adversarial behaviour of the fully trained network is closer to some of the earlier kernels than to the final kernel. However, in both cases, adversarial examples generated by the initial NTK do not transfer at all to fully trained networks, suggesting that the initialization NTK analysis of adversarial examples in some theoretical work [19, 6] may not be accurately describe the behaviour of adversarial examples in practical networks.

6 SGD vs Linearized Dynamics at low learning rates

In Sec. 4, we showed the adversarial robustness can arise from linearized and centered training, in which the underlying feature set is fixed. In this section, we investigate whether freezing the kernel is necessary for robustness gains. To investigate this, we trained networks with adversarial training with standard dynamics until epoch 10. We then performed centered training on top of the resulting kernel. We chose 10 epochs, as it corresponds to the large jump in robust accuracy. The centered network serves as the control, when the feature set is frozen. Then, the kernel varies into two ways. First, we trained a network using "centered standard" dynamics, where $f_{\text{cen, stan},\theta}(x) = f_\theta(x) - f_{\theta_t}(x)$, that is, we subtract the network from its initialization's output, and train with standard gradient descent. We use learning rates of either $\eta = 0.0001$ or $\eta = 0.01$, corresponding to high and low learning rates. Previously, we had argues that freezing the batchorm running mean and standard deviation is necessary so that the feature map $\nabla_{\theta'} f_{\theta'}(x)\big|_{\theta'=\theta_t}$ does not change. Here, we question this assumption and either keep the batchnorm parameters frozen or let them change.

Table 1 shows the resulting benign and adversarial accuracies on CIFAR-10, as well as the kernel distance between the final network's kernel and the kernel after stage 1. Additional results for different spawn epochs and for CIFAR-100 are reported in Appendix. We see that in the frozen batchnorm setting, both SGD variants lose robust accuracy. SGD does not freeze the kernel, we also see that that the kernel changes too (as seen from the kernel distance), with SGD with a larger learning rate seeing a larger change. Letting the batchnorm parameters change results in low adversarial and benign accuracy for all training models, with correspondingly higher kernel distances. This interpretation of freezing batchnorm parameters to preserve the NTK provides a different perspective as to why more sophisticated batchnorm schemes improve performance in few-shot learning [9].

7 Adversarial Training on a Frozen NTK

In fig. 1, we observed that adversarial robustness could be inherited from a kernel in stage 1 of training, even if stage 2 was performed on benign data. We now investigate whether we can gain robustness by performing adversarial training in stage 2 on top of a frozen kernel. Much theoretical analysis of adversarial robustness has been in the frozen kernel regime or linear classification [19, 6, 45, 29, 53], as analysis of neural network training simplifies when the underlying feature set does not change.

For this experiment, we ran adversarial training using centered dynamics for three kernels. First, we used the initialization kernel, that is, $K_{t=0}$. Then we used the post-training kernels for networks

Table 2: Centered network performance with benign or adversarial training in stage 2. (n=3)

Base Kernel	Benign		Adversarial	
	Benign Accuracy	Adversarial Accuracy	Benign Accuracy	Adversarial Accuracy
Standard Adversarial Training (SGD, No Kernel)	81.58 ± 0.63	51.77 ± 0.80	-	-
Initialization Kernel $K_{t=0}$	34.11 ± 1.35	0.00 ± 0.00	10.46 ± 0.66	6.27 ± 4.45
Benign Training $K_{t=100,\text{benign}}$	85.06 ± 0.75	41.41 ± 9.75	84.85 ± 0.65	$\mathbf{76.15 \pm 1.91}$
Adversarial Training $K_{t=100,\text{adv}}$	79.65 ± 0.30	55.46 ± 1.79	81.23 ± 0.57	57.50 ± 1.56

Initialization NTK   Benign Training NTK   Adversarial Training NTK

$\mathbf{max}\cos(v_i, \phi(x))$

$\mathbf{min}\cos(v_i, \phi(x))$

Figure 4: Visualizations of the top 4 eigenvectors of the initial NTK, benign training NTK, and adversarial training NTK. We either maximize the cosine similarity (top row), or minimize it (bottom).

trained either use benign training or adversarial. As a baseline, we compare to the accuracies achieved by adversarial training under standard dynamics. These results are shown in table 2, with additional results on CIFAR-100 in Appendix.

The initialization kernel fails to learn the dataset under adversarial training, achieving near random benign accuracy, and no meaningful adversarial accuracy. Adversarial training sees a very limited gain in robust accuracy, improving only 2%, and most surprisingly, the benign training kernel sees a dramatic robustness gain, achieving 76.15%, surpassing the robustness of all other methods described in this paper. Similar results are reported in Appendix for CIFAR-100, with the adversarial kernel seeing little gain and the benign kernel surpassing robustness of all other methods. While we do not have a clear explanation as why we see such a dramatic improvement, we do have a few speculative hypotheses. Firstly, it has been argued that fitting global structure before fitting local structure can improve robust accuracy [13, 46]. Under this view, we can consider stage 1 training as learning global structure by choosing task predictive features, and stage 2 as fitting local structure by performing adversarial training. Secondly, separating the two tasks can reduce some of the instability caused by adversarial training [23, 57], as only the linear weights changed in stage 2.

From a theoretical perspective, adversarial training in linear classificatiion far easier to analyze, and thus this regime has been the interest of several papers [53, 19, 6]. However, in practice these analysis have not been very practically useful as neural network behaviour needs deviates far from the linear ideal in order to achieve high standard accuracy [36]. As we have shown here, linearized training can achieve high benign and robust accuracy, provided that we use the learned NTK as opposed to the initial one. This linearized regime can thus serve as a middle ground where many of the analysis tools of adversarial training are applicable, while still retaining high practical performance.

8 Visualizing NTK eigenvectors

In the lazy dynamics regime, the resulting classifier is linear in its features given by $\phi(x) = \nabla_{\theta'} f_{\theta'}(x)\big|_{\theta'=\theta_t}$. Furthermore, the effective classifier weights $(\theta - \theta_t)$ lie in the span of the space of the features of the training set: $J = [\phi(x_1), \phi(x_2)...\phi(x_N)]^T \in R^{N \times P}$, with P the number of parameters. The top eigenvectors of the NTK $K = JJ^T$ correspond to the dominant features of the dataset in the the NTK feature space. While much work has looked the properties of the NTK eigenvectors/value at initialization to understand neural network generalization, or how the eigenspace evolves over training, here we visualize these eigenvectors directly. It has been shown that not only are adversarial examples generated by robustly trained networks more visually interpretable, but also that they make reasonable generative models by directly maximizing the class logits $\log p(y = c|f_\theta(x))$

w.r.t to the inputs x [17]. By visualizing the eigenvectors of the network directly, we can disambiguate whether this property is caused by the linear fit on top of the eigenvectors, or directly from the feature space caused by adversarial training.

To visualize these eigenvectors we describe the following algorithm. First, we calculate the feature space representation of the top eigenvectors. This corresponds to the first columns of V in the singular value decomposition of the training set features: $J = U\Sigma V^T$. Typically $P > 10^6$ and $N \sim 10^5$, so calculating this SVD directly is prohibitive. Instead, we note that $\Sigma V^T = U^T J$, so the ith eigenvector $v_i \propto J^T u_i$ (because Σ is a rectangular diagonal matrix), where u_i is the ith eigenvector of K. We can calculate $K = U\Lambda U^T$ since $N << P$. Calculating J directly is too expensive, so instead we note that $J^T u_i = \frac{\partial}{\partial \theta}(u_i^T f_\theta(X))$, i.e. we take derivatives of a weighted sum of the network on training samples, with respect to the parameters.

Now with the feature space representation of eigenvectors v_i, we visualize them by optimizing x_i to optimizing $\cos(v_i, \phi(x_i))$, given us $2N$ images, with the factor 2 arising from whether we maximize or minimizing the cosine similarity. As this algorithm describes how to visualize eigenvectors for only scalar functions f, we choose the dog class of the neural network as the chosen function to visualize, however in practice we found that eigenvectors for other classes looked very similar. As before, computing K is too expensive for the full dataset, so we pick a subset of 500 images from the training set to calculating the NTK.

The visualizations of the top 4 eigenvectors of the kernels generated for the initial NTK, the kernel after 100 epochs of benign training, and the kernel after 100 epochs of adversarial training are visualized in fig. 4. The initial NTK has visually meaningless eigenvectors which look indistinguishable from pure noise. Meanwhile, the eigenvectors after benign training seem to distinguish the edges of CIFAR-10 classes, but still are largely uninterpretable. Finally, the adversarial kernel results in the eigenvectors that clearly belong to different classes.

9 Discussions, limitations and Conclusions

The experiments in this paper showed that adversarial training results in a distinct and measurable change in the NTK compared to standard training. While under both training regimes, the NTK converges quickly in the first few epochs of training, the adversarial NTK appears to have a high effective rank and lower mean kernel specialization compared to the standard training NTK. Visually, the top eigenvectors in the adversarial NTK correspond to much more visually interpretable images compared to the standard NTK and the initialization NTK.

Furthermore, we showed that classifiers built on top of the adversarial Kernel retain significant amounts of adversarial accuracy, despite being trained without ever seeing adversarial examples. The initial NTK results in classifiers with no adversarial robustness, and surprisingly, the standard training NTK sees a dramatic increase in adversarial robustness over time. We additionally demonstrated that a frozen feature set is necessary for retaining the full robustness aspect of these kernels, as either allowing the batchnorm parameters to vary or using SGD as opposed to linearized training in the second stage results in a drop in robust accuracy.

Limitations. Here, we performed our analysis on robustness to an L_∞ PGD adversary which is an uncertified attack, but was designed to fool networks under standard dynamics, and is unproven against networks under centered or linearized dynamics. Furthermore, while this paper presents many interesting empirical insights about adversarial training on kernels, there is a great opportunity for developing the theory of the observed interplay of adversarial training and NTK evolution.

Previous research had to impose limiting assumptions, e.g., fixed kernels on NTKs due to the nonlinear nature of neural nets [53, 19, 6]. We hope that our study of adversarial training in the frozen kernel regime with learned kernels could bridge the gap between these two extremes by having simple linear dynamics, but still matching or exceeding the performance of standard networks. As shown in Sec. 7, the performance of adversarial training in the frozen feature regime can significantly exceed that of standard dynamics. Moreover, based on our observations, we believe that centered and linearized dynamics can be used as a defense against adversarial examples.

References

[1] L. Aitchison, A. X. Yang, and S. W. Ober. Deep kernel processes, 2021. URL https://openreview.net/forum?id=ZUW6N_SVKxq.

[2] K. Aitken and G. Gur-Ari. On the asymptotics of wide networks with polynomial activations. *ArXiv*, abs/2006.06687, 2020.

[3] S. Arora, R. Ge, B. Neyshabur, and Y. Zhang. Stronger generalization bounds for deep nets via a compression approach. In *ICML*, 2018.

[4] S. Arora, S. S. Du, W. Hu, Z. Li, R. R. Salakhutdinov, and R. Wang. On exact computation with an infinitely wide neural net. In *Advances in Neural Information Processing Systems*, pages 8141–8150. Curran Associates, Inc., 2019.

[5] A. Atanasov, B. Bordelon, and C. Pehlevan. Neural networks as kernel learners: The silent alignment effect. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=1NvflqAdoom.

[6] P. Bartlett, S. Bubeck, and Y. Cherapanamjeri. Adversarial examples in multi-layer random reLU networks. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021. URL https://openreview.net/forum?id=BKpNqR19JgD.

[7] A. Blaas, A. Patané, L. Laurenti, L. Cardelli, M. Z. Kwiatkowska, and S. J. Roberts. Adversarial robustness guarantees for classification with gaussian processes. In *AISTATS*, 2020.

[8] J. Bradbury, R. Frostig, P. Hawkins, M. J. Johnson, C. Leary, D. Maclaurin, G. Necula, A. Paszke, J. VanderPlas, S. Wanderman-Milne, and Q. Zhang. JAX: composable transformations of Python+NumPy programs, 2018. URL http://github.com/google/jax.

[9] J. Bronskill, J. Gordon, J. Requeima, S. Nowozin, and R. Turner. Tasknorm: Rethinking batch normalization for meta-learning. In –, 03 2020.

[10] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

[11] S. Bubeck and M. Sellke. A universal law of robustness via isoperimetry. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems*, volume 34, pages 28811–28822. Curran Associates, Inc., 2021. URL https://proceedings.neurips.cc/paper/2021/file/f197002b9a0853eca5e046d9ca4663d5-Paper.pdf.

[12] S. Bubeck, Y. Cherapanamjeri, G. Gidel, and R. T. des Combes. A single gradient step finds adversarial examples on random two-layers neural networks. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021. URL https://openreview.net/forum?id=NE0YlkgRo9x.

[13] Y. Carmon, A. Raghunathan, L. Schmidt, J. C. Duchi, and P. S. Liang. Unlabeled data improves adversarial robustness. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/32e0bd1497aa43e02a42f47d9d6515ad-Paper.pdf.

[14] L. Chizat, E. Oyallon, and F. R. Bach. On lazy training in differentiable programming. In *NeurIPS*, 2019.

[15] J. Cohen, E. Rosenfeld, and Z. Kolter. Certified adversarial robustness via randomized smoothing. In K. Chaudhuri and R. Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 1310–1320. PMLR, 09–15 Jun 2019. URL https://proceedings.mlr.press/v97/cohen19c.html.

[16] P. Domingos. Every model learned by gradient descent is approximately a kernel machine, 2020. URL https://arxiv.org/abs/2012.00152.

[17] L. Engstrom, A. Ilyas, S. Santurkar, D. Tsipras, B. Tran, and A. Madry. Adversarial robustness as a prior for learned representations, 2019. URL https://arxiv.org/abs/1906.00945.

[18] S. Fort, G. K. Dziugaite, M. Paul, S. Kharaghani, D. M. Roy, and S. Ganguli. Deep learning versus kernel learning: an empirical study of loss landscape geometry and the time evolution of the neural tangent kernel. In *NeurIPS*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/405075699f065e43581f27d67bb68478-Abstract.html.

[19] R. Gao, T. Cai, H. Li, L. Wang, C. Hsieh, and J. D. Lee. Convergence of adversarial training in overparametrized networks. *CoRR*, abs/1906.07916, 2019. URL http://arxiv.org/abs/1906.07916.

[20] A. Garriga-Alonso, L. Aitchison, and C. E. Rasmussen. Deep convolutional networks as shallow gaussian processes. In *International Conference on Learning Representations*, 2019.

[21] J. Gilmer, L. Metz, F. Faghri, S. S. Schoenholz, M. Raghu, M. Wattenberg, and I. J. Goodfellow. Adversarial spheres. *CoRR*, abs/1801.02774, 2018. URL http://arxiv.org/abs/1801.02774.

[22] I. J. Goodfellow, J. Shlens, and C. Szegedy. Explaining and harnessing adversarial examples, 2014. URL https://arxiv.org/abs/1412.6572.

[23] S. Gowal, K. Dvijotham, R. Stanforth, R. Bunel, C. Qin, J. Uesato, R. Arandjelovic, T. A. Mann, and P. Kohli. On the effectiveness of interval bound propagation for training verifiably robust models. *CoRR*, abs/1810.12715, 2018. URL http://arxiv.org/abs/1810.12715.

[24] B. Hanin and M. Nica. Finite depth and width corrections to the neural tangent kernel. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=SJgndT4KwB.

[25] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[26] W. Hu, Z. Li, and D. Yu. Simple and effective regularization methods for training on noisily labeled data with generalization guarantee. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=Hke3gyHYwH.

[27] J. Huang and H.-T. Yau. Dynamics of deep neural networks and neural tangent hierarchy. In H. D. III and A. Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 4542–4551. PMLR, 13–18 Jul 2020. URL https://proceedings.mlr.press/v119/huang20l.html.

[28] M. Huh, H. Mobahi, R. Zhang, B. Cheung, P. Agrawal, and P. Isola. The low-rank simplicity bias in deep networks. In –, 03 2021.

[29] A. Ilyas, S. Santurkar, D. Tsipras, L. Engstrom, B. Tran, and A. Madry. Adversarial examples are not bugs, they are features, 05 2019.

[30] A. Jacot, F. Gabriel, and C. Hongler. Neural tangent kernel: Convergence and generalization in neural networks. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurips.cc/paper/2018/file/5a4be1fa34e62bb8a6ec6b91d2462f5a-Paper.pdf.

[31] M. Khoury and D. Hadfield-Menell. On the geometry of adversarial examples. *CoRR*, abs/1811.00525, 2018. URL http://arxiv.org/abs/1811.00525.

[32] A. Krizhevsky. Learning multiple layers of features from tiny images. Technical report, CIFAR, 2009.

[33] M. Lecuyer, V. Atlidakis, R. Geambasu, D. Hsu, and S. Jana. Certified robustness to adversarial examples with differential privacy, 2018. URL https://arxiv.org/abs/1802.03471.

[34] J. Lee, Y. Bahri, R. Novak, S. Schoenholz, J. Pennington, and J. Sohl-dickstein. Deep neural networks as gaussian processes. In *International Conference on Learning Representations*, 2018.

[35] J. Lee, L. Xiao, S. S. Schoenholz, Y. Bahri, R. Novak, J. Sohl-Dickstein, and J. Sohl-Dickstein. Wide neural networks of any depth evolve as linear models under gradient descent. In *NeurIPS*, 2019.

[36] J. Lee, S. Schoenholz, J. Pennington, B. Adlam, L. Xiao, R. Novak, and J. Sohl-Dickstein. Finite versus infinite neural networks: an empirical study. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 15156–15172. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/ad086f59924fffe0773f8d0ca22ea712-Paper.pdf.

[37] A. Lewkowycz, Y. Bahri, E. Dyer, J. Sohl-Dickstein, and G. Gur-Ari. The large learning rate phase of deep learning: the catapult mechanism, 03 2020.

[38] P. M. Long. Properties of the after kernel, 2021. URL https://arxiv.org/abs/2105.10585.

[39] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu. Towards deep learning models resistant to adversarial attacks, 2017. URL https://arxiv.org/abs/1706.06083.

[40] A. Matthews, J. Hron, M. Rowland, R. E. Turner, and Z. Ghahramani. Gaussian process behaviour in wide deep neural networks. In *International Conference on Learning Representations*, 2018.

[41] S. Moosavi-Dezfooli, A. Fawzi, O. Fawzi, and P. Frossard. Universal adversarial perturbations. *CoRR*, abs/1610.08401, 2016. URL http://arxiv.org/abs/1610.08401.

[42] L. Muñoz González, B. Biggio, A. Demontis, A. Paudice, V. Wongrassamee, E. C. Lupu, and F. Roli. *Towards Poisoning of Deep Learning Algorithms with Back-Gradient Optimization*, page 27–38. Association for Computing Machinery, New York, NY, USA, 2017. ISBN 9781450352024. URL https://doi.org/10.1145/3128572.3140451.

[43] R. M. Neal. Priors for infinite networks (tech. rep. no. crg-tr-94-1). *University of Toronto*, 1994.

[44] R. Novak, L. Xiao, J. Lee, Y. Bahri, G. Yang, J. Hron, D. A. Abolafia, J. Pennington, and J. Sohl-Dickstein. Bayesian deep convolutional networks with many channels are gaussian processes. In *International Conference on Learning Representations*, 2019.

[45] G. D. Palma, B. T. Kiani, and S. Lloyd. Adversarial robustness guarantees for random deep neural networks. In *ICML*, 2021.

[46] A. Raghunathan, S. M. Xie, F. Yang, J. C. Duchi, and P. Liang. Understanding and mitigating the tradeoff between robustness and accuracy. In *Proceedings of the 37th International Conference on Machine Learning*, ICML'20. JMLR.org, 2020.

[47] A. Ramesh, P. Dhariwal, A. Nichol, C. Chu, and M. Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 2022.

[48] S. Reed, K. Zolna, E. Parisotto, S. G. Colmenarejo, A. Novikov, G. Barth-Maron, M. Gimenez, Y. Sulsky, J. Kay, J. T. Springenberg, et al. A generalist agent. *arXiv preprint arXiv:2205.06175*, 2022.

[49] D. A. Roberts, S. Yaida, and B. Hanin. The principles of deep learning theory, 2021. URL https://arxiv.org/abs/2106.10165.

[50] O. Roy and M. Vetterli. The effective rank: A measure of effective dimensionality. –, 01 2007.

[51] H. Salman, A. Ilyas, L. Engstrom, A. Kapoor, and A. Madry. Do adversarially robust imagenet models transfer better? In H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 3533–3545. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/24357dd085d2c4b1a88a7e0692e60294-Paper.pdf.

[52] H. Salman, A. Ilyas, L. Engstrom, S. Vemprala, A. Madry, and A. Kapoor. Unadversarial examples: Designing objects for robust vision. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021. URL https://openreview.net/forum?id=DxXNxZQVcc.

[53] L. Schmidt, S. Santurkar, D. Tsipras, K. Talwar, and A. Madry. Adversarially robust generalization requires more data. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, page 5019–5031, Red Hook, NY, USA, 2018. Curran Associates Inc.

[54] A. Shafahi, W. R. Huang, C. Studer, S. Feizi, and T. Goldstein. Are adversarial examples inevitable? In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=r1lWUoA9FQ.

[55] H. Shah, K. Tamuly, A. Raghunathan, P. Jain, and P. Netrapalli. The pitfalls of simplicity bias in neural networks. In *NeurIPS*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/6cfe0e6127fa25df2a0ef2ae1067d915-Abstract.html.

[56] H. Shan and B. Bordelon. Rapid feature evolution accelerates learning in neural networks. *ArXiv*, abs/2105.14301, 2021.

[57] C. Sitawarin, S. Chakraborty, and D. Wagner. Improving adversarial robustness through progressive hardening. In –, 03 2020.

[58] C. Szegedy, W. Zaremba, I. Sutskever, J. Bruna, D. Erhan, I. Goodfellow, and R. Fergus. Intriguing properties of neural networks. –, 12 2013.

[59] N. Tishby and N. Zaslavsky. Deep learning and the information bottleneck principle. *CoRR*, abs/1503.02406, 2015. URL http://arxiv.org/abs/1503.02406.

[60] N. Tsilivis and J. Kempe. The NTK adversary: An approach to adversarial attacks without any model access, 2022. URL https://openreview.net/forum?id=M5hiCgL7qt.

[61] D. Tsipras, S. Santurkar, L. Engstrom, A. Turner, and A. Madry. Robustness may be at odds with accuracy. –, 04 2019.

[62] G. Yang and E. Hu. Feature learning in infinite-width neural networks. In –, 11 2020.

[63] C.-H. Yuan and S.-H. Wu. Neural tangent generalization attacks. In M. Meila and T. Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 12230–12240. PMLR, 18–24 Jul 2021. URL https://proceedings.mlr.press/v139/yuan21b.html.

[64] H. Zhang, Y. Yu, J. Jiao, E. Xing, L. E. Ghaoui, and M. Jordan. Theoretically principled trade-off between robustness and accuracy. In K. Chaudhuri and R. Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 7472–7482. PMLR, 09–15 Jun 2019. URL https://proceedings.mlr.press/v97/zhang19p.html.