Falconn++: A Locality-sensitive Filtering Approach for Approximate Nearest Neighbor Search

Abstract

We present Falconn++, a novel locality-sensitive filtering (LSF) approach for approximate nearest neighbor search on angular distance. Falconn++ can filter out potential far away points in any hash bucket *before* querying, which results in higher quality candidates compared to other hashing-based solutions. Theoretically, Falconn++ asymptotically achieves lower query time complexity than Falconn, an optimal locality-sensitive hashing scheme on angular distance. Empirically, Falconn++ achieves a higher recall-speed tradeoff than Falconn on many real-world data sets. Falconn++ is also competitive against HNSW, an efficient representative of graph-based solutions on high search recall regimes.

1 Introduction

Nearest neighbor search (NNS) on a unit sphere is the task of, given a point set $\mathbf{X} \subset \mathcal{S}^{d-1}$ of size n and a query point $\mathbf{q} \in \mathcal{S}^{d-1}$, finding the point $\mathbf{p} \in \mathbf{X}$ such that $\mathbf{p} = \arg\min_{\mathbf{x} \in \mathbf{X}} \|\mathbf{x} - \mathbf{q}\|$. Since both data set $\mathbf{X}$ and query $\mathbf{q}$ are on a unit sphere, NNS using Euclidean distance is identical to NNS using angular distance (i.e. $\mathbf{p} = \arg\max_{\mathbf{x} \in \mathbf{X}} \mathbf{x}^\top \mathbf{q}$). NNS and its variant top-k NNS on angular distance are the fundamental problems in computer science, e.g. web search [11], recommender system [20], machine learning [7], and computer vision [21].

NNS dates back to Minsky and Papert [16], who studied a tradeoff between query time and indexing space in high dimensions. Due to the "curse of dimensionality", linear scan outperforms space/data partitioning solutions on solving exact NNS given a linear indexing space [23]. Given a polynomial indexing space $n^{\mathcal{O}(1)} d^{\mathcal{O}(1)}$, there is no known algorithm to solve exact NNS in truly sublinear time. In fact, if there exists such an algorithm, the Strong Exponential Time Hypothesis (SETH) [12], a fundamental conjecture in computational complexity theory, is wrong [3, 24].

Due to the hardness of exact NNS, researchers study efficient solutions for approximate NNS (ANNS). Given an approximation factor $c' > 1$, ANNS aims at finding the point $\mathbf{p}' \in \mathbf{X}$ within distance $c' \cdot \|\mathbf{p} - \mathbf{q}\|$. Since we can reduce ANNS to its "decision version", called (c, r)-approximate near neighbor ((c, r)-NN) for an approximation factor $c > 1$ and a radius r [10], solving ANNS boils down to (c, r)-NN. The problem (c, r)-NN that asks to return any point within distance cr to $\mathbf{q}$ if there is a point within distance r to $\mathbf{q}$ is the key algorithmic component of many ANNS solvers. *Locality-sensitive hashing* (LSH) [13] is the first *provable* sublinear query time solution using a polynomial indexing space for (c, r)-NN in high dimensions.

In principle, LSH hashes "close" points, i.e. within radius r to $\mathbf{q}$, into the same bucket with $\mathbf{q}$ with high probability, and hashes "far away" points, i.e. outside radius cr to $\mathbf{q}$, into the same bucket with low probability. Given a parameter $0 < \rho < 1$, LSH answers (c, r)-NN in $\mathcal{O}(n^\rho)$ time and uses $\mathcal{O}(nd + n^{1+\rho})$ space. Since the exponent ρ governs the complexity of LSH, it is desirable to have LSH families with the smallest ρ. LSH families with optimal values $\rho \approx 1/c^2$ on Euclidean distance

are well studied in theory [1, 5]. In practice, to the best of our knowledge, only Falconn [2] with the cross-polytope LSH family asymptotically achieves $\rho \approx 1/c^2$ on the Euclidean unit sphere.

In spite of provable sublinear query time guarantees, the indexing space of LSH is a primary bottleneck. Since different queries require different values of r, practical LSH-based solutions often use hundreds of tables to guarantee the querying performance. To overcome this bottleneck, Lv et al. [14] propose a multi-probing trick that sequentially checks the nearby buckets of the query's bucket. This is due to the fact that the hash values of the nearest neighbors of $\mathbf{q}$ tend to be close to the hash values of $\mathbf{q}$ on the hashing space [18]. Therefore, multi-probe LSH achieves a similar success probability with a smaller number of hash tables than the standard LSH.

However, we observe that LSH and its multi-probe schemes are not efficient to answer ANNS on high recall regimes. Since the distance gaps between the nearest neighbors are tiny in many real-world data sets, we need a very small approximation factor c, e.g. $c = 1.01$. This requirement degrades the performance of LSH-based solutions as ρ tends to close to 1. For this situation, multi-probe LSH has to increase the number of probes and hence number of candidates. That significantly reduces the querying performance since the probed buckets different from the query bucket tend to have more far away points. Empirically, multi-probe Falconn [2] with $L = 100$ hash tables on the Glove300 data set needs 4,000 probes and computes more than $0.1 \cdot n$ number of distances to achieve 90% recall. We believe that this is the rationale that LSH-based solutions are less favorable than the recent graph-based solutions [6], e.g. HNSW [15] for ANNS on high recall regimes.

To further facilitate LSH-based solutions for ANNS, we propose a *filtering mechanism* that can efficiently filter out the far away points in any bucket *before* querying. Our proposed mechanism is also *locality-sensitive* in the sense that far away points will be filtered out with high probability while close points will be pruned with low probability. Therefore, we can safely remove far away points while building the index to improve the query time and reduce the indexing space *simultaneously*. This feature significantly increases the performance of multi-probe LSH since it dramatically reduces the number of distance computations while preserving the search recall.

We implement the proposed filtering mechanism for angular distance based on the asymptotic property of the concomitant of extreme order statistics [9, 19]. Similar to Falconn [2], our approach utilizes many random projection vectors and only considers specific vectors $\mathbf{r}_i$ that are closest or furthest to the point. The key difference with Falconn is that we can use the random projection value $\mathbf{x}^\top \mathbf{r}_i$ to estimate $\mathbf{x}^\top \mathbf{q}$ by utilizing the asymptotic behavior of these projection values. This feature makes our filtering mechanism *locality-sensitive*.

Theoretically, our proposed locality-sensitive filtering (LSF) scheme, named *Falconn++*, asymptotically achieves smaller ρ, a parameter governing the query time complexity, than Falconn. Empirically, Falconn++ with a new add-on that applies multi-probing on *both* querying and indexing, achieves a significantly higher recall-speed tradeoff than Falconn on many real-world data sets. We further innovate Falconn++ with several heuristics that makes it competitive against HNSW [15], a recent efficient graph-based solution for ANNS on high recall regimes.

2 Preliminary

2.1 Locality-sensitive hashing (LSH)

Since 1998, LSH [13] has emerged as an algorithmic primitive of ANNS in high dimensions. LSH *provably* guarantees a sublinear query time for ANNS by solving the (c, r)-approximate near neighbor problem $((c, r)$-NN$)$ over $\tilde{\mathcal{O}}(\log n)$ different radii. Given a distance function $dist(\cdot, \cdot)$, the LSH definition is as follows.

Definition 1 (LSH). *For positive reals r, c, p_1, p_2, and $0 < p_2 < p_1 \leq 1$, $c > 1$, a family of functions $\mathcal{H}$ is (r, cr, p_1, p_2)-sensitive if for uniformly chosen $h \in \mathcal{H}$ and all $\mathbf{x}, \mathbf{y}, \mathbf{q} \in \mathbb{R}^d$:*

- *If $dist(\mathbf{x}, \mathbf{q}) \leq r$, then $\mathbf{Pr}\left[h(\mathbf{x}) = h(\mathbf{q})\right] \geq p_1$;*
- *If $dist(\mathbf{y}, \mathbf{q}) \geq cr$, then $\mathbf{Pr}\left[h(\mathbf{y}) = h(\mathbf{q})\right] \leq p_2$.*

To simplify notation, we call $\mathbf{x}$ as a "close" point if $dist(\mathbf{x}, \mathbf{q}) \leq r$ and $\mathbf{y}$ as "far away" point if $dist(\mathbf{y}, \mathbf{q}) \geq cr$. To minimize the collision probability of far away points, we combine $l = \mathcal{O}(\log n)$ different LSH functions together to form a new LSH family (r, cr, p_1^l, p_2^l) and set $p_2^l = 1/n$. Since

(a) An illustration of Falconn with $\mathbf{r}_1, \mathbf{r}_2, \mathbf{r}_3$. $h(\mathbf{x}) = h(\mathbf{z}) = h(\mathbf{q}) = \mathbf{r}_1, h(\mathbf{y}) = -\mathbf{r}_2$.

(b) A comparison of ρ between Falconn++ and Falconn while fixing $c = 1.5$ and varying r; and fixing $cr = \sqrt{2}$ and varying c.

the combination also decreases the collision probability of close points from p_1 to p_1^l, we need $L = \mathcal{O}\left(1/p_1^l\right)$ hash tables to ensure that we can find any close point with a constant probability. Given the setting $p_2^l = 1/n$ and denote by $\rho = \log(1/p_1)/\log(1/p_2)$, LSH needs $L = \mathcal{O}\left(n^\rho\right)$ tables and compute $\mathcal{O}\left(n^\rho\right)$ distances in $\mathcal{O}\left(dn^\rho\right)$ time to answer (c, r)-NN with a constant probability.

It is clear that the exponent ρ governs the complexity of LSH algorithm, which highly depends on the distance function, r, and cr. O'Donnell et al. [17] show that $\rho \geq 1/c^2 - o(1)$ on Euclidean distance. However, it is difficult to implement LSH families with optimal ρ in practice.

2.2 Falconn: An optimal LSH on angular distance

Andoni et al. [2] introduce *Falconn* that uses a cross-polytope LSH family on angular distance (i.e. cosine similarity). Given D random vectors $\mathbf{r}_i \in \mathbb{R}^d, i \in [D]$ whose coordinates are randomly selected from the standard normal distribution $N(0, 1)$ and $\mathtt{sgn}(\cdot)$ is the sign function, the cross-polytope LSH family uses the index of the random vector as the hash value. In particular, w.l.o.g. we assume that $\mathbf{r}_1 = \arg\max_{\mathbf{r}_i} |\mathbf{q}^\top \mathbf{r}_i|$, then $h(\mathbf{q})$ is calculated as follows.

$$h(\mathbf{q}) = \begin{cases} \mathbf{r}_1 \text{ if } \mathtt{sgn}(\mathbf{q}^\top \mathbf{r}_1) \geq 0 \,, \\ -\mathbf{r}_1 \text{ otherwise.} \end{cases} \tag{1}$$

A geometric intuition of Falconn is that $h(\mathbf{q}) = \mathbf{r}_1$ (or $h(\mathbf{q}) = -\mathbf{r}_1$) indicates that $\mathbf{q}$ is closest (or furthest) to the random vector $\mathbf{r}_1$ among D random vectors, as can be seen in Figure 1a. Falconn uses D random vectors $\mathbf{r}_i$ to partition the sphere into $2D$ wedges centered by the $2D$ random vectors $\pm \mathbf{r}_i$. If $\mathbf{x}$ and $\mathbf{q}$ are similar, they tend to be closest or furthest to the same random vector, and hence are hashed into the same wedge corresponding to that random vector. The following lemma states the asymptotic collision probability between two points $\mathbf{x}, \mathbf{q}$ when D is sufficiently large.

Lemma 1. *[2, Theorem 1] Given two points $\mathbf{x}, \mathbf{q} \in \mathcal{S}^{d-1}$ such that $\|\mathbf{x} - \mathbf{q}\| = r$ where $0 < r < 2$. Then, we have*

$$\mathbf{Pr}\left[h(\mathbf{x}) = h(\mathbf{q})\right] \approx D^{-\frac{1}{4/r^2 - 1}} \,. \tag{2}$$

Given a small c, Equation 2 indicates that Falconn has an optimal exponent $\rho \approx \frac{4/c^2 r^2 - 1}{4/r^2 - 1} \approx 1/c^2$.

Multi-probe Falconn. To reduce the number of hash tables, multi-probe Falconn considers the next closest or furthest random vectors to generate the probing sequence in a hash table. For example, in Figure 1a, since $\mathbf{q}$ is next closest to $-\mathbf{r}_2$, the bucket corresponding to the blue wedge will be the next probe. Given a fixed total number of query probes $qProbes$ for a query, ranking the buckets across L tables is challenging. Falconn heuristically uses the distance between the projection values of $\mathbf{q}$ on random vectors to construct the probing sequence. For example, in the table corresponding to Figure 1a, the ranking score of the blue wedge for probing is $|\mathbf{q}^\top \mathbf{r}_1| - |\mathbf{q}^\top \mathbf{r}_2|$. Even though multi-probe Falconn can significantly reduce the number of hash tables, it demands a significantly large $qProbes$ and candidate sizes to solve ANN on high recall due to the small distance gap among nearest neighbors.

2.3 CEOs: An optimal dimensionality reduction on unit sphere

Pham proposes CEOs [19], an optimal dimensionality reduction for ANN on angular distance. While CEOs shares the same spirit that utilizes random projections as Falconn, it is a similarity estimation technique rather than hashing. In particular, CEOs randomly projects $\mathbf{X}$ and $\mathbf{q}$ onto D Gaussian random vectors and considers the projection values on specific random vectors that are closest or furthest to $\mathbf{q}$, e.g. $\arg\max_{\mathbf{r}_i} |\mathbf{q}^\top \mathbf{r}_i|$. Asymptotically, given a sufficiently large D, the following lemma states the projection values on a few specific random vectors preserve the inner product.

Lemma 2. *[19] Given two points $\mathbf{x}, \mathbf{q} \in \mathcal{S}^{d-1}$ and a significantly large D random vectors $\mathbf{r}_i$, w.l.o.g we assume that $\mathbf{r}_1 = \arg\max_{\mathbf{r}_i} |\mathbf{q}^\top \mathbf{r}_i|$. Then, we have*

$$\mathbf{x}^\top \mathbf{r}_1 \sim N\left(\text{sgn}(\mathbf{q}^\top \mathbf{r}_1) \cdot \mathbf{x}^\top \mathbf{q} \sqrt{2 \log D}, 1 - (\mathbf{x}^\top \mathbf{q})^2\right). \tag{3}$$

We can see that, among D random vectors, if $\mathbf{r}_1$ is closest (or furthest) to $\mathbf{q}$, then the projection values of all points in $\mathbf{X}$ preserves their inner product order expectation. For example, in Figure 1a, since $\mathbf{q}$ is closest to $\mathbf{r}_1$, the order of projection values onto $\mathbf{r}_1$, e.g. $\mathbf{x}^\top \mathbf{r}_1 > \mathbf{z}^\top \mathbf{r}_1$, preserves the inner product order, e.g. $\mathbf{x}^\top \mathbf{q} > \mathbf{z}^\top \mathbf{q}$.

Importantly, given a constant $s_0 > 0$, Lemma 2 also holds for the top-s_0 closest vectors and top-s_0 furthest random vectors to $\mathbf{q}$ due to the asymptotic property of extreme normal order statistics [9]. For example, in Figure 1a, we can see that the inner product order is preserved on $-\mathbf{r}_1, -\mathbf{r}_2$.

Connection to Falconn. From Equations 1 and 3, we can see that Falconn uses the top-1 closest or furthest random vector (i.e. $\mathbf{r}_1$) as the hash value of $\mathbf{q}$ while CEOs uses the projection values over this random vector as inner product estimates. Furthermore, the multi-probe Falconn likely probes buckets corresponding to the $2s_0$ random vectors closest or furthest to $\mathbf{q}$. Since the inner product order is well preserved on the projections onto these $2s_0$ vectors, thanks to the CEOs property, we can keep a small fraction of number of points with the largest projection values in the Falconn's buckets. This filtering approach will significantly save the indexing space and decrease the query time while maintaining the same recall as multi-probe Falconn. The next section will theoretically analyze this approach and describe its practical implementation.

3 Falconn++: A locality-sensitive filtering approach

3.1 A locality-sensitive filtering (LSF)

Let $0 < q_2 < q_1 \leq 1$, we define an *LSF mechanism* that can keep in any bucket $h(\mathbf{q})$ any close point $\mathbf{x}$ with probability at least q_1 and any far away point $\mathbf{y}$ with probability at most q_2 as follows.

Definition 2 (LSF). *For positive reals r, c, q_1, q_2, and $0 < q_2 < q_1 \leq 1$, $c > 1$, given $\mathbf{x}, \mathbf{y}$ in the bucket $h(\mathbf{q})$ where h is randomly chosen from a LSH family, an LSF mechanism is a filter that have the following properties:*

- *If $dist(\mathbf{x}, \mathbf{q}) \leq r$, then $\mathbf{Pr}\left[\mathbf{x} \text{ is not filtered}\right] \geq q_1$;*
- *If $dist(\mathbf{y}, \mathbf{q}) \geq cr$, then $\mathbf{Pr}\left[\mathbf{y} \text{ is not filtered}\right] \leq q_2$.*

Applying the LSF mechanism on each bucket of the hash table constructed by any (r, cr, p_1, p_2)-sensitive LSH, the new collision probabilities among $\mathbf{x}, \mathbf{y}, \mathbf{q}$ after hashing and filtering are:

$$\mathbf{Pr}\left[h(\mathbf{x}) = h(\mathbf{q}), \mathbf{x} \text{ is not filtered}\right] \geq q_1 p_1, \quad \mathbf{Pr}\left[h(\mathbf{y}) = h(\mathbf{q}), \mathbf{y} \text{ is not filtered}\right] \leq q_2 p_2.$$

Assume that LSF has the property $\log(1/q_1)/\log(1/q_2) \leq \rho$, applying hashing and filtering, we can solve (c, r)-NN with the new exponent $\rho' \leq \rho$.

Benefits of LSF. Given the condition $\log(1/q_1)/\log(1/q_2) \leq \rho$ of LSF, combining filtering and hashing mechanisms leads to a faster LSH-based (c, r)-NN solver since $\rho' \leq \rho$. We note that the number of required tables is now $\mathcal{O}(1/q_1 p_1)$ whereas the standard LSH only needs $\mathcal{O}(1/p_1)$. Since the number of close points is often much smaller than that of far away points in real-world data sets, an LSF table contains *at most* nq_1 points in expectation. Therefore, the combination of LSF and LSH improves *both* query time and indexing space compared to LSH.

Challenges. The challenge is how to design an LSF mechanism with $\log(1/q_1)/\log(1/q_2) \leq 1/c^2$ since Falconn has an asymptotically optimal $\rho \approx 1/c^2$. If this condition does not hold, the LSF

mechanism will increase the exponent ρ and degrade the querying performance. For example, randomly discarding a point in a bucket will significantly increase ρ. Next, we will instantiate the LSF mechanism based on the CEOs property, that leads to an evolution of Falconn for angular distance.

3.2 LSF with CEOs

Given a sufficiently large D random vectors $\mathbf{r}_i$, w.l.o.g. we assume $h(\mathbf{q}) = \mathbf{r}_1 = \arg\max_{\mathbf{r}_i} \mathbf{q}^\top \mathbf{r}_i$. We denote by random variables $X = \mathbf{x}^\top \mathbf{r}_1, Y = \mathbf{y}^\top \mathbf{r}_1$ corresponding to $\mathbf{x}, \mathbf{y}$ in the bucket $h(\mathbf{q})$. From Lemma 2 we have $X \sim N\left(\mathbf{x}^\top \mathbf{q}\sqrt{2\log D}, 1 - \left(\mathbf{x}^\top \mathbf{q}\right)^2\right), Y \sim N\left(\mathbf{y}^\top \mathbf{q}\sqrt{2\log D}, 1 - \left(\mathbf{y}^\top \mathbf{q}\right)^2\right)$.
Exploiting this property, we propose the filtering mechanism as follows:

Given a threshold $t = (1 - r^2/2)\sqrt{2\log D}$, we keep any point $\mathbf{x}$ in the bucket $h(\mathbf{q})$ if $\mathbf{x}^\top \mathbf{r}_1 \geq t$ and discard any point $\mathbf{y}$ if $\mathbf{y}^\top \mathbf{r}_1 < t$.

The following theorem shows that our mechanism is locality-sensitive.

Theorem 1. *Given a sufficiently large D random vectors and $c > 1$, the proposed filtering mechanism asymptotically has the following properties:*

- *If $\|\mathbf{x} - \mathbf{q}\| \leq r$, then $\mathbf{Pr}\left[\mathbf{x} \text{ is not filtered}\right] \geq q_1 = 1/2$;*
- *If $\|\mathbf{y} - \mathbf{q}\| \geq cr$, then $\mathbf{Pr}\left[\mathbf{y} \text{ is not filtered}\right] \leq q_2 = \frac{1}{\sqrt{2\pi}\gamma}\exp(-\gamma^2/2) < q_1$ where $\gamma = \frac{cr(1-1/c^2)}{\sqrt{4-c^2r^2}} \cdot \sqrt{2\log D}$.*

The proof uses a classical tail bound on normal variables X, Y over t (see the supplementary material for details). Given a sufficiently large D, we can make $\log(1/q_1)/\log(1/q_2)$ arbitrarily smaller than $1/c^2$. Hence, the proposed LSF mechanism can be used to improve Falconn for ANNS.

3.3 Falconn++: A locality-sensitive filtering approach

Falconn++ is an essential combination between the proposed LSF and the cross-polytope LSH of Falconn using a sufficiently large D random vectors. For each bucket, we simply filter out potential far away points if its projection value is smaller than $t = (1 - r^2/2)\sqrt{2\log D}$. From Theorem 1, we have:
$\log(1/q_1) = \log 2$ and $\log(1/q_2) = \log\sqrt{2\pi} + \log\gamma + \gamma^2/2$, where $\gamma = \frac{cr(1-1/c^2)}{\sqrt{4-c^2r^2}} \cdot \sqrt{2\log D}$. For a large D, we have $\log(1/q_2) \approx \gamma^2/2 = \frac{c^2r^2(1-1/c^2)^2}{4-c^2r^2} \cdot \log D$. The new exponent ρ' of Falconn++ on answering (c, r)-NN is strictly smaller than the exponent ρ of Falconn since

$$\rho' = \frac{\log(1/q_1p_1)}{\log(1/q_2p_2)} \approx \frac{\log 2/\log D + (4/c^2r^2 - 1)}{\frac{c^2r^2(1-1/c^2)^2}{4-c^2r^2} + (4/r^2 - 1)} \leq \frac{4/c^2r^2 - 1}{4/r^2 - 1} = \rho \text{ when } D \text{ is sufficiently large.}$$

For a fixed r, $\frac{c^2r^2(1-1/c^2)^2}{4-c^2r^2} \to 0$ when $c \to 1$. However, when c rises, $\frac{c^2r^2(1-1/c^2)^2}{4-c^2r^2}$ increases and hence the gap between ρ' and ρ is significant. Figure 1b shows a clear gap between ρ' of Falconn++ compared to ρ of Falconn on various settings of r and c.

Connection to recent LSF frameworks. Our proposed LSF mechanism combined with Falconn can be seen as a practical instance of the asymmetric LSF frameworks that are recently studied in theory [4, 8]. These frameworks use different filtering conditions on the data and query points to govern the space-time tradeoff of ANNS. In particular, given two thresholds t_u, t_q, over the random choice of $\mathbf{r}_i$, the LSF frameworks study the probability where both $\mathbf{x}$ and $\mathbf{q}$ pass the filter corresponding to $\mathbf{r}_i$, i.e. $\mathbf{Pr}\left[\mathbf{x}^\top \mathbf{r}_i \geq t_u, \mathbf{q}^\top \mathbf{r}_i \geq t_q\right]$. Indeed, Falconn++ can be seen as a specific design of the asymmetric LSF framework where we utilize cross-polytope LSH to implement the filtering condition for queries and the asymptotic property of CEOs to implement the filtering condition for data points. We believe that our approach is much simpler in term of theoretical analysis and practical implementation. Empirically, we observe that Falconn++ with practical add-ons provides higher search recall than the corresponding instantiation of the theoretical LSF frameworks.

3.4 Practical implementation and add-ons of Falconn++

In the previous section, we prove that there exists a threshold t so that Falconn++ runs faster and uses less indexing space on answering (c, r)-NN than Falconn. Since the nearest neighbor distance

---

Algorithm 1 Falconn++ with multi-probe indexing

1: **procedure** MULTI-PROBE INDEXING($\mathbf{X}, \alpha, D$ random vectors $\mathbf{r}_i, iProbes$)
2:     **for** each $\mathbf{x} \in \mathbf{X}$ **do**
3:         Compute top-$iProbes$ vectors $\mathbf{r}_i$ s.t. $|\mathbf{x}^\top \mathbf{r}_i|$ is largest.
4:         Add $\mathbf{x}$ into the $iProbes$ buckets corresponding to these $iProbes$ vectors.
5:     **end for**
6:     For each bucket of size B corresponding to $\mathbf{r}_i$, keep top-$(\alpha B / iProbes)$ points with largest absolute projection values on $\mathbf{r}_i$.
7: **end procedure**

---

is different from different queries in practice, it is difficult to find an optimal t for all queries. We simplify the process of selecting t by introducing a *scaling* factor $0 < \alpha < 1$ to control the fraction of number of points in a bucket. In particular, for any bucket of size B corresponding to the random vector $\mathbf{r}_i$, we keep only the top-(αB) points $\mathbf{x}$ where $|\mathbf{x}^\top \mathbf{r}_i|$ is largest. Hence, the total number of points in one hash table is scaled down to αn.

Note that selecting an α fraction of points in a bucket is similar to selecting different values of t on different density areas. In particular, we tend to use a larger t for large buckets covering dense areas, and a smaller t for small buckets covering sparse areas. This simple scheme can be seen as a *data-dependent* LSF without any training phase.

Multi-probing for indexing: A new add-on We note that multi-probing is motivated from the observation that randomly perturbing $\mathbf{q}$ generates many perturbed objects that tend to be close to $\mathbf{q}$ and to hash into the same bucket with $\mathbf{q}$'s nearest neighbors [18]. This observation is also true in the reverse case where we perturb $\mathbf{q}$'s nearest neighbors to form new perturbed objects that tend to hash into the $\mathbf{q}$'s bucket. Hence, multi-probing trick can be used for indexing where we hash one point into multiple buckets. However, the downside of this approach is an increase of the table size from n to $iProbes \cdot n$ points where $iProbes \geq 1$ is the number of indexing probes for one data point. Therefore, the multi-probing trick for indexing has not been used in practice.

We note that the key feature of Falconn++ is the capacity of ranking and filtering out the points in any bucket based on their projection values to govern the space complexity. Given this mechanism, Falconn++ can utilize the multi-probe indexing to improve the query performance without increasing the indexing space. Particularly, after executing D random projections, we add $\mathbf{x}$ into the $iProbes$ buckets corresponding to the top-$iProbes$ random vector $\mathbf{r}_i$ closest or furthest to $\mathbf{x}$, as shown in Algorithm 1. Since we further scale down each bucket by $iProbes$ times, the number of points in a table is still αn. Empirically, a large $iProbes$ does not improve the performance of Falconn++. This is because we tend to keep points that are closest to the random vector $\mathbf{r}_i$ itself. When $\mathbf{q}$ is not close enough to $\mathbf{r}_i$, we will get all false positive candidates.

Multi-probing for querying: A new criteria. Among D random vectors, the CEOs property asymptotically holds for the $2s_0$ closest and furthest random vectors to $\mathbf{q}$ for a constant $s_0 > 0$. Hence, Falconn++ can probe up to $2s_0$ buckets on each table. Different from Falconn, we rank the probing sequences based on $\mathbf{q}^\top \mathbf{r}_i$ where $\mathbf{r}_i$ is the random vector corresponding to the probing bucket.

New heuristics makes Falconn++ more efficient. Besides the Structured Spinners [2] that exploit the fast Hadamard transform (FHT) to simulate Gaussian random projections in $\mathcal{O}(D \log D)$ time, we proposes other heuristics to improve the performance of Falconn++.

(1) Centering the data points. We observe that when the data set distribution is skewed on a specific area of the sphere, Falconn variants do not perform well. This is because a majority of the data points will be hashed into a few buckets. To handle this issue, we center the data set before building the index. Denote by $\mathbf{c} = \sum_i \mathbf{x}_i / n$ the center of $\mathbf{X}$, we map $\mathbf{x}_i \mapsto \mathbf{x}'_i = \mathbf{x}_i - \mathbf{c}$. This mapping can diverge $\mathbf{X}$ to the whole sphere and hence increases the performance of Falconn's variants. We note that after centering, $\arg\max_{\mathbf{x} \in \mathbf{X}} \mathbf{x}^\top \mathbf{q} = \arg\max_{\mathbf{x}' \in \mathbf{X}} \mathbf{x}'^\top \mathbf{q}$. Although $\|\mathbf{x}'_i\| \neq 1$, it does not affect the performance of Falconn++ since the CEOs property holds for the inner product.

(2) Limit scaling. We observe that we do not need to scale down small buckets since they might already contain high quality candidates. While we are scaling the bucket size on Line 6, Algorithm 1, we keep $max(k, \alpha B / iProbes)$ points. Note that this trick will increase the space usage in practice. However, it achieves a better recall-speed tradeoff given the same space complexity configuration.

Figure 2: The recall-time tradeoff of Falconn++ with various settings on Glove200.

Figure 3: The performance of Falconn++ ($L = 500, \alpha = 0.1, iProbes = 3$) with new heuristics and its query cost components.

4 Experiment

We implement Falconn and Falconn++ in C++ and compile with `g++ -O3 -std=c++17 -fopenmp -march=native`. We conduct experiments on Ubuntu 20.04.4 with an AMD Ryzen Threadripper 3970X CPU 2.2 MHz, 128GB of RAM using 64 threads. We present empirical evaluations on top-k NNS to verify our claims, including:

- Falconn++ with multi-probe indexing and querying provides a higher search recall-speed tradeoff than FalconnLib [1] given the same amount of indexing space.
- Falconn++ builds index faster and achieves a competitive recall-speed tradeoff compared to HNSW, [2] a recent efficient graph-based solution for ANNS on high search recall regimes.

We set $k = 20$ for all experiments. We use the average number of queries per second and search recall to measure the recall-speed tradeoff. A better solution will give the recall-speed curve towards the top right corner. We conduct experiments on three popular data sets, including Glove200 ($n = 1,183,514, d = 200$), Glove300 ($n = 2,196,017, d = 300$), and NYTimes ($n = 290,000, d = 256$). We extract 1000 points to form the query set. All results are the average of 5 runs of the algorithms.

A note on our implementation. Our implementation uses `std::vector` to store hash tables and the Eigen library [3] for SIMD vectorization. We use `boost::dynamic_bitset` to remove candidate duplicates. For multi-threading, we add `#pragma omp parallel` directive on the for loop over 1000 queries. Compared to the released FalconnLib and HnswLib, our implementation is rather straightforward and lacks many optimized routines, such as prefetching instructions, optimized multi-threading primitives, and other hardware-specific optimizations. Given the same configuration, our Falconn's indexing time is 3 times slower than FalconnLib. Though Falconn++ still provides higher search-recall than these two highly optimized libraries, we believe that there are rooms to engineer Falconn++ for further improvements.

Falconn++ and FalconnLib parameter settings. FalconnLib uses the number of bits to control the number of buckets in a hash table, which implicitly governs the number of concatenating hash functions. Throughout the experiment, our Falconn and Falconn++ uses 2 concatenated LSH functions and explicitly sets the number of buckets via the number of random projections D. Since each hash

---

[1]We use the latest version 1.3.1 from https://github.com/FALCONN-LIB/FALCONN

[2]We use the released version on Dec 28, 2021 from https://github.com/nmslib/hnswlib

[3]https://eigen.tuxfamily.org

Figure 4: The recall-speed comparison between Falconn++ and FalconnLib on 3 data sets.

function returns $2D$ different hash values, Falconn++ has $4D^2$ buckets on a hash table. For example, on Glove200 where $d = 200$, the setting $D = 256 = 2^8$ of Falconn++ leads to the suggested configuration of FalconnLib using 18 bits. Regarding the indexing space, both Falconn++ and Falconn use roughly the same amount of space to contain the same number of points in a hash table.

4.1 An ablation study on Glove200

This subsection measures the performance of our implemented Falconn++ and Falconn. We show the advantage of functionalities of Falconn++, including multi-probe indexing and proposed heuristics for improving the recall-time tradeoff. We conduct the experiments on Glove200 using 64 threads. Both Falconn variants use $D = 256$. To have the same indexing space, Falconn uses L hash tables and Falconn++ uses L/α where α is a scaling factor. Falconn++ with index probing $iProbes$ uses $L/(\alpha \cdot iProbes)$. Note that Falconn is Falconn++ with $iProbes = 1, \alpha = 1$.

Falconn++ with muti-probing tricks. Figure 2 shows the recall-time tradeoff of Falconn++ with various settings of L and α such that the total number of points in all tables is nL. Falconn uses $qProbes = \{1000, \ldots, 10000\}$ and Falconn++ uses $qProbes/\alpha$ to have sufficient candidates.

Without index probing i.e. $iProbes = 1$, Figure 2a shows that Falconn++ provides a lower query time than Falconn given the same recall rate. Falconn++ achieves a better recall-time tradeoff when α is smaller. In Figure 2b, though we use $qProbes/\alpha$, $\alpha = 0.1$ has the smallest candidate sizes given the same recall. Note that Falconn++'s indexing time is increased by $1/\alpha$ times.

With the index probing, Falconn++ with $L = 500, \alpha = 0.1$ improves the performance when $iProbes = 3$ in Figure 2c. Larger $iProbes$ values are not helpful since Falconn++ tends to keep points closest or furthest to the random vectors only.

Falconn++ with new heuristics. Figure 3 shows the performance of Falconn++ with the centering and limit scaling heuristics. Given $L = 500, \alpha = 0.1, iProbes = 3$, the limit scaling that keeps $max(k, \alpha B/iProbes)$ points in any bucket increases the number of points in a table from $0.1n$ to $2.42n$ points. This is because many empty or small buckets tend to contain more points (up to $k = 20$) with index probing. However, such an increased number of points in a table pays off. Each bucket has sufficient high quality candidates and hence we do not need a large $qProbes$ to get high recalls. In this case, one hash table of Falconn++ can be seen as a "merged version" of 3 hash tables of Falconn.

Figure 3a shows the recall-speed comparison between Falconn++ with centering and limit scaling heuristics and Falconn variants given the same $2.42 \cdot nL$ points in the index. Though Falconn with the centering heuristic achieves a higher tradeoff than standard Falconn, both of them with $L = 1210$ tables are inferior to Falconn++. Figure 3b shows that centering heuristic provides better candidates while Falconn++ and centering Falconn use a similar number of inner product computations to achieve the same recall. Figure 3c shows the query time breakdown components. Since Falconn++ uses less L and $qProbes$, it has less hashing and probing time and hence less total query time compared to centering Falconn for the same 95% recall ratio.

4.2 Comparison between Falconn++ and FalconnLib

This subsection compares our implemented Falconn++ with the released FalconnLib [2] given the same number of points in the index. Since FalconnLib does not support multi-threading for querying, Falconn++ uses 1 thread for a sake of comparison. Falconn++ uses $L = 50, \alpha = 0.1$,

Figure 5: The recall-speed comparison between Falconn++ and FalconnLib on 3 data sets.

$iProbes = 10$ on NYTimes, $L = 500, \alpha = 0.1, iProbes = 1$ on Glove300, and $L = 500, \alpha = 0.1$, $iProbes = 3$ on Glove200. For each data set, FalconnLib uses the corresponding scaled tables $L = \{200, 50, 1210\}$, respectively, to ensure the same space usage. We observe that FalconnLib needs $\{16, 18, 18\}$ bits for the corresponding data sets to gain the highest performance. For Falconn++, we set $D = \{128, 256, 256\}$ accordingly. For all approaches, we select $qProbes = \{1000, \dots 20000\}$.

Figure 4 shows the recall-speed comparison between Falconn++ and FalconnLib on these 3 data sets. On NYTimes, the center $\mathbf{c} \approx \mathbf{0}$, hence the centering trick is not necessary. Instead, we plot our own implemented Falconn, which has lower recall-speed tradeoff than FalconnLib. This again shows that our implementation is not well optimized. Nevertheless, Falconn++ shows a superior performance compared to FalconnLib on all 3 data sets. The significant improvement is from Glove300 and Glove200 where Falconn++ gains substantial advantages from higher quality candidates and less number of query probes.

4.3 Comparison between Falconn++ and HNSW on high search recall regimes

This subsection compares Falconn++ with the released HnswLib [15], a highly optimized library for ANNS using 64 threads. HNSW has two parameters to control the indexing space and time, including ef_index and M. We set $ef\_index = 200$ and use $M = \{1024, 512, 512\}$ for NYTimes, Glove300, and Glove200, respectively, to achieve high recall with fast query time. Falconn++ uses $L = 500, \alpha = 0.1, iProbes = 10$ on NYTimes, $L = 900, \alpha = 0.1, iProbes = 1$ on Glove300, $L = 500, \alpha = 0.1, iProbes = 3$ on Glove200 to have the same indexing space as HNSW.

Figure 5 shows the recall-speed comparison between Falconn++, HNSW, and a bruteforce where Falconn++ uses $qProbes = \{1000, \dots, 20000\}$ and HNSW sets $ef\_query = \{100, \dots, 2000\}$. Falconn++ provides a higher recall-speed tradeoff than HNSW when the recall is at least 97% on the 3 data sets. Since NYTimes has a large average nearest neighbor distance ($\approx 3\sqrt{2}/4$, i.e. two nearest vectors are almost orthogonal), the gap is substantial. Regarding the indexing space and time, they both uses nearly the same amount of RAM, as can be seen in Table 1. However, Falconn++ runs at least 5 times faster than HNSW and hence might be better for streaming ANNS applications [22].

5 Conclusion

We present Falconn++, a practical locality-sensitive filtering scheme for ANNS on angular distance. Theoretically, Falconn++ asymptotically has lower query time complexity than Falconn, an optimal LSH scheme. Though our implementation of Falconn++ lacks many optimized routines, Falconn++ with several heuristic add-ons gives a higher recall-speed tradeoff than Falconn. It is also competitive against HNSW, an efficient representative of graph-based solutions on high search recall regimes.

Table 1: Indexing space and time comparison between Falconn++ and HNSW on 3 data sets.

Algorithms	NYTimes		Glove300		Glove200	
	Space	Time	Space	Time	Space	Time
Hnsw	2.5 GB	7.8 mins	10.9 GB	26.7 mins	5.4 GB	13.7 mins
Falconn++	2.7 GB	**0.6 mins**	10.8 GB	**5.4 mins**	7.2 GB	**1.5 mins**

References

[1] Alexandr Andoni and Piotr Indyk. Near-optimal hashing algorithms for approximate nearest neighbor in high dimensions. In *FOCS*, pages 459–468, 2006.

[2] Alexandr Andoni, Piotr Indyk, Thijs Laarhoven, Ilya P. Razenshteyn, and Ludwig Schmidt. Practical and optimal LSH for angular distance. In *NIPS*, pages 1225–1233, 2015.

[3] Alexandr Andoni, Piotr Indyk, and Ilya P. Razenshteyn. Approximate nearest neighbor search in high dimensions. *CoRR*, abs/1806.09823, 2018.

[4] Alexandr Andoni, Thijs Laarhoven, Ilya P. Razenshteyn, and Erik Waingarten. Optimal hashing-based time-space trade-offs for approximate near neighbors. In *SODA*, pages 47–66, 2017.

[5] Alexandr Andoni and Ilya P. Razenshteyn. Optimal data-dependent hashing for approximate near neighbors. In *STOC*, pages 793–801, 2015.

[6] Martin Aumüller, Erik Bernhardsson, and Alexander John Faithfull. Ann-benchmarks: A benchmarking tool for approximate nearest neighbor algorithms. *Inf. Syst.*, 87, 2020.

[7] George H. Chen and Devavrat Shah. Explaining the success of nearest neighbor methods in prediction. *Found. Trends Mach. Learn.*, 10(5-6):337–588, 2018.

[8] Tobias Christiani. A framework for similarity search with space-time tradeoffs using locality-sensitive filtering. In *SODA*, pages 31–46, 2017.

[9] H. A. David and J. Galambos. The asymptotic theory of concomitants of order statistics. *Journal of Applied Probability*, 11(4):762–770, 1974.

[10] Sariel Har-Peled, Piotr Indyk, and Rajeev Motwani. Approximate nearest neighbor: Towards removing the curse of dimensionality. *Theory of Computing*, 8(1):321–350, 2012.

[11] Monika Rauch Henzinger. Finding near-duplicate web pages: a large-scale evaluation of algorithms. In *SIGIR*, pages 284–291, 2006.

[12] Russell Impagliazzo, Ramamohan Paturi, and Francis Zane. Which problems have strongly exponential complexity? *J. Comput. Syst. Sci.*, 63(4), 2001.

[13] Piotr Indyk and Rajeev Motwani. Approximate nearest neighbors: Towards removing the curse of dimensionality. In *STOC*, pages 604–613, 1998.

[14] Qin Lv, William Josephson, Zhe Wang, Moses Charikar, and Kai Li. Multi-probe LSH: efficient indexing for high-dimensional similarity search. In *VLDB*, pages 950–961, 2007.

[15] Yu A Malkov and Dmitry A Yashunin. Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs. *IEEE transactions on pattern analysis and machine intelligence*, 42(4):824–836, 2018.

[16] Marvin Minsky and Seymour A Papert. *Perceptrons: An introduction to computational geometry*. MIT press, 1969.

[17] Ryan O'Donnell, Yi Wu, and Yuan Zhou. Optimal lower bounds for locality-sensitive hashing (except when q is tiny). *ACM Trans. Comput. Theory*, 6(1):5:1–5:13, 2014.

[18] Rina Panigrahy. Entropy based nearest neighbor search in high dimensions. In *SODA*, pages 1186–1195, 2006.

[19] Ninh Pham. Simple yet efficient algorithms for maximum inner product search via extreme order statistics. In *KDD*, pages 1339–1347, 2021.

[20] Badrul Munir Sarwar, George Karypis, Joseph A. Konstan, and John Riedl. Item-based collaborative filtering recommendation algorithms. In *WWW*, pages 285–295, 2001.

[21] Gregory Shakhnarovich, Trevor Darrell, and Piotr Indyk. Nearest-neighbor methods in learning and vision. *IEEE Trans. Neural Networks*, 19(2):377, 2008.

[22] Narayanan Sundaram, Aizana Turmukhametova, Nadathur Satish, Todd Mostak, Piotr Indyk, Samuel Madden, and Pradeep Dubey. Streaming similarity search over one billion tweets using parallel locality-sensitive hashing. *PVLDB*, 6(14):1930–1941, 2013.

[23] Roger Weber, Hans-Jörg Schek, and Stephen Blott. A quantitative analysis and performance study for similarity-search methods in high-dimensional spaces. In *VLDB*, pages 194–205, 1998.

[24] Ryan Williams and Huacheng Yu. Finding orthogonal vectors in discrete structures. In *SODA*, pages 1867–1877, 2014.