BOUNDING MEMBERSHIP INFERENCE

ABSTRACT

Differential Privacy (DP) is the de facto standard for reasoning about the privacy guarantees of a training algorithm. Despite the empirical observation that DP reduces the vulnerability of models to existing membership inference (MI) attacks, a theoretical underpinning as to why this is the case is largely missing in the literature. In practice, this means that models need to be trained with differential privacy guarantees that greatly decrease their accuracy. In this paper we provide a tighter bound on the accuracy of any membership inference adversary when a training algorithm provides ϵ-DP. Our bound informs the design of a novel privacy amplification scheme, where an effective training set is sub-sampled from a larger set prior to the beginning of training, to greatly reduce the bound on MI accuracy. As a result, our scheme enables ϵ-DP users to employ looser differential privacy guarantees when training their model to limit the success of any MI adversary; this in turn ensures that the model's accuracy is less impacted by the privacy guarantee. Finally, we discuss implications of our MI bound on machine unlearning.

1 INTRODUCTION

Differential Privacy (DP) (Dwork, 2006) is employed extensively to reason about privacy guarantees in a variety of different settings (Dwork, 2008). Recently, DP started being used to give privacy guarantees for the training data of deep neural networks (DNNs) learned through stochastic gradient descent (Abadi et al., 2016). However, even though DP gives privacy guarantees and bounds the worst case privacy leakage, it is not immediately clear how these guarantees bound the accuracy of known existing forms of privacy infringement attacks.

At the time of writing, the most practical attack on the privacy of DNNs is Membership Inference (MI) (Shokri et al., 2017), where an attacker predicts whether or not a model used a particular data point for training (note that this is quite similar to the hypothetical adversary at the core of the game instantiated in the definition of DP); membership inference attacks saw a strong interest by the community, and several improvements and renditions were proposed since its inception (Sablayrolles et al., 2019; Choquette-Choo et al., 2021; Maini et al., 2021; Hu et al., 2021). Having privacy guarantees would desirably defend against MI, and in fact current literature highlights that DP does indeed give an upper bound on the performance of MI under various assumptions about the adversary (Yeom et al., 2018; Erlingsson et al., 2019; Sablayrolles et al., 2019; Jayaraman et al., 2020).

In this paper, we first propose a tighter bound on MI accuracy for training algorithms that provide ϵ-DP. Our approach uses a lemma about an equivalence of certain sets of datasets. Furthermore, in obtaining our bound, we also show how this bound can benefit from a form of privacy amplification where the training dataset itself is sub-sampled from a larger dataset. Amplification is a technique pervasively found in work improving the analysis of DP learners like DP-SGD (Abadi et al., 2016), and we observe the affect of our amplification on MI accuracy is significantly stronger than batch sampling (the common privacy amplification scheme for training DNNs).

Our bound also has consequences for the problem of unlearning (or data forgetting in ML) introduced by Cao & Yang (2015). In particular the MI accuracy on the point to be unlearned is a popular measure for how well a model has unlearned (Baumhauer et al., 2020; Graves et al., 2020; Golatkar et al., 2020b;a). However empirical verification of the MI accuracy can be open ended, as it is subjective to the attack employed. Theoretical bounds on all MI attacks, such as the one proposed in this work, circumvent this issue; a bound on the accuracy of MI attacks, in particular the probability

a data point was used in the training dataset, indicates a limitation for any entity to discern if the model had trained on the data point. In the case when this is sufficiently low (where sufficiently is defined apriori), one can then claim to have unlearned by achieving a model sufficiently likely to have not come from training with the data point. Our analysis shows that, if dataset subsampling is used, one can unlearn under this definition by training with a relatively large ϵ (and thus have less cost to performance).

To summarize, our contributions are:

- We present a tighter general bound on MI accuracy for ϵ-DP;
- We show how our tighter MI accuracy bound can benefit from a form of privacy amplification using dataset subsampling;
- We discuss the benefits of such bounds to Machine Unlearning as a rigorous way to use MI as a metric for unlearning.

2 BACKGROUND

2.1 DIFFERENTIAL PRIVACY

Differential privacy (DP) (Dwork, 2006) bounds how different the outputs of a function on adjacent inputs can be in order to give privacy guarantees for the inputs. More formally a function F is ϵ-DP if for all adjacent inputs x and x' (*i.e.* inputs with hamming distance 1) we have for all sets S in the output space:

$$\mathbb{P}(F(x) \in S) \le e^\epsilon \mathbb{P}(F(x') \in S) \tag{1}$$

We also have a more relaxed notion of (ϵ, δ)-DP where in the same setup as above, but with a parameter $\delta \in (0, 1]$, we have $\mathbb{P}(F(x) \in S) \le e^\epsilon \mathbb{P}(F(x') \in S) + \delta$. Notably, (ϵ, δ)-DP is used for functions where it is more natural to work with ℓ_2 metrics on the input space, which has to do with how DP guarantees are obtained.

To achieve DP guarantees one usually introduces noise to the output of the function F. The amount of noise is calibrated to the maximal ℓ_2 or ℓ_1 difference between all possible outputs of the function on adjacent datasets (also called sensitivity). Significant progress was achieved on minimizing the amount of noise needed for a given sensitivity (Balle & Wang, 2018), and on how DP guarantees scale when composing multiple DP functions (Dwork et al., 2010; Kairouz et al., 2015).

Abadi et al. (2016) demonstrated a method to make the final model returned by mini-batch SGD (ϵ, δ)-DP with respect to its training dataset by bounding the sensitivity of gradient updates during mini-batch SGD and introducing Gaussian noise to each update. This approach became the de-facto standard for DP guarantees in DNNs. However, the adoption is still greatly limited because of an observed trade-off between privacy guarantees and model utility. At the time of writing there is still no feasible ways to learn with low ϵ and high accuracy, and past work (Jagielski et al., 2020) have suggested that DP-analysis may be too loose and provides more privacy than is expected.

However, more recently Nasr et al. (2021) showed (using statistical tests and stronger adversaries) that the current state of the art approaches to achieving (ϵ, δ)-DP bounds for deep learning are tight, in contrast to Jagielski et al. (2020) results suggesting that they were loose. That is, there is not much more improvement to be gained by studying how to improve the (ϵ, δ)-DP bound from a given amount of noise or improving composition rules. Facing this, future improvements in DP training would lie in understanding the guarantees that DP bounds provide against the performance of relevant privacy attacks. This would allow us to be more informed about the guarantees required during training to defeat practical attacks and enable the use of looser guarantees if one is only interested in defending against a specific set of attacks.[1]

---

[1]It is worth noting that Nasr et al. (2021) showed that current analytic upper bounds on DP guarantees are tight, measuring them empirically with various strong privacy adversaries. Although results do suggest that bounds match, the paper did not investigate how DP guarantees limit performance of the adversary.

2.2 MEMBERSHIP INFERENCE

Shokri et al. (2017) introduced a MI attack against DNNs, which leveraged shadow models (models with the same architecture as the target model) trained on similar data in order to train a classifier which, given the outputs of a model on a data point, predicts if the model was trained on that data point or not. Since the introduction of this initial attack, the community has proposed several improved and variations of the original MI attack (Yeom et al., 2018; Salem et al., 2018; Sablayrolles et al., 2019; Truex et al., 2019; Jayaraman et al., 2020; Choquette-Choo et al., 2021; Maini et al., 2021), such as an attack that only look at predicted labels of the target model (Choquette-Choo et al., 2021).

MI attacks are currently the main practical threat to the privacy of a user's data used to train DNNs. Especially in the context of DP DNN learning, it would be beneficial to know how DP bounds translate to bounds on the accuracy of MI attacks. This would provide an understanding on what sort of DP guarantees an entity requires to ensure a sufficiently low maximum accuracy of an adversary trying to discern their training data from their deployed model. The bounds would hence help in guiding decisions regarding setting these parameters and their corresponding guarantees.

2.3 PREVIOUS BOUNDS

Before giving bounds on MI accuracy, we have to formally define the attack setting. Two of the main bounds (Yeom et al., 2018; Erlingsson et al., 2019) focused on an experimental setup first introduced by Yeom et al. (2018). To summarize the experiment, and in particular the situation the adversary is operating in, an adversary f is given a datapoint $\mathbf{x}^*$ that is 50% likely to have been used to train a model S or not. The adversary then either predicts 1 if they think it was used, or 0 otherwise. Let $b = 1$ or 0 indicate if the datapoint was or was not used for training respectively. We say the adversary was correct if their prediction matches b. We then define the adversary's advantage as improvement in accuracy over the 50% baseline of random guessing, or more specifically $2(A(f) - 0.5)$ where $A(f)$ is the accuracy of f.

For such an adversary operating in a scenario where data is equally likely to be included or not in the training dataset, Yeom et al. (2018) showed that they could bound the advantage of the adversary by $e^\epsilon - 1$ when training with ϵ-DP. In other words, they showed that they could bound the accuracy of the MI adversary by $e^\epsilon/2$. Their proof used the fact that the true positive rate (TPR) and false positive rate (FPR) of their adversary could be represented as expectations over the different data points in a dataset, and from that introduced the DP condition to obtain their MI bound, noting that MI advantage is equivalent to TPR - FPR.

Erlingsson et al. (2019) improved on the bound developed by Yeom et al. (2018) for an adversary operating under the same condition by utilizing a proposition given by Hall et al. (2013) on the relation between TPR and FPR for an (ϵ, δ)-DP function. Using these facts, Erlingsson et al. (2019) bounded the membership advantage by $1 - e^{-\epsilon} + \delta e^{-\epsilon}$, which is equivalent to bounding the accuracy of the adversary by $1 - e^{-\epsilon}/2$ when $\delta = 0$ (*i.e.* in ϵ-DP). This is, to the best of our knowledge, the previous state-of-the-art bound for high ϵ.

Other work have considered more general setups where the probability of sampling a datapoint in the dataset can vary, similar to what we consider in Section 3.1. For ϵ-DP, Sablayrolles et al. (2019) bounded the probability of a datapoint $\mathbf{x}^*$ being used in the training set of a model (i.e., the accuracy of an attacker who predicted the datapoint was in the dataset of the model) by $\mathbb{P}_{\mathbf{x}^*}(1) + \frac{\epsilon}{4}$ where $\mathbb{P}_{\mathbf{x}^*}(1)$ is the probability of the datapoint being in the dataset. This is, to the best of our knowledge, the previous state-of-the-art bound for low ϵ (when reduced to case of Yeom et al. (2018) by setting $\mathbb{P}_{\mathbf{x}^*}(1) = 0.5$ as to compare with Erlingsson et al. (2019)).

Finally, Jayaraman et al. (2020) bounded the positive predictive value of an attacker (*i.e.* its precision) on a model trained with (ϵ, δ)-DP when the FPR is fixed. It is worth noting that although the considered setup is similar to works covered above, it assumes an unbalanced sampling procedure. Similarly, Jayaraman et al. further bounded membership advantage under the experiment described by Yeom et al. (2018) for a fixed FPR. Erlingsson et al. (2019) followed a similar argument for their bound but were also able to remove the need for an explicit knowledge of the FPR.

2.4 UNLEARNING

Having bounds on membership inference is particularly relevant to machine unlearning for DNNs. Machine unlearning was first introduced by Cao & Yang (2015), who described a setting where it is important for the model to be able to forget certain training data points and focused on the cases where there were efficient analytic solutions. It was then extended to DNNs by Bourtoule et al. (2019) with the definition that a model has unlearned a data point if after the unlearning, the distribution of models returned is identical to the one that would result from not training with the data point at all. This definition was also stated earlier by Ginart et al. (2019) for other classes of machine learning models.

Given that unlearning is interested in removing the impact a data point had on the model, further work employed MI accuracy on the data point to be unlearned as a metric for how well the model had forgotten it after using some proposed unlearning method (Baumhauer et al., 2020; Graves et al., 2020; Golatkar et al., 2020b;a). Yet, empirical estimates on the membership status of a datapoint are subjective to the concrete MI attacks employed – indeed it may be possible that there exists a stronger practical attack.

Analytic bounds to MI attacks, on the other hand, resolve the subjectivity issue of MI as a metric for unlearning as they bound the success of any adversary. Therefore, our analysis has direct consequences on the field of machine unlearning, which we further discuss in Section 6.

3 THE BOUND

3.1 THE SCENARIO

We now proceed to formalize the scenario under which our adversary operates. Here, our scenario is more general than the one introduced by Yeom et al. (2018) and, as we note later, a specific instance of it can be reduced to their setup. In particular we formalize how an entity samples data into the training dataset, and proceed with our analysis from there.

Our intuition here is that one can imagine the existence of some large data superset containing all the data points an entity could have in their training dataset. Yet, any one of these datapoints only has some probability of being sampled into the training dataset. For example, this larger dataset could consist of all the users that gave an entity access to their data, and the probability comes from the entity randomly sampling the data to use in their training dataset. This randomness can be a black-box such that not even the entity knows what data was used to train. In essence, this is the scenario Jayaraman et al. (2020) considers, though in their case, the larger dataset is implicit and takes the form of a distribution. We can then imagine that the adversary (or perhaps an arbitrator in an unlearning setup) knows the larger dataset and tries to infer whether a particular data point was used in the training dataset. The particular MI attack that we analyze and bound is based on this scenario.

Specifically, let the individual training datasets D be constructed by sampling from a finite countable set where all datapoints are unique and sampled independently, *i.e.* from some larger set $\{\mathbf{x}_1, \cdots, \mathbf{x}_N\}$. That is if $D = \{\mathbf{x}_1, \mathbf{x}_2, \cdots, \mathbf{x}_n\}$ then the probability of sampling D is $\mathbb{P}(D) = \mathbb{P}_{\mathbf{x}_1}(1)\mathbb{P}_{\mathbf{x}_2}(1)\cdots\mathbb{P}_{\mathbf{x}_n}(1)\mathbb{P}_{\mathbf{x}_{n+1}}(0)\cdots\mathbb{P}_{\mathbf{x}_N}(0)$, where $\mathbb{P}_{\mathbf{x}_i}(1)$ is probability of drawing $\mathbf{x}_i$ into the dataset and $\mathbb{P}_{\mathbf{x}_i}(0)$ is the probability of not.

We define $\mathfrak{D}$ as the set of all datasets. Let now $\mathfrak{D}_{\mathbf{x}^*}$ be the set of all datasets that contain a particular point $\mathbf{x}^* \in \{\mathbf{x}_1, \cdots, \mathbf{x}_N\}$, that is $\mathfrak{D}_{\mathbf{x}^*} = \{D \ s.t \ \mathbf{x}^* \in D\}$. Similarly let $\mathfrak{D}_{\mathbf{x}^*}'$ be the set of all datasets that do not contain $\mathbf{x}^*$, *i.e.* $\mathfrak{D}_{\mathbf{x}^*}' = \{D' \ s.t \ \mathbf{x}^* \notin D'\}$. Note $\mathfrak{D} = \mathfrak{D}_{\mathbf{x}^*} \cup \mathfrak{D}_{\mathbf{x}^*}'$ by the simple logic that any dataset has or does not have $\mathbf{x}^*$ in it. We then have the following lemma.

Lemma 1. *$\mathfrak{D}_{\mathbf{x}^*}$ and $\mathfrak{D}_{\mathbf{x}^*}'$ are in bijective correspondence with $\mathbb{P}(D)\frac{\mathbb{P}_{\mathbf{x}^*}(0)}{\mathbb{P}_{\mathbf{x}^*}(1)} = \mathbb{P}(D')$ for $D \in \mathfrak{D}_{\mathbf{x}^*}$ and $D' \in \mathfrak{D}_{\mathbf{x}^*}'$ that map to each other under the bijective correspondence.*

See Appendix A for the proof.

Once some dataset D is obtained, we call H the training function which takes in D and outputs a model M as a set of weights in the form of a real vector. Recall that H is ϵ-DP if for all adjacent datasets D and D' and any set of model(s) S in the output space of H (*i.e.* some weights) we have:

$$\mathbb{P}(H(D) \in S) \le e^{\epsilon}\mathbb{P}(H(D') \in S) \tag{2}$$

It should be noted that from now on we assume that a set S has a non-zero probability to be produced by H. This is sensible as we are not interested in membership inference attacks on sets of models that have 0 probability to come from training; note if $\mathbb{P}(H(D) \in S) = 0$, then $\mathbb{P}(H(D') \in S) = 0$ for all adjacent D' as $0 \le \mathbb{P}(H(D') \in S) \le e^{\epsilon}\mathbb{P}(H(D) \in S) = 0$, and thus the probability is 0 for all countable datasets as we can construct any dataset by removing and adding a data point (which does not change the probability if it is initially 0) countably many times.

Lastly, we define our MI adversary as a function f which takes a set of models S and a data point $\mathbf{x}^*$ to deterministically output either 1 or 0, corresponding to whether $\mathbf{x}^*$ was in the dataset D used to obtain the models in S or not respectively. Note the generality of this adversary, as we do not consider how the adversary obtains the function *i.e.* it can have arbitrary strength. Any such adversary will then satisfy the upper and lower bounds we derive in Theorem 1 and Corollary 1.

With that, we have the following definition of accuracy, *i.e.* how often f is correct given we repeat the above probabilistic data sampling and training infinitely many times and test how often a particular set S did in fact come from $D \in \mathfrak{D}_{\mathbf{x}^*}$ if $f(\mathbf{x}^*, S) = 1$, or how often did it come from $D' \in \mathfrak{D}_{\mathbf{x}^*}'$ if $f(\mathbf{x}^*, S) = 0$. Note here "how often" means the probability.

Definition 1 (MI accuracy). *The positive accuracy of $f(\mathbf{x}^*, S)$, the accuracy if f outputs 1 which we define as $A(f(\mathbf{x}^*, S) = 1)$, is $\mathbb{P}(\mathbf{x}^* \in D|S)$ and the negative accuracy, the accuracy if f outputs 0 which we define as $A(f(\mathbf{x}^*, S) = 0)$, is $\mathbb{P}(\mathbf{x}^* \notin D|S) = 1 - \mathbb{P}(\mathbf{x}^* \in D|S)$*

3.2 MAIN RESULT

We now proceed to use Lemma 1 to bound the positive and negative accuracy of MI, as stated in Definition 1, for a training function H that is ϵ-DP under the data-sampling scenario defined earlier. Our approach differs from those we discussed in Section 2.3 in that we now focus on the definition of the conditional probability $\mathbb{P}(\mathbf{x}^* \in D|S)$ as a quotient; finding a bound then reduces to finding a way to simplify the quotient with the ϵ-DP definition, which we achieve using Lemma 1.

What follows are the technical results, with Section 4, 5, and 6 discussing the main consequences of the bound.

Theorem 1 (DP bounds MI positive accuracy). *If f is a MI attack applied to a set of models S and it predicts if $\mathbf{x}^*$ was in the datasets used to obtain them, and the training process H is DP with ϵ, its accuracy is upper-bounded by $\left(1 + \frac{e^{-\epsilon}\mathbb{P}_{\mathbf{x}^*}(0)}{\mathbb{P}_{\mathbf{x}^*}(1)}\right)^{-1}$ and lower bounded by $\left(1 + \frac{e^{\epsilon}\mathbb{P}_{\mathbf{x}^*}(0)}{\mathbb{P}_{\mathbf{x}^*}(1)}\right)^{-1}$, where $\mathbb{P}_{\mathbf{x}^*}(1)$ is the probability of drawing $\mathbf{x}^*$ into the dataset.*

See Appendix A for the proof.

By the definition of negative accuracy of f we have the following corollary:

Corollary 1 (DP bounds MI negative accuracy). *If f is an MI attack applied to a set of models S and it predicts if $\mathbf{x}^*$ is not in it, and the training process H is DP with ϵ, then the accuracy is upper-bounded by $\left(1 + \frac{e^{-\epsilon}\mathbb{P}_{\mathbf{x}^*}(1)}{\mathbb{P}_{\mathbf{x}^*}(0)}\right)^{-1}$ and lower-bounded by $\left(1 + \frac{e^{\epsilon}\mathbb{P}_{\mathbf{x}^*}(1)}{\mathbb{P}_{\mathbf{x}^*}(0)}\right)^{-1}$, where $\mathbb{P}_{\mathbf{x}^*}(1)$ is the probability of drawing $\mathbf{x}^*$ into the dataset.*

See Appendix A for the proof.

Note that in the case $\mathbb{P}_{\mathbf{x}^*}(1) = \mathbb{P}_{\mathbf{x}^*}(0) = 0.5$, the bounds given by Theorem 1 and Corollary 1 are identical. Therefore, as $f(\mathbf{x}^*, S)$ must output either 0 or 1, we have a more general claim that the attack accuracy (maximum of positive or negative accuracy) is always bounded by the same values given by Theorem 1.

4 THE AMPLIFICATION EFFECT OF $\mathbb{P}_{\mathbf{x}^*}(1)$

The above scenario is a specific instance of what Theorem 1 implies. More generally, Theorem 1 shows that decreasing $\mathbb{P}_{\mathbf{x}^*}(1)$ directly leads to a decrease in the upper bound of the accuracy

an adversary has when predicting the presence of x^* in the training dataset. That is, by simply reducing $\mathbb{P}_{\mathbf{x}^*}(1)$ an entity can reduce the accuracy of associating $\mathbf{x}^*$ to any specific set of models in a fashion similar to privacy amplification for DP, where low batch sampling probability increases privacy (Beimel et al., 2010; Kasiviswanathan et al., 2011; Abadi et al., 2016).

The importance of $\mathbb{P}_{\mathbf{x}^*}(1)$ against positive MI accuracy, defined as $\mathbb{P}(\mathbf{x}^*|S)$ where S is any set of models, is depicted in Figure 4 (see Appendix B), where for different ϵ we plotted the upper bound on positive accuracy given by Theorem 1 as we change $\mathbb{P}_{\mathbf{x}^*}(1)$. In particular for $\epsilon = 2$ when $\mathbb{P}_{\mathbf{x}^*}(1) = 0.01$ (*i.e.* 1%) we have the positive accuracy is bounded by 6.9%.

An interesting question is how does DP privacy amplification (which we get by sampling relatively small batches compared to the dataset) compare to the amplification we get from $\mathbb{P}_{\mathbf{x}^*}(0)/\mathbb{P}_{\mathbf{x}^*}(1)$ for our bound. Note that decreasing $\mathbb{P}_{\mathbf{x}^*}(0)/\mathbb{P}_{\mathbf{x}^*}(1)$ places no restriction on the sampling rate for batch sizes (which is how one would get DP privacy amplification) upto a point. After this point, the expectation of the training dataset size decreases and thus the lowest possible sampling rate $1/n$, where n in the training set size, increases in expectation. Nevertheless, now including q for DP privacy amplification, we can compare their effect by focusing on just the $e^{-q\epsilon_0}\mathbb{P}_{\mathbf{x}}(0)/\mathbb{P}_{\mathbf{x}}(1)$ term in the bound given by Theorem 1, where the goal is to maximize this in order the make the upper bound as small as possible. In particular, we see decreasing q increases this term by $O(e^{-t})$ where as decreasing $\mathbb{P}_{\mathbf{x}^*}(1)$ increases this term by $O((1-t)/t)$, which is slower than $O(e^{-t})$ upto a point, then faster (do note that we are looking at the order as the variable t decreases); Figure 1 plots this relation. This same comparison holds more generally when comparing the effect of ϵ and $\mathbb{P}_{\mathbf{x}^*}(1)$.

More generally, what this says is that to defend against an adversary there needs to be some indistinguishability between models from adjacent datasets (the ϵ-DP guarantee). However, after a certain point the uncertainty from sampling the training dataset is much more influential than the one obtained by making the models even less distinguishable. That said, one should note that sampling the training dataset may eventually significantly decrease the accuracy of models learned (from less data). This may put practical constraints on how much one can reduce $\mathbb{P}_{\mathbf{x}^*}(1)$.

Figure 1: Comparing the DP amplification observed by decreasing batch probability (given by e^{-t}) to the amplification we observe from decreasing $\mathbb{P}_{\mathbf{x}}(1)$ (given by $(1-t)/t$)

5 DISCUSSION

5.1 OUR BOUND IS TIGHTER THAN EARLIER RESULTS

We first compare our main technical result, the bound on a MI adversary's success, with the two key baselines we identified earlier (Sablayrolles et al., 2019; Erlingsson et al., 2019). The setup described in Section 3.1 is equivalent to the MI experiment defined by Yeom et al. (2018) when $\mathbb{P}_{\mathbf{x}_i}(1) = 0.5 \; \forall \mathbf{x}_i \in \{\mathbf{x}_1, \cdots, \mathbf{x}_N\}$. That is, if the training dataset was constructed by sampling data points from a larger dataset by a coin flip, then when the adversary is given any data point from the larger dataset to test there is a 50% chance it was in the training set or not. Furthermore, recall that when $\mathbb{P}_{\mathbf{x}^*}(1) = 0.5$, then Theorem 1 reduces to bounds on the overall accuracy of any MI attack f (as the bounds on positive and negative accuracy are the same). We can thus compare the upper-bound on MI accuracy that we achieved with the current tightest bounds given by Erlingsson

Figure 2: Comparing the upper bound to MI performance we achieved to that given by Erlingsson et al. (2019) and Sablayrolles et al. (2019). In particular note we are tighter for all ϵ.

et al. (2019) and Sablayrolles et al. (2019) for ϵ-DP; we stated these bounds earlier in Section 2.3, where for the latter bound we also set $\mathbb{P}_{\mathbf{x}^*}(1) = 0.5$.

Our bound, and these two previous bounds, are depicted in Figure 2, where we see the bound given in Theorem 1 is always tighter than both of the previous bounds. In particular, we see that it is closer to the one introduced by Sablayrolles et al. for small ϵ and closer to the one defined by Erlingsson et al. for large ϵ. Notably, for $\epsilon = 1$, we bound the accuracy of an MI attack by 73.1% whereas Erlingsson et al. bound it by 81.6%, and Sablayrolles et al. by 75%. For $\epsilon = 2$, we bound MI accuracy by 88% whereas Erlingsson et al. bound it by 95% and Sablayrolles et al. by 100%.

5.2 ANALYSIS OF 1D LOGISTIC REGRESSION

We now motivate future work on MI bounds by illustrating how our approach of bounding the positive accuracy (defined as $\mathbb{P}(\mathbf{x}^*|S)$) of a MI adversary for ϵ-DP does not immediately extend to (ϵ, δ)-DP. Such an extension would be desirable so one can capture the success of MI adversaries against training algorithms that only provide relaxed guarantees of DP, as opposed to the ε-DP guarantees we studied. In particular, we give a practical counter-example that shows for a specific MI attack on an (ϵ, δ)-DP logistic regression that there is no bound on the positive accuracy of the adversary, unlike what follows from our bound for ε-DP. Nevertheless, we demonstrate how one can still tailor bounds on general MI accuracy for this specific attack and remark how the bound we get by doing this is much tighter than what our theorem states for any MI adversary in the tighter ϵ-DP privacy conditions.

5.2.1 POSITIVE ACCURACY IS NOT BOUNDED

Consider a set of two (scalar) points $\{x_1, x_2\}$ which are drawn into the training set D with $\mathbb{P}_{x_1}(1) = 1$ and $\mathbb{P}_{x_2}(1) = 0.5$; that is x_1 is always in the training set, and x_2 has a 50% chance of being in the training set. Let model M be a single dimensional logistic regression without bias defined as $M(x) = wx$ initialized such that for cross-entropy loss L, $\nabla L|_{\mathbf{x}_1} \approx 0$ (i.e. set $x_1 = \{(10^6, 1)\}$ and the weights $w = 10^6$ so that $M(x) = 10^6 x$ and thus the softmax output of the model is approximately 1 on x_1 and thus gradient is approximately 0). Conversely set x_2 such that the gradient on it is less than -1 (i.e., for the above setup set $x_2 = \{(10^6, 0)\}$).

Now, train the model to $(1, 10^{-5})$-DP following Abadi et al. (2016) with $\eta = 1$, sampling rate of 100%, a maximum gradient norm of 1, for one step. Note these are just parameters which we are allowed to change under the DP analysis, and we found the noise we would need for $(1, 10^{-5})$-DP is 4.0412. Then consider running a MI attack on the above setup where if for some threshold α the final weights $\mathbf{W}$ are s.t if $\mathbf{W} \leq \alpha$ one classifies those weights as having come from the dataset with x_2, otherwise not. Do note that here we use $\mathbf{W}$ for the final weights as opposed to w to emphasize that we are now talking about a random variable. The intuition for this attack is that if the dataset only contain x_1 then the weights do not change, but if the dataset contains x_2 we know the resulting gradient is negative (by construction) and thus decreases the weights (before noise).

By the earlier setup on how training datasets are constructed note that $D = \{x_1\}$ or $D = \{x_1, x_2\}$, and we will denote these D_1 and D_2 respectively. Note that if M trained on D_1 following the suggested data points and initial weights, we have the distribution of final weight $\mathbf{W}_{D_1} = N(10^6, \sigma) =$

(a) Positive accuracy as a function of the threshold   (b) Accuracy as a function of the threshold

Figure 3: Impact of threshold on positive accuracy and accuracy.

$N(10^6, 4.0412)$ where σ denotes the noise needed for $(1, 10^{-5})$-DP as stated earlier. Similarly $\mathbf{W}_{D_2} = N(10^6 - 1, 4.0412)$, since the maximum gradient norm is set to 1.

For the above MI attack we can then bound the positive accuracy as a function of α by:

$$\mathbb{P}(D_2|\mathbf{W} \leq \alpha) = \frac{\mathbb{P}(\mathbf{W}_{D_2} \leq \alpha) * \mathbb{P}(D_2)}{\mathbb{P}(\mathbf{W}_{D_2} \leq \alpha) * \mathbb{P}(D_2) + \mathbb{P}(\mathbf{W}_{D_1} \leq \alpha) * \mathbb{P}(D_1)} \tag{3}$$

$$= \frac{\phi(\mathbf{W}_{D_2}, \alpha) * 0.5}{\phi(\mathbf{W}_{D_1}, \alpha) * 0.5 + \phi(\mathbf{W}_{D_2}, \alpha) * 0.5} \tag{4}$$

where $\phi(\mathbf{W}, \alpha)$ is the (Gaussian) cumulative function of random variable $\mathbf{W}$ upto α.

We plot this in Figure 3a, and unlike Theorem 1, note how it is not bounded by anything less than 1 and goes to 1 as the threshold α decreases (*i.e.* $\forall m \in [0, 1) \ \exists \alpha$ s.t $S = (-\infty, \alpha]$ yields positive accuracy greater than m).

5.2.2 MI ACCURACY IS BOUNDED

The previous section showed that for (ϵ, δ)-DP the positive accuracy of our adversary is not bounded. However, as we will show in this section, this does not mean the overall accuracy is not bounded. Specifically, for the same attack and setup as in Section 5.2.1, note that we have a bound on the general accuracy of this specific attack given by:

$$\mathbb{P}(D_1|\mathbf{W} \geq \alpha)*\mathbb{P}(\mathbf{W} \geq \alpha)+\mathbb{P}(D_2|\mathbf{W} \leq \alpha)*\mathbb{P}(\mathbf{W} \leq \alpha) = (1-\phi(\mathbf{W}_{D_1}, \alpha))*0.5+\phi(\mathbf{W}_{D_2}, \alpha)*0.5 \tag{5}$$

We illustrate this in Figure 3b and observe that it is bounded by 54.9% for $\alpha = 10^6 - 0.5$. Do note that 54.9% is significantly less than 73.1% which is what our bound gives for $\epsilon = 1$-DP, and $\epsilon = 1$-DP is a tighter DP condition than $(\epsilon = 1, \delta = 10^{-5})$-DP which is what is depicted in Figure 3b. This illustrates how the bound can be further tightened with a better understanding of the (worst case scenario) weight distribution and the nature of the attack. We leave this to future work.

5.3 MI ADVANTAGE

Previous work, particularly Yeom et al. (2018) and Erlingsson et al. (2019), focused on membership advantage, which is essentially an improvement in accuracy of f over the random guess of 50% of drawing a point in the training dataset. More specifically, if we let $A(f)$ denote the accuracy of f, then membership advantage is computed as $2(A(f) - 0.5)$. We can generalize this to ask what the membership advantage of the positive accuracy of f compared to the baseline $\mathbb{P}_{\mathbf{x}^*}(1)$ is.

Theorem 1 gives us an upper bound on the positive accuracy and thus an upper bound on the positive advantage of f denoted as $Ad(f)$:

$$Ad(f) = 2\left(A(f(\mathbf{x}^*, S) = 1) - \mathbb{P}_{\mathbf{x}^*}(1)\right) \leq 2\left(\left(1 + \frac{e^{-\epsilon}\mathbb{P}_{\mathbf{x}^*}(0)}{\mathbb{P}_{\mathbf{x}^*}(1)}\right)^{-1} - \mathbb{P}_{\mathbf{x}^*}(1)\right) \tag{6}$$

We plotted this advantage as a function of $\mathbb{P}_{\mathbf{x}^*}(1)$ for different fixed ϵ in Figure 5 (see Appendix B). We observe that the advantage clearly depends on $\mathbb{P}_{\mathbf{x}^*}(1)$, and in fact for different ϵ, the $\mathbb{P}_{\mathbf{x}^*}(1)$ resulting in the maximum advantage changes. In particular, $\mathbb{P}_{\mathbf{x}^*}(1) = 0.5$ is not close to the advantage for large ϵ, which shows how the fixed experiment proposed by Yeom et al. (2018) does not necessarily give the maximum advantage an adversary could have.

However, it should be noted that higher advantage here does not mean a higher upper bound on accuracy; as we already saw in Figure 4, the upper bound on accuracy increases monotonically with $\mathbb{P}_{\mathbf{x}^*}(1)$, in contrast to the bump observed with membership advantage. This serves to contrast the study of advantage and the study of accuracy for future work.

6 IMPORTANCE TO DATA DELETION

The ability for an entity to decrease the ability for an arbitrator to attribute a data point to a model also has consequences for machine unlearning and data deletion requests as mentioned in Section 2.4.

In particular if $\mathbb{P}(\mathbf{x}^* \in D|S)$ is sufficiently low, that is the likelihood of S coming from $\mathbf{x}^*$ is low, then an entity could claim that they do not need to delete the users data since their model is most likely independent of that data point as it most likely came from a model without it: *i.e.* leading to plausible deniability. This is similar to the logic presented by Sekhari et al. (2021) where unlearning is presented probablistically in terms of (ϵ, δ)-unlearning (which (ϵ, δ)-DP is sufficient for, but is not necessary).

We also observe an analogous result to Sekhari et al. (2021) where we can only handle a maximum number of deletion requests before no longer having sufficiently low probability. To be exact, let us say we do not need to undergo any unlearning process given a set of data deletion request $\hat{\mathbf{x}}^*$ if $\mathbb{P}(\hat{\mathbf{x}}^* \notin D|S) \geq B$ for some B (*i.e.* we are working with probability of not having that set of data in our training set which we want to be high). Note that we sampled data independently, thus if $\hat{\mathbf{x}}^* = \{\mathbf{x}_1^*, \mathbf{x}_2^*, \cdots, \mathbf{x}_m^*\}$, then $\mathbb{P}(\hat{\mathbf{x}}^* \notin D|S) = \mathbb{P}(\mathbf{x}_1^* \notin D|S) \cdots \mathbb{P}(\mathbf{x}_m^* \notin D|S)$.

Now, for simplicity, assume the probability of drawing all points into the datasets are the same, so that for all $\mathbf{x}_i^*$ we have the same bound given by Corollary 1, that is $\mathbb{P}(\mathbf{x}_i^* \notin D|S) > L$ for some $L \leq 1$. Then we have $\mathbb{P}(\hat{\mathbf{x}}^* \notin D|S) \geq L^m$ and so an entity does not need to unlearn if $L^m \geq B$, *i.e.* if $m \leq \frac{\ln 1/B}{\ln 1/L} = \frac{\ln B}{\ln L}$. This gives a bound on how many deletion requests the entity can avoid in terms of the lower bound given in Corollary 1.

In particular, note that if $\{\mathbf{x}_1 \cdots \mathbf{x}_N\}$ is the larger set of data points an entity is sampling from, and $\mathbb{P}_{\mathbf{x}}(1) = c/N \; \forall \mathbf{x} \in \{\mathbf{x}_1 \cdots \mathbf{x}_N\}$, then the lower bound given by Corollary 1 is $\left(1 + \frac{e^{-\epsilon} \frac{c}{N}}{1 - \frac{c}{N}}\right)^{-1}$. Sekhari et al. (2021) showed that with typical DP the deletion requests grow linearly with the size of the training (in the above case c represents the expected training set size). We thus compare a linear line w.r.t to c to $\frac{\ln B}{\ln L(c)}$ (where L is given in the earlier expression for the bound from Corollary 1) in Figure 6 (see Appendix B) to observe their respective magnitude: we fix $B = 0.8, N = 10000$ and $\epsilon = 1$ as we are interested in general trends. We observe that our deletion capacity is significantly higher for low expected training set sizes and is marginally lower than a linear trend for larger training set sizes.

7 CONCLUSION

In this work, we provide a tighter bound on MI accuracy against ML models trained with ϵ-DP. Our bound highlights that intricacies of dataset construction are of great importance for model vulnerability to MI attacks. Indeed, based on our findings, we develop a privacy amplification scheme that just requires one to sub-sample their training dataset from larger pool of possible data points.

Based on our results, entities training their ML models with DP can employ looser privacy guarantees (and thereby preserve their models' accuracy better) while still limiting the success of MI attacks. Finally, our bound, and more generally bounds on positive MI accuracy, can also be applied to handle unlearning requests when doing machine unlearning if unlearning is defined by achieving a model with low probability of having come that data point.

REFERENCES

Martin Abadi, Andy Chu, Ian Goodfellow, H Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. Deep learning with differential privacy. In *Proceedings of the 2016 ACM SIGSAC conference on computer and communications security*, pp. 308–318, 2016.

Borja Balle and Yu-Xiang Wang. Improving the gaussian mechanism for differential privacy: Analytical calibration and optimal denoising. In *International Conference on Machine Learning*, pp. 394–403. PMLR, 2018.

Thomas Baumhauer, Pascal Schöttle, and Matthias Zeppelzauer. Machine unlearning: Linear filtration for logit-based classifiers. *arXiv preprint arXiv:2002.02730*, 2020.

Amos Beimel, Shiva Prasad Kasiviswanathan, and Kobbi Nissim. Bounds on the sample complexity for private learning and private data release. In *Theory of Cryptography Conference*, pp. 437–454. Springer, 2010.

Lucas Bourtoule, Varun Chandrasekaran, Christopher A Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. Machine unlearning. *arXiv preprint arXiv:1912.03817*, 2019.

Yinzhi Cao and Junfeng Yang. Towards making systems forget with machine unlearning. In *2015 IEEE Symposium on Security and Privacy*, pp. 463–480. IEEE, 2015.

Christopher A Choquette-Choo, Florian Tramer, Nicholas Carlini, and Nicolas Papernot. Label-only membership inference attacks. In *International Conference on Machine Learning*, pp. 1964–1974. PMLR, 2021.

Cynthia Dwork. Differential privacy. In *International Colloquium on Automata, Languages, and Programming*, pp. 1–12. Springer, 2006.

Cynthia Dwork. Differential privacy: A survey of results. In *International conference on theory and applications of models of computation*, pp. 1–19. Springer, 2008.

Cynthia Dwork, Guy N Rothblum, and Salil Vadhan. Boosting and differential privacy. In *2010 IEEE 51st Annual Symposium on Foundations of Computer Science*, pp. 51–60. IEEE, 2010.

Úlfar Erlingsson, Ilya Mironov, Ananth Raghunathan, and Shuang Song. That which we call private. *arXiv preprint arXiv:1908.03566*, 2019.

Antonio Ginart, Melody Y Guan, Gregory Valiant, and James Zou. Making ai forget you: Data deletion in machine learning. *arXiv preprint arXiv:1907.05012*, 2019.

Aditya Golatkar, Alessandro Achille, and Stefano Soatto. Eternal sunshine of the spotless net: Selective forgetting in deep networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9304–9312, 2020a.

Aditya Golatkar, Alessandro Achille, and Stefano Soatto. Forgetting outside the box: Scrubbing deep networks of information accessible from input-output observations. In *European Conference on Computer Vision*, pp. 383–398. Springer, 2020b.

Laura Graves, Vineel Nagisetty, and Vijay Ganesh. Amnesiac machine learning. *arXiv preprint arXiv:2010.10981*, 2020.

Rob Hall, Alessandro Rinaldo, and Larry Wasserman. Differential privacy for functions and functional data. *The Journal of Machine Learning Research*, 14(1):703–727, 2013.

Hongsheng Hu, Zoran Salcic, Gillian Dobbie, and Xuyun Zhang. Membership inference attacks on machine learning: A survey. *arXiv preprint arXiv:2103.07853*, 2021.

Matthew Jagielski, Jonathan Ullman, and Alina Oprea. Auditing differentially private machine learning: How private is private sgd? *arXiv preprint arXiv:2006.07709*, 2020.

Bargav Jayaraman, Lingxiao Wang, Katherine Knipmeyer, Quanquan Gu, and David Evans. Revisiting membership inference under realistic assumptions. *arXiv preprint arXiv:2005.10881*, 2020.

Peter Kairouz, Sewoong Oh, and Pramod Viswanath. The composition theorem for differential privacy. In *International conference on machine learning*, pp. 1376–1385. PMLR, 2015.

Shiva Prasad Kasiviswanathan, Homin K Lee, Kobbi Nissim, Sofya Raskhodnikova, and Adam Smith. What can we learn privately? *SIAM Journal on Computing*, 40(3):793–826, 2011.

Pratyush Maini, Mohammad Yaghini, and Nicolas Papernot. Dataset inference: Ownership resolution in machine learning. *arXiv preprint arXiv:2104.10706*, 2021.

Milad Nasr, Shuang Song, Abhradeep Thakurta, Nicolas Papernot, and Nicholas Carlini. Adversary instantiation: Lower bounds for differentially private machine learning. *arXiv preprint arXiv:2101.04535*, 2021.

Alexandre Sablayrolles, Matthijs Douze, Cordelia Schmid, Yann Ollivier, and Hervé Jégou. White-box vs black-box: Bayes optimal strategies for membership inference. In *International Conference on Machine Learning*, pp. 5558–5567. PMLR, 2019.

Ahmed Salem, Yang Zhang, Mathias Humbert, Pascal Berrang, Mario Fritz, and Michael Backes. Ml-leaks: Model and data independent membership inference attacks and defenses on machine learning models. *arXiv preprint arXiv:1806.01246*, 2018.

Ayush Sekhari, Jayadev Acharya, Gautam Kamath, and Ananda Theertha Suresh. Remember what you want to forget: Algorithms for machine unlearning. *arXiv preprint arXiv:2103.03279*, 2021.

Reza Shokri, Marco Stronati, Congzheng Song, and Vitaly Shmatikov. Membership inference attacks against machine learning models. In *2017 IEEE Symposium on Security and Privacy (SP)*, pp. 3–18. IEEE, 2017.

Stacey Truex, Ling Liu, Mehmet Emre Gursoy, Lei Yu, and Wenqi Wei. Demystifying membership inference attacks in machine learning as a service. *IEEE Transactions on Services Computing*, 2019.

Samuel Yeom, Irene Giacomelli, Matt Fredrikson, and Somesh Jha. Privacy risk in machine learning: Analyzing the connection to overfitting. In *2018 IEEE 31st Computer Security Foundations Symposium (CSF)*, pp. 268–282. IEEE, 2018.

A PROOFS

Lemma 1 Note that for a given $D = \{\mathbf{x}_1, \cdots, \mathbf{x}_n\} \in \mathfrak{D}_{\mathbf{x}^*}$, $D' = D/\mathbf{x}^* \in \mathfrak{D}_{\mathbf{x}^*}'$ is unique (*i.e.* the map by removing $\mathbf{x}^*$ is injective) and similarly for a given $D' \in \mathfrak{D}_{\mathbf{x}^*}'$ $D = D' \cup \mathbf{x}^*$ is unique (*i.e.* the map by adding $\mathbf{x}^*$ is injective). Thus, we have injective maps running both ways which are the inverses of each other. As a consequence, we have $\mathfrak{D}_{\mathbf{x}^*}$ and $\mathfrak{D}_{\mathbf{x}^*}'$ are in bijective correspondence.

Now if the larger set of datapoints is $\{\mathbf{x}_1 \cdots \mathbf{x}_{n-1}, \mathbf{x}^*, \mathbf{x}_n \cdots \mathbf{x}_N\}$ letting $D = \{\mathbf{x}_1 \cdots \mathbf{x}_{n-1}\} \cup \mathbf{x}^*$ and $D' = \{\mathbf{x}_1 \cdots \mathbf{x}_{n-1}\}$ be any pair of datasets that map to each other by the above bijective map, then note $\mathbb{P}(D) = \mathbb{P}_{\mathbf{x}_1}(1)\mathbb{P}_{\mathbf{x}_2}(1)\cdots\mathbb{P}_{\mathbf{x}_{n-1}}(1)\mathbb{P}_{\mathbf{x}^*}(1)\cdots\mathbb{P}_{\mathbf{x}_{n+1}}(0)\cdots\mathbb{P}_{\mathbf{x}_N}(0)$ and $\mathbb{P}(D') = \mathbb{P}_{\mathbf{x}_1}(1)\mathbb{P}_{\mathbf{x}_2}(1)\cdots\mathbb{P}_{\mathbf{x}_{n-1}}(1)\mathbb{P}_{\mathbf{x}^*}(0)\cdots\mathbb{P}_{\mathbf{x}_{n+1}}(0)\cdots\mathbb{P}_{\mathbf{x}_N}(0)$. In particular we have $\mathbb{P}(D)\frac{\mathbb{P}_{\mathbf{x}^*}(0)}{\mathbb{P}_{\mathbf{x}^*}(1)} = \mathbb{P}(D')$.

Theorem 1 The positive accuracy of f is:

$$A(f(\mathbf{x}^*, S) = 1) = \mathbb{P}(\mathbf{x}^*|S) = \frac{\sum_{D\in\mathfrak{D}_{\mathbf{x}^*}} \mathbb{P}(H(D) \in S)\mathbb{P}(D)}{\sum_{D\in\mathfrak{D}} \mathbb{P}(H(D) \in S)\mathbb{P}(D)} \tag{7}$$

By the observation $\mathfrak{D} = \mathfrak{D}_{\mathbf{x}^*} \cup \mathfrak{D}_{\mathbf{x}^*}'$ we have that the denominator can be split into $\sum_{D\in\mathfrak{D}_{\mathbf{x}^*}} \mathbb{P}(H(D) \in S)\mathbb{P}(D) + \sum_{D'\in\mathfrak{D}_{\mathbf{x}^*}'} \mathbb{P}(H(D') \in S)\mathbb{P}(D')$.

By Lemma 1, we can replace the $D' \in \mathfrak{D}_{\mathbf{x}^*}'$ in the second sum by $D \in \mathfrak{D}_{\mathbf{x}^*}$ and replace $\mathbb{P}(D')$ by $\mathbb{P}(D)\frac{\mathbb{P}_{\mathbf{x}^*}(0)}{\mathbb{P}_{\mathbf{x}^*}(1)}$. For $\mathbb{P}(H(D') \in S)$ note by H being ϵ-DP we have $\mathbb{P}(H(D') \in S) \geq$

$e^{-\epsilon}\mathbb{P}(H(D) \in S)$ and so with the previous replacements we have that the denominator is greater than $(1 + \frac{e^{-\epsilon}\mathbb{P}_{\mathbf{x}^*}(0)}{\mathbb{P}_{\mathbf{x}^*}(1)}) \cdot \sum_{D \in \mathfrak{D}_{\mathbf{x}^*}} \mathbb{P}(H(D) \in S)\mathbb{P}(D)$.

Thus, the accuracy of f is $\leq \frac{1}{1 + \frac{e^{-\epsilon}\mathbb{P}_{\mathbf{x}^*}(0)}{\mathbb{P}_{\mathbf{x}^*}(1)}}$ (*i.e.* the upper bound).

If instead we used the fact that $\mathbb{P}(H(D') \in S) \leq e^{\epsilon}\mathbb{P}(H(D) \in S)$, we would find that the accuracy of f is $\geq \frac{1}{1 + \frac{e^{\epsilon}\mathbb{P}_{x^*}(0)}{\mathbb{P}_{\mathbf{x}^*}(1)}}$ (*i.e.* the lower bound).

Corollary 1 Immediately follows from Theorem 1 and Defintion 1, as if $A(f(\mathbf{x}^*, S) = 1) \leq \frac{1}{1 + \frac{e^{\epsilon}\mathbb{P}_{x^*}(0)}{\mathbb{P}_{x^*}(1)}}$ then $A(f(\mathbf{x}^*, S) = 0) = 1 - A(f(\mathbf{x}^*, S) = 1) \leq 1 - \frac{1}{1 + \frac{e^{\epsilon}\mathbb{P}_{x^*}(0)}{\mathbb{P}_{x^*}(1)}} = \frac{1}{1 + \frac{e^{-\epsilon}\mathbb{P}_{x^*}(1)}{\mathbb{P}_{x^*}(0)}}$.

Similarly, we get $A(f(\mathbf{x}^*, S) = 0) = 1 - A(f(\mathbf{x}^*, S) = 1) \geq 1 - \frac{1}{1 + \frac{e^{-\epsilon}\mathbb{P}_{x^*}(0)}{\mathbb{P}_{x^*}(1)}} = \frac{1}{1 + \frac{e^{\epsilon}\mathbb{P}_{x^*}(1)}{\mathbb{P}_{x^*}(0)}}$

B Figures

Figure 4: Upper bound on MI positive accuracy as a function of $\mathbb{P}_{\mathbf{x}^*}(1)$

Figure 5: MI advantage

Figure 6: Comparing our deletion capacity trend to the trend Sekhari et al. (2021) describes. In particular our number of deletions degrades with training size while theirs increasing.