HyperDomainNet: Universal Domain Adaptation for Generative Adversarial Networks

Abstract

Domain adaptation framework of GANs has achieved great progress in recent years as a main successful approach of training contemporary GANs in the case of very limited training data. In this work, we significantly improve this framework by proposing an extremely compact parameter space for fine-tuning the generator. We introduce a novel domain-modulation technique that allows to optimize only 6 thousand-dimensional vector instead of 30 million weights of StyleGAN2 to adapt to a target domain. We apply this parameterization to the state-of-art domain adaptation methods and show that it has almost the same expressiveness as the full parameter space. Additionally, we propose a new regularization loss that considerably enhances the diversity of the fine-tuned generator. Inspired by the reduction in the size of the optimizing parameter space we consider the problem of multi-domain adaptation of GANs, i.e. setting when the same model can adapt to several domains depending on the input query. We propose the HyperDomainNet that is a hypernetwork that predicts our parameterization given the target domain. We empirically confirm that it can successfully learn a number of domains at once and may even generalize to unseen domains.

1 Introduction

Contemporary generative adversarial networks (GANs) [5, 11, 12, 10, 1] show remarkable performance in modeling image distributions and have applications in a wide range of computer vision tasks (image enhancement [14, 33], editing [6, 23], image-to-image translation [9, 36, 37], etc.). However, the training of modern GANs requires thousands of samples that limits its applicability only to domains that are represented by a large set of images. The mainstream approach to sidestep this limitation is transfer learning (TL), i.e. fine-tuning the generative model to a domain with few samples starting with a pretrained source model.

The standard approach of GAN TL methods is to fine-tune almost *all* weights of the pretrained model [15, 17, 29, 28, 10, 34, 19, 4, 38]. It can be reasonable in the case when the target domain is very far from the source one, e.g. when we adapt the generator pretrained on human faces to the domain of animals or buildings. However, there is a wide range of cases when the distance between data domains is not so far. In particular, the majority of target domains used in works [15, 28, 19, 4, 38] are similar to the source one and differ mainly in texture, style, geometry while keep the same content like faces or outdoor scenes. For such cases it seems redundant to fine-tune all weights of the source generator. It was shown in the paper [31] that after transfer learning of the StyleGAN2 [12] to similar domains some parts of the network almost do not change. This observation motivates us to find a more efficient and compact parameter space for domain adaptation of GANs.

In this paper, we propose a novel *domain-modulation* operation that reduces the parameter space for fine-tuning the StyleGAN2. The idea is to optimize for each target domain only a single vector

d. We incorporate this vector into the StyleGAN2 architecture through the modulation operation at each convolution layer. The dimension of the vector d equals 6 thousand that is *5 thousand times* less than the original weights space of the StyleGAN2. We apply this parameterization for the state-of-the-art domain adaptation methods StyleGAN-NADA [4] and MindTheGAP [38]. We show that it has almost the same expressiveness as the full parameterization while being more lightweight. To further advance the domain adaptation framework of GANs we propose a new regularization loss that improves the diversity of the fine-tuned generator.

Such considerable reduction in the size of the proposed parameterization motivates us to consider the problem of multi-domain adaptation of GANs, i.e. when the same model can adapt to multiple domains depending on the input query. Typically, this problem is tackled by previous methods just by fine-tuning separate generators for each target domain independently. In contrast, we propose to train a hyper-network that predicts the vector d for the StyleGAN2 depending on the target domain. We call this network as HyperDomainNet. Such hyper-network would be impossible to train if we needed to predict all weights of StyleGAN2. The immediate benefits of multi-domain framework consist of reducing the training time and the number of trainable parameters because instead of fine-tuning n separate generators we train one HyperDomainNet to adapt to n domains simultaneously. Another advantage of this method is that it can generalize to *unseen* domains if n is sufficiently large and we empirically observe this effect.

We provide extensive experiments to empirically confirm the effectiveness of the proposed parameterization and the regularization loss on a wide range of domains. We illustrate that our parameterization can achieve quality comparable with the full parameterization (i.e. when we optimize all weights). The proposed regularization loss significantly improves the diversity of the fine-tuned generator that is validated qualitatively and quantitatively. Further, we conduct experiments with the HyperDomainNet and show that it can be successfully trained on a number of target domains simultaneously. Also we show that it can generalize to a number of diverse unseen domains.

To sum up, our main contributions are

- We reduce the number of trainable parameters for domain adaptation of StyleGAN2 [12] generator by proposing the domain-modulation technique. Instead of fune-tuning all 30 millions weights of StyleGAN2 for each new domain now we can train only 6 thousand-dimensional vector.

- We introduce a novel regularization loss that considerably improves the diversity of the adapted generator.

- We propose a HyperDomainNet that predicts the parameterization vector for the input domain and allows multi-domain adaptation of GANs. It shows inspiring generalization results on unseen domains.

2 Related Work

Domain Adaptation of GANs The aim of few-shot domain adaptation of GANs is to learn accurate and diverse distribution of the data represented by only a few images. The standard approach is to utilize a generator pretrained on source domain and fine-tune it to a target domain. There are generally two different regimes of this task. The first one is when we adapt the generator to completely new data (e.g. faces $\rightarrow$ landscapes, churches, etc.), and the second regime is when the target domain relates to the source one (e.g. faces $\rightarrow$ sketches, artistic portraits, etc.).

Methods that tackle the first regime typically require several hundreds or thousands samples to adapt successfully. Such setting assumes that the weights of the generator should be changed significantly because the target domain can be very far from the source. The paper [10] shows that for distant domains training from scratch gives comparable results to transfer learning. It also confirms that for such regime there is no point to reduce the parameter space. Typcally such approaches utilize data augmentations [10, 24, 34, 35], or use auxiliary tasks for the discriminator to more accurately fit the available data [16, 32], or freeze lower layers of the discriminator to avoid overfitting [17].

In the second regime the transfer learning is especially crucial because the pretrained generator already contains many information about the target domain. In this setting the required number of available data can be significantly smaller and range from hundreds to several images. The main challenges in the case of such limited data are to avoid over-fitting of the generator and leverage its

diversity learned from the source domain. To tackle these challenges existing methods introduce restrictions on the parameter space [22, 18], mix the weights of the adapted and the source generators [20], utilize a small network to force sampling in special regions of the latent space [28], propose new regularization terms [15, 25], or apply contrastive learning techniques to enhance cross-domain consisitency [19]. The state-of-the-art methods [4, 38] leverage supervision from vision-language CLIP model [21]. StyleGAN-NADA [4] applies it for text-based domain adaptation when we have no access to images but only to the textual description. MindTheGap [38] employs CLIP model to further significantly improve the quality of one-shot domain adaptation.

Constraining Parameter Space for GAN's Adaptation   In the second regime of GAN's adaptation it is especially important for the generator to leverage the information from the source domain during adapting to the target one. The common approach is to introduce some restrictions on the trainable weights to regularize them during fine-tuning. For example, the work [22] proposes to optimize only the singular values of the pretrained weights and apply it for few shot domain adaptation, however the reported results show the limited expressiveness of such parameterization [22]. Another method [18] constrains the parameter space for models with batch normalization (BN) layers such as BigGAN [1] by optimizing only BN statistics during fine-tuning. While it allows to decrease the number of trainable parameters, it also considerably reduces the expressiveness of the generator [22, 19]. Other approach is to adaptively choose a subset of layers during optimization at each step as in StyleGAN-NADA [4]. It helps to stabilize the training, however it does not reduce the parameter space because each layer can potentially be fine-tuned. In contrast, the size of our parameterization is less by orders of magnitude than the size of the full parameter space while having the comparable expressiveness.

3   Preliminaries

In this work, we focus on StyleGAN generators in the context of domain adaptation. We consider StyleGAN2 [12] as a base model. As the state-of-the-art domain adaptation methods we use StyleGAN-NADA [4] and MindTheGAP [38].

StyleGAN2   The StyleGAN2 generation process consists of several components. The first part is a mapping network $M(z)$ that takes as an input random vectors $z \in \mathcal{Z}$ from the initial latent space, $\mathcal{Z}$ that is typically normally distributed. It transforms these vectors z into the intermediate latent space $\mathcal{W}$. Each vector $w \in \mathcal{W}$ is further fed into different affine transformations $A(w)$ for each layer of the generator. The output of this part forms StyleSpace $\mathcal{S}$ [30] that consists of channel-wise style parameters $s = A(w)$. The next part of the generation process is the synthesis network G_{sys} that takes as an input the constant tensor c and style parameters s at the corresponding layers and produces the final feature maps at different resolutions $F = G_{sys}(c, s)$. These feature maps move on to the last part which consists of toRGB layers G_{tRGB} that generate the output image $I = G_{tRGB}(F)$.

Problem Formulation of Domain Adaptation   The problem of domain adaptation of StyleGAN2 can be formulated as follows. We are given a trained generator G^A for the source domain A, and the target domain B that is represented by the one image I_B (one-shot adaptation) or by the text description t_B (text-guided adaptation). The aim is to fine-tune the weights θ of a new generator G_θ^B for the domain B starting from the weights of G^A. The optimization process in the general form is

$$\mathcal{L}_B(\theta) = \mathcal{L}(\{G_\theta^B(w_i)\}_{i=1}^n, \{G^A(w_i)\}_{i=1}^n, G_\theta^B, B, A) \; \rightarrow \; \min_\theta, \tag{1}$$

where $\mathcal{L}$ is some loss function, n is a batch size, $w_1, \ldots, w_n$ are random latent codes, $\{G_\theta^B(w_i)\}_{i=1}^n$ and $\{G^A(w_i)\}_{i=1}^n$ are batches of images sampled by G_θ^B and G^A generators, respectively, and B, A are domains that are represented by images or text descriptions.

CLIP model   CLIP [21] is a vision-language model that is composed of text and image encoders E_T, E_I, respectively, that maps their inputs into a joint, multi-modal space of vectors with a unit norm (this space is often called as CLIP space). In this space the cosine distance between embeddings reflects the semantic similarity of the corresponding objects.

137 **StyleGAN-NADA**   StyleGAN-NADA [4] is a pioneering work that utilizes the CLIP model [21] for
138 text-guided domain adaptation of StyleGAN. The proposed loss function is

$$\Delta T(B, A) = E_T(t_B) - E_T(t_A),$$
$$\Delta I(G_\theta^B(w), G^A(w)) = E_I(G_\theta^B(w)) - E_I(G^A(w)),$$
$$\mathcal{L}_{direction}(G_\theta^B(w), G^A(w), B, A) = 1 - \frac{\Delta I(G_\theta^B(w), G^A(w)) \cdot \Delta T(B, A)}{|\Delta I(G_\theta^B(w), G^A(w))||\Delta T(B, A)|}. \quad (2)$$

139 The idea is to align the CLIP-space direction between the source and target images
140 $\Delta I(G_\theta^B(w), G^A(w))$ with the direction between a pair of source and target text descriptions
141 $\Delta T(B, A)$. So, the overall optimization process has the form

$$\mathcal{L}_B(\theta) = \sum_{i=1}^{n} \mathcal{L}_{direction}(G_\theta^B(w_i), G^A(w_i), B, A) \to \min_\theta. \quad (3)$$

142 In StyleGAN-NADA method the $\mathcal{L}_B(\theta)$ loss is optimized only with respect to the weights θ of the
143 synthesis network G_{sys}^B which has 24 million weights.

144 **MindTheGap**   The MindTheGap method [38] is proposed for a one-shot domain adaptation of
145 StyleGAN, i.e. the domain B is represented by the single image I_B. In principle StyleGAN-NADA
146 method can solve this problem just by replacing the text direction $\Delta T(B, A)$ from Equation (2) to an
147 image one

$$\Delta I'(B, A) = E_I(I_B) - \frac{1}{|A|} \sum_{I_A \in A} [E_I(I_A)], \quad (4)$$

148 where $\frac{1}{|A|} \sum_{I_A \in A} [E_I(I_A)]$ is the mean embedding of the images from domain A. However, as stated
149 in [38] this leads to an undesirable effect that transferred images lose the initial diversity of domain
150 A and become too close to the I_B image. So, the key idea of the MindTheGap is to replace the mean
151 embedding from Equation (4) by the embedding of projection I_A^* of I_B image to A domain obtained
152 by the GAN inversion method II2S [39]:

$$\Delta I''(B, A) = E_I(I_B) - E_I(I_A^*), \quad (5)$$

153 So, the MindTheGap uses the modified $\mathcal{L}'_{direction}$ loss that is renamed to $\mathcal{L}_{clip\_accross}$

$$\mathcal{L}_{clip\_accross}(G_\theta^B(w), G^A(w), B, A) = 1 - \frac{\Delta I(G_\theta^B(w), G^A(w)) \cdot \Delta I''(B, A)}{|\Delta I(G_\theta^B(w), G^A(w))||\Delta I''(B, A)|}. \quad (6)$$

154 In addition to this idea several new regularizers are introduced that force the generator G_θ^B to
155 reconstruct the I_B image from its projection I_A^*. It further stabilizes and improves the quality of
156 domain adaption. Overall, the MindTheGAP loss function $\mathcal{L}_{MTG}$ has four terms to optimize G_θ^B.
157 For more details about each loss please refer to the original paper [38].

4   Approach

4.1   Domain-Modulation Technique for Domain Adaptation

160 Our primary goal is to improve the domain adaptation of StyleGAN by exploring an effective and
161 compact parameter space to use it for fine-tuning G_θ^B. As we described in Section 3 StyleGAN has
162 four components: the mapping network $M(\cdot)$, affine transformations $A(\cdot)$, the synthesis network
163 $G_{sys}(\cdot, \cdot)$, and toRGB layers $G_{tRGB}(\cdot)$. It is observed in the paper [31] that the main part of
164 StyleGAN that is mostly changed during fine-tuning to a target domain is the synthesis network
165 $G_{sys}(\cdot, \cdot)$. It is also confirmed by StyleGAN-NADA [4] and MindTheGap [38] methods as they adapt
166 only the weights of $G_{sys}(\cdot, \cdot)$ for the target domain.

167 So, we aim to find an effective way to fine-tune the weights of feature convolutions of $G_{sys}(\cdot, \cdot)$. In
168 StyleGAN2 [12] these convolutions utilize modulation/demodulation operations to process the input

(a) Domain-modulation technique   (b) Fine-tuning StyleGAN2 by optimizing the domain vector D

Figure 1: Detailed diagram of proposed method. (a) Revised ModulatedConv block with introduced domain-modulation operation. (b) Fully detailed training process of the domain adaptation with the proposed domain-modulation technique.

tensor and the corresponding style parameters s. Let us revisit the mechanism of these operations:

$$\text{modulation: } w'_{ijk} = s_i \cdot w_{ijk}, \tag{7}$$

$$\text{demodulation: } w''_{ijk} = \frac{w'_{ijk}}{\sqrt{\sum_{i,k} {w'_{ijk}}^2 + \varepsilon}}, \tag{8}$$

where w, w' and w'' are the original, modulated and demodulated weights, respectively, s_i is the component of the style parameters s, i and j enumerate input and output channels, respectively. The idea behind modulation/demodulation is to replace the standard adaptive instance normalization (AdaIN) [26, 3] to a normalization that is based on the expected statistics of the input feature maps rather than forcing them explicitly [12]. So, the modulation part is basically an adaptive scaling operation as in AdaIN that is controled by the style parameters s. This observation inspires us to use this technique for the domain adaptation.

The problem of fine-tuning GANs to a new domain is very related to the task of style transfer where the goal is also to translate images from the source domain to a new domain with the specified style. The contemporary approach to solve this task is to train an image-to-image network which takes the target style as an input condition. The essential ingredient of such methods is the AdaIN that provides an efficient conditioning mechanism. In particular, it allows to train arbitrary style transfer models [8]. So, it motivates us to apply the AdaIN technique for adapting GANs to new domains.

We introduce a new *domain-modulation* operation that reduces the parameter space for fine-tuning StyleGAN2. The idea is to optimize only a vector d with the same dimension as the style parameters s. We incorporate this vector into StyleGAN architecture by the additional modulation operation after the standard one from Equation (7):

$$\text{domain-modulation: } w'_{ijk} = d_i \cdot w_{ijk}, \tag{9}$$

where d_i is the component of the introduced domain parameters d (see Figure 1a). So, instead of optimizing all weights θ of the G_{sys} part we train only the vector d.

We apply these new parameterization to StyleGAN-NADA and MindTheGAP methods, i.e. instead of optimizing its loss functions wrt θ we optimize it wrt d vector (see Figure 1b) The dimension of the vector d equals 6 thousand that is 4 thousand times less than the original weights space θ of $G_{sys}(\cdot, \cdot)$ part. While the proposed parameter space is radically more constrained we observe that it has the expressiveness comparable with the whole weight space.

4.2 Improving Diversity of CLIP-Guided Domain Adaptation

The CLIP-based domain adaptation methods StyleGAN-NADA and MindTheGap use $\mathcal{L}_{direction}$ (or $\mathcal{L}_{clip\_accross}$) loss (see Equations (2) and (6)) that was initially introduced to deal with the mode

Figure 2: Detailed training process of the HyperDomainNet. On the training phase only reference descriptions are included into CLIP-guided training.

collapsing problem of the fine-tuned generator [4]. However, we empirically observe that it solves the issue only partially. In particular, it preserves the diversity only at the begining of the fine-tuning process and starts collapsing after several hundred iterations. It is a significant problem because for some domains we need much more iterations to obtain the acceptable quality.

The main cause of such undesirable behaviour of the $\mathcal{L}_{direction}$ (the same for $\mathcal{L}_{clip\_accross}$) loss is that it calculates the CLIP cosine distance between embeddings that do not lie in the CLIP space. Indeed, the cosine distance is a natural distance for objects that lie on a CLIP sphere but becomes less evident for vectors $\Delta T, \Delta I$ that represent the difference between clip embeddings that no longer lie on a unit sphere. Therefore, the idea behind the $\mathcal{L}_{direction}$ loss may be misleading and in practice we can observe that it still suffers from mode collapse.

We introduce a new regularizer for improving diversity that calculates the CLIP cosine distance only between clip embeddings. We called it *indomain angle consistency* loss and we define it as follows

$$\mathcal{L}_{indomain-angle}(\{G_d^B(w_i)\}_{i=1}^n, \{G^A(w_i)\}_{i=1}^n, B, A) = \tag{10}$$

$$= \sum_{i,j}^n (\langle E_I(G^A(w_i)), E_I(G^A(w_j))\rangle - \langle E_I(G_d^B(w_i)), E_I(G_d^B(w_j))\rangle)^2, \tag{11}$$

The idea of $\mathcal{L}_{indomain-angle}$ loss is to preserve the CLIP pairwise cosine distances between images before and after domain adaptation. We observe that this loss significantly improves the diversity of the generator G_d^B compared to the original $L_{direction}$ or $\mathcal{L}_{clip\_accross}$ losses.

4.3 Designing the HyperDomainNet for Universal Domain Adaptation

The proposed domain-modulation technique allows us to reduce the number of trainable parameters which motivates us to tackle the problem of multi-domain adaption of StyleGAN2. Our aim is to train the HyperDomainNet that predicts the domain parameters given the input target domain. This problem can be formulated as follows. We are given a trained generator G^A for a source domain A and a number of target domains $B_1, \ldots, B_m$ that can be represented by the single image or the text description. The aim is to learn the HyperDomainNet $D_\varphi(\cdot)$ that can predict the domain parameters $d_{B_i} = D_\varphi(B_i)$ which will be used to obtain the fine-tuned generator $G_{d_{B_i}}^{B_i}$ by the domain-modulation operation (see Section 4.1).

In this work, we focus on the setting when the target domains $B_1, \ldots, B_m$ are represented by text descriptions $t_{B_1}, \ldots, t_{B_m}$. The HyperDomainNet $D_\varphi(\cdot)$ takes as an input the embedding of the text obtained by the CLIP encoder $E_T(\cdot)$ and outputs the domain parameters $d_{B_i} = D_\varphi(E_T(t_{B_i}))$. The training process is described in the Figure 2.

To train the HyperDomainNet $D_\varphi(\cdot)$ we use the sum of $\mathcal{L}_{direction}$ losses for each target domains. In addition, we introduce $\mathcal{L}_{tt-direction}$ loss ("tt" stands for target-target) that is the same as $\mathcal{L}_{direction}$, but we compute it between two target domains instead of target and source. The idea is to keep away the images from different target domains in the CLIP space. We observe that without $\mathcal{L}_{tt-direction}$ loss the HyperDomainNet tends to learn the mixture of domains.

StyleGAN-NADA Ours

Figure 3: Comparison with the original StyleGAN-NADA [4] method (left) and its version with our parameterization.

In multi-domain adaptation setting, the regularizer $\mathcal{L}_{indomain-angle}$ becomes inefficient because during training batch consists of samples from different domains and the number of images from one domain can be very small. Therefore, we introduce an alternative regularization $\mathcal{L}_{domain-norm}$ for the HyperDomainNet that constrains the norm of the predicted domain parameters. To be exact it equals to $\|D_\varphi(E_T(t_{B_i})) - 1\|^2$.

So, the objective function of the HyperDomainNet consists of $\mathcal{L}_{direction}$, $\mathcal{L}_{tt-direction}$ and $\mathcal{L}_{domain-norm}$ losses. For more detailed description of these losses the overall optimization process, please refer to Appendix A.2.

5 Experiments

In this section, we provide qualitative and quantitative results of the proposed approaches. At first, we consider the text-based domain adaptation and show that our parameterization has comparable quality with the full one. Next, we tackle one-shot domain adaptation and confirm the same quantitatively and also show the importance of the $\mathcal{L}_{indomain-angle}$ loss. Finally, we solve the multi-domain adaptation problem by the proposed HyperDomainNet, show its generalization ability on unseen domains. For the detailed information about setup of the experiments please refer to Appendix A.1.

Text-Based Domain Adaptation We compare the StyleGAN-NADA [4] method with the proposed parameterization and the original version on a number of diverse domains. In Figure 3, we see that the expressiveness of our parameterization is on par with the original StyleGAN-NADA. We observe that the domain-modulation technique allows to adapt the generator to various style and texture changes. For results on more domains please refer to Appendix A.3.

Figure 4: Comparison with one-shot domain adaptation methods. Left block is MindThe-Gap+indomain and right block is StyleGAN-NADA [38]. The middle block is the MindThe-Gap+indomain with our parameterization.

One-Shot Domain Adaptation In this part, we examine our parameterization and the indomain angle consistency loss by applying them to the MindTheGap [38] method. We show qualitative and quantitative results and compare them with other few-shot domain adaptation methods such as StyleGAN-NADA, TargetCLIP [2] and Cross-correspondence [19] method. To assess the domain adaptation quality we use the standard metrics FID [7], precision and recall [13]. As a target domain we take the common benchmark dataset of face sketches [27] that has approximately 300 samples. We consider the one-shot adaptation setting. We provide the results in Table 1. At fisrt, we see that the MindTheGap with our parameterization shows comparable results with the original version while having less trainable parameters by three orders of magnitude. Secondly, we examine the effectiveness of the indomain angle consistency. We show that it considerably improves FID and precision metrics for both the original MindTheGap and the one with our parameterization.

The qualitative results are provided in Figure 4 for MindTheGap+indomain, MindTheGap+indomain with our parameterization ("Ours") and StyleGAN-NADA. For other methods please see Appendix A.4. We observe that MindTheGap+indomain and our version shows comparable visual quality and outperform StyleGAN-NADA in terms of diversity and maintaining the similarity to the source image.

Overall, we demonstrate that our parameterization is applicable to the state-of-the-art methods StyleGAN-NADA and MindTheGap and it can be further improved by the indomain angle consistency loss.

Multi-Domain Adaptation Now we consider the multi-domain adaptation problem. We apply the HyperDomainNet in two different scenarios: (i) training on fixed number of domains, (ii) training on

Table 1: Evaluation of one-shot adaptation methods. Results for TargetCLIP, Cross-correspondence and StyleGAN-NADA methods are taken from [38].

Model	Model quality			Model complexity
	FID	Precision	Recall	# trainable parameters
TargetCLIP [2]	199.33	0.000	0.293	30M
Cross-correspondence [19]	158.86	0.001	0	30M
StyleGAN-NADA [4]	124.55	0.118	0	24M
MindTheGap [38]	78.35	0.326	0.017	24M
MindTheGap (our param.)	79.83	0.452	0.017	6k
MindTheGap+indomain	71.46	0.503	0.014	24M
MindTheGap+indomain (our param.)	72.71	0.472	0.028	6k

Figure 5: Comparison of training setups. The top row represents the real images embedded into StyleGAN2 latent space which latents are then used for HyperDomainNet inference. The left block represents results obtained from text-descriptions presented in the train list. The right block represents results of HyperDomainNet inference on unseen text-descriptions.

potentially arbitrary number of domains. The first scenario is simple, we train the HyperDomainNet on 20 different domains such as "Anime Painting", "Pixar", etc. (for the full list of domains please refer to Appendix). The second scheme is more complicated. We fix large number of domains (several hundreds) and calculate its CLIP embeddings. During training we sample new embeddings from the convex hull of the initial ones and use them in the optimization process (see Figure 2). This technique allows us to generalize to unseen domains. For more details about both scenarios please refer to Appendix A.2.

The results of the HyperDomainNet for both scenarios are provided in Figure 5. The left part is results for the first setting, the right one is results for the unseen domains in the second scheme. For more domains and generated images please refer to Appendix A.2. We see that in the first scenario the HyperDomainNet shows results comparable to the case when we train separate models for each domain (see Figure 3). It shows that the proposed optimization process for the HyperDomainNet is effective. The results for the second scenario looks promising. We can observe that the HyperDomainNet has learnt very diverse domains and shows sensible adaptation results for unseen ones.

6 Conclusion

We propose a novel domain-modulation technique that allows us to considerably reduce the number of trainable parameters during domain adaptation of StyleGAN2. We successfully apply it to the state-of-the-art methods. In addition, we introduce a new indomain angle consistency loss that improves the diversity of the fine-tuned generator. Finally, equipped with the efficient parameterization we propose the HyperDomainNet for multi-domain adaptation of StyleGAN2. We empirically show that it can be trained to several domains successfully. And when the number of training domains is large it can generalize to unseen domains.

The main limitation of our approach is that it is not applicable for the cases when target domains are very far from the source one. In such setting, we cannot limit the parameter space, so we should use the full parameterization.

The potential negative societal impacts of domain adaptation of GANs and generally training of GANs include different forms of disinformation, e.g. deepfakes of celebrities or senior officials, fake avatars in social platforms. However, it is the issue of the whole field and this work does not amplify this impact.

References

[1] Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale gan training for high fidelity natural image synthesis. *arXiv preprint arXiv:1809.11096*, 2018.

[2] Hila Chefer, Sagie Benaim, Roni Paiss, and Lior Wolf. Image-based clip-guided essence transfer. *arXiv preprint arXiv:2110.12427*, 2021.

[3] Vincent Dumoulin, Jonathon Shlens, and Manjunath Kudlur. A learned representation for artistic style. *arXiv preprint arXiv:1610.07629*, 2016.

[4] Rinon Gal, Or Patashnik, Haggai Maron, Gal Chechik, and Daniel Cohen-Or. Stylegan-nada: Clip-guided domain adaptation of image generators. *arXiv preprint arXiv:2108.00946*, 2021.

[5] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

[6] Erik Härkönen, Aaron Hertzmann, Jaakko Lehtinen, and Sylvain Paris. Ganspace: Discovering interpretable gan controls. *Advances in Neural Information Processing Systems*, 33:9841–9850, 2020.

[7] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. *Advances in neural information processing systems*, 30, 2017.

[8] Xun Huang and Serge Belongie. Arbitrary style transfer in real-time with adaptive instance normalization. In *Proceedings of the IEEE international conference on computer vision*, pages 1501–1510, 2017.

[9] Phillip Isola, Jun-Yan Zhu, Tinghui Zhou, and Alexei A Efros. Image-to-image translation with conditional adversarial networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1125–1134, 2017.

[10] Tero Karras, Miika Aittala, Janne Hellsten, Samuli Laine, Jaakko Lehtinen, and Timo Aila. Training generative adversarial networks with limited data. *Advances in Neural Information Processing Systems*, 33:12104–12114, 2020.

[11] Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 4401–4410, 2019.

[12] Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. Analyzing and improving the image quality of stylegan. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 8110–8119, 2020.

[13] Tuomas Kynkäänniemi, Tero Karras, Samuli Laine, Jaakko Lehtinen, and Timo Aila. Improved precision and recall metric for assessing generative models. *Advances in Neural Information Processing Systems*, 32, 2019.

[14] Christian Ledig, Lucas Theis, Ferenc Huszár, Jose Caballero, Andrew Cunningham, Alejandro Acosta, Andrew Aitken, Alykhan Tejani, Johannes Totz, Zehan Wang, et al. Photo-realistic single image super-resolution using a generative adversarial network. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4681–4690, 2017.

[15] Yijun Li, Richard Zhang, Jingwan Lu, and Eli Shechtman. Few-shot image generation with elastic weight consolidation. *arXiv preprint arXiv:2012.02780*, 2020.

[16] Bingchen Liu, Yizhe Zhu, Kunpeng Song, and Ahmed Elgammal. Towards faster and stabilized gan training for high-fidelity few-shot image synthesis. In *International Conference on Learning Representations*, 2020.

[17] Sangwoo Mo, Minsu Cho, and Jinwoo Shin. Freeze the discriminator: a simple baseline for fine-tuning gans. *arXiv preprint arXiv:2002.10964*, 2020.

[18] Atsuhiro Noguchi and Tatsuya Harada. Image generation from small datasets via batch statistics adaptation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 2750–2758, 2019.

[19] Utkarsh Ojha, Yijun Li, Jingwan Lu, Alexei A Efros, Yong Jae Lee, Eli Shechtman, and Richard Zhang. Few-shot image generation via cross-domain correspondence. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10743–10752, 2021.

[20] Justin NM Pinkney and Doron Adler. Resolution dependent gan interpolation for controllable image synthesis between domains. *arXiv preprint arXiv:2010.05334*, 2020.

[21] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pages 8748–8763. PMLR, 2021.

[22] Esther Robb, Wen-Sheng Chu, Abhishek Kumar, and Jia-Bin Huang. Few-shot adaptation of generative adversarial networks. *arXiv preprint arXiv:2010.11943*, 2020.

[23] Yujun Shen, Jinjin Gu, Xiaoou Tang, and Bolei Zhou. Interpreting the latent space of gans for semantic face editing. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9243–9252, 2020.

[24] Ngoc-Trung Tran, Viet-Hung Tran, Ngoc-Bao Nguyen, Trung-Kien Nguyen, and Ngai-Man Cheung. On data augmentation for gan training. *IEEE Transactions on Image Processing*, 30:1882–1897, 2021.

[25] Hung-Yu Tseng, Lu Jiang, Ce Liu, Ming-Hsuan Yang, and Weilong Yang. Regularizing generative adversarial networks under limited data. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7921–7931, 2021.

[26] Dmitry Ulyanov, Andrea Vedaldi, and Victor Lempitsky. Instance normalization: The missing ingredient for fast stylization. *arXiv preprint arXiv:1607.08022*, 2016.

[27] Xiaogang Wang and Xiaoou Tang. Face photo-sketch synthesis and recognition. *IEEE transactions on pattern analysis and machine intelligence*, 31(11):1955–1967, 2008.

[28] Yaxing Wang, Abel Gonzalez-Garcia, David Berga, Luis Herranz, Fahad Shahbaz Khan, and Joost van de Weijer. Minegan: effective knowledge transfer from gans to target domains with few images. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9332–9341, 2020.

[29] Yaxing Wang, Chenshen Wu, Luis Herranz, Joost van de Weijer, Abel Gonzalez-Garcia, and Bogdan Raducanu. Transferring gans: generating images from limited data. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 218–234, 2018.

[30] Zongze Wu, Dani Lischinski, and Eli Shechtman. Stylespace analysis: Disentangled controls for style-gan image generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12863–12872, 2021.

[31] Zongze Wu, Yotam Nitzan, Eli Shechtman, and Dani Lischinski. Stylealign: Analysis and applications of aligned stylegan models. *arXiv preprint arXiv:2110.11323*, 2021.

[32] Ceyuan Yang, Yujun Shen, Yinghao Xu, and Bolei Zhou. Data-efficient instance generation from instance discrimination. *Advances in Neural Information Processing Systems*, 34, 2021.

[33] Tao Yang, Peiran Ren, Xuansong Xie, and Lei Zhang. Gan prior embedded network for blind face restoration in the wild. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 672–681, 2021.

[34] Shengyu Zhao, Zhijian Liu, Ji Lin, Jun-Yan Zhu, and Song Han. Differentiable augmentation for data-efficient gan training. *Advances in Neural Information Processing Systems*, 33:7559–7570, 2020.

[35] Zhengli Zhao, Zizhao Zhang, Ting Chen, Sameer Singh, and Han Zhang. Image augmentations for gan training. *arXiv preprint arXiv:2006.02595*, 2020.

[36] Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. In *Proceedings of the IEEE international conference on computer vision*, pages 2223–2232, 2017.

[37] Jun-Yan Zhu, Richard Zhang, Deepak Pathak, Trevor Darrell, Alexei A Efros, Oliver Wang, and Eli Shechtman. Toward multimodal image-to-image translation. *Advances in neural information processing systems*, 30, 2017.

[38] Peihao Zhu, Rameen Abdal, John Femiani, and Peter Wonka. Mind the gap: Domain gap control for single shot domain adaptation for generative adversarial networks. *arXiv preprint arXiv:2110.08398*, 2021.

[39] Peihao Zhu, Rameen Abdal, Yipeng Qin, John Femiani, and Peter Wonka. Improved stylegan embedding: Where are the good latents? *arXiv preprint arXiv:2012.09036*, 2020.