UNICORN: A UNIFIED BACKDOOR TRIGGER INVERSION FRAMEWORK

ABSTRACT

The backdoor attack, where the adversary uses inputs stamped with triggers (e.g., a patch) to activate pre-planted malicious behaviors, is a severe threat to Deep Neural Network (DNN) models. Trigger inversion is an effective way of identifying backdoor models and understanding embedded adversarial behaviors. A challenge of trigger inversion is that there are many ways of constructing the trigger. Existing methods cannot generalize to various types of triggers by making certain assumptions or attack-specific constraints. The fundamental reason is that existing work does not formally define the trigger and the inversion problem. This work formally defines and analyzes the trigger and the inversion problem. Then, it proposes a unified framework to invert backdoor triggers based on the formalization of triggers and the identified inner behaviors of backdoor models from our analysis. Our prototype UNICORN is general and effective in inverting backdoor triggers in DNNs. The code can be found at https://anonymous.4open.science/r/UNICORN-FA0E.

1 INTRODUCTION

Backdoor attacks against Deep Neural Networks (DNN) refer to the attack where the adversary creates a malicious DNN that behaves as expected on clean inputs but predicts a predefined target label when the input is stamped with a trigger (Liu et al., 2017; Gu et al., 2017; Chen et al., 2017; Liu et al., 2019; Wang et al., 2022b; Barni et al., 2019; Nguyen & Tran, 2021). The malicious models can be generated by data poisoning (Gu et al., 2017; Chen et al., 2017) or supply-chain attacks (Liu et al., 2017; Nguyen & Tran, 2021). The adversary can choose desired target label(s) and the trigger. Existing work demonstrates that DNNs are vulnerable to various types of triggers. For example, the trigger can be a colored patch (Gu et al., 2017), a image filter (Liu et al., 2019) and a warping effect (Nguyen & Tran, 2021). Such attacks pose a severe threat to DNN based applications especially those in security-critical tasks such as malware classification (Severi et al., 2021; Yang et al., 2022; Li et al., 2021a), face recognition (Sarkar et al., 2020; Wenger et al., 2021), speaker verification (Zhai et al., 2021), medical image analysis (Feng et al., 2022), brain-computer interfaces (Meng et al., 2020), and autonomous driving (Gu et al., 2017; Xiang et al., 2021).

Due to the threat of backdoor attacks, many countermeasures have been proposed. For example, anti-poisoning training (Li et al., 2021c; Wang et al., 2022a; Hong et al., 2020; Tran et al., 2018; Hayase et al., 2021; Chen et al., 2018) and runtime malicious inputs detection (Gao et al., 2019; Chou et al., 2018; Doan et al., 2020; Zeng et al., 2021b). Different from many methods that can only work under specific threat models (e.g., anti-poisoning training can only work under the data-poisoning scenario), trigger inversion (Wang et al., 2019; Liu et al., 2019; Guo et al., 2019; Chen et al., 2019; Shen et al., 2021) is practical and general because it can be applied in both poisoning and supply-chain attack scenarios. It is a post-training method where the defender aims to detect whether the given model contains backdoors. It reconstructs backdoor triggers injected in the model as well as the target labels, which helps analyze the backdoors. If there exists an inverted pattern that can control the predictions of the model, then it determines the model is backdoored. Most existing trigger inversion methods (Guo et al., 2019; Liu et al., 2019; Shen et al., 2021; Chen et al., 2019) are built on Neural Cleanse (Wang et al., 2019), which assumes that the backdoor triggers are static patterns in the pixel space. It defines a backdoor sample as $\tilde{x} = (1 - m) \odot x + m \odot t$, where m and t are pixel space trigger mask and trigger pattern. It inverts the trigger via devising an optimization problem that searches for a small and static pixel space pattern. Such methods achieve

Fig. 1: Existing trigger inversion methods and our method.

good performance on the specific type of triggers that are static patterns in the pixel space (Gu et al., 2017; Chen et al., 2017). However, it can not generalize to different types of triggers such as image filters (Liu et al., 2019) and warping effects (Nguyen & Tran, 2021). Existing methods fail to invert various types of triggers because they do not formally define the backdoor trigger injected in different input spaces, and the trigger inversion problem.

In this paper, we propose a trigger inversion framework that can generalize to different types of triggers. We first define a backdoor trigger as a predefined perturbation in a particular input space. A backdoor sample $\tilde{x}$ is formalized as $\tilde{x} = \phi^{-1}\left((1 - m) \odot \phi(x) + m \odot t\right)$, where m and t are input space trigger mask and trigger pattern, x is a benign sample, ϕ is an invertible input space transformation function that maps from the pixel space to other input spaces. ϕ^{-1} is the inverse function of ϕ, i.e., $x = \phi^{-1}\left(\phi(x)\right)$. As shown in Fig. 1, the critical difference between our framework and existing methods is that we introduce an input space transformation ϕ to unify the backdoor triggers injected in different spaces. Besides searching for the pixel space trigger mask m and pattern t as existing methods do, our method also searches the input space transformation function ϕ to find the input space where the backdoor is injected. We also observe successful backdoor attacks will lead to compromised activation vectors in the intermediate representations when the model recognizes backdoor triggers. Besides, we find that the benign activation vector will not affect the predictions of the model when the compromised activation values are activated. This observation means the compromised activation vector and the benign activation vector are disentangled in successful backdoor attacks. Based on the formalization of triggers and the observation of the inner behaviors of backdoor models, we formalize the trigger inversion as a constrained optimization problem.

Based on the devised optimization problem, we implemented a prototype UNICORN (**Uni**fied **B**a**c**kd**o**or **Tr**igger **In**version) in PyTorch and evaluated it on nine different models and eight different backdoor attacks (i.e., Patch attack (Gu et al., 2017), Blend attack (Chen et al., 2017), SIG (Barni et al., 2019), moon filter, kelvin filter, 1977 filter (Liu et al., 2019), WaNet (Nguyen & Tran, 2021) and BppAttack (Wang et al., 2022b)) on CIFAR-10 and ImageNet dataset. Results show UNICORN is effective for inverting various types of backdoor triggers. On average, the attack success rate of the inverted triggers is 95.60%, outperforming existing trigger inversion methods.

Our contributions are summered as follows: We formally define the trigger in backdoor attacks. Our definition can generalize to different types of triggers. We also find the compromised activations and the benign activations in the model's intermediate representations are disentangled. Based on the formalization of the backdoor trigger and the finding of intermediate representations, we formalize our framework as a constrained optimization problem and propose a new trigger inversion framework. We evaluate our framework on nine different DNN models and eight backdoor attacks. Results show that our framework is more general and more effective than existing methods. Our open-source code can be found at `https://anonymous.4open.science/r/UNICORN-FA0E`.

2 BACKGROUND & MOTIVATION

Backdoor. Existing works (Turner et al., 2019; Salem et al., 2020; Nguyen & Tran, 2020; Tang et al., 2021; Liu et al., 2020; Lin et al., 2020; Li et al., 2020; 2021d; Doan et al., 2021) demonstrate that deep neural networks are vulnerable to backdoor attacks. Models infected with backdoors behave as expected on normal inputs but present malicious behaviors (i.e., predicting a certain label) when the input contains the backdoor trigger. Existing methods defend against backdoor attacks during training (Du et al., 2019; Hong et al., 2020; Huang et al., 2022; Li et al., 2021c; Wang et al., 2022a; Hayase et al., 2021; Tran et al., 2018), or detect malicious inputs during inference (Gao et al., 2019; Doan et al., 2020; Chou et al., 2018), or remove and mitigate backdoors in the given model offline (Liu et al., 2018; Li et al., 2021b; Zeng et al., 2021a; Wu & Wang, 2021; Tao et al., 2022b).

Trigger Inversion. Trigger inversion (Wang et al., 2019; Liu et al., 2019; Guo et al., 2019; Chen et al., 2019) is a post-training approach to defending against backdoor attacks. Compared to training-time backdoor defenses, this method can also defend against supply-chain backdoor attacks. Meanwhile, this approach is more efficient than inference-time defenses. Moreover, it can recover the used trigger, assisting other types of backdoor analysis. The overreaching idea is to optimize a satisfactory trigger that can fool the model. Existing trigger inversion methods achieve promising performance on specific triggers. However, they are not generalizable by making certain assumptions or constraints during optimizing the trigger. During the optimization, it assumes that the trigger is a static pattern with a small size in the pixel space. Such assumption is suitable for pixel space attacks (e.g., BadNets (Gu et al., 2017) and Blend attack (Chen et al., 2017)) but does not hold for feature-space attacks that have dynamic pixel space perturbations, e.g., WaNet (Nguyen & Tran, 2021). Most existing approaches (Shen et al., 2021; Liu et al., 2019; Guo et al., 2019; Chen et al., 2019; Hu et al., 2021) follow the similar assumption and thus have the same limitation. In this paper, we propose a general trigger inversion framework.

3 BACKDOOR ANALYSIS

3.1 THREAT MODEL

Attacker's Goal. Backdoor attacks aim to generate a backdoor model $\mathcal{M}$ s.t. $\mathcal{M}(\boldsymbol{x}) = y, \mathcal{M}(\tilde{\boldsymbol{x}}) = y_t$, where $\boldsymbol{x}$ is a clean sample, $\tilde{\boldsymbol{x}}$ is a backdoor sample (with the trigger), and $y_t \neq y$ is the target label. A successful backdoor attack achieves the following goals:

Effectiveness. The backdoor model shall have a high attack success rate on backdoor inputs while maintaining high accuracy on benign inputs.

Stealthiness. The backdoor trigger shall not change the ground truth label of the input, i.e., a benign input and its malicious version (with trigger) shall be visually similar.

Defender's Goal & Capability. In this paper, we focus on reconstructing the backdoor triggers injected into the infected models. Following existing trigger inversion methods (Wang et al., 2019; Liu et al., 2019; Guo et al., 2019; Chen et al., 2019), we assume a small dataset containing correctly labeled benign samples is available and defenders have access to the target model. Note that our trigger inversion method does not require knowing the target label, it conducts trigger inversion for all labels and identifies the potential target label.

3.2 FORMALIZING BACKDOOR TRIGGERS

In software security, backdoor attack mixes malicious code into benign code to hide malicious behaviors or secrete access to the victim system, which are activated by trigger inputs. Backdoor attacks in DNN systems share the same characteristics. Trigger inversion essentially recovers the backdoor trigger by finding input patterns that activate such behaviors. Existing trigger inversion methods (Wang et al., 2019; Liu et al., 2019; Guo et al., 2019; Shen et al., 2021) can not generalize to different types of triggers. They define the backdoor samples as $\tilde{\boldsymbol{x}} = (1 - \boldsymbol{m}) \odot \boldsymbol{x} + \boldsymbol{m} \odot \boldsymbol{t}$, where $\boldsymbol{m}$ and $\boldsymbol{t}$ are pixel space trigger mask and trigger pattern. The reason why they can not invert different types of triggers is that existing attacks inject triggers in other input spaces (Liu et al., 2019; Wang et al., 2022b; Nguyen & Tran, 2021) while existing trigger inversion methods cannot handle them all. In this paper, we define backdoor triggers as:

Definition 1 *(Backdoor Trigger) A backdoor trigger is a mask $\boldsymbol{m}$ and content pattern $\boldsymbol{t}$ pair $(\boldsymbol{m}, \boldsymbol{t})$ so that for a pair of functions ϕ and ϕ^{-1} that transfer an image from pixel space to other input spaces that satisfy $\boldsymbol{x} = \phi^{-1}(\phi(\boldsymbol{x}))$ for an input $\boldsymbol{x}$ represented in the pixel space, we have a backdoor sample $\tilde{\boldsymbol{x}} = \phi^{-1}((1 - \boldsymbol{m}) \odot \phi(\boldsymbol{x}) + \boldsymbol{m} \odot \boldsymbol{t})$.*

The difference between our definition and that of existing works is that we introduce an input space transformation function pair ϕ and ϕ^{-1} that convert images from/to the pixel space to/from other spaces. The input space transformation function ϕ is invertible, i.e., $\boldsymbol{x} = \phi^{-1}(\phi(\boldsymbol{x}))$. For pixel space attacks, $\phi^{-1}(\boldsymbol{x}) = \phi(\boldsymbol{x}) = \boldsymbol{x}$. Fig. 2 classifies input spaces used by existing attacks. **Pixel Space Attacks** mixes the malicious pixels and benign contents at the pixel level. For example, patch attack (Gu et al., 2017) directly uses a static colored patch as a trigger; Blend attack (Chen

Space	Pixel			Signal			Feature	Numerical
Attack	Patch	Blend	SIG	1977	Kelvin	Moon	WaNet	BppAttack
Backdoor Samples								

Fig. 2: Backdoor attacks in different spaces.

et al., 2017) generates backdoor samples via blending the images with a predefined pattern; SIG attack (Barni et al., 2019) uses the sinusoidal signal pattern to create backdoor samples. In **Signal Space Attacks**, the adversary mixes the malicious signals with benign ones. For instance, the Filter attack (Liu et al., 2019) uses an image signal processing kernel (e.g., 1977, Kelvin and Moon filters used in Instagram) to generate backdoor samples. For **Feature Space Attacks**, backdoor samples inject malicious abstracted features and benign ones. As an example, WaNet (Nguyen & Tran, 2021) introduces the warping feature as a trigger. To perform **Numerical Space Attacks**, the attacker creates backdoor samples by changing numerical representations, e.g., the BppAttack (Wang et al., 2022b) generates backdoor samples via introducing quantization effects into the numerical representation of images. Existing trigger inversion methods (Wang et al., 2019; Liu et al., 2019; Guo et al., 2019; Shen et al., 2021) define backdoor triggers in the pixel space, and can not generalize to the attacks in different spaces. Compared to existing works, our definition is more general, and it can represent the triggers in different spaces.

3.3 BACKDOOR BEHAVIORS IN INTERMEDIATE REPRESENTATIONS

A successful backdoor attack will lead to compromised activation values that are highly associated with backdoor triggers. The intermediate representation of DNNs contains the activation values of different neurons, the composite of these values can be viewed as a vector. In this section, we use $\boldsymbol{u}$ to represent the basis vector in the intermediate representations. In backdoored DNNs, the intermediate activation vector $\boldsymbol{A}$ can be decomposed into compromised activation vector $\boldsymbol{A}_c$ and the benign activation vector $\boldsymbol{A}_b$, i.e., $\boldsymbol{A} = \boldsymbol{A}_c + \boldsymbol{A}_b$. $\boldsymbol{A}_c$ is on compromised activation direction $\boldsymbol{u}_c$ that is most sensitive to the backdoor triggers, namely, $\boldsymbol{u}_c = \max_{\boldsymbol{u}} \|\boldsymbol{u}(\tilde{\boldsymbol{x}}) - \boldsymbol{u}(\boldsymbol{x})\|, \boldsymbol{x} \in \mathcal{X}$, where $\tilde{\boldsymbol{x}}$ is the samples pasted with trigger and $\boldsymbol{x}$ is the clean sample. $\boldsymbol{u}(\boldsymbol{x})$ is the projection value on direction $\boldsymbol{u}$ for input $\boldsymbol{x}$'s intermediate representation. Meanwhile, $\boldsymbol{A}_b$ is on benign activation direction $\boldsymbol{u}_b$ that is not sensitive to the backdoor triggers (i.e., $\|\boldsymbol{u}_c(\tilde{\boldsymbol{x}}) - \boldsymbol{u}_c(\boldsymbol{x})\| < \tau$, where τ is a threshold value), and sensitive to the benign contents. Given a backdoor model, the backdoor trigger will lead to a specific projection value on compromised direction $\boldsymbol{u}_c$, i.e., $\boldsymbol{x} \in F(\mathcal{X}) \implies \boldsymbol{A}_c \approx \boldsymbol{S}$, where F is the trigger pasting function to create the backdoor sample $\tilde{\boldsymbol{x}}$ via benign sample $\boldsymbol{x}$, i.e., $\tilde{\boldsymbol{x}} = F(\boldsymbol{x})$. $\boldsymbol{S}$ is the backdoor vector.

Corollary 1 *When the compromised activation vector $\boldsymbol{A}_c$ is close to the backdoor vector $\boldsymbol{S}$, the model $\mathcal{M}$ will predict the target label y_t regardless of benign activation vector $\boldsymbol{A}_b$, i.e., $\forall \boldsymbol{A}_b, \boldsymbol{A}_c \approx \boldsymbol{S} \implies g(\boldsymbol{A}_c, \boldsymbol{A}_b) = y_t$, where g is the sub-model from the intermediate layer to the output layer.*

As discussed in §3.1, a backdoor attack is effective means it has a high attack success rate and high benign accuracy simultaneously. If the model has high benign accuracy, then it can extract the benign features well. Namely, different benign features will cause different activation values in benign activation vector. Meanwhile, if the attack success rate is high, then the model will predict target labels if it recognizes the trigger, regardless of the benign contents. Also, backdoor trigger will cause specific intermediate representations in model. Based on the above analysis, we conclude that the backdoor intermediate representations on the compromised activations will lead to the model predicting the target label while ignoring the activation values on the benign activation vector.

4 OPTIMIZATION PROBLEM

Based on the discussed attack goals and observation, we propose a backdoor trigger inversion framework to reconstruct the injected triggers in the given models. In Definition 1, we introduce input space transformation functions ϕ and ϕ^{-1} to specify the input space where the backdoor is injected. Trigger inversion is an optimization problem finding the input space mask and pattern $\boldsymbol{m}$ and $\boldsymbol{t}$

as well as the input space transformation functions. Directly optimizing functions is challenging. Because of the high expressiveness of neural networks (Hornik et al., 1989), in our optimization problem, we use two neural networks P and Q to correspondingly approximate ϕ and its inverse function ϕ^{-1}. We define it as a constrained optimization problem in Eq. 1, where P, Q, $\boldsymbol{m}$ and $\boldsymbol{t}$ are approximated input space transformation function, approximated inverse transformation function, backdoor mask and pattern in the infected space, respectively. Function $\mathcal{L}$ is the loss function of the target neural network, y_t is the target label, P_θ and Q_θ are the parameters of model P and Q.

$$
\begin{aligned}
&\min_{P_\theta, Q_\theta, \boldsymbol{m}, \boldsymbol{t}, \boldsymbol{m}'} \quad \mathcal{L}\left(\mathcal{M}(\tilde{\boldsymbol{x}}), y_t\right) \\
&\text{where } \tilde{\boldsymbol{x}} = Q\left((1 - \boldsymbol{m}) \odot P(\boldsymbol{x}) + \boldsymbol{m} \odot \boldsymbol{t}\right), \; \boldsymbol{x} \in \mathcal{X} \\
&s.t. \|Q(P(\boldsymbol{x})) - \boldsymbol{x}\| < \alpha, \; \|\boldsymbol{m}\| < \beta, \; \text{SSIM}(\tilde{\boldsymbol{x}}, \boldsymbol{x}) > \gamma, \; \boldsymbol{A}_c \perp \boldsymbol{A}_b \\
&\text{where } \boldsymbol{A}_c = \boldsymbol{m}' \odot h(\tilde{\boldsymbol{x}}), \; \boldsymbol{A}_b = (1 - \boldsymbol{m}') \odot h(\boldsymbol{x})
\end{aligned}
\tag{1}
$$

Objectives. Based on the goal of the attacker, the attack success rate (ASR) should be high. We achieve the effectiveness objective by optimizing the classification loss of inverted backdoor samples on the target label. Minimizing $\mathcal{L}\left(\mathcal{M}(\tilde{\boldsymbol{x}}), y_t\right)$ means optimizing the ASR for the inverted trigger.

Invertible Constraint. As neural networks P and Q are used to model the input space transformation function ϕ and its inverse function ϕ^{-1}, we add the constraint that the inputs generated by composite function $Q \circ P$ should be close to the original inputs, i.e., $\|Q(P(\boldsymbol{x})) - \boldsymbol{x}\| < \alpha$, where α is a threshold value.

Mask Size Constraint. As pointed out in Neural Cleanse (Wang et al., 2019), the trigger can only modify a small part of the input space. Similar to Neural Cleanse, we also constrain the size of the input space mask $\boldsymbol{m}$, i.e., $\|\boldsymbol{m}\| < \beta$.

Stealthiness Constraint. Based on the attacker's goal, the backdoor sample and the clean sample should be similar to the human visual system. Following existing works (Tao et al., 2022a; Cheng et al., 2021), we use SSIM score (Wang et al., 2004) to measure the visual difference between two images. Thus, the SSIM score between original sample $\boldsymbol{x}$ and the sample pasted with inverted trigger $\tilde{\boldsymbol{x}}$ should be higher than a threshold γ, i.e., $\text{SSIM}(\tilde{\boldsymbol{x}}, \boldsymbol{x}) > \gamma$.

Disentanglement Constraint. Based on our observation, the inverted trigger should lead to a specific projection value on the compromised activation vector. Meanwhile, the model will predict target labels regardless of the benign activations. We denote the constraint as disentangled constraint, i.e., $\boldsymbol{A}_c \perp \boldsymbol{A}_b$. To implement it, we devise a loss item $\mathcal{L}_{dis}$. Formally, it is defined in Eq. 2, where function h and g are the sub-model from the input layer to the intermediate layer and the sub-model from the intermediate layer to the output layer. By default, we separate h and g at the last convolutional layer in the model as it has well-abstracted feature representations. In Eq. 2, $\boldsymbol{m}'$ is the model's feature space mask indicating the compromised activation direction. We constrain the size of $\boldsymbol{m}'$ (10% of the whole intermediate representation space by default) and use gradient descent to search the direction of the compromised activation vector. We then combine the compromised activation vector and benign activation vector. Given a input sample $\boldsymbol{x}$, we first compute the $\boldsymbol{A}_c$ via using the inverted trigger function F (i.e., $F(\boldsymbol{x}) = \tilde{\boldsymbol{x}} = Q\left((1 - \boldsymbol{m}) \odot P(\boldsymbol{x}) + \boldsymbol{m} \odot \boldsymbol{t}\right)$). We then randomly select a set of different input samples $\boldsymbol{x}'$ and calculate the benign activation vector on it, i.e., $\boldsymbol{A}_b$. If the disentangle loss $\mathcal{L}_{dis}$ achieves low values, it means the benign activations can not influence the model's prediction when it recognizes backdoor representations on compromised activations. We consider it satisfy the disentanglement constraint is the value of $\mathcal{L}\left(g(\boldsymbol{A}_c, \boldsymbol{A}_b), y_t\right)$ is lower than a threshold value δ.

$$
\begin{aligned}
&\mathcal{L}_{dis} = \mathcal{L}\left(g(\boldsymbol{A}_c, \boldsymbol{A}_b), y_t\right) + \|\boldsymbol{m}'\| \\
&\text{where } \boldsymbol{A}_c = \boldsymbol{m}' \odot h(F(\boldsymbol{x})), \; \boldsymbol{A}_b = (1 - \boldsymbol{m}') \odot h(\boldsymbol{x}'), \; \boldsymbol{x}' \neq \boldsymbol{x}
\end{aligned}
\tag{2}
$$

Implementation. To solve the optimization problem formalized in Eq. 1, we also design a loss in Eq. 3. w_1, w_2, w_3 and w_4 are coefficient values for different items. Following existing methods (Wang et al., 2019; Liu et al., 2021; 2019), we adjust these coefficients dynamically to satisfy the constraints. A detailed adjustment method can be found in the §A.3. We use a representative deep neural network UNet (Ronneberger et al., 2015) to model the space transformation function ϕ. By default, we set $\alpha = 0.01$, β as 10% of the input space, $\gamma = 0.85$, and $\delta = 0.5$.

$$\mathcal{L}_{inv} = \mathcal{L}\left(\mathcal{M}(\tilde{\boldsymbol{x}}), y_t\right) + w_1 \cdot \|Q(P(\boldsymbol{x})) - \boldsymbol{x}\| + w_2 \cdot \|\boldsymbol{m}\| - w_3 \cdot \text{SSIM}(\tilde{\boldsymbol{x}}, \boldsymbol{x}) + w_4 \cdot \mathcal{L}_{dis} \quad (3)$$

5 EXPERIMENTS AND RESULTS

In this section, we first introduce the experiment setup (§5.1). We then evaluate the effectiveness of our method (§5.2) and conduct ablation studies (§5.3). We also evaluate UNICORN's generalizability to self-supervised models (§5.4).

5.1 EXPERIMENT SETUP.

Our method is implemented with python 3.8 and PyTorch 1.11. We conduct all experiments on a Ubuntu 20.04 server equipped with 64 CPUs and six Quadro RTX 6000 GPUs.

Datasets and models. Two publicly available datasets (i.e., CIFAR-10 (Krizhevsky et al., 2009) and ImageNet (Russakovsky et al., 2015)) are used to evaluate the effectiveness of UNICORN. The details of the datasets can be found in the §A.1. Nine different network architectures (i.e., NiN (Lin et al., 2013), VGG16 (Simonyan & Zisserman, 2014), ResNet18 (He et al., 2016), Wide-ResNet34 (Zagoruyko & Komodakis, 2016), MobileNetV2 (Sandler et al., 2018), InceptionV3 (Szegedy et al., 2016), EfficientB0 (Tan & Le, 2019), DenseNet121, and DenseNet169 (Huang et al., 2017)) are used in the experiments. These architectures are representative and are widely used in prior backdoor related researches (Liu et al., 2019; Wang et al., 2019; Li et al., 2021d;c; Liu et al., 2021; Xu et al., 2019; Huang et al., 2022; Xiang et al., 2022).

Attacks. We evaluate UNICORN on the backdoors injected in different spaces, including pixel space, signal space, feature space and numerical Space. For pixel space, we use three different attacks (i.e., Patch (Gu et al., 2017), Blended (Chen et al., 2017), and SIG (Barni et al., 2019)). For signal space, we use Filter attack (Liu et al., 2019) that modifying the whole image with three different filters from Instagram, i.e., 1977, kelvin, and moon. For feature space, warpping-based attack WaNet (Nguyen & Tran, 2021) is used. We also evaluate UNICORN on numberical space attack BppAttack (Wang et al., 2022b). More details about the used attacks can be found in the §A.2.

Baselines. We compare UNICORN with two existing trigger inversion methods, i.e., Neural Cleanse (Wang et al., 2019) and K-arm (Shen et al., 2021). Note that most existing trigger inversion methods use the optimization problem proposed in Neural Cleanse and share the same limitations (i.e., they can not generalize to different types of triggers).

Evaluation metrics. We use Attack Success Rate of the inverted trigger (ASR-Inv) on testset (the samples that are unseen during the trigger inversion) to evaluate the effectiveness of the trigger inversion methods. It is calculated as the number of samples pasted with inverted trigger that successfully attack the models (i.e., control the model to predict backdoor samples as the target label) divided by the number of all samples pasted with inverted trigger.

5.2 EFFECTIVENESS.

To measure the effectiveness of UNICORN, we collect the ASR of the inverted triggers (ASR-Inv) generated by UNICORN and existing methods (Wang et al., 2019) on different attacks, datasets and models. Note that the ASR on the injected trigger (ASR-Inj) are all above 95%. We also show the visualizations of the inverted triggers. We assume only 10 clean samples for each class are available for trigger inversion as our default setting, which is a challenging but practical scenario. It is also a common practice. (Wang et al., 2019; Shen et al., 2021; Liu et al., 2019).

Attack success rate of inverted triggers. Table 1 shows the ASR-Inv under the backdoored models generated by attacks in different spaces. The inverted triggers generated by UNICORN achieves ASR-Inv in all settings. In detail, the average ASR-Inv under pixel space attacks, signal space attacks, feature space attacks and numerical space attacks are 96.37%, 96.55%, 95.55%, and 93.92%, respectively. These results indicate UNICORN is effective for inverting backdoor triggers injected in different spaces. We also show the visualization of the inverted triggers as well as the ground-truth triggers in Fig. 3. The first row shows the original image and the samples pasted with different injected triggers. The dataset and the model used here are ImageNet and VGG16. As can be observed,

Table 1: ASR-Inv on different attacks, models and datasets.

Dataset	Network	Pixel Space			Signal Space			Feature	Numerical
		Patch	Blend	SIG	1977 Filter	Kelvin Filter	Moon Filter	WaNet	BppAttack
CIFAR-10	NiN	97.62%	91.41%	98.39%	97.69%	97.96%	96.87%	92.10%	96.68%
	VGG16	99.86%	98.83%	98.43%	97.42%	99.60%	98.72%	98.71%	91.97%
	ResNet18	99.61%	99.74%	99.17%	96.54%	94.57%	97.50%	99.95%	99.33%
	Wide-ResNet34	98.51%	98.52%	94.14%	95.31%	99.64%	97.73%	84.45%	91.91%
	MobileNetV2	96.50%	99.48%	95.31%	93.51%	96.60%	93.12%	98.75%	82.29%
	InceptionV3	99.24%	99.35%	97.65%	98.46%	93.59%	97.65%	96.98%	92.26%
	EfficientB0	98.95%	97.89%	95.99%	92.42%	95.54%	91.41%	85.93%	95.89%
	DenseNet121	99.01%	90.63%	99.60%	98.04%	94.14%	96.79%	100.00%	96.74%
ImageNet	VGG16	95.12%	91.75%	95.75%	99.02%	98.85%	99.34%	99.85%	96.18%
	ResNet18	98.25%	97.12%	93.00%	97.25%	98.65%	94.37%	99.74%	99.50%
	DenseNet169	92.45%	87.75%	85.50%	93.85%	97.93%	96.28%	94.62%	90.45%

UNICORN can effectively invert the trigger that is similar to injected triggers. For example, for the backdoored models produced via patch attack (Gu et al., 2017), the inverted trigger share the same location (i.e., right upper corner) and the color (i.e., yellow) with the injected trigger. For the attack in filter space, feature space and numerical space, our method also successfully inverted the global perturbations. The inverted triggers might be not equal to the injected triggers. This is understandable because existing backdoor attacks are actually inaccurate (Wang et al., 2022a). In other words, a trigger that is similar but not equal to the injected one is also able to activate the malicious backdoor behaviors of the model. The results show that UNICORN can effectively invert the triggers in different input spaces.

Comparison to existing methods. To compare the effectiveness of UNICORN and existing trigger inversion methods, we collect the ASR-Inv obtained by different methods.

The dataset and the model used is CIFAR-10 and ResNet18, respectively. The number of available clean samples is 10 samples for each class. Results in Table 2 demonstrate the average ASR-Inv of UNICORN are 99.51%, 96.20%, 99.95%, and 99.33% for the attack in pixel space, signal space, feature space and numerical space, respectively. On average, the ASR-Inv of UNICORN is 1.32 times higher than that of Neural Cleanse (NC), and 1.33 times higher than that of K-arm. For existing methods, their inverted trigger has higher ASR-Inv on

Table 2: ASR-Inv for different methods.

Space	Attack	NC	K-arm	UNICORN
Pixel	Patch	92.40%	89.47%	99.61%
	Blend	90.75%	88.24%	99.74%
	SIG	89.69%	91.32%	99.17%
Signal	1977	63.63%	65.28%	96.54%
	Kelvin	67.46%	63.54%	94.57%
	Moon	73.93%	72.93%	97.50%
Feature	WaNet	61.90%	62.50%	99.95%
Numerical	BppAttack	55.83%	59.84%	99.33%

pixel space attacks, while the ASR-Inv on other three spaces is much lower. This is understandable because existing methods assumes the trigger is a static pattern with small size in the pixel space, and it formalize the trigger by using pixel space masks and patterns. However, UNICORN formalizes the triggers in a more general form, thus it has better generalizability and it is highly effective for various types of triggers.

5.3 ABLATION STUDIES.

In this section, we evaluate the impacts of different constraints used in Eq. 1 (i.e., mask size constraint, stealthiness constraint and disentanglement constraint).

Effects of mask size constraint. In Eq. 1, we constrain the size of the input space mask. In detail, we use the threshold value β and make the size of the input space mask smaller than β. To study the influence of the mask size constraint, we vary the threshold value β and collect the cosine similarity (SIM) between model's intermediate representations produced by injected triggers (ground-truth) and the inverted triggers under different β. Higher

Table 3: Influence of mask size threshold.

β	1%	3%	5%	10%	20%
SIM	0.54	0.62	0.76	0.80	0.65

SIM value means the intermediate representations of the inverted trigger is closer to that of the injected trigger. The results are demonstrated in Table 3. As can be observed, the similarity between

Patch	Blended	SIG	Filter	WaNet	BppAttack

Fig. 3: Visualizations of the inverted triggers.

the inverted trigger features and the injected trigger features achieves highest value when the value of β is around 10% of the entire input space. Thus, we set the default value of as 10%.

Effects of disentanglement constraint. In our trigger inversion framework, we also add a constraint to disentangle the compromised activation vector and benign activation vector (§4). To investigate the effects of it, we compare the ASR-Inv of our method with and without the disentanglement constraint. The model and the dataset used is EfficientNetB0 and CIFAR-10. Results in Table 4 show that the ASR-Inv of the inverted triggers drop rapidly if the disentanglement constraint is removed. In detail, the average ASR-Inv is 94.25% and 64.56% for the method with and without disentanglement constraint, respectively. The results demonstrate that the disentanglement constraint is important for inverting the injected triggers in the model.

Effects of stealthiness constraint. As we discussed in §4, we use SSIM score to constrain the stealthiness of the backdoor samples. In Eq. 1, we use a threshold value γ to constrain the SSIM score. The higher the SSIM score is, the stealthier the trigger is. In this section, we show the inverted backdoor samples generated by the framework with and without the SSIM constraint (stealthiness constraints). The results are demonstrated in Fig. 4. We also show the sample pasted with injected trigger at the left

Fig. 4: Effects of stealthiness constraint.

most column. As can be observed, when we remove the stealthiness constraint, the main contents in the image becomes difficult to tell, and the quality of the image becomes low. When the constraint is added, the samples pasted with the inverted trigger is close to the injected backdoor sample. Thus, to satisfy the stealthiness requirement, adding the stealthiness constraint in the optimization of trigger inversion is needed. We set $\gamma = 0.85$ as the default setting.

5.4 EXTENSION TO SELF-SUPERVISED MODELS.

To investigate if UNICORN can generalize to models generated by different training paradigms, in this section, we evaluate our framework on self-supervised learning models. Different from supervised learning, self-supervised learning (Chen et al., 2020; He et al., 2020) first pre-trains an encoder

Table 4: Effects of disentanglement constraint.

	Pixel			Signal			Feature	Numerical
	Patch	Blended	SIG	1977 Filter	Kelvin Filter	Moon Filter	WaNet	BppAttack
ASR-Inj	99.92%	99.70%	98.71%	98.46%	99.31%	98.67%	98.69%	99.18%
ASR-Inv w/o Disentanglement	68.08%	64.64%	68.78%	63.20%	55.42%	70.50%	58.82%	70.54%
ASR-Inv w/ Disentanglement	98.95%	97.89%	95.99%	92.42%	95.54%	91.41%	85.93%	95.89%

with unlabeled data, and then builds downstream classifiers by using the encoder as feature extractor. In backdoor attacks for self-supervised learning, backdoor injected into pre-trained encoders can be inherited to the downstream classifiers. Directly conducting trigger inversion on encoders is important as it can reduce the cost of training extra downstream classifiers for inverting triggers. In this section, we use a mainstream self-supervised learning backdoor attack Badencoder (Jia et al., 2021) to evaluate if UNICORN can be applied for self-supervised models. Badencoder assumes that attackers have knowledge of the downstream task and have access to few reference samples belong to the downstream target class. It first trains a clean encoder using SimCLR (Chen et al., 2020), then injects backdoors into this pre-trained encoder. By default, Badencoder uses a white square patch as its trigger. Its backdoor optimization maximizes the similarity between clean encoder extracted and backdoored encoder extracted features of benign inputs, and maximizes the similarity between backdoored encoder extracted features of inputs with triggers and features of reference samples.

We use the backdoored encoder generated by Badencoder on CIFAR-10 dataset (Krizhevsky et al., 2009) to invert triggers. Instead of minimizing the classification loss on the target labels, we use one reference sample for each target class as the Badencoder does, and maximize the similarity between the embedding of reference sample and that of samples pasted with inverted triggers. As illustrated in Fig. 5, we visualize the inverted triggers and injected triggers in a backdoored encoder. It shows

Table 5: ASR in self-supervised learning.

Target class	ASR-Inj	ASR-Inv
Airplane	98.92%	99.92%
Truck	99.81%	99.75%
Horse	94.88%	91.35%
Average	97.87%	97.01%

that UNICORN can invert a similar patch trigger as the injected one at the bottom right corner of input images. We also evaluate the attack success rate of our inverted triggers (ASR-Inv) in downstream classifiers. We adopt STL10 (Coates et al., 2011) as the downstream dataset and fine-tune 20 epochs for classifiers. The target classes of the reference input we use are truck, airplane, and horse, respectively, which are the same as Badencoder. In Table 5, ASR-Inj means the ASR of injected triggers. From Table 5, we can observe that in different target class, our inverted triggers all have comparative ASR (i.e., over 90%) as injected triggers.

6 DISCUSSION

Ethics. Studies on adversarial machine learning potentially have ethical concerns. This paper proposes a general framework to invert backdoor triggers in DNN models. We believe this framework can help improve the security of DNNs and be beneficial to society.

Extention to NLP models. In this paper, we have discussed backdoor triggers in different input spaces in CV models. Similarly, backdoor triggers can be injected into NLP models in different input spaces, e.g., word space (Chen et al., 2021; Qi et al., 2021b), token space (Shen et al., 2021; Zhang et al., 2021), and embedding space (Qi et al., 2021a; Kurita et al., 2020; Yang et al., 2021). Expanding our framework to NLP trigger inversion will be our future work.

7 CONCLUSION

In this paper, we formally define the trigger in backdoor attacks against DNNs, and identify the inner behaviors in backdoor models based on the analysis. Based on it, we propose a backdoor trigger inversion method that can generalize to various types of triggers. Experiments on different datasets, models and attacks show that our method is robust to different types of backdoor attacks, and it outperforms prior methods that are based on attack-specific constraints.

REFERENCES

Mauro Barni, Kassem Kallas, and Benedetta Tondi. A new backdoor attack in cnns by training set corruption without label poisoning. In *2019 IEEE International Conference on Image Processing (ICIP)*, pp. 101–105. IEEE, 2019.

Bryant Chen, Wilka Carvalho, Nathalie Baracaldo, Heiko Ludwig, Benjamin Edwards, Taesung Lee, Ian Molloy, and Biplav Srivastava. Detecting backdoor attacks on deep neural networks by activation clustering. *arXiv preprint arXiv:1811.03728*, 2018.

Huili Chen, Cheng Fu, Jishen Zhao, and Farinaz Koushanfar. Deepinspect: A black-box trojan detection and mitigation framework for deep neural networks. In *IJCAI*, pp. 4658–4664, 2019.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. *arXiv preprint arXiv:2002.05709*, 2020.

Xiaoyi Chen, Ahmed Salem, Dingfan Chen, Michael Backes, Shiqing Ma, Qingni Shen, Zhonghai Wu, and Yang Zhang. Badnl: Backdoor attacks against nlp models with semantic-preserving improvements. In *Annual Computer Security Applications Conference*, pp. 554–569, 2021.

Xinyun Chen, Chang Liu, Bo Li, Kimberly Lu, and Dawn Song. Targeted backdoor attacks on deep learning systems using data poisoning. *arXiv preprint arXiv:1712.05526*, 2017.

Siyuan Cheng, Yingqi Liu, Shiqing Ma, and Xiangyu Zhang. Deep feature space trojan attack of neural networks by controlled detoxification. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 1148–1156, 2021.

Edward Chou, Florian Tramèr, Giancarlo Pellegrino, and Dan Boneh. Sentinet: Detecting physical attacks against deep learning systems. 2018.

Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 215–223. JMLR Workshop and Conference Proceedings, 2011.

Bao Gia Doan, Ehsan Abbasnejad, and Damith C Ranasinghe. Februus: Input purification defense against trojan attacks on deep neural network systems. In *Annual Computer Security Applications Conference*, pp. 897–912, 2020.

Khoa Doan, Yingjie Lao, Weijie Zhao, and Ping Li. Lira: Learnable, imperceptible and robust backdoor attacks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 11966–11976, 2021.

Min Du, Ruoxi Jia, and Dawn Song. Robust anomaly detection and backdoor attack detection via differential privacy. *arXiv preprint arXiv:1911.07116*, 2019.

Yu Feng, Benteng Ma, Jing Zhang, Shanshan Zhao, Yong Xia, and Dacheng Tao. Fiba: Frequency-injection based backdoor attack in medical image analysis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 20876–20885, 2022.

Yansong Gao, Change Xu, Derui Wang, Shiping Chen, Damith C Ranasinghe, and Surya Nepal. Strip: A defence against trojan attacks on deep neural networks. In *Proceedings of the 35th Annual Computer Security Applications Conference*, pp. 113–125, 2019.

Tianyu Gu, Brendan Dolan-Gavitt, and Siddharth Garg. Badnets: Identifying vulnerabilities in the machine learning model supply chain. *arXiv preprint arXiv:1708.06733*, 2017.

Wenbo Guo, Lun Wang, Xinyu Xing, Min Du, and Dawn Song. Tabor: A highly accurate approach to inspecting and restoring trojan backdoors in ai systems. *arXiv preprint arXiv:1908.01763*, 2019.

Jonathan Hayase, Weihao Kong, Raghav Somani, and Sewoong Oh. Defense against backdoor attacks via robust covariance estimation. In *International Conference on Machine Learning*, pp. 4129–4139. PMLR, 2021.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9729–9738, 2020.

Sanghyun Hong, Varun Chandrasekaran, Yiğitcan Kaya, Tudor Dumitraş, and Nicolas Papernot. On the effectiveness of mitigating data poisoning attacks with gradient shaping. *arXiv preprint arXiv:2002.11497*, 2020.

Kurt Hornik, Maxwell Stinchcombe, and Halbert White. Multilayer feedforward networks are universal approximators. *Neural networks*, 2(5):359–366, 1989.

Xiaoling Hu, Xiao Lin, Michael Cogswell, Yi Yao, Susmit Jha, and Chao Chen. Trigger hunting with a topological prior for trojan detection. *arXiv preprint arXiv:2110.08335*, 2021.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4700–4708, 2017.

Kunzhe Huang, Yiming Li, Baoyuan Wu, Zhan Qin, and Kui Ren. Backdoor defense via decoupling the training process. *arXiv preprint arXiv:2202.03423*, 2022.

Jinyuan Jia, Yupei Liu, and Neil Zhenqiang Gong. Badencoder: Backdoor attacks to pre-trained encoders in self-supervised learning. *arXiv preprint arXiv:2108.00352*, 2021.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Keita Kurita, Paul Michel, and Graham Neubig. Weight poisoning attacks on pre-trained models. *arXiv preprint arXiv:2004.06660*, 2020.

Chaoran Li, Xiao Chen, Derui Wang, Sheng Wen, Muhammad Ejaz Ahmed, Seyit Camtepe, and Yang Xiang. Backdoor attack on machine learning based android malware detectors. *IEEE Transactions on Dependable and Secure Computing*, 2021a.

Shaofeng Li, Minhui Xue, Benjamin Zhao, Haojin Zhu, and Xinpeng Zhang. Invisible backdoor attacks on deep neural networks via steganography and regularization. *IEEE Transactions on Dependable and Secure Computing*, 2020.

Yige Li, Nodens Koren, Lingjuan Lyu, Xixiang Lyu, Bo Li, and Xingjun Ma. Neural attention distillation: Erasing backdoor triggers from deep neural networks. *arXiv preprint arXiv:2101.05930*, 2021b.

Yige Li, Xixiang Lyu, Nodens Koren, Lingjuan Lyu, Bo Li, and Xingjun Ma. Anti-backdoor learning: Training clean models on poisoned data. *Advances in Neural Information Processing Systems*, 34, 2021c.

Yuezun Li, Yiming Li, Baoyuan Wu, Longkang Li, Ran He, and Siwei Lyu. Invisible backdoor attack with sample-specific triggers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 16463–16472, 2021d.

Junyu Lin, Lei Xu, Yingqi Liu, and Xiangyu Zhang. Composite backdoor attack for deep neural network by mixing existing benign features. In *Proceedings of the 2020 ACM SIGSAC Conference on Computer and Communications Security*, pp. 113–131, 2020.

Min Lin, Qiang Chen, and Shuicheng Yan. Network in network. *arXiv preprint arXiv:1312.4400*, 2013.

Kang Liu, Brendan Dolan-Gavitt, and Siddharth Garg. Fine-pruning: Defending against backdooring attacks on deep neural networks. In *International Symposium on Research in Attacks, Intrusions, and Defenses*, pp. 273–294. Springer, 2018.

Yingqi Liu, Shiqing Ma, Yousra Aafer, Wen-Chuan Lee, Juan Zhai, Weihang Wang, and Xiangyu Zhang. Trojaning attack on neural networks. 2017.

Yingqi Liu, Wen-Chuan Lee, Guanhong Tao, Shiqing Ma, Yousra Aafer, and Xiangyu Zhang. Abs: Scanning neural networks for back-doors by artificial brain stimulation. In *Proceedings of the 2019 ACM SIGSAC Conference on Computer and Communications Security*, pp. 1265–1282, 2019.

Yingqi Liu, Guangyu Shen, Guanhong Tao, Zhenting Wang, Shiqing Ma, and Xiangyu Zhang. Ex-ray: Distinguishing injected backdoor from natural features in neural networks by examining differential feature symmetry. *arXiv preprint arXiv:2103.08820*, 2021.

Yunfei Liu, Xingjun Ma, James Bailey, and Feng Lu. Reflection backdoor: A natural backdoor attack on deep neural networks. In *European Conference on Computer Vision*, pp. 182–199. Springer, 2020.

Lubin Meng, Jian Huang, Zhigang Zeng, Xue Jiang, Shan Yu, Tzyy-Ping Jung, Chin-Teng Lin, Ricardo Chavarriaga, and Dongrui Wu. Eeg-based brain-computer interfaces are vulnerable to backdoor attacks. *arXiv preprint arXiv:2011.00101*, 2020.

Anh Nguyen and Anh Tran. Input-aware dynamic backdoor attack. *arXiv preprint arXiv:2010.08138*, 2020.

Anh Nguyen and Anh Tran. Wanet–imperceptible warping-based backdoor attack. *arXiv preprint arXiv:2102.10369*, 2021.

Fanchao Qi, Yangyi Chen, Xurui Zhang, Mukai Li, Zhiyuan Liu, and Maosong Sun. Mind the style of text! adversarial and backdoor attacks based on text style transfer. *arXiv preprint arXiv:2110.07139*, 2021a.

Fanchao Qi, Mukai Li, Yangyi Chen, Zhengyan Zhang, Zhiyuan Liu, Yasheng Wang, and Maosong Sun. Hidden killer: Invisible textual backdoor attacks with syntactic trigger. *arXiv preprint arXiv:2105.12400*, 2021b.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pp. 234–241. Springer, 2015.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3):211–252, 2015.

Ahmed Salem, Rui Wen, Michael Backes, Shiqing Ma, and Yang Zhang. Dynamic backdoor attacks against machine learning models. *arXiv preprint arXiv:2003.03675*, 2020.

Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4510–4520, 2018.

Esha Sarkar, Hadjer Benkraouda, and Michail Maniatakos. Facehack: Triggering backdoored facial recognition systems using facial characteristics. *arXiv preprint arXiv:2006.11623*, 2020.

Giorgio Severi, Jim Meyer, Scott Coull, and Alina Oprea. {Explanation-Guided} backdoor poisoning attacks against malware classifiers. In *30th USENIX Security Symposium (USENIX Security 21)*, pp. 1487–1504, 2021.

Guangyu Shen, Yingqi Liu, Guanhong Tao, Shengwei An, Qiuling Xu, Siyuan Cheng, Shiqing Ma, and Xiangyu Zhang. Backdoor scanning for deep neural networks through k-arm optimization. *arXiv preprint arXiv:2102.05123*, 2021.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2818–2826, 2016.

Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International conference on machine learning*, pp. 6105–6114. PMLR, 2019.

Di Tang, XiaoFeng Wang, Haixu Tang, and Kehuan Zhang. Demon in the variant: Statistical analysis of dnns for robust backdoor contamination detection. In *30th {USENIX} Security Symposium ({USENIX} Security 21)*, 2021.

Guanhong Tao, Yingqi Liu, Siyuan Cheng, Shengwei An, Zhuo Zhang, Qiuling Xu, Guangyu Shen, and Xiangyu Zhang. Deck: Model hardening for defending pervasive backdoors. *arXiv preprint arXiv:2206.09272*, 2022a.

Guanhong Tao, Yingqi Liu, Guangyu Shen, Qiuling Xu, Shengwei An, Zhuo Zhang, and Xiangyu Zhang. Model orthogonalization: Class distance hardening in neural networks for better security. In *2022 IEEE Symposium on Security and Privacy (SP). IEEE*, volume 3, 2022b.

Brandon Tran, Jerry Li, and Aleksander Madry. Spectral signatures in backdoor attacks. *arXiv preprint arXiv:1811.00636*, 2018.

Alexander Turner, Dimitris Tsipras, and Aleksander Madry. Label-consistent backdoor attacks. *arXiv preprint arXiv:1912.02771*, 2019.

Bolun Wang, Yuanshun Yao, Shawn Shan, Huiying Li, Bimal Viswanath, Haitao Zheng, and Ben Y Zhao. Neural cleanse: Identifying and mitigating backdoor attacks in neural networks. In *2019 IEEE Symposium on Security and Privacy (SP)*, pp. 707–723. IEEE, 2019.

Zhenting Wang, Hailun Ding, Juan Zhai, and Shiqing Ma. Towards understanding and defending input space trojans. *arXiv preprint arXiv:2202.06382*, 2022a.

Zhenting Wang, Juan Zhai, and Shiqing Ma. Bppattack: Stealthy and efficient trojan attacks against deep neural networks via image quantization and contrastive adversarial learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 15074–15084, 2022b.

Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 13(4):600–612, 2004.

Emily Wenger, Josephine Passananti, Arjun Nitin Bhagoji, Yuanshun Yao, Haitao Zheng, and Ben Y Zhao. Backdoor attacks against deep learning systems in the physical world. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6206–6215, 2021.

Dongxian Wu and Yisen Wang. Adversarial neuron pruning purifies backdoored deep models. *Advances in Neural Information Processing Systems*, 34:16913–16925, 2021.

Zhen Xiang, David J Miller, Siheng Chen, Xi Li, and George Kesidis. A backdoor attack against 3d point cloud classifiers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 7597–7607, 2021.

Zhen Xiang, David J Miller, and George Kesidis. Post-training detection of backdoor attacks for two-class and multi-attack scenarios. *arXiv preprint arXiv:2201.08474*, 2022.

Xiaojun Xu, Qi Wang, Huichen Li, Nikita Borisov, Carl A Gunter, and Bo Li. Detecting ai trojans using meta neural analysis. *arXiv preprint arXiv:1910.03137*, 2019.

Limin Yang, Zhi Chen, Jacopo Cortellazzi, Feargus Pendlebury, Kevin Tu, Fabio Pierazzi, Lorenzo Cavallaro, and Gang Wang. Jigsaw puzzle: Selective backdoor attack to subvert malware classifiers. *arXiv preprint arXiv:2202.05470*, 2022.

Wenkai Yang, Lei Li, Zhiyuan Zhang, Xuancheng Ren, Xu Sun, and Bin He. Be careful about poisoned word embeddings: Exploring the vulnerability of the embedding layers in nlp models. *arXiv preprint arXiv:2103.15543*, 2021.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

Yi Zeng, Si Chen, Won Park, Z Morley Mao, Ming Jin, and Ruoxi Jia. Adversarial unlearning of backdoors via implicit hypergradient. *arXiv preprint arXiv:2110.03735*, 2021a.

Yi Zeng, Won Park, Z Morley Mao, and Ruoxi Jia. Rethinking the backdoor attacks' triggers: A frequency perspective. *arXiv preprint arXiv:2104.03413*, 2021b.

Tongqing Zhai, Yiming Li, Ziqi Zhang, Baoyuan Wu, Yong Jiang, and Shu-Tao Xia. Backdoor attack against speaker verification. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 2560–2564. IEEE, 2021.

Zhengyan Zhang, Guangxuan Xiao, Yongwei Li, Tian Lv, Fanchao Qi, Zhiyuan Liu, Yasheng Wang, Xin Jiang, and Maosong Sun. Red alarm for pre-trained models: Universal vulnerability to neuron-level backdoor attacks. *arXiv preprint arXiv:2101.06969*, 2021.

A APPENDIX

A.1 DETAILS OF DATASETS

In this section, we introduce the details of the datasets involved in the experiments. All datasets used are open-sourced.

CIFAR10 (Krizhevsky et al., 2009). This dataset is built for recognizing general objects such as dogs, cars, and planes. It contains 50000 training samples and 10000 training samples in 10 classes.

ImageNet (Russakovsky et al., 2015). This dataset is a large-scale object classification benchmark. In this paper, we use a subset of the original ImageNet dataset specified in Li et al. (Li et al., 2021d). The subset has 100000 training samples and 10000 test samples in 200 classes.

A.2 DETAILS OF ATTACKS

In this section, we introduce the details of the used backdoor attacks. The attacks are in single-target setting. The target label of the attack is randomly selected for each backdoored model.

Patch Attack (Gu et al., 2017). This attack uses a static pattern (i.e., a patch) as backdoor trigger. It generates backdoor inputs by pasting its pre-defined trigger pattern (e.g., a colored square) on the original inputs. It then compromises the victim models by poisoning a subset of the training data (i.e., injecting backdoor samples and modifying their labels to target labels). In our experiments, we use a 3×3 yellow patch located at the right-upper corner as the backdoor trigger. The poisoning rate we used is 5%.

Blend Attack (Chen et al., 2017). This attack generates backdoor samples via blending the clean input with a predefined pattern, e.g., a cartoon cat. It also considers the poisoning threat model where the attacker can modify the training data, but can not control the whole training process. The poisoning rate we used is 5%.

SIG Attack (Barni et al., 2019). This attack uses superimposed sinusoidal signals as backdoor triggers. It assumes that adversary can poison a subset of training samples but can not fully control the training process. In our experiments, we set the poisoning rate as 5%. Also, we set the frequency and the magnitude of the backdoor signal as 6 and 20, respectively.

Filter Attack (Liu et al., 2019). This attack exploits image filters as triggers and creates backdoor samples by applying selected filters on images. Similar to BadNets, the backdoor triggers are injected with poisoning. In our experiments, we use a 5% poisoning rate and apply the 1977, Kelvin and Moon filter from Instagram as backdoor triggers.

WaNet (Nguyen & Tran, 2021). This method achieves backdoor attacks by image warping. It adopts an elastic warping operation to transform backdoor triggers. Different from BadNets and Filter Attack, in WaNet, the adversary can modify the training process of the victim models to make the attack more resistant to backdoor defenses. WaNet is nearly imperceptible to human, and it is

Fig. 5: Visualization of inverted triggers of backdoored encoders.

able to bypass many existing backdoor defenses (Gao et al., 2019; Chen et al., 2018; Liu et al., 2018; Wang et al., 2019). In our experiments, the warping strength and the grid size are set to 0.5 and 4, respectively.

BppAttack (Wang et al., 2022b). This attack creates backdoor samples by using image quantization and dithering techniques. It changes the numerical representations of the images. It considers the attacker that can access the full control of the training process. It is even more stealthier than WaNet (Nguyen & Tran, 2021). In this paper, we set the bits depth for the backdoor inputs as 5.

A.3 COEFFICIENT ADJUSTMENT IN OPTIMIZATION

In this section, we discuss the detailed method for adjusting the coefficients for different items in the optimization. Following existing works (Wang et al., 2019; Liu et al., 2021), coefficients are dynamic in the optimization. When the loss value is larger (or smaller) than the threshold value (i.e., the loss value does not satisfy the constraint), we use a large coefficient w_{large}. Otherwise, if the loss value satisfy the constraint, we apply a small coefficient w_{small}. By default we set $w_{small} = 0$. The default w_{large} value for w_1, w_2, w_3, and w_4 are 200, 10, 10, and 1.