Sparse Hypergraph Community Detection Thresholds in Stochastic Block Model

Abstract

Community detection in random graphs or hypergraphs is an interesting fundamental problem in statistics, machine learning and computer vision. When the hypergraphs are generated by a *stochastic block model*, the existence of a sharp threshold on model parameters for community detection was conjectured by Angelini et al. 2015. In this paper, we confirm the positive part of the conjecture, the possibility of non-trivial reconstruction above the threshold, for the case of two blocks by comparing the hypergraph stochastic block model with its Erdös-Rényi counterpart. Furthermore, we show the negative part of the conjecture by relating the model with the so-called *multi-type Galton-Watson hypertrees* and considering the broadcasting problem on these hypertrees. The methods developed in this paper are generalised from the study of sparse random graphs by Mossel et al. 2015.

1 Introduction

Community detection or clustering, aiming to identify groups sharing similar properties from a global population: is a fundamental important problem in statistics, network analysis and computer vision [15, 36, 11, 31, 27]. Many clustering algorithms have been developed based on graphs in which each edge contains exactly two vertices representing pairwise relationships on data. However, real-world data are often much more complicated than the ordinary graph structures. For example, in the co-authorship network [9, 25, 28], the number of co-authors may vary from paper to paper so that one can hardly study edges consisting of two co-authors only.

To represent higher order relationships among data, *hypergraphs* have been proposed to model data and have been shown to have some advantages over graphs [38]. In the co-authorship example above, a generalised edge (called *hyperedge*) allows us to consider the connectivity of arbitrarily many co-authors. In recent years, hypergraphs have been widely used to model complex data relationships, for instance, in robust multi-structure clustering [27], bioinformatics [34], and social networks extraction [37]. However, from both theoretical and methodological sides, the complexity of hypergraphs creates much more challenges: in the sense that many analysis tools developed in the graph case can not be easily generalised to the hypergraph case. In general, analysing the spectral properties of the adjacency tensor of a hypergraph is more difficult than studying the spectral of the adjacency matrix of a graph.

The *stochastic block model* (SBM), also known as *planted partition model*, was initially proposed by Holland et al. [17] to model random graphs with community structures. The general idea behind this model is to label each vertices as a community member identically and independently, and then construct a random graph based on the membership and some given probabilities. It becomes the well-known Erdös-Rényi graph model if we ignore the membership restriction. The recovery or detection problem based on the SBM is to find the community membership when the number of vertices is sufficiently large. SBM often serves as a benchmark for clustering algorithms on graph

data. Likewise, an analogous model called *hypergraph stochastic block model* (HSBM) was proposed to model higher-order relationships for random hypergraphs [13]. In what follows, we will present a brief introduction to hypergraphs, HSBM and its associated detection problem.

1.1 The stochastic block model for hypergraphs

A *hypergraph* is a pair $H = (\mathcal{V}, \mathcal{E})$, where $\mathcal{V}$ is a set of vertices and $\mathcal{E}$ is a set of *hyperedges*, which is a collection of subsets of $\mathcal{V}$. The *degree* of a vertex $v \in \mathcal{V}$ is the number of hyperedges in H that contains v. The *degree* of a hyperedge $e \in \mathcal{E}$ is the number of vertices contained in e. The hypergraph H is called *d-uniform* if the degree of any hyperedge $e \in \mathcal{E}$ is d. A 2-uniform hypergraph is a graph. An *l-cycle* in H is a cyclic ordering of a subset of the vertex set, and of hyperedges, where any two adjacent hyperedges have exactly l common vertices. We call an *l-cycle* *loose* if $l = 1$. For instance, let $H_3 = (\mathcal{V}, \mathcal{E})$ be a 3-uniform hypergraph, where $\mathcal{V} = \{v_1, v_2, \cdots, v_7\}$, $\mathcal{E} = \{(v_i, v_j, v_k) | 1 \le i < j < k \le 7\}$. Then $\{(v_1, v_2, v_3), (v_3, v_4, v_5), (v_5, v_6, v_1)\}$ is a loose cycle.

There are many ways to represent a hypergraph. For instance, the *incidence matrix* of a hypergraph H is defined as $A \in \{0,1\}^{|\mathcal{V}| \times |\mathcal{E}|}$, where $A(v, e) = 1$ if the vertex $v \in \mathcal{V}$ is contained in the hyperedge $e \in \mathcal{E}$, and 0 otherwise. The *adjacency tensor* of H is defined as $T \in \{0,1\}^{n^n}$, where $T_{i_1, \cdots, i_d} = 1$ if $\{i_1, \cdots, i_d\}$ is a hyperedge of H, and 0 otherwise. The *adjacency matrix* of H is defined as $B = (B_{ij})_{|\mathcal{V}| \times |\mathcal{V}|}$, where $B_{ij} = \sum_{e:\{i,j\} \in e} T_e$ if $i \ne j$, and 0 otherwise, here e is a hyperedge and T_e is an element in its associated adjacency tensor. Unfortunately, most of the computations involving the adjacency tensor are NP-hard [16].

For simplicity, from now on, we specify our d-uniform hypergraph stochastic block model with two roughly balanced communities. For non-uniform hypergraphs or hypergraphs with multi-communities, it may require extra effort to consider, which will be reserved for future work. Let $H = ([n], \mathcal{E})$ be a d-uniform hypergraph with vertex set $[n] := \{1, 2, \cdots, n\}$ and hyperedge set $\mathcal{E}$, $\sigma := (\sigma_1, \cdots, \sigma_n) = \{+1, -1\}^n$ the spins on $[n]$, which means each vertex $i \in [n]$ is assigned with a spin $\sigma_i \in \{+1, -1\}$. Let $\mathcal{S}_n$ be the set of all pairs (H, σ), we can generate a random pair (H, σ) from the finite set $\mathcal{S}_n$ as follows ([13, 14, 20, 26]):

- First generate i.i.d random variables $\sigma_i \in \{+1, -1\}$ uniformly for each $i \in [n]$.
- Then, for the obtained $\sigma = (\sigma_1, \cdots, \sigma_n)$, we generate a random d-uniform hypergraph H where an hyperedge $e = \{i_1, \cdots, i_d\}$ is included independently with probability p_n if $\sigma_{i_1} = \cdots = \sigma_{i_d}$, and with probability q_n otherwise, where $0 < q_n < p_n < 1$ (p_n, q_n possibly depending on n).

We denote by $\mathcal{H}_d(n, p_n, q_n)$ a d-uniform hypergraph generated by the process above. (With a little notation abuse, we sometimes denote the distribution that such hypergraphs follow by the same notation). In particular, $\mathcal{H}_2(n, p_n, q_n)$ is a random graph generated by the graph version of the SBM.

Suppose $\mathcal{C}_1 = \{i \in [n] | \sigma_i = +1\}$ and $\mathcal{C}_2 = \{i \in [n] | \sigma_i = -1\}$ are two communities in the hypergraph H. The goal of community detection is to estimate the unknown spin σ up a sign flip by observing H only from a sample (H, σ) drawn from $\mathcal{H}_d(n, p_n, q_n)$, i.e., to find estimators $\hat{\sigma}_i \in \{+1, -1\}$ that are correlated with the true partition σ_i. By correlation, we mean there exists a constant $c \in (0, 1)$, for any $\epsilon > 0$,

$$\lim_{n \to \infty} \mathbb{P}(\{|\mathcal{O}_n(\hat{\sigma}, \sigma) - c| > \epsilon\} \cap \{|\mathcal{O}_n(\hat{\sigma}, \sigma) + c| > \epsilon\}) = 0,$$

where $\mathcal{O}_n(\hat{\sigma}, \sigma) := \frac{1}{n} \sum_{i \in [n]} \sigma_i \hat{\sigma}_i$ is the empirical overlap between σ and $\hat{\sigma}$.

The study of *sparse* graphs/hypergraphs as well those with constant average degree, is well motivated from the viewpoint of real networks. For instance, many large social networks like Twitter or LinkedIn, may have several millions of nodes but only ten times more edges [21]. A coauthorship network may have millions of nodes, but the average degree is no more than 20 in general [25]. Therefore, It is natural to consider the sparse HSBM with p_n and q_n of the order $\mathcal{O}(1/\binom{n}{d-1})$.

Decelle et al. [7] conjectured the existence of a sharp threshold, called *Kesten-Stigun threshold*, of detection in the sparse graph SBM based on some ideas from statistical physics. More precisely, if $p_n = \frac{a}{n}, q_n = \frac{b}{n}$, where a, b are constants independent of n, then detection is possible if and only if $(a - b)^2 > 2(a + b)$. This conjecture was confirmed in [22, 23, 24, 6], for examples, by studying the

86   spectra of the non-backtracking [6], self-avoiding [22] or graph powering [1] matrices. Moreover,
87   some efficient algorithms were proposed to achieve detection at the threshold [6, 32, 1].

88   In the case of the hypergraph SBM, Angelini et al. [2] conjectured the existence of a sharp threshold on
89   the model parameters, for community detection in the sparse hypergraph. If $p_n = \frac{a}{\binom{n}{d-1}}$, $q_n = \frac{b}{\binom{n}{d-1}}$,
90   i.e., the hypergraph $H \sim \mathcal{H}_d(n, p_n, q_n)$ has constant expected vertex degree. Pal et al. [26] proved
91   the positive part of the conjecture, the detection is possible if $\beta^2 > \alpha$, where $\alpha = (d-1)\frac{a+(2^{d-1}-1)b}{2^{d-1}}$,
92    $\beta = (d-1)\frac{a-b}{2^{d-1}}$. Their method is based on the spectral analysis of the so-called *self-avoiding matrix*
93   associated with the hypergraph, which is a generalisation to random hypergraphs of the method
94   developed by Massoulié [22] for sparse random graphs. Moreover, the consistent estimators for
95   model parameters a and b are still unknown.

96   In the present paper, we reconfirm the positive part of the conjecture by comparing the sparse HSBM
97   with an appropriate Erdös-Rényi hypergraph model see Theorem 1.1. Further, in the same theorem
98   we give consistent estimators for a and b if the detection is possible. More importantly, we show that
99   it is impossible (Theorem 1.3) to detect communities if $\beta^2 < \alpha$ by coupling our hypergraph with the
100   multi-type Galton-Watson hypertree and studying broadcasting problems on hypertree. The threshold
101   of broadcasting on a (hyper)tree results in that of detection on the HSBM. Our methods are motivated
102   by the study of the community detection problem on the graph SBM conducted by Mossel et al. [23].
103   The main results of the present paper are summarised as follows.

1.2   Main results

105   Let $\mathcal{H}_d(n, \frac{p_n+(2^{d-1}-1)q_n}{2^{d-1}})$ be the Erdös-Rényi model in which each hyperedge is included with
106   a common probability $\frac{p_n+(2^{d-1}-1)q_n}{2^{d-1}}$, which is chosen to make sure this model have the same
107   average degree as $\mathcal{H}_d(n, p_n, q_n)$. In other words, $\mathcal{H}_d(n, \frac{p_n+(2^{d-1}-1)q_n}{2^{d-1}})$ represents a d-uniform
108   random hypergraph without any community structures. In particular, $\mathcal{H}_2(n, \frac{p_n+q_n}{2})$ is the traditional
109   Erdös-Rényi random graph that has been extensively studied in the graph literature [4, 12, 8].

110   Let $\mathbb{P}_n$ and $\tilde{\mathbb{P}}_n$ denote the probability measures with respect to $\mathcal{H}_d(n, p_n, q_n)$ and
111   $\mathcal{H}_d(n, \frac{p_n+(2^{d-1}-1)q_n}{2^{d-1}})$, respectively. Then $\mathbb{P}_n$ and $\tilde{\mathbb{P}}_n$ are said to be *mutually contiguous* if for
112   any measurable sets A_n, $\mathbb{P}_n(A_n) \to 0$ if and only if $\tilde{\mathbb{P}}_n(A_n) \to 0$ as $n \to \infty$. $\mathbb{P}_n$ and $\tilde{\mathbb{P}}_n$ are said to
113   be *asymptotically orthogonal* if there exists a sequence of measurable sets A_n such that $\mathbb{P}_n(A_n) \to 0$
114   and $\tilde{\mathbb{P}}_n(A_n) \to 1$ as $n \to \infty$. From now on, we fix the following notation,

$$p_n := \frac{a}{\binom{n}{d-1}}, \quad q_n := \frac{b}{\binom{n}{d-1}},$$

115   where $a > b > 0$ are some constants independent of n, $d \geq 3$ is an integer. Define

$$\alpha := (d-1)\frac{a+(2^{d-1}-1)b}{2^{d-1}}, \quad \beta := (d-1)\frac{a-b}{2^{d-1}},$$

116   where α measures the expected degree of any vertex and β measures the discrepancy between the
117   number of neighbors with different signs of any vertex.

118   **Theorem 1.1.** *If $\beta^2 > \alpha$, then $\mathbb{P}_n$ and $\tilde{\mathbb{P}}_n$ are asymptotically orthogonal. Let X_{ζ_n} be the number of*
119   *loose cycles of length ζ_n and define*

$$\hat{\alpha}_n := \frac{d|\mathcal{E}|}{\binom{n}{d-1}}, \quad \hat{\beta}_n := (2\zeta_n X_{\zeta_n} - \hat{\alpha}_n^{\zeta_n})^{\frac{1}{\zeta_n}},$$

120   *where $\zeta_n = \lfloor \log^{1/4} n \rfloor$, $|\mathcal{E}|$ is the number of observed hyperedges, then $\hat{a}_n = \frac{1}{d-1}(\hat{\alpha}_n + (2^{d-1}-1)\hat{\beta}_n)$*
121   *and $\hat{b}_n = \frac{1}{d-1}(\hat{\alpha}_n - \hat{\beta}_n)$ are consistent estimators for a and b, respectively. Namely, $\hat{a}_n \to a$ and*
122   *$\hat{b}_n \to b$ in probability as $n \to \infty$.*

123   **Theorem 1.2.** *If $\beta^2 < \alpha$, then for any fixed vertices v_1 and v_2, $H \sim \mathcal{H}_d(n, p_n, q_n)$,*

$$\lim_{n\to\infty} \mathbb{P}_n(\sigma_{v_1} = +1 | H, \sigma_{v_2}) = \frac{1}{2}.$$

Theorem 1.3. *If $\beta^2 < \alpha$, then $\mathbb{P}_n$ and $\tilde{\mathbb{P}}_n$ are mutually contiguous. Further more, there is no consistent estimator for a and b if $\beta^2 < \alpha$.*

When $d = 2$, the condition $\beta^2 = \alpha$ becomes $(a-b)^2 = 2(a+b)$, which is the threshold for community detection in the (graph-based) SBM. Readers may refer to [22, 23, 24] for more detail. Intuitively speaking, Theorem 1.1 says that $\mathcal{H}_d(n, p_n, q_n)$ and $\mathcal{H}_d(n, \frac{p_n+(2^{d-1}-1)q_n}{2^{d-1}})$ are asymptotically almost surely distinguishable above the threshold (i.e., can distinguish a community with structure from a random hypergraph with the same average degree). While Theorem 1.3 states that they are not distinguishable below the threshold. Figure 1 shows the phase transition of community detection in the sparse HSBM where $d = 3, 4, 5$. Consider any two random vertices of a hypergraph H, Theorem 1.2 claims that no algorithm can tell whether they have the same spin, i.e., the probability of identifying them with the same spin is asymptotically almost surely the same as the probability of finding them with different spins. Put loosely, it is not possible to do any better than random chance when assigning labels.

Figure 1: Phase transition of community detection in the sparse HSBM: the detection is impossible below the dashed curves, while possible above the dashed curves (and below the purple line). The larger d is, the larger the area of possible detection is, which can be viewed from the threshold $\beta^2 = \alpha$, i.e., $b = a + \frac{2^{2d-3}-2^{d-2}}{d-1} - \sqrt{\frac{2^{2d-2}}{d-1}a + \frac{(2^{2d-3}-2^{d-2})^2}{(d-1)^2}}$.

The remainder of the present paper is organised as follows: In section 2, we study the probability distribution of the number of ζ_n-loose cycle X_{ζ_n} and then prove Theorem 1.1. In section 3, based on the multi-type Galton-Watson hypertree proposed in [26], we investigate the connection between the detection problem on $\mathcal{H}_d(n, p_n, q_n)$ and the broadcasting problem on the hypertree, which provides some tools to prove Theorem 1.2. Mossel et al. in [23] adopted Theorem 4.1 in [35] that gave sufficient conditions for contiguity to prove Theorem 1.3 where $d = 2$ (i.e., the graph SBM case). To prove Theorem 1.3 in the sparse HSBM case, we need to verify all conditions of Theorem 4.1 in [35]. Section 4 concludes the paper, including some further discussion.

2 The distribution of loose cycles

In this section, we mainly show that the number of ζ_n-loose cycles of $H \sim \mathcal{H}_d(n, p_n, q_n)$ or $H \sim \mathcal{H}_d(n, \frac{p_n+(2^{d-1}-1)q_n}{2^{d-1}})$ is asymptotically approximately Poisson-distributed. In general inhomogeneous graphs, Bollobaás et al. [5] demonstrated that the number of cycles asymptotically follows the Poisson distribution. We borrow their proof techniques to get a similar conclusion in the hypergraph case. Then, by comparing the first two moments of the number of ζ_n-loose cycles, we can find that $\mathcal{H}_d(n, p_n, q_n)$ and $\mathcal{H}_d(n, \frac{p_n+(2^{d-1}-1)q_n}{2^{d-1}})$ are asymptotically orthogonal if $\beta^2 > \alpha$.

Theorem 2.1. *Let X_{ζ_n} be the number of ζ_n-loose cycle of a hypergraph H. Suppose $\zeta_n = \mathcal{O}(\log^{1/4}(n))$.*

(1) If $H \sim \mathcal{H}_d(n, p_n, q_n)$, then $X_{\zeta_n} \xrightarrow{d} Pois(\frac{\alpha^{\zeta_n}+\beta^{\zeta_n}}{2\zeta_n})$;

(2) If $H \sim \mathcal{H}_d(n, \frac{p_n+(2^{d-1}-1)q_n}{2^{d-1}})$, then $X_{\zeta_n} \xrightarrow{d} Pois(\frac{\alpha^{\zeta_n}}{2\zeta_n})$,

156   *where $\xrightarrow{d}$ denotes convergent in distribution.*

157   For any non-negative integer s, let $[X]_s$ be the product $X(X-1)\cdots(X-s+1)$. By Lemma
158   2.8 in [35] (Lemma A.1 in the Appendix), if we can prove the expectation $\mathbb{E}[X_{\zeta_n}]_r \to \mu^r$, then
159   $X_{\zeta_n} \xrightarrow{d} \mathrm{Pois}(\mu)$. Refer to the Appendix for the detailed proof.

160   With the preparation provided by establishing Theorem 2.1, now we can prove our first main
161   result, Theorem 1.1. We use $\mathbb{P}_n(\cdot)$, $\mathbb{E}(\cdot)$, $\mathrm{Var}(\cdot)$ to denote probability, mean and variation with
162   respect to $\mathcal{H}_d(n, p_n, q_n)$ while notations with tilde above denote their counterparts with respect to
163   $\mathcal{H}_d(n, \frac{p_n + (2^{d-1}-1)q_n}{2^{d-1}})$.

164   *Proof of Theorem 1.1.* Since $\beta^2 > \alpha$, there exists a constant ρ satisfying $\beta > \rho > \sqrt{\alpha}$. Then
165   $\mathbb{E}X_{\zeta_n} = \mathrm{Var}X_{\zeta_n} = o(\rho^{2\zeta_n})$ and $\tilde{\mathbb{E}}X_{\zeta_n} = \tilde{\mathrm{Var}}X_{\zeta_n} = o(\rho^{2\zeta_n})$ as $n \to \infty$.

166   Let $A_n := \{X_{\zeta_n} \le \tilde{\mathbb{E}}X_{\zeta_n} + \rho^{\zeta_n}\}$, by Chebyshev's inequality,

$$\tilde{\mathbb{P}}_n(A_n) = \tilde{\mathbb{P}}_n\left(\frac{X_{\zeta_n} - \tilde{\mathbb{E}}X_{\zeta_n}}{\sqrt{\tilde{\mathrm{Var}}X_{\zeta_n}}} \le \frac{\rho^{\zeta_n}}{\sqrt{\tilde{\mathrm{Var}}X_{\zeta_n}}}\right) \ge 1 - \frac{\tilde{\mathrm{Var}}X_{\zeta_n}}{\rho^{2\zeta_n}} \to 1, \quad \text{as } n \to \infty. \qquad (1)$$

167   Since $\mathbb{E}X_{\zeta_n} - \tilde{\mathbb{E}}X_{\zeta_n} \sim \frac{\beta^{\zeta_n}}{2\zeta_n} = \omega(\rho^{\zeta_n})$, then for larger enough ζ_n, $\mathbb{E}X_{\zeta_n} - \rho^{\zeta_n} \ge \tilde{\mathbb{E}}X_{\zeta_n} + \rho^{\zeta_n}$,
168   which implies $\mathbb{P}_n(A_n) \le \mathbb{P}_n(X_{\zeta_n} \le \mathbb{E}X_{\zeta_n} - \rho^{\zeta_n})$. By Chebyshev's inequality,

$$\mathbb{P}_n(A_n) \le \mathbb{P}_n\left(\frac{X_{\zeta_n} - \mathbb{E}X_{\zeta_n}}{\sqrt{\mathrm{Var}X_{\zeta_n}}} \le \frac{-\rho^{\zeta_n}}{\sqrt{\mathrm{Var}X_{\zeta_n}}}\right) \le \frac{\mathrm{Var}X_{\zeta_n}}{\rho^{2\zeta_n}} \to 0, \quad \text{as } n \to \infty. \qquad (2)$$

169   By (1) and (2), we have shown that $\mathbb{P}_n$ and $\tilde{\mathbb{P}}_n$ are asymptotically orthogonal.

170   Now we show that Theorem 2.1 can provide us consistent estimators for a and b. First of all, we have
171   a consistent estimator $\hat{\alpha}_n$ for α by simply counting the number of hyperedges. If we can prove that
172   β can be consistently estimated by $\hat{\beta}_n = (2\zeta_n X_{\zeta_n} - \hat{\alpha}_n^{\zeta_n})^{\frac{1}{\zeta_n}}$, then $\hat{a}_n = \frac{1}{d-1}(\hat{\alpha}_n + (2^{d-1}-1)\hat{\beta}_n)$
173   and $\hat{b}_n = \frac{1}{d-1}(\hat{\alpha}_n - \hat{\beta}_n)$ are consistent estimators for a and b, respectively.

174   Take $\rho \in (\sqrt{\alpha}, \beta)$, by Chebyshev's inequality,

$$\begin{aligned}
\mathbb{P}_n(2\zeta_n X_{\zeta_n} - \alpha^{\zeta_n} \ge \beta^{\zeta_n} - \rho^{\zeta_n}) &= \mathbb{P}_n\left(\frac{X_{\zeta_n} - \frac{\alpha^{\zeta_n} + \beta^{\zeta_n}}{2\zeta_n}}{\sqrt{\mathrm{Var}X_{\zeta_n}}} \ge \frac{-\frac{\rho^{\zeta_n}}{2\zeta_n}}{\sqrt{\mathrm{Var}X_{\zeta_n}}}\right) \\
&\ge 1 - \left(\frac{2\zeta_n\sqrt{\mathrm{Var}X_{\zeta_n}}}{\rho^{\zeta_n}}\right)^2 \to 1, \quad \text{as } \zeta_n \to \infty.
\end{aligned} \qquad (3)$$

175

$$\begin{aligned}
\mathbb{P}_n(2\zeta_n X_{\zeta_n} - \alpha^{\zeta_n} \le \beta^{\zeta_n} + \rho^{\zeta_n}) &= \mathbb{P}_n\left(\frac{X_{\zeta_n} - \frac{\alpha^{\zeta_n} + \beta^{\zeta_n}}{2\zeta_n}}{\sqrt{\mathrm{Var}X_{\zeta_n}}} \le \frac{\frac{\rho^{\zeta_n}}{2\zeta_n}}{\sqrt{\mathrm{Var}X_{\zeta_n}}}\right) \\
&\ge 1 - \left(\frac{2\zeta_n\sqrt{\mathrm{Var}X_{\zeta_n}}}{\rho^{\zeta_n}}\right)^2 \to 1, \quad \text{as } \zeta_n \to \infty.
\end{aligned} \qquad (4)$$

176   Thus, $2\zeta_n X_{\zeta_n} - \alpha^{\zeta_n} \in [\beta^{\zeta_n} - \rho^{\zeta_n}, \beta^{\zeta_n} + \rho^{\zeta_n}]$ a.a.s. Since $\rho^{\zeta_n} = o(\beta^{\zeta_n})$ as $\zeta_n \to \infty$, we have
177   $2\zeta_n X_{\zeta_n} - \alpha^{\zeta_n} = (1 + o(1))\beta^{\zeta_n}$ a.a.s. Since $\hat{\alpha}_n^{\zeta_n} \to \alpha^{\zeta_n}$ as $\zeta_n \to \infty$, we have $2\zeta_n X_{\zeta_n} - \hat{\alpha}_n^{\zeta_n} = $
178   $(1 + o(1))\beta^{\zeta_n}$ a.a.s. Therefore, $\hat{\beta}_n = (2\zeta_n X_{\zeta_n} - \hat{\alpha}_n^{\zeta_n})^{\frac{1}{\zeta_n}} \to \beta$ as $\zeta_n \to \infty$. $\qquad \square$

3   Non-reconstruction of the community structures

180   To prove Theorem 1.2, we use a multi-type Galton-Watson hypertree (proposed in [26]) that is
181   coupled with $\mathcal{H}_d(n, p_n, q_n)$. Intuitively speaking, a neighborhood of a vertex in $\mathcal{H}_d(n, p_n, q_n)$ looks

like the hypertree with high probability. We take advantage of the threshold of broadcasting on the hypertree to show a threshold for community detection on the HSBM.

Let T be an infinite rooted hypertree with root ρ constructed as follows: Generate a root ρ with spin $\tau_\rho \in \{+1, -1\}$ and then generate $\mathrm{Pois}(\alpha)$ many hyperedges that only intersects at ρ. For $0 \le s \le d-1$, a hyperedge is called *type s* if there are s many children with spin τ_ρ and $d-1-s$ many children with spin $-\tau_\rho$ in the hyperedge. Hyperedges of type $d-1$ are generated with probability $\frac{(d-1)a}{\alpha 2^{d-1}}$ and of type s with probability $\frac{(d-1)b\binom{d-1}{s}}{\alpha 2^{d-1}}$ for $0 \le s \le d-2$. It is easy to check that $\frac{(d-1)a}{\alpha 2^{d-1}} + \sum_{s=0}^{d-2} \frac{(d-1)b\binom{d-1}{s}}{\alpha 2^{d-1}} = 1$. We generate hyperedges of different types i.i.d. by Poisson distribution. For each hyperedge of type s, in the first generation, we uniformly and randomly pick s vertices with spin τ_ρ and the rest of the $d-1-s$ vertices with spin $-\tau_\rho$. The subsequent generations are generated by induction. The generated random hypertree, denoted by (T, ρ, τ), is called a *multi-type Galton-Watson hypertree*. Figure 2 shows an example of a multi-type Galton-Watson hypertree where $d = 3$.

Figure 2: A multi-type Galton-Watson hypertree with $d = 3$, where vertices with spin $+$ are in blue and with spin $-$ are in red.

The broadcasting problem on (T, ρ, τ) is whether the spin τ_ρ could be deduced from the spins at generation l of the hypertree, where l is sufficiently large. Such a problem on general infinite trees was initially proposed by Kesten and Stigum in 1966 [19], although they used somewhat different terminologies. This problem was solved by Blecher et al. [3] and Evans et al. [10].

Let T_l be the vertices of generations no more than l in T, ∂T_l the vertices of generation l in T, then we have (refer to the Appendix for the proof):

Theorem 3.1. *Suppose (T, ρ, τ) is a multi-type Galton-Watson hypertree where the offspring distribution has mean $\alpha > 1$, if $\beta^2 < \alpha$, then*

$$\lim_{l \to \infty} \mathbb{P}(\tau_\rho = +1 | \tau_{\partial T_l}) = \frac{1}{2} \quad a.s. \tag{5}$$

where $\tau_{\partial T_l} = \{\tau_v | v \in \partial T_l\}$.

Let $(H, \rho, \sigma)_l$ be the rooted hypergraph (H, ρ, σ) truncated at generation l from ρ, $(T, \rho, \tau)_l$ the rooted hypertree (T, ρ, τ) truncated at generation l from ρ, then for sufficiently large n, $l = c \log(n)$ with $c \log(\alpha) < \frac{1}{4}$ and c is a constant, there exists a coupling between (H, ρ, σ) and (T, ρ, τ) such that $(H, \rho, \sigma)_l \equiv (T, \rho, \tau)_l$ with probability at least $1 - n^{-1/5}$ (see Theorem 5.2 in [26]). That is, a neighborhood in H looks like a broadcasting process on a multi-type Galton-Watson hypertree T.

The statement of Theorem 1.2 is equivalent to $\mathbb{E}(\sigma_\rho | H, \sigma_v) \to 0$, also equivalent to $\mathrm{Var}(\sigma_\rho | H, \sigma_v) \to 1$. In order to prove Theorem 1.2, we can consider the variation $\mathrm{Var}(\sigma_\rho | H, \sigma_{\partial H_l})$, which asymptotically almost surely is equal to $\mathrm{Var}(\tau_\rho | T, \tau_{\partial T_l})$. By the property of monotonicity of variation, we can add conditions on the spins σ_v and $\sigma_{\partial H_l}$, which can make the reconstruction easier. Then we wish to remove the condition σ_v and such action will not lose much information, i.e., $\sigma_{\partial H_l}$ gives much more information in the process. To fill the gap that once we have conditioned on $\sigma_{\partial H_l}$, we can remove the condition on σ_v, the following lemma is required.

Lemma 3.2. *Let V_1, V_2, V_3 be a random partition of the vertex set $\mathcal{V}(H)$ such that V_2 separates V_1 and V_3. If $|V_1 \cup V_2| = o(\sqrt{n})$ for a.a.e H, then*

$$\mathbb{P}(\sigma_{V_1} | H, \sigma_{V_2}) = (1 + o(1))\mathbb{P}(\sigma_{V_1} | H, \sigma_{V_2 \cup V_3}) \tag{6}$$

218 *for a.a.e. H and σ.*

219 Now we can establish the second main result, Theorem 1.2.

220 *Proof of Theorem 1.2.* By the property of the monotonicity of conditional variation, for $v \notin H_l$, we
221 have

$$\mathrm{Var}(\sigma_\rho | H, \sigma_v, \sigma_{\partial H_l}) \leq \mathrm{Var}(\sigma_\rho | H, \sigma_v). \tag{7}$$

222 By Lemma 3.2, σ_ρ and σ_v are a.a.s. conditionally independent given $\sigma_{\partial H_l}$ and H, which
223 means $\mathrm{Var}(\sigma_\rho | H, \sigma_v, \sigma_{\partial H_l}) \to \mathrm{Var}(\sigma_\rho | H, \sigma_{\partial H_l})$. By Theorem 5.2 in [26], $\mathrm{Var}(\sigma_\rho | H, \sigma_{\partial H_l}) \to$
224 $\mathrm{Var}(\tau_\rho | T, \tau_{\partial T_l})$. By Theorem 3.1, $\mathrm{Var}(\tau_\rho | T, \tau_{\partial T_l}) \to 1$ a.a.s. Therefore, $\mathrm{Var}(\sigma_\rho | H, \sigma_v) \to 1$
225 a.a.s. $\qquad\square$

226 In the rest of this section, we will show our last main result, Theorem 1.3. The second half of Theorem
227 1.3 can be derived from its first half as follows: If $\beta^2 < \alpha$, suppose $\hat{a}$ and $\hat{b}$ are estimators for a and b
228 which converge in probability, we claim their limits depend on $a + (2^{d-1} - 1)b$ only. To verify this,
229 let A, B be another choice of model parameters with $(d-1)(A-B)^2 < 2^{d-1}(A + (2^{d-1} - 1)B)$
230 and $A + (2^{d-1} - 1)B = a + (2^{d-1} - 1)b$. Let $\mathbb{P}'_n$ be the probability with respect to the model
231 $\mathcal{H}_d(n, \frac{A}{\binom{n}{d-1}}, \frac{B}{\binom{n}{d-1}})$, and suppose

$$\hat{a} \to a^* \quad \mathbb{P}_n - a.a.s, \quad \hat{a} \to A^* \quad \mathbb{P}'_n - a.a.s.$$

232 For any $\epsilon > 0$, let A_n be the event that $|\hat{a} - a^*| > \epsilon$, then $\mathbb{P}_n(A_n) \to 0$. By the first half of Theorem
233 1.3, $\tilde{\mathbb{P}}_n(A_n) \to 0$. Since $A + (2^{d-1} - 1)B = a + (2^{d-1} - 1)b$, using the first half of Theorem 1.3
234 again, we have $\mathbb{P}'_n(A_n) \to 0$, which implies $A^* = a^*$. Therefore, $\hat{a}$ converges to the same limit
235 under $\mathbb{P}_n$ and $\mathbb{P}'_n$, i.e., $\hat{a}$ is not a consistent estimator for a (same argument for b).

236 The first half of Theorem 1.3 is a bit difficult to prove. Here, we give some outline of how to establish
237 it, and the lengthy proof is put in the Appendix. For our purpose, we will use the small subgraph
238 conditioning method, which was initially proposed by Robinson et al. [29, 30] and then applied by
239 Janson [18] to prove contiguity. The follow theorem from [35] is a crucial tool to show the contiguity
240 between $\mathcal{H}_d(n, p_n, q_n)$ and $\mathcal{H}_d(n, \frac{p_n + (2^{d-1} - 1)q_n}{2^{d-1}})$ when $\beta^2 < \alpha$.

241 **Theorem 3.3** (Theorem 4.1 in [35]). *Let $\mathbb{P}_n$ and $\tilde{\mathbb{P}}_n$ be two fixed sequences of probability measures*
242 *on a common measurable space, $Y_n = \frac{\mathbb{P}_n}{\tilde{\mathbb{P}}_n}$ the density of $\mathbb{P}_n$ with respect to $\tilde{\mathbb{P}}_n$. For $i \geq 1$, let $\lambda_i > 0$,*
243 $\delta_i \geq -1$, *for each n, suppose random variables X_{in} satisfy*

244 *(C1) $X_{in} \xrightarrow{d} W_i$ as $n \to \infty$ jointly for all i under $\tilde{\mathbb{P}}_n$, where $W_i \sim Pois(\lambda_i)$ are independent Poisson*
245 *variables;*

246 *(C2) For every non-negative integers $s_1, \cdots, s_k$,*

$$\tilde{\mathbb{E}}(Y_n[X_{1n}]_{s_1} \cdots [X_{kn}]_{s_k}) / \tilde{\mathbb{E}}Y_n \to \prod_{i=1}^{k} (\lambda_i(1 + \delta_i))^{s_i}.$$

247 *(C3) $\sum_{i \geq 1} \lambda_i \delta_i^2 < \infty$;*

248 *(C4) $\tilde{\mathbb{E}}Y_n^2 / (\tilde{\mathbb{E}}Y_n)^2 \to \exp(\sum_{i \geq 1} \lambda_i \delta_i^2)$.*

249 *Then, $\tilde{\mathbb{P}}_n$ and $\mathbb{P}_n$ are contiguous.*

250 In order to apply the theorem above, we will take Y_n to be the likelihood ratio of the adjacency
251 tensor A of H, and X_{in} to be the number of i-loose cycles in H. To shorten notation, we adopt
252 $i_1 * i_d$ to represent the ordering $i_1 i_2 \cdots i_d$. $A_{i_1 * i_d} := A_{i_1 i_2 \cdots i_d}$. $I[\sigma_{i_1} * \sigma_{i_d}] := I[\sigma_{i_1} = \cdots = \sigma_{i_d}]$,
253 which is 1 if $\sigma_{i_1} = \cdots = \sigma_{i_d}$, and 0 otherwise. $\varrho(s, t) = \{(i_1, \cdots, i_s) | 1 \leq i_1 \leq \cdots \leq i_s \leq t\}$.
254 $\hat{d} := \frac{a + (2^{d-1} - 1)b}{2^{d-1}}$. $p_0 := \frac{\hat{d}}{\binom{n}{d-1}}$, $q_0 := 1 - p_0$. Then, for $H \sim \mathcal{H}_d(n, p_n, q_n)$, its hyperedge
255 probabilities $p_{i_1 * i_d}(\sigma)$ and $q_{i_1 * i_d}(\sigma)$ can be given by

$$p_{i_1 * i_d}(\sigma) = \mathbb{P}(A_{i_1 * i_d} = 1 | \sigma) = p_n^{I[\sigma_{i_1} * \sigma_{i_d}]} q_n^{1 - I[\sigma_{i_1} * \sigma_{i_d}]},$$
$$q_{i_1 * i_d}(\sigma) = \mathbb{P}(A_{i_1 * i_d} = 0 | \sigma) = 1 - p_{i_1 * i_d}(\sigma).$$

For $H \sim \mathcal{H}_d(n, p_0)$, its hyperedge probabilities can be given by $\mathbb{P}(\{i_1 * i_d\}) = p_0^{A_{i_1 * i_d}} q_0^{1 - A_{i_1 * i_d}}$.

Therefore, the likelihood ratio $Y_n = \frac{\mathbb{P}_n(A)}{\mathbb{P}_n(A)}$ of the adjacency tensor A can be written as

$$Y_n = 2^{-n} \sum_{\sigma \in \{\pm 1\}^n} \prod_{i \in \varrho(d,n)} \left(\frac{p_{i_1 * i_d}(\sigma)}{p_0} \right)^{A_{i_1 * i_d}} \left(\frac{q_{i_1 * i_d}(\sigma)}{q_0} \right)^{1 - A_{i_1 * i_d}}. \tag{8}$$

Obviously, we have $\tilde{\mathbb{E}} Y_n = 1$. The condition (C1) is easy to verify as we can see from Theorem 2.1, which also implies that λ_i can be chosen as $\frac{\alpha^i}{2i}$. Then, we need to estimate the asymptotics of $\tilde{\mathbb{E}}(Y_n[X_{1n}]_{s_1} \cdots [X_{kn}]_{s_k})$ and $\tilde{\mathbb{E}} Y_n^2$, where the calculation of first moment is somewhat similar to calculations in the proof of Theorem 2.1. The following lemma gives an estimation for the second moment of Y_n.

Lemma 3.4.

$$\begin{aligned} \tilde{\mathbb{E}} Y_n^2 = (1 + o(1)) \exp\{ &\frac{1}{\hat{d} \binom{n}{d-1}} (\binom{n}{d}(b - \hat{d})^2 + (a - b)^2 \sum_{i \in \varrho(d,n)} I[\sigma_{i_1} * \sigma_{i_d}] I[\tau_{i_1} * \tau_{i_d}] \\ &+ (a - b)(b - \hat{d}) \sum_{i \in \varrho(d,n)} (I[\sigma_{i_1} * \sigma_{i_d}] + I[\tau_{i_1} * \tau_{i_d}])) \}. \end{aligned} \tag{9}$$

After verifying all the conditions of Theorem 3.3 (see the Appendix) the first half of Theorem 1.3 follows directly.

4 Conclusion

Community detection is of great interest in many fields such as network analysis, statistics and computer vision. Hypergraphs have been widely used to model higher-order relationships among data. The SBM (graph-based) model is popular in community detection but only directly models pair-wise interactions. Its hypergraph version, HSBM, likewise serves as a benchmark for clustering algorithms on higher order interaction (hypergraph) data.

This paper provides theoretical analyses on the community detection thresholds in the sparse HSBM. Specifically, we address a previous conjecture that there exists a sharp threshold on the model parameters for community detection to be possible. We proved that above the threshold, it is possible to asymptotically almost surely construct a bi-partition of the hypergraph positively correlated with the true bi-partition. Moreover, below the threshold, we show that community detection is information-theoretically impossible. Importantly, we also provide consistent estimators for the model parameters, when the detection is possible.

Our estimators require the counting of the number of loose cycles in the hypergraph. To our best knowledge, there is no efficient algorithm to count the number of loose cycles in hypergraphs in general. Therefore, from the algorithmic side, it might be more practical to count the number of non-backtracking/self-avoiding walks of the same length [26, 33], which can be computed by matrix multiplication efficiently. Nevertheless, from the theoretical side, confirming the positive side of the threshold conjecture by analysing the number of loose cycles has not been done before. Moreover, providing more practical estimators (or examining whether one can estimate the number of loose cycles sufficiently accurate to still use the estimators of model parameters we provide, is a worthy topic of future research.

Note that the non-uniform hypergraphs can be viewed as a 'superposition' of a collection of uniform hypergraphs. Thus it may be possible to generalise our proofs to cover non-uniform hypergraphs in future work. Considering other variants of the hypergraph community detection problem, for instances, multi-community structures, extremely sparse scenario ($p_n, q_n \ll 1/n^{d-1}$), moderate sparse scenario ($p_n, q_n = \mathcal{O}(\log(n)/n^{d-1})$), dense scenario ($p_n, q_n \gg 1/n^{d-1}$), are future research directions that would complete the work presented here.

References

[1] Emmanuel Abbe, Enric Boix-Adsera, Peter Ralli, and Colin Sandon. Graph powering and spectral robustness. *SIAM Journal on Mathematics of Data Science*, 2(1):132–157, 2020.

[2] Maria Chiara Angelini, Francesco Caltagirone, Florent Krzakala, and Lenka Zdeborová. Spectral detection on sparse hypergraphs. In *2015 53rd Annual Allerton Conference on Communication, Control, and Computing (Allerton)*, pages 66–73. IEEE, 2015.

[3] Pavel M Bleher, Jean Ruiz, and Valentin A Zagrebnov. On the purity of the limiting gibbs state for the ising model on the bethe lattice. *Journal of Statistical Physics*, 79(1):473–482, 1995.

[4] Béla Bollobás. Random graphs. In *Modern graph theory*, pages 215–252. Springer, 1998.

[5] Béla Bollobás, Svante Janson, and Oliver Riordan. The phase transition in inhomogeneous random graphs. *Random Structures & Algorithms*, 31(1):3–122, 2007.

[6] Charles Bordenave, Marc Lelarge, and Laurent Massoulié. Non-backtracking spectrum of random graphs: community detection and non-regular ramanujan graphs. In *2015 IEEE 56th Annual Symposium on Foundations of Computer Science*, pages 1347–1357. IEEE, 2015.

[7] Aurelien Decelle, Florent Krzakala, Cristopher Moore, and Lenka Zdeborová. Asymptotic analysis of the stochastic block model for modular networks and its algorithmic applications. *Physical Review E*, 84(6):066106, 2011.

[8] Paul Erdös, Alfréd Rényi, et al. On the evolution of random graphs. *Publ. Math. Inst. Hung. Acad. Sci*, 5(1):17–60, 1960.

[9] Ernesto Estrada and Juan A Rodriguez-Velazquez. Complex networks as hypergraphs. *arXiv preprint physics/0505137*, 2005.

[10] William Evans, Claire Kenyon, Yuval Peres, and Leonard J Schulman. Broadcasting on trees and the ising model. *Annals of Applied Probability*, pages 410–433, 2000.

[11] Santo Fortunato. Community detection in graphs. *Physics reports*, 486(3-5):75–174, 2010.

[12] Alan Frieze and Michał Karoński. *Introduction to random graphs*. Cambridge University Press, 2016.

[13] Debarghya Ghoshdastidar and Ambedkar Dukkipati. Consistency of spectral partitioning of uniform hypergraphs under planted partition model. *Advances in Neural Information Processing Systems*, 27, 2014.

[14] Debarghya Ghoshdastidar and Ambedkar Dukkipati. Consistency of spectral hypergraph partitioning under planted partition model. *The Annals of Statistics*, 45(1):289–315, 2017.

[15] Anna Goldenberg, Alice X Zheng, Stephen E Fienberg, Edoardo M Airoldi, et al. A survey of statistical network models. *Foundations and Trends® in Machine Learning*, 2(2):129–233, 2010.

[16] Christopher J Hillar and Lek-Heng Lim. Most tensor problems are np-hard. *Journal of the ACM (JACM)*, 60(6):1–39, 2013.

[17] Paul W Holland, Kathryn Blackmond Laskey, and Samuel Leinhardt. Stochastic blockmodels: First steps. *Social networks*, 5(2):109–137, 1983.

[18] Svante Janson. Random regular graphs: asymptotic distributions and contiguity. *Combinatorics, Probability and Computing*, 4(4):369–405, 1995.

[19] Harry Kesten and Bernt P Stigum. A limit theorem for multidimensional galton-watson processes. *The Annals of Mathematical Statistics*, 37(5):1211–1223, 1966.

[20] Chiheon Kim, Afonso S Bandeira, and Michel X Goemans. Stochastic block model for hypergraphs: Statistical limits and a semidefinite programming approach. *arXiv preprint arXiv:1807.02884*, 2018.

[21] Jure Leskovec, Kevin J Lang, Anirban Dasgupta, and Michael W Mahoney. Statistical properties of community structure in large social and information networks. In *Proceedings of the 17th international conference on World Wide Web*, pages 695–704, 2008.

[22] Laurent Massoulié. Community detection thresholds and the weak ramanujan property. In *Proceedings of the forty-sixth annual ACM symposium on Theory of computing*, pages 694–703, 2014.

[23] Elchanan Mossel, Joe Neeman, and Allan Sly. Reconstruction and estimation in the planted partition model. *Probability Theory and Related Fields*, 162(3):431–461, 2015.

[24] Elchanan Mossel, Joe Neeman, and Allan Sly. A proof of the block model threshold conjecture. *Combinatorica*, 38(3):665–708, 2018.

[25] Xavier Ouvrard, Jean-Marie Le Goff, and Stéphane Marchand-Maillet. Networks of collaborations: Hypergraph modeling and visualisation. *arXiv preprint arXiv:1707.00115*, 2017.

[26] Soumik Pal and Yizhe Zhu. Community detection in the sparse hypergraph stochastic block model. *Random Structures & Algorithms*, 59(3):407–463, 2021.

[27] Pulak Purkait, Tat-Jun Chin, Alireza Sadri, and David Suter. Clustering with hypergraphs: the case for large hyperedges. *IEEE transactions on pattern analysis and machine intelligence*, 39(9):1697–1711, 2016.

[28] José J Ramasco, Sergey N Dorogovtsev, and Romualdo Pastor-Satorras. Self-organization of collaboration networks. *Physical review E*, 70(3):036106, 2004.

[29] Robert W. Robinson and Nicholas C. Wormald. Almost all cubic graphs are hamiltonian. *Random Structures & Algorithms*, 3(2):117–125, 1992.

[30] Robert W. Robinson and Nicholas C. Wormald. Almost all regular graphs are hamiltonian. *Random Structures & Algorithms*, 5(2):363–374, 1994.

[31] Jianbo Shi and Jitendra Malik. Normalized cuts and image segmentation. *IEEE Transactions on pattern analysis and machine intelligence*, 22(8):888–905, 2000.

[32] Ludovic Stephan and Laurent Massoulié. Robustness of spectral methods for community detection. In *Conference on Learning Theory*, pages 2831–2860. PMLR, 2019.

[33] Ludovic Stephan and Yizhe Zhu. Sparse random hypergraphs: Non-backtracking spectra and community detection. *arXiv preprint arXiv:2203.07346*, 2022.

[34] Ze Tian, TaeHyun Hwang, and Rui Kuang. A hypergraph-based learning algorithm for classifying gene expression and arraycgh data with prior knowledge. *Bioinformatics*, 25(21):2831–2838, 2009.

[35] Nicholas C Wormald et al. Models of random regular graphs. *London Mathematical Society Lecture Note Series*, pages 239–298, 1999.

[36] Mingao Yuan, Ruiqi Liu, Yang Feng, and Zuofeng Shang. Testing community structure for hypergraphs. *The Annals of Statistics*, 50(1):147–169, 2022.

[37] Yunpeng Zhao, Elizaveta Levina, and Ji Zhu. Community extraction for social networks. *Proceedings of the National Academy of Sciences*, 108(18):7321–7326, 2011.

[38] Dengyong Zhou, Jiayuan Huang, and Bernhard Schölkopf. Learning with hypergraphs: Clustering, classification, and embedding. *Advances in neural information processing systems*, 19, 2006.