Know Your Action Set: Learning Action Relations for Reinforcement Learning

Abstract

Intelligent agents can solve tasks in a variety of ways depending on the action set at their disposal. For instance, while using a toolkit for repair, the choice of tool (the action) closely depends on what other tools are available. Yet, such dependence on other available actions is ignored in conventional reinforcement learning (RL) since it assumes a fixed action set. In this work, we posit that learning the interdependence between actions is crucial for RL agents acting under a varying action set. To this end, we propose a novel policy architecture that consists of an input graph composed of available actions and a graph attention network to learn the action interdependence. We demonstrate that our architecture makes action decisions by correctly attending to the relevant actions in both value-based and policy-based RL. Consequently, it consistently outperforms non-relational architectures on applications where the action space can vary, such as recommender systems and physical reasoning with tools and skills.

1   Introduction

Imagine you want to hang a picture on the wall. You may start by placing a nail on the wall and then use a hammer to nail it in. However, if you do not have access to a hammer, you would not use the nail. Instead, you would try alternative approaches such as using a hook and adhesive-strips, or a screw and a drill (Figure 1). In general, we solve tasks by choosing actions that interact with each other to achieve a desired outcome in the environment. Therefore, the best action decision depends not only on the environment, but also on what other actions are available to use.

In this work, we address the setting of varying action space in sequential decision-making. Typically reinforcement learning (RL) assumes a fixed action space, but recent work has explored variations in action space when adding or removing actions (Boutilier et al., 2018; Chandak et al., 2020a;b) or for generalization to unseen actions (Jain et al., 2020). These assume that the given actions can be treated independently in decision-making. But this assumption often does not hold. As the picture hanging example illustrates, the optimality of choosing the nail is dependent on the availability of a hammer. Therefore, our goal is to address this problem of learning the interdependence of actions.

Addressing this problem is important for many varying action space applications. These include recommender systems where articles to recommend vary every day and physical reasoning where decision-making must be robust to any given set of tools, objects, or skills. In this paper, we benchmark three such scenarios where learning action interdependence is crucial for solving the task optimally. These are (i) shortcut-actions in grid navigation, whose presence shortens the path to the goal, (ii) co-dependent actions in tool reasoning, where tools need other tools to be useful, and (iii) list-actions or slate-actions (Sunehag et al., 2015) in simulated and real-data recommender systems, where the user satisfaction is a consequence of the collective effect of the recommended list.

There are three key challenges in learning action interdependence for RL with varying action space. First, since the overall actions are not known in advance, the policy framework must be flexible to work with action representations. Second, the action space is now an additional variable component just like state observations in RL. Therefore, the policy framework must incorporate a variably sized set of action representations as part of the input. Finally, an agent's decision for each action's utility (e.g. Q-value or probability) should explicitly model its relationship with other available actions.

Figure 1: Picture hanging task with different tool sets. Intelligent agents adapt task solutions based on how the given actions relate to each other. (Left) Since hammer is available, the agent starts by choosing the nail to place on the wall. (Right) The nail is no longer a useful tool without a hammer, so using an adhesive tape is better since a hook is provided. The relationship of nail & hammer and tape & hook (shown with bold lines) is crucial for these decisions. We show a GAT can learn these.

To address these challenges, we propose a novel policy architecture: AGILE, Action Graph for Interdependence Learning. AGILE builds on the utility network proposed in Jain et al. (2020) to incorporate action representations. Its key component is a graph attention network (GAT) (Veličković et al., 2017) over a fully connected graph of actions. This serves two objectives: summarizing the action set input and computing the action utility with relational information of other actions.

Our primary contribution is introducing the problem of learning action interdependence for RL with variable action space. We demonstrate our proposed policy architecture, AGILE, learns meaningful action relations. This enables it to improve optimality in varying action space tasks such as simulated and real-world recommender systems, and reasoning with skills and tools.

2 RELATED WORK

2.1 STOCHASTIC ACTION SETS

In recent work, Boutilier et al. (2018) provide the theoretical foundations of MDPs with Stochastic Action Sets (SAS-MDPs), where actions are sampled from a known base set of actions. They propose a solution with Q-learning and Chandak et al. (2020a) extend it to policy gradients. An instance of SAS-MDPs is when certain actions become invalid, e.g. in games, they are masked out from the output action probability distribution (Huang & Ontañón, 2020; Ye et al., 2020; Kanervisto et al., 2020). However, the assumption of knowing the finite base action set limits the practical applicability of SAS-MDPs. For example, recommender agents often receive unseen items to recommend and a robotic agent does not know beforehand what tools it would encounter in the future. We work with action representations to alleviate this limitation. Furthermore, in SAS-MDPs the action set can vary at any timestep of an episode. Thus, the learned policy will only be optimal on average over all the possible action sets (Qin et al., 2020). Whereas in our setting, the action sets only change at the beginning of a task instance and stays constant over the episode. This is a more practical setup and raises the challenging problem of solving a task optimally with any given action space.

2.2 ACTION REPRESENTATIONS

In discrete action RL, action representations have enabled learning in large action spaces (Dulac-Arnold et al., 2015; Chandak et al., 2019), transfer learning to a different action space (Chen et al., 2019b), and efficient exploration by exploiting the shared structure among actions (He et al., 2015; Tennenholtz & Mannor, 2019; Kim et al., 2019). Recently, Chandak et al. (2020b) use them to accelerate adaptation when new actions are added to an existing action set. In contrast, our setting requires learning in a constantly varying action space where actions can be added, removed, or completely replaced in an episode. Closely related to our work, Jain et al. (2020) assume a similar setting of varying action space while training to generalize to unseen actions. Following their motivation, we use action representations to avoid making assumptions on the base action set. However, their policy treats each action independently, which we demonstrate leads to a suboptimal performance.

2.3 List-wise Action Space

In listwise RL (or slate RL), the action space is combinatorial in list size. Commonly it has applications in recommendation systems (Sunehag et al., 2015; Zhao et al., 2017; 2018; Ie et al., 2019b; Gong et al., 2019; Liu et al., 2021; Jiang et al., 2018; Song et al., 2020). In recent work, Chen et al. (2019a) proposed Cascaded DQNs (CDQN) framework which learns a Q-network for every index in the list and train them all with a shared reward. For our experiments on listwise RL, we utilize CDQN as the algorithm and show how it can be used with AGILE as the policy framework.

2.4 Relational Reinforcement Learning

Graph neural networks (Battaglia et al., 2018) have been explored in RL tasks with a rich relational structure, such as morphological control (Wang et al., 2018; Sanchez-Gonzalez et al., 2018; Pathak et al., 2019), multi-agent RL (Tacchetti et al., 2019), physical construction (Hamrick et al., 2018), and structured perception in games like StarCraft (Zambaldi et al., 2018). In this paper, we propose that the set of actions possess a relational structure which enables the actions to interact and solve tasks in the environment. Therefore, we leverage graph attention networks (Veličković et al., 2017) to learn these action relations and show that it can represent meaningful action interactions.

3 Problem Formulation

A hallmark of intelligence is the ability to be robust in an ever changing environment. To this end, we consider the setting of RL with a varying action space, where an agent receives a different action set in every task instance. Our key problem is to learn the interdependence of actions so the agent can act optimally with any given action set. Figure 1 illustrates that for a robot with the task of hanging a picture on the wall, starting with a nail is optimal only if it can access a hammer subsequently.

3.1 Reinforcement Learning with Varying Action Space

We consider episodic Markov Decision Processes (MDPs) with discrete action spaces, supplemented with action representations. The MDP is defined by a tuple $\{\mathcal{S}, \mathbb{A}, \mathcal{T}, \mathcal{R}, \gamma\}$ of states, actions, transition probability, reward function, and discount factor, respectively. The base set of actions $\mathbb{A}$ can be countably infinite. To support infinite base actions, we use D-dimensional action representations $c_a \in \mathbb{R}^D$ to denote an action $a \in \mathbb{A}$. These can be image or text features of a recommendable item, or behavior characteristics of a tool, or simply be one-hot vectors for a known and finite action set.

In each instance of the MDP, a subset of actions $\mathcal{A} \subset \mathbb{A}$ is given to the agent, with associated representations $\mathcal{C}$. Thereafter, at each time step t in the episode, the agent receives a state observation $s_t \in \mathcal{S}$ from the environment and acts with $a_t \in \mathcal{A}$. This results in a state transition to s_{t+1} and a reward r_t. The objective of the agent is to learn a policy $\pi(a|s, \mathcal{A})$ that maximizes the expected discounted reward over evaluation episodes with potentially unseen actions, $\mathbb{E}_{\mathcal{A} \subset \mathbb{A}} \left[\sum \gamma^{t-1} r_t \right]$.

3.2 Challenges of Varying Action Space

1. **Using Action Representations**: The policy framework should be flexible to take a set of action representations $\mathcal{C}$ as input, and output corresponding Q-values or probability distribution for RL.

2. **Action Set as part of State:** When action set varies, the original state space $\mathcal{S}$ is not anymore Markovian. For example, the state of a robot hanging the picture is under-specified without knowing if its toolbox contains a hammer or not. The MDP can be preserved by reformulating the state space as $S' = \{s \circ \mathcal{C}_{\mathcal{A}} : s \in \mathcal{S}, \mathcal{A} \subset \mathbb{A}\}$ to include the representations $\mathcal{C}_{\mathcal{A}}$ associated with the available actions $\mathcal{A}$ (Boutilier et al., 2018). Thus, the policy framework must support the input of $s \circ \mathcal{C}_{\mathcal{A}}$, where $\mathcal{A}$ is a variably sized action set.

3. **Interdependence of Actions:** The optimal choice of an action $a_t \in \mathcal{A}$ is dependent on the action choices that would be available in the future steps of the episode, $a_{t'} \in \mathcal{A}$. Recalling Figure 1, a nail should only be picked initially from the toolbox if a hammer is accessible later. Thus, we must explicitly model the relationships between the characteristics of the current action c_{a_t} and the possible future actions $c_{a_i} \forall a_i \in \mathcal{A}$.

Figure 2: Given an action set, AGILE builds a complete action graph by joining action representations and state encoding. A graph attention network learns to attend to other actions that are relevant for each action in the current state. For example, the attention weight is expected to be high between the cannon and the fire because fire can activate the cannon. The output relational action features are better suited for decision-making via a utility network that computes the value or selection probability of the action. This utility network also takes as input the state and mean-pooled vector of the relational action features.

4 APPROACH

Our goal is to design a policy framework that is optimal for any given action space by addressing the challenges in Sec. 3.2. To work with action representations, we build on the utility network proposed by Jain et al. (2020). Our key insight is to use graph neural networks for both, summarizing the list of given action representations and learning inter-action interdependence.

4.1 AGILE: ACTION GRAPH FOR INTERDEPENDENCE LEARNING

We propose AGILE, a relational framework for learning action interdependence in RL with a varying action space. Given a list of action representations $\mathcal{C}$, AGILE builds a fully-connected action graph. This is processed by a graph attention network (GAT) (Veličković et al., 2017) which learns action relations. In a GAT, the attention weights are expected to be high for closely interdependent actions. The resultant nodes are pooled together to form a compact relational summary of the action space. This summary vector and each action's relational representation is used to compute an action's utility, which is used as a Q-value or as a probability logit for policy gradient methods (Figure 2).

Action Graph The input to our policy framework consists of the state s and a list $\mathcal{C} = [c_{a_0}, ..., c_{a_k}]$ of action representations for each action $a_i \in \mathcal{A}$. We build a fully connected action graph $\mathcal{G}$ with vertices corresponding to each action. If certain action relations are predefined in domain knowledge, we can remove other edges to ease training (Appendix B.1). The relations that we must infer depend on the current state. For instance, a screwdriver is relevant to a screw while repairing furniture, but a drill machine is more related when the screw is for a wall. Following this insight, we join state and action representations, $c'_{a_k} = (s, c_{a_k})$ to form the input nodes of the graph. In Sec. 6.3.2, we validate this insight by comparing against having graph nodes as action representations only.

Graph Attention Network: The action graph $\mathcal{G}$ is input to a GAT. Since the graph is fully-connected, we choose an attention-based graph architecture which can learn to focus on the most relevant actions in the given set. A similar insight was employed by Zambaldi et al. (2018) where the entities inferred from the visual observation are assumed to form a fully connected graph. To enable propagation of sufficient relational information between actions, we use two graph attention layers with an ELU activation in between (Clevert et al., 2015). We found a residual connection after the second GAT layer was crucial in experiments.

Action Set Summary: The output of the GAT is a list of relational action features $\mathcal{C}^R = \{c^R_{a_0}, ...c^R_{a_k}\}$ which contain the information about presence of other available actions and their relations. Therefore, we compute the action set summary in a compact form by mean-pooling the relational action features, $\bar{c}^R = \frac{1}{K} \sum_{k=1}^{K} c^R_{a_k}$.

Action Utility In order to use the relational action representations with RL, we follow the insight of utility network π_u from Jain et al. (2020). It takes the relational action representations, state, and action summary as input for each action and outputs a utility score reflecting how useful the action is for the current state and in relation to the other available actions. The utility score can be used as Q-value directly if the training algorithm is DQN, whereas it can be used as a logit fed into a softmax function to form a probability distribution over the available actions.

4.2 Training AGILE framework with Reinforcement Learning

The AGILE architecture can be trained with both policy gradient and value-based RL methods.

Policy Gradient (PPO) : For every action decision step, we take the output action utility and use a softmax over all available actions to get a probability distribution. We use PPO (Schulman et al., 2017) to train the policy. PPO requires a value function $V(s')$ as a baseline. We represent $s' = (s, \bar{c}^R)$ as the concatenation of the state encoding and the action set summary $\bar{c}^R$ inferred from the GAT. An important implementation detail to make the training faster and stable was to *not* share the GAT weights used for the actor $\pi(a|s', c_a^R)$ and the critic $V(s')$ networks.

Value-based RL (DQN) The output action utility can be directly treated as the $Q(s', a)$ value of the action at the current state with the given available action set $\mathcal{A}$. This can be trained using standard Q-learning Bellman backup.

Listwise RL (CDQN): To solve the combinatorial action space problem of listwise actions, we follow the Cascaded DQN (CDQN) framework of Chen et al. (2019a). The main challenge is that building the list all at once is not feasible due to the intractably large number of possible lists. Therefore, the key is to build the list incrementally, one action at a time. Thus, each list index can be treated as an individual non-combinatorial action which can be trained with RL. We replace the Q-network of CDQN with AGILE in order to accommodate a varying action space. We share the weights of the cascaded Q-networks. Algorithm 1 provides complete details on listwise AGILE.

5 Environments

We evaluate AGILE on three varying action set scenarios requiring learning action interdependence. (i) shortcut actions in goal-reaching, whose presence shortens the optimal path to the goal in a 2D Grid World, (ii) co-dependent actions in tool reasoning, which require other tools to activate their functionality, and (iii) list-actions in simulated and real-data recommender systems where the cumulative list affects the user preference. Figure 3 provides an overview of the tasks, base and varying action space, and an illustration of how action interdependence is important. More environment details such as tasks, action representations, and data collection are present in Appendix A.

5.1 Dig Lava Grid Navigation

We modify the grid world environment (Chevalier-Boisvert et al., 2018) where an agent navigates a 2D maze with two lava rivers to reach a goal. The agent always has access to 4 direction movements and a *turn-left* skill (Figure 5). However, two actions out of 4 special skills: *turn-right, step-forward, dig-orange-lava* and *dig-pink-lava*, are randomly sampled for the agent in every task instance. The agent can walk over lava for one timestep without dying, but it can remove the lava by using the matching *dig-lava* skill. Thus, when available, *dig-lava* skills can be used to build shortcut paths to the goal on the other end, and thus receive a higher reward. We use PPO to train all methods.

5.2 Chain REAction Tool Environment: CREATE

We use the CREATE environment (Jain et al., 2020) as a challenging environment with a large base action space and unseen actions for evaluation. The task is to sequentially select tools from a given toolbox and place them appropriately on the screen with the objective to push the red ball towards the green goal. We deal with the hybrid action space with an auxiliary network that takes the state and action set summary as input, following Jain et al. (2020). We simulate the need of action relation learning by associating each tool (e.g. cannon) with an activator tool (e.g. fire). A tool functions only if in contact with the right activator, otherwise the objects pass through it. Thus the tool choice must now consider the current environment state as well as whether its activators are available. We borrow the action representations from the prior work and add extra dimensions to accommodate one-hot vectors for the activator tools.

Figure 3: **Environment Setup.** (Left) In the grid world, the red agent must avoid orange and pink lava to reach the green goal. The dig lava skills, when available, enable shortcut paths to the goal. (Middle) In CREATE, tools are selected and placed sequentially with the aim to push the red ball to the green goal. General tools (cannon, fan) require activator tools (fire, electric) to start functioning. The choice of general tools depend on what activators are available and vice-versa. (Right) In simulated and real-data recommender systems, the agent selects a list of items. Lists with coherent categories and complementary sub-categories improve user satisfaction (e.g. click likelihood).

5.3 RECOMMENDER SYSTEMS

Recommender system is a natural application of the problem of varying action space where items to recommend change often. Specifically, action interdependence is apparent in the case of listwise actions. For example, a list of diverse ads is more likely to get a user click than ads from the same domain (Zhou et al., 2010). In this work, we experiment with the listwise metric of Complementary Product Recommendation (CPR) (Hao et al., 2020).

Complementary Product Recommendation (CPR): concerns with the scenario where user satisfaction with a recommended list increases if the list is coherent at a high-level but diverse at a low-level. Specifically, we consider each item to have a primary category, such as all of them are shirts, and a subcategory, such as color of the shirt. We define the CPR of a list as, $\frac{\text{Entropy of subcategory}}{\text{Entropy of category}}$. This encourages diversity in subcategories and similarity in the main category theme. We demonstrate the effect of maximizing CPR in different ways for the simulated and real-data experiments.

5.3.1 SIMULATED RECOMMENDER SYSTEM: RECSIM

We develop on the open-sourced simulator RecSim simulator ((Ie et al., 2019a)) which allows an agent to interact with simulated users by recommending a list of items. We have a base action set of 250 train items and 250 test items, and in each episode 20 items are given to the agent. It must recommend a list of size 6. We take user preference vector as the state (MDP) and ground truth action representations from the environment. We incorporate CPR by boosting up the probability of user clicking any item proportional to the CPR. This simulates one of the scenarios where user preference model is influenced by the entire list. An optimal agent should identify the most common category in the available action set and try to recommend most items in its list from category. This requires understanding the relation with the other candidate items from the same category. We train CDQN-based models to maximize the number of clicks in a user session.

5.3.2 REAL-DATA RECOMMENDER SYSTEM

We collect interaction data for one month for a listwise online campaign recommender system. Users are represented by attributes such as age, occupation, and localities. Items attributes are also given such as text features, image features, and reward points of campaigns. We simulate a representative RL environment by training a reward model on a set of 68,775 users and 57 items to estimate the click likelihood of the users(Appendix A.4). We augment the user reward model with the CPR reward to incentivize the agent to recommend high-CPR user-relevant items. We train a VAE (Kingma & Welling, 2013) to learn action representations, which are given to the RL agent as input. The test data consists of 82,445 users and 58 items, about 30 of which are shared with the training items. We report the test reward for models trained with CDQN algorithm.

Figure 4: We evaluate AGILE against baselines on both training (top) and unseen testing actions (bottom) during the course of training. The generalization to unseen actions is possible due to continuous action representations, described in Appendix A. The results are averaged over 5 random seeds and the seed variance is shown with shading. AGILE outperforms all baselines which either do no consider the overall action set as input or cannot deal with unseen actions.

6 EXPERIMENTS

Our experiments are designed to answer the following questions in the context of RL with varying action space: (1) How effective is AGILE compared to prior works that treat actions independently or assume a fixed action set? (2) How effective are AGILE's relational action representations for computing action set summary and action utilities? (3) Does the attention in AGILE capture meaningful action relations? (4) Is attention necessary in the graph network of AGILE? (5) Is learning state-dependent action relations necessary for solving general varying action space tasks?

6.1 EFFECTIVENESS OF AGILE IN VARYING ACTION SPACES

We evaluate AGILE against baselines from prior work in varying action space, that either assume a fixed action set or work without the knowledge of the other available actions. For ablations, we keep the action set summarizer, but replace the relational action features with raw action representations to compute action utility. The architectures of all methods are visually compared in Appendix C.1. All methods share the same training framework (PPO or CDQN) depending on the environment.

6.1.1 BASELINES

- **Mask-Output** (No representations, No input action set): Assuming a fixed action space in the output, q-values or policy probabilities are masked out for unavailable actions. It represents prior SAS-MDP works - Boutilier et al. (2018); Chandak et al. (2020a), Huang & Ontañón (2020).

- **Mask-Input-Output** (No representations): Augments the binary availability mask of given actions, 1s for available indices and 0s for unavailable, to the state input of *Mask-Output*.

- **Utility-Policy** (No input action set): Proposed by Jain et al. (2020), action representations are used independently for computing each action's utility, ignoring any interdependence.

- **Simple DQN** (No cascade, No input action set): For listwise RL specifically, we include the DQN baseline that simply selects top-K items, instead of reasoning about the overall list. Thus, it ignores both action interdependences: (i) on other available actions, (ii) on other items in the list.

6.1.2 ABLATIONS

- **Summary-LSTM**: A Bi-LSTM (Huang et al., 2015) encodes the list of action representations.

- **Summary-Deep Set**: A deep set architecture (Zaheer et al., 2017) with mean pooling is used to aggregate the input action list.

- **Summary-GAT**: AGILE where action set summary is used, but relational action feature output of GAT is not used for computing an action's utility. Instead, raw action representations are used. This delineates the importance of using action interdependence for decision-making.

Figure 5: Comparison against ablations.

6.1.3 RESULTS

Baselines: Figure 4 shows baseline results on train and test actions. Grid world has no unseen actions, so we report only train reward. **Grid World**: all methods learn to reach the goal with perfect success, but achieve different rewards due to the length of path. The methods which do not take action set as input, *Mask-Output* and *Utility Policy*, resort to the safe strategy of going around the lava rivers (Figure 6(b)). This is because to take a shortcut, the agent must enter the lava and then dig it. So before taking the *move-right* action into lava, the agent must know whether that *dig-lava* skill is available. **CREATE**: *Mask* baselines do not support generalization due to fixed action set assumption and train poorly as they do not exploit the structure in action representations. *Utility policy* outperforms the other baselines by virtue of ease of learning with action representations. Finally, AGILE clearly outperforms all the baselines demonstrating that relational knowledge of other available actions is crucial for an optimal policy. **RecSim** and **Real RecSys**: result trends are consistent with CREATE, but less pronounced for Real RecSys. Additionally, DQN is worse than CDQN-based architectures because the top-K greedy list action building ignores list interdependence.

Ablations: Figure 5 shows ablation results on test actions. **Grid World**: all ablations utilize the summary of action set as input, aggregated via different mechanisms. Thus, they can identify which *dig-lava* skills are available and guide each action decision accordingly. In such small action spaces with simple action relations, summary-ablations are on par with AGILE. This also holds true for **RecSim** and **Real RecSys**, where the information of the most common category is sufficient to select the same category's items to maximize CPR (e.g. Figure 6(c)). Therefore, we observe only $5 - 20\%$ gains of AGILE over the ablations. To test consistency of results, we further evaluate on two more RecSim tasks: (i) Direct CPR: task is still to maximize CPR, but agent receives additional CPR metric reward on top of click/no-click reward (Sec B.3, and (ii) Pairing environment: task is to recommend pairs of associated items based on predefined pairings. We reproduce the trend that AGILE $>=$ ablations. However, the difference is more pronounced $(30 - 50\%)$ in **CREATE**, where each action decision relies on different relations between various tools and activators. Learning a shared summary-vector that captures all the relevant diverse action relations is inefficient in such complex environments. For instance, in Figure 6(a), the decision of *Spring* requires relations with all other tools that spring can activate and one of *trampoline* requires relations with *Spring*. Thus, encoding such different relations for all tools into a single summary vector is limiting for the task.

A detailed comparison (C.1) and visualization (Figure 17) of all baselines, ablations and AGILE is present in Appendix, with details of hyperparameter-tuning (D.2,D.3) and network designs(C.3).

6.2 DOES THE ATTENTION IN AGILE LEARN MEANINGFUL ACTION RELATIONS?

In Figure 6, we analyze the agent performance qualitatively. (a) In CREATE, at $t = 0$, the selected action *spring* in AGILE's GAT attends to various other tools, especially covers all the tools that get activated with spring, such as trampoline. At $t = 1$, the trampoline tool is selected with a strong attention on spring. This shows that for selecting trampoline, the agent checks for the presence of spring, so it is possible to place it before or after the trampoline. (b) In Grid World, we visualize the *Summary-GAT* ablation to see how summarizer utilizes attention. We consider the case where both $dig - lava$ skills are available. The agent goes right, digs the orange lava, and is about to enter the pink lava. At this point, the *Right* action attends with a high weight to $Dig - Pink$ skill, checking for its presence before making an irreversible decision of entering the lava. In contrast, the *Utility Policy* always follows the safe suboptimal path as it is blind to the knowledge of dig-skills before entering lava. Finally, in RecSim, we observe that the agent is able to maximize the CPR score by selecting 5 out of 6 items in the list from the same primary category. In contrast, *Utility Policy* cannot determine the most common category and is unable to maximize CPR well.

Figure 6: Qualitative Analysis. (a,b) The attention maps from GAT show the reasoning behind an action decision. The nodes show available actions and edge widths are proportional to attention weight (thresholded for clarity). (b) Utility Policy learns the same suboptimal solution for any given action set, while Summary-GAT adapts to the best strategy by exploiting dig-skills. (c) AGILE is able to optimize CPR by identifying the most common item category, unlike Utility Policy. We provide qualitative video results for Grid World and CREATE on the project page https://sites.google.com/view/varyingaction.

6.3 ADDITIONAL ANALYSES

6.3.1 IMPORTANCE OF ATTENTION IN THE GRAPH NETWORK

Figure 7: Additional Analyses (i) GAT v/s GCN, and (ii) state-action graph v/s action-only graphs.

We validate the choice of using graph attention network as the relational architecture. In Figure 7, we compare GAT against a graph convolutional network (GCN) (Kipf & Welling, 2016) in the action graph of AGILE. We observe that for the simple grid world and RecSim tasks, GCN achieves optimal performance. This is because GCN can still act like a summarizer, despite the edge weights not being learned. However, it suffers in CREATE and RecSim-pairing (Figure 16) where the action space is large and requires diverse action relations. Moreover, we believe that the attention in GAT makes the graph sparse to ease RL training, which in contrast, is difficult in a fully-connected GCN.

6.3.2 IMPORTANCE OF STATE-DEPENDENT LEARNING OF ACTION RELATIONS

We compare the version of AGILE where the GAT only receives action features as input and no state. Thus, the decision-choice is still aware of other actions, but the learned relations are fixed, not dependent on the state. Figure 7 shows a drop in performance for Grid World and CREATE, where the relevant action relations change based on the state. However, there is no drop in RecSim because CPR task only requires knowing the most common category, which is independent of user state.

7 CONCLUSION

We present AGILE, a policy architecture for leveraging action relations for reinforcement learning with varying action spaces. AGILE builds a complete graph of available actions' representations and utilizes a graph attention network to learn the interdependence between actions. We demonstrate that utilizing the knowledge of available actions is crucial for optimal decision-making and relational action features ease learning in 4 environments, including a real-data recommendation task.

REFERENCES

Peter W Battaglia, Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, et al. Relational inductive biases, deep learning, and graph networks. *arXiv preprint arXiv:1806.01261*, 2018.

Lukas Biewald. Experiment tracking with weights and biases. *Software available from wandb. com*, pp. 33, 2020.

Craig Boutilier, Alon Cohen, Amit Daniely, Avinatan Hassidim, Yishay Mansour, Ofer Meshi, Martin Mladenov, and Dale Schuurmans. Planning and learning with stochastic action sets. *arXiv preprint arXiv:1805.02363*, 2018.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

Yash Chandak, Georgios Theocharous, James Kostas, Scott Jordan, and Philip Thomas. Learning action representations for reinforcement learning. In *International Conference on Machine Learning*, pp. 941–950. PMLR, 2019.

Yash Chandak, Georgios Theocharous, Blossom Metevier, and Philip Thomas. Reinforcement learning when all actions are not always available. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 3381–3388, 2020a.

Yash Chandak, Georgios Theocharous, Chris Nota, and Philip Thomas. Lifelong learning with a changing action set. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 3373–3380, 2020b.

Xinshi Chen, Shuang Li, Hui Li, Shaohua Jiang, Yuan Qi, and Le Song. Generative adversarial user model for reinforcement learning based recommendation system. In *International Conference on Machine Learning*, pp. 1052–1061. PMLR, 2019a.

Yu Chen, Yingfeng Chen, Yu Yang, Ying Li, Jianwei Yin, and Changjie Fan. Learning action-transferable policy with action embedding. *arXiv preprint arXiv:1909.02291*, 2019b.

Heng-Tze Cheng, Levent Koc, Jeremiah Harmsen, Tal Shaked, Tushar Chandra, Hrishi Aradhye, Glen Anderson, Greg Corrado, Wei Chai, Mustafa Ispir, et al. Wide & deep learning for recommender systems. In *Proceedings of the 1st workshop on deep learning for recommender systems*, pp. 7–10, 2016.

Maxime Chevalier-Boisvert, Lucas Willems, and Suman Pal. Minimalistic gridworld environment for openai gym. `https://github.com/maximecb/gym-minigrid`, 2018.

Kyunghyun Cho, Bart Van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using rnn encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*, 2014.

Djork-Arné Clevert, Thomas Unterthiner, and Sepp Hochreiter. Fast and accurate deep network learning by exponential linear units (elus). *arXiv preprint arXiv:1511.07289*, 2015.

Gabriel Dulac-Arnold, Richard Evans, Hado van Hasselt, Peter Sunehag, Timothy Lillicrap, Jonathan Hunt, Timothy Mann, Theophane Weber, Thomas Degris, and Ben Coppin. Deep reinforcement learning in large discrete action spaces. *arXiv preprint arXiv:1512.07679*, 2015.

Yu Gong, Yu Zhu, Lu Duan, Qingwen Liu, Ziyu Guan, Fei Sun, Wenwu Ou, and Kenny Q Zhu. Exact-k recommendation via maximal clique optimization. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 617–626, 2019.

Jessica B Hamrick, Kelsey R Allen, Victor Bapst, Tina Zhu, Kevin R McKee, Joshua B Tenenbaum, and Peter W Battaglia. Relational inductive bias for physical construction in humans and machines. *arXiv preprint arXiv:1806.01203*, 2018.

Junheng Hao, Tong Zhao, Jin Li, Xin Luna Dong, Christos Faloutsos, Yizhou Sun, and Wei Wang. P-companion: A principled framework for diversified complementary product recommendation. In *Proceedings of the 29th ACM International Conference on Information & Knowledge Management*, pp. 2517–2524, 2020.

Ji He, Jianshu Chen, Xiaodong He, Jianfeng Gao, Lihong Li, Li Deng, and Mari Ostendorf. Deep reinforcement learning with a natural language action space. *arXiv preprint arXiv:1511.04636*, 2015.

Shengyi Huang and Santiago Ontañón. A closer look at invalid action masking in policy gradient algorithms. *arXiv preprint arXiv:2006.14171*, 2020.

Zhiheng Huang, Wei Xu, and Kai Yu. Bidirectional lstm-crf models for sequence tagging, 2015.

Eugene Ie, Chih-wei Hsu, Martin Mladenov, Vihan Jain, Sanmit Narvekar, Jing Wang, Rui Wu, and Craig Boutilier. Recsim: A configurable simulation platform for recommender systems. *arXiv preprint arXiv:1909.04847*, 2019a.

Eugene Ie, Vihan Jain, Jing Wang, Sanmit Narvekar, Ritesh Agarwal, Rui Wu, Heng-Tze Cheng, Tushar Chandra, and Craig Boutilier. Slateq: A tractable decomposition for reinforcement learning with recommendation sets. 2019b.

Ayush Jain, Andrew Szot, and Joseph Lim. Generalization to new actions in reinforcement learning. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 4661–4672. PMLR, 13–18 Jul 2020. URL http://proceedings.mlr.press/v119/jain20b.html.

Ray Jiang, Sven Gowal, Timothy A Mann, and Danilo J Rezende. Beyond greedy ranking: Slate optimization via list-cvae. *arXiv preprint arXiv:1803.01682*, 2018.

Anssi Kanervisto, Christian Scheller, and Ville Hautamäki. Action space shaping in deep reinforcement learning. In *2020 IEEE Conference on Games (CoG)*, pp. 479–486. IEEE, 2020.

Hyoungseok Kim, Jaekyeom Kim, Yeonwoo Jeong, Sergey Levine, and Hyun Oh Song. EMI: Exploration with mutual information. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 3360–3369, Long Beach, California, USA, 09–15 Jun 2019. PMLR. URL http://proceedings.mlr.press/v97/kim19a.html.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

Ilya Kostrikov. Pytorch implementations of reinforcement learning algorithms. https://github.com/ikostrikov/pytorch-a2c-ppo-acktr-gail, 2018.

Shuchang Liu, Fei Sun, Yingqiang Ge, Changhua Pei, and Yongfeng Zhang. Variation control and evaluation for generative slate recommendations. *Proceedings of the Web Conference 2021*, Apr 2021. doi: 10.1145/3442381.3449864. URL http://dx.doi.org/10.1145/3442381.3449864.

Andrew L Maas, Awni Y Hannun, Andrew Y Ng, et al. Rectifier nonlinearities improve neural network acoustic models. In *Proc. icml*, volume 30, pp. 3. Citeseer, 2013.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32: 8026–8037, 2019.

Deepak Pathak, Chris Lu, Trevor Darrell, Phillip Isola, and Alexei A. Efros. Learning to control self-assembling morphologies: A study of generalization via modularity, 2019.

Zhiwei Qin, Xiaocheng Tang, Yan Jiao, Fan Zhang, Zhe Xu, Hongtu Zhu, and Jieping Ye. Ride-hailing order dispatching at didi via reinforcement learning. *INFORMS Journal on Applied Analytics*, 50(5):272–286, 2020.

Alvaro Sanchez-Gonzalez, Nicolas Heess, Jost Tobias Springenberg, Josh Merel, Martin Riedmiller, Raia Hadsell, and Peter Battaglia. Graph networks as learnable physics engines for inference and control. In *International Conference on Machine Learning*, pp. 4470–4479. PMLR, 2018.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Junshuai Song, Zhao Li, Chang Zhou, Jinze Bai, Zhenpeng Li, Jian Li, and Jun Gao. Co-displayed items aware list recommendation. *IEEE Access*, 8:64591–64602, 2020. doi: 10.1109/ACCESS. 2020.2984543.

Peter Sunehag, Richard Evans, Gabriel Dulac-Arnold, Yori Zwols, Daniel Visentin, and Ben Coppin. Deep reinforcement learning with attention for slate markov decision processes with high-dimensional states and actions. *arXiv preprint arXiv:1512.01124*, 2015.

Andrea Tacchetti, H. Francis Song, Pedro A. M. Mediano, Vinicius Zambaldi, János Kramár, Neil C. Rabinowitz, Thore Graepel, Matthew Botvinick, and Peter W. Battaglia. Relational forward models for multi-agent learning. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=rJlEojAqFm.

Guy Tennenholtz and Shie Mannor. The natural language of actions. *arXiv preprint arXiv:1902.01119*, 2019.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. *arXiv preprint arXiv:1710.10903*, 2017.

Tingwu Wang, Renjie Liao, Jimmy Ba, and Sanja Fidler. Nervenet: Learning structured policy with graph neural networks. In *International Conference on Learning Representations*, 2018.

Deheng Ye, Zhao Liu, Mingfei Sun, Bei Shi, Peilin Zhao, Hao Wu, Hongsheng Yu, Shaojie Yang, Xipeng Wu, Qingwei Guo, et al. Mastering complex control in moba games with deep reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 6672–6679, 2020.

Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Russ R Salakhutdinov, and Alexander J Smola. Deep sets. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/f22e4747da1aa27e363d86d40ff442fe-Paper.pdf.

Vinicius Zambaldi, David Raposo, Adam Santoro, Victor Bapst, Yujia Li, Igor Babuschkin, Karl Tuyls, David Reichert, Timothy Lillicrap, Edward Lockhart, et al. Deep reinforcement learning with relational inductive biases. In *International Conference on Learning Representations*, 2018.

Xiangyu Zhao, Liang Zhang, Long Xia, Zhuoye Ding, Dawei Yin, and Jiliang Tang. Deep reinforcement learning for list-wise recommendations. *arXiv preprint arXiv:1801.00209*, 2017.

Xiangyu Zhao, Long Xia, Liang Zhang, Zhuoye Ding, Dawei Yin, and Jiliang Tang. Deep reinforcement learning for page-wise recommendations. *Proceedings of the 12th ACM Conference on Recommender Systems*, Sep 2018. doi: 10.1145/3240323.3240374. URL http://dx.doi.org/10.1145/3240323.3240374.

Tao Zhou, Zoltán Kuscsik, Jian-Guo Liu, Matúš Medo, Joseph Rushton Wakeling, and Yi-Cheng Zhang. Solving the apparent diversity-accuracy dilemma of recommender systems. *Proceedings of the National Academy of Sciences*, 107(10):4511–4515, 2010.

A   ENVIRONMENT DETAILS

A.1   DIG LAVA GRID NAVIGATION

The grid world environment, introduced in Sec. 5.1, requires an agent to reach a goal by navigating a 2D maze with 2 lava rivers using a variable set of skills.

State: The state space is a concatenation of two flattened 9x9 grids:

1. Environment: each grid element is an integer ID representing whether the cell is empty, orange-lava, pink-lava, goal, or sub-goal
2. Agent: an empty grid except for 1 at agent-coordinates.

Termination: An episode is terminated in success when the agent reaches the goal and in failure when the agent stays in lava for two consecutive time steps or after a total of 50 time steps. Note that the agent can leave a lava cell only using the dig lava skill of the corresponding color.

Actions: The base action set is a fixed set of 9 skills and in each episode, a set of 7 skills is given to the agent. 5 skills are always available: *move-right*, *move-down*, *move-left*, *move-up*, and *turn-left*. The other 2 skills are randomly sampled from a set of 4 skills: *turn-right*, *step-forward*, *dig-orange-lava*, and *dig-pink-lava*.

Reward: The agent receives a large goal reward on reaching the goal. There are 2 subgoal rewards for a successful crossing of each lava column (i.e. column 4 and column 8) for the first time. The goal and subgoal rewards are discounted based on the number of action steps taken to reach that location, thus rewarding shorter paths. To further encourage shorter paths, successful lava digging is rewarded. A small exploration reward is added whenever the agent visits a new cell in the episode. To ensure exploration does not hinder learning short paths, the accumulated exploration reward is subtracted back when the agent reaches a subgoal or a goal. Thus,

$$R(s,a) = \mathbb{1}_{Goal} \cdot \left[R_{\text{Goal}} \left(1 - \lambda_{\text{Goal}} \frac{N_{\text{current steps}}}{N_{\text{max steps}}} \right) - R_{\text{Exploration}} \, N_{\text{steps from prev subgoal}} \right] +$$
$$\mathbb{1}_{Subgoal} \cdot \left[R_{\text{Subgoal}} \left(1 - \lambda_{\text{Subgoal}} \frac{N_{\text{current steps}}}{N_{\text{max steps}}} \right) - R_{\text{Exploration}} \, N_{\text{steps from prev subgoal}} \right] +$$
$$\mathbb{1}_{\text{Successful Dig}} \cdot R_{\text{Dig}} \; + \; \mathbb{1}_{\text{New State}} \cdot R_{\text{Exploration}}$$
(1)

where $R_{\text{Goal}} = 100, \; R_{\text{Subgoal}} = 0.5, \; R_{\text{Exploration}} = 0.01, \; R_{\text{Dig}} = 0.01,$
$\lambda_{\text{Goal}} = 0.99, \; \lambda_{\text{Subgoal}} = 0.9, \; N_{\text{max steps}} = 50$

Action Representations: The action representations are 11-dimensional vectors manually defined using a mix of one-hot vectors, as shown in Table 1. Dimensions 1-5 identify the category of skills (movement, elemental, dig-orange, dig-pink), 6-7 are distinguish movement skills (right, down, left, up), 8-9 are always 0 (originally meant for diagonal skills), 10-11 are used to distinguish elemental skills (turn-left, turn-right, move-forward).

Category	Skill	Action Representation										
Movement	move-right	0	0	0	0	1	-1	-1	0	0	0	0
	move-down	0	0	0	0	1	-1	1	0	0	0	0
	move-left	0	0	0	0	1	1	-1	0	0	0	0
	move-up	0	0	0	0	1	1	1	0	0	0	0
Elemental	turn-left	0	0	1	0	0	0	0	0	0	-1	1
	turn-right	0	0	1	0	0	0	0	0	0	1	-1
	move-forward	0	0	1	0	0	0	0	0	0	1	1
Digging	dig-orange	0	1	0	0	0	0	0	0	0	0	0
	dig-pink	1	0	0	0	0	0	0	0	0	0	0

Table 1: Action representations for the skills used in Dig Lava Grid Navigation environment.

A.2   CHAIN REACTION TOOL ENVIRONMENT (CREATE)

The CREATE environment (Sec. 5.2) requires an agent to place tools in a physics-based puzzle to make the target ball reach the goal position. We follow all the base settings of the CREATE Push Environment from Jain et al. (2020). We add the functionality of new activator tools and reduce the number of available actions per episode from 50 to 25.

State: The agent receives the past 3 gray-scale frames which are stacked channel-wise to make a 84x84x3 input.

Termination: The episode ends in success when the agent accomplishes the goal and in failure when there is no remaining movement in the game or after 30 time steps.

Actions: Each original tool from CREATE is now associated with newly added *activator tools* as shown in Figure 8. Thus, we add 5 activator tools to the 2110 general tools which are variations in angle, size, friction, or elasticity of the tools shown in Figure 8. Unlike Jain et al. (2020), we remove the No-Operation action. Activator tools are pass-through tools and only serve the function of activating their corresponding general tools when placed in contact.

We split the general tool space into 1098 tools for training, 507 tools for validation, and 507 tools for testing. Any of the 5 activator tools can be sampled during training, validation, and testing. In each episode, 23 general tools and 2 activator tools are randomly sampled and made available to the agent. The agent outputs in a hybrid action space consisting of (1) the discrete tool selection, and (2) (x, y) coordinates of tool position.

Figure 8: **CREATE Activator Mapping**: Original CREATE tools (right) are activated by the respective newly introduced activator tools (left). E.g., a *Cannon* tool (abbreviated as CNN in attention maps) placed on the environment will only be functional when a *Fire* tool is placed in contact with it. Other objects are not affected by non-functional tools - they simply pass through.

Reward: We adopt the reward structure from Jain et al. (2020). CREATE Push is a sparse reward environment with rewards for reaching the goal and making the target ball move. There is an additional *alive* reward to continue the episode. Placements outside the scene are penalized. The original CREATE environment penalizes overlapping tools. However, since overlapping activators and general tools is required for solving tasks, we modify the overlap penalty to apply only when either both are general tools or both are activator tools. Thus, the agent receives the following reward:

$$R(s,a) = R_{\text{alive}} + \mathbb{1}_{\text{Goal}} \cdot R_{\text{Goal}} + \mathbb{1}_{\text{target hit}} \cdot R_{\text{target hit}} + \mathbb{1}_{\text{invalid}} \cdot R_{\text{invalid}} + \mathbb{1}_{\text{overlap}} \cdot R_{\text{overlap}}$$

(2)

where $R_{\text{alive}} = 0.01$, $R_{\text{Goal}} = 10.0$, $R_{\text{target hit}} = 1$, and $R_{\text{invalid}} = R_{\text{overlap}} = -0.01$.

Action Representations: Each action representation is a 134-dimensional vector, a concatenation of two 128-D and 6-D vectors, as shown in Table 2. The 128-D vector corresponds to the learned characteristics of the tool and the 6-D vector is a binary vector denoting whether the tool is a general tool, an activator tool, or a no-op tool (no-op is disabled for experiments).

For general tools, Jain et al. (2020) obtain action representations using a Hierarchical VAE. They encode a set of tool observations into a latent representation. Each tool is made to interact with a probing ball launched from various angles, positions, and speeds. The tool characteristics can be inferred from this collection of tool interactions. We utilize these 128-D learned tool representations from Jain et al. (2020) for the general tools and pad them with a 6-D zero-vector. Generalization to unseen tools is possible because a trained agent can utilize the 128-D tool embedding to extract the relevant characteristics of any given tool. Note that the agent still needs to infer which activator a general tool is associated with, using its tool embedding.

For activator tools, the first 128 dimensions are always zero and the final 6 dimensions correspond to a one-hot vector, each for {no-op, Fire, Water, Electric, Magnet, Spring}.

Tool	Action Representation						
General Tools	Learned 128-D tool characteristics	0	0	0	0	0	0
No-Op	128-D Zero Vector	1	0	0	0	0	0
Fire	128-D Zero Vector	0	1	0	0	0	0
Water	128-D Zero Vector	0	0	1	0	0	0
Electric	128-D Zero Vector	0	0	0	1	0	0
Magnet	128-D Zero Vector	0	0	0	0	1	0
Spring	128-D Zero Vector	0	0	0	0	0	1

Table 2: Action representations for the tools in CREATE environment.

A.3 RecSim

The simulated recommender system environment (RecSim in Sec. 5.3.1), requires an agent to select a list of items that match the user's interest out of a variety of recommendable items. We simulate users that have a preference over high-CPR lists (Sec 5). The task of the agent is to infer this preference from user clicks and recommend a list of items that optimize both user interest and CPR.

State: The state is represented by the user interest embedding ($e_u \in \mathbb{R}^n$ where n denotes the number of categories of items) in categories that transitions over time as the user consumes different items upon click. So, when the user clicks an item with the corresponding item embedding($e_i \in \mathbb{R}^n$) then the user interest embedding(e_u) will be updated as follows,

$$\Delta(e_u) = (-y|e_u| + y) \cdot (1 - e_u), \text{ for } y \in [0, 1]$$
$$e_i \leftarrow e_u + \Delta(e_u) \text{ with probability}[e_u^T e_i + 1]/2$$
$$e_u \leftarrow e_u - \Delta(e_u) \text{ with probability}[1 - e_u^T e_i]/2$$

This essentially pulls the user preference towards the item that was clicked.

Action: The base action set is a set of 500 items (250 for each train and test action set) and in each episode, a sampled subset of size 20 is given to the agent. In order to simulate the varying action space environment, we implemented the **most common category sampling** method to form the candidate-set. Here, the majority of items are sampled from one common category and the remaining items are sampled from other categories. In this way, identifying the most common category is crucial to recommend a coherent list of items. Note that if we just sampled items uniformly across all categories, then CPR maximization would be less interesting as no single category has the potential to fill the entire list of items (i.e. achieve maximum CPR).

(a) Items with main category   (b) Items with main and sub category

Figure 9: t-SNE visualization of synthetically generated items in RecSim.

Reward: The base reward is a simulated response (e.g., clicks) from users (the user model (Ie et al., 2019a) stochastically skips or clicks an item in the list based on the user interest embedding). To better simulate the realistic scenario of user preference being affected by CPR of a presented list, we implement additional features in the user model:

$$\text{score}_{item} = \alpha_{user} * \langle e_u, e_i \rangle + \alpha_{metric} * m$$

$$p_{item} = \frac{e^{s_{item}}}{\sum e^{s_{item}}}$$

$$R = f_{\text{click\_or\_skip}}(p_{item})$$

where, $e_u, e_i \in \mathbb{R}^n$ are the user and item embedding, respectively, $\langle \cdot, \cdot \rangle$ is the dot product notation and $\alpha_{user}, \alpha_{metric}, m \in \mathbb{R}$ where m denotes the list-metric (e.g., CPR-score). So, given the score score_{item} of an item, the user model computes the click likelihood through a softmax function over all items and a predefined skip-item followed by a categorical distribution ($f_{\text{click\_or\_skip}}$). It takes the computed likelihood and outputs either click (reward=1) or skip (reward=0) as user feedback.

Action Representations: Originally, Ie et al. (2019a) use the discrete representation of items based on the one-hot encoding of item-category. However, this does not support generalization over items (actions). Therefore, we implement continuous item representations sampled from a Gaussian Mixture Model (GMM) with centers around each item category. Each item category has two sub-categories for items, which are also clustered. This ensures that the action representation contains information about both the primary category and the sub-category. Fig. 9 shows the t-SNE visualization of action representations for the 500 items, based on a GMMs. There are 10 main categories that each have two sub-categories. Figure 9a shows item representations labeled according to the primary category. Figure 9b shows item representations clustered according to sub-category.

A.4 REAL-DATA RECOMMENDER SYSTEM

The real-data recommender system environment (Sec. 5.3.2) requires an agent to select a list of items that match the user's interest out of a variety of recommendable items. We experiment with the scenario that domain engineers want an RL agent's list-actions to not only conform to the user preference but also optimize some list-metric. Since CPR having a high CPR is correlated with better user response (Hao et al., 2020), we use CPR as the additional list-metric. Thus, we reward the agent based on (i) user models trained from real data, and (ii) CPR of the recommended list of items. We collected the dataset from two different periods, two weeks in late August in 2021 as the offline period (used for training) and the following two weeks from early September in 2021 as the online period (used for evaluation).

State: The state is a concatenation of a sequence of historical user interactions. Concretely, a set of item representations (32 dimensional real vectors) of the three most recent clicked items (i.e., 32×3 matrix) are appended individually to the user attributes (137 dimensional real vectors) such as age, occupation, and localities. Therefore, the state is in the form of $507 = 169 \times 3 = (32 + 137) \times 3$. To act optimally, the agent must extract the useful representation of the user preference through this historical observation.

Figure 10: Real-Data Recommender System: F1 Score for Training/test user models. (Left) Online user model is trained on online-training data and evaluated on both online-training (green) and online-held-out (orange) data. (Right) Offine user model is trained on offline-training data and evaluated on both offline-training (green) and offline-held-out data (orange). Thus, the disparity between online data training and evaluation curves (left) shows that it is hard to train the online user model, whereas the offline user model generalizes reasonably well (right).

Figure 11: (a) F1 Score for Training/test user models (b) t-SNE visualization of Train/Test items (c) Item distribution of main category. (d) Item distribution of sub category.

Action: The base action set is a set of 85 items and in each episode, a sampled subset of size 20 is given to the agent. We employed the same sampling methods as in Sec. A.3. So, the agent needs to select a list of 6 items given the sampled candidate set of 20 items.

Reward: The base reward is a simulated response (click or skip) from the user model trained from real data. We add the CPR metric (between 0 to 1) to this click reward (1 or 0). The agent's objective is to optimize both user preference and the CPR of the list of items it recommends.

Training of User models: We follow the two different periods (offline and online) in the data extraction procedure. Thus, we trained two different user models ($f_{user} : \mathcal{S} \times \mathcal{A}^{\text{list-size}} \to \mathbb{R}$) to (i) train the agents offline and (ii) evaluate them with online users. The result of training those user models can be found in Figure 10 (a). Thus, the reward is computed as follows; $R = f_{user}(e_{user}, e_{item}) + m$ where f_{user} is either the offline user model or the online user model that provides us with the simulated response of users (e.g., click or skip). The user model architectures are described in Sec. C.3.5.

Action Representation: In the previous work CDQN (Chen et al., 2019a)), the authors found it useful to characterize the items by wide and deep features. For example, in the movie recommendation task, they considered the text description as the wide feature and the movie category as the deep feature. And they utilized the Wide and Deep Network (Cheng et al., 2016) to get useful representations of items. Following their work, we used the wide and deep network to pretrain the item embedding given the rich item features in the real-world data. However, we empirically observed that employing VAEs for each wide and deep feature of items leads to the better-segregated representation of items. Therefore, given an item instance, we separate the raw item attributes into the deep attributes (e.g., reward points of campaigns) and the wide attributes (e.g., text description), which are then fed into the VAE based wide and deep network to get the compressed representation by combining the wide and the deep features together. See Sec C.3.4 for more details about the network architecture. Thus, each action representation is a 32-dimensional vector encoded by

a VAE based Wide and Deep network. The learned representation of items are visualized based on the train-test split, distribution of the main category, and distribution of sub-category in Figure 11.

B FURTHER EXPERIMENTAL RESULTS

B.1 EFFECT OF USING DOMAIN KNOWLEDGE IN ACTION GRAPH EDGES

To show how to incorporate domain knowledge about action relations into the action graph (discussed in Section 4, we use the Dig Lava Grid World environment. Specifically, we use the knowledge that directional actions are always available. Thus, the only relevant action relations are the ones with the variable actions, i.e., 2 out of 4 actions (including both dig-lava skills). So, while building the action graph, instead of having a fully-connected structure, we only keep connections to and from the 2 variable actions. The rest of the AGILE architecture and algorithm stays the same. This reduces the number of bidirectional edges from $7^2 = 49$ to 29 by removing 20 edges between the always available actions. As shown in Figure 12, the learning speed of AGILE is slightly accelerated and the seed variance has reduced. We expect domain knowledge to help efficiency, even more, when the action space is large since the number of edges scales quadratically.

(a) Training Curve: Slightly faster   (b) Attention Map: Fewer edges

Figure 12: Effect of using domain knowledge to predefine the possible relations via edges in the action graph of AGILE. We know that in the Grid Navigation task, only the action relations with respect to variable actions are important. Thus, we remove all the other edges. This makes the learning slightly faster and more stable as shown by a reduction in seed variance. (5 seeds)

B.2 VALIDATING DESIGN CHOICES FOR VALUE-BASED AGILE

We conducted an exhaustive search on the architecture of value-based AGILE from two different perspectives; (a) Hyper-parameters and (b) Architectures. Note that the same hyper-parameter search procedure of this section was applied to all other methods and the same trend of the improvement in AGILE was found for other methods. In this section, AGILE that used in the main results (Fig. 4, 5, 7) is called, *AGILE-Tuned* and the barebone version of *AGILE-Tuned* is called *AGILE-Untuned* to illustrate how each change contributes to the performance.

B.2.1 HYPER-PARAMETER SEARCH IN AGILE

- **AGILE-Tuned without sync-freq-change:** In Mnih et al. (2015), the authors used the periodic syncing between the target and the main networks to alleviate the issue of the frequently moving target in updating the Q-network. In this work, we compared two extreme cases of the frequency period in syncing the networks; 10 (*Sync-freq=10* in Fig. 13 (a)) and 500 (*AGILE-Tuned*).

- **AGILE-Tuned without graph-dim-change:**   In order to understand the difficulty in expressing the action relation through the compact representation, we compared the big and the small representations in the action graph, i.e., the node-features are encoded in 32 (*Graph-dim=32*) or 64(*AGILE-Tuned*) dimensions.

(a) Hyperparameter search

(b) Design choices

Figure 13: Comparison of AGILE architectures. (Left) Train actions and (Right) Test actions

Figure 13(a) shows the result on both train and test actions. *AGILE-Tuned* outperformed all the methods. *Graph-dim=32* is slightly worse than *AGILE-Tuned* and *Sync-freq=10* is far below of them and is almost at the same level as *AGILE-Untuned*. We observed that the frequently moving target particularly harms the agent's performance while sufficient expressiveness in the action graph contributes in the performance.

B.2.2 DESIGN CHOICES OF AGILE

- **AGILE-Tuned with pre-summarizer:** Following the comparison with *Graph-dim=32*, we also examined if we can improve the performance by transforming the raw node-features(the concatenation of the raw action representation and the state information; See Sec.C.3.1) into the compact representation by having the 2 layer MLP with ReLU before the GAT in the action graph.

- **AGILE-Tuned without target-q-change:** In CDQN (Chen et al., 2019a), they computed the target q-values using the list at the next time-step in updating the Q-networks. But, we found that from a user point of view, the next time-step is rather the next position in the same list. So, here, we compared two different updating methods; (a) Intra-list(*AGILE-Tuned*): the target q-value is from the next intra-time-step. (b) Across-list(No target-q change): the target q-value is from the next time-step.

- **AGILE-Tuned without twinGAT-change:** In AGILE, the action graph provides the utility network with the relational action representation and the action summary. Here, we compared options; (a) Sharing GAT (*No twin-GAT*): there is a single GAT working to provide both of them. (b) Non-sharing GAT (*AGILE-Tuned*): this employs two different GATs for each, respectively.

- **AGILE-Tuned without main/target-encoder-separation-change:** In the implementation of AGILE, we compared two different architectural decisions; (a) *No main-target separation*: Sep-

Figure 14: Comparison against the baselines.

Figure 15: Comparison against ablations.

arate the list encoder in CDQN to the main and the target ones as the Q-networks are separated accordingly. (b) *AGILE-Tuned:* it shares the same list encoder for both the target and the main Q-networks.

Figure 13(b) shows the result on both train and test actions. *AGILE-Tuned, With pre-summrizer*, and *No twin-GAT* showed the similar performance which is better than *No target-q-change*. The difference between *AGILE-Tuned* and *No target-q-change* shows that since the cascaded network considers the intermediate list constructed in decision-making, in the computation of the target q-values the agent also needs to refer to the q-value of the next position in the same list instead of another list from the future time-step.

B.3 EFFECT OF DIRECT V/S INDIRECT REWARD IN RECSIM

In Fig.4, we studied the learning capability of AGILE under the action interdependence on RecSim in which the CPR itself was not directly visible to the agents. Therefore, agents need to understand how well the list-action is through the user feedback (i.e., clicks) indirectly. In this section, we strengthen our results by examining the consistency of results in the setting where the CPR is made directly visible to all the agents. So, we implemented the additional environment in RecSim that the reward signal itself contains the signal of how well the provided list of items is, such that the CPR metric is directly added to the click signal. And we called this environment as *Direct CPR*. Figure.14 shows the comparison of AGILE against the baselines the same agents as in Fig.4 on the Direct CPR

Figure 16: Analyses of (i) GAT v/s GCN and (ii) state-action graph v/s action-only graphs on (left) RecSim: Direct CPR environment and (right) RecSim: Pairing environment.

RecSim. And in Fig.15 and Fig.16, we got the consistent result that AGILE slightly outperforms the ablations and shows the competitive performance. AGILE clearly outperforming the baselines shows that the knowledge of dependence on other available actions is crucial for optimal policy and this result is consistent with the indirect CPR optimization setting in Fig.4. So AGILE is able to perform well in the direct maximization of CPR.

B.4   RECSIM-PAIRING ENVIRONMENT

In the experiment of Fig. 5, we found that in RecSim the relation of items is easy to model such that AGILE could not outperform the ablations whereas AGILE outperformed the ablations in CREATE and Grid World by correctly utilizing the action relation in decision-making. Then, we hypothesized that the existence of the complex relations between actions in the environment (e.g., tools and activators in CREATE) injects the complex action relations in the environment. For instance, an appropriate pair of an activator and a tool to use in CREATE depends on the situation. To this end, we implemented the pre-defined pairings among items in RecSim such that clicks can only happen when the correct pairs of items are recommended. Since action relations are complex, AGILE is expected to outperform the ablations. Figure 14 shows that AGILE beats the baselines and in Fig.15 AGILE slightly but consistently outperforms the ablations. In Fig.16, AGILE outperformed AGILE-GCN shows that a GAT is capable of modeling the action relations correctly and AGILE converging faster than AGILE Only Action shows that the intermediate list information is crucial to efficiently learn to attend the other half in the pairing of items.

C   APPROACH AND BASELINE DETAILS

C.1   DETAILS OF BASELINES AND ABLATIONS

Like AGILE, all baselines and ablations receive the state and action representations as input and output a Q-value or a probability distribution over available actions. Figure 17 describes the architectures of all the methods. Here, we discuss how each baseline and ablation is different from AGILE and why AGILE is expected to outperform them:

- **Mask-Output** (No representations, No input action set): This baseline assumes a fixed-action space that is known in advance. Since it does not use action representations, it cannot generalize to unseen actions and cannot exploit the structure in action space. Moreover, it does not take any information of available action set as input and thus cannot solve tasks where action decisions require knowledge of other actions.

- **Mask-Input-Output** (No representations): By augmenting a binary availability mask of given actions to the state input of *Mask-Output*, this method can utilize the information about the available action set as a set. However, the input availability-mask is fed into an MLP which lacks the inductive bias of order invariance of action set and cannot learn relations explicitly like graph networks.

- **Utility-Policy** (No input action set): By using action representations, this method can use the structure of action space for efficient training and also generalize to unseen actions. However, like

(a) Mask-Output and Mask-Input-Output Baselines

(b) Utility-Policy Baseline

(c) Summary-GAT, -LSTM, and -Deep Set Ablations

(d) AGILE

(e) AGILE-Only Action Analysis

Figure 17: Architectures of all methods used as baselines (Sec. 6.1.1), ablations (Sec. 6.1.2), and analyses (Sec. 6.3.2). (a) Following prior work in SAS-MDPs (Boutilier et al., 2018; Chandak et al., 2020a) and invalid action masking (Huang & Ontañón, 2020; Ye et al., 2020; Kanervisto et al., 2020), the **mask-output** baseline masks out the unavailable actions assuming a known action set. The **mask-input-output** baseline additionally augments the state with the action availability mask. (b) Utility-policy (Jain et al., 2020) can generalize over actions by using action representations, however, computes each action utility independent of other available actions. (c) **Summary** Ablations augment the utility-policy with an extra action-summary input, which is a compressed version of the list of available action representations. This compression can be done by mean-pooling over a *Bi-LSTM* output layer, or a *deep set*, or a graph network (*GAT*) processed node features. (d) **AGILE (Ours)** uses a GAT's node features both to compute an action set summary and as relational action features replacing the original action representations. While the action set summary is a compact representation of the available actions, it does not sufficiently scale when there are many actions or for tasks requiring many actual relations for each action decision. (e) **AGILE-Only Action** is the version of AGILE where the state is not used to compute action relations in GAT. This is a simpler architecture to learn but is not expected to work for certain tasks where action relations change depending on the state.

Mask-Output, it does not utilize the available action set as part of the state and makes each action decision independent of other actions. Thus, it is expected to be suboptimal in all the tasks we consider.

- **Summary-LSTM**: This is an ablation where we do not utilize the per-action relational features computed by a GAT in AGILE. Instead, we use raw action features as input to the utility network. However, we do utilize the information of the available action set by summarizing the set of input action representations into a vector. Summarization based on Bi-LSTM does not utilize the order invariance property of the action set and can be less efficient to learn than other summarizers. AGILE is expected to outperform all summary-only ablations in environments where several different action relations need to be modeled for computing different action utilities. This is true for complex environments like CREATE, where the agent needs to consider various tools and various activators to make an optimal decision about its action choice. In such environments, learning a shared summary-vector for all action utility computations is inefficient and possibly prohibitive for learning. We note that in simple environments such as Grid World navigation, the summary-ablations are sufficient as all the agent needs to do is summarize which of the two dig-lava skills are available. Such a summary is enough to compute the utility of each of the 7 available actions.

- **Summary-Deep Set**: This ablation utilizes the order invariance of action sets using a deep-set. While it still suffers from the limitations of lack of per-action relational action features, it is a low-parameter network and thus easy to train.

- **Summary-GAT**: This is a variation of AGILE, where the relational action features are replaced by raw action features. Using a GAT to extract the action set summary exploits order invariance. However, being a fully-connected graph network, it is can be slow to train, while not offering much more than the deep-set summarizer. This can be useful when certain action relations are predefined using domain knowledge (Section B.1).

- **Agile-Only-Action**: This variation of AGILE does not utilize state input in the GAT. Thus, the summary vector and relational action features are computed independently of state-context. While this is a simpler architecture to train, it can be insufficient in environments where the action relations vary depending on the state.

C.2 DETAILS ON LISTWISE AGILE

AGILE is implemented based on the listwise RL architecture, CDQN (Chen et al., 2019a). As shown in Algorithm 1, CDQN builds a list-action incrementally by selecting N actions in sequence. For each list-index, a Q-network is used to select the best action. In addition to the usual state input, the partially built list-action is also an input to the Q-network. Concretely, for any list index, the state and current list are encoded into latent embeddings. These are concatenated with each action representation in the remaining action set to build a list of nodes to be input into the action graph of AGILE. Treating it as a fully-connected graph, AGILE outputs a set of relational action features for all inputs actions. These are mean-pooled into a summary vector representing the entire action set. The representations of state, current-list, summary, and relational action features are used as input by a utility network (MLP) which outputs the Q-value of that particular action for the current list-index. The action with the maximum Q-value is added to the list and the algorithm moves to the next list-index.

For training AGILE based CDQN, we maintain a target Q-network that is synchronized periodically with the main Q-network. Suppose a tuple of $(s, a_{\text{list}}, r, \tilde{s})$ is sampled from the replay buffer. For list index n between 1 and $N - 1$, we compute the target Q-value using the current state s with partial list-action $a_{1:n}$ as input. However, for the last list index $n = N$, we compute the target Q-value using the next state $\tilde{s}$ for its first list index. A mean-squared error loss is used over all the list indices to train the main Q-network.

Algorithm 1 Cascaded DQN: Listwise Action RL

1: **def** listwise_action():
2:     **Parameters**: Q-network ϕ - Encoders, GAT and Utility network
3:     **Inputs**: State s, actions $\mathcal{A}$, representations $\mathcal{C} = \{c_{a_0}, ..., c_{a_k}\}$, list-action length N
4:     **Initialize**: List Action $a_{\text{list}} = []$. Candidate Actions $\mathcal{A}' = \mathcal{A}$
5:     **for** $n = 1, \ldots, N$ **do**:
6:         Encode State: $e_s = \phi_s(s)$
7:         Encode Current List: $e_{\text{list}} = \phi_{\text{list}}(a_{\text{list}})$
8:         Build Graph Nodes: $\mathcal{V} = \{[e_s, e_{\text{list}}, c_a] \ : \ a \in \mathcal{A}' \}$
9:         Build fully-connected Adjacency Matrix of size $|\mathcal{V}|$: $\mathcal{E}$
10:        Relational Action Features: $e_{\text{relational}}^a = \phi_{\text{GAT}}(\mathcal{V}, \mathcal{E}) \ \forall a \in \mathcal{A}'$
11:        Action Set Summary: $e_{\text{summary}} = \frac{1}{|\mathcal{V}|} \sum_a e_{\text{relational}}^a$
12:        Q-values: $Q_n(s, a, \mathcal{A}') = \phi_{\text{utility}}(e_s, e_{\text{list}}, e_{\text{summary}}, e_{\text{relational}}^a)$ ▷ Ablations: $e_{\text{relational}}^a = c_a$
13:        Select action: $a_n = \arg\max_{a \in \mathcal{A}'} Q_n(s, a, \mathcal{A}')$
14:        Update: $a_{\text{list}} = a_{\text{list}} \cup a_n$. $\mathcal{A}' = \mathcal{A}' \setminus a_n$
15: **def** listwise_update():
16:     **Parameters**: Q-network ϕ, Target Q-network ϕ_T, discount factor γ
17:     **Inputs**: state s, action $a_{\text{list}} = a_1, \ldots a_N$, reward r, next state $\tilde{s}$
18:     **for** $n = 1, \ldots, N$ **do**:
19:         Use listwise_action(ϕ) to get Q-function: $q_n = Q_n(s, a_n, \mathcal{A} \setminus a_{1:n-1})$
20:         Use listwise_action(ϕ_T) to get target Q-value :

$$y_n = \begin{cases} r + \gamma \max_a Q_{n+1}(s, a, \mathcal{A} \setminus a_{1:n}) & n < N \\ r + \gamma \max_a Q_1(\tilde{s}, a, \mathcal{A}) & n = N \end{cases}$$

21:     Optimize Loss $\mathcal{L} = \sum_{n=1}^{N} (q_n - y_n)^2$

C.3   Network Architectures

C.3.1   Action Graph

The action graph takes as input the action representations and the state-information (we also include the list-embedding for Listwise AGILE; See Sec. C.2). Given the concatenation of the input components above, an optional 2-layer MLP with ReLU, called *pre-summarizer-mlp*, transforms it into the node features for the action graph. Then, the resultant node-features are passed on to a Multi-head GAT layer followed by another GAT layer and a residual connection. The same architecture of GAT is duplicated with different weights to provide separate pathways to compute the summary vector and relational action features. Therefore, we have two different sets of node-features. One set of node-features is averaged over the nodes (mean-pooling) to produce the action-summary vector which is put through a 2-layer MLP with ReLU to post-process before being passed on to the utility network. The other set of node-features (i.e. the relational action features) are also directly fed into the utility network.

AGILE with GCN: When the GCN is used in the action graph, the same input as above goes into a linear layer to compress the size. Subsequently, the resultant node-features are used in GCN message-passing based on the normalized adjacency matrix, with all the diagonal elements made 0. Otherwise, the GCN reduces to learning the same edge coefficients for all the nodes. The rest of the following architecture is the same as GAT above.

Summary-GAT: In this ablation, instead of the relational action features being fed into the utility network, the raw action representations are used. The rest of the architecture remains the same.

C.3.2   Summarizers: Bi-LSTM and Deep Set

Bi-LSTM: The raw action representations of candidate actions are passed on to the 2-layer MLP followed by ReLU. Then the output of the MLP is processed by a 2-layer bidirectional LSTM (Huang

et al., 2015) followed by another 2-layer MLP to create the action-summary to be used in the subsequent utility network.

DeepSet: Similar to the Bi-LSTM variant of the summarizer, we employed the 2-layer MLP with ReLU followed by the mean pooling over all the candidate actions to compress the information. Finally, the 2-layer MLP with ReLU provides the resultant action summary with the subsequent utility network described in the next subsection.

C.3.3 UTILITY NETWORK

We implemented two different types of the utility networks to show the potential of AGILE architecture working with different kinds of RL algorithms and environments. Both the utility networks take as input the same components: the state-information, the relational or raw action representations, and the action summary of the action graph (See Sec C.3.1). The utility network is a 2-layer MLP that is applied parallelly on all these inputs corresponding to each action. It computes a scalar value for each action.

Policy Gradient(PPO):
The action utility values are used as logits of a Categorical distribution, which is then used to train the AGILE architecture with policy gradient algorithm, PPO.

Value-based(CDQN):
List Encoder: An intermediate list that contains the currently selected list items at each intra-list time-step is passed on to a single layer gated recurrent network (GRU (Cho et al., 2014)) followed by a 2-layer MLP to extract the compact representation of the intermediate list. See Algorithm 1 for details on this.

Q-network: As in Sec C.3.1, the input components for the utility network are the raw action representation, the state-information, the list-embedding, and the node-features as well as the action summary of the action graph($(s_t, e_{\text{list}}, e_{\text{node}}, e_{\text{summary}}, a_k)$ in Algorithm 1) are concatenated into a single vector and passed on to a 2-layer MLP with ReLU to compute the Q-value of an item.

C.3.4 ACTION REPRESENTATION NETWORK

Hierarchical VAE (CREATE): The CREATE action representations are borrowed directly from Jain et al. (2020). The Hierarchical VAE network takes as input a list of behavioral trajectories representing each action (tool) and reconstructs it with a two-layer hierarchy of VAEs. We refer the reader to Appendix D.3.1 of Jain et al. (2020) for complete details of the Hierarchical VAE network.

VAE in Deep and Wide architecture (Real World recommender system):
In a VAE, the encoder is implemented with a 5-layer MLP with a Batch Normalization layer (Maas et al., 2013) and LeakyReLU (Maas et al., 2013). On the other hand, the decoder is implemented with a single MLP to process the input followed by the same architecture of MLPs used in the encoder. Finally, a 2-layer MLP with Batch Norm and LeakyReLU as well as the hyperbolic tangent activation function is used to reconstruct the input instance.

C.3.5 REWARD INFERENCE NETWORK (USER MODEL IN REAL WORLD RECSYS)

The user model takes as input the user information(i.e., a concatenation of user attributes and a sequence of the user interactions) and a set of item embeddings in the list. The user information is passed on to a single layer gated recurrent network(GRU (Cho et al., 2014)) followed by a 2-layer MLP to extract the compact representation of the state. Also, the set of item embeddings is processed by the same architecture of the GRU network(this and the one before are not shared and initialized differently) as the list-embedding. Finally, a 2-layer MLP takes as input the concatenation of those two embeddings(i.e., state-embedding and list-embedding) and provides the scores of items in the list followed by the sigmoid function to transform to the individual click likelihood.

D   EXPERIMENT DETAILS

D.1   IMPLEMENTATION DETAILS

We used PyTorch (Paszke et al., 2019) for our implementation, and the experiments were primarily conducted on workstations with either NVIDIA GeForce RTX 2080 Ti, P40 or V100 GPUs. Each experiment seed takes about 4 hours for Grid Navigation, 60 hours for CREATE, 8 hours for Rec-Sim, and 15 hours for Real-Data Recommender Systems, to converge. We use the Weights & Biases tool (Biewald, 2020) for logging and tracking experiments. All the environments were developed using the OpenAI Gym interface (Brockman et al., 2016). For training Grid Navigation and CRE-ATE environments, we use the PPO (Schulman et al., 2017) implementation based on Kostrikov (2018). For the recommender system environments, we use DQN (Mnih et al., 2015). We use the Adam optimizer (Kingma & Ba, 2014) throughout. We attach the code with details to reproduce all the experiments, except the real-data recommender system.

D.2   HYPERPARAMETERS

We build on hyperparameters used in prior work on CDQN (Chen et al., 2019a) and utility policy (Jain et al., 2020). The hyperparameters for the additional components introduced in AGILE, baselines, and ablations are shown in Table 3. The environment-specific and RL algorithm hyperparameters are described in Table 4.

Hyperparameter	Value
AGILE	
number of GAT layers	2
number of attention heads	1
number of message passing steps	1
leakyReLU alpha	0.2
graph hidden dimension	64
Residual Connection	True
Mask-Input-Output	
Availability mask MLP hidden size	64
Ablations	
Summary-LSTM hidden size	64
Summary-LSTM directions	2
Summary-LSTM number of layers	2
Summary-Deep-Set hidden size	64
Summary-GAT hidden size	64
Summarizer pooling operation	mean

Table 3: AGILE, baseline and ablations - Added Components Hyperparameters

D.3   HYPERPARAMETER TUNING

Initial hyperparameters are inherited from the prior works (PPO: Jain et al. (2020); CDQN: Chen et al. (2019a)). To ensure fairness across all baselines and our methods, we use the original hyperparameters for the RL algorithms, such as learning rate, entropy coefficient etc. (Table 4. We choose a sufficiently large number for total epochs (DQN) and total environment steps (PPO) to ensure all the methods converge.

Our main contribution is the AGILE architecture. Thus, to correctly validate against baseline and ablation architectures, we search over shared parameters together and generally observe the same trend across all methods. This was expected because of the shared underlying implementation of the RL algorithm. Specifically, we searched over the following shared parameters, usually over 5 seeds and sometimes 3 seeds:

Hyperparameter	Grid world	CREATE	RecSim	Real RecSys
Environment				
action representation size	11	134	20	32
observation space	162	$84 \times 84 \times 3$	10	507
candidate actions per episode	7	25	20	20
max. episode length	50	30	15	10
RL Training				
training batch size	8192	4608	128	128
parallel processes	64	48	16	16
discount factor	0.99	0.99	0.99	0.99
learning rate	1e-3	1e-3	1e-4	1e-4
hidden layer size	64	64	64	64
PPO				
entropy coefficient	0.05	0.005		
continuous action entropy coefficient	-	0.0005		
total environment steps	8×10^6	10^8		
value loss coefficient	0.5	0.5		
PPO epochs	4	4		
PPO clip parameter	0.1	0.1		
DQN				
epochs			10000	5000
target network sync frequency			500	500
Q-network hidden dimension			256×64	256×64
list encoder dimension			64	64
action encoder dimension			32	32
list size			6	6
replay buffer size			10^6	10^6
initialize replay buffer size			5000	100
epsilon decay			$1 \rightarrow 0.1$	$1 \rightarrow 0.1$
epsilon decay last epoch			500	250

Table 4: Environment/Policy-specific Hyperparameters

- **Hidden dimension in DQN networks**: We searched over $\{32, 64, 128\}$ and found that $64 \approx 128 > 32$. We choose 64 as the base hidden dimension across all encoders, summarizers, and GATs.

- **Target network sync frequency**: This was a sensitive parameter for DQN training. We searched over $\{10, 20, 100, 500, 1000\}$ and found 500 to be the best performing across all methods. **Weight sharing in CDQN**: In Chen et al. (2019a), the authors did not share the weights of Q-nets in their Cascading architecture, but we empirically observed that sharing the weights of them improved the performance. This is likely due to the nature of RecSim tasks requiring similar items to be recommended to maximize CPR.

- **Training batch size (DQN)**: We searched over $\{32, 64, 128, 256\}$ on RecSim and chose 128 as beyond that we observed diminishing returns. For Real RecSys, we used the same batch size.

- **Training batch size (PPO)**: We searched over $\{4096, 8192\}$ for Grid World and $\{3072, 4608\}$ for CREATE and observed that larger batch sizes are better. We did not increase the batch size further due to limits on GPU memory size.

Below, we detail the hyperparameters and network variations searched over specifically for the graph attention network (GAT) used in AGILE and its variants.

- **Skip Connection**: Adding skip connection was crucial to making AGILE learn well.

- **Number of graph attention layers**: We searched over $\{1, 2, 3\}$ layers and found 2 layers to be the best performing for both PPO and CDQN based policies.

- **Number of attention heads**: We compared having $\{1, 2\}$ attention heads and found that no meaningful learning for 2 attention heads.

- **Number of message passing steps**: Adding more message passing steps than 1 did not improve AGILE performance.

Other relevant design choices are described and validated in Section B.2.