LEARN GOAL-CONDITIONED POLICY WITH INTRINSIC MOTIVATION FOR DEEP REINFORCEMENT LEARNING

ABSTRACT

It is of significance for an agent to learn a widely applicable and general-purpose policy that can achieve diverse goals including images and text descriptions. Considering such perceptually-specific goals, the frontier of deep reinforcement learning research is to learn a goal-conditioned policy without hand-crafted rewards. To learn this kind of policy, recent works usually take as the reward the non-parametric distance to a given goal in an explicit embedding space. From a different viewpoint, we propose a novel unsupervised learning approach named goal-conditioned policy with intrinsic motivation (GPIM), which jointly learns both an abstract-level policy and a goal-conditioned policy. The abstract-level policy is conditioned on a latent variable to provide intrinsic reward and discovers diverse states that are further rendered into perceptually-specific goals for the goal-conditioned policy, and both of the policies share the identical reward function. Experiments on various robotic tasks demonstrate the effectiveness and efficiency of our proposed GPIM method which substantially outperforms prior techniques.

1 INTRODUCTION

Reinforcement learning (RL) makes it possible to drive agents to achieve sophisticated goals in complex and uncertain environments, from computer games (Badia et al., 2020; Berner et al., 2019) to real robot control (Lee et al., 2018; Lowrey et al., 2018; Vecerik et al., 2019; Popov et al., 2017), which usually involves learning a specific policy for individual task relying on task-specific reward. However, autonomous agents are expected to exist persistently in the world and have the ability to solve diverse tasks. To achieve this, one needs to build a universal reward function and design a mechanism to automatically generate diverse goals for training. Raw sensory inputs such as images have been considered as common goals for agents to practice on and achieve (Watter et al., 2015; Florensa et al., 2019; Nair et al., 2018; 2019). It is currently an open challenge to build autonomous RL agents that can deal with such perceptually-specific inputs.

Previous works make full use of a goal achievement reward function as available prior knowledge (Pong et al., 2018), such as Euclidean distance. Unfortunately, this kind of measurement in original space is not very effective for visual tasks since the distance between images does not correspond to meaningful distance between states (Zhang et al., 2018). Further, the measure function is applied in the embedding space, where the representations of raw sensory inputs are learned by means of using a latent variable model like VAE (Higgins et al., 2017b; Nair et al., 2018) or using the contrastive loss (Sermanet et al., 2018; Warde-Farley et al., 2018). We argue that these approaches taking prior non-parametric reward function in original or embedding space as above may limit the repertoires of behaviors and impose manual engineering burdens (Pong et al., 2019).

In the absence of any prior knowledge about the measure function, an unsupervised method in RL is to learn a latent-conditioned policy by maximizing an information theoretic objective or taking self-consistent trajectory autoencoder (Co-Reyes et al., 2018; Hausman et al., 2018). However, this procedure, similar to parameter initialization or hierarchical RL, needs an external reward function; otherwise the learned latent-conditioned policy cannot be applied directly to user-specified goals. Although the learned discriminator in Eysenbach et al. (2018) can be adopted to estimate which skill was most likely to have generated the states, the user-specified goals are usually heterogeneous to the states, making the discriminator unusable. Sharma et al. (2019) adopts a model-based approach to reuse skills but requires additional training to model the environment.

Different from previous works, a novel unsupervised RL scheme is proposed in this paper to learn goal-conditioned policy by jointly learning an extra abstract-level policy conditioned on latent variables. The abstract-level policy is trained to generate diverse abstract skills while the goal-conditioned policy is trained to efficiently achieve perceptually-specific goals that are rendered from states induced by the corresponding abstract skill. Both abstract-level and goal-conditioned policies *share an identical intrinsic reward function* that distinguishes the states induced by abstract skills. This shared reward function is generated within our framework and optimized in an unsupervised manner for the purpose of reliable exploration (Salge et al., 2014). In essence, the abstract-level policy can reproducibly influence the environment, and the goal-conditioned policy perceptibly imitates these influences. To improve the generalization ability of goal-conditioned policy in dealing with perceptually-specific inputs, a latent variable model is further considered in our GPIM to disentangle goals into latent generative factors.

The main contribution of our work is an unsupervised RL method that can learn perceptually-specific goal-conditioned policy without extrinsic reward for autonomous agents. We propose a novel training procedure for this model, which provides an effective reward function for various perceptual goals, e.g. images and text descriptions. Furthermore, we introduce a latent variable model for learning the representations of high-dimensional goals, and demonstrate the potential of our model to generalize behaviors across new tasks. Extensive experiments and detailed analysis demonstrate the effectiveness and efficiency of our proposed method.

2 PRELIMINARIES

RL: An agent interacts with an environment and selects actions in RL so as to maximize the expected amount of reward received in the long run (Sutton & Barto, 2018), which can be modeled as a Markov decision process (MDP) (Puterman, 2014). An MDP is defined as a tuple $\mathcal{M} = (S, A, p, R, \gamma)$, where S and A are state and action spaces, $p(\cdot|s, a)$ gives the next-state distribution upon taking action a in state s, $R(s, a, s')$ is a random variable representing the reward received at transition $s \xrightarrow{a} s'$, and $\gamma \in [0, 1)$ is a discount factor.

Intrinsic Motivation: RL with intrinsic motivation obtains the intrinsic reward by maximizing the mutual information between latent variables ω and agent's behaviors τ: $\mathcal{I}(\omega; \tau)$, where the specific manifestation of τ can be an entire trajectory (Achiam et al., 2018), an individual state (Eysenbach et al., 2018) or a final state (Gregor et al., 2016); and the specific implementation includes *reverse* and *forward* forms (Campos et al., 2020). Please refer to Aubret et al. (2019) for more details.

Disentanglement: Given an observation x with a dimension of N, VAE (Kingma & Welling, 2013; Higgins et al., 2017a) is a latent model that pairs a top-down encoder $q(z|x)$ with bottom-up decoder network $p(x|z)$ by introducing a latent factor z, where $dim(z) < N$. To encourage the inferred latent factor z to capture the generative factor of x in a disentangled manner, an isotropic unit Gaussian prior $p(z) \sim N(0; I)$ is commonly used to control the capacity of the information bottleneck (Burgess et al., 2018) by minimizing the KL divergence between $q(z|x)$ and $p(z)$.

3 THE METHOD

In this section, we firstly formalize the problem and introduce the framework. Secondly, we elaborate on the process of how to jointly learn the goal-conditioned policy and abstract-level policy. Thirdly, disentanglement is applied in our setting to improve the generalization ability.

3.1 OVERVIEW

Given perceptually-specific goal g, our objective is to learn a goal-conditioned policy $\pi_\theta(\tilde{a}|\tilde{s}, g)$ that inputs state $\tilde{s}$ and g and outputs action $\tilde{a}$ as shown in Fig. 1. The abstract-level policy $\pi_\mu(a|s, \omega)$ takes as input state s and a latent variable ω and outputs action a, where ω corresponds to diverse latent skills. Two policies π_μ and π_θ share the same reward network (i.e., discriminator q_ϕ), which is optimized for reliable exploration *only at the abstract level*. The abstract-level policy is able to generate diverse states s that are further rendered as perceptually-specific goal $g = Render(s)$ (Brockman et al., 2016). On this basis, $\pi_\theta(\tilde{a}|\tilde{s}, g)$ conditioned on the rendered goal g interacts with the reset environment under the instruction of the reward function q_ϕ.

Figure 1: Framework of our GPIM method. The abstract-level policy π_μ and goal-conditioned policy π_θ share an identical reward network (i.e., discriminator) q_ϕ. State s_{t+1} (e.g., position of an agent) induced by π_μ is converted into a perceptually-specific goal g_t (e.g., image showing the position of the agent) for π_θ. Initial states s_0 of π_μ and $\tilde{s}_0$ of π_θ are sampled from the same distribution.

3.2 PROPOSED GPIM METHOD

In order to jointly learn the abstract-level policy $\pi_\mu(a|s,\omega)$ and goal-conditioned policy $\pi_\theta(\tilde{a}|\tilde{s},g)$, we maximize the mutual information between the state s and latent variable w for π_μ, and simultaneously maximize the mutual information between the state $\tilde{s}$ and goal g for π_θ. Consequently, the overall objective function to be maximized can be expressed as follows

Figure 2: Graphical model.

$$\mathcal{F}(\mu,\theta) = \mathcal{I}(s;\omega) + \mathcal{I}(\tilde{s};g). \tag{1}$$

For clarification, Fig. 2 depicts the graphical model for the latent variable ω, state s induced by π_μ, goal g rendered from s, and state $\tilde{s}$ induced by π_θ. As seen, the latent variable $\omega \sim p(\omega)$[1] is firstly used to generate state s via the policy π_μ interacting with dynamic environment. Then, we use the state s to generate perceptually-specific goal g. After that, the goal-conditioned policy π_θ outputs action $\tilde{a}$ to interact with the environment to obtain the state $\tilde{s}$ at the next time step. In particular, ω is expected to generate diverse behavior modes through π_μ while π_θ behaving like $\tilde{s}$ is to imitate this behavior by taking as input the rendered goal g. Based on the context, the correlation between $\tilde{s}$ and g is no less than that between $\tilde{s}$ and w, so that $\mathcal{I}(\tilde{s};g) \geq \mathcal{I}(\tilde{s};\omega)$ (Beaudry & Renner, 2011). Thus, we can obtain the lower bound of $\mathcal{F}(\mu,\theta)$:

$$\begin{aligned}\mathcal{F}(\mu,\theta) &\geq \mathcal{I}(s;\omega) + \mathcal{I}(\tilde{s};\omega) \\ &= 2\mathcal{H}(\omega) - \mathcal{H}(\omega|s) - \mathcal{H}(\omega|\tilde{s}) \\ &= \mathbb{E}_{\omega,s,\tilde{s}}\left[\log p(\omega|s) + \log p(\omega|\tilde{s}) - 2\log p(\omega)\right].\end{aligned} \tag{2}$$

Since it is difficult to exactly compute the posterior distributions $p(\omega|s)$ and $p(\omega|\tilde{s})$, Jensen's Inequality (Barber & Agakov, 2003) is further applied for approximation by using a learned discriminator network $q_\phi(\omega|\cdot)$. Thus,

$$\mathcal{F}(\mu,\theta) \geq \mathbb{E}_{\omega,s,\tilde{s}}\left[\log q_\phi(\omega|s) + \log q_\phi(\omega|\tilde{s}) - 2\log p(\omega)\right] \triangleq \mathcal{J}(\mu,\phi,\theta), \tag{3}$$

where it is worth noting that the identical discriminator q_ϕ with the parameter ϕ is used for the variational approximation of $p(\omega|s)$ and $p(\omega|\tilde{s})$. For the state s induced by skill w and $\tilde{s}$ originating from g, the shared discriminator q_ϕ assigns a similarly high probability on w for both states s and $\tilde{s}$ associated with the same ω. Therefore, q_ϕ can be regarded as a reward network shared by the abstract-level policy $\pi_\mu(a|s,\omega)$ and goal-conditioned policy $\pi_\theta(\tilde{a}|\tilde{s},g)$.

---

[1]p(ω) denotes the prior distribution. Fixing $p(\omega)$ instead of learning it is to prevent π_μ from collapsing to sampling only a handful of skills.

Algorithm 1 Learning process of our proposed GPIM

1: **while** not converged **do**	13: *# Step II*
2: Sample skill $\omega \sim p(\omega)$.	14: Sample initial state $\tilde{s}_0 \sim p_0(\tilde{s})$.
3: *# Step I*	15: **for** $t = 0, 1, ..., T - 1$ steps **do**
4: Sample initial state $s_0 \sim p_0(s)$.	16: Sample action $\tilde{a}_t \sim \pi_\theta(\tilde{a}_t | \tilde{s}_t, g_t)$.
5: **for** $t = 0, 1, ..., T$ steps **do**	17: Step environment: $\tilde{s}_{t+1} \sim p(\tilde{s}_{t+1} | \tilde{s}_t, \tilde{a}_t)$.
6: Sample action $a_t \sim \pi_\mu(a_t | s_t, \omega)$.	18: Compute reward $\tilde{r}_t$ for policy π_θ using (7).
7: Step environment: $s_{t+1} \sim p(s_{t+1} | s_t, a_t)$.	19: Update policy π_θ to maximize $\tilde{r}_t$ with SAC
8: Render goal: $g_t = Render(s_{t+1})$.	$(\theta = \{\vartheta_E, \vartheta_G\}$ when considering the dis-
9: Compute reward r_t for policy π_μ using (5).	entanglement).
10: Update policy π_μ to maximize r_t with SAC.	20: Update ϑ_E and ϑ_D by maximizing *Dis_loss*
	in (8) using SGD.
11: Update discriminator (q_ϕ) to maximize	21: **end for**
$\log q_\phi(\omega | s_{t+1})$ with SGD.	22: **end while**
12: **end for**	

According to the objective function $\mathcal{J}(\mu, \phi, \theta)$ in (3), we propose an alternating optimization between π_μ and π_θ as follows:

Step I: Fix π_θ and update π_μ and q_ϕ. In this case, θ is not a variable to update and $\mathcal{J}(\mu, \phi, \theta)$ becomes

$$\mathcal{J}(\mu, \phi) = \mathbb{E}_{\omega, s} \left[\log q_\phi(\omega | s) \right] + \underbrace{\mathbb{E}_{\omega, \tilde{s}} \left[\log q_\phi(\omega | \tilde{s}) - 2 \log p(\omega) \right]}_{\text{Variable independent term}}. \tag{4}$$

According to (4), $\mathcal{J}(\mu, \phi)$ can be thus optimized by setting the reward at time step t for π_μ as

$$r_t = \log q_\phi(\omega | s_{t+1}) - \log p(\omega), \tag{5}$$

where the term $- \log p(\omega)$ is added for agents to avoid artificial termination and reward-hacking issues (Amodei et al., 2016). We implement this optimization with soft actor-critic (SAC). On the other hand, the reward network q_ϕ can be updated with SGD by maximizing $\mathbb{E}_{\omega, s} \left[\log q_\phi(\omega | s) \right]$.

Step II: Fix π_μ and q_ϕ to update π_θ. In this case, μ and ϕ are not variables to update any more and $\mathcal{J}(\mu, \phi, \theta)$ can be simplified as

$$\mathcal{J}(\theta) = \mathbb{E}_{\omega, \tilde{s}} \left[\log q_\phi(\omega | \tilde{s}) \right] + \underbrace{\mathbb{E}_{\omega, s} \left[\log q_\phi(\omega | s) - 2 \log p(\omega) \right]}_{\text{Variable independent term}}. \tag{6}$$

According to (6), $\mathcal{J}(\theta)$ can thus be optimized by setting the reward at time step t for π_θ as

$$\tilde{r}_t = \log q_\phi(\omega | \tilde{s}_{t+1}) - \log p(\omega), \tag{7}$$

where the term $- \log p(\omega)$ is added for the same reason as above and we also implement this optimization with SAC. These two steps are performed alternately until convergence. The overall GPIM is summarized in Algorithm 1, which includes the disentanglement (*red*) in the next subsection.

3.3 IMPROVE GENERALIZATION VIA DISENTANGLEMENT

The goal g_t can be further disentangled (Higgins et al., 2017a) so as to improve the generalization ability of goal-conditioned policy π_θ. As shown in Fig. 3, we decompose π_θ into two components: the encoder network E parameterized by ϑ_E and the generative network G parameterized by ϑ_G. So we have $\pi_\theta(\tilde{a}_t | \tilde{s}_t, g_t) = p_{\vartheta_G}(\tilde{a}_t | \tilde{s}_t, q_{\vartheta_E}(z | g_t))$.

Figure 3: Disentanglement of policy π_θ.

To encourage this disentangling property in the inferred $q_{\vartheta_E}(z | g_t)$, we adopt an prior $p(z) \sim N(0; I)$ to control the capacity of the information bottleneck by minimizing the KL divergence between $q_{\vartheta_E}(z | g_t)$ and $p(z)$. Hence, the overall objective function of goal-conditioned policy π_θ becomes

$$\max_{\vartheta_E, \vartheta_G, \vartheta_D} \quad \mathbb{E}_{\omega, \tilde{s}_t}[\tilde{r}_t] + \underbrace{\alpha \cdot \mathbb{E}_{g_t, z}[p_{\vartheta_D}(g_t|z)] - \beta \cdot \mathbb{E}_{g_t}[KL(q_{\vartheta_E}(z|g_t)||p(z))]}_{\triangleq Dis\_loss}, \qquad (8)$$

where α and β are two hyperparameters. It is worth noting that the update of the encoder E is based on gradients from both π_θ and Dis_loss. With this disentanglement, the overall GPIM method is given in Algorithm 1 as mentioned above.

4 RELATED WORK

Investigating goal distribution: Many prior methods (Schaul et al., 2015; Andrychowicz et al., 2017; Pong et al., 2018; Hartikainen et al., 2019) assume an available distribution of goals during exploration for sparse-reward problems, where the resampled goals are restricted to states encountered along the trajectory (Andrychowicz et al., 2017; Levy et al., 2017) or in an embedding space (Nair et al., 2018). The setting of goals for learning policy has been discussed in Baranes & Oudeyer (2013). Recently, several works (Colas et al., 2018; Warde-Farley et al., 2018; Florensa et al., 2019; Nair et al., 2018; Péré et al., 2018) adopt heuristics to design a goal distribution based on previously visited states. However, many of these (Nair et al., 2018; Pong et al., 2019; Warde-Farley et al., 2018) assume an ideal matching of the goal space with the state space.

Learning goal-conditioned policy: Several recent works propose various methods for agents to automatically learn policies by maximizing the mutual information between behaviors (e.g., latent variables) and tasks (e.g., goals). DISCERN (Warde-Farley et al., 2018) simultaneously learns a goal-conditioned policy and a goal achievement reward function that measures how similar a state is to the goal state. Pong et al. (2019) concurrently trains a goal-reaching policy and maximizes the entropy of the generated goal distribution. Given the difficulty of vision-based RL, Pong et al. (2019) resorts to RIG (Nair et al., 2018), which obtains reward using prior non-parametric measure function in embedding spaces. Other unsupervised methods (Sharma et al., 2019; Campos et al., 2020), capable of learning diverse skills, are difficult to apply directly to user-specified tasks.

Learning disentanglement representation: Many prior works utilize unsupervised learning in RL to acquire disentanglement representation (Bengio et al., 2013; Higgins et al., 2017a; Chen et al., 2016; Burgess et al., 2018). Some works take the disentanglement representation as a substitute for states (Higgins et al., 2017b; Ha & Schmidhuber, 2018; Jonschkowski et al., 2017; Finn et al., 2016; Lange et al., 2012; Watter et al., 2015; Srinivas et al., 2018; Nair et al., 2019; Srinivas et al., 2018) while others consider a non-parametric metric in a latent space to acquire a reward function (Nair et al., 2018; Sermanet et al., 2018). Besides, a few works directly embed manipulation tasks to generalize to long-horizon tasks (Goyal et al., 2019; Hausman et al., 2018; Mandlekar et al., 2020).

Hindsight, self-play and knowledge distillation: Our method is similar in spirit to goal relabeling methods like hindsight experience replay (HER) (Andrychowicz et al., 2017) which replays each episode with a different goal in addition to the one the agent was trying to achieve. However, HER requires a prior reward function and a hand-crafted goal space. By contrast, GPIM is unsupervised and able to find its own goal space. The self-play (Sukhbaatar et al., 2017; 2018) is closely related to our scheme, leading to emergent autocurricula by pitting two versions of the same agent against one another. However, these approaches generally require prior reward functions. As for knowledge distillation (Xu et al., 2020), we aim at extracting the relationship between two different tasks.

5 EXPERIMENTS

Extensive experiments are conducted to evaluate our proposed GPIM method, where the following four questions[2] will be considered: 1) By using "archery" task, we clarify whether q_ϕ can provide an effective reward function on learning goal-conditioned policy π_θ. Furthermore, more complex tasks including navigation, object manipulation, atari games, and mujoco tasks are introduced to answer: 2) Does our model learn effective behaviors conditioned on a variety of goals, including high-dimensional images and text descriptions that are heterogeneous to states? 3) Does the proposed GPIM on learning a goal-conditioned policy outperform baselines? 4) How does the disentanglement of goals in GPIM affect the learned behaviors in terms of the generalization to new tasks? Video is available under https://sites.google.com/view/gpim.

---

[2]Due to the page limitation, more experimental analysis and results are included in the Appendix.

(a) 2D navigation (b) Object manipulation (c) Atari games

(d) Swimmer (e) Half cheetah (f) Fetch

Figure 5: Goals and learned behaviors by GPIM: Dots in 2D navigation (left subfigure, x-y goal) and atari games denote different final goal states, and curves with same color represent corresponding trajectories; Goals in 2D navigation (right subfigure, color-shape goal) and object manipulation are described using the text at the top of the diagram, where the purple lines imply the behaviors; In mujoco tasks, the first (swimmer, half cheetah and fetch) and third (swimmer and half cheetah) rows represent the expert trajectories, and the row below represents the corresponding behavior.

Visualizing the learned reward function. We start with simple "archery" task to visualize how the learned reward function (discriminator q_ϕ) accounts for goal-conditioned behaviors in dynamics. The task shown in Fig. 4 requires choosing an angle at which we shoot an arrow to the target. The left upper subfigure shows that in a deterministic environment, given three different but fixed targets (with different colors), the arrow reaches the corresponding target

Figure 4: "Archery" tasks and learned rewards.

successfully under the learned reward function q_ϕ. The reward as a function of the final location of arrows in three tasks is shown on the right. We can find that the learned reward functions resemble convex in terms of the distance between final states to targets, where vertexes appear in the positions of the corresponding targets. Specifically, the maximum value of the learned reward function is achieved when the final state is close to the given target. The farther away the agent's final state is from the target, the smaller this reward value is. Similarly, the same conclusion can be drawn from the stochastic environment in the left lower subfigure, where the angle of the arrow has a 50% chance to become a mirror-symmetric angle. We see that the learned reward function substantially describes the dynamics and the corresponding tasks, both in deterministic and stochastic environments. This answers our *first* question.

Scaling to more complex tasks. To answer our *second* question, we now consider more complex tasks as shown in Fig. 5. 1) In *2D navigation tasks*, an agent can move in each of the four cardinal directions. We consider the following two tasks: moving the agent to a specific coordinate named *x-y goal*[3] and moving the agent to a specific object with certain color and shape named *color-shape goal*. 2) *Object manipulation* considers a moving agent in 2D environment with one block for manipulation, and the other block as a distractor. The agent first needs to reach the block and then move the block to the given location, where the block is described using color and shape. In other words, the description of the goal contains the *color-shape goal* of real block and the *x-y goal* of the target coordinate. 3) Three *atari games* including seaquest, berzerk and montezuma revenge require an agent to reach the given final states. 4) We use three *mujoco tasks* (swimmer, half cheetah, and fetch) taken from OpenAI GYM (Brockman et al., 2016) to fast imitate given expert trajectories. Specifically, the goals for π_θ in 2D navigation, object manipulation and atari games are the rendered final state s_T induced by abstract-level policy π_μ: $g_t = Render(s_T)$, and the goals for π_θ in mujoco tasks are the rendered trajectories induced by π_μ: $\{g_0, g_1, ...\} = Render(\{s_1, s_2, ...\})$.

---

[3]Definitions of *x-y goal*, *color-shape goal*, and environment details are given in Appendix E.

Figure 7: Performance of our GPIM and three baselines, where GPIM generally achieves smaller distances to goals in comparison to baselines.

The left subfigure of Fig. 5(a) shows the learned behaviors of navigation in continuous action space given the x-y goal which is denoted as the small circle, and the right subfigure shows the trajectory of behavior with the given color-shape goal. More results on discrete navigation can be found in Appendix I. As observed, the agent manages to learn navigation tasks by using GPIM. Further, 2D navigation with color-shape goal (Fig. 5(a) *right*) and object manipulation tasks (Fig. 5(b)) show the effectiveness of our model facing heterogeneous goals and states. Specifically, Fig. 5(b) shows the behaviors of the agent on object manipulation, where the agent is asked to first arrive at a block (i.e., blue circle and green square respectively) and then push it to the given location inside a dark circle (i.e., [6.7, 8.0] and [4.8, 7.9] respectively), where the red object exists as a distractor. Fig. 5(c) shows the behaviors of agents that reach the final states in a higher dimensional (action, state and goal) space on seaquest, berzerk and montezuma revenge respectively. Fig. 5(d-f) shows how the agent imitates expert trajectories of swimmer, half cheetah and fetch.

Solving complex temporally-extended tasks is a long-standing RL problem (Jiang et al., 2019). For this purpose, we further make agents imitate the given composite behaviors (i.e., expert behaviors) and show their performance in Fig. 6. Specifically, we consider the fetch task as in Fig. 5(f), where the gripper of the robot arm is used to render a series of 3D coordinates as goals for imitation in training phase. During test, we employ two parameterized complex

Figure 6: Expert behaviors and learned behaviors.

curves for the gripper to follow: $(x, y, z) = (t \sin(t)/50, t \cos(t)/50 - 1/50, -\log(t+1)/5)$ (left) and $(x, y, z) = (t/5, \cos(t)/5 - 1/5, \sin(t)/5)$ (right). It is worth noting that during training the agent is required to imitate a large number of simple behaviors and has never seen such complex goals before testing. It is observed from Fig. 6 that the imitation curves are almost overlapping with the given expert trajectories, indicating that the agent using GPIM has the potential to learn such compositional structure of goals during training and generalize to new composite goals during test.

Comparison with baselines. For the *third* question, we compare our method to three baselines: **RIG** (Nair et al., 2018), **DISCERN** (Warde-Farley et al., 2018), and **L2 Distance**. L2 Distance measures the distance between states and goals, where the $L2$ distance $-||s_t - s_g||^2/\sigma_{pixel}$ is considered with a hyperparameter σ_{pixel}. Note that 2D navigation with the color-shape goal and object manipulation using text description makes the dimensions of states and goals different, so L2 cannot be used in these two tasks. In RIG, we obtain rewards by using the distances in two embedding spaces and learning two independent VAEs, where one VAE is to encode states and the other is to encode goals. We use the normalized distance to goals [4] as the evaluation metric, where we randomly sampled 50 samples (tasks) from the goal space.

We show the results in Fig. 7 by plotting the normalized distance to goals as a function of the number of actor's steps, where each curve considers 95% confidence interval in terms of the mean value across three seeds. As observed, our GPIM consistently outperforms baselines in almost all tasks

---

[4]Definition and further descriptions can be found in Appendix F.

except for the RIG in 2D navigation (x-y goal) due to the simplicity of this task. Particularly, as the task complexity increases from 2D navigation (x-y goal) to 2D navigation (color-shape goal) until object manipulation (mixed x-y goal and color-shape goal), GPIM converges faster than baselines and the performance gap between our GPIM and baselines becomes larger. Moreover, although RIG learns fast on navigation with x-y goal, it fails to accomplish complex navigation with color-shape goal because the embedding distance between two independent VAEs has difficulty in capturing the correlation of heterogeneous states and goals. Especially in high-dimensional action space and on more exploratory tasks (atari and mujoco tasks), our method substantially outperforms the baselines.

To gain more intuition for our method, we record the distance (Δr) between the final state induced by π_θ and the goal rendered by π_μ throughout the training process of the 2D navigation (x-y goal). For this purpose, in this specific experiment, we update π_μ and q_ϕ but ignore the update of π_θ before 200 k steps to show the exploration of π_μ at the abstract level. As shown in Fig. 8, Δr steadily increases during the first 200 k steps, indicating that the abstract-level policy π_μ explores the environment (i.e., goal space) to distinguish skills more easily,

Figure 8: Abstract-level policy π_μ gradually explores the environment, generating more difficult goals. q_ϕ encourages π_θ to gradually mimic π_μ.

and as a result, generates diverse goals for training π_θ. After around 1.5 M training steps, Δr almost comes to 0, indicating that the goal-conditioned policy π_θ has learned a good strategy to reach the rendered goals. In Appendix B, we visually show the generated goals at the abstract level in more complex tasks and compare them with baselines, which shows our straightforward framework can effectively explore the environment without additional sophisticated exploration strategies[5].

Ablation study. To answer the *forth* question on how the disentanglement affect the learned behaviors, we conduct the ablation study on 2D navigation task (see results on mujoco tasks in Appendix C). For convenience, we remove certain component from GPIM and define the new method as follows: *w/o Rec* - removing the reconstruction loss (i.e. $\alpha = 0$); *w/o KL* - removing the KL loss (i.e. $\beta = 0$); *w/o Pol* - removing the policy loss updating ϑ_E as shown in Fig. 3.

Figure 9: Ablation study and disentanglement.

The performance is reported in Fig. 9. It is observed that *w/o. Pol* performs worse than all other methods, which is consistent with the performance of RIG that trains VAE and policy separately. The main reason is that the disentanglement fails to figure out the required latent factors on given tasks. Moreover, although GPIM has a similar performance with the other three methods on 2D navigation task, GPIM has better interpretability to behaviors. As shown at the bottom of Fig. 9, considering a series of goals from the first red to the last green (*left*) in a counterclockwise order, GPIM can successfully disentangle them and learn effective latent z (*right*), but *w/o KL* fails to keep the original order of goals (*middle*). By learning to reach diverse goals generated by the abstract-level policy and then disentangling the goals, the agent learns the ability to infer new goals later encountered by the agent. For example, as in Fig. 5(a) (*right*), learning three behaviors with the goal of red-square, red-circle or blue-square in a gray background makes the agent accomplish the new goal of blue-circle in a white background. More experiments to show the generalization of the goal-conditioned policy to unseen goals can be found in Appendix D.

6 CONCLUSION

We propose a novel GPIM method to learn goal-conditioned policy in an unsupervised manner. Specifically, the goal-conditioned policy is learned by sharing the intrinsic reward with an abstract-level policy, where the abstract-level policy also provides diverse but distinguishing goals for the goal-conditioned policy. Experiments on a variety of robotic tasks demonstrate the effectiveness and efficiency of our proposed method which substantially outperforms prior unsupervised techniques.

---

[5]We leave extensions combing sophisticated exploration strategies as future work.

REFERENCES

Joshua Achiam, Harrison Edwards, Dario Amodei, and Pieter Abbeel. Variational option discovery algorithms. *arXiv preprint arXiv:1807.10299*, 2018.

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in ai safety. *arXiv preprint arXiv:1606.06565*, 2016.

Marcin Andrychowicz, Filip Wolski, Alex Ray, Jonas Schneider, Rachel Fong, Peter Welinder, Bob McGrew, Josh Tobin, OpenAI Pieter Abbeel, and Wojciech Zaremba. Hindsight experience replay. In *Advances in neural information processing systems*, pp. 5048–5058, 2017.

Arthur Aubret, Laetitia Matignon, and Salima Hassas. A survey on intrinsic motivation in reinforcement learning. *arXiv preprint arXiv:1908.06976*, 2019.

Adria Puigdomenech Badia, Bilal Piot, Steven Kapturowski, Pablo Sprechmann, Alex Vitvitskyi, Daniel Guo, and Charles Blundell. Agent57: Outperforming the atari human benchmark. *arXiv preprint arXiv:2003.13350*, 2020.

Adrien Baranes and Pierre-Yves Oudeyer. Active learning of inverse models with intrinsically motivated goal exploration in robots. *Robotics and Autonomous Systems*, 61(1):49–73, 2013.

David Barber and Felix V Agakov. The im algorithm: a variational approach to information maximization. In *Advances in neural information processing systems*, pp. None, 2003.

Normand J Beaudry and Renato Renner. An intuitive proof of the data processing inequality. *arXiv preprint arXiv:1107.0740*, 2011.

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.

Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemyslaw Debiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*, 2019.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym, 2016.

Christopher P Burgess, Irina Higgins, Arka Pal, Loic Matthey, Nick Watters, Guillaume Desjardins, and Alexander Lerchner. Understanding disentangling in beta-vae. *arXiv preprint arXiv:1804.03599*, 2018.

Victor A. Campos, A. Trott, Caiming Xiong, R. Socher, Xavier Giro i Nieto, and J. Torres. Explore, discover and learn: Unsupervised discovery of state-covering skills. *ArXiv*, abs/2002.03647, 2020.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *Advances in neural information processing systems*, pp. 2172–2180, 2016.

John D Co-Reyes, YuXuan Liu, Abhishek Gupta, Benjamin Eysenbach, Pieter Abbeel, and Sergey Levine. Self-consistent trajectory autoencoder: Hierarchical reinforcement learning with trajectory embeddings. *arXiv preprint arXiv:1806.02813*, 2018.

Cédric Colas, Olivier Sigaud, and Pierre-Yves Oudeyer. Gep-pg: Decoupling exploration and exploitation in deep reinforcement learning algorithms. *arXiv preprint arXiv:1802.05054*, 2018.

Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. *arXiv preprint arXiv:1802.06070*, 2018.

Chelsea Finn, Xin Yu Tan, Yan Duan, Trevor Darrell, Sergey Levine, and Pieter Abbeel. Deep spatial autoencoders for visuomotor learning. In *2016 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 512–519. IEEE, 2016.

Carlos Florensa, Jonas Degrave, Nicolas Heess, Jost Tobias Springenberg, and Martin Ried-miller. Self-supervised learning of image embedding for continuous control. *arXiv preprint arXiv:1901.00943*, 2019.

Anirudh Goyal, Riashat Islam, Daniel Strouse, Zafarali Ahmed, Matthew Botvinick, Hugo Larochelle, Yoshua Bengio, and Sergey Levine. Infobot: Transfer and exploration via the in-formation bottleneck. *arXiv preprint arXiv:1901.10902*, 2019.

Karol Gregor, Danilo Jimenez Rezende, and Daan Wierstra. Variational intrinsic control. *arXiv preprint arXiv:1611.07507*, 2016.

David Ha and Jürgen Schmidhuber. World models. *arXiv preprint arXiv:1803.10122*, 2018.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*, 2018.

Kristian Hartikainen, Xinyang Geng, Tuomas Haarnoja, and Sergey Levine. Dynamical distance learning for semi-supervised and unsupervised skill discovery. In *International Conference on Learning Representations*, 2019.

Karol Hausman, Jost Tobias Springenberg, Ziyu Wang, Nicolas Heess, and Martin Riedmiller. Learning an embedding space for transferable robot skills. 2018.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. *Iclr*, 2(5):6, 2017a.

Irina Higgins, Arka Pal, Andrei Rusu, Loic Matthey, Christopher Burgess, Alexander Pritzel, Matthew Botvinick, Charles Blundell, and Alexander Lerchner. Darla: Improving zero-shot trans-fer in reinforcement learning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 1480–1490. JMLR. org, 2017b.

Yiding Jiang, Shixiang Shane Gu, Kevin P Murphy, and Chelsea Finn. Language as an abstrac-tion for hierarchical deep reinforcement learning. In *Advances in Neural Information Processing Systems*, pp. 9419–9431, 2019.

Rico Jonschkowski, Roland Hafner, Jonathan Scholz, and Martin Riedmiller. Pves: Position-velocity encoders for unsupervised learning of structured state representations. *arXiv preprint arXiv:1705.09805*, 2017.

Rawal Khirodkar, Donghyun Yoo, and Kris M Kitani. Vadra: Visual adversarial domain randomiza-tion and augmentation. *arXiv preprint arXiv:1812.00491*, 2018.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Sascha Lange, Martin Riedmiller, and Arne Voigtländer. Autonomous reinforcement learning on raw visual input data in a real world application. In *The 2012 international joint conference on neural networks (IJCNN)*, pp. 1–8. IEEE, 2012.

Youngwoon Lee, Shao-Hua Sun, Sriram Somasundaram, Edward S Hu, and Joseph J Lim. Com-posing complex skills by learning transition policies. In *International Conference on Learning Representations*, 2018.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tuto-rial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

Andrew Levy, George Konidaris, Robert Platt, and Kate Saenko. Learning multi-level hierarchies with hindsight. *arXiv preprint arXiv:1712.00948*, 2017.

Kendall Lowrey, Aravind Rajeswaran, Sham Kakade, Emanuel Todorov, and Igor Mordatch. Plan online, learn offline: Efficient learning and exploration via model-based control. *arXiv preprint arXiv:1811.01848*, 2018.

Ajay Mandlekar, Danfei Xu, Roberto Martín-Martín, Silvio Savarese, and Li Fei-Fei. Learning to generalize across long-horizon tasks from human demonstrations. *arXiv preprint arXiv:2003.06085*, 2020.

Ashvin Nair, Shikhar Bahl, Alexander Khazatsky, Vitchyr Pong, Glen Berseth, and Sergey Levine. Contextual imagined goals for self-supervised robotic learning. *arXiv preprint arXiv:1910.11670*, 2019.

Ashvin V Nair, Vitchyr Pong, Murtaza Dalal, Shikhar Bahl, Steven Lin, and Sergey Levine. Visual reinforcement learning with imagined goals. In *Advances in Neural Information Processing Systems*, pp. 9191–9200, 2018.

Alexandre Péré, Sébastien Forestier, Olivier Sigaud, and Pierre-Yves Oudeyer. Unsupervised learning of goal spaces for intrinsically motivated goal exploration. *arXiv preprint arXiv:1803.00781*, 2018.

Vitchyr Pong, Shixiang Gu, Murtaza Dalal, and Sergey Levine. Temporal difference models: Model-free deep rl for model-based control. *arXiv preprint arXiv:1802.09081*, 2018.

Vitchyr H Pong, Murtaza Dalal, Steven Lin, Ashvin Nair, Shikhar Bahl, and Sergey Levine. Skew-fit: State-covering self-supervised reinforcement learning. *arXiv preprint arXiv:1903.03698*, 2019.

Ivaylo Popov, Nicolas Heess, Timothy Lillicrap, Roland Hafner, Gabriel Barth-Maron, Matej Vecerik, Thomas Lampe, Yuval Tassa, Tom Erez, and Martin Riedmiller. Data-efficient deep reinforcement learning for dexterous manipulation. *arXiv preprint arXiv:1704.03073*, 2017.

Martin L Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

Christoph Salge, Cornelius Glackin, and Daniel Polani. Empowerment–an introduction. In *Guided Self-Organization: Inception*, pp. 67–114. Springer, 2014.

Tom Schaul, Daniel Horgan, Karol Gregor, and David Silver. Universal value function approximators. In *International conference on machine learning*, pp. 1312–1320, 2015.

Pierre Sermanet, Corey Lynch, Yevgen Chebotar, Jasmine Hsu, Eric Jang, Stefan Schaal, Sergey Levine, and Google Brain. Time-contrastive networks: Self-supervised learning from video. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1134–1141. IEEE, 2018.

Archit Sharma, Shixiang Gu, Sergey Levine, Vikash Kumar, and Karol Hausman. Dynamics-aware unsupervised discovery of skills. *arXiv preprint arXiv:1907.01657*, 2019.

Aravind Srinivas, Allan Jabri, Pieter Abbeel, Sergey Levine, and Chelsea Finn. Universal planning networks. *arXiv preprint arXiv:1804.00645*, 2018.

Sainbayar Sukhbaatar, Zeming Lin, Ilya Kostrikov, Gabriel Synnaeve, Arthur Szlam, and Rob Fergus. Intrinsic motivation and automatic curricula via asymmetric self-play. *arXiv preprint arXiv:1703.05407*, 2017.

Sainbayar Sukhbaatar, Emily Denton, Arthur Szlam, and Rob Fergus. Learning goal embeddings via self-play for hierarchical reinforcement learning. *arXiv preprint arXiv:1811.09083*, 2018.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 23–30. IEEE, 2017.

Mel Vecerik, Oleg Sushkov, David Barker, Thomas Rothörl, Todd Hester, and Jon Scholz. A practical approach to insertion with variable socket position using deep reinforcement learning. In *2019 International Conference on Robotics and Automation (ICRA)*, pp. 754–760. IEEE, 2019.

David Warde-Farley, Tom Van de Wiele, Tejas Kulkarni, Catalin Ionescu, Steven Hansen, and Volodymyr Mnih. Unsupervised control through parametric discriminative rewards. *arXiv preprint arXiv:1811.11359*, 2018.

Manuel Watter, Jost Springenberg, Joschka Boedecker, and Martin Riedmiller. Embed to control: A locally linear latent dynamics model for control from raw images. In *Advances in neural information processing systems*, pp. 2746–2754, 2015.

Guodong Xu, Ziwei Liu, Xiaoxiao Li, and Chen Change Loy. Knowledge distillation meets self-supervision. *arXiv preprint arXiv:2006.07114*, 2020.

Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 586–595, 2018.

A   ADDITIONAL EXPERIMENT: COMPARISON WITH DIAYN VARIANTS

In this section, we expect to clarify the difference and connection with DIAYN (Eysenbach et al., 2018) experimentally, and indicate the limitations of maximizing $\mathcal{I}(s; \omega)$ and maximizing $\mathcal{I}(s; g)$ separately on learning goal-conditioned policy.

(a) DIAYN-Imitator: $\mathcal{I}(s; \omega)$.   (b) DIAYN-Goal: $\mathcal{I}(s; g)$.   (c) GPIM: $\mathcal{I}(s; \omega) + \mathcal{I}(s; g)$

Figure 10: 2D navigation with (a) DIAYN-Imitator, (b) DIAYN-Goal, and (c) our proposed GPIM. In (a), (b) and (c-left), the open circle denotes the user-specified goal, and the line with a solid circle at the end is the corresponding behavior. Specifically, the white lines in (a) are the learned skills in training, where we show 10 diverse skills. We can see that neither DIAYN-Imitator nor DIAYN-Goal approaches the corresponding goals, while our model succeeds in reaching the goal as shown in (c-left). In (c-right), we also show the generative factor z by disentangling goals in (c-left), where the open circles with different colors in (c-right) correspond to the goals in (c-left).

In DIAYN, authors show the ability of the model to imitate an expert. Given the goal, DIAYN uses the learned discriminator to estimate which skill was most likely to have generated the goal g:

$$\hat{\omega} = \arg \max_{\omega} q_\phi(\omega|g). \tag{9}$$

Here we call this model *DIAYN-Imitator*. We also directly substitute the perceptually-specific goals for the latent variable in DIAYN's objective to learn a goal-conditioned policy. We call this model *DIAYN-Goal*:

$$\max \ \mathcal{I}(s; g), \tag{10}$$

where g is sampled from the prior goal distribution $p(g)$. Please note that we do not adopt the prior non-parametric distance as in DISCERN (Warde-Farley et al., 2018) to calculate the reward. We obtain the reward as in normal DIAYN using the variational inference: $r_t = q_\phi(g_t|s_{t+1})$.

Fig. 10 shows the comparison of our GPIM with DIAYN variants including DIAYN-Imitator and DIAYN-Goal, where the 2D navigation task is considered. As observed, DIAYN-Imitator can reach seen goals but not unseen goals in Fig. 10(a), because it cannot effectively accomplish the interpolation between skills that are induced in training. And behaviors generated by DIAYN-Goal cannot guarantee consistency with the preset goals in Fig. 10(b). The main reason is that this objective only ensures that when g (or ω) is different, the states generated by g (or ω) are different. However, there is no guarantee that g (or ω) and the state generated by the current g (or ω) have semantically consistent behavior information. Our proposed GPIM method, capable of solving interpolation and consistency issues, exhibits the best performance in this 2D navigation task.

Moreover, when the user-specified goals are heterogeneous to the states, the learned discriminator q_ϕ in DIAYN is unable to estimate which skill is capable of inducing given goals. Specifically, when the goals are visual inputs, and the states in training is feature vectors (e.g., joint angles), the learned discriminator is unable to choose the skills due to a lack of models for converting high-dimensional figure into low-dimensional feature vectors. On the contrary, there are lots of off-the-shelf models to render low-dimensional feature vectors into perceptually-specific high-dimensional inputs (Tobin et al., 2017; Khirodkar et al., 2018).

B   AUTOMATED GOAL-GENERATION FOR EXPLORATION

In general, for unsupervised RL, we would like to ask the agent to carry out autonomous "practice" during training phase, where we do not know which particular goals will be provided in test phase. In order to maximize the state coverage, the ability to automatically explore the environment and discover diverse goals is crucial. In this section, we will further analyze the goal distribution of

(a) Decoded latent goals (RIG).

(b) Goals (DISCERN).   (c) Goals (GPIM).   (d) Performance.

Figure 11: Distribution of sampled goals for the goal-conditioned policy, where the initial state is [5,2] (the red star) and the actor step is 20 for each rollout. (a) The goals (images) are obtained by decoding 30 sampled latent goals z_g in VAE framework; (b) The goals (colored dots) are sampled from the agent's behaviors by random exploration; (c) The goals (colored dots) are rendered from the states induced by our abstract-level policy. (d): Evaluation on reaching user-specified goals, where GPIM significantly outperforms baselines.

three methods (RIG (Nair et al., 2018), DISCERN (Warde-Farley et al., 2018), GPIM) in a new 2D obstacle navigation task as shown in Fig. 11(a), Fig. 11(b), and Fig. 11(c). The size of the environment is 10×10, the initial state is set as $[5, 2]$, and there are two obstacles that prevent the agent from passing through each of which is 3×6 in size.

DISCERN samples goals during training by maintaining a fixed sized buffer $\mathcal{G}$ of past observations. We simply mimic the process of goal generation by taking random actions for 20 environment steps after initialization of the method. As in Fig. 11(b), we generate 100 goals with different colors. We can see that the majority of goals locate between the two obstacles, which limits the further exploration of the environment.

RIG samples a representation (latent goals z_g) from the learned VAE prior, which represents a distribution over latent goals and state observation. The policy network takes the representation as a substitute for the user-specified goal. For a clear visualization of the distribution of the sampled latent goals, we further feed the sampled latent goals into the decoder to obtain the real goals in the user-specified space. The decoded latent goals are shown in Fig. 11(a), where we sample 30 goals. It is shown that the majority of goals are also between the two obstacles because the goals for training the VAE prior come from the same distribution as in DISCERN.

Our method, GPIM, obtains goals from the behaviors induced by the abstract-level policy. Maximizing $\mathcal{I}(s; \omega)$ encourages different skills to induce different states that are further rendered to goals. This objective ensures that each skill individually is distinct and the skills collectively explore large parts of the state space (Eysenbach et al., 2018). As shown in Fig. 11(c), our method provides better coverage of the state space than DISCERN and RIG.

Fig. 11(d) shows the performance of the three methods, where we randomly sample goals from the whole state (or goal) space at test phase. We can see that our method significantly outperforms the baselines. The most common failure mode for prior methods is that the goal distribution collapses (Pong et al., 2019), causing that the agent can reach only a fraction of the state space, as shown in Fig. 11(a) and 11(b).

Exploration is a well-studied problem in the field of RL, and there are many proven approaches with different benefits to improve the exploration (Colas et al., 2018; Campos et al., 2020). Note that these benefits are orthogonal to those provided by our straightforward GPIM, and these approaches could be combined with GPIM for even greater effect. We leave combing our method with sophisticated exploration strategies to future work.

C ABLATION STUDY ON MUJOCO TASKS

Figure 12: Ablation study on mujoco tasks.

We further study the impact of disentanglement part in our framework. The performance is reported in Fig. 12. It is observed that *w/o Pol* performs worse than all other methods, which is consistent with the performance in 2D navigation task[6]. And we can find that when we remove the reconstruction loss ($\alpha = 0$), the performance of *w/o Rec* degrades in these three environments. The main reason is that the process of learning generative factors become more difficult without the supervised reconstruction loss. While in 2D navigation task, the reconstruction loss has little impact on the performance. Even though that *w/o KL* has a similar performance with our full GPIM method, GPIM demonstrates better interpretability to behaviors as shown in Fig. 10(c).

D GENERALIZATION ON THE GRIDWORLD TASK

Here we show the generalization in the gridworld task, we introduce an illustrative example of gridworld task and then show the generalization when the dynamics and goal conditions are missing in the gridworld task.

Illustrative example. We start with a simple gridworld example: the environment is shown on the left of Fig. 13, where the goal for the agent is to navigate from the middle to the given colored room. By abstract-level training, our method quickly acquire four skills to reach different rooms. Each time the agent arrives in a room induced by π_μ, we train π_θ conditioned on the room's color (e.g., green), allowing the agent to be guided to the same room by the current reward function. The learning process is shown on the right of Fig. 13. It is concluded that the agent can automatically learn how to complete tasks given semantic goals in an unsupervised manner.

Figure 13: Gridworld tasks. Y-axis is the percentage of different rooms that the robot arrives in.

Generalization on the gridworld task. We further show the generalization when the dynamics and goal conditions are missing in the gridworld task, where there are four rooms in different colors: blue, green, orange and magenta. We consider the situation where we train the goal-conditioned policy in the blue room, the green room and the orange room, and test in the magenta room.

---

[6]The results of 2D navigation task are shown in the full paper.

Figure 14: Gridworld tasks. The Y-axis is the percentage of different rooms that agent arrives in.

As shown in Fig. 14, we quickly acquire four skills for different rooms through the training at the abstract level. After the agent reaches at the colored rooms, we rendered the corresponding room as a two-bit representation: *Render('blue')* $= 10$, *Render('green')* $= 00$, and *Render('orange')* $= 01$; we do not render the magenta room. We take the magenta room corresponding to 11 as the test goal to verify the generalization ability.

In lower part of Fig. 14, we show the learning process of the goal-conditioned policy. We can find that the blue room tasks are learned quickly, and the green and magenta rooms are learned relatively slowly, but the agent is still able to complete the test task successfully (the magenta room). Compared to the task in Fig. 13 that renders all the rooms as goals, the whole learning process in Fig. 14 is much slower. We hypothesize that the main reason is that the agent needs to further infer the relationship between different goals. The lack of goal information (i.e., missing magenta 11) leads to a lower efficiency and unstable training.

E ENVIRONMENT DETAILS

We introduce the details of environments and tasks here, including the environment setting of 2D navigation (*x-y goal* and *color-shape goal*), object manipulation, three atari games (seaquest, berzerk and montezuma revenge), and the mujoco tasks (swimmer, half cheetah and fetch).

2D navigation tasks: In 2D navigation tasks, the agent moves in each of the four cardinal directions, where the states denote the 2D location of the agent. We consider the following two tasks: moving the agent to a specific coordinate named *x-y goal* and moving the agent to a specific object with certain color and shape named *color-shape goal*.

- **2D Navigation (*x-y goal*):** The size of the environment is 10×10 (continuous state space) or 7×7 (discrete state space). The state is the location of the agent, and the goal is the location of the final location.
- **2D Navigation (*color-shape goal*):** The size of the environment is 10×10. The state consists of the locations of the agent and three objects with different color-shape pairs (one real target and two distractors). The goal is described by the color and shape of the real target, encoded with one-hot.

Object manipulation: More complex manipulation considers a moving agent in 2D environment with one block for manipulation, and the other as a distractor. The agent first needs to reach the block and then move the block to the given location, where the block is described using color and shape. The size of the environment is 10×10. The state consists of the locations of the agent and two blocks with different color-shape pairs (one real target and one distractor). The goal consists of the one-hot encoding of the color-shape of the target block that needs to be moved, and the 2D coordinate of the final location of the movement.

Atari games: We test the performance on three atari games: seaquest, berzerk, and montezuma revenge. In order to reduce the difficulty of training, we adopt the RAM-environment (i.e., Seaquest-ram-v0, Berzerk-ram-v0, and MontezumaRevenge-ram-v0), where each state represents a 128-dimensional vector. Each action repeatedly performs for a duration of k frames, where k is uniformly sampled from Table 1.

Table 1: The repetition length of the action.

Environments	k
Seaquest-ram-v0	2, 3, 4, 5
Berzerk-ram-v0	34, 36, 38, 40
MontezumaRevenge-ram-v0	2, 3, 4, 5

Mujoco tasks: We consider to make diverse agents to fast imitate a given goal trajectory, including the imitation of behaviors of a swimmer, a half cheetah, and a fetch, where the states in the trajectory denote the positions of agents. Such experiments are conducted to demonstrate the effectiveness of our proposed method in learning behaviors over a continuous high-dimensional action space, which is more complicated in physics than the 2D navigation.

Note that the goals in all the experiments are images $50 \times 50 \times 3$ (3 channels, RGB) in size, except that the *color-shape goal* is encoded with one-hot.

F METRICS, NETWORK ARCHITECTURES AND HYPERPARAMETERS

Here we give a clear definition of our evaluation metric – "normalized distance to goal":

I: When the goal is to reach the final state of the trajectory induced by π_μ (Figs. 5(a), 5(b) and 5(c)), the distance to goal is the L2-distance between the final state $\tilde{s}^k_{T-1}$ induced by $\pi_\theta(\cdot|\cdot, g^k)$ and the goal state g^k randomly sampled from the goal (task) space:

$$Dis = \frac{1}{N} \sum_{k=1}^{N} L2(\tilde{s}^k_{T-1}, g^k),$$

where N is the number of testing samples. We set $N = 50$ for 2D navigation, object manipulation and atari games (seaquest, berzerk and montezuma revenge).

II: When the goal is to imitate the whole trajectory induced by π_μ (Figs. 5(d), 5(e) and 5(f)), the distance is the expectation of distance over the whole trajectory $\{\tilde{s}^k_0, \tilde{s}^k_1, ..., \tilde{s}^k_{T-1}\}$ induced by $\pi_\theta(\cdot|\cdot, \{g^k_0, g^k_1, ..., g^k_{T-1}\})$ and goal trajectory $\{g^k_0, g^k_1, ..., g^k_{T-1}\}$ randomly sampled from the trajectory (task) space:

$$Dis = \frac{1}{N} \sum_{k=1}^{N} \left(\frac{1}{T} \sum_{t=0}^{T-1} L2(\tilde{s}^k_t, g^k_t) \right),$$

where N is the number of testing samples. We set $N = 50$ for mujoco tasks (swimmer, half cheetah and fetch) .

The term "normalized" means that the distance is divided by a scale factor.

Note that, for three atari games (seaquest, berzerk, and montezuma revenge), the L2-distance for evaluation[7] is the difference between the position of controllable agent and the target's position, where the position is obtained by matching the pixel on the imaged state. See the Python code below.

```python
def obtainxy_seaquest(img):
  temp = np.where((img[:,:,0]==187)&(img[:,:,1]==187)&(img[:,:,2]==53))
  global seaquestxy
  if len(temp[0])==0:
    temp = seaquestxy
  else:
    seaquestxy = temp
  xy = np.array([np.mean(temp[0]), np.mean(temp[1])])/100
return xy
```

---

[7]The reward function for our baseline **L2 Distance** still calculates the L2-distance directly on the original state space, instead of the distance of the agents' positions after pixel matching here.

```python
def obtainxy_montezuma_revenge(img):
  img[:20] = 0
  temp = np.where((img[:,:,0]==200)&(imgo[:,:,1]==72)&(img[:,:,2]==72))
  global montezumaxy
  if len(temp[0])==0:
    temp = montezumaxy
  else:
    montezumaxy = temp
  xy = np.array([np.mean(temp[0]), np.mean(temp[1])])/100
return xy

def obtainxy_berzerk(img):
  temp = np.array(img)
  temp[1:-1, 1:-1] = temp[:-2, :-2]/3+temp[2:,2:]/3+temp[1:-1,1:-1]/3
  temp = np.where((temp[:,:,0]==240)&(temp[:,:,1]==170)&(temp[:,:,2]==103
                                                          ))
  global berzerkxy
  if len(temp[0])==0:
    temp = berzerkxy
  else:
    berzerkxy = temp
    xy = np.array([np.mean(temp[0]), np.mean(temp[1])])/100
  return xy
```

In our implementation, we use two independent SAC architectures (Haarnoja et al., 2018) for abstract-level policy π_μ and goal-conditioned policy π_θ. We find empirically that having two networks share a portion of the network structure will degrade the experimental performance. We adopt universal value function approximates (UVFAs) (Schaul et al., 2015) for extra input (goals). For the abstract-level policy π_μ, to pass latent variable ω to the Q function, value function, and policy, as in DIAYN, we simply concatenate ω with the current state s_t (and action a_t). For goal-conditioned policy π_θ, we also concatenate g_t with current state $\tilde{s}_t$ (and action $\tilde{a}_t$). We update the ϑ_E using the gradients from both the *Dis_loss* and Q function's loss of the goal-conditioned policy π_θ.

The hyper-parameters are presented in Table 2.

G BROADER IMPACT

The main concern in the research area of goal-conditioned policy is how to find numerous diverse goals as well as obtain the reward function. Particularly, in practical application, the goal and state are often heterogeneous data with high variability of data types and formats, which further aggravates the difficulty of policy learning. Our model addresses these problems by allowing agents to interact with objects or environment, and learn the behaviors in a fully autonomous way on the basis of intrinsic motivations. Bridging with the render function between abstract level and goal-conditioned policy, we could obtain diverse and versatile policies. By optimizing the intrinsic reward, our GPIM makes an agent capable of solving diverse tasks, which fits for wide-range applications such as quick imitation on behavior states, interactive navigation and object manipulation, and so on.

Moreover, our model provides an approach to address the Robot open-Ended Autonomous Learning (REAL). This framework is likely to speed up the progress of the general-purpose robots that can achieve complex tasks given the corresponding goals, and drive the development of autonomous robot learning in a life-long learning mode.

By autonomous exploration of the environment, the agent is likely to generate some useful behaviors as well as the majority of useless skills. Of particular concern is that the use of autonomous exploration is likely to generate a strategy that will induce dire consequences, such as a collision skill in an autonomous driving environment. How to generate useful behaviors for user-specified tasks and how to use these induced skills are also open problems. An alternative solution is to use an extrinsic reward to guide the exploration or the offline reinforcement learning (Levine et al., 2020). While another issue comes from the exploration-exploitation trade-off. We would encourage further work

Table 2: Hyper-parameters

Hyper-parameter			value
Batch Size			256
Discount Factor			0.99
Buffer Size			10000
Smooth coefficient			0.05
Temperature			0.2
Learning Rate	2D Navigation	x-y goal	0.001
		color-shape goal	0.001
	Object Manipulation		0.001
	Mujoco tasks	Swimmer	0.0001
		HalfCheetah	0.0001
		Fetch	0.0001
	Atari games	Seaquest	0.0003
		Berzerk	0.0003
		Montezuma Revenge	0.0003
Path Length	2D Navigation	x-y goal	20
		color-shape goal	20
	Object Manipulation		20
	Mujoco tasks	Swimmer	50
		HalfCheetah	50
		Fetch	100
	Atari games	Seaquest	25
		Berzerk	25
		Montezuma Revenge	25
Hidden Size	2D Navigation	x-y goal	128
		color-shape goal	128
	Object Manipulation		128
	Mujoco tasks	Swimmer	256
		HalfCheetah	256
		Fetch	256
	Atari games	Seaquest	256
		Berzerk	256
		Montezuma Revenge	256
Dimension of Generative Factor	2D Navigation	x-y goal	2
		color-shape goal	2
	Object Manipulation		4
	Mujoco tasks	Swimmer	3
		HalfCheetah	4
		Fetch	4
	Atari games	Seaquest	16
		Berzerk	16
		Montezuma Revenge	16
α			1
γ			5
δ_{pixel}			255

to understand the limitations of REAL interacting with the environment autonomously. We would also encourage research to understand the risks arising from autonomous robot learning.

Another limitation is that our learning framework needs an extra abstract-level policy training for rendering goals and providing a reward function. This requires twice as much interaction time with the environment as learning a single policy network. For practical application, a simulation platform is preferred for pre-training. We also encourage researchers to mitigate the difference between the simulation platform and the actual environment. We also pursue the effective models of transfer learning.

H   LEARNED BEHAVIORS ON TEMPORALLY-EXTENDED TASKS

More experimental results are given in Fig. 15 to show the imitation on several temporally-extended tasks.

Figure 15: Expert behaviors and learned behaviors. The four expert trajectories are described parametrically as: $(x, y, z) = (\log_{10}(t + 1) + t/50, \sin(t)/5 + t/5, t/5)$, $(x, y, z) = (t/5, \cos(t)/5 - 1/5 + t/5, \sin(t)/5)$, $(x, y, z) = (\cos(t)/5 + t/50 - 1/1, \sin(t)/5 + t/5, t/5)$, and $(x, y, z) = (\sin(t) - \sin(2t)/2, -t/5, \cos(t)/2 - \cos(2t)/2)$.

I   LEARNED BEHAVIORS FROM GPIM

More experimental results are given in Fig. 16 to show the learned behaviors on 2D navigation, object manipulation, three atari games (seaquest, berzerk and montezuma revenge), and the mujoco tasks (swimmer, half cheetah and fetch). Videos are available under https://sites.google.com/view/gpim.

Figure 16: Discovered goal-conditioned behaviors. (f-h): The left subfigure shows the expert behaviors (goals); The middle subfigure shows the learned behaviors by GPIM; The right subfigure is the stacked view of goals and GPIM behaviors.