RANK THE EPISODES:
A SIMPLE APPROACH FOR EXPLORATION IN PROCEDURALLY-GENERATED ENVIRONMENTS

ABSTRACT

Exploration under sparse reward is a long-standing challenge of model-free reinforcement learning. The state-of-the-art methods address this challenge by introducing intrinsic rewards to encourage exploration in novel states or uncertain environment dynamics. Unfortunately, the methods based on intrinsic rewards often fall short in procedurally-generated environments, where a different environment is generated in each episode so that the agent is not likely to visit the same state more than once. Motivated by how humans distinguish good exploration behaviors by looking into the entire episode, we introduce RAPID, a simple yet effective episode-level exploration method for procedurally-generated environments. RAPID regards each episode as a whole and gives an episodic exploration score from both per-episode and long-term views. Those highly scored episodes are treated as good exploration behaviors and are stored in a small ranking buffer. The agent then imitates the episodes in the buffer to reproduce the past good exploration behaviors. We demonstrate our method on several procedurally-generated MiniGrid environments, a first-person-view 3D Maze navigation task from MiniWorld, and several sparse MuJoCo tasks. The results show that RAPID significantly outperforms the state-of-the-art intrinsic reward strategies in terms of sample efficiency and final performance. The code is available at https://github.com/anonymousubmition/rapid.

1 INTRODUCTION

Deep reinforcement learning (RL) has made significant progress in various tasks, such as games (Mnih et al., 2015; Silver et al., 2016; Mnih et al., 2016), and robotic control (Lillicrap et al., 2015; Andrychowicz et al., 2017). However, RL algorithms often require tremendous number of samples to achieve reasonable performance (Hessel et al., 2018). This sample efficiency issue becomes more pronounced in sparse reward environments, where the agent may take extremely long time before bumping into a reward signal (Riedmiller et al., 2018). Thus, how to efficiently explore the environment under sparse reward remains an open challenge (Osband et al., 2019).

To address the above challenge, many exploration methods have been investigated and demonstrated to be effective on hard-exploration environments. One of the most popular techniques is to use intrinsic rewards to encourage exploration (Schmidhuber, 1991; Oudeyer & Kaplan, 2009; Guo et al., 2016; Zheng et al., 2018; Du et al., 2019). The key idea is to give intrinsic bonus based on uncertainty, e.g., assigning higher rewards to novel states (Ostrovski et al., 2017), or using the prediction error of a dynamic model as the intrinsic reward (Pathak et al., 2017). While many intrinsic reward methods have demonstrated superior performance on hard-exploration environments, such as Montezuma's Revenge (Burda et al., 2018b) and Pitfall! (Badia et al., 2019), most of the previous studies use the same singleton environment for training and testing, i.e., the agent aims to solve the same environment in each episode. However, recent studies show that the agent trained in this way is susceptible to overfitting and may fail to generalize to even a slightly different environment (Rajeswaran et al., 2017; Zhang et al., 2018a). To deal with this issue, a few procedually-generated environments are designed to test the generalization of RL, such as (Beattie et al., 2016; Chevalier-Boisvert et al., 2018; Nichol et al., 2018; Küttler et al., 2020), in which the agent aims to solve the same task, but a different environment is generated in each episode.

(a) Count-based exploration   (b) Episodic exploration score

Figure 1: A motivating example of count-based exploration versus episode-level exploration score. While count-based exploration works well in singleton setting, i.e., the environment is the same in each episode, it may be brittle in procedurally-generated setting. In (a), if the observation of the third block in an episode is sampled from ten possible values, the third block will have very high intrinsic reward because the agent is uncertain on the new states. This will reward the agent for exploring the third block and also its neighbors, and hence the agent may get stuck around the third block. In (b), we score behaviors in episode-level with *# visited states/ # total states*. The episodic exploration score can effectively distinguish good exploration behaviors in procedurally-generated setting.

Unfortunately, encouraging exploration in procedurally-generated environments is a very challenging task. Many intrinsic reward methods, such as count-based exploration and curiosity-driven exploration, often fall short in procedurally-generated environments (Raileanu & Rocktäschel, 2020; Campero et al., 2020). Figure 1a shows a motivating example of why count-based exploration is less effective in procedurally-generated environments. We consider a 1D grid-world, where the agent (red) needs to explore the environment to reach the goal within 7 timesteps, that is, the agent needs to move right in all the steps. While count-based exploration assigns reasonable intrinsic rewards in singleton setting, it may generate misleading intrinsic rewards in procedurally-generated setting because visiting a novel state does not necessarily mean a good exploration behavior. This issue becomes more pronounced in more challenging procedurally-generated environments, where the agent is not likely to visit the same state more than once. To tackle the above challenge, this work studies how to reward good exploration behaviors that can generalize to different environments.

When a human judges how well an agent explores the environment, she often views the agent from the episode-level instead of the state-level. For instance, one can easily tell whether an agent has explored a maze well by looking into the coverage rate of the current episode, even if the current environment is different from the previous ones. In Figure 1b, we can confidently tell that the episode in the right-hand-side is a good exploration behavior because the agent achieves 0.875 coverage rate. Similarly, we can safely conclude that the episode in the left-hand-side does not explore the environment well due to its low coverage rate. Motivated by this, we hypothesize that episode-level exploration score could be a more general criterion to distinguish good exploration behaviors than state-level intrinsic rewards in procedurally-generated setting.

To verify our hypothesis, we propose exploration via **Ra**nking the **E**pi**sod**es (RAPID). Specifically, we identify good exploration behaviors by assigning episodic exploration scores to past episodes. To efficiently learn the past good exploration behaviors, we use a ranking buffer to store the highly-scored episodes. The agent then learns to reproduce the past good exploration behaviors with imitation learning. We demonstrate that RAPID significantly outperforms the state-of-the-art intrinsic reward methods on several procedurally-generated benchmarks. Moreover, we present extensive ablations and analysis for RAPID, showing that RAPID can well explores the environment even without extrinsic rewards and could be generally applied in tasks with continuous state/action spaces.

2   Exploration via Ranking the Episodes

An overview of RAPID is shown in Figure 2. The key idea is to assign episodic exploration scores to past episodes and store those highly-scored episodes into a small buffer. The agent then treats the episodes in the buffer as demonstrations and learns to reproduce these episodes with imitation learning. RAPID encourages the agent to explore the environment by reproducing the past good exploration behaviors. This section introduces how we define the episodic exploration score for procedurally-generated environments and how the proposed method can be combined with state-of-the-art reinforcement learning agents.

Figure 2: An overview of RAPID. The past episodes are assigned episodic exploration scores based on the local view, the global view, and the extrinsic reward. Those highly scored episodes are stored in a small ranking buffer. The agent is then encouraged to reproduce the past good exploration behaviors, i.e., the episodes in the buffer, with imitation learning.

2.1 EPISODIC EXPLORATION SCORE

Each episode is scored from both local and global perspectives. The local score is a per-episode view of the exploration behavior, which measures how well the current episode itself explores the environment. The global score provides a long-term and historical view of exploration, i.e., whether the current episode has explored the regions that are not well explored in the past. Additionally, we consider extrinsic reward, which is the episodic reward received from the environment. It is an external criterion of exploration since a high extrinsic reward often suggests good exploration in sparse environments. The overall episodic exploration score is obtained by the weighted sum of the above three scores. We expect that these scores can model different aspects of exploration behaviors and they are complementary in procedurally-generated environments.

Local Score. The intuition of the local exploration bonus is that the agent is expected to visit as many distinct states as possible in one episode. In our preliminary experiments on MiniGrid, we observe that many poor exploration episodes repeatedly visit the same state. As a result, the agent may get stuck in a well-known region but never reach out to unexplored regions. From a local view, we can quantify this exploration behavior based on the diversity of the visited states. Specifically, we define the local exploration score as

$$S_{\text{local}} = \frac{N_{\text{distinct}}}{N_{\text{total}}},\tag{1}$$

where N_{total} is the total number of states in the episode, and N_{distinct} is the number of distinct states in the episode. Intuitively, optimizing the local score will encourage the agent to reach out to the unexplored regions in the current episode. In an ideal case, the episodes that never visit the same state twice will receive a local bonus of 1. There could be various ways to extend the above definition to continuous state space. In this work, we empirically define the local score in continuous state space as the mean standard deviation of all the states in the episode.

Global Score. The global score is designed to model long-term exploration behavior. While a different environment will be generated in each episode in the procedurally-generated setting, the environments in different episodes usually share some common characteristics. For example, in the MiniGrid MultiRoom environment (Figure 3a), although a different maze will be generated in a new episode, the basic building blocks (e.g., walls, doors, etc.), the number of rooms, and the size of each room will be similar. From a global view, the agent should explore the regions that are not well explored in the past. Motivated by count-based exploration, we define the global score as

$$S_{\text{global}} = \frac{1}{N_{\text{total}}} \sum_s \frac{1}{\sqrt{N(s)}},\tag{2}$$

where $N(s)$ is the state count of s throughout the training process, that is, the global score is the mean count-based intrinsic reward of all the states in the episode.

Algorithm 1 Exploration via Ranking the Episodes (RAPID)

1: **Input:** Training steps S, buffer size D, RL rollout steps T
2: Initialize the policy π_θ, replay buffer $\mathcal{D}$
3: **for** iteration = 1, 2, ... until convergence **do**
4:     Execute π_θ for T timesteps
5:     Update π_θ with RL objective (also update value functions if any)
6:     **for** each generated episode τ **do**
7:         Compute episodic exploration score S_τ based on Eq. (3)
8:         Give score S_τ to all the state-action pairs in τ and store them to the buffer
9:         Rank the state-action pairs in $\mathcal{D}$ based on their exploration scores
10:        **if** $\mathcal{D}.length > D$ **then**
11:           Discard the state-action pairs with low scores so that $\mathcal{D}.length = D$
12:        **end if**
13:        **for** step = 1, 2, .., S **do**
14:           Sample a batch from $\mathcal{D}$ and train π_θ using the data in $\mathcal{D}$ with behavior cloning
15:        **end for**
16:     **end for**
17: **end for**

Episodic Exploration Score. Suppose S_{ext} is the total extrinsic reward of an episode received from the environment . The episodic exploration score is obtained by the weighted sum of the extrinsic reward S_{ext}, the local score S_{local}, and the global score S_{global}:

$$S = w_0 S_{\text{ext}} + w_1 S_{\text{local}} + w_2 S_{\text{global}}, \tag{3}$$

where w_0, w_1 and w_2 are hyperparameters. We speculate that the three scores are complementary and the optimal w_0, w_1 and w_2 could vary in diffident environments. For example, a higher w_1 will give a higher weight to the per-episode view of exploration behavior. A higher w_2 will focus more on whether the current episode has explored the past unexplored regions. Nevertheless, we find that a single set of w_0, w_1 and w_2 works well across many tasks.

Comparison with Prior Work. Several papers have studied episode-level feedback to improve the sample efficiency of RL. To the best of our knowledge, the existing work mainly focuses on learning a meta-policy based on episodic rewards (Xu et al., 2018; Zha et al., 2019), or imitating the episodes with high episodic rewards (Guo et al., 2018; Srivastava et al., 2019). However, in very sparse environments, it is not likely to receive a non-zero reward from the environment without exploration. These methods are not suitable for very sparse environments since episodic rewards could be always zero. In this work, we propose local and global episodic scores to quantify the exploration behaviors and encourage the agent to visit distinct states from per-episode and long-term views.

2.2 REPRODUCING PAST GOOD EXPLORATION BEHAVIORS WITH IMITATION LEARNING

A straightforward idea is to treat the episodic exploration score as a reward signal and assign it to the last timestamp of the episode. In this way, the agent can be updated with any reinforcement learning objective. However, this strategy is not very effective with three potential limitations. First, the reward remains sparse so that the reinforcement learning agents may not be able to effectively exploit the reward signals. Second, the intrinsic exploration bonus may introduce bias in the objective. While the local score and global score may encourage exploration at the beginning stage, they are not true objectives and may degrade the final performance. Third, it only uses a good episode once. In fact, many past good episodes can be exploited many times to improve sample efficiency.

To overcome the above limitations, we propose to use a small ranking buffer to store past good state-action pairs and then use imitation objective to enhance exploration. Specifically, we assign the same episodic exploration score to all the state-action pairs in an episode and rank all the state-action pairs based on scores. In addition to the original RL objective, we employ behavior cloning, the simplest form of imitation learning, to encourage the agent to reproduce the state-action pairs in the buffer. This simple ranking buffer can effectively exploit the past good experiences since a good state-action pair could be sampled more than once. The procedure is summarized in Algorithm 1.

(a) MultiRoom-N12-S10 (b) KeyCorridor-S4-R3   (c) Maze   (d) Maze (top view)

Figure 3: Rendering of the procedually-generated environments in our experiments.

3 EXPERIMENTS

The experiments are designed to answer the following research questions: **RQ1:** how is RAPID compared with the state-of-the-art intrinsic reward methods on benchmark procedurally-generated environments (Section 3.2)? **RQ2:** how will RAPID perform if removing one of the scores (i.e., the local score, the global score, and the extrinsic reward) or the buffer (Section 3.3)? **RQ3:** how will the hyperparameters impact the performance of RAPID (Section 3.3)? **RQ4:** can RAPID explore the environment without extrinsic reward (Section 3.3)? **RQ5:** how will RAPID perform with larger and more challenging grid-world (Section 3.3)? **RQ6:** can RAPID generalize to 3D navigation task and continuous state/action space, such as MuJoCo (Section 3.4)?

3.1 ENVIRONMENTS AND BASELINES

Figure 3 shows the rendering of procedurally-generated environments used in this work. Following the previous studies of exploration in procedurally-generated environments (Raileanu & Rocktäschel, 2020; Campero et al., 2020), we mainly focus on MiniGrid environments (Chevalier-Boisvert et al., 2018), which provide procedurally-generated grid-worlds. We consider two types of hard exploration tasks: *MultiRoom-NX-SY*, where X and Y indicate the number of rooms and the room size, respectively, and *KeyCorridor-SX-RY*, where X and Y indicate the room size and the number of rows, respectively. A large X or Y suggests a larger environment, which will be more difficult to explore. The agent has a partial view of the environment and needs to navigate the green block or the red ball under sparse rewards. To test whether RAPID can generalize to continuous state space, we consider MiniWorld Maze (Chevalier-Boisvert, 2018). Similarly, the agent in MiniWorld Maze has a 3D partial view of the environment and needs to navigate the red box. The maze is procedurally-generated, i.e., a different maze will be generated in each episode. We further study RAPID in continuous state and action spaces on sparse MuJoCo tasks (Todorov et al., 2012; Brockman et al., 2016). More details of the above environments are described in Appendx B.

While exploration has been extensively studied in the literature, very few methods are designed for procedurally-generated environments. To better understand the performance of RAPID, we consider the baselines in the following categories. **Traditional Methods:** we consider several popular methods designed for singleton environments, including count-based exploration (COUNT) (Bellemare et al., 2016), Random Network Distillation Exploration (RANDOM) (Burda et al., 2018b), and curiosity-driven exploration (CURIOSITY) (Pathak et al., 2017). **Methods for Procedurally-Generated Environments:** we consider two state-of-the-art exploration methods, including Impact-Driven Exploration (RIDE) (Raileanu & Rocktäschel, 2020), and exploration with Adversarially Motivated Intrinsic Goals (AMIGO) (Campero et al., 2020). **Self-Imitation Methods**: self-imitation learning (SIL) (Oh et al., 2018) also exploits past good experiences to encourage exploration. We further include PPO (Schulman et al., 2017) as a reinforcement learning baseline. All the algorithms are run the same number timesteps for a fair comparison. More details are provided in Appendix A.

3.2 MINIGRID RESULTS

To study **RQ1**, we plot the learning curves of RAPID and the baselines on MiniGrid benchmarks in Figure 4. We can make three observations. First, RAPID performs significantly better than the state-of-the-art methods designed for singleton or procedurally-generated environments in terms of sample efficiency and final performance. For example, on MultiRoom-N7-S8, RAPID is at least 10

Figure 4: Performance of RAPID against baselines on hard-exploration environments in MiniGrid. All the experiments are run 5 times with different random seeds. The shaded area represents mean ± standard deviation.

	RAPID	w/o local	w/o global	w/o reward	w/o buffer
MR-N7S4	0.787 ± 0.001	0.787 ± 0.000	0.787 ± 0.001	0.781 ± 0.002	0.000 ± 0.000
MR-N10S4	0.778 ± 0.000	0.778 ± 0.000	0.778 ± 0.001	0.775 ± 0.002	0.000 ± 0.000
MR-N7S8	0.678 ± 0.001	0.677 ± 0.002	0.677 ± 0.002	0.652 ± 0.004	0.000 ± 0.000
MR-N10S10	0.632 ± 0.001	0.238 ± 0.288	0.630 ± 0.002	0.604 ± 0.010	0.000 ± 0.000
MR-N12S10	0.644 ± 0.001	0.001 ± 0.001	0.633 ± 0.005	0.613 ± 0.007	0.000 ± 0.000
KC-S3R2	0.934 ± 0.004	0.933 ± 0.002	0.934 ± 0.000	0.929 ± 0.003	0.018 ± 0.008
KC-S3R3	0.922 ± 0.001	0.885 ± 0.022	0.912 ± 0.003	0.903 ± 0.002	0.012 ± 0.007
KC-S4R3	0.473 ± 0.087	0.150 ± 0.095	0.244 ± 0.144	0.035 ± 0.035	0.000 ± 0.000

Table 1: Performance of RAPID and the ablations on MiniGrid environments. The mean maximum returns and standard deviations are reported. MR stands for MultiRoom; KC stands for KeyCorridor. Learning curves are in Appendix C.

.

times more sample efficient than RIDE. On KeyCorridor-S4-R3, RAPID is the only algorithm that successfully navigates the goal within 20 million timesteps. Second, the traditional intrinsic reward methods perform well on easy procedurally-generated environments but perform poorly on hard-exploration tasks. For example, COUNT performs as well as RAPID on KeyCorridor-S3-R2 but fails on more challenging tasks, such as MultiRoom-N7-S8. This suggests that traditional methods may fall short in challenging procedurally-generated environments, which is consistent with the results in previous work (Raileanu & Rocktäschel, 2020). Third, RAPID outperforms SIL across all the tasks. Recall that both RAPID and SIL learn to reproduce past good experiences. While SIL reproduces experiences with high intrinsic rewards, RAPID additionally considers local and global exploration scores. This verifies the effectiveness of the episodic exploration scores.

3.3 ABLATIONS AND ANALYSIS

To study **RQ2**, we perform ablation studies on RAPID. Specifically, we remove one of the local score, the global score, and the extrinsic reward, and compare each ablation with RAPID. Besides, we consider a variant that directly uses the episodic exploration score as the reward signal without buffer. Table 1 shows the results. We observe that all the scores contribute to the final performance. In particular, on KeyCorridor-S4-R3, RAPID is significantly better than all the ablations. We also observe that the agent fails in almost all the tasks without buffer. This suggests that the ranking buffer is an effective way to exploit past good exploration behaviors.

(a) Impact of training steps   (b) Imapct of buffer size   (c) Pure exploration   (d) Local exploration score

Figure 5: Analysis of RAPID on MultiRoom-N12-S10. Results for other environments are in Appendix D. **(a)(b):** the impact of the hyperparameters. **(c)(d):** the returns without extrinsic rewards (pure exploration) and the corresponding local exploration scores.

Figure 6: **Left:** the maximum returns w.r.t. the number of rooms under room size 4 (full curves in Appendix E). **Middle:** the maximum returns w.r.t. the room sizes with 4 rooms (full curves in Appendix F). **Right:** learning curves on MiniWolrd Maze (more results in Appendix G).

To study **RQ3**, we plot the learning curves with different training steps S and buffer size D in Figure 5a and 5b. We observe that larger number of training steps usually leads to faster learning speed at the beginning stage but may result in sub-optimal performance. For the buffer size, we observe that a large buffer will lead to slow learning speed with more stable performance. We speculate that there is a trade-off between learning speed and the final performance. In our experiments, we set training steps S to be 5 and buffer size D to be 10000, respectively, across all the tasks.

To investigate **RQ4**, we remove extrinsic rewards and show the learning curves of RAPID and the baselines in Figure 5c with the corresponding local exploration scores in Figure 5d. We make two interesting observations. First, without extrinsic rewards, RAPID can deliver reasonable performance. For example, on MultiRoom-N12-S10, RAPID achieves nearly 0.5 average return with pure exploration, compared with around 0.6 if using extrinsic rewards. We look into the episodes generated by RAPID with pure exploration and observe that, in most cases, the agent is able to reach the goal but struggles to find the optimal path to the goal. This is expected because the extrinsic reward is obtained by whether the agent can reach the goal subtracting some penalties of the timesteps spent. The extrinsic reward can encourage the agent to choose the shortest path to reach the goal. For other baselines, we observe that only RIDE and AMIGO can occasionally reach the goal. Second, we observe that some baselines, such as RIDE, are indirectly maximizing the local exploration scores. For example, we observe that the local exploration score increases for RIDE on MultiRoom-N12-S10. However, the local score of RAPID drops after about 10 million timesteps. This suggests the episode-level score may better align with good exploration behaviors. A possible explanation for the superiority of RAPID is that it is designed to directly optimize episodic exploration score.

To answer **RQ5**, we focus on *MultiRoom-NX-SY* and ambitiously vary X and Y to make the environments more challenging. Specifically, we fix Y to be 4 and vary X in the left-hand-side of Figure 6, and fix X to be 4 and vary Y in the middle of Figure 6. Compared with RIDE, our RAPID delivers stronger performance on more challenging mini-worlds.

3.4 MINIWORLD MAZE AND SPARSE MUJOCO RESULTS

For **RQ6**, the learning curves on 3D Maze are shown in the right-hand-side of Figure 6. RAPID performs significantly better than the baselines. We also conduct experiments on a subset of sparse MuJoCo tasks (Figure 7). The results show that RAPID improves over PPO and SIL. Interestingly, RAPID achieves more than 200 average return on Swimmer, which surpasses some previous results reported on the dense reward counterpart (Duan et al., 2016; Henderson et al., 2018; Lai et al., 2020).

Figure 7: Performance on MuJoCo tasks with episodic reward. i.e., a non-zero reward is only provided at the end of an episode. All the experiments are run 5 times with different random seeds.

4 RELATED WORK

Count-Based and Curiosity-Driven Exploration. These two classes of intrinsic motivations are the most popular and proven to be effective in the literature. Count-based exploration encourages the agent to visit the novel states, which is first studied in tabular setting (Strehl & Littman, 2008) and has been recently extended to more complex state space (Bellemare et al., 2016; Ostrovski et al., 2017; Tang et al., 2017; Martin et al., 2017; Machado et al., 2018; Osband et al., 2019). Curiosity-driven exploration learns the environment dynamics to encourage exploration (Stadie et al., 2015; Pathak et al., 2017; Sukhbaatar et al., 2018; Burda et al., 2018a). However, these methods are designed for singleton environments and often struggle to generalize to procedurally-generated environments (Raileanu & Rocktäschel, 2020).

Exploration for Procedurally-Generated Environments. Several recent studies have discussed the generalization of reinforcement learning (Rajeswaran et al., 2017; Zhang et al., 2018a;b; Choi et al., 2018) and designed procedurally-generated environments to test the generalization of reinforcement learning (Beattie et al., 2016; Nichol et al., 2018; Küttler et al., 2020). More recent papers show that traditional exploration methods fall short in procedurally-generated environments and address this issue with new exploration methods (Raileanu & Rocktäschel, 2020; Campero et al., 2020). This work studies a new perspective of exploration bonus in episode-level and achieves significantly better performance than the previous methods on procedurally-generated benchmarks.

Experience Replay Buffer and Self-Imitation Learning. Experience replay mechanism is widely used and is initially designed to stabilize deep reinforcement learning (Lin, 1992; 1993; Mnih et al., 2015; Zhang & Sutton, 2017; Zha et al., 2019; Fedus et al., 2020). Self-Imitation Learning extends the experience replay buffer and uses it to store past good experiences (Oh et al., 2018; Guo et al., 2018; 2019; Gangwani et al., 2018). However, Self-Imitation only exploits highly rewarded experiences and thus is not suitable for very sparse environments. Our work incorporates local and global scores to encourage past good exploration behaviors in sparse procedurally-generated environments.

5 CONCLUSIONS AND FUTURE WORK

This work studies how we can reward good exploration behaviors in procedurally-generated environments. We hypothesize that episode-level exploration score could be a more general criterion to distinguish good exploration behaviors. To verify our hypothesis, we design RAPID, a practical algorithm that learns to reproduce past good exploration behaviors with a ranking buffer. Experiments on benchmark hard-exploration procedurally-generated environments show that RAPID significantly outperforms state-of-the-art intrinsic reward methods in terms of sample efficiency and final performance. Further analysis shows that RAPID has robust performance across different configurations, even without extrinsic rewards. Moreover, experiments on a 3D navigation task and a subset of sparse MuJoCo tasks show that RAPID could generalize to continuous state/action spaces, showing the promise in rewarding good episode-level exploration behaviors to encourage exploration. In the future, we will extend our idea and test it in more challenging procedurally-generated environments. We will also explore the possibility of combining the episode-level exploration bonus with intrinsic rewards. Last, we will try other imitation learning techniques beyond behavior cloning.

REFERENCES

Marcin Andrychowicz, Filip Wolski, Alex Ray, Jonas Schneider, Rachel Fong, Peter Welinder, Bob McGrew, Josh Tobin, OpenAI Pieter Abbeel, and Wojciech Zaremba. Hindsight experience replay. In *Advances in Neural Information Processing Systems*, 2017.

Adrià Puigdomènech Badia, Pablo Sprechmann, Alex Vitvitskyi, Daniel Guo, Bilal Piot, Steven Kapturowski, Olivier Tieleman, Martin Arjovsky, Alexander Pritzel, Andrew Bolt, et al. Never give up: Learning directed exploration strategies. In *International Conference on Learning Representations*, 2019.

Charles Beattie, Joel Z Leibo, Denis Teplyashin, Tom Ward, Marcus Wainwright, Heinrich Küttler, Andrew Lefrancq, Simon Green, Víctor Valdés, Amir Sadik, et al. Deepmind lab. *arXiv preprint arXiv:1612.03801*, 2016.

Marc Bellemare, Sriram Srinivasan, Georg Ostrovski, Tom Schaul, David Saxton, and Remi Munos. Unifying count-based exploration and intrinsic motivation. In *Advances in Neural Information Processing Systems*, 2016.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

Yuri Burda, Harri Edwards, Deepak Pathak, Amos Storkey, Trevor Darrell, and Alexei A Efros. Large-scale study of curiosity-driven learning. In *International Conference on Learning Representations*, 2018a.

Yuri Burda, Harrison Edwards, Amos Storkey, and Oleg Klimov. Exploration by random network distillation. In *International Conference on Learning Representations*, 2018b.

Andres Campero, Roberta Raileanu, Heinrich Küttler, Joshua B Tenenbaum, Tim Rocktäschel, and Edward Grefenstette. Learning with amigo: Adversarially motivated intrinsic goals. *arXiv preprint arXiv:2006.12122*, 2020.

Maxime Chevalier-Boisvert. gym-miniworld environment for openai gym. `https://github.com/maximecb/gym-miniworld`, 2018.

Maxime Chevalier-Boisvert, Lucas Willems, and Suman Pal. Minimalistic gridworld environment for openai gym. *GitHub repository*, 2018.

Jongwook Choi, Yijie Guo, Marcin Moczulski, Junhyuk Oh, Neal Wu, Mohammad Norouzi, and Honglak Lee. Contingency-aware exploration in reinforcement learning. In *International Conference on Learning Representations*, 2018.

Yali Du, Lei Han, Meng Fang, Ji Liu, Tianhong Dai, and Dacheng Tao. Liir: Learning individual intrinsic reward in multi-agent reinforcement learning. In *Advances in Neural Information Processing Systems*, 2019.

Yan Duan, Xi Chen, Rein Houthooft, John Schulman, and Pieter Abbeel. Benchmarking deep reinforcement learning for continuous control. In *International Conference on Machine Learning*, 2016.

William Fedus, Prajit Ramachandran, Rishabh Agarwal, Yoshua Bengio, Hugo Larochelle, Mark Rowland, and Will Dabney. Revisiting fundamentals of experience replay. In *International Conference on Machine Learning*, 2020.

Tanmay Gangwani, Qiang Liu, and Jian Peng. Learning self-imitating diverse policies. In *International Conference on Learning Representations*, 2018.

Xiaoxiao Guo, Satinder Singh, Richard Lewis, and Honglak Lee. Deep learning for reward design to improve monte carlo tree search in atari games. In *International Joint Conference on Artificial Intelligence*, 2016.

Yijie Guo, Junhyuk Oh, Satinder Singh, and Honglak Lee. Generative adversarial self-imitation learning. *arXiv preprint arXiv:1812.00950*, 2018.

Yijie Guo, Jongwook Choi, Marcin Moczulski, Samy Bengio, Mohammad Norouzi, and Honglak Lee. Efficient exploration with self-imitation learning via trajectory-conditioned policy. *arXiv preprint arXiv:1907.10247*, 2019.

Peter Henderson, Riashat Islam, Philip Bachman, Joelle Pineau, Doina Precup, and David Meger. Deep reinforcement learning that matters. In *AAAI Conference on Artificial Intelligence*, 2018.

Matteo Hessel, Joseph Modayil, Hado Van Hasselt, Tom Schaul, Georg Ostrovski, Will Dabney, Dan Horgan, Bilal Piot, Mohammad Azar, and David Silver. Rainbow: Combining improvements in deep reinforcement learning. In *AAAI Conference on Artificial Intelligence*, 2018.

Heinrich Küttler, Nantas Nardelli, Alexander H Miller, Roberta Raileanu, Marco Selvatici, Edward Grefenstette, and Tim Rocktäschel. The nethack learning environment. *arXiv preprint arXiv:2006.13760*, 2020.

Kwei-Herng Lai, Daochen Zha, Yuening Li, and Xia Hu. Dual policy distillation. In *International Joint Conference on Artificial Intelligence*, 2020.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

Long-Ji Lin. Self-improving reactive agents based on reinforcement learning, planning and teaching. *Machine learning*, 8(3-4):293–321, 1992.

Long-Ji Lin. Reinforcement learning for robots using neural networks. Technical report, Carnegie-Mellon Univ Pittsburgh PA School of Computer Science, 1993.

Marlos C Machado, Marc G Bellemare, and Michael Bowling. Count-based exploration with the successor representation. *arXiv preprint arXiv:1807.11622*, 2018.

Jarryd Martin, S Suraj Narayanan, Tom Everitt, and Marcus Hutter. Count-based exploration in feature space for reinforcement learning. In *International Joint Conference on Artificial Intelligence*, 2017.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International Conference on Machine Learning*, 2016.

Alex Nichol, Vicki Pfau, Christopher Hesse, Oleg Klimov, and John Schulman. Gotta learn fast: A new benchmark for generalization in rl. *arXiv preprint arXiv:1804.03720*, 2018.

Junhyuk Oh, Yijie Guo, Satinder Singh, and Honglak Lee. Self-imitation learning. In *International Conference on Machine Learning*, 2018.

Ian Osband, Benjamin Van Roy, Daniel J Russo, and Zheng Wen. Deep exploration via randomized value functions. *Journal of Machine Learning Research*, 20(124):1–62, 2019.

Georg Ostrovski, Marc G Bellemare, Aäron Oord, and Rémi Munos. Count-based exploration with neural density models. In *International Conference on Machine Learning*, 2017.

Pierre-Yves Oudeyer and Frederic Kaplan. What is intrinsic motivation? a typology of computational approaches. *Frontiers in neurorobotics*, 1:6, 2009.

Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *IEEE Conference on Computer Vision and Pattern Recognition Workshops*, 2017.

Roberta Raileanu and Tim Rocktäschel. Ride: Rewarding impact-driven exploration for procedurally-generated environments. In *International Conference on Learning Representations*, 2020.

Aravind Rajeswaran, Kendall Lowrey, Emanuel V Todorov, and Sham M Kakade. Towards generalization and simplicity in continuous control. In *Advances in Neural Information Processing Systems*, 2017.

Martin Riedmiller, Roland Hafner, Thomas Lampe, Michael Neunert, Jonas Degrave, Tom Wiele, Vlad Mnih, Nicolas Heess, and Jost Tobias Springenberg. Learning by playing solving sparse reward tasks from scratch. In *International Conference on Machine Learning*, 2018.

Jürgen Schmidhuber. A possibility for implementing curiosity and boredom in model-building neural controllers. In *International conference on simulation of adaptive behavior: From animals to animats*, 1991.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of go with deep neural networks and tree search. *nature*, 529(7587):484–489, 2016.

Rupesh Kumar Srivastava, Pranav Shyam, Filipe Mutz, Wojciech Jaśkowski, and Jürgen Schmidhuber. Training agents using upside-down reinforcement learning. *arXiv preprint arXiv:1912.02877*, 2019.

Bradly C Stadie, Sergey Levine, and Pieter Abbeel. Incentivizing exploration in reinforcement learning with deep predictive models. *arXiv preprint arXiv:1507.00814*, 2015.

Alexander L Strehl and Michael L Littman. An analysis of model-based interval estimation for markov decision processes. *Journal of Computer and System Sciences*, 74(8):1309–1331, 2008.

Sainbayar Sukhbaatar, Zeming Lin, Ilya Kostrikov, Gabriel Synnaeve, Arthur Szlam, and Rob Fergus. Intrinsic motivation and automatic curricula via asymmetric self-play. In *International Conference on Learning Representations*, 2018.

Haoran Tang, Rein Houthooft, Davis Foote, Adam Stooke, OpenAI Xi Chen, Yan Duan, John Schulman, Filip DeTurck, and Pieter Abbeel. # exploration: A study of count-based exploration for deep reinforcement learning. In *Advances in Neural Information Processing Systems*, 2017.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, 2012.

Tianbing Xu, Qiang Liu, Liang Zhao, and Jian Peng. Learning to explore with meta-policy gradient. In *International Conference on Machine Learning*, 2018.

Daochen Zha, Kwei-Herng Lai, Kaixiong Zhou, and Xia Hu. Experience replay optimization. In *International Joint Conference on Artificial Intelligence*, 2019.

Amy Zhang, Nicolas Ballas, and Joelle Pineau. A dissection of overfitting and generalization in continuous reinforcement learning. *arXiv preprint arXiv:1806.07937*, 2018a.

Chiyuan Zhang, Oriol Vinyals, Remi Munos, and Samy Bengio. A study on overfitting in deep reinforcement learning. *arXiv preprint arXiv:1804.06893*, 2018b.

Shangtong Zhang and Richard S Sutton. A deeper look at experience replay. *NIPS Deep Reinforcement Learning Symposium*, 2017.

Zeyu Zheng, Junhyuk Oh, and Satinder Singh. On learning intrinsic rewards for policy gradient methods. In *Advances in Neural Information Processing Systems*, 2018.

A Hyperparameters and Neural Network Architecture

For the proposed RAPID, the common hyperparameters are summarized in Table 2. RAPID is based on the PPO implementation from OpenAI baselines[1]. The nstep is 128 for all MiniGrid environments and MuJoCo environments, and 512 for MiniWorld-Maze-S5. For MuJoCo environments, we report the results with only imitation loss since we find that the policy loss of PPO will harm the performance in the episodic reward setting. The learning rate is 10^{-4} for all MiniGrid environments and MiniWorld-Maze-S5, and 5×10^{-4} for MuJoCo environments. Since MiniWorld-Maze-S5 and MuJoCo environments have continuous state space, we set $w_2 = 0$. In practice, in MiniWorld-Maze-S5, we observe that counting the states will usually lead to memory error because it is not likely to encounter the same state again in MiniWorld-Maze-S5 (COUNT is excluded in comparison due to memory issues). Note that it is possible to use pseudo-counts (Bellemare et al., 2016; Ostrovski et al., 2017), which we will study in our future work. For MiniGrid-KeyCorridorS2R3-v0, MiniGrid-KeyCorridorS3R3-v0 and MiniWorld-Maze-S5, the update frequency of imitation learning is linearly annealed to 0 throughout the training process. For other environments, the imitation learning is performed after each episode. We keep all other hyperparameters of PPO as default and use the default CNN architecture provided in OpenAI baselines for MiniWorld-Maze-S5 and MLP with 64-64 for other environments. The PPO also uses the same hyperparameters.

Hyperparameter	Value
w_0	1
w_1	0.1
w_2	0.001
buffer Size	10000
batch Size	256
number of update steps	5
entropy coefficient	0.01
value function coefficient	0.5
γ	0.99
λ	0.95
clip range	0.2

Table 2: Common hyperparameters of the proposed RAPID (top) and the hyperparameters of PPO baseline (bottom).

For RANDOM, we implement the two networks with 64-64 MLP. For CURIOSITY and RIDE, we use 64-64 MLP for state embedding model, forward dynamics model and inverse dynamics model, respectively. However, with extensive hyperparameters search, we are not able to reproduce the RIDE results in MiniGrid environments even with the exactly same neural architecture and hyperparameters as suggested in (Raileanu & Rocktäschel, 2020). Thus, we use the authors' implementation[2] (Raileanu & Rocktäschel, 2020), which is well-tuned on MiniGrid tasks. Our reported result is on par with that reported in (Raileanu & Rocktäschel, 2020). For SIL and AMIGO, we use the implementations from the authors[3,4] with the recommended hyperparameters.

For the methods based on intrinsic rewards, i.e., RIDE,, AMIGO CURIOSITY, RANDOM, and COUNT, we search intrinsic reward coefficient from $\{0.1, 0.05, 0.01, 0.005, 0.001, 0.0005, 0.0001\}$. For RIDE, the intrinsic reward coefficient is 0.1 for MiniGrid-KeyCorridorS2R3-v0, MiniGrid-KeyCorridorS3R3-v0, MiniGrid-KeyCorridorS4R3-v0, MiniGrid-MultiRoom-N10S4-v0, MiniGrid-MultiRoom-N7S4-v0 and MiniWorld-Maze-S5, and 0.5 for MiniGrid-MultiRoom-N7S8-v0, MiniGrid-MultiRoom-N10S10-v0 and MiniGrid-MultiRoom-N12S10-v0. For AMIGO and CURIOSITY, the intrinsic reward coefficient is 0.1 for all the environments. For COUNT, the intrinsic reward coefficient is 0.005 for all the environments. For RANDOM, the intrinsic reward coefficient is 0.001 for all the environemnts. We also tune the entropy coefficient of RIDE

---

[1]`https://github.com/openai/baselines`

[2]`https://github.com/facebookresearch/impact-driven-exploration`

[3]`https://github.com/junhyukoh/self-imitation-learning`

[4]`https://github.com/facebookresearch/adversarially-motivated-intrinsic-goals`

from $\{0.001, 0.0005\}$, as suggested by the original paper. The entropy coefficient is 0.0005 for MiniGrid-KeyCorridorS2R3-v0, MiniGrid-KeyCorridorS3R3-v0, MiniGrid-KeyCorridorS4R3-v0, MiniGrid-MultiRoom-N10S4-v0, MiniGrid-MultiRoom-N7S4-v0 and MiniWorld-Maze-S5, and 0.001 for MiniGrid-MultiRoom-N7S8-v0, MiniGrid-MultiRoom-N10S10-v0 and MiniGrid-MultiRoom-N12S10-v0.

B ENVIRONMENTS

B.1 MINIGRID ENVIRONMENTS

MiniGrid[5] is a suite of light-weighted and fast gridworld environments with OpenAI gym interfaces. The environments are partially observable with a grid size of $N \times N$. Each tile in the gird can have at most one object, that is, 0 or 1 object. The possible objects are wall, floor, lava, door, key, ball, box and goal. Each object will have an associated color. The agent can pick up at most one object (ball or key). To open a locked door, the agent must use a key. Most of the environments in MiniGrid are procedurally-generated, i.e. a different grid will be sampled in each episode. Figure 8 shows the grids in four different episodes. The procedurally-generated nature makes training RL challenging because the RL agents need to learn the skills that can generalize to different grids. The environments can be easily modified so that we can create different levels of the environments. For example, we can modify the number of rooms and the size of each room to create hard-exploration or easy-exploration environments. The flexibility of MiniGrid environments enables us to conduct systematic comparison of algorithms under different difficulties.

Figure 8: Rendering of MultiRoom-N12-S10 (top row) and KeyCorridor-S4-R3(bottom row) in 4 different episodes. The environments are procedually-generated, i.e., a different room is generated in a new episode.

The original observations of MiniGrid are dictionaries, which consist of a *image* field providing a partially observable view of the environment, and a *mission* field describing the goal with texts. In our experiments, we use `ImgObsWrapper` which only keeps the *image* field. The environment uses a compact encoding with 3 input values per visible grid cell. Note that the cells behind the wall or unopened doors are invisible.

The possible actions in MiniGrid are (1) turn left, (2) turn right, (3) move forward, (4) pick up an object, (5) drop the carried object, (6) open doors/interact with objects, and (7) done. The agent will remain in the same state if the action is not legal. For example, if there is no object in front of the agent, the agent will remain in the same state when performing action (4) pick up an object.

We focus on MultiRoom-NX-SY and KeyCorridor-SX-RY, where X and Y are hyperparameters specifying the number of rooms or the room sizes in the environments. With larger X and Y, the environments will become more difficult to solve due to the sparse rewards. Figure 9 shows the

---
[5]`https://github.com/maximecb/gym-minigrid`

environments (with different difficulties) in this work. In MultiRoom-NX-SY, the agent needs to navigate the green tile in the last room. If the agent successfully navigates the goal, the agent will receive a reward of 1 subtracting some penalties of the timesteps spent. In KeyCorridor-SX-RY, the agent needs to pick up the key, use the key to open the locked door, and pick up the ball. Similarly, the agent will receive a reward of 1 subtracting some penalties of the timesteps spent if it picks up the ball. Both environments are extremely difficult to solve using RL alone due to the sparse rewards.

(a) MultiRoom-N7-S4   (b) MultiRoom-N10-S4   (c) MultiRoom-N7-S8   (d) MultiRoom-N10-S10

(e) KeyCorridor-S3-R2   (f) KeyCorridor-S3-R3   (g) KeyCorridor-S4-R3   (h) MultiRoom-N12-S10

Figure 9: Rendering of Minigird environments used in the work.

B.2 MINIWORLD MAZE ENVIRONMENT

MiniWorld[6] is a minimalistic 3D interior environment simulator. Similar to Minigrid, we can easily create environments with different levels. We focus on MiniWorld-Maze, where the agent is asked to navigate the goal through a procedurally-generated maze. The agent has a first-person partially observable view of the environment. This environment is extremely difficult to solve due to sparse reward, long-horizon, and the procedurally-generated nature of the environments.

In this work, we focus on MiniWorld-Maze-S5, a variant of the MiniWorld Maze environment with 5×5 tiles. Figure 10 shows the top view of the mazes in four different episodes. In each episode, the agent and the goal are initialized in the top-left and bottom-right corners of the map, respectively. In this way, we ensure that the agent and the goal are far away enough so that the agent can not easily see the goal without exploration. A random maze will be generated in each episode. There are three possible actions: (1) move forward, (2) turn left, and (3) turn right. The agent will move $0.4 \times tile\_length$ if moving forward, where $tile\_length$ is the length of one side of a tile. The agent will rotate 22.5 degrees if turning right/left. The time budget of each episode is 600. The agent will not receive any positive reward if it can not navigate the goal under the time budget.

Figure 10: Example generated mazes in 4 diffident episodes.

---

[6] https://github.com/maximecb/gym-miniworld

B.3 SPARSE MUJOCO ENVIRONMENTS

Mujoco is a physical engine for continuous control (Todorov et al., 2012). Figure 11 shows the rendering of the four MuJoCo tasks used in our work. The original MuJoCo environments use dense rewards, i.e., a well-defined reward is given in each timestep. However, in many scenarios, well-defined dense rewards may be not available. We consider a variant of MuJoCo task using only episodic reward. Specifically, the original rewards are accumulated and only an episodic reward is given in the final timestep. The agent will receive a 0 reward in all the other timesteps. This sparse setting makes the tasks much more challenging to solve. Contemporary RL algorithms will usually suffer from the sparse rewards and deliver unsatisfactory performance. We aim to use these sparse variants to study whether our RAPID can effectively capture the sparse rewards.

| (a) Walker2d | (b) Hopper | (c) InvertedPendulum | (d) Swimmer |

Figure 11: Rendering of Mujoco environments.

C ABLATIONS

Figure 12 shows the learning curves of RAPID against different ablations. Without local scores, we observe significant performance drop on challenging environments in terms of sample efficiency and final performance, i.e., on MultiRoom-N7-S8, MultiRoom-N10-S10, MultiRoom-N12-S10, KeyCorridor-S3-R3, and KeyCorridor-S4-R3. This suggests that the proposed local score plays an important role in encouraging exploration. We also observe that without buffer, the agent fails to learn a good policy. Naively using the proposed scores as intrinsic reward will harm the performance. Using the extrinsic reward and the global score to rank the episodes also contribute in the challenging environments, such as KeyCorridor-S4-R3. Therefore, the three proposed scoring methods may be complementary and play different roles in different environments.

Figure 12: Learning curves of RAPID and the ablations

D FULL ANALYSIS RESULTS

D.1 IMPACT OF THE NUMBER OF UPDATE STEPS

Figure 13: Impact of training steps S on MiniGrid environments.

D.2 IMPACT OF BUFFER SIZE

Figure 14: Impact of buffer size D on MiniGrid environments.

D.3   PURE EXPLORATION ON MINIGRID

Figure 15: Extrinsic rewards achieved by RAPID and baselines with pure exploration

D.4   LOCAL EXPLORATION SCORE OF PURE EXPLORATION ON MINIGRID

Figure 16: Local exploration scores achieved by RAPID and baselines with pure exploration

E   LEARNING CURVES WITH MORE ROOMS

(a) MultiRoom-N4-S4   (b) MultiRoom-N8-S4   (c) MultiRoom-N12-S4   (d) MultiRoom-N16-S4

(e) MultiRoom-N20-S4   (f) MultiRoom-N24-S4   (g) MultiRoom-N28-S4

Figure 17: The learning curves with more rooms

F   LEARNING CURVES WITH LARGE ROOMS

(a) MultiRoom-N4-S4   (b) MultiRoom-N4-S8   (c) MultiRoom-N4-S12

(d) MultiRoom-N4-S16   (e) MultiRoom-N4-S20   (f) MultiRoom-N4-S24

(g) MultiRoom-N4-S28   (h) MultiRoom-N4-S32   (i) MultiRoom-N4-S36

Figure 18: The learning curves with larger rooms sizes.

G   ABLATION AND ANALYSIS OF MINIWORLD-MAZE

Figure 19: Learning curves of RAPID and the ablations on MiniWorld Maze. We observe minor performance drop when removing the local score, substantial performance drop when removing extrinsic rewards or the buffer.

Figure 20: Impact of training steps on MiniWorld Maze.

Figure 21: Impact of buffer size on MiniWorld Maze.

Figure 22: Extrinsic rewards achieved by RAPID and baselines on MiniWorld Maze with pure exploration.

Figure 23: Local exploration scores achieved by RAPID and baselines on MiniWorld Maze with pure exploration.