Uncertainty-aware Active Learning for Optimal Bayesian Classifier

Abstract

For pool-based active learning, in each iteration a candidate training sample is chosen for labeling by optimizing an acquisition function. Expected Loss Reduction (ELR) methods maximize the expected reduction in the classification error given a new labeled candidate based on a one-step-look-ahead strategy. ELR is the optimal strategy with a single query; however, since such myopic strategies cannot identify the long-term effect of a query on the classification error, ELR may get stuck before reaching the optimal classifier. To improve convergence in the context of optimal Bayesian classification, we utilize an one-step-look-ahead acquisition function based on a weighted form of the mean objective cost of uncertainty (MOCU) that focuses on the uncertainty related to the classification error. The weight scheme is designed to guarantee the Weighted-MOCU algorithm converging to the optimal classifier of the true model. We demonstrate its performance with both synthetic and real-world datasets.

1 Introduction

In supervised learning, labeling data is often expensive and highly time consuming. Active learning is one field of research that aims to address the problem and has been demonstrated for sample-efficient learning with less required labeled data (Gal et al., 2017; Tran et al., 2019; Sinha et al., 2019). In this paper, we focus on pool-based Bayesian active learning for classification with 0-1 loss function. Bayesian active learning starts from the prior knowledge of uncertain models. By optimizing an acquisition function, it chooses the next query training sample for labeling, and then based on the acquired data, updates the belief of uncertain models through Bayes' rule to approach the optimal classifier of the true model, which minimizes the classification error.

Many algorithms have been proposed for active learning for classification. Maximum Entropy Sampling (MES) or Uncertainty Sampling, simply queries the candidate with the maximum predictive entropy (Lewis & Gale, 1994; Sebastiani & Wynn, 2000; Mussmann & Liang, 2018); but the method fails to differentiate between the model uncertainty and the observation uncertainty. Bayesian Active Learning by Disagreement (BALD) seeks the data point that maximizes the mutual information between the observation and the model parameters (Houlsby et al., 2011; Kirsch et al., 2019). Golovin et al. (2010) proposed a greedy algorithm, Equivalence Class Edge Cutting (EC^2), to reduce model uncertainty and proved it to have a near-optimal performance. Maximum Gibbs Error Criterion (maxGEC), targeting at minimizing the policy Gibbs error, is a greedy criterion to choose the candidate with the maximum Gibbs error (Cuong et al., 2013). Most of existing methods focus on reducing the model uncertainty. However, not all the model uncertainty will affect the performance of the learning task of interest. These methods do not identify whether the uncertainty is related to the classification error or not. As a result, they can be inefficient in the sense that they may query candidates that do not directly help improve prediction performance. Besides, there is no theoretical guarantee for these algorithms to reach the optimal classifier.

There exist several Expected Loss Reduction (ELR) methods for active learning that aim to maximize the expected reduction in loss based on a one-step-look-ahead manner (Roy & McCallum, 2001; Zhu et al., 2003; Kapoor et al., 2007), in which the expected future loss is estimated given some new candidate x is labeled. The ELR methods can focus on only the uncertainty related to the loss function to achieve sample-efficient learning. In fact, ELR is the optimal strategy for active learning with a single query (Roy & McCallum, 2001). However, since such myopic algorithms

(a) Predictive probability of class 1

(b) Error regret comparison among methods

Figure 1: (a) Predictive probability of class 1 under uncertainty: the red lines indicate the upper and lower bounds of the predictive probability; the blue dash line is the mean of the predictive probability; the green dash line indicates that the probability is equal to 0.5. (b) Active learning performance.

cannot identify the long-term effect of a query on the loss functions, without special design on the loss function, they may get stuck before reaching the optimal classifier. In this paper, we show such a phenomenon with the ELR methods by both theoretical and empirical analyses. To the best of our knowledge, there are no myopic algorithms that focus on loss reduction while being guaranteed to reach the optimal classifier.

Fig. 1a provides an example of binary classification with one feature where both BALD and ELR methods fail. In the figure, the red lines indicate the upper and lower bounds of the prediction probability of class 1, illustrating the model with higher probability uncertainty on the sides than that in the middle. Querying candidates on the sides will provide more information of the model parameters, and therefore is preferred in BALD. However, since the possible probabilities on the sides are always larger than or less than 0.5, querying candidates on the sides will not help reduce the classification error. On the other hand, ELR queries candidates that help reduce the classification error the most, so it prefers data in the middle whose optimal labels are uncertain given the prior knowledge. The performance shown in Fig. 1b agrees with our analysis. Fig. 1b shows the performance average over 1000 runs, with more details and discussions of the example included in the Appendix. BALD performs inefficiently at the beginning by querying points on both sides. On the other hand, the ELR method performs the best at the beginning, but becomes inefficient after some iterations ($\sim$100), indicating some of its runs get stuck before reaching the optimal classifier.

In this paper, we analyze the reason why ELR methods may get stuck before reaching the optimal classifier, and propose a new strategy to solve this problem. Our contributions are in four parts: 1. We show that ELR methods may get stuck, abstaining active learning from reaching the optimal classifier efficiently. 2. We propose a novel weighted-MOCU active learning method that can focus only on the uncertainty related to the loss for efficient active learning and is guaranteed to converge to the optimal classifier of the true model. 3. We provide the convergence proof of the weighted-MOCU method. 4. We demonstrate the sample-efficiency of our weighted-MOCU method with both synthetic and real-world datasets.

2 BACKGROUND

Optimal Bayesian classifier. Consider a classification problem with candidates $x \in \mathcal{X}$ and class labels $y \in \mathcal{Y} = \{0, 1, \dots, M-1\}$. The predictive probability $p(y|x, \theta)$ is modeled with parameters θ. Assume θ is uncertain with a distribution $\pi(\theta)$ within the uncertainty class Θ. The classification problem is to find a classifier $\psi : \mathcal{X} \to \mathcal{Y}$, which assigns a predicted class label to a given candidate.

The expected 0-1 loss of the classifier ψ for a candidate x, dependent on θ, is defined as $C_\theta(\psi, x)$, which can be derived to be the classification error: $C_\theta(\psi, x) = 1 - p(y = \psi(x)|x, \theta)$. The *optimal classifier* with θ is defined as the classifier minimizing the loss $C_\theta(\psi_\theta, x) = \min_\psi C_\theta(\psi, x) = \min_y \{1 - p(y|x, \theta)\}$. Apparently $\psi_\theta(x) = \arg\max_y p(y|x, \theta)$. When there is model uncertainty with $\pi(\theta)$, an Optimal Bayesian Classifier (OBC) $\psi_{\pi(\theta)}$ is the classifier that has the minimum expected loss over $\pi(\theta)$ (Dalton & Dougherty, 2013):

$$\mathbb{E}_{\pi(\theta)}[C_\theta(\psi_{\pi(\theta)}, x)] = \min_\psi \mathbb{E}_{\pi(\theta)}[C_\theta(\psi, x)] = \min_y \{1 - p(y|x)\} \tag{1}$$

where $p(y|x) = \mathbb{E}_{\pi(\theta)}[p(y|x,\theta)]$ is the predictive distribution. It's easily to see $\psi_{\pi(\theta)}(x) = \arg\max_y p(y|x)$.

Active learning. Active learning collects the training dataset D in a sequential way. For pool-based active learning, in each iteration, we choose a candidate x from the set of potential training samples $\mathcal{X}$ to query for the class label by optimizing an acquisition function $U(x)$. Then, in the Bayesian setting, by including the observed data pair (x,y) to D, we update the posterior distribution based on Bayes' rule. In each iteration, the acquisition function depends on the posterior distribution of model parameters $\pi(\theta|D)$. In the following discussion, to simplify notations, we just use π^* and p^* to stand for the posterior and predictive distributions conditioning on D. When a new observed data point is included, the distributions are updated by Bayes' rule and total probability rule as: $\pi^*(\theta|x,y) = \frac{\pi^*(\theta)p(y|x,\theta)}{p^*(y|x)}$ and $p^*(y'|x',x,y) = \mathbb{E}_{\pi^*(\theta|x,y)}[p(y'|x',\theta)]$.

The acquisition function of ELR methods in the Bayesian setting can be defined by the expected OBC prediction error reduction after observing the new pair (x,y) (Roy & McCallum, 2001):

$$U^{\text{ELR}}(x) = \mathbb{E}_{p(x')}\{\mathbb{E}_{\pi^*(\theta)}[C_\theta(\psi_{\pi^*(\theta)},x')] - \mathbb{E}_{p^*(y|x)}[\mathbb{E}_{\pi^*(\theta|x,y)}[C_\theta(\psi_{\pi^*(\theta|x,y)},x')]]\}, \quad (2)$$

where $p(x')$ is the distribution over $\mathcal{X}$, independent of θ and D. ELR methods assume that we use OBC as the classifier, and in each iteration we should choose the query that maximize the decrease in OBC prediction error. The first term in (2) is the OBC prediction error of $\psi_{\pi^*(\theta)}$, and the second term is the expected prediction error of $\psi_{\pi^*(\theta|x,y)}$, the one-step-look-ahead OBC, with respect to $p^*(y|x)$. In the following section, we analyze why this acquisition function is sample-efficient as it directly targets at classification error reduction while ignoring irrelevant uncertainty with respect to the learning task; but it may get stuck before converging to the true optimal classifier (optimal classifier of the true model).

3 MOCU-BASED ACTIVE LEARNING

3.1 ANALYSIS OF ELR METHODS

In the following analysis, we assume that Θ contains the true model θ_r and $\pi(\theta_r) > 0$. For analyzing ELR methods, we need to borrow the idea of the Mean Objective Cost of Uncertainty (MOCU) for active learning with respect to the corresponding posterior $\pi^*(\theta)$. MOCU is a general objective-oriented uncertainty quantification framework (Yoon et al., 2013). For active learning, MOCU can be defined as the expected loss difference between the OBC and the optimal classifier:

$$\mathcal{M}(\pi^*(\theta)) = \mathbb{E}_{p(x')}[\mathbb{E}_{\pi^*(\theta)}[C_\theta(\psi_{\pi^*(\theta)},x') - C_\theta(\psi_\theta,x')]] \quad (3)$$

$$= \mathbb{E}_{p(x')}[\min_{y'}\{1 - p^*(y'|x')\} - \mathbb{E}_{\pi^*(\theta)}[\min_{y'}\{1 - p(y'|x',\theta)\}]]. \quad (4)$$

The second line is derived from the definition of ψ_θ and (1). The first term in (3) is the OBC error as the loss. In the second term, ψ_θ is the optimal classifier with a specific θ. For the terms inside the expectation operator, we have $C_\theta(\psi_{\pi^*(\theta)},x') - C_\theta(\psi_\theta,x') \geq 0$. Therefore, the second term in (3) is a lower bound of the OBC prediction error.

Similar as ELR methods, we can define an acquisition function by the reduction of MOCU in a one-step-look-ahead manner:

$$U^{\text{MOCU}}(x;\pi(\theta)) = \mathcal{M}(\pi^*(\theta)) - \mathbb{E}_{p^*(y|x)}\mathcal{M}(\pi^*(\theta|x,y)). \quad (5)$$

We will show that the second term in (3), the lower bound of the OBC error, can be cancelled in (5). The acquisition function (5) hence captures the expected reduction of the OBC error given new data and is equivalent to the ELR acquisition function (2). Expanding the second term in (5), we have:

$$\mathbb{E}_{p^*(y|x)}\mathcal{M}(\pi^*(\theta|x,y)) = \mathbb{E}_{p(x')}\{\mathbb{E}_{p^*(y|x)}[\mathbb{E}_{\pi^*(\theta|x,y)}[C_\theta(\psi_{\pi^*(\theta|x,y)},x') - C_\theta(\psi_\theta,x')]]\}. \quad (6)$$

Since $\sum_y p^*(y|x)\pi^*(\theta|x,y) = \pi^*(\theta)$, we can rewrite the first term in (5) as:

$$\mathcal{M}(\pi^*(\theta)) = \mathbb{E}_{p(x')}\{\mathbb{E}_{p^*(y|x)}[\mathbb{E}_{\pi^*(\theta|x,y)}[C_\theta(\psi_{\pi^*(\theta)},x') - C_\theta(\psi_\theta,x')]]\}. \quad (7)$$

Combining (6) and (7) and canceling the corresponding terms, the acquisition function is:

$$U^{\text{MOCU}}(x;\pi^*(\theta)) = \mathbb{E}_{p(x')}\{\mathbb{E}_{p^*(y|x)}[\mathbb{E}_{\pi^*(\theta|x,y)}[C_\theta(\psi_{\pi^*(\theta)},x') - C_\theta(\psi_{\pi^*(\theta|x,y)},x')]]\}. \quad (8)$$

From (8), we can also conclude that $U^{\text{MOCU}}(x; \pi^*(\theta)) \geq 0$. By definition, $\psi_{\pi^*(\theta|x,y)}$ is the OBC with the minimum expected classification error over $\pi^*(\theta|x,y)$. Therefore, $\mathbb{E}_{\pi^*(\theta|x,y)}[C_\theta(\psi_{\pi^*(\theta|x,y)}, x')] \leq \mathbb{E}_{\pi^*(\theta|x,y)}[C_\theta(\psi_{\pi^*(\theta)}, x')]$ and we have $U^{\text{MOCU}}(x; \pi^*(\theta)) \geq 0$, indicating collecting new data will reduce MOCU.

We first analyze ELR methods in the form of MOCU-based methods by showing that MOCU ignores the uncertainty irrelevant to the OBC prediction error. MOCU captures the difference between the OBC error and its lower bound. When MOCU is 0, the OBC converges to the true optimal classifier and we cannot reduce the OBC prediction error further. In that case, we say that OBC has reached the true optimal classifier. From (4), when $\mathcal{M}(\pi^*(\theta)) = 0$, we have $\forall x \in \mathcal{X}$, $\forall \theta \in \text{supp}(\pi^*)$, $\psi_\theta = \psi_{\pi^*(\theta)}$, i.e. $\arg \max_y p(y|x, \theta) = \arg \max_y p(y|x)$. On the other hand, MOCU being 0 does not require elimination of total model uncertainties, for which it requires $p(y|x, \theta) = p(y|x)$, $\forall x \in \mathcal{X}$, $\forall \theta \in \text{supp}(\pi^*)$, apparently a stronger statement than MOCU being 0. That means not all the uncertainties in $p(y|x, \theta)$ are captured in MOCU. Denote MOCU at point x as $K(x, \pi^*(\theta)) = \mathbb{E}_{\pi^*(\theta)}[C_\theta(\psi_{\pi^*(\theta)}, x) - C_\theta(\psi_\theta, x)]$, so that $\mathcal{M}(\pi^*(\theta)) = \mathbb{E}_{p(x)}[K(x, \pi^*(\theta))]$. We consider the uncertainty in $p(y|x, \theta)$ to be "objective-irrelevant" to OBC prediction error if $\mathbb{E}_{\pi^*(\theta)}[p(y|x, \theta) - p(y|x)]^2 > 0$ and $K(x, \pi^*(\theta)) = 0$. If we only reduce objective-irrelevant uncertainty, the value of MOCU will not change. For example, in Fig. 1a the uncertainty of $p(y|x, \theta)$ on the two sides is objective-irrelevant. Evaluating points at $x = \pm 4$ will only reduce irrelevant uncertainty and it will not be considered in either MOCU- or ELR-based methods. That explains why in the first several active learning iterations, the ELR or MOCU reduction methods can be more efficient than the methods guided by total uncertainty reduction, such as BALD.

Now we explain why ELR methods may get stuck before converging to the true optimal classifier. When we have $\forall x \in \mathcal{X}, U^{\text{MOCU}}(x; \pi^*(\theta)) = 0$ and assume the tie is broken randomly, the acquisition function will suggest any random candidate in the pool. When that happens, we say that ELR methods get stuck as the OBC has not reached the true optimal classifier; i.e., $\mathcal{M}(\pi^*(\theta))$ is still larger than 0. This is possible because in (8), the difference directly depends on $\arg \max_{y'} p^*(y'|x')$ and $\arg \max_{y'} p^*(y'|x', x, y)$, not the values of $p^*(y'|x')$ and $p^*(y'|x', x, y)$. Assume that observing x can reduce uncertainty on $p(y|x, \theta)$ and $K(x', \pi^*(\theta)) > 0$, i.e. the MOCU at x' is larger than 0. When we observe a single query pair (x, y), the value of $p^*(y'|x', x, y)$ may not change enough so that $\arg \max_{y'} p^*(y'|x', x, y)$ may still be the same. Consequently, OBC prediction may not change by observing one single query pair and the myopic acquisition function may ignore the potential that sampling x multiple times may shift the OBC predictions in the long run. In theory, based on (8), $\forall x \in \mathcal{X}, U^{\text{MOCU}}(x; \pi^*(\theta)) = 0$ iff $\forall x, x' \in \mathcal{X}$, $\forall y \in \mathcal{Y}$, $\psi_{\pi^*(\theta|x,y)} = \psi_{\pi^*(\theta)}$, i.e. $\arg \max_{y'} p(y'|x', x, y) = \arg \max_{y'} p(y'|x')$. On the other hand, converging to the optimal classifier requires $\mathcal{M}(\pi^*(\theta)) = 0$, which is a stronger statement as shown below. Since $U^{\text{MOCU}}(x; \pi^*(\theta)) = \mathcal{M}(\pi^*(\theta)) - \mathbb{E}_{p^*(y|x)}[\mathcal{M}(\pi^*(\theta|x,y))] \geq 0$, $\mathcal{M}(\pi^*(\theta)) = 0$ indicates $\mathbb{E}_{p^*(y|x)}[\mathcal{M}(\pi^*(\theta|x,y))] = 0$. Therefore $\mathcal{M}(\pi^*(\theta)) = 0$ if and only if $\forall x, x' \in \mathcal{X}$, $\forall y \in \mathcal{Y}$, $\forall \theta \in \text{supp}(\pi^*)$, $\arg \max_{y'} p(y'|x', x, y) = \arg \max_{y'} p(y'|x') = \arg \max_{y'} p(y'|x', \theta)$. Hence, we have no guarantee that $\forall x \in \mathcal{X}, U^{\text{MOCU}}(x; \pi^*(\theta)) = 0$ indicates $\mathcal{M}(\pi^*(\theta)) = 0$.

In summary, ELR methods are efficient by ignoring objective-irrelevant uncertainty. But if sampling one data point can only provide little information and cannot help OBC prediction, they will ignore its long-run effect on prediction performance. As a result, they may get stuck before converging to the optimal classifier. To keep the efficient sampling property by ignoring objective-irrelevant uncertainty but avoid getting stuck, we propose a one-step-look-ahead acquisition function based on a weighted version of MOCU, which can capture the change of the predictive probability from one-step samples. If that change can potentially shift the OBC predictions in the long run, our acquisition function will have a positive value, and thereby avoid the problems that ELR suffers from.

3.2 WEIGHTED MOCU-BASED ACTIVE LEARNING

In this section, we propose a modified MOCU-based acquisition function that has the theoretical guarantee to converge to the optimal classifier. Specifically, we propose a modified MOCU function that multiplies a weight with each loss difference between the OBC $\psi_{\pi^*(\theta)}$ and the optimal classifier ψ_θ in the original MOCU definition as follows:

$$\mathcal{M}^w(\pi^*(\theta)) = \mathbb{E}_{p(x')}\{\mathbb{E}_{\pi^*(\theta)}\{w(\pi^*(\theta), x', \theta)[C_\theta(\psi_{\pi^*(\theta)}, x') - C_\theta(\psi_\theta, x')]\}\}, \quad (9)$$

where $w(\pi^*(\theta), x', \theta) > 0$ is the weighting function. The corresponding acquisition function is:

$$U^w(x; \pi^*(\theta)) = \mathcal{M}^w(\pi^*(\theta)) - \mathbb{E}_{p^*(y|x)}[\mathcal{M}^w(\pi^*(\theta|x, y))]. \tag{10}$$

In (9), as more data are collected and the model parameter distribution $\pi^*(\theta)$ changes, $w(\pi^*(\theta), x', \theta)$ will change accordingly. The change of $w(\pi^*(\theta), x', \theta)$ cannot affect the value of weighted-MOCU if $C_\theta(\psi_{\pi^*(\theta)}, x') - C_\theta(\psi_\theta, x') = 0$, $\forall \theta \in \mathrm{supp}(\pi^*(\theta))$, which means the uncertainty at x' is objective-irrelevant. So the acquisition function based on the weighted MOCU will inherit the property of MOCU-based active learning to directly target at classification error reduction while ignoring irrelevant uncertainty. On the other hand, by introducing the predictive probability into the weighting functions, the probability change from one-step samples can be captured by the weighted-MOCU based acquisition function such that it can have theoretical convergence guaranteed to the optimal classifier.

There are some active learning policies, such as uniform exploration and ϵ-greedy policies (Hoang et al., 2014), that can converge to the true model almost surely. However, they focus on the total uncertainty reduction to derive the full knowledge of the true model. Since our learning objective is to minimize the classification error, we focus on the convergence to the optimal classifier. Converging to the true model is unnecessary and inefficient for classification. Our weighted-MOCU based policy as a myopic policy can converge to the optimal classifier and hence it is expected to be efficient both at the beginning and in the long run.

In the following, we design a weighting function to make $\mathcal{M}^w(\pi^*(\theta)) = 0$ if and only if $\forall x \in \mathcal{X}, U^w(x; \pi^*(\theta)) = 0$ and show that active learning based on this weighted MOCU converges to the optimal classifier. Specifically, we propose the following weighting function:

$$w(\pi^*(\theta), x', \theta) = 1 - K(x', \pi^*(\theta)), \text{ with} \tag{11}$$

$$K(x', \pi^*(\theta)) = \mathbb{E}_{\pi^*(\theta)}[C_\theta(\psi_{\pi^*(\theta)}, x') - C_\theta(\psi_\theta, x')] \tag{12}$$

$$= \min_{y'} \mathbb{E}_{\pi^*(\theta)}[1 - p(y'|x', \theta)] - \mathbb{E}_{\pi^*(\theta)}[\min_{y'}(1 - p(y'|x', \theta)] \tag{13}$$

$$= \mathbb{E}_{\pi^*(\theta)}[\max_{y'} p(y'|x', \theta)] - \max_{y'} p^*(y'|x'). \tag{14}$$

It is clear that $K(x', \pi^*(\theta)) \geq 0$ by (13). For binary classification, $\max_{y'} p^*(y'|x') \geq 0.5$. As $\mathbb{E}_{\pi^*(\theta)}[\max_{y'} p(y'|x', \theta)] \leq 1$, from (14), we have $K(x', \pi^*(\theta)) \leq 0.5$, demonstrating that the weighting function in (11) satisfies the requirement $w(\pi^*(\theta), x', \theta) > 0$.

Note that this simple weighting function does not change with respect to the model parameter values. Substituting it into the weighted MOCU expression, we have:

$$\mathcal{M}^w(\pi^*(\theta)) = \mathbb{E}_{p(x')}\{(1 - K(x', \pi^*(\theta))) \cdot K(x', \pi^*(\theta))\}. \tag{15}$$

Theoretical convergence guarantee. Now we prove that if active learning for a binary classification problem is guided by the acquisition function defined by (10) and (11), MOCU will converge to 0 almost surely and hence the procedure will converge to learning the optimal classifier of the true model. We assume that both $\mathcal{X}$ and Θ are discrete with finite elements; the true model parameter $\theta_r \in \Theta$ and the prior distribution $\pi^0(\theta)$ over Θ satisfies $\pi^0(\theta_r) > 0$. In the following proofs, we denote the posterior by $\pi^n(\theta)$ and predictive probability $p^n(y|x)$ in the n-th weighted MOCU based active learning iteration, respectively.

Lemma 1 *Given $\pi(\theta)$, $\mathcal{M}(\pi(\theta)) = 0$ if and only if $\mathcal{M}^w(\pi(\theta)) = 0$.*

Lemma 1 indicates that if $\mathcal{M}^w(\pi(\theta)) = 0$, $\psi_{\pi(\theta)}$ converges to the optimal classifier ψ_{θ_r} as explained in Section 3.1.

Proof. Based on (3), since $C_\theta(\psi_{\pi(\theta)}, x') - C_\theta(\psi_\theta, x') \geq 0$, so $\mathcal{M}(\pi(\theta)) = 0$ iff $C_\theta(\psi_{\pi(\theta)}, x') - C_\theta(\psi_\theta, x') = 0 \ \forall x' \in \mathcal{X}, \ \forall \theta \in \mathrm{supp}(\pi)$. In addition, in (9), $w(\pi(\theta), x', \theta) > 0$, so $C_\theta(\psi_{\pi(\theta)}, x') - C_\theta(\psi_\theta, x') = 0 \ \forall x' \in \mathcal{X}, \ \forall \theta \in \mathrm{supp}(\pi)$ iff $\mathcal{M}^w(\pi(\theta)) = 0$, which concludes the proof.

Lemma 2 *Define $G(x', \pi(\theta)) = (1 - K(x', \pi(\theta)))K(x', \pi(\theta))$. $G(x', \pi(\theta))$ is a concave function of $\pi(\theta)$.*

It is important to choose a weight function rendering a concave function G as it guarantees the acquisition function to be larger than or equal to 0, which means adding a new observation helps to reduce weighted MOCU.

Proof. In the following proof, we omit the argument x' in G and K for simplicity. Owing to the concavity of the $\min$ operator, $\min_{y'} \mathbb{E}_{\pi(\theta)}[1 - p(y'|x', \theta)]$ is a concave function of $\pi(\theta)$. With $\mathbb{E}_{\pi(\theta)}[\min_{y'}(1 - p(y'|x', \theta)]$ being a linear function of $\pi(\theta)$, based on (13), $K(\pi(\theta))$ equals to a concave function subtracting a linear function and thus is also a concave function.

As analyzed in Section 3.2, $0 \leq K(\pi(\theta)) \leq 0.5$. We define $T(\kappa) = (1 - \kappa)\kappa, \kappa \in [0, 0.5]$, a strictly increasing and strictly concave function. $G(\pi(\theta)) = T[K(\pi(\theta))]$ is a composite function of T and K. So we conclude the proof with the property of the concavity for the composite functions:

$$
\begin{aligned}
T[K(\lambda \pi_1(\theta) + (1 - \lambda)\pi_2(\theta))] &\geq T[\lambda K(\pi_1(\theta)) + (1 - \lambda)K(\pi_2(\theta))] \\
&\geq \lambda T[K(\pi_1(\theta))] + (1 - \lambda)T[K(\pi_2(\theta))]. \quad (16)
\end{aligned}
$$

The first inequality is because T is increasing and K is concave; and the second inequality holds as T is a concave function.

Lemma 3 $\forall x \in \mathcal{X}, U^w(x; \pi(\theta)) \geq 0$.

Proof. Since $\pi(\theta) = \sum_y p(y|x)\pi(\theta|x, y)$, by Jensen's inequality, we have $G(x', \pi(\theta)) \geq \mathbb{E}_{y|x}[G(x', \pi(\theta|x, y))]$ as G is a concave function. So the weighted MOCU acquisition function:

$$
U^w(x; \pi(\theta)) = \mathbb{E}_{x'}[G(x', \pi(\theta))] - \mathbb{E}_{x'}[\mathbb{E}_{y|x}[G(x', \pi(\theta|x, y))]] \geq 0. \quad (17)
$$

Lemma 4 *At the n-th active learning iteration, if $U^w(x; \pi^n(\theta)) = 0, \forall x \in \mathcal{X}, \mathcal{M}^w(\pi^n(\theta)) = 0$.*

This lemma states that if the acquisition function values of all candidates with respect to $\pi(\theta)$ are 0, the weighted MOCU is 0. By Lemma 1, so is MOCU. With these, we can conclude that the OBC with respect to $\pi(\theta)$ has converged to the optimal classifier. This is significant when comparing with original MOCU- or ELR-based methods as we have shown that this is not the case for them, which may get stuck earlier and therefore lose efficiency.

Proof. We will prove the contrapositive of the lemma: assuming $\mathcal{M}^w(\pi^n(\theta)) > 0, \exists x \in \mathcal{X}$ s.t. $U^w(x; \pi^n(\theta)) > 0$.

Based on (15), $M^w(\pi^n(\theta)) > 0$ indicating $\exists x \in \mathcal{X}$ s.t. $K(x, \pi^n(\theta)) > 0$. It is sufficient to show that if $K(x, \pi^n(\theta)) > 0$, then $U^w(x; \pi^n(\theta)) > 0$. To prove that, we only need to prove $G(x, \pi^n(\theta)) > \mathbb{E}_{p^n(y|x)}[G(x, \pi^n(\theta|x, y))]$; then by (17), $U^w(x; \pi^n(\theta)) > 0$.

Since G is a concave function, we know $G(x, \pi^n(\theta)) \geq \mathbb{E}_{p^n(y|x)}[G(x, \pi^n(\theta|x, y))]$. With $\pi^n(\theta) = \sum_y p^n(y|x)\pi^n(\theta|x, y)$, we can rewrite (16) as:

$$
T[K(x, \pi^n(\theta))] \geq T[\mathbb{E}_{p^n(y|x)}[K(x, \pi^n(\theta|x, y))]] \geq \mathbb{E}_{p^n(y|x)}[T[K(x, \pi^n(\theta|x, y))]].
$$

The second equality holds only if $\forall y \in \{0, 1\}, K(x, \pi^n(\theta|x, y)) = K(x, \pi^n(\theta))$, which means that to prove $G(x, \pi^n(\theta)) > \mathbb{E}_{y|x}[G(x, \pi^n(\theta|x, y))]$, we just need to show $\exists y \in \{0, 1\}, K(x, \pi^n(\theta|x, y)) \neq K(x, \pi^n(\theta))$. In the following proof, we will show if $K(x, \pi^n(\theta)) > 0$, then $\exists y \in \{0, 1\}$, s.t. $K(x, \pi^n(\theta|x, y)) \neq K(x, \pi^n(\theta))$.

Denote $\hat{y} = \arg \max_y p^n(y|x)$. By (14) we have:

$$
K(x, \pi^n(\theta)) = \sum_{\theta \in \text{supp}(\pi^n)} \pi^n(\theta)[\max_y p(y|x, \theta) - p(\hat{y}|x, \theta)]. \quad (18)
$$

Since $K(x, \pi^n(\theta)) > 0$, the parameter set $\Theta_o^n = \{\theta \in \text{supp}(\pi^n) : \arg \max_y p(y|x, \theta) \neq \hat{y}\}$ is not empty. We only keep the nonzero terms in K:

$$
K(x, \pi^n(\theta)) = \sum_{\theta \in \Theta_o} \pi^n(\theta)[\max_y p(y|x, \theta) - p(\hat{y}|x, \theta)]. \quad (19)
$$

For binary classification, $\hat{y} = \arg \max_y p^n(y|x)$, indicating that the predictive probability $p^n(\hat{y}|x) \geq 0.5$. For $\theta \in \Theta_o, p(\hat{y}|x, \theta) < 0.5$, we have: if $\theta \in \Theta_o, \pi^n(\theta|x, \hat{y}) = \frac{\pi^n(\theta)p(\hat{y}|x, \theta)}{p^n(\hat{y}|x)} < \pi^n(\theta)$.

If we observe $(x, \hat{y})$ in $(n+1)$-th iteration, the updated posterior predictive probability $p^n(\hat{y}|x, \{x, \hat{y}\}) \geq p^n(\hat{y}|x) \geq 0.5$ and therefore $\max_y p^n(y|x, \{x, \hat{y}\}) = \hat{y}$. Hence,

$$K(x, \pi^n(\theta|x, \hat{y})) = \sum_{\theta \in \Theta_o} \pi^n(\theta|x, \hat{y})[\max_y p(y|x, \theta) - p(\hat{y}|x, \theta)] < K(x, \pi^n(\theta)). \quad (20)$$

Since $K(\pi^n(\theta|x, \hat{y}), x) \neq K(\pi^n(\theta), x)$, we have $G(x, \pi^n(\theta)) > \mathbb{E}_{p^n(y|x)}[G(x, \pi^n(\theta|x, y))]$ and

$$U^w(x; \pi^n(\theta)) = \mathbb{E}_{p(x')}[G(x', \pi^n(\theta))] - \mathbb{E}_{p(x')}[\mathbb{E}_{p^n(y|x)}[G(x', \pi^n(\theta|x, y))]]$$
$$\geq p(x)[G(x, \pi^n(\theta)) - \mathbb{E}_{p^n(y|x)}[G(x, \pi^n(\theta|x, y))]] > 0. \quad (21)$$

This concludes our proof.

Lemma 5 *If following some policy a candidate x is measured infinitely often almost surely, then $\lim_{n \to \infty} U^w(x; \pi^n(\theta)) = 0$ almost surely.*

Intuitively, if a candidate has been measured many times, there is no benefit to measure it again.

Proof. Adding a new data point (x, y) to D, the posterior change is: $\pi^n(\theta|x, y) = \frac{\pi^n(\theta)p(y|x,\theta)}{p^n(y|x)}$. Define $\Theta_x = \{\theta \in \Theta : p(y|x, \theta) = p(y|x, \theta_r)\}$. Denote $N_x(n)$ as the times of the candidate x being queried at the n-th iteration. Based on the posterior consistency theory we have $\sum_{\theta \in \Theta_x} \pi^n(\theta) \xrightarrow{a.s.} 1$ as $N_x(n) \to \infty$ (Gelman et al., 2013). Since $p^n(y|x) = \sum_{\theta \in \Theta} \pi^n(\theta)p(y|x, \theta)$, we have $\lim p^n(y|x) \xrightarrow{a.s.} p(y|x, \theta_r)$. Hence $\lim_{n \to \infty} \pi^n(\theta|x, y) = \pi^n(\theta)$ almost surely, which indicates $\lim_{n \to \infty} U^w(x; \pi^n(\theta)) = 0$ almost surely.

Theorem 1 *Assume that both $\mathcal{X}$ and Θ are discrete with finite elements, the true model parameter $\theta_r \in \Theta$ and the prior distribution $\pi^0(\theta)$ over Θ satisfies $\pi^0(\theta_r) > 0$; then for the active learning algorithm defined by the acquisition function (10), we have $\lim_{n \to \infty} \mathcal{M}(\pi^n(\theta)) = 0$.*

Proof. As the number of active learning iterations $n \to \infty$, following the acquisition function (10), some of the candidates can be measured infinite times. Define $\mathcal{X}_A \subset \mathcal{X}$ as the set whose candidates have been measured infinite times. Denote the measuring sequence of the candidates following (10) as $\{x_n\}$, we have: $\exists N, \; s.t. \; \forall n > N, x_n \in \mathcal{X}_A(\omega)$. Based on Lemma 5, $\lim_{n \to \infty} D^w(x_n) = 0$.

On the other hand, since with the weighted MOCU $U^w(x_n; \pi^n(\theta)) = \max_{x \in \mathcal{X}} U^w(x; \pi^n(\theta))$, then $\lim_{n \to \infty} D^w(x_n) = 0$ indicates that $\forall x \in \mathcal{X}$, $U^w(x; \pi^n(\theta))$ uniformly converges to 0. Based on Lemma 4, $\lim_{n \to \infty} \mathcal{M}_n^w = 0$ and we can conclude the proof with Lemma 1.

Figure 2: The expected OBC error regret comparison between different active learning algorithms on binary classification.

4 EMPIRICAL RESULTS

We benchmark our weighted-MOCU method with other active learning algorithms, including random sampling, MES (Sebastiani & Wynn, 2000), BALD (Houlsby et al., 2011) and ELR (Roy & McCallum, 2001), on both simulated and real-world classification datasets.

Simulated experiments. In addition to the one-dimensional simulated example introduced in Section 1, we test our model on a similar simulation setting as the *block in the middle* dataset in (Houlsby et al., 2011), where noisy observations with flip error are simulated in a block region on the decision boundary. We generate data based on a two-dimensional Bayesian logistic regression model: $p(y = 1|\boldsymbol{x}, \boldsymbol{w}, b) = \frac{1}{1+\exp(-\boldsymbol{w}^T\boldsymbol{x}-b)}$ with $\boldsymbol{x} \in [-4, 4]^2$. The block region is within $[-0.5, 0.5]^2$ with the flip error rate equal to 0.3. For the model parameter prior, $w_1 \sim \mathcal{U}(0.3, 0.8)$ is uniformly distributed and $w_2 \sim \mathcal{U}(-0.25, 0.25)$ and $b \sim \mathcal{U}(-0.25, 0.25)$; w_1, w_2 and b are independent.

We randomly sample 100 particles from the parameter prior with one of the particles as the true model parameter. The five active learning algorithms are compared for 500 iterations by the OBC error with respect to the testing data generated from the true model. We repeat the simulations for 500 runs and plot the average performance with standard deviation bars in Fig. 2. The error regret is defined as the error difference between the OBC and the true optimal classifier. From the figure, MES simply chooses the candidates with the predictive probability closest to 0.5, it can sample many noisy observations from the block region. ELR performs well in the first several iterations but poorly after 200 samples. Our weighted MOCU performs the best.

Figure 3: The expected OBC error regret comparison between different active learning algorithms on 3 class classification.

We have also benchmarked our weighted MOCU with other active learning algorithms for a synthetic multi-class classification problem. We assume that the probabilistic model $p(y|\boldsymbol{x}, \sigma_y^2) = f_y(\boldsymbol{x}, \sigma_y^2)/\sum_{y'} f(\boldsymbol{x}, \sigma_{y'}^2)$ with $\boldsymbol{x} \in [-2, 2]^2$, $y \in \{0, 1, 2\}$ and $f_y = \exp(-(x - m_y)^2/2\sigma_y^2)$. We set m_y to be $(0, 0)$, $(1, 0)$, $(0, 1)$ for $y = 0, 1, 2$ respectively; and $\sigma_y^2 \sim \mathcal{U}(1, 5)$ being the uncertain parameters. Same as the previous binary classification experiment, we test for 300 runs and plot the average performance with standard deviations in Fig. 3. We can observe that ELR performs poorly in the long run while our Weighted MOCU has better empirical performance on par with BALD More results and discussion are in Appendix D & E.

Real-world benchmark experiments. We also present the results on the UCI User Knowledge dataset (Kahraman et al., 2013). The dataset includes 403 samples assigned to 4 classes (High, Medium, Low, Very Low) with each sample having five features in $[0, 1]^5$. We have grouped the samples into two classes with 224 samples in High or Medium, 179 in Low or Very Low. We consider the first and fifth features for classification and equally divide the feature space into 4×4 bins. For the i-th bin, the probability of candidates belonging to High

Figure 4: Classification error rate comparison on UCI User Knowledge dataset

or Medium is denoted by θ_i, $1 \leq i \leq 16$ and θ_i's are independent and $\theta_i \sim \text{Beta}(\alpha_i, \beta_i)$, with hyperparameters α_i and β_i. We present the results with the uncertainty class by setting $\alpha_i = \beta_i = 10$ in eight randomly chosen bins and for the other bins, $\alpha_i = 5, \beta_i = 2$ if the true frequency of High or Medium in the i-th bin is lower than 0.5 and $\alpha_i = 2, \beta_i = 5$ otherwise. We have randomly drawn 150 samples from each class as the candidate pool and perform the five different active learning algorithms. We repeat the whole procedure 150 times and the average error rates are shown in Fig. 4. While ELR clearly gets stuck in this setup, our Weighted MOCU method can converge to the optimal classifier with less samples than all the competing methods. BALD performs poorly as the bins with $\alpha = \beta = 10$ have less uncertainty but have more impact on OBC prediction and BALD fails to identify that. More comprehensive results and discussion, including results on the UCI Letter Recognition dataset (Dua & Graff, 2017), can be found in Appendix F.

5 CONCLUSIONS

We have identified potential convergence problems of existing ELR methods and proposed a novel active learning strategy for classification based on weighted MOCU. Our weighted MOCU directly targets at decreasing the classification error and ignores uncertainty irrelevant to the classification performance. More critically, it can capture continuous change in objective-relevant uncertainty. Hence, our new active learning can be efficient both at the beginning and in the long run with the guarantee of converging to the optimal classifier. Empirical results have demonstrated active learning guided by weighted MOCU leads to sample-efficient learning. Future work includes theoretical analysis of MOCU-guided active learning for multi-class classification, as well as developing optimization methods for active learning in continuous space.

REFERENCES

Nguyen Viet Cuong, Wee Sun Lee, Nan Ye, Kian Ming A Chai, and Hai Leong Chieu. Active learning for probabilistic hypotheses using the maximum gibbs error criterion. In *Advances in Neural Information Processing Systems*, pp. 1457–1465, 2013.

Lori A Dalton and Edward R Dougherty. Optimal classifiers with minimum expected error within a bayesian frameworkpart i: Discrete and gaussian models. *Pattern Recognition*, 46(5):1301–1314, 2013.

Dheeru Dua and Casey Graff. UCI machine learning repository, 2017. URL `http://archive.ics.uci.edu/ml`.

Yarin Gal, Riashat Islam, and Zoubin Ghahramani. Deep bayesian active learning with image data. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 1183–1192. JMLR. org, 2017.

Andrew Gelman, John B Carlin, Hal S Stern, David B Dunson, Aki Vehtari, and Donald B Rubin. *Bayesian data analysis*. CRC press, 2013.

Daniel Golovin, Andreas Krause, and Debajyoti Ray. Near-optimal bayesian active learning with noisy observations. In *Advances in Neural Information Processing Systems*, pp. 766–774, 2010.

Trong Nghia Hoang, Bryan Kian Hsiang Low, Patrick Jaillet, and Mohan Kankanhalli. Nonmyopic ϵ-bayes-optimal active learning of gaussian processes. 2014.

Neil Houlsby, Ferenc Huszár, Zoubin Ghahramani, and Máté Lengyel. Bayesian active learning for classification and preference learning. *arXiv preprint arXiv:1112.5745*, 2011.

H Tolga Kahraman, Seref Sagiroglu, and Ilhami Colak. The development of intuitive knowledge classifier and the modeling of domain dependent data. *Knowledge-Based Systems*, 37:283–295, 2013.

Ashish Kapoor, Eric Horvitz, and Sumit Basu. Selective supervision: Guiding supervised learning with decision-theoretic active learning. In *IJCAI*, volume 7, pp. 877–882, 2007.

Andreas Kirsch, Joost van Amersfoort, and Yarin Gal. Batchbald: Efficient and diverse batch acquisition for deep bayesian active learning. In *Advances in Neural Information Processing Systems*, pp. 7024–7035, 2019.

David D Lewis and William A Gale. A sequential algorithm for training text classifiers. In *SIGIR94*, pp. 3–12. Springer, 1994.

Stephen Mussmann and Percy Liang. On the relationship between data efficiency and error for uncertainty sampling. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 3674–3682, Stockholmsmssan, Stockholm Sweden, 10–15 Jul 2018. PMLR.

N Roy and A McCallum. Toward optimal active learning through sampling estimation of error reduction. int. conf. on machine learning, 2001.

Paola Sebastiani and Henry P Wynn. Maximum entropy sampling and optimal bayesian experimental design. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 62(1): 145–157, 2000.

Samarth Sinha, Sayna Ebrahimi, and Trevor Darrell. Variational adversarial active learning. In *The IEEE International Conference on Computer Vision (ICCV)*, October 2019.

Toan Tran, Thanh-Toan Do, Ian Reid, and Gustavo Carneiro. Bayesian generative active deep learning. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 6295–6304, Long Beach, California, USA, 09–15 Jun 2019. PMLR.

Byung-Jun Yoon, Xiaoning Qian, and Edward R Dougherty. Quantifying the objective cost of uncertainty in complex dynamical systems. *IEEE Transactions on Signal Processing*, 61(9):2256–2266, 2013.

Xiaojin Zhu, John Lafferty, and Zoubin Ghahramani. Combining active learning and semi-supervised learning using gaussian fields and harmonic functions. In *ICML 2003 workshop on the continuum from labeled to unlabeled data in machine learning and data mining*, volume 3, 2003.

Uncertainty-aware Active Learning for OBC: Appendix

In this appendix, we provide the pseudo-code of our weighted-MOCU based active learning algorithm, as well as more detailed descriptions of our experiments, additional results, and discussions on the weighted MOCU for multi-class classification.

A. WEIGHTED-MOCU BASED ACTIVE LEARNING & COMPUTATIONAL COMPLEXITY

The pseudo-code of our weighted-MOCU based active learning is provided in Algorithm 1, with the following computational complexity analysis.

Computational complexity We now estimate the computational complexity of Algorithm 1 for the discrete feature and parameter spaces. Assume that the size of the discrete feature space is $N_x = |\mathcal{X}|$, the size of the uncertainty set of classifiers is $N_\theta = |\Theta|$. For active learning, there are T iterations of queries as the total budget. We study the total complexity of the active learning algorithm. In the WMOCU function, line 36 is called for $O(N_x N_\theta M)$ times. In ACQUISITIONFUN, WMOCU is called for constant times. Finally, in the main procedure, in each iteration, ACQUISITIONFUN is called for each x. Hence, the total complexity of Weighted MOCU-based active learning is $O(T N_x^2 N_\theta)$.

(a) Acquisition function of BALD   (b) Acquisition function of ELR

Figure S1. The acquisition functions based on the model (22).

B. DETAILS OF THE ONE-DIMENSIONAL ACTIVE LEARNING EXAMPLE IN INTRODUCTION

The example in the Introduction of the main text is a binary classification problem with $y \in \{0, 1\}$ based on only one feature $x \in [-4, 4]$. The underlying discriminative model is based on:

$$p_c(y = 1|x, a, b) = S(x) + \epsilon(x, a, b)$$
$$S(x) = 0.6 \frac{\exp(x)}{1 + \exp(x)} + 0.2$$
$$\epsilon(x, a, b) = a \exp(-x^2) + b[\exp(-(x-4)^2) + \exp(-(x+4)^2)], \quad (22)$$

where $\boldsymbol{\theta} = (a, b)^{\mathrm{T}}$ is the uncertain parameter vector, with a and b independently uniformly distributed on the intervals $[-0.1, 0.1]$ and $[-0.2, 0.2]$ respectively. The discriminative model equals to a sigmoid function $S(x)$ plus the perturbation $\epsilon(x, a, b)$, a mixed Gaussian function that changes with a and b, the uncertainty class of classifiers can be constructed by such deviations on $S(x)$. The discriminative model has higher uncertainty near $x \pm 4$, which depends on the value of b, than the uncertainty near $x = 0$, which depends on a. Value of a and b has negligible influence on the $p(y = 1|x)$ near $x \pm 4$ and $x = 0$, respectively. So by observing data at $x = \pm 4$, the uncertainty on $p_c(y = 1|x = 0)$ will not be reduced significantly.

In Figs. S1(a) and (b), we show how the acquisition functions of BALD and ELR change with respect to x. It is clear that the acquisition function of BALD at $x = \pm 4$ should have the largest value since $p(y|x)$ has the highest uncertainty. On the other hand, since $p(y|x = \pm 4)$ is always above

---

Algorithm 1 Weighted-MOCU based active learning

1: **function** MAINPROCEDURE( )
2:     Set a discrete candidate set $\mathcal{X}$, the probability array p_x, and iteration number T
3:     Set the discrete parameter set Θ and the corresponding probability array π_θ
4:     Initialize the data set $D = \emptyset$
5:     $\pi_{\theta|D} = \pi_\theta$
6:     **for** $t = 1$ to T **do**
7:         **for** x in $\mathcal{X}$ **do**
8:             Store ACQUISITIONFUN$(x, \pi_{\theta|D})$ to the array $U_\mathcal{X}$
9:         **end for**
10:        Optimize $U_\mathcal{X}$ and find the maximum point x^*
11:       Obtain the label y^* corresponds to x^* and update $D = D \cup \{x^*, y^*\}$
12:       **for** θ in Θ **do**
13:          Update $\pi_{\theta|D} \propto \pi_{\theta|D} \cdot p(y^*|x^*, \theta)$
14:       **end for**
15:       $\mathcal{X} = \mathcal{X}/\{x^*\}$
16:     **end for**
17: **end function**

18: **function** ACQUISITIONFUN$(x, \pi_{\theta|D})$
19:     $wmocu_current = $WMOCU$(\pi_{\theta|D})$
20:     $wmocu\_next = 0$
21:     **for** y in $\{0, 1\}$ **do**
22:         **for** θ in Θ **do**
23:             Generate array $p(\theta, y|D, x) = \pi_{\theta|D} \cdot p(y|x, \theta)$
24:         **end for**
25:         $p(y|D, x) = \sum_\theta p(\theta, y|D, x)$
26:         $\pi_{\theta|D,x,y} = p(\theta, y|D, x)/p(y|D, x)$
27:         $wmocu\_next = wmocu\_next + p(y|D, x) \cdot$ WMOCU$(\pi_{\theta|D,x,y})$
28:     **end for**
29:     **return** $wmocu\_current - wmocu\_next$
30: **end function**

31: **function** WMOCU$(\pi_{\theta|D})$
32:     $wmocu = 0$
33:     **for** x' in $\mathcal{X}$ **do**
34:         $bayesian\_error = 0$
35:         **for** θ in Θ **do**
36:             $bayesian\_error = bayesian\_error + \pi_{\theta|D} \cdot (1 - \max_{y'} p(y'|x', \theta))$
37:         **end for**
38:         **for** y' in $\{0, 1\}$ **do**
39:             $p(y'|D, x') = \sum_\theta \pi_{\theta|D} \cdot p(y'|x', \theta)$
40:         **end for**
41:         $obc\_error = 1 - \max_{y'} p(y'|D, x')$
42:         $K = obc\_error - bayesian\_error$
43:         $wmocu = wmocu + p(x') \cdot [(1 - K)K]$
44:     **end for**
45:     **return** $wmocu$
46: **end function**

---

or below 0.5, the specific value of $p(y|x, a, b)$ will not affect the corresponding optimal Bayesian classifier (OBC) and therefore the loss reduction in Fig. S1(b) at $x = \pm 4$ is always 0; the acquisition function of ELR around $x = 0$ can be larger than 0, since knowing the specific value of $p(y|x = 0, a, b)$ can reduce the classification error.

Figure S2. The expected OBC error regret comparison between different active learning algorithms on binary classification.

C. ADDITIONAL SYNTHETIC EXPERIMENTS

We run the same synthetic experiment of Fig. 2 with a different prior setting: $w_1 \sim \mathcal{U}(0.3, 0.8)$, $w_2 \sim \mathcal{U}(-0.02, 0.02)$ and $b \sim \mathcal{U}(-0.25, 0.25)$, and the results is shown in Figure S2. The performance shows that only our Weighted MOCU method performs better than the random benchmark.

Here we benchmark different active learning strategies for OBC with another synthetic example. Assume the classification problem with two dimensional input features $\boldsymbol{x} = (x_1, x_2) \in \mathbb{R}^2$ and binary class labels $y \in \{0, 1\}$. The computational model is derived by a decision boundary in a quadratic form: $x_2 = ax_1^2 + bx_1 + c$, i.e. $p(y = 1|\boldsymbol{x}, a, b, c) = \mathbb{1}(x_2 > ax_1^2 + bx_1 + c)$. The parameter vector $\theta = (a, b, c) \in \mathbb{R}^3$ is uncertain and the true model is characterized by a true parameter θ^*. Unlike Monte Carlo sampling in the main text, here we consider a discrete grid setting for both input space and parameter space with discretization for each variable as follows:
1. x_1 ranges in $[-0.5, 0.5]$ with increment 0.05
2. x_2 ranges in $[0, 2]$ with increment 0.1.
3. a ranges in [-4.3, -3.8] with increment 0.05,
4. b ranges in [-0.25, 0.25] with increment 0.05,
5. c ranges in [1, 2] with increment 0.05.

For now, we simply assume that the distributions over the feature space and parameter space are all uniform to illustrate the effectiveness of MOCU-based active learning. With prior knowledge of the system of interest, knowledge-driven prior should be incorporated. Following the weighted-MOCU based active learning algorithm in Algorithm 1, we can sequentially query the true system and reduce the model uncertainty in a way that maximally reduces the classification error of the corresponding OBC.

Now we assume that when querying the system, the class label is given with a heterogeneous random flipping error with the error probability being a function of x_1: $p(y = 1|z = 0) = p(y = 0|z = 1) = 0.3 \times (1 - 4x_1^2) + 0.1$. Therefore, when $x_1 = 0$, the flipping error is 0.4; and when $x_1 = \pm 0.5$, the flipping error is 0.1. We have implemented the same methods as in the main text with 50 iterations and 100 runs, The active learning results are illustrated in Fig. S2. As we can see, in this figure, MES does not perform well as it cannot differentiate between model uncertainty and observation error. ELR performs similarly to BALD and our weighted-MOCU based method at the beginning, but then it gets stuck before finding the true boundary. BALD and our weighted MOCU perform similarly. This is because in this setting $p(y|x, \theta)$ is either 1 or 0, so there is no irrelevant uncertainty with which $p(y|x, \theta)$ is always larger or smaller than 0.5 but the value is uncertain.

Figure S3. The expected OBC error comparison between different active learning algorithms in the setting with heterogeneous observation error.

D. MULTI-CLASS CLASSIFICATION

Although we have shown in the main text that our weighted-MOCU can achieve good empirical performance of converging to OBC with the simulated multi-class classification experiment, active learning for multi-class classification problems can be complicated. The weighting function (10) adopted in the main text may not have the same theoretical convergence guarantee to the optimal classifier if applied to multi-class classification problems. Here we just show a counter example, for which Lemma 4 does not hold if using the same weighting function.

Assume a three-class classification problem $y \in \{0, 1, 2\}$. The candidate pool only has one candidate $\mathcal{X} = \{x\}$ and the parameter set $\Theta = \{\theta_1, \theta_2, \theta_3\}$. In addition we set the probabilistic model $p(y|x, \theta)$ and the prior $\pi(\theta)$ as shown in Tables S1 and S2, and calculate the posterior and posterior predictive probabilities. In the tables, y_o denotes the one-step-look-ahead observation corresponding to x, and x is omitted for simplicity.

	$p(y|\theta_1)$	$p(y|\theta_2)$	$p(y|\theta_3)$	$p(y)$	$p(y|y_o = 0)$	$p(y|y_o = 1)$	$p(y|y_o = 2)$
$y = 0$	0.4	0.4	0.4	0.4	0.4	0.4	0.4
$y = 1$	0.3	0.1	0.5	0.3	0.3	0.327	0.273
$y = 2$	0.3	0.5	0.1	0.3	0.3	0.273	0.327

Table S1. The probabilities of $p(y|x, \theta)$ and $p(y|x, y_o)$.

	$\pi(\theta)$	$\pi(\theta|y_o = 0)$	$\pi(\theta|y_o = 1)$	$\pi(\theta|y_o = 2)$
$\theta = \theta_1$	0.8	0.8	0.8	0.8
$\theta = \theta_2$	0.1	0.1	0.17	0.03
$\theta = \theta_3$	0.1	0.1	0.03	0.17

Table S2. The prior and posterior of $\pi(\theta)$.

Here two properties in the setting are worth mentioning:

1. $\pi(\theta_1)$ is close to 1 and as a result $\forall y_o \in \{0, 1, 2\}$, we have $\max_y p(y) = \max_y p(y|y_o) = \max_y p(y|\theta_1) = 0.4$;

2. $p(y|\theta_2)$ and $p(y|\theta_3)$ are symmetric and $\pi(\theta_2) = \pi(\theta_3)$, as a result $\forall y_o \in \{0, 1, 2\}$, $\pi(\theta_1) = \pi(\theta_1|y_o) = 0.8$ and therefore $\mathbb{E}_{\pi(\theta)}[\max_{y'} p(y|\theta)] = \mathbb{E}_{\pi(\theta|y_o)}[\max_{y'} p(y|\theta)] = 0.8 \times 0.4 + 0.2 \times$

$0.5 = 0.42$.

Recall that the K function and weighted MOCU are:

$$K(\pi(\theta)) = \mathbb{E}_{\pi(\theta)}[\max_{y'} p(y|\theta)] - \max_{y'} p(y), \tag{23}$$

$$\mathcal{M}^w(\pi(\theta)) = [1 - K(\pi(\theta))] \cdot K(\pi(\theta)). \tag{24}$$

Therefore, we have $\forall y_o \in \{0, 1, 2\}$, $K(\pi(\theta)) = K(\pi(\theta|y_o)) = 0.02$ and $\mathcal{M}^w(\pi(\theta)) = \mathcal{M}^w(\pi(\theta|y_o)) > 0$. On the other hand,

$$U^w(\pi(\theta)) = \mathcal{M}^w(\pi(\theta)) - \mathbb{E}_{p(y_o)}[\mathcal{M}^w(\pi(\theta|y_o))] = 0, \tag{25}$$

which means that the algorithm may get stuck. Here we just give an extreme case where only one candidate is in the search pool, but it is straightforward to build a more practical example based on what we have shown here.

From the example we can see that, unlike in the cases of binary classification problems, the K function may remain unchanged for a single observation in multi-class problems. Because of this, the weighted-MOCU algorithm with the same weighting function may get stuck. Therefore the simple weighting function that is unrelated to the value of θ is not suitable for multi-class problems. We are currently constructing more general weighting functions for efficient active learning and are working on theoretical convergence analyses for multi-class classification problems.

E. ANOTHER WEIGHTED MOCU SCHEME FOR MULTI-CLASS CLASSIFICATION

We have tested other weighting functions for active learning with multi-class classification, including the following function:

$$w(\pi^*(\theta), x', \theta) = \frac{\exp(\max_y p(y|x))}{\sum_i \exp(p(y_i|x))}, \tag{26}$$

where $p(y|x)$ is the posterior predictive distribution at the current active learning iteration. We compare this Weighted MOCU with other active learning algorithms empirically on the synthetic three-class classification problem and the performance comparison is shown in Fig. S4. This new Weighted MOCU (Weighted MOCU2) performs slightly better than other algorithms on this multi-class classification problem.

F. REAL-WORLD BENCHMARK EXPERIMENTS.

We here present the complete results on the UCI User Knowledge dataset (Kahraman et al., 2013). In addition to the uncertainty class setup in the main text, we have tested two other setups of hyper-parameter values: 1) 'uniform prior' with $\alpha_i = \beta_i = 1$, and 2) 'good prior' with $\alpha_i = \beta_i = 10$ in eight bins chosen randomly, for other bins $\alpha_i = 5, \beta_i = 2$ if the true frequency of High or Medium in the i-th bin is higher than 0.5 and $\alpha_i = 2, \beta_i = 5$ if the frequency is lower than 0.5. We also randomly draw 150 samples from each class as the candidate pool and perform the five different active learning algorithms. We repeat the whole procedure 150 times and the average error rates are shown in Fig. 4. In both Fig. 6a and Fig. 6b, ELR performs the best in these two setups while our Weighted MOCU performs similarly. BALD performs reasonably in Fig. 6a but it again performs poorly in Fig. 6b. This is because the bins with $\alpha = \beta = 10$ have less uncertainty but have more impact on OBC prediction and BALD fails to identify that in this setup again.

We also present the results on the UCI Letter Recognition dataset (Dua & Graff, 2017). Letter Recognition is a multi-class classification dataset with each sample having 16 numerical features generated from typed images of the capital letters in the English alphabet. We select two pairs of hard-to-distinguish letters: E vs. F and D vs. P. The total number of training samples is 1543 and 1608 for E vs. F and D vs. P, respectively. Active learning algorithms are applied with Bayesian logistic regression models. We randomly take 100 data points first to construct the prior, and use the rest of the data as the pool to test the five active learning algorithms. For prior construction, we train a logistic regression model on the 100 data points and take the trained parameters as the mean of a normal distributed prior with the variance equal to 1. Then we sample 1000 particles from the prior

Figure S4. The expected OBC error regret comparison between different active learning algorithms for the three-class classification problem.

(a) Uniform prior

(b) Good prior

Figure S5. Classification error rate comparison on UCI User Knowledge dataset

as the uncertain parameter set. We repeat the whole procedure 100 times and the average error rates are shown in Fig. S6. Unlike the synthetic datasets, the real-world datasets have no corresponding true models. We can only find the optimal models that approximate the data best. However, we

(a) Performance of letter E vs. F classification

(b) Performance of letter P vs. D classification

Figure S6. Classification error rate comparison on UCI Letter Recognition dataset

can still see the trends of different algorithms. Compared with random sampling, all the algorithms quickly converge to the optimal models. ELR performs the best in the first several iterations, while converges slowly in the latter iterations. Our weighted MOCU based method is again demonstrated to converge faster than other competing methods.

It is clear from all our experiments for both simulated and real-world data that, in addition to its theoretical guarantee for active learning with OBC, our weighted MOCU method has achieved consistently better or similar empirical performances compared to the best performing ones among the existing pool-based active learning methods, approaching the corresponding OBCs faster with less labeled samples.