Subequivariant Morphology-Behavior Co-Evolution in 3D Environments

Figure 1: The left illustrates uncoordinated morphology and control without subequivariance, resulting in task failure. The right demonstrates symmetry in morphology and control through subequivariant co-evolution, enabling successful goal completion.

Abstract

The co-evolution of morphology and behavior in 3D space has garnered considerable interest in the field of embodied intelligence. While recent studies have highlighted the considerable benefits of geometric symmetry for tasks like learning to locomote, navigate, and explore in dynamic 3D environments, its role within co-evolution setup remains unexplored. Existing benchmarks encounter several key issues: 1) the task lacks consideration for spatial geometric information; 2) the method lacks geometric symmetry to deal with the complexities in 3D environments. In this work, we propose a novel setup, named Subequivariant Morphology-Behavior Co-Evolution in 3D Environments (3DS-MB), to address the identified limitations. To be specific, we propose EquiEvo, which injects geometric symmetry, i.e., subequivariance, to construct dynamic, learnable local reference frames, enabling the joint policy to generalize to diverse task spatial structures, thereby improving co-evolution efficiency. Then, we evaluate EquiEvo on the proposed environments, where our method consistently and significantly outperforms existing approaches in tasks such as locomotion navigation and adversarial scenarios. Extensive experiments underscore the importance of subequivariance for the co-evolution of morphology and behavior, effective morphology-task mapping and robust morphology-behavior mapping.

1 Introduction

The rich diversity of animal morphologies, shaped over millions of years in complex environments, underscores the deep link between body form and intelligence, where well-adapted morphologies enable agents to learn and perform complex tasks effectively (Gupta et al., 2021; Brooks, 1991). Morphology evolution is fundamentally driven by environmental interactions and task demands, as supported by evolutionary biology (Maynard-Smith, 1974; Gould, 2010). The co-evolution of morphology and behavior in 3D environments has gained significant interest (Sims, 1994; Dong et al., 2023; Chen et al., 2023b; Gupta et al., 2021), focusing on how agents' form and function evolve together to improve adaptability and performance. Some works, such as (Gupta et al., 2021; Dong et al., 2023), impose bilateral symmetry constraints directly on morphology, diverging from evolutionary principles, as agents should evolve optimal morphologies through interaction with the environment, rather than relying on predefined constraints.

Alternatively, the geometric symmetry of environments and dynamic systems naturally exists, which motivates us to explore how leveraging such symmetry can accelerate the evolution of optimal morphologies through interaction with the environment. Recent studies highlight that leveraging geometric symmetry in tasks like locomotion, navigation, and exploration within dynamic 3D settings

can significantly improve the efficiency of behavioral evolution (Chen et al., 2023a; 2024). While recent co-evolution benchmarks (Yuan et al., 2022; Huang et al., 2024; Liu et al., 2022) have achieved remarkable progress (Liu et al., 2022), they often fail to fully exploit geometric symmetry within 3D spaces. These benchmarks face two main issues: 1) a focus on tasks with limited spatial geometric considerations, such as the "move forward" objective, which are simplified to fixed directional movements and do not require complex direction-aware strategies; 2) a lack of research exploring the use of geometric symmetry in co-evolution setups to handle the directional complexities of 3D environments effectively.

In this work, we address the limitations of current co-evolution benchmarks by focusing on tasks that require rich 3D spatial understanding and incorporate dynamic interactions. To achieve this, we propose a novel setup, named Subequivariant Morphology-Behavior Co-Evolution in 3D Environments (3DS-MB). Our setup extends two core tasks to enable co-evolution in complex 3D spatial environments: navigation and sumo (Chen et al., 2023a; Huang et al., 2024). In the navigation task, the agent moves towards randomly generated goals, requiring continuous adaptation to new spatial contexts. In the sumo task, two agents compete in an arena, where the objective is to push the opponent out. The constantly changing adversarial dynamics require agents to adapt to varying attack and defense angles, demanding both strategic behavior and morphology adaptation to effectively leverage rich directional information. These tasks introduce variability in movement and environmental interaction, challenging agents to develop robust, generalized policies that account for diverse geometric conditions.

To effectively handle the directional complexities of 3D environments, we incorporate subequivariant neural networks within our co-evolution framework. As illustrated in Figure 1, we introduce subequivariant graph neural networks (Chen et al., 2023a; Han et al., 2022a) to predict a dynamic, adaptive Local Reference Frame (LRF) for the agent (Chen et al., 2024). By projecting directional vectors from the global world frame into this LRF, we transform the spatial representations into an invariant form, preserving geometric symmetry while reducing the complexity of the search space. This approach enables the policy to generalize across diverse task spatial structures and enhances both the generalization ability and sample efficiency of the co-evolution process, allowing agents to better learn and adapt to complex directional information inherent in 3D tasks. An essential aspect of our approach is ensuring that the evolution of morphology remains invariant to geometric transformations, such as rotations or translations, as these do not alter the intrinsic properties of the environment. Therefore, incorporating subequivariance is crucial for aligning morphology adaptation with the environment's intrinsic symmetry.

Our contributions can be summarized as follows:

- We introduce 3DS-MB, a benchmark for subequivariant morphology-behavior co-evolution, designed to capture the rich spatial geometric information and variability inherent in complex 3D environments.

- We propose EquiEvo, a novel co-evolution framework that leverages subequivariant graph neural networks to effectively incorporate geometric symmetry, enhancing both morphology adaptation and behavior control.

- We empirically validate the performance of EquiEvo on the 3DS-MB, where our approach consistently outperforms existing methods. Extensive ablation studies and analyses further demonstrate the framework's robustness and highlight the benefits of integrating subequivariance in co-evolution tasks.

2 PRELIMINARIES

Morphology-Behavior Co-Evolution. To account for the effect of morphology to agent's behavior, the typical MDP formulation could be extended by incorporating the agent's morphology. Specifically, we define the extended MDP as $\mathcal{M} = (\mathcal{S}, \mathcal{A}, \mathcal{T}, R, \gamma, \mathcal{G}_{\mathrm{m}})$ of state space, action space, transition dynamics, a reward function, a discount factor and the agent's morphology. $\mathcal{G}_{\mathrm{m}}$ is typically represented as a graph. The transition dynamics $P(s_{t+1}|s_t, a_t, \mathcal{G}_{\mathrm{m}})$ and the control policy $\pi(a_t|s_t, \mathcal{G}_{\mathrm{m}})$ are all conditioned on $\mathcal{G}_{\mathrm{m}}$. The expected return depends on both the policy π and the morphology $\mathcal{G}_{\mathrm{m}}$: $J(\pi, \mathcal{G}_{\mathrm{m}}) := \mathbb{E}_{\pi, \mathcal{G}_{\mathrm{m}}}[\sum_{t=0}^{\infty} \gamma^t r_t]$. The morphology-behavior co-evolution problem

can be mathematically described as optimizing the following two-layer objective:

$$\mathcal{G}_{\mathrm{m}}^* := \arg\max_{\mathcal{G}_m} J(\pi_{\mathcal{G}}, \mathcal{G}_{\mathrm{m}})$$

$$\text{s.t.} \quad \pi_{\mathcal{G}} = \arg\max_{\pi} J(\pi, \mathcal{G}_{\mathrm{m}}). \tag{1}$$

Building on the classical policy optimization algorithm, PPO (Schulman et al., 2017), Yuan et al. (2022) propose a unified approach to jointly optimize two sub-policies: morphology transformation and behavior control. Specifically, the policy is structured to first transform the agent's morphology and develop its attributes, which is then followed by behavior control for the resulting morphology within each episode.

Geometric Symmetry. Learning in 3D environments is hard due to the excess requirement of exploration. To relieve the difficulty of co-evolution in 3D environments with the massive search space, the inherent geometric symmetry of 3D environments should be exploited. Intuitively, if the entire environment undergoes rigid transformations such as rotations and translations, the perceived environment should remain unchanged from the perspective of an agent within it. In other words, the agent should remain unaffected by global geometric transformations. This property is formally captured by the concept of *equivariance*, defined as follows:

Definition 1 (Equivariance). *Suppose $\vec{z}^1$ to be vector features (positions, velocities, etc) that are steerable by a group G, and $\boldsymbol{h}$ non-steerable scale features. A function f is G-equivariant, if for any transformation $g \in G, \forall \vec{z} \in \mathbb{R}^{3 \times m}, \boldsymbol{h} \in \mathbb{R}^d, f(g \cdot \vec{z}, \boldsymbol{h}) = g \cdot f(\vec{z}, \boldsymbol{h})$. Similarly, f is invariant if $f(g \cdot \vec{z}, \boldsymbol{h}) = f(\vec{z}, \boldsymbol{h})$. Here $\cdot$ denotes the group operation.*

To adhere to the principles of classical physics under the influence of gravity in typical 3D environments, we consider equivariance over a specific subgroup of $\mathrm{E}(3)^2$ defined as $\mathrm{E}_{\vec{g}}(3)$. This subgroup is composed of $\mathrm{O}_{\vec{g}}(3) := \{\boldsymbol{O} \in \mathbb{R}^{3 \times 3} \mid \boldsymbol{O}^\top \boldsymbol{O} = \boldsymbol{I}, \boldsymbol{O}\vec{g} = \vec{g}\}$ and $\mathrm{T}_{\vec{g}}(3) := \{\vec{t} \in \mathbb{R}^3 \mid \vec{t} \times \vec{g} = \vec{0}\}$. The group operation of $\mathrm{E}_{\vec{g}}(3)$ is instantiated as $g \cdot \vec{z} := \boldsymbol{O}\vec{z} + \vec{t}^3$. In this way, $\mathrm{E}_{\vec{g}}(3)$-equivariance is constrained to translations, rotations, and reflections along the direction of $\vec{g}$. We refer to this property as *subequivariance*, specifically highlighting $\mathrm{E}_{\vec{g}}(3)$-equivariance. This relaxation of group constraints is critical in environments influenced by gravity, as it allows the model to capture gravitational effects. Unless otherwise specified, in the following text, we will use the term "equivariance" to refer to $\mathrm{E}_{\vec{g}}(3)$-equivariance, and "invariance" to refer to $\mathrm{E}_{\vec{g}}(3)$-invariance.

Subequivariant Graph. Subequivariant graph is an extention of geometric graph (Han et al., 2024), defined as $\vec{\mathcal{G}}_{\vec{g}} := (\mathcal{V}, \mathcal{E}, \boldsymbol{H}, \vec{\boldsymbol{Z}}, \vec{g})$. $\boldsymbol{H} \in \mathbb{R}^{N \times C_h}$ contains scalar node features of C_h channels. $\vec{\boldsymbol{Z}} \in \mathbb{R}^{N \times 3 \times C_z}$ contains vector node features of C_z channels. $\vec{g}$ indicates that the permitted transformations to the graph must be elements of $\mathrm{E}_{\vec{g}}(3)$. The transformation of subequivariant graph by $g \in \mathrm{E}_{\vec{g}}(3)$ is defined as $g \cdot \vec{\mathcal{G}}_{\vec{g}} := (\mathcal{V}, \mathcal{E}, \boldsymbol{H}, g \cdot \vec{\boldsymbol{Z}}, \vec{g})$. To effectively make use of subequivariant graph, previous works have adopted a universally expressive construction of $\mathrm{O}_{\vec{g}}(3)$-equivariant function (Han et al., 2022a; Chen et al., 2023a; 2024):

$$f_{\vec{g}}(\vec{z}, \boldsymbol{h}) = [\vec{z}, \vec{g}]\sigma([\vec{z}, \vec{g}]^\top[\vec{z}, \vec{g}], \boldsymbol{h}), \tag{2}$$

where $\sigma(\cdot)$ is an Multi-Layer Perceptron and [ ] denotes concatenation along the last dimension.

3 SETUP AND METHOD

Our goal is to learn a co-evolution policy in 3D environments that simultaneously adapts the agent's morphology and enhances behavior control skills to optimize task performance. To achieve this, we first introduce our newly proposed 3D morphology-behavior co-evolution setup, termed 3DS-MB,

Table 1: Comparison of Setups.

Aspect	Prior	3DS-MB
Task Graph	Fixed Directions Topology Graph	Variable Directions Subequivariant Graph
Group	$\emptyset$	$\mathrm{E}_{\vec{g}}(3)$

---

[1]Note that we use a right-arrow superscript on $\vec{z}$ to distinguish it from the scalar $\boldsymbol{h}$, which remains unaffected by the transformations.

[2]The symmetrical structure of 3D environments is captured by $\mathrm{E}(3)$, the 3-dimensional Euclidean group, which includes rotations, reflections, and translations.

[3]Note that $\vec{t}$ only acts on the 3D coordinate vector.

which incorporates tasks involving richer 3D information. We then present our co-evolution framework, EquiEvo (illustrated in Figure 2), which leverages the symmetric structure of 3D environments through subequivariant neural networks to efficiently evolve morphology and learn control skills. We also outline our method in Algorithm 1.

3.1 EXTENSION TO 3DS-MB

Setups. Exploring how agents evolve and behave in tasks involving complex state information of 3D environments is crucial, as factors like positions, velocities, and directions are inherently represented as vectors.

While prior works have made significant strides, existing benchmarks (Yuan et al., 2022; Huang et al., 2024) primarily focus on tasks with fixed directions and limited consideration of those requiring richer vector representations, particularly tasks involving variable directions. Consequently, there is no need to utilize symmetry groups, and modeling with topology graphs is sufficient for co-evolution of morphology and behavior in their tasks. In contrast, our proposed 3DS-MB setup introduces tasks with variable directions, employs subequivariant graphs, and leverages the group $E_{\vec{g}}(3)$ to capture the geometric properties of 3D spaces. A detailed comparison of the environment setups between 3DS-MB and prior benchmarks is provided in Table 1.

Invariant of Morphology Value. The evolution of morphology should be invariant to geometric transformations like rotations or translations, as these do not alter the intrinsic properties of the environment. From the perspective of PPO optimization, to optimize the morphology transform policy, we need to estimate the value of morphology transform actions, which must be invariant to $E_{\vec{g}}(3)$ transformations. For example, consider a scenario where an agent with the same morphology is initialized in a state that has been rotated within the environment. The behavior should rotate correspondingly, ensuring that the morphology value determined by behavior remains consistent. In co-evolution frameworks like Transform2Act Yuan et al. (2022), morphology transformation and behavior control are treated as different steps within a single episode.

Figure 2: Flowchart of EquiEvo.

Consistent feedback for morphology transformation can only be achieved by leveraging geometric symmetry throughout the interaction with the environment. To achieve this, we integrate equivariant networks into the behavior control policy. By inject symmetry into the model architecture, the output is constrained to be equivariant, provides consistent value for morphology value estimation, and facilitates the co-evolution learning process. Furthermore, equivariant networks have been proven to learn control policies more efficiently, which is crucial for reducing the complexity of solving the complex two-layer optimization problem.

3.2 EQUIEVO

Agent Representation. The morphology of the agent is a graph $\mathcal{G}_{\mathrm{m}} := (\mathcal{V}, \mathcal{E}, \boldsymbol{H}^m)$. where each node $i \in \mathcal{V}$ represents a limb, and each edge $(i, j) \in \mathcal{E}$ corresponds to the joint that connects the limbs i and j. The morphology structure of the agent is represented by the topology of graph. $\boldsymbol{H}^{\mathrm{m}}$ contains morphology attributes for the agent's limbs, joints, and the specific design for the structure

given by the graph. For each node i, $\boldsymbol{h}_i^{\mathrm{m}} \in \mathbb{R}^{C_{\mathrm{m}}}$ includes the length and size of the limb, joint torque limit, the node depth in the body tree, etc.

The agent's state is defined as a subequivariant graph $\vec{\mathcal{G}}_{\vec{g}} \coloneqq (\mathcal{V}, \mathcal{E}, \boldsymbol{H}^{\mathrm{m}}, \boldsymbol{H}^{\mathrm{b}}, \vec{\boldsymbol{Z}}, \vec{g}) = (\mathcal{G}, \boldsymbol{H}^{\mathrm{b}}, \vec{\boldsymbol{Z}}, \vec{g})$. Each node i has scalar state and vector state, expressed as $\boldsymbol{h}_i^{\mathrm{b}} \in \boldsymbol{H}^{\mathrm{b}}$ and $\vec{z}_i \in \vec{\boldsymbol{Z}}$, respectively. The scalar state $\boldsymbol{h}_i^{\mathrm{b}} \in \mathbb{R}^{C_{\mathrm{b}}}$ contains scalars representing the configuration of the joint, including joint angle, joint angular velocity, etc. The vector joint state $\vec{z}_i \in \mathbb{R}^{3 \times C_{\mathrm{m}}}$ contains position $\vec{p}_i \in \mathbb{R}^3$, direction, linear velocity, angular velocity, etc. Here, position $\vec{p}_i$ is transformed into a translation-invariant representation by subtracts position of root node, thereby ensuring translation invariance. Notably, the morphology attributes and the scalar state are invariant, while the vector state is equivariant.

We emphasize the differences between $\mathcal{G}_{\mathrm{m}}$ and $\mathcal{G}_{\vec{g}}$. $\mathcal{G}_{\mathrm{m}}$ solely represents the agent's morphology and does not interact with the environment. In contrast, $\mathcal{G}_{\vec{g}}$ interacts with the environment, involving $\boldsymbol{H}^b$ and $\vec{\boldsymbol{Z}}$, which are obtained during the rollout process.

Morphology Transform. In the morphology transform stage, starting from the original morphology, the agent undergoes morphology transform actions $\boldsymbol{a}^{\mathrm{m}}$ to modify the structure and attributes through the morphology transform sub-policy π_θ^{m}. We adopted the two-stage design introduced in Transform2Act (Yuan et al., 2022). The transform actions $\boldsymbol{a}^{\mathrm{m}} \in \{\boldsymbol{a}^{\mathrm{s}}, \boldsymbol{a}^{\mathrm{a}}\}$ include two types: (1) Structure transform actions $\boldsymbol{a}^{\mathrm{s}}$, which are discrete and change the topological structure of the morphology by adding or removing joints and limbs; (2) Attribute transform actions $\boldsymbol{a}^{\mathrm{a}}$, which can be continuous or discrete, used to modify the specific instantiation of the given structure. Accordingly, π_θ^{m} is a composition of the structure transform sub-policy π_θ^{s} and the attribute transform policy π_θ^{a}. We divide the morphology transform stage into two sub-stages - structure transform stage and attribute transform stage - and use Φ as the stage identifier. We can represent the morphology transform sub-policy as follows:

$$\pi_\theta^{\mathrm{m}}(\boldsymbol{a}^{\mathrm{m}}|\mathcal{G}_{\mathrm{m}}, \Phi) \coloneqq \begin{cases} \pi_\theta^{\mathrm{s}}(\boldsymbol{a}^{\mathrm{s}}|\mathcal{G}_{\mathrm{m}}, \Phi), & \text{if } \Phi = \text{Structure} \\ \pi_\theta^{\mathrm{a}}(\boldsymbol{a}^{\mathrm{a}}|\mathcal{G}_{\mathrm{m}}, \Phi), & \text{if } \Phi = \text{Attribute} \end{cases} \tag{3}$$

The structural transform stage lasts for N_{s} steps, while the attribute transform stage spans N_{a} steps. The resulting morphology is then utilized by the behavior sub-policy to interact with the environment. Notably, during the morphology transform stage, no environment reward is assigned to the agent, as there is no direct interaction with the environment. Instead, the morphology transform sub-policy is updated solely based on feedback from the subsequent behavior control stage.

Local Reference Frame Canonicalization. According to Han et al. (2024), the Local Reference Frame (LRF) Canonicalization is a common technique in geometric graph neural networks to achieve equivariance (or invariance). We chose to use the LRF in our work for its simplicity and effectiveness. During the behavior control stage, at each step, we first predict a local reference frame (LRF) using subequivariant graph neural networks. We then perform canonicalization by projecting the vector states from the global world frame into the LRF as follows:

$$\mathcal{G}_{\vec{g}} \leftarrow \text{LRF}(\vec{\mathcal{G}}_{\vec{g}}). \tag{4}$$

To obtain LRF, We use subequivariant graph neural networks φ to process $\vec{\mathcal{G}}_{\vec{g}}$, predict two candidate vectors and perform orthonormalization OP:

$$\vec{u}, \vec{v} \leftarrow \varphi\left(\vec{\mathcal{G}}_{\vec{g}}\right), \tag{5}$$

$$\boldsymbol{O} \leftarrow \text{OP}(\vec{u}, \vec{v}). \tag{6}$$

Specifically, φ consists of L subequivariant message passing layers. The message passing mechanism operates as follows: we first construct edge features from the node features, and then use both $\phi_{\vec{g}}$ and $\psi_{\vec{g}}$, as described in Equation (2), to generate messages. These messages are subsequently aggregated and merged with the original state. For details on subequivariant message passing, please refer to Appendix B.

After message passing, we predict $\vec{u}$ and $\vec{v}$ by using the output vector state $\vec{z}_1^{(L)}$ of the root node:

$$\vec{u} \leftarrow \vec{z}_1^{(L)} \boldsymbol{W}_{\vec{u}}, \tag{7}$$

$$\vec{v} \leftarrow \vec{z}_1^{(L)} \boldsymbol{W}_{\vec{v}}, \tag{8}$$

where $\boldsymbol{W}_{\vec{u}} \in \mathbb{R}^{m \times 1}$ and $\boldsymbol{W}_{\vec{v}} \in \mathbb{R}^{m \times 1}$.

Now we use $\vec{u}$ and $\vec{v}$ to construct a orthonormal basis. As $\vec{z}$ only consider $\mathrm{O}_{\vec{g}}(3)$-equivariant transformations, we could set one of the axes as parallel to $\vec{g}$. We have $\boldsymbol{O} := [\vec{e}_1, \vec{e}_2, \vec{e}_3] \leftarrow \mathrm{OP}(\vec{u}, \vec{v})$:

$$\vec{e}_3 \leftarrow [0, 0, 1]^\top \tag{9}$$

$$\vec{e}_1 \leftarrow \frac{\vec{u} - \langle \vec{u}, \vec{e}_3 \rangle \vec{e}_3}{\|\vec{u} - \langle \vec{u}, \vec{e}_3 \rangle \vec{e}_3\|}, \tag{10}$$

$$\vec{e}_2 \leftarrow \frac{\vec{v} - \langle \vec{v}, \vec{e}_1 \rangle \vec{e}_1 - \langle \vec{v}, \vec{e}_3 \rangle \vec{e}_3}{\|\vec{v} - \langle \vec{v}, \vec{e}_1 \rangle \vec{e}_1 - \langle \vec{v}, \vec{e}_3 \rangle \vec{e}_3\|}. \tag{11}$$

Having obtained $\boldsymbol{O}$, we project the agent's vector state into the local reference frame to obtain the invariant vector state:

$$\boldsymbol{z}_i \leftarrow \boldsymbol{O}^\top \vec{z}_i^{(0)}, \tag{12}$$

where $\vec{z}_i^{(0)} \in \mathbb{R}^{3 \times m}$ is the input vector state of node i in the global world frame, and $z_i \in \mathbb{R}^{3 \times m}$ is the invariant vector state in the local reference frame.

Finally, we transform the subequivariant graph of the agent's state into an invariant graph $\mathcal{G}_{\vec{g}} := (\mathcal{G}_\mathrm{m}, \boldsymbol{H}^\mathrm{b}, \boldsymbol{Z}, \vec{g}) \leftarrow \mathrm{LRF}(\vec{\mathcal{G}}_{\vec{g}})$. A formal proof of the invariance of LRF Canonicalization is presented in Theorem 1.

Behavior Control. We use the invariant graph $\mathcal{G}_{\vec{g}}$ (such as GraphConv (Kipf & Welling, 2017)) to perform behavior control. We use a conventional neural network $\varphi_\theta^\mathrm{b}$ (such as MLP) to instantiate the behavior control sub-policy π_θ^b and predict the behavior control action $\boldsymbol{a}^\mathrm{b}$:

$$\boldsymbol{a}^\mathrm{b} \leftarrow \varphi_\theta^\mathrm{b} (\mathcal{G}_{\vec{g}}). \tag{13}$$

Value Estimation. In the value estimation process, for greater flexibility, we employ separate individual models with the same architecture as φ in Equation (5) to predict $\mathcal{G}_{\vec{g}}^V$. The invariant graph $\mathcal{G}_{\vec{g}}^V$ is then used for value estimation. We instantiate the value function V_ϕ using a conventional neural network φ_ϕ (such as MLP), which predicts the value V as follows:

$$V \leftarrow \varphi_\phi (\mathcal{G}_{\vec{g}}^V). \tag{14}$$

Formal proof of the invariance of the co-evolution are presented in Appendix A.

4 EXPERIMENTS

4.1 3DS-MB ENVIRONMENTS

To evaluate our EquiEvo method, we extend the morphology-behavior co-evolution environments (Yuan et al., 2022; Huang et al., 2024), based on the MuJoCo simulation engine (Todorov et al., 2012), to operate within a practical three-dimensional physical environment. We refer to this new environment as 3DS-MB. In the 3DS-MB environments, the agent's morphology design and state are represented by the morphology graph $\mathcal{G}^\mathrm{m}$ and the subequivariant graph $\vec{\mathcal{G}}_{\vec{g}}$. We apply the 3DS-MB environments to three different tasks, as shown in Figure 3.

(a)
(Evo)Humanoid Navigation.

(b)
(Evo)Ant Navigation.

(c)
(Evo)Ants Sumo.

Figure 3: Illustrations of Tasks. Navigation: the agent navigates towards the target (green). Sumo: Two agents compete against each other to push the opponent out of the arena.

(a) Ant. (b) Humanoid.

Figure 4: Training and Evaluation Curves in Navigation.

Humanoid Navigation.   1. Initial Conditions. The agent's position and orientation are initialized randomly, with the goal point placed randomly within a radius of $[3, 4]$ from the agent. Each time the agent reaches the goal, a new goal point is generated randomly, requiring the agent to continually adjust its direction of movement to reach as many goal points as possible. For this task, we use a humanoid morphology. To maintain the humanoid structure, we skip the structural transform stage and start directly with the attribute transform. **2. Termination.** The state must simultaneously satisfy isfinite($\vec{p}$), isfinite($\vec{v}$), and $h \in [\text{minHeight}, \text{maxHeight}]$, where $\vec{p}$, $\vec{v}$, and h represent the position, velocity, and height of the agent, respectively. The values minHeight and maxHeight are the preset minimum and maximum heights. If any of these conditions are not met, the training is terminated. For the humanoid agent, we set $h \in [1, 2]$. **3. Reward.** For the navigation task, we design a reward structure for the humanoid agent that consists of six components: *success bonus, forward reward, distance reward, control cost, contact cost,* and *survive reward.* The total reward is the sum of these components. For more details, please refer to Appendix D.1.

Ant Navigation.   1. Initial Conditions. The initial setup is similar to that of the Humanoid Navigation task. In this task environment, we use the ant morphology for experimentation, incorporating the structure transform stage, attribute transform stage, and behavior control stage during the evolution process. **2. Termination.** The termination conditions mirror those of the Humanoid Navigation task. For the ant agent, we set $h \in [0.28, 0.8]$. **3. Reward.** For the navigation task, we design a reward structure for the Ant agent consisting of four components: *success bonus, distance reward, control cost,* and *survive reward.* The total reward is the sum of these components. For further details, please refer to Appendix D.1.

Ants Sumo.   1. Initial Conditions. The positions and orientations of two agents are randomly initialized, requiring them to learn to attack and defend in various strategic situations while attempting to push each other out of the arena. The radius of the arena is randomized within the range of $[2.5, 4.5]$, and the arena has a fixed height of 0.5. Additionally, the agents are permitted to reach a maximum height of 0.29 above the arena ground. In this environment, we use the ant morphology for experimentation. Following the CompetEvo Huang et al. (2024) setup, the structure transform stage is omitted, retaining only the attribute transform stage and behavior control stage. **2. Termination.** The objective is for one agent to win by disqualifying the opponent, which occurs when an agent pushes the other out of the arena or when an agent's height exceeds the set limit (draw outcomes). The disqualified agent loses, ending the episode. **3. Reward.** For the Ants Sumo task, we design a reward structure consisting of seven components: *win bonus, lose bonus, draw bonus, control cost, push opponent reward, move reward,* and *survive reward.* The total reward is the sum of these components. For more details, please refer to Appendix D.1.

We chose to evolve morphology skeletons from scratch to address the most challenging setup and eliminate biases from prior knowledge, starting the Ant Navigation task with a simple "atomic morphology" (a torso body). For other starting morphologies, such as in the Humanoid Navigation and Ants Sumo tasks, we focused solely on attribute transformations to maintain task-specific constraints, as structural transformation boundaries are less well-defined.

Figure 5: Training and Evaluation Curves for Sumo.

4.2 Baselines, Metrics, and Implementations

Baselines. For Agent X(Ant/Humanoid), we employ the EquiEvo method to obtain EquiEvoX. To conduct a comprehensive comparison, we define the other three baseline methods: EquiX, EvoX, X. EquiX maintains subequivariance but removes the morphology transform component. EvoX includes morphology transform but does not integrate subequivariance. X is the most basic baseline method, lacking both subequivariance and morphology transform component. For the three types of tasks, the specific methods adopted are as follows:

- Ant Navigation: EquiEvoAnt, EquiAnt, EvoAnt, Ant.
- Humanoid Navigation: EquiEvoHumanoid, EquiHumanoid, EvoHumanoid, Humanoid.
- Ants Sumo: EquiEvoAnt, EquiAnt, EvoAnt, Ant.

The Ant Navigation uses the Transform2Act (Yuan et al., 2022) codebase as the baseline, while the Humanoid Navigation and Ant Sumo use the CompetEvo (Huang et al., 2024) codebase as the baseline. For more information on the baselines, please refer to Appendix D.2.

Metrics. For Navigation task, we use cumulative reward to assess the performance of the agents; for Sumo task, we use win rate (*Win Rate* = #*win_episode* / #*all_episode*). Each experiment is trained with 3 seeds to report the average and standard deviation of the cumulative reward or win rate.

Implementations. We use PPO (Schulman et al., 2017) as the reinforcement learning algorithm in all experiments. We implemented EquiEvo based on the Transform2Act codebase (Yuan et al., 2022) and the CompetEvo codebase (Huang et al., 2024), which are built on the PyTorch framework. There is no weight sharing between the policy network π_θ and the value estimation network V_ϕ. The value of the maximum timesteps of an episode is 1,000 (Navigation) / 500 (Sumo). The value of the maximum epoch is 500 (Ant) / 2,000 (Humanoid). Additionally, in Sumo, we adopt Bansal et al. (2018)'s approach, where teams using different methods compete against each other within an arena. For detailed hyperparameters, refer to Table 2.

4.3 Main Results

Navigation. We first conduct a performance comparison of methods on the navigation task, as shown in Figure 4.

For the Humanoid agent, *EquiEvo* surpasses baseline methods across random scenarios (Figure 4b). The ranking from best to worst—*EquiEvoHumanoid*, *EquiHumanoid*, *Humanoid*, and *EvoHumanoid*—highlights the significance of subequivariance in morphology-behavior co-evolution. Without subequivariance, applying morphology transform alone (*Evo*) expands the search space,

Humanoid   EvoHumanoid   EquiEvoHumanoid

Figure 6: Visualization of Humanoid Morphology.

Figure 7: Comparisons with Hand-Craft Normalization.

hindering efficient training. This demonstrates the crucial role of subequivariance in optimizing co-evolution.

The visualization in Figure 6 demonstrates that subequivariance significantly impacts the shape of the humanoid agent. *EvoHumanoid*, developed without geometric symmetry constraints, lacks balance, resulting in poor coordination and stability during movement. In contrast, *EquiEvoHumanoid* develops a more coordinated morphology, leading to greater stability and flexibility—more akin to that of a professional athlete.

For Ant, the experimental results (Figure 4a) rank *EquiEvoAnt* as the best in locomotion navigation, followed by *EvoAnt*, *EquiAnt*, and *Ant*. The *EquiEvo* method enhances learning by integrating subequivariance and morphology transform, demonstrating the effectiveness of both components in our approach. *EvoAnt* performs well due to its morphology transform, while *EquiAnt* is weaker without it but still outperforms *Ant*.

Sumo. In the sumo task (Figure 5), the *EquiEvoAnt* agent consistently outperformed all baselines. The results emphasize the critical impact of subequivariance, which proved more influential than morphology evolution alone in enhancing performance. However, integrating morphology evolution with subequivariance yielded a synergistic effect, further boosting the agents' capabilities. This highlights that subequivariance is key to success in sumo tasks, with the addition of morphology evolution refining and optimizing strategies for significant performance gains.

4.4 ABLATIONS AND ANALYSES

Comparisons with Hand-Crafted Normalization. In addition to our equivariant network approach, hand-crafted methods can also construct a Local Reference Frame (LRF). To compare the effectiveness of these approaches, we designed the following experiments, ablated in Figure 7: **1. Evo+DN**: a variant using hand-crafted normalization where $\vec{z}$ are treated as scalars and the goal direction is used to construct the LRF; **2. Evo+HN**: another hand-crafted normalization variant, treating $\vec{z}$ as scalars but constructing the LRF based on the agent's heading direction; **3. Evo**: a non-equivariant variant that treats $\vec{z}$ as scalars without any LRF construction.

Can equivariant network methods replace or even surpass hand-crafted normalization? Experiments demonstrate that regardless of using goal or heading direction to construct the LRF, hand-crafted methods perform worse than ours, indicating that equivariant networks are more effective for morphology evolution, offering a plug-in solution for equivariant adaptation.

Do different tasks require different LRF designs for symmetry? We observe that EvoAnt, a goal-directed task, benefits more from DN since the primary reward comes from approaching the goal. In contrast, the humanoid task, which requires both goal-reaching and forward motion, sees better performance with HN. This suggests that optimal LRF design varies by task. Additionally, evidences from prior works Chen et al. (2023a; 2024) indicate that learning-based equivariant methods, which automatically identify the optimal LRF by leveraging geometric information, outperform hand-crafted approaches that rely on manually applying symmetry priors.

Figure 8: Ablations of Equivariance on EvoAnt.   Figure 9: Analyses of Morphology-Task.

Ablations of Equivariance.   In *EquiEvo* (or *EquiActorCritic*), both the Actor and Critic networks are designed to be subequivariant, ensuring that the entire reinforcement learning process adheres to equivariance under the Actor-Critic framework. To evaluate the impact of each network, we perform ablation experiments where one network retains subequivariance while the other does not, producing the variants *EquiActor* and *EquiCritic*, respectively. The results in Figure 8 demonstrate that the performance of *EquiEvo* diminishes when either the Actor or Critic lacks subequivariance, emphasizing the necessity of this property in both networks. Moreover, the Actor's subequivariance appears to play a more crucial role than the Critic's, likely because of its direct impact on decision-making and action selection. These findings underscore the importance of maintaining subequivariance in both the Actor and Critic to achieve an efficient and consistent reinforcement learning process.

Analyses of Morphology-Task Mapping.   The evolved morphology of *EquiEvoAnt* exhibits strong symmetry, as seen in Figure 10, which coincides with the symmetric structure of the task reward. To investigate how task design affects morphology evolution, we introduce a forward reward to *EvoAnt*

Figure 10: Visualization of Morphology Transform step by step. (a) EvoAnt; (b) EquiEvoAnt; (c) EquiEvoAnt with Forward Reward.

and train both *EquiEvoAnt* and *EvoAnt* under this modified reward structure. The reward curves, presented in Figure 9, indicate that *EquiEvoAnt* continues to outperform *EvoAnt* in this altered task. In Figure 10 (b) and (c), we compare the evolution processes under different task (reward) settings. For the task with a forward reward, the evolved morphology exhibits a laterally symmetric structure with stronger front legs and weaker hind legs, while the task without a forward reward leads to an radially symmetric morphology. This shows that the evolution of morphology is fundamentally shaped by environmental interactions and task demands, rather than being a predefined goal. The comparison between Figure 10 (a) and (b) shows that methods without integrating geometric equivariance, due to lower sample efficiency, fail to fully evolve a radially symmetric morphology that meets task requirements. This highlights the necessity of considering geometric equivariance in the co-evolution of morphology and behavior frameworks.

Analysis of Morphology-Behavior Mapping.   We conduct experiments on the Ant Navigation task to analyze robust Morphology-Behavior Mapping, with details in Appendix D.3.

5   CONCLUSIONS

We present EquiEvo, a 3D subequivariant framework for co-evolving morphology and behavior, leveraging geometric symmetries to enhance efficiency and adaptability. Our results demonstrate its effectiveness in navigation and sumo tasks, highlighting the importance of geometric equivariance in driving task-specific morphologies through interaction-driven optimization. Future work can explore more complex environments, tasks, and morphology evolution settings to further advance embodied intelligence and robotic design.

REFERENCES

Trapit Bansal, Jakub Pachocki, Szymon Sidor, Ilya Sutskever, and Igor Mordatch. Emergent complexity via multi-agent competition. In *International Conference on Learning Representations*, 2018. 4.2

Cenk Baykal and Ron Alterovitz. Asymptotically optimal design of piecewise cylindrical robots using motion planning. In *Robotics: science and systems*, volume 2017. Orlando, FL, USA, 2017. B

Rodney A. Brooks. New approaches to robotics. *Science*, 253(5025):1227–1232, 1991. doi: 10.1126/science.253.5025.1227. 1

Runfa Chen, Jiaqi Han, Fuchun Sun, and Wenbing Huang. Subequivariant graph reinforcement learning in 3d environment. In *International Conference on Machine Learning*. PMLR, 2023a. 1, 2, 4.4, B

Runfa Chen, ling Wang, Yu Du, Tianrui Xue, Fuchun Sun, Jianwei Zhang, and Wenbing Huang. Subequivariant reinforcement learning in 3d multi-entity physical environments. In *International Conference on Machine Learning*. PMLR, 2024. 1, 2, 4.4, B

Tianjian Chen, Zhanpeng He, and Matei Ciocarlie. Hardware as policy: Mechanical and computational co-optimization using deep reinforcement learning. *ArXiv preprint*, abs/2008.04460, 2020. URL https://arxiv.org/abs/2008.04460. B

Xinglin Chen, Da Huang, Minglong Li, Yishuai Cai, Zhuoer Wen, Zhongxuan Cai, and Wenjing Yang. Evolving physical instinct for morphology and control co-adaption. In *2023 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 6616–6623. IEEE, 2023b. 1, B

Nick Cheney, Robert MacCurdy, Jeff Clune, and Hod Lipson. Unshackling evolution: evolving soft robots with multiple materials and a powerful generative encoding. *ACM SIGEVOlution*, 7(1): 11–23, 2014. B

Taco Cohen and Max Welling. Group equivariant convolutional networks. In *International conference on machine learning*, pp. 2990–2999. PMLR, 2016a. B

Taco S Cohen and Max Welling. Steerable cnns. *arXiv preprint arXiv:1612.08498*, 2016b. B

Ruta Desai, Ye Yuan, and Stelian Coros. Computational abstractions for interactive design of robotic devices. In *2017 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1196–1203. IEEE, 2017. B

Heng Dong, Junyu Zhang, Tonghan Wang, and Chongjie Zhang. Symmetry-aware robot design with structured subgroups. In *International Conference on Machine Learning*, pp. 8334–8355. PMLR, 2023. 1

Stephen Jay Gould. *The panda's thumb: More reflections in natural history*. WW Norton & company, 2010. 1

Agrim Gupta, Silvio Savarese, Surya Ganguli, and Li Fei-Fei. Embodied intelligence via learning and evolution. *Nature communications*, 12(1):5721, 2021. 1, B

David Ha. Reinforcement learning for improving agent design. *Artificial life*, 25(4):352–365, 2019. B

Sehoon Ha, Stelian Coros, Alexander Alspach, Joohyung Kim, and Katsu Yamane. Joint optimization of robot design and motion parameters using the implicit function theorem. In *Robotics: Science and systems*, volume 13, pp. 10–15607, 2017. B

Jiaqi Han, Wenbing Huang, Hengbo Ma, Jiachen Li, Josh Tenenbaum, and Chuang Gan. Learning physical dynamics with subequivariant graph neural networks. In Sanmi Koyejo, S. Mohamed, A. Agarwal, Danielle Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 - December 9,*

2022, 2022a. URL `http://papers.nips.cc/paper_files/paper/2022/hash/a845fdc3f87751710218718adb634fe7-Abstract-Conference.html`. 1, 2

Jiaqi Han, Yu Rong, Tingyang Xu, and Wenbing Huang. Geometrically equivariant graph neural networks: A survey. *arXiv preprint arXiv:2202.07230*, 2022b. B

Jiaqi Han, Jiacheng Cen, Liming Wu, Zongzhao Li, Xiangzhe Kong, Rui Jiao, Ziyang Yu, Tingyang Xu, Fandi Wu, Zihe Wang, et al. A survey of geometric graph neural networks: Data structures, models and applications. *arXiv preprint arXiv:2403.00485*, 2024. 2, 3.2

Jiaheng Hu, Julian Whitman, and Howie Choset. Glso: grammar-guided latent space optimization for sample-efficient robot design automation. In *Conference on Robot Learning*, pp. 1321–1331. PMLR, 2023. B

Kangyao Huang, Di Guo, Xinyu Zhang, Xiangyang Ji, and Huaping Liu. Competevo: Towards morphological evolution from competition. *ArXiv preprint*, abs/2405.18300, 2024. URL `https://arxiv.org/abs/2405.18300`. 1, 3.1, 4.1, 4.1, 4.2, B

Donald Joseph Hejna III, Pieter Abbeel, and Lerrel Pinto. Task-agnostic morphology evolution. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL `https://openreview.net/forum?id=CGQ6ENUMX6`. B

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL `https://openreview.net/forum?id=SJU4ayYgl`. 3.2

Xingyu Liu, Deepak Pathak, and Kris M Kitani. Revolver: Continuous evolutionary models for robot-to-robot policy transfer. *arXiv preprint arXiv:2202.05244*, 2022. 1

John Maynard-Smith. *Models in ecology*. Cambridge university press, 1974. 1

Charles Schaff, David Yunis, Ayan Chakrabarti, and Matthew R Walter. Jointly learning to construct and control agents using deep reinforcement learning. In *2019 international conference on robotics and automation (ICRA)*, pp. 9798–9805. IEEE, 2019. B

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *ArXiv preprint*, abs/1707.06347, 2017. URL `https://arxiv.org/abs/1707.06347`. 2, 4.2

Karl Sims. Evolving virtual creatures. In *Proceedings of the 21st annual conference on Computer graphics and interactive techniques*, pp. 15–22, 1994. 1

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 5026–5033. IEEE, 2012. 4.1

Elise van der Pol, Daniel E. Worrall, Herke van Hoof, Frans A. Oliehoek, and Max Welling. MDP homomorphic networks: Group symmetries in reinforcement learning. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL `https://proceedings.neurips.cc/paper/2020/hash/2be5f9c2e3620eb73c2972d7552b6cb5-Abstract.html`. B

Tingwu Wang, Renjie Liao, Jimmy Ba, and Sanja Fidler. Nervenet: Learning structured policy with graph neural networks. In *International conference on learning representations*, 2018. B

Tingwu Wang, Yuhao Zhou, Sanja Fidler, and Jimmy Ba. Neural graph evolution: Towards efficient automatic robot design. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019. URL `https://openreview.net/forum?id=BkgWHnR5tm`. B

Daniel E Worrall, Stephan J Garbin, Daniyar Turmukhambetov, and Gabriel J Brostow. Harmonic networks: Deep translation and rotation equivariance. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 5028–5037, 2017. B

Ye Yuan, Yuda Song, Zhengyi Luo, Wen Sun, and Kris M. Kitani. Transform2act: Learning a transform-and-control policy for efficient agent design. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net, 2022. URL https://openreview.net/forum?id=UcDUxjPYWSr. 1, 2, 3.1, 3.1, 3.2, 4.1, 4.2, B, D.3

A PROOFS

In this section, we theoretically prove that our proposed EquiEvo ensures the co-evolution process preserve the symmetry as desired.

Finally, we transform the subequivariant graph of the agent's state into an invariant graph

Theorem 1. *The LRF canonicalization, denoted as $\mathcal{G}_{\vec{g}} \leftarrow \mathrm{LRF}(\vec{\mathcal{G}}_{\vec{g}})$ is $\mathrm{O}_g(3)$-invariant, satisfying any transformation $g \in \mathrm{O}_{\vec{g}}(3)$, $\mathcal{G}_{\vec{g}} = \mathrm{LRF}(g \cdot \vec{\mathcal{G}}_{\vec{g}})$.*

Proof. Let the projected graph $\mathcal{G}_{\vec{g}}$ be the output of the LRF canonicalization with input $\vec{\mathcal{G}}_{\vec{g}} = (\mathcal{G}_{\mathrm{m}}, \boldsymbol{H}^{\mathrm{b}}, \vec{\boldsymbol{Z}}, \vec{g})$. Similarly, let $\mathcal{G}'_{\vec{g}}$ be the output of the LRF canonicalization with input $g \cdot \vec{\mathcal{G}}_{\vec{g}} = (\mathcal{G}_{\mathrm{m}}, \boldsymbol{H}^{\mathrm{b}}, g \cdot \vec{\boldsymbol{Z}}, \vec{g})$, for any transformation $g \in \mathrm{O}_{\vec{g}}(3)$. If $\mathcal{G}_{\vec{g}} = \mathcal{G}'_{\vec{g}}$, this indicates that the LRF canonicalization preserves $\mathrm{O}_{\vec{g}}(3)$-invariance.

We first prove that OP in Equation (6) is equivariant.

Let g be a transformation in $\mathrm{O}_{\vec{g}}(3)$, which includes rotation and reflection R along the direction of $\vec{g}$. Specifically, the transformation is applied as follows:

$$\boldsymbol{O}' \leftarrow g \cdot \boldsymbol{O} \coloneqq R\boldsymbol{O}_i, \tag{15}$$

$$\boldsymbol{z}' \leftarrow g \cdot \vec{\boldsymbol{v}} \coloneqq R\vec{\boldsymbol{z}}. \tag{16}$$

We use the fact that $\forall R \in \mathrm{O}_{\vec{g}}(3), \forall \vec{\boldsymbol{x}}, \vec{\boldsymbol{y}} \in \mathbb{R}^3, \langle R\vec{\boldsymbol{x}}, R\vec{\boldsymbol{y}} \rangle = \vec{\boldsymbol{x}}^\top R^\top R\vec{\boldsymbol{y}} = \vec{\boldsymbol{x}}^\top \vec{\boldsymbol{y}} = \langle \vec{\boldsymbol{x}}, \vec{\boldsymbol{y}} \rangle$ and $\|R\vec{\boldsymbol{x}}\| = \langle R\vec{\boldsymbol{x}}, R\vec{\boldsymbol{x}} \rangle = \langle \vec{\boldsymbol{x}}, \vec{\boldsymbol{x}} \rangle = \|\vec{\boldsymbol{x}}\|$. By definition, $R\vec{e}_3 = \vec{e}_3$. According to the property of Equation (5), we know that $\vec{z}_1^{(L)}$, $\vec{\boldsymbol{u}}$ and $\vec{\boldsymbol{v}}$ are $\mathrm{O}_{\vec{g}}(3)$-equivariant.

Let $\boldsymbol{O}' \leftarrow \mathrm{OP}(g \cdot \vec{\boldsymbol{u}}, g \cdot \vec{\boldsymbol{v}})$. By the properties of the orthogonalization process in Equations (9) to (11), we have:

$$\vec{e}'_3 = [0, 0, 1]^\top = \vec{e}_3 = R\vec{e}_3, \tag{17}$$

$$\vec{e}'_1 = \frac{R\vec{\boldsymbol{u}} - \langle R\vec{\boldsymbol{u}}, \vec{e}'_3 \rangle \vec{e}'_3}{\|R\vec{\boldsymbol{u}} - \langle R\vec{\boldsymbol{u}}, \vec{e}'_3 \rangle \vec{e}'_3\|} \tag{18}$$

$$= \frac{R\vec{\boldsymbol{u}} - \langle R\vec{\boldsymbol{u}}, R\vec{e}_3 \rangle R\vec{e}_3}{\|R\vec{\boldsymbol{u}} - \langle R\vec{\boldsymbol{u}}, R\vec{e}_3 \rangle R\vec{e}_3\|} \tag{19}$$

$$= \frac{R(\vec{\boldsymbol{u}} - \langle \vec{\boldsymbol{u}}, \vec{e}_3 \rangle \vec{e}_3)}{\|R(\vec{\boldsymbol{u}} - \langle \vec{\boldsymbol{u}}, \vec{e}_3 \rangle \vec{e}_3)\|} \tag{20}$$

$$= R\frac{(\vec{\boldsymbol{u}} - \langle \vec{\boldsymbol{u}}, \vec{e}_3 \rangle \vec{e}_3)}{\|(\vec{\boldsymbol{u}} - \langle \vec{\boldsymbol{u}}, \vec{e}_3 \rangle \vec{e}_3)\|} \tag{21}$$

$$= R\vec{e}_1, \tag{22}$$

$$\vec{e}'_2 = \frac{R\vec{\boldsymbol{v}} - \langle R\vec{\boldsymbol{v}}, \vec{e}'_1 \rangle \vec{e}'_1 - \langle R\vec{\boldsymbol{v}}, \vec{e}'_3 \rangle \vec{e}'_3}{\|R\vec{\boldsymbol{v}} - \langle R\vec{\boldsymbol{v}}, \vec{e}'_1 \rangle \vec{e}'_1 - \langle R\vec{\boldsymbol{v}}, \vec{e}'_3 \rangle \vec{e}'_3\|} \tag{23}$$

$$= \frac{R\vec{\boldsymbol{v}} - \langle R\vec{\boldsymbol{v}}, R\vec{e}_1 \rangle R\vec{e}_1 - \langle R\vec{\boldsymbol{v}}, R\vec{e}_3 \rangle R\vec{e}_3}{\|R\vec{\boldsymbol{v}} - \langle R\vec{\boldsymbol{v}}, R\vec{e}_1 \rangle R\vec{e}_1 - \langle R\vec{\boldsymbol{v}}, R\vec{e}_3 \rangle R\vec{e}_3\|} \tag{24}$$

$$= \frac{R(\vec{\boldsymbol{v}} - \langle \vec{\boldsymbol{v}}, \vec{e}_1 \rangle \vec{e}_1 - \langle \vec{\boldsymbol{v}}, \vec{e}_3 \rangle \vec{e}_3)}{\|R(\vec{\boldsymbol{v}} - \langle \vec{\boldsymbol{v}}, \vec{e}_1 \rangle \vec{e}_1 - \langle \vec{\boldsymbol{v}}, \vec{e}_3 \rangle \vec{e}_3)\|} \tag{25}$$

$$= R\frac{(\vec{\boldsymbol{v}} - \langle \vec{\boldsymbol{v}}, \vec{e}_1 \rangle \vec{e}_1 - \langle \vec{\boldsymbol{v}}, \vec{e}_3 \rangle \vec{e}_3)}{\|(\vec{\boldsymbol{v}} - \langle \vec{\boldsymbol{v}}, \vec{e}_1 \rangle \vec{e}_1 - \langle \vec{\boldsymbol{v}}, \vec{e}_3 \rangle \vec{e}_3)\|} \tag{26}$$

$$= R\vec{e}_2. \tag{27}$$

Therefore,

$$\boldsymbol{O}' = [\vec{e}'_1, \vec{e}'_2, \vec{e}'_3] = R[\vec{e}_1, \vec{e}_2, \vec{e}_3] = R\boldsymbol{O}. \tag{28}$$

Then we have

$$\boldsymbol{z}'_i = {\boldsymbol{O}'}^\top \vec{\boldsymbol{z}}_i^{(0)'} = \boldsymbol{O}^\top R^\top R\vec{\boldsymbol{z}}_i^{(0)} = \boldsymbol{O}^\top \vec{\boldsymbol{z}}_i^{(0)} = \boldsymbol{z}_i. \tag{29}$$

Hence,

$$\mathcal{G}'_{\vec{g}} = (\mathcal{G}_{\mathrm{m}}, \boldsymbol{H}^{\mathrm{b}}, \boldsymbol{Z}', \vec{g}) \tag{30}$$

$$= (\mathcal{G}_{\mathrm{m}}, \boldsymbol{H}^{\mathrm{b}}, \boldsymbol{Z}, \vec{g}) \tag{31}$$

$$= \mathcal{G}_{\vec{g}}. \tag{32}$$

$\square$

Corollary 1. *Let* $\boldsymbol{a}_t^{\mathrm{m}}, \boldsymbol{a}_t^{\mathrm{b}}, V_\phi$ *be output of the actor and the critic of EquiEvo with* $\mathcal{G}^{\mathrm{m}}$ *and* $\vec{\mathcal{G}}_{\vec{g}}$ *as input. Let* $\boldsymbol{a}_t^{\mathrm{m}\prime}, \boldsymbol{a}_t^{\mathrm{b}\prime}, V'_\phi$ *be the actor and critic with* $g \cdot \mathcal{G}^{\mathrm{m}}$ *and* $g \cdot \vec{\mathcal{G}}_{\vec{g}}$ *as input,* $g \in O_{\vec{g}}(3)$*. Then,* $(\boldsymbol{a}_t^{\mathrm{m}\prime}, \boldsymbol{a}_t^{\mathrm{b}\prime}, V'_\phi) = (\boldsymbol{a}_t^{\mathrm{m}}, \boldsymbol{a}_t^{\mathrm{b}}, V_\phi)$*, indicating the EquiEvo preserve* $O_{\vec{g}}(3)$*-invariance.*

Proof. First, based on the geometric transformation properties of the topology graph, we have

$$\mathcal{G}^{\mathrm{m}\prime} = g \cdot \mathcal{G}^{\mathrm{m}} = \mathcal{G}^{\mathrm{m}}. \tag{33}$$

Then, by Theorem 1, $\forall R \in \boldsymbol{O}_{\vec{g}}(3)$, we have

$$\mathcal{G}'_{\vec{g}} = g \cdot \vec{\mathcal{G}}_{\vec{g}} = \mathcal{G}_{\vec{g}}. \tag{34}$$

Therefore,

$$\boldsymbol{a}_t^{\mathrm{m}\prime} = \varphi_\theta^{\mathrm{m}}(\mathcal{G}^{\mathrm{m}\prime}) \tag{35}$$

$$= \varphi_\theta^{\mathrm{m}}(\mathcal{G}^{\mathrm{m}}) = \boldsymbol{a}_t^{\mathrm{m}}, \tag{36}$$

$$\boldsymbol{a}_t^{\mathrm{b}\prime} = \varphi_\theta^{\mathrm{b}}(\mathcal{G}'_{\vec{g}}) \tag{37}$$

$$= \varphi_\theta^{\mathrm{b}}(\mathcal{G}'_{\vec{g}}) = \boldsymbol{a}_t^{\mathrm{b}}, \tag{38}$$

and

$$V'_\phi = \varphi_\phi^{\mathrm{b}}(\mathcal{G}'_{\vec{g}}) \tag{39}$$

$$= \varphi_\phi^{\mathrm{b}}(\mathcal{G}'_{\vec{g}}) = V_\phi. \tag{40}$$

$\square$

B   RELATED WORK

Optimization of Agent morphology Design: Research in the field of optimization of agent morphology design mainly falls into two mainstream approaches: the first focuses on optimizing the properties, functions, and design parameters of agents (Schaff et al., 2019; Ha, 2019; Chen et al., 2023b), and the second on structure optimization based on graph neural networks (Wang et al., 2018; Yuan et al., 2022; Hu et al., 2023). The former often adopts population-based methods, handling morphology and control strategy optimization separately through a two-level optimization process (Ha, 2019), such as the application of evolutionary search in morphology optimization (Gupta et al., 2021; Wang et al., 2019); the latter focuses on multi-objective joint optimization (Yuan et al., 2022). Research also includes the optimization of continuous design parameters of agents, using methods such as simulated annealing, trajectory optimization, and deep reinforcement learning (Baykal & Alterovitz, 2017; Ha et al., 2017; Chen et al., 2020). Recent studies have further simplified the evolutionary process and improved task-independent design optimization (Cheney et al., 2014; Desai et al., 2017; III et al., 2021). Despite the progress made by these methods, sample efficiency remains a challenge, as agents with different design morphologies often learn independently within the population. Yuan et al. (2022) introduce Transform2Act, an innovative policy for simultaneous morphology design and control optimization that adapts skeletal structures and joint attributes for efficient environmental interaction, advancing integrated agent design and control. Huang et al. (2024) presents CompetEvo, a system that integrates morphology evolution with adversarial game self-training to enhance agents' capabilities, showing morphology evolution significantly boosts combat skills and emergent behaviors.

Geometric Equivariant Models: Notably, the physical realm exhibits inherent symmetries, and extensive research has been conducted on group equivariant models (Cohen & Welling, 2016a;b; Worrall et al., 2017). In recent times, the research area of geometrically equivariant graph neural networks (Han et al., 2022b) has emerged, utilizing symmetry as an inductive bias during the learning process. These models are crafted to ensure that their outputs undergo rotation, translation, or reflection in alignment with the inputs, thereby preserving the symmetry. Within a Markov decision process (MDP) that exhibits symmetries (van der Pol et al., 2020), the state-action space possesses inherent symmetries, allowing policies to be optimized within a more straightforward, abstract MDP. van der Pol et al. (2020) endeavors to train policy networks that are equivariant and value networks that are invariant in two-dimensional simulated environments. In contrast, Chen et al. (2023a) delves into the study of body-level equivariant policy networks within intricate 3D physics environments, enhancing policy generalization over various orientations. Additionally, Chen et al. (2024) address the challenges of multi-agent games by employing entity assignment along with an entity-level subequivariant message-passing mechanism. Both our approach and Chen et al. (2023a; 2024) implement equivariance based on the core function described in Equation (2). However, there are key differences in the design and application. Chen et al. (2023a) employs a transformer architecture with a fully connected topology, whereas both Chen et al. (2024) and our approach utilize GNNs. The main distinction lies in the graph construction: Chen et al. (2024) models multi-agent relationships, requiring an entity assignment to define the graph's topology, while our method focuses on single-agent morphology evolution, directly using the morphology's inherent topology to build the graph. This design aligns with our goal of co-optimizing morphology and behavior efficiently within a single-agent framework.

C SUBEQUIVARIANT MESSAGE PASSING

Concretely, we have:

$$\vec{z}_{ij}^{(l)} = [(\vec{p}_j - \vec{p}_i), \vec{z}_i^{(l)}, \vec{z}_j^{(l)}], \tag{41}$$

$$h_{ij}^{(l)} = [\|\vec{p}_j - \vec{p}_i\|_2, h_i^{(l)}, h_j^{(l)}], \tag{42}$$

$$\vec{m}_{ij}^{(l)}, m_{ij}^{(l)} = \phi_{\vec{g}}\left(\vec{z}_{ij}^{(l)}, h_{ij}^{(l)}\right), \tag{43}$$

$$\vec{m}_i^{(l)}, m_i^{(l)} = \sum_{j \in \mathcal{N}(i)} \vec{m}_{ij}^{(l)}, \sum_{j \in \mathcal{N}(i)} m_{ij}^{(l)}, \tag{44}$$

$$(\vec{z}_i^{(l+1)}, h_i^{(l+1)}) = (\vec{z}_i^{(l)}, h_i^{(l)}) + \psi_{\vec{g}}\left([\vec{m}_i^{(l)}, \vec{z}_i^{(l)}], [m_i^{(l)}, h_i^{(l)}]\right), \tag{45}$$

where

- $\vec{p}_i$, the position of node i;
- $h_i^{(l)}$ and $\vec{z}_i^{(l)}$, the scalar and vector states of node i at the l-th layer;
- $h_{ij}^{(l)}$ and $\vec{z}_{ij}^{(l)}$, the scalar and vector states of edge ij at the l-th layer;
- $\vec{m}_{ij}^{(l)}$ and $m_{ij}^{(l)}$, the vector and scalar messages passed through edge ij;
- $\vec{m}_i^{(l)}$ and $m_i^{(l)}$, the aggregated vector and scalar messages at node i;
- $\phi_{\vec{g}}$ and $\psi_{\vec{g}}$, as described in Equation (2), the subequivariant functions used for message passing and state updates.

D MORE EXPERIMENTALS DETAILS AND RESULTS

D.1 REWARD

Humanoid Navigation: For the navigation task, we design the reward for Humanoid agent. The designed reward structure comprises six components: **a. Success Bonus:** A significant sparse reward of 1,000 is awarded. **b. Forward Reward:** It is quantified as $1.25 \times \frac{\frac{\vec{p}}{\|\vec{p}\|} \cdot \Delta \vec{p}}{\Delta t}$, where $\frac{\vec{p}}{\|\vec{p}\|}$ represents

the unit direction vector of the agent's position, and $\Delta\vec{p}$ represents the displacement of the agent from the current time step. **c. Distance Reward:** A dense reward to incentivize the achievement of the task objective. It is computed as $\frac{\Delta s}{\Delta t}$, where Δs represents the change in distance from the agent to the target. **d. Control Cost:** This penalty discourages agents from executing excessively large actions, and is calculated as $-0.1 \times \sum \sqrt{a_i}$. **e. Contact Cost:** The penalty discourages excessive contact forces, and is calculated as $-\min(0.5 \times 10^{-6} \times \sum c_i^2, 10)$, where c_i represents the component of the force exerted on the agent by external forces. **f. Survive Reward:** For each step taken, the agent receives a survival reward of 5. Thus, the reward is equal to the sum of the aforementioned rewards.

Ant Navigation: For the navigation task, we design the reward for Ant agent. The designed reward structure comprises four components: **a. Success Bonus:** A significant sparse reward of 1,000 is awarded. **b. Distance Reward:** A dense reward to incentivize the achievement of the task objective. It is computed as $10 \times \frac{\Delta s}{\Delta t}$, where Δs represents the change in distance from the agent to the target. **c. Control Cost:** This penalty discourages agents from executing excessively large actions, and is calculated as $-0.01 \times \sum \sqrt{a_i}$. **d. Survive Reward:** For each step taken, the agent receives a survival reward of 1. Thus, the reward is equal to the sum of the aforementioned rewards.

Ants Sumo: For Ants Sumo task, we design the reward structure. The designed reward structure comprises seven components: **a. Win Bonus:** A sparse reward of 2000 for achieving the win condition. **b. Lose Bonus:** A sparse penalty of -2000 for the losing condition. **c. Draw Bonus:** A sparse penalty of -1000 for the draw condition. This penalty is meant to encourage confrontation. **d. Control Cost:** This penalty discourages agents from executing excessively large actions, and is calculated as $-0.1 \times \sum \sqrt{a_i}$. **e. Push Opponent Reward:** This motivates agents to push the opponent, calculated as $-10 \times \exp(-||\vec{p}_{opp}||)$, where $\vec{p}_{opp}$ represents the position of the opponent. **f. Move Reward:** This motivates agents to move closer to the opponent, calculated as $10 \times \max(\Delta\vec{p} \cdot \frac{\vec{p}_{opp}-\vec{p}}{||\vec{p}_{opp}-\vec{p}||}, 0)$, where $\Delta\vec{p}$ represents the displacement of the agent from the current time step. **g. Survive Reward:** For each step taken, the agent receives a survival reward of 2. Thus, the reward is equal to the sum of the aforementioned rewards.

D.2 BASELINE METHODS

Ant Navigation: In the navigation task, we use Ant agent for experimentation. The agent we improve by using EquiEvo method is named EquiEvoAnt, which integrates both subequivariance and morphology evolution mechanism. To conduct a comprehensive comparison, we define the following three baseline methods: EquiAnt: This baseline method maintains subequivariance but removes the morphology evolution component. EvoAnt: This baseline method includes morphology evolution but does not integrate subequivariance. Ant: This is the most basic baseline method, lacking both subequivariance and morphology evolution component.

Humanoid Navigation: In the navigation task, we also introduce Humanoid agent for experimentation, while we omit structure transform stage during evolution. After applying the EquiEvo method, we name the agent EquiEvoHumanoid. To conduct a comprehensive comparison, we define the following three baseline methods: EquiHumanoid: This baseline method maintains subequivariance but removes the morphology evolution component. EvoHumanoid: This baseline method includes morphology evolution but does not integrate subequivariance. Humanoid: This is the most basic baseline method, lacking both subequivariance and morphology evolution capabilities. In this task, we skip structure transform stage.

Ants Sumo: In the sumo task, we still use the Ant agent for experimentation. We adopt the EquiEvo method and omit the structure transform stage during evolution, naming it EquiEvoAnt, which integrates both subequivariant networks and morphology evolution mechanisms. To conduct a comprehensive comparison, we define the following three baseline methods: EquiAnt: This baseline method maintains subequivariance but removes the morphology evolution component. EvoAnt: This baseline method includes morphology evolution but does not integrate subequivariance. Ant: This is the most basic baseline method, lacking both subequivariance and morphology evolution capabilities. In this task, we skip structure transform stage.

Figure 11: Analyses of Morphology-Behavior.

D.3 ANALYSIS OF MORPHOLOGY-BEHAVIOR MAPPING

We conduct experiments on the Ant Navigation task to analyze the impact of Morphology-Behavior Mapping, particularly focusing on the role of JSMLP, which was proposed in Transform2Act (Yuan et al., 2022) to differentiate joint actions. While JSMLP introduces body-specific characteristics, enhancing effectiveness in some contexts, it reduces the generality of the morphology-behavior mapping and impedes reusability in tasks with symmetric structures. To validate this, we ablate four variants: *Evo w. JSMLP* (baseline with JSMLP), *Evo w.o. JSMLP* (baseline without JSMLP), *EquivEvo w.o. JSMLP* (our method without JSMLP), and *EquivEvo w. JSMLP* (our method with JSMLP). As shown in Figure 11, the removal of the JSMLP module improves performance, with *EquivEvo w.o. JSMLP* outperforming all variants. This indicates that eliminating JSMLP enhances adaptability and learning by maintaining the generality of the morphology-behavior mapping, allowing better exploitation of task symmetry. Consequently, simplifying the model by omitting JSMLP within the *EquivEvo* framework facilitates more efficient navigation in symmetric tasks.

Algorithm 1 EquiEvo

1: Initialize policy π_θ and value V_ϕ {including topological graph neural networks $\varphi_\theta^{\mathrm{s}}, \varphi_\theta^{\mathrm{a}}, \varphi_\theta^{\mathrm{b}}, \varphi_\phi$, and subequivariant graph neural network $\varphi_\theta^{\mathrm{g}}$}
2: **while** not reached maximum iteration **do**
3:     Initialize memory $\mathbb{M} \leftarrow \emptyset$
4:     **while** $\mathbb{M}$ not reached batch size **do**
5:         $\mathcal{G}^{\mathrm{m}} \leftarrow$ initial morphology topology graph
        {Structure Transform Stage}
6:         **for** $t = 0, 1, \ldots, N_{\mathrm{s}} - 1$ **do**
7:             Sample structure transform action $a_t^{\mathrm{s}} \sim \varphi_\theta^{\mathrm{s}}(\mathcal{G}^{\mathrm{m}})$
8:             $\Phi \leftarrow$ Structure
9:             $\mathcal{G}^{\mathrm{m}} \leftarrow$ apply $\boldsymbol{a}^{\mathrm{s}}$ to modify $\mathcal{G}^{\mathrm{m}}$'s morphology structure $(\mathcal{V}, \mathcal{E})$
10:            $r \leftarrow 0$; Store $(r, \boldsymbol{a}^{\mathrm{s}}, \mathcal{G}^{\mathrm{m}}, \Phi)$ to $\mathbb{M}$
11:        **end for**
        {Attribute Transform Stage}
12:        **for** $t = N_{\mathrm{s}}, \ldots, N_{\mathrm{s}} + N_{\mathrm{a}} - 1$ **do**
13:            Sample attribute transform action $\boldsymbol{a}^{\mathrm{a}} \sim \varphi_\theta^{\mathrm{a}}(\mathcal{G}^{\mathrm{m}})$
14:            $\Phi \leftarrow$ Attribute
15:            $\mathcal{G}^{\mathrm{m}} \leftarrow$ apply a^{a} to modify $\mathcal{G}^{\mathrm{m}}$'s bone joint attributes $\boldsymbol{H}^{\mathrm{m}}$
16:            $r \leftarrow 0$; Store $(r, \boldsymbol{a}^{\mathrm{a}}, \mathcal{G}^{\mathrm{m}}, \Phi)$ to $\mathbb{M}$
17:        **end for**
        {Behavior Control Stage}
18:        $\vec{\mathcal{G}}_{\vec{\boldsymbol{g}}, N_{\mathrm{s}} + N_{\mathrm{a}}} \leftarrow$ initial morphology subequivariant graph
19:        **for** $t = N_{\mathrm{s}} + N_{\mathrm{a}}, \ldots, N_{\mathrm{s}} + N_{\mathrm{a}} + N_{\mathrm{e}} - 1$ **do**
20:            $\vec{\boldsymbol{v}}_t \leftarrow \varphi_\theta^{\mathrm{g}}(\vec{\mathcal{G}}_{\vec{\boldsymbol{g}}})$ {LRF Canonicalization}
21:            Use the calculated LRF transformation vector $\vec{\boldsymbol{u}}, \vec{\boldsymbol{v}}$ to predict a local reference frame and project the morphology subequivariant graph $\vec{\mathcal{G}}_{\vec{\boldsymbol{g}}}$ to the geometry-invariant representation $\mathcal{G}_{\vec{\boldsymbol{g}}}$
22:            Sample motor control action $\boldsymbol{a}^{\mathrm{b}} \sim \varphi_\theta^{\mathrm{b}}(\mathcal{G}_{\vec{\boldsymbol{g}}})$
23:            $\Phi \leftarrow$ Execution
24:            $\mathcal{G}_{\vec{\boldsymbol{g}}} \leftarrow$ environment dynamics $P^{\mathrm{b}}(\mathcal{G}_{\vec{\boldsymbol{g}}} | \mathcal{G}_{\vec{\boldsymbol{g}}}, \boldsymbol{a}^{\mathrm{b}})$
25:            $r \leftarrow$ environment reward; Store $(r, \boldsymbol{a}^{\mathrm{b}}, \mathcal{G}_{\vec{\boldsymbol{g}}}, \Phi)$ to $\mathbb{M}$
26:        **end for**
27:    **end while**{Policy Network Update}
28:    Update policy π_θ and value V_ϕ using PPO algorithm based on samples in $\mathbb{M}$
29: **end while**
30: **return** π_θ

Table 2: Hyperparameter Settings for EquiEvo

Hyperparameter	Setting
Number of structural transformations N_{s}	5
Number of attribute transformations N_{a}	1
Number of control executions N_{e}	1,000
Topological graph neural network layer type	GraphConv
Geometric graph neural network layer type	SubequivariantMP
Topological graph neural network size (structural transformation phase)	(64, 64, 64)
Topological graph neural network size (attribute transformation phase)	(64, 64, 64)
Geometric graph neural network vector size (geometric subgroup equivariant transformation phase)	(16, 16, 16)
Geometric graph neural network scalar feature size (geometric subgroup equivariant transformation phase)	(32, 32, 32)
Topological graph neural network size (control execution phase)	(64, 64, 64)
Policy learning rate	5e-5
Value estimation graph neural network size	(64, 64, 64)
Value estimation MLP size	(512, 256)
Value learning rate	3e-4
PPO clipping ϵ	0.2
PPO batch size	50000
PPO mini-batch size	2048
PPO iterations per batch	10
Training epochs	1000
Discount factor γ	0.995
GAE λ	0.95