CMAT: A Multi-Agent Collaboration Tuning Framework for Enhancing Small Language Models

Abstract

Open large language models (LLMs) have significantly advanced the field of natural language processing, showcasing impressive performance across various tasks.

Despite the significant advancements in LLMs, their effective operation still relies heavily on human input to accurately guide the dialogue flow, with agent tuning being a crucial optimization technique that involves human adjustments to the model for better response to such guidance. Addressing this dependency, our work introduces the TinyAgent model, trained on a meticulously curated high-quality dataset.

We also present the Collaborative Multi-Agent Tuning (CMAT) framework, an innovative system designed to augment language agent capabilities through adaptive weight updates based on environmental feedback. This framework fosters collaborative learning and real-time adaptation among multiple intelligent agents, enhancing their context-awareness and long-term memory. In this research, we propose a new communication agent framework that integrates multi-agent systems with environmental feedback mechanisms, offering a scalable method to explore co-operative behaviors. Notably, our TinyAgent-7B model exhibits performance on par with GPT-3.5, despite having fewer parameters, signifying a substantial improvement in the efficiency and effectiveness of LLMs.

Figure 1: TinyAgent demonstrates outstanding performance, comparable to that of GPT-3.5. TinyAgent is a series of models fine-tuned based on Qwen (Bai et al., 2023) and Codellama (Roziere et al., 2023).

1 Introduction

In the rapid development of the field of artificial intelligence, large language models (LLMs) such as BERT and GPT-4 (OpenAI, 2023) have become important cornerstones of natural language processing (NLP). These models utilize the Transformer architecture and effectively capture long-distance dependencies through multi-head self-attention mechanisms, demonstrating strong capabilities across various NLP tasks. With technological advancements, the performance and application scope of LLMs continue to expand, promising significant improvements in computational efficiency and functionality, including anticipated advanced features such as self-improvement, self-checking, and sparse expert models (Liu et al., 2023).

However, it is noteworthy that the success of these models largely depends on human input to guide the correct dialogue. This dependency requires users to provide relevant and precise prompts based on their intentions and the feedback from the chat agent, raising a critical question: ***Can we replace human intervention with autonomous communication agents***

Figure 2: In the CMAT framework, the user assigns tasks to an assistant, which generates SQL commands based on short-term and long-term memories: short-term memory provides immediate context from trajectory history, while self-reflective outputs are stored as long-term memory. The checker verifies the correctness of SQL commands before they are executed in the environment.

capable of steering conversations towards task completion with minimal human supervision?

Our research is driven by the need to overcome the significant challenges faced by LLMs in real-world deployments, particularly the high computational resource requirements, data biases, and lack of robustness. These issues limit their applicability in resource-constrained environments and highlight the urgency of enhancing model efficiency and adaptability (Abid et al., 2021; Du et al., 2022). As demonstrated by Figure 1, we aim to address these limitations by optimizing models and training methods to enable smaller models to match the performance levels of larger models. Additionally, recognizing the potential of MAS to improve processing efficiency and system adaptability through agent cooperation, we seek to develop a collaborative agent framework. This framework aims to facilitate effective cooperation among agents, thereby overcoming the performance gap and propelling further research and innovation in the field of LLMs (Ferry et al., 2018; Talwar et al., 2005). In our experiments, we evaluated the capabilities of large models with and without the use of prompts and observed that low-quality prompts can significantly degrade model performance. Consequently, we propose the Collaborative Multi-Agent Tuning (CMAT) framework.

The CMAT framework introduces a structured environment where individual agents, each with specialized roles and capabilities, work together to process information, make decisions, and solve complex tasks (Hernández-Orallo et al., 2017). By sharing insights and learning from interactions within this multi-agent ecosystem, the framework allows for a more scalable and flexible approach to training LLMs (Lewis et al., 2017). This collaborative effort not only helps in bridging the gap in performance between smaller and larger models but also fosters a more resilient system capable of adapting to new challenges without extensive human intervention (Kaplan et al., 2020). Through CMAT, we aim to push the boundaries of what is possible with LLMs, making them more accessible and effective for a wider range of applications (Rajpurkar et al., 2018).

The main contributions of our work are as follows:

- We propose the CMAT framework which represents an innovative approach that allows for dynamic and real-time memory updates within multi-agent systems.

- We design a novel role-playing mechanism for precise task allocation and enhanced agent communication, significantly boosting overall per-

formance and cooperation.

- We evaluated the fine-tuned TinyAgent models across multiple agent tasks, finding that in certain scenarios, their performance rivals that of advanced LLMs like GPT-4 and agentlm (Zeng et al., 2023), demonstrating the potential efficiency and capabilities of compact models.

2 Related Work

2.1 LLMs Applications in a Multi-Agent Framework

We explore the applications of LLMs within multi-agent systems, highlighting their role versatility as users, assistants, and checkers, and their capability to offer bespoke support and solutions across such environments (de Zarzà et al., 2023; Talebirad and Nadiri, 2023). LLMs showcase remarkable adaptability to tasks through methods like supervised fine-tuning and real-time feedback learning, notably in tasks that require a sophisticated understanding and execution related to operating systems or databases (Christianos et al., 2023; Li et al., 2023). Furthermore, LLMs are adept at enhancing communication and collaboration among agents, a critical component for addressing complex issues that necessitate multi-role coordination (Zhao et al., 2021). Nevertheless, LLMs encounter specific challenges within multi-agent frameworks, especially in situations that demand a nuanced contextual comprehension and sustained memory retention, as well as adapting to fast-evolving environments and unforeseeable tasks (Diallo et al., 2020). Issues such as data bias, security concerns, and the intricacies of crafting effective protocols for multi-agent cooperation stand as significant hurdles in this domain (Zhang et al., 2017; García et al., 2015). Thus, by summarizing LLMs' roles in multi-agent frameworks, we underscore the critical need for continued innovation and research exploration, aimed at overcoming these technological hurdles and leveraging the full potential of LLMs in complex systems (Lu and Zhang, 2020).

To enhance the adaptability and collaborative capabilities of LLMs in multi-agent systems, we've implemented memory modes, including long-term support and short-term memory with environmental feedback (Liang et al., 2016). This allows LLMs to better interact, learn, and adapt in dynamic environments, leveraging past experiences and responding to changes swiftly.

2.2 The tuning method for LLMs

The main tuning methods include supervised fine-tuning and reinforcement learning (Ouyang et al., 2022). Supervised fine-tuning enhances performance by training models on specific task datasets, and is especially suitable for tasks such as natural language understanding (NLU) (Howard and Ruder, 2018). On the other hand, reinforcement learning, guided by reward mechanisms, is suitable for handling complex and variable tasks (Mnih et al., 2015). The effective combination of these two methods can significantly improve the performance of LLMs in various tasks. Notably, LLMs of reduced scale, such as those encompassing 1.8 billion parameters, can achieve performance levels akin to those of models with greater parameter counts, like 6 billion parameters, when supported by high-quality datasets (Stiennon et al., 2020). This demonstrates that excellent data quality and appropriate tuning strategies play a decisive role in the performance of LLMs. Therefore, investing efforts in improving data quality and choosing the right tuning methods is essential for achieving optimal performance of LLMs in various application scenarios (Howard and Ruder, 2018). Through our work combining supervised fine-tuning with reinforcement learning, we've notably advanced LLM performance across a spectrum of tasks, showcasing significant improvements in task-specific benchmarks (Ouyang et al., 2022).

3 Methodology

Our research focuses on the development and implementation of the Collaborative Multi-Agent Language Model Tuning (CMAT) framework, which aims to enhance decision-making quality, controllability, and operational efficiency in complex systems through the collaboration of various agent roles: the User ($\mathcal{U}$), Assistant ($\mathcal{A}$), and Checker ($\mathcal{C}$). The CMAT framework employs advanced supervised fine-tuning techniques such as Low-Rank Adaptation (LoRA) (Hu et al., 2021) and Prompt Tuning (P-Tuning) (Lester et al., 2021), leveraging pre-trained datasets like AgentBench ($\mathcal{D}_{\text{AgentBench}}$).

Figure 3: Comparative study of Llama-2-7b and TinyAgent-7b in DataBase cases. (1) In DataBase tasks with a reflection mechanism, Llama-2-7b still made errors after reflection, while TinyAgent-7b adjusted its operations after reflecting on its first failed attempt. (2) Without a reflection mechanism, TinyAgent-7b repeated the same operation and ultimately failed to complete the task.

Additionally, it incorporates mechanisms inspired by Reinforcement Learning from Human Feedback (RLHF) (Vázquez-Canteli and Nagy, 2019), Chain of Thought (CoT), and ReAct methods.

3.1 Agent Roles

In the CMAT framework, we define a collaborative system with three agents: User ($\mathcal{U}$), Assistant ($\mathcal{A}$), and Checker ($\mathcal{C}$). The Assistant acts as the Actor, while the Checker serves as the Critic, forming an *Actor-Critic* dynamic.

At each time step t, the User $\mathcal{U}$ provides an input $\mathbf{x}_t \in \mathcal{X}$ to the Assistant. The Assistant $\mathcal{A}$, modeled as a language model $\mathcal{M}_{\theta_{\text{actor}}}$ with parameters θ_{actor}, generates an action $\mathbf{a}_t$ based on its policy $\pi_{\theta_{\text{actor}}}$: $\mathbf{a}_t = \pi_{\theta_{\text{actor}}}(\mathbf{x}_t)$. The Checker $\mathcal{C}$ evaluates the Assistant's action using a feedback function $F : \mathcal{A} \times \mathcal{X} \rightarrow$ $\mathcal{F}$, providing feedback f_t: $f_t = F(\mathbf{a}_t, \mathbf{x}_t)$. The feedback loop embodies the Actor-Critic Dynamics, where the Assistant (Actor) adapts its policy based on the evaluation from the Checker (Critic), facilitating continuous learning and improvement.

3.2 Learning Strategy

To optimize the Assistant's policy $\pi_{\theta_{\text{actor}}}$, we employ a learning strategy that integrates supervised fine-tuning, feedback-driven reinforcement learning using the Actor-Critic method, and advanced reasoning methods like Chain of Thought (CoT) and ReAct.

3.2.1 Supervised Fine-Tuning

The Assistant's model $\mathcal{M}_{\theta_{\text{actor}}}$ is initially fine-tuned on a dataset $\mathcal{D} = \{(\mathbf{x}_i, \mathbf{y}_i)\}$ using techniques like LoRA (Hu et al., 2021) and P-Tuning (Lester et al.,

2021), minimizing the loss function:

$$L_{\text{sup}}(\theta_{\text{actor}}) = \mathbb{E}_{(\mathbf{x},\mathbf{y})\sim\mathcal{D}}\left[\ell\left(\mathcal{M}_{\theta_{\text{actor}}}(\mathbf{x}),\mathbf{y}\right)\right], \quad (1)$$

where $\ell(\cdot,\cdot)$ denotes the cross-entropy loss.

3.2.2 Incorporating Chain of Thought and ReAct

To enhance reasoning capabilities, the Assistant employs Chain of Thought (CoT) prompting, generating intermediate reasoning steps $\mathbf{c}_t$ before producing the final action $\mathbf{a}_t$: $\mathbf{c}_t = \text{CoT}(\mathbf{x}_t)$, $\mathbf{a}_t = \pi_{\theta_{\text{actor}}}(\mathbf{c}_t,\mathbf{x}_t)$.

ReAct further integrates reasoning and acting by allowing the Assistant to interleave reasoning tokens and action tokens during generation, improving task performance.

We observe that the generation order of CoT significantly impacts the correctness of the Assistant's responses. Specifically, generating the CoT before the final answer leads to higher accuracy compared to generating the answer first and then the CoT. This suggests that the Assistant's reasoning process benefits from explicitly formulating thought sequences prior to action selection.

3.2.3 Feedback-Driven Policy Optimization Inspired by Actor-Critic Dynamics

Following supervised fine-tuning, the Assistant interacts with the Checker to receive feedback f_t, updating its parameters θ_{actor} to enhance policy performance. We employ an Actor-Critic-inspired method for policy optimization without engaging in traditional reinforcement learning dynamics.

The Assistant updates its policy parameters θ_{actor} using gradient ascent as follows:

$$\theta_{\text{actor}} \leftarrow \theta_{\text{actor}} + \alpha\nabla_{\theta_{\text{actor}}}\log\pi_{\theta_{\text{actor}}}(\mathbf{a}_t|s_t)\delta_t, \quad (2)$$

where α is the learning rate, and δ_t represents the error term calculated as:

$$\delta_t = r_t + \gamma V_{\theta_{\text{critic}}}(s_{t+1}) - V_{\theta_{\text{critic}}}(s_t), \quad (3)$$

In this context, $r_t = R(f_t)$ denotes the feedback-derived reward from the Checker, $V_{\theta_{\text{critic}}}(s_t)$ is the value function estimated by the Checker (Critic) with parameters θ_{critic}, and γ is the discount factor.

The Checker updates its value function parameters θ_{critic} based on the error term δ_t using the following rule:

$$\theta_{\text{critic}} \leftarrow \theta_{\text{critic}} + \beta\delta_t\nabla_{\theta_{\text{critic}}}V_{\theta_{\text{critic}}}(s_t), \quad (4)$$

where β is the learning rate for the Critic.

This feedback-driven policy optimization framework allows the Assistant to iteratively refine its decision-making strategy based on the Checker's evaluations. Unlike traditional reinforcement learning, the approach does not involve exploration of an environment or accumulation of rewards over time. Instead, it relies on direct feedback from the Checker to guide policy adjustments, ensuring continuous improvement in task performance through collaborative interactions.

3.3 Checker-In-The-Loop Mechanism

The *Checker-In-The-Loop* concept introduces the Checker $\mathcal{C}$ as an integral part of the learning process, not only providing feedback but actively guiding the Assistant's optimization. The Checker evaluates the Assistant's actions and provides corrective feedback f_t that influences both the Actor's policy and the Critic's value function, ensuring that the Assistant adheres to predefined standards.

3.4 Memory Management and Reflexion Process

The Assistant employs a dual-memory system $\mathcal{M} = \{\mathcal{M}_S, \mathcal{M}_L\}$ to balance short-term responsiveness and long-term learning:

- **Short-Term Memory ($\mathcal{M}_S$):** Stores recent interactions, capturing immediate context for quick decision-making.

- **Long-Term Memory ($\mathcal{M}_L$):** Accumulates significant experiences and insights from self-reflection to improve future performance.

At each time step t, $\mathcal{M}_S$ is updated as:

$$\mathcal{M}_S^{t+1} = \mathcal{U}(\mathcal{M}_S^t, \mathbf{x}_t, \mathbf{a}_t, f_t), \quad (5)$$

where $\mathcal{U}$ represents the memory update operation, maintaining a fixed capacity by removing the oldest entries when necessary.

The Assistant evaluates its action $\mathbf{a}_t$ and feedback f_t, generating self-reflection s_t:

$$s_t = \varphi(\mathbf{a}_t, f_t, \mathcal{M}_S^t), \tag{6}$$

which is consolidated into long-term memory:

$$\mathcal{M}_L^{t+1} = \mu(\mathcal{M}_L^t, s_t). \tag{7}$$

Policy parameters are updated based on feedback and self-reflection:

$$\theta_{\text{actor}} \leftarrow \theta_{\text{actor}} - \alpha \nabla_{\theta_{\text{actor}}} L(f_t, \mathbf{a}_t) + \gamma \nabla_{\theta_{\text{actor}}} G(s_t), \tag{8}$$

where $L(f_t, \mathbf{a}_t)$ is the feedback loss derived from the Checker, $G(s_t)$ represents self-reflection gains, and γ is the learning rate for self-reflection.

By integrating short-term and long-term memory with reflexion, the Assistant refines its policy $\pi_{\theta_{\text{actor}}}$, continuously learning from interactions and accumulated knowledge.

4 Experiments

Our evaluation framework rigorously tests intelligent agents in six key domains to ensure their readiness for diverse real-world challenges (Ross et al., 2023). These areas include seamless LLM integration into OS with an emphasis on security and user interaction; proficiency in real DB operations using SQL (Halevy et al., 2004); task execution on the simulated e-commerce platform Web-Shop(WS) (Yao et al., 2022); constructing and using KGs for enhanced semantic understanding; employing the M2W dataset for complex web tasks, marking the first dataset for developing general web agents following language instructions; and applying abstract reasoning and visual tasks in the text-based ALFWorld(ALF) (Shridhar et al., 2021). For more implementation and evaluation details, see Appendices A and B.

4.1 Dataset

The dataset for our research was meticulously constructed to comprehensively evaluate the capabilities of agents (Gou et al., 2020). It was established through self-collected methods, aimed at providing a rich and diverse testing environment to thoroughly assess the performance of deep learning models

Table 1: Evaluation of Code Correction

Model	BLEU-4	ROUGE-1	ROUGE-2	ROUGE-L
codellama-7b	25.01	45.91	29.83	26.24
codellama-13b	26.96	45.31	29.54	25.91
tinyllama-1.8b	**43.38**	**59.86**	**37.81**	**42.86**

across various tasks (Sachdeva and McAuley, 2023). The construction of the dataset included key processes such as data collection, filtering, enhancement, and knowledge distillation (Chen and Liu, 2018). Through detailed screening and processing, we ensured the accuracy and consistency of the dataset, retaining only high-quality samples directly related to the testing objectives (Sachdeva and McAuley, 2023). Faced with issues of data imbalance and insufficient samples, we utilized data augmentation and knowledge distillation techniques. Knowledge distillation helped us to extract the most valuable and representative information from the vast amount of collected data, thus building an efficient and refined testing dataset. This process significantly improved the quality and applicability of the dataset, providing a solid foundation for evaluating the capabilities of model agents (Mishra and Marr, 2017).

4.2 Evaluating Code Correction

As shown in the Table 1, in this study, we conducted a comprehensive performance evaluation of TinyAgent-1.8B and the CodeLlama series models (CodeLlama7B and CodeLlama13B), aiming to explore their multi-task checking capabilities, including but not limited to code correction, OS configuration, DB query optimization, and WS. The experimental results showed that TinyAgent-1.8B demonstrated a significant advantage in cross-task performance evaluation compared to the CodeLlama series models. This performance was not only significant in code correction tasks but also prominent in other checking tasks such as OS configuration, DB query optimization, and WS management. These findings highlight that TinyAgent-1.8B not only possesses efficient code analysis capabilities but is also widely applicable to the inspection and optimization of other complex systems.

4.3 Baselines

In the baseline section of our study, we've selected Qwen-1.8B and CodeLlama-7B as pivotal bench-

Table 2: Test set results of AGENTBENCH. Comparison between API-based models and open-source models. Bold: The best among API-based and open-source models.

LLM Type	Models	VER	OS	DB	KG	ALF	WS	M2W
API	gpt-3.5-turbo	0613	31.6	15.7	25.9	16.0	**64.1**	16.0
	gpt-4	0613	**42.4**	**32.0**	**58.8**	**78.0**	61.6	**29.0**
	text-davinci-003	-	20.1	16.3	34.9	20.0	61.7	26.0
	text-davinci-002	-	8.3	16.7	41.5	16.0	56.3	9.0
OSS	tinyllama-1.1b (Zhang et al., 2024)	-	2.8	0.0	0.0	0.0	0.0	0.0
	opt-1.3b (Zhang et al., 2022)	-	0.7	0.0	0.0	0.0	0.0	0.0
	opt-2.7b	-	1.4	0.0	0.0	0.0	0.0	0.0
	qwen-1.8b	chat	10.4	22.67	6.8	0.0	26.6	5.0
	chatglm2-6b [1]	v1.1	4.2	1.3	0.0	0.0	0.0	0.0
	codellama-7b	instruct	9.7	2.7	0.0	0.0	14.3	5.0
	llama2-7b (Touvron et al., 2023)	chat	0.0	4.2	8.0	0.0	11.6	7.0
	zephyr-7b (Tunstall et al., 2023)	alpha	12.5	9.7	5.0	8.0	45.0	11.0
	baichuan2-6b (Yang et al., 2023)	chat	2.8	9.7	0.0	0.0	6.1	11.0
	mpt-7b [2]	chat	5.6	9.7	12.7	0.0	0.0	0.0
	qwen-7b	chat	12.5	13.0	7.0	**34.3**	0.0	0.0
	agentlm-7b	chat	14.6	33.0	9.0	16.4	18.4	10.0
	agentlm-7b(SFT)	chat	17.4	37.0	10.0	17.4	26.6	10.0
	tinyagent-1.8b	chat	17.7	28.33	**48.0**	6.0	32.7	11.0
	tinyagent-7b	chat	**23.1**	**41.3**	28.0	8.0	**58.7**	**12.0**

marks to assess the TinyAgent series' performance, excluding the CMAT framework's influence.

4.4 Results analysis

The results in Table 2 underscore the effectiveness of our fine-tuning methods, especially for the TinyAgent models. Tinyagent-1.8B demonstrates significant performance in the KG task, on par with advanced models like GPT-3.5. Tinyagent-7B also showcases its strengths, notably in the DB task, where it surpasses its foundational model (Antonello et al., 2020), CodeLlama-7B, and offers competitive scores against GPT-4. These findings indicate the TinyAgent models' capacity to match or even surpass models with larger parameters in certain aspects. Moreover, the CMAT framework's potential to enhance the capabilities of smaller-scale models is highlighted, allowing the TinyAgent models to closely compete with the performance of advanced models such as GPT-4.

As illustrated in Figure 1, Our comparative analysis indicates that Tinyagent models, refined from Qwen-1.8B and CodeLlama-7B, exhibit superior per-

formance to their base models. The incorporation of the CMAT framework further amplifies their functionality, equipping these small Models to match the capabilities of GPT-3.5. This performance boost is credited to CMAT's optimization of model interactions and its strategic use of memory modes for specific tasks, confirming its effectiveness in enhancing the sophistication of fine-tuned models (Deshpande et al., 2021).

Table 3 presents the impact of different prompting strategies on performance metrics. High-quality prompts significantly outperform low-quality prompts and scenarios without prompts across all evaluation metrics, demonstrating the importance of prompt design in optimizing model performance.

Table 3: Evaluation Metrics Results

Evaluation Method	BLEU-4	ROUGE-1	ROUGE-2	ROUGE-L
prompt - High-quality	44.4	57.3	35.0	42.5
prompt - Low-quality	15.2	27.4	10.3	16.8
without prompts	26.8	47.2	30.2	26.7

4.5 Error analysis

In our testing framework's error analysis, we observed common challenges in DB tasks faced by models, such as difficulties in understanding user requests, executing actions, and pre-action problem analysis. Many models simply respond with "OK" to specific instructions without performing actual SQL operations, indicating a gap in transforming user requests into database actions. Models often provide superficial acknowledgments without delivering precise execution or in-depth problem analysis, failing to meet user expectations. In contrast, the TinyAgent series excels in understanding and converting user requests into actual SQL operations, effectively comprehending and executing tasks. It provides clear responses and adheres to user-specified SQL formats, fulfilling user expectations comprehensively. Additionally, TinyAgent's thorough pre-action problem analysis and reflection demonstrate its advanced problem-solving skills and deep understanding of issues.

As illustrated in Table 4, the distribution of various execution results across six tasks highlights the prevalence of specific error types, such as exceeding task limits (TLE) and invalid actions, which point to limitations in LLM agents' reasoning and decision-making within constrained timeframes.

Table 4: Distribution of various execution results across six tasks. (CLE: Exceeded Context Limit, TLE: Surpassed Task Limit). Task limits exceeded are the main reason for incomplete tasks, pointing to limitations in LLM agents' reasoning and decision-making within constrained timeframes.

Execution Results	OS	DB	KG	ALF	WS	M2W
Completed	84.7	84.0	25.0	2.0	93.5	57.0
CLE	0.0	0.0	0.0	0.0	0.0	0.0
Invalid Format	0.0	3.0	0.0	0.0	0.0	0.0
Invalid Action	0.0	0.0	0.0	96.0	0.0	8.0
TLE	15.3	13.0	75.0	2.0	6.5	35.0

4.6 Ablation Study

The Table 5 presents an ablation study on the TinyAgent-7B model, delineating the impact of agent-specific and general instructions on task performance. The composite model, TinyAgent-7B, demonstrates the highest efficacy, notably in WS and

Table 5: Ablation study on the effect of agent and general instructions.

Models	OS	DB	KG	ALF	WS	M2W
tinyagent-7b	**27.3**	**43.0**	**38.0**	**10.0**	**61.8**	**14.0**
- agent only	20.1	39.3	25.0	2.0	55.7	7.0
- general only	9.7	5.4	0.0	0.0	26.6	5.0

DB tasks, which implies its adeptness in handling complex e-commerce interactions and database management. The agent-only variant exhibits a decline in performance, suggesting that while task-specific instructions are crucial, they are not wholly sufficient for the breadth of tasks such as KG. The general-only model's performance is considerably reduced across all tasks, with a complete inability to perform in KG and ALF, highlighting the indispensability of agent-specific instructions. This data underscores the necessity of integrating both agent-specific and general instructions to enhance the versatility and effectiveness of AI models in diverse task domains.

5 Conclusions

The main findings of our work reveal that carefully trained small-parameter models on excellent datasets can achieve performance comparable to that of large-parameter models. With the application of the CMAT framework, we further demonstrate the significant potential for performance improvement in large-parameter models, highlighting the importance of model design and optimization strategies for parameter size. In our evaluation, although most open-source LLMs performed poorly compared to API-provided models without optimization, some models displayed similar capabilities to API models after meticulous fine-tuning of the TinyAgent model. This finding emphasizes not only the importance of parameter size in handling real-world environmental interactions but also showcases the enormous potential of even smaller models through the CMAT framework and precise adjustment strategies.

6 Limitations

In this study, we demonstrated the potential for performance improvement by applying the CMAT framework to TinyAgent series models and other large language models (LLMs). However, there are

clear limitations to the research: First, although most models showed improved performance, some models saw limited improvement due to weaker base agent capabilities, indicating that the effectiveness of the CMAT framework might vary significantly between different models; second, the limitations of datasets and task types could affect the broad applicability of the conclusions, while low-quality datasets could negatively impact model performance; lastly, although evaluations based on AgentBench ensured fairness, they might not fully reflect the complexity of real-world scenarios, and due to computational resource constraints, larger-scale models could not be tested. This underscores the importance of future work to consider a wider range of models, datasets, and task types, especially the implementation of optimization strategies and framework applications in resource-constrained situations.

References

Abubakar Abid, Maheen Farooqi, and James Zou. 2021. Large language models associate muslims with violence. *Nature Machine Intelligence*, 3(6):461–463.

Richard J. Antonello, Javier Turek, and Alexander G. Huth. 2020. Selecting informative contexts improves language model fine-tuning. *ArXiv*, abs/2005.00175.

Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei Huang, et al. 2023. Qwen technical report. *arXiv preprint arXiv:2309.16609*.

Yalong Bai, Kuiyuan Yang, Wei Yu, Chang Xu, Wei-Ying Ma, and T. Zhao. 2015. Automatic image dataset construction from click-through logs using deep neural network. *Proceedings of the 23rd ACM international conference on Multimedia*.

C. L. P. Chen and Zhulin Liu. 2018. Broad learning system: An effective and efficient incremental learning system without the need for deep architecture. *IEEE Transactions on Neural Networks and Learning Systems*, 29:10–24.

Filippos Christianos, Georgios Papoudakis, Matthieu Zimmer, Thomas Coste, Zhihao Wu, Jingxuan Chen, Khyati Khandelwal, James Doran, Xidong Feng, Jiacheng Liu, et al. 2023. Pangu-agent: A fine-tunable generalist agent with structured reasoning. *arXiv preprint arXiv:2312.14878*.

I de Zarzà, J de Curtò, Gemma Roig, Pietro Manzoni, and Carlos T Calafate. 2023. Emergent cooperation and strategy adaptation in multi-agent systems: An extended coevolutionary theory with llms. *Electronics*, 12(12):2722.

A. Deshpande, A. Achille, Avinash Ravichandran, Hao Li, L. Zancato, Charless C. Fowlkes, Rahul Bhotika, Stefano Soatto, and P. Perona. 2021. A linearized framework and a new benchmark for model selection for fine-tuning. *ArXiv*, abs/2102.00084.

Elhadji Amadou Oury Diallo, Ayumi Sugiyama, and T. Sugawara. 2020. Coordinated behavior of cooperative agents using deep reinforcement learning. *Neurocomputing*, 396:230–240.

Mengnan Du, Fengxiang He, Na Zou, Dacheng Tao, and Xia Hu. 2022. Shortcut learning of large language models in natural language understanding: A survey. *arXiv preprint arXiv:2208.11857*.

Alexander Dunn, John Dagdelen, Nicholas Walker, Sanghoon Lee, Andrew S Rosen, Gerbrand Ceder, Kristin Persson, and Anubhav Jain. 2022. Structured information extraction from complex scientific text with fine-tuned large language models. *arXiv preprint arXiv:2212.05238*.

N. Ferry, F. Chauvel, Hui Song, A. Rossini, Maksym Lushpenko, and Arnor Solberg. 2018. Cloudmf: Model-driven management of multi-cloud applications. *ACM Trans. Internet Techn.*, 18:16:1–16:24.

Eloy García, Yongcan Cao, and D. Casbeer. 2015. Periodic event-triggered synchronization of linear multi-agent systems with communication delays. *IEEE Transactions on Automatic Control*, 62:366–371.

Jianping Gou, B. Yu, S. Maybank, and D. Tao. 2020. Knowledge distillation: A survey. *International Journal of Computer Vision*, 129:1789 – 1819.

A. Halevy, Z. Ives, J. Madhavan, P. Mork, Dan Suciu, and I. Tatarinov. 2004. The piazza peer data management system. *IEEE Transactions on Knowledge and Data Engineering*, 16:787–798.

José Hernández-Orallo, Marco Baroni, Jordi Bieger, Nader Chmait, David L Dowe, Katja Hofmann, Fernando Martínez-Plumed, Claes Strannegård, and Kristinn R Thórisson. 2017. A new ai evaluation cosmos: Ready to play the game? *AI Magazine*, 38(3):66–69.

Jeremy Howard and Sebastian Ruder. 2018. Universal language model fine-tuning for text classification. pages 328–339.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. 2020. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*.

Brian Lester, Rami Al-Rfou, and Noah Constant. 2021. The power of scale for parameter-efficient prompt tuning. *arXiv preprint arXiv:2104.08691*.

Mike Lewis, Denis Yarats, Yann N Dauphin, Devi Parikh, and Dhruv Batra. 2017. Deal or no deal? end-to-end learning for negotiation dialogues. *arXiv preprint arXiv:1706.05125*.

Guohao Li, Hasan Abed Al Kader Hammoud, Hani Itani, Dmitrii Khizbullin, and Bernard Ghanem. 2023. Camel: Communicative agents for" mind" exploration of large scale language model society. *arXiv preprint arXiv:2303.17760*.

Xin Liang, G. Shen, and Shanshan Bu. 2016. Multia-gent systems in construction: A ten-year review. *Journal of Computing in Civil Engineering*, 30:04016016–04016016.

Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, et al. 2023. Agentbench: Evaluating llms as agents. *arXiv preprint arXiv:2308.03688*.

Kai Lu and Chongyang Zhang. 2020. Blockchain-based multiparty computation system. In *2020 IEEE 11th International Conference on Software Engineering and Service Science (ICSESS)*, pages 28–31. IEEE.

Asit K. Mishra and Debbie Marr. 2017. Apprentice: Using knowledge distillation techniques to improve low-precision network accuracy. *ArXiv*, abs/1711.05852.

Volodymyr Mnih, K. Kavukcuoglu, David Silver, Andrei A. Rusu, J. Veness, Marc G. Bellemare, A. Graves, Martin A. Riedmiller, A. Fidjeland, Georg Ostrovski, Stig Petersen, Charlie Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, D. Kumaran, Daan Wierstra, S. Legg, and D. Hassabis. 2015. Human-level control through deep reinforcement learning. *Nature*, 518:529–533.

OpenAI. 2023. Gpt-4 technical report.

Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, J. Schulman, Jacob Hilton, Fraser Kelton, Luke E. Miller, Maddie Simens, Amanda Askell, P. Welinder, P. Christiano, J. Leike, and Ryan J. Lowe. 2022. Training language models to follow instructions with human feedback. *ArXiv*, abs/2203.02155.

Pranav Rajpurkar, Robin Jia, and Percy Liang. 2018. Know what you don't know: Unanswerable questions for squad. *arXiv preprint arXiv:1806.03822*.

Steven I. Ross, Fernando Martinez, Stephanie Houde, Michael J. Muller, and Justin D. Weisz. 2023. The programmer's assistant: Conversational interaction with a large language model for software development. *ArXiv*, abs/2302.07080.

Baptiste Roziere, Jonas Gehring, Fabian Gloeckle, Sten Sootla, Itai Gat, Xiaoqing Ellen Tan, Yossi Adi, Jingyu Liu, Tal Remez, Jérémy Rapin, et al. 2023. Code llama: Open foundation models for code. *arXiv preprint arXiv:2308.12950*.

Noveen Sachdeva and Julian McAuley. 2023. Data distillation: A survey. *ArXiv*, abs/2301.04272.

Mohit Shridhar, Xingdi Yuan, Marc-Alexandre Côté, Yonatan Bisk, Adam Trischler, and Matthew Hausknecht. 2021. ALFWorld: Aligning Text and Embodied Environments for Interactive Learning. In *Proceedings of the International Conference on Learning Representations (ICLR)*.

Nisan Stiennon, Long Ouyang, Jeff Wu, Daniel M. Ziegler, Ryan J. Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul Christiano. 2020. Learning to summarize from human feedback. *ArXiv*, abs/2009.01325.

Yashar Talebirad and Amirhossein Nadiri. 2023. Multi-agent collaboration: Harnessing the power of intelligent llm agents. *arXiv preprint arXiv:2306.03314*.

V. Talwar, Qinyi Wu, C. Pu, W. Yan, G. Jung, and D. Milojicic. 2005. Comparison of approaches to service deployment. *25th IEEE International Conference on Distributed Computing Systems (ICDCS'05)*, pages 543–552.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Lewis Tunstall, Edward Beeching, Nathan Lambert, Nazneen Rajani, Kashif Rasul, Younes Belkada, Shengyi Huang, Leandro von Werra, Clémentine Fourrier, Nathan Habib, et al. 2023. Zephyr: Direct distillation of lm alignment. *arXiv preprint arXiv:2310.16944*.

José R Vázquez-Canteli and Zoltán Nagy. 2019. Reinforcement learning for demand response: A review of algorithms and modeling techniques. *Applied energy*, 235:1072–1089.

Jun Wang, Yong-Hong Sun, Z. Fan, and Yan Liu. 2005. A collaborative e-learning system based on multi-agent. pages 455–463.

Aiyuan Yang, Bin Xiao, Bingning Wang, Borong Zhang, Ce Bian, Chao Yin, Chenxu Lv, Da Pan, Dian Wang, Dong Yan, et al. 2023. Baichuan 2: Open large-scale language models. *arXiv preprint arXiv:2309.10305*.

Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. 2022. Webshop: Towards scalable real-world web interaction with grounded language agents.

Aohan Zeng, Mingdao Liu, Rui Lu, Bowen Wang, Xiao Liu, Yuxiao Dong, and Jie Tang. 2023. Agenttuning: Enabling generalized agent abilities for llms. *arXiv preprint arXiv:2310.12823*.

Peiyuan Zhang, Guangtao Zeng, Tianduo Wang, and Wei Lu. 2024. Tinyllama: An open-source small language model. *arXiv preprint arXiv:2401.02385*.

Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, et al. 2022. Opt: Open pre-trained transformer language models. *arXiv preprint arXiv:2205.01068*.

Wentao Zhang, Yang Liu, Jianquan Lu, and Jinde Cao. 2017. A novel consensus algorithm for second-order multi-agent systems without velocity measurements. *International Journal of Robust and Nonlinear Control*, 27:2510 – 2528.

Kai Zhao, Yongduan Song, CL Philip Chen, and Long Chen. 2021. Adaptive asymptotic tracking with global performance for nonlinear systems with unknown control directions. *IEEE Transactions on Automatic Control*, 67(3):1566–1573.

A   Implementation Settings

In this paper, we describe an experiment conducted using the Low-Rank Adaptation (LoRA) fine-tuning method to enhance the performance of various models (Wang et al., 2005). The accuracy of the LoRA method is of paramount importance in dealing with personalized and emotionally rich content. It enables the models to adapt to new data features while maintaining their core capabilities (Bai et al., 2015).

During the experiment, we set the temperature parameter of the test models to 0.7 to increase the diversity of the content, and adjusted the top-p value to 0.95 to improve the precision of the generated content. We employed a learning rate of 2e-4 and beta values of (0.9, 0.999) to ensure the stability of the training process. The batch size was set to 4, with gradient accumulation, to ensure efficiency within the limits of computational resources. To balance innovation and coherence, we used LoRA parameters with a rank of 8 and an alpha value of 32, and adjusted both the top-p value and the temperature parameter to 0.7.These adjustments significantly enhanced the models' flexibility and accuracy in handling personalized and emotionally rich content.

B   Evaluation criteria

(1) **Operating systems** Integrating LLMs into operating systems offers vast potential for automating and optimizing tasks. This integration demands a secure, user-friendly interface for effective LLM-OS interaction and requires LLMs to accurately understand the OS context for informed operations. Ensuring the safety of these operations is paramount to prevent misuse. Moreover, the system must handle errors and provide clear feedback to users, enhancing interaction and control. Addressing these aspects can revolutionize computer interaction and efficiency across industries.

(2) **Database** Database (DB). Due to the crucial and challenging nature of database analysis in many daily affairs, it is paramount to examine the abilities of LLMs to operate on real databases via SQL. Previous research has placed significant emphasis on individual procedures, such as showcasing the effectiveness of LLMs in automating database access through T5QL, a new SQL generation method. Additionally, utilizing fine-tuned LLMs (such as GPT-3.5) to extract and link complex scientific information from scientific texts has demonstrated the capacity of LLMs to obtain structured knowledge from unstructured text and subsequently construct large databases (Dunn et al., 2022).

(3) **WebShop** represents an innovative simulation of an e-commerce website environment, featuring 1.18 million real-world products and 12,087 crowd-sourced text instructions. This platform challenges agents to navigate through multiple types of webpages and perform a variety of actions to find, customize, and purchase prod-

ucts according to given instructions. WebShop presents several challenges, including understanding compositional instructions, query (re-)formulation, dealing with noisy text in webpages, and conducting strategic exploration.

(4) Knowledge Graphs The utilization of LLMs in constructing and interacting with knowledge graphs (KG) offers a promising avenue for enhancing semantic understanding and information retrieval. This involves assessing the models' ability to not only generate but also interpret complex interrelations within data, facilitating more intuitive and context-aware responses. The effectiveness of LLMs in this domain could significantly improve AI's capacity for reasoning and decision-making based on structured knowledge.

(5) Mind2Web Mind2Web (M2W) is a dataset for developing web agents that perform complex tasks on real websites via language instructions. It features over 2,000 tasks across 137 sites from 31 domains. M2W's real web environments and diverse user interactions make it a crucial platform for advancing AI navigation capabilities.

(6) ALFWorld bridges interactive TextWorld environments with embodied tasks from the AL-FRED dataset, enabling agents to learn abstract strategies and apply them to real-world tasks. It facilitates abstract reasoning and concrete execution, allowing agents to plan actions in a text-based simulator and then execute these tasks in a visual environment. This approach enhances agent generalization and problem-solving skills across various domains, such as language understanding and visual navigation, by leveraging a modular design that simplifies research improvements.

C Details about Experiment

By examining prompts of varying quality—high-quality, low-quality, and no prompts—we aimed to reveal how these factors influence the model's capability, especially in identifying and correcting programming errors. Our findings indicate that fine-tuned high-quality prompts significantly enhance the

model's ability to write and rigorously check code, enabling it to produce high-quality code and conduct stricter code inspections. As demonstrated in the Table 23∼ 25 .In contrast, low-quality prompts might lead to the model generating nonsensical and ineffective code, and in situations where correct code is provided, the model might even alter it to incorrect code. The decline in model output quality in these instances is primarily due to the vague and unclear descriptions provided by the prompts and the lack of specific guidance, which prevents the model from effectively utilizing the knowledge it acquired during training to focus on key error points and make accurate correction decisions. Moreover, our study also showed that in the absence of any prompt guidance, the model's performance tends to be limited by the quality and scope of its training data, particularly when faced with novel or complex error types. This finding underscores the importance of high-quality prompts in designing effective NLP models for complex tasks like code correction. High-quality prompts not only guide the model to more accurately understand and address specific programming issues but also reduce noise in the processing, thereby improving overall efficiency and accuracy.

D Prompts for Tasks

We describe the task to the checker agent using the following instruction as shown in Table 6 ∼ 12.

E Examples of Tasks

All tasks in the dataset are divided into six categories. For each category, we present an example of successful execution as shown in Table 13∼ 22.

Table 6: Prompt for DATABASE

DATABASE(DB)

```
User
As the Database Inspector, your role involves overseeing and
    validating the assistant's interactions with a MySQL database.
    The objective is a seamless collaboration to fulfill a specified
    task. The process is straightforward: the assistant will submit
    SQL queries, and it's your responsibility to examine the SQL
    syntax and logic to confirm their accuracy in addressing the
    given question.
The mission is to collaborate effectively. You leverage your
    expertise, guiding the assistant through the task. If the
    assistant deviates from the correct approach, you're expected to
    provide guidance, offering both your insight and the correct
    solution. Documenting your thought process is essential.
During each review cycle, you're given the option to act by
    providing a SQL command or conclude with an answer. Your actions
    should adhere to this format:
Action: Execute SQL
    Example: SELECT * FROM table WHERE condition;
    Ensure the SQL is concise, presented in markdown format,
        restricted to a single line without additional commentary.
        Only one SQL statement should be executed at a time.
The assistant will execute only the first SQL code block you provide
    and then share the output. Once you've completed an action and
    are ready to present a final answer, your submission should be as
    follows:
Action: Submit Final Answer
    Final Answer: ["Answer 1", "Answer 2", ...]
Your final answer must be precise and correct, perfectly aligning
    with the expected answer. If the task involves modifying the
    database, the answer field might vary post-operation. Nonetheless
    , any departure from the specified response format will lead to
    an immediate failure of the task.
It's important to remember that you will be presented with the raw
    MySQL response to analyze independently. Accuracy and correctness
     are crucial in this joint effort.
```

Table 7: Prompt for KNOWLEDGE GRAPH

KNOWLEDGE GRAPH(KG)

User

As a reviewer, your task is to verify that the system for answering
   questions based on a knowledge base (KB) operates correctly. To
   achieve this goal, you will need to use the following tools to
   review the query process in the knowledge base:

1. Verify Relation Retrieval (get_relations(variable: var) -> list
   of relations)
   Confirm whether the system can correctly return a list of direct
      relations associated with a specified variable. The variable
      can be either a single entity or a set of entities (i.e., the
      result of a previous query). This function helps determine
      which relation to use for the next step in expanding the query
      .
   Example: Verify if `get_relations(Barack Obama)` can find all
      relations/edges starting from the entity Barack Obama.
   Note: The argument for `get_relations` must be a clearly defined
      entity or a variable obtained from a previous query (such as
      #0).

2. Verify Neighbor Retrieval (get_neighbors(variable: var, relation:
    str) -> variable)
   Validate whether the system can return all entities connected to
      the given variable via the specified relation. Note that `
      get_neighbors()` can only be used after `get_relations()` is
      used to find a set of viable relations.
   Example: Verify if `get_neighbors(Barack Obama, people.person.
      profession)` correctly returns Obama's profession in Freebase.

3. Verify Intersection Calculation (intersection(variable1: var,
   variable2: var) -> variable)
   Confirm whether the system can correctly calculate the
      intersection of two variable sets and return the result.
      Importantly, the two variable sets must be of the same type.

4. Verify Attribute Retrieval (get_attributes(variable: var) -> list
    of attributes)
   Confirm whether the system can correctly find all numerical
      attributes of the variable. This function is only used when
      the question requires extremum analysis (such as argmax or
      argmin).

Table 8: Prompt for KNOWLEDGE GRAPH

KNOWLEDGE GRAPH(KG)

```
5. Verify Maximum Value Retrieval (argmax(variable: var, attribute:
   str) -> variable)
   Validate whether the system can find the entity with the maximum
      value of the specified attribute from a set of variables. This
       operation requires using `get_attributes()` first to obtain a
       list of viable attributes.
   Example: Verify if `argmax(variable, age)` correctly returns the
      oldest entity in the variable set.

6. Verify Minimum Value Retrieval (argmin(variable: var, attribute:
   str) -> variable)
   Similar to `argmax`, but needs to validate whether the system can
       return the entity with the minimum attribute value.

7. Verify Count Function (count(variable: var) -> int)
   Validate whether the system can correctly return the number of
      entities belonging to the variable set.

Throughout the review process, you need to ensure the correctness of
    each step, thereby verifying the accuracy of the knowledge base.
    Each variable is represented by an id starting from 0. Once the
   final answer is determined, you should confirm whether the system
    can correctly respond in the form of "Final Answer: #id", where
   id is the id of the variable that is considered the final answer.
    For example, confirm if the system correctly responded with "
   Final Answer: #3" when it determined #3 to be the final answer.

Your goal is to ensure the accuracy and logical consistency of the
   knowledge base query process, to help improve system performance
   and answer quality.
```

Table 9: Prompt for WEBSHOP

WEBSHOP(WS)

> **User**
> As the Shopping Experience Auditor, you are charged with the task of verifying that all actions undertaken in our web shopping simulation adhere to the given instructions and are executed correctly.
> Your responsibility includes scrutinizing each step to ensure the selection of the correct product, compliance with price criteria, and the proper execution of actions based on available options. Should any discrepancies arise, it's within your purview to identify them and recommend appropriate corrections.
> You are invited to specify any particular interactions for verification, and you will conduct a thorough assessment to guarantee the precision of our shopping procedure.

Table 10: Prompt for ALFWORLD

ALFWORLD(ALF)

> **User**
> As an Interactive Environment Auditor, your task is to meticulously review the actions taken by the intelligent agent in the household environment, ensuring they comply with the given instructions and the range of available actions.
> You are to analyze the environment's feedback after each turn to assess the validity and effectiveness of the actions in accomplishing the task. Should an action result in "Nothing happened," it falls to you to deem it invalid and recommend alternative actions from those available.
> Your objective is to ensure that the intelligent agent's decisions are logical, permissible, and conducive to achieving the task's goal. I ask you to provide the sequence of actions and environmental feedback for your review.

Table 11: Prompt for MIND2WEB

MIND2WEB(M2W)

```
User

As the Web Browsing Quality Supervisor, your role is to evaluate the
    agent's attempt at completing the following task and assess
   whether the chosen action aligns with the HTML webpage and task
   description:

Task Description:
[Insert specific task description here]

Previous actions taken by the agent:
[List of previous actions]

Agent's proposed next action:
Element: [Description of the selected element]
Action: [Type of action]
Value: [Value for input or selection, if the action is not a click]

Please examine the HTML element and the task description. Determine
   if the agent's proposed action accurately fulfills the task
   requirements.
Provide feedback on the appropriateness of the action. If it
   deviates from what is required, kindly specify the correct action
    that should be taken.
```

Table 12: Prompt for OPERATING SYSTEM

OPERATING SYSTEM(OS)

User

As the System Operation Audit Expert, your role is to evaluate the
    assistant's actions in the context of a simulated interaction
    with a Linux (Ubuntu) operating system.
The assistant will perform tasks based on your requests and provide
    explanations for their actions. For each round, review the
    assistant's thought process and the action taken, and determine
    if the task has been correctly completed.
The assistant can take one of three actions:
1. If the assistant decides to execute bash code, they will present
    their thought process in the "Think" section and the bash code in
     the "Act" section.
2. If the assistant believes the task is finished, they will
    indicate completion in the "Think" section and provide a
    justification for why the task is considered complete.
3. If the assistant has an answer to a question, they will explain
    how they arrived at the answer in the "Think" section and provide
     the answer in the "Act" section.
Your task is to assess the assistant's performance based on the
    following criteria:
Accuracy: Is the action taken appropriate for the task described?
Completeness: Has the assistant provided all necessary information
    and performed all required steps?
Justification: Is the thought process logical and does it support
    the action taken?
Please provide feedback on the assistant's actions, including any
    errors or omissions, and suggest corrections if necessary. If the
     assistant's output is truncated, consider whether the provided
    information up to the truncation point is sufficient for the task
     at hand.

Begin your evaluation with the following prompt:
Please evaluate the assistant's last action and thought process. Was
     the task performed correctly? If not, what was missing or
    incorrect, and what should have been done instead? Provide
    specific feedback based on the assistant's "Think" and "Act"
    sections.

Table 13: Example for OPERATING SYSTEM

OPERATING SYSTEM(OS)

```
BASH>
ls /etc
User: The output of the OS: cpi cron.hourly fuse.conf iproute2 lvm
    networkd-dispatcher protocols selinux tmpfiles.d [truncated
    because the output is too long]

Agent: Think: The output has been truncated because it is too long,
    so I need to count files by script directly.
Act: bash
<BASH>
ls -1 /etc | wc -l

User: The output of the OS: 220

Agent: Think: Now I get the answer, it is 220.
Act: answer(220)

User: Now, I will start a new problem in a new OS. My problem is: In
     this problem, you need to find the total number of lines
    containing the word "Linux" in all the ".txt" files inside a
    given directory and its subdirectories.
Here's the problem detail: A new directory named "Linux_files" will
    be created in your home directory. The "Linux_files" directory
    will contain multiple ".txt" files and subdirectories. Some of
    the subdirectories inside "Linux_files" will also contain ".txt"
    files. Some of the ".txt" files will contain the word "Linux" in
    one or more lines.
Your task is to find the total number of lines containing the word "
    Linux" in all the ".txt" files inside the "Linux_files" directory
     and its subdirectories. Submit your answer as an integer.

Agent: Think: To find the total number of lines containing the word
    "Linux" in all the ".txt" files inside the "Linux_files"
    directory and its subdirectories, I can use the grep command with
     the -r option to search recursively.
Act: bash
<BASH>
grep -r "Linux" ~/Linux_files/*.txt | wc -l

User: The output of the OS: 4

Agent: Think: The output shows that there are 4 lines containing the
     word "Linux" in all the ".txt" files inside the "Linux_files"
    directory and its subdirectories.
Act: answer(4)
```

KNOWLEDGE GRAPH(KG)

```
Agent: Thought: Now I need to find the city where Busch Stadium is
   located. To achieve this, I will query the KB to find relations
   connected to the variable #1.
Action: get_relations(#1)

User: Observation: [List of relations including location.location.
   containedby, location.location.adjoin_s, location.location.
   contains, and many others]

Agent: Thought: From the above relations, I might use location.
   location.containedby to find the location of Busch Stadium.
Action: get_neighbors(Busch Stadium, location.location.containedby)

User: Observation: variable #2, which are instances of location.
   location

Agent: Thought: Now I need to find the city where Busch Stadium is
   located. To achieve this, I will query the KB to find relations
   connected to the variable #2.
Action: get_relations(#2)

User: Observation: [List of relations similar to the first list]

Agent: Thought: From the above relations, I might use location.
   location.containedby to find the location of Busch Stadium.
Action: get_neighbors(Busch Stadium, location.location.containedby)

User: Observation: variable #3, which are instances of location.
   location

Agent: Thought: The Busch Stadium is located in St. Louis, Missouri,
    USA. Now I need to find the city where the stadium is located.
   To achieve this, I will query the KB to find relations connected
   to the variable #3.
Action: get_relations(#3)
```

Table 15: Example for KNOWLEDGE GRAPH

KNOWLEDGE GRAPH(KG)

```
User: Observation: [List of relations similar to the previous lists]

Agent: Thought: From the above relations, I might use location.
    location.containedby to find the location of Busch Stadium.
Action: get_neighbors(Busch Stadium, location.location.containedby)

User: Observation: variable #4, which are instances of location.
    location

Agent: Thought: The Busch Stadium is located in St. Louis, Missouri,
     USA. Now I need to find the city where the stadium is located.
    To achieve this, I will query the KB to find relations connected
    to the variable #4.
Action: get_relations(#4)

User: Observation: [List of relations similar to the previous lists]

Agent: Thought: From the above relations, I might use location.
    location.containedby to find the location of Busch Stadium.
Action: get_neighbors(Busch Stadium, location.location.containedby)

User: Observation: variable #5, which are instances of location.
    location

Agent: Thought: The Busch Stadium is located in St. Louis, Missouri,
     USA. Now I need to find the city where the stadium is located.
    To achieve this, I will query the KB to find relations connected
    to the variable #5.
Action: get_relations(#5)

User: Observation: [List of relations similar to the previous lists]
```

ALFWORLD(ALF)

```
Agent Thought: "The task is to examine the mug with the desklamp. I
   need to find where the mug is first and then find the desklamp to
    light it up. I'll start my search on desk 1."

Agent Action: "go to desk 1"
Environment Feedback: "On the desk 1, you see a bowl 1, a desklamp
   1, a laptop 1, and a pen 1."

Agent Action: "examine bowl 1 with desklamp 1"
Environment Feedback: "You pick up the bowl 1 from the desk 1."

Agent Action: "put bowl 1 in/on desk 1"
Environment Feedback: "You put the bowl 1 in/on the desk 1."

Agent Thought: "The task is to examine the mug with the desklamp. I
   need to find where the mug is first and then find the desklamp to
    light it up. I'll start my search on desk 1."
Agent Action: "examine desk 1"
Environment Feedback: "On the desk 1, you see a bowl 1, a desklamp
   1, a laptop 1, and a pen 1."

Agent Action: "take mug 1 from desk 1"
Environment Feedback: "You pick up the bowl 1 from the desk 1."

Agent Action: "use desklamp 1"
Environment Feedback: "You turn on the desklamp 1."

Agent Action: "examine mug 1 with desklamp 1"
Environment Feedback: "You turn on the desklamp 1."
```

MIND2WEB(M2W)

```
User: Based on the HTML webpage above, try to complete the following
    task:
Task: Find tuition & fees for full term graduate students in the
    college of engineering for the academic year 2022-2023
Previous actions:
[link] Costs & Financial Aid -> CLICK
[combobox] Academic Year -> SELECT: 2022-2023
[combobox] College/School -> SELECT: College of Engineering
[combobox] Full or Half Term -> SELECT: Full Term
[combobox] Level of Study -> SELECT: Graduate
What should be the next action? Please select from the following
    choices (If the correct action is not in the page above, please
    select A. 'None of the above'):
A. None of the above
B. <a id=0> Graduation </a>
C. <select id=1 academic_year> <option all> Select </option> <option
    175 true>
D. <select id=2 college_school> <option all> Select </option> <
    option 17> College
E. <select id=3 level_of_study> <option all> Select </option> <
    option 38 true>
F. <input id=4 submit apply />
Agent: Thought: The search has already been set to College of
    Engineering and Graduate level. Next, I should select Full Term.
Answer: E.
Action: SELECT
User: Based on the HTML webpage above, try to complete the following
    task:
Task: Find tuition & fees for full term graduate students in the
    college of engineering for the academic year 2022-2023
Previous actions:
[link] Costs & Financial Aid -> CLICK
[combobox] Academic Year -> SELECT: 2022-2023
[combobox] College/School -> SELECT: College of Engineering
[combobox] Full or Half Term -> SELECT: Full Term
[combobox] Level of Study -> SELECT: Graduate
What should be the next action? Please select from the following
    choices (If the correct action is not in the page above, please
    select A. 'None of the above'):
A. None of the above
B. <input id=0 text search />
C. <a id=1> Tuition </a>
D. <div id=2> Tuition & Fees </div>
E.  Tuition & Fees 
F. <a id=4> Class Fees </a>
```

Table 18: Example for MIND2WEB

MIND2WEB(M2W)

```
Agent: Thought: The search has already been set to Tuition. Next, I
   should find the tuition & fees for full term graduate students in
    the college of engineering for the academic year 2022-2023.
Answer: D.
Action: CLICK on the link with the text "Tuition & Fees"
User: Based on the HTML webpage above, try to complete the following
    task:
Task: Find tuition & fees for full term graduate students in the
   college of engineering for the academic year 2022-2023
Previous actions:
[link] Costs & Financial Aid -> CLICK
[combobox] Academic Year -> SELECT: 2022-2023
[combobox] College/School -> SELECT: College of Engineering
[combobox] Full or Half Term -> SELECT: Full Term
[combobox] Level of Study -> SELECT: Graduate
What should be the next action? Please select from the following
   choices (If the correct action is not in the page above, please
   select A. 'None of the above'):
A. None of the above
B. <div id=0> Tuition & Fees </div>
C. <select id=1 level_of_study> <option all> Select </option> <
   option 38 true>
Agent: Thought: The search has already been set to graduate students
    in the college of engineering for the academic year 2022-2023.
   Next, I should select the level of study.
Answer: C.
Action: SELECT: Graduate
```

WEBSHOP(WS)

```
User: You are web shopping. I will give you instructions about what
   to do. You have to follow the instructions. Every round I will
   give you an observation and a list of available actions, you have
    to respond with an action based on the state and instruction.
   You can use the search action if the search is available. You can
    click one of the buttons in clickables. An action should be of
   the following structure: search[keywords] or click[value]. If the
    action is not valid, perform nothing. Keywords in search are up
   to you, but the value in click must be a value in the list of
   available actions. Remember that your keywords in search should
   be carefully designed. Your response should use the following
   format:

Thought:
I think ...

Action:
click[something]

Agent: Ok.

User: Observation:
"WebShop [SEP] Instruction: [SEP] I'm looking for rubber stole shoes
    for light wearing it was brown in color, and price lower than
   70.00 dollars [SEP] Search"

Available Actions:
{"has_search_bar": true, "clickables": ["search"]}

Agent: Thought:
I think I should use the search bar to look for the product I need.

Action:
search[rubber stole shoes brown price < 70.00]

User: Observation:
Instruction: [SEP] I'm looking for rubber stole shoes for light
   wearing it was brown in color, and price lower than 70.00 dollars
    [SEP] Back to Search [SEP] Page 1 (Total results: 50) [SEP] Next
    > [SEP] B08XHSG67V [SEP] Crosley Furniture Madeleine 53.25"
   Farmhouse Metal Kitchen Island in Brown/Black [SEP] 331.49 [SEP]
   B07CZ5YKWW [SEP] Roper Tumbled Womens Brown Leather Petty Slip-On
    Shoes [...]
```

WEBSHOP(WS)

```
[...]
Available Actions:
{"has_search_bar": false, "clickables": ["back to search", "next >",
    "b08xhsg67v", "b07cz5ykww", "b000jiatqs", "b01ld5a59g", "
   b085wr7626", "b07s7qxncw", "b01lykp60o", "b004xj62re", "
   b07fy9mfhx", "b09cfqjt7h"]}

Agent: Thought:
I think I should click on the product I need, which is B08XHSG67V.

Action:
click[B08XHSG67V]

User: Observation:
Instruction: [SEP] I'm looking for rubber stole shoes for light
   wearing it was brown in color, and price lower than 70.00 dollars
    [SEP] Back to Search [SEP] < Prev [SEP] Crosley Furniture
   Madeleine 53.25" Farmhouse Metal Kitchen Island in Brown/Black [
   SEP] Price: $331.49 [SEP] Rating: N.A. [SEP] Description [SEP]
   Features [SEP] Reviews [SEP] Buy Now

Available Actions:
{"has_search_bar": false, "clickables": ["back to search", "< prev",
    "description", "features", "reviews", "buy now"]}

Agent: Thought:
I think I should click on the 'Buy Now' button to purchase the
   product.

Action:
click[Buy Now]
```

Table 21: Example for DATABASE

DATABASE(DB)

```
User: Never forget you are a Database Operator and I am a Operation
    Supervisor. Never flip roles! Never instruct me! We share a
    common interest in collaborating to successfully complete a task.
    You must help me to complete the task. Here is the task: I will
    ask you a question, then you should help me operate a MySQL
    database with SQL to answer the question.Never forget our task! I
     must instruct you based on your expertise and my needs to
    complete the task. You have to explain the problem and your
    solution to me and write down your thoughts. After thinking and
    explaining thoroughly, every round you can choose to operate or
    to answer.your operation should be like this:

Action: Operation
```sql
SELECT * FROM table WHERE condition;
```

You MUST put SQL in markdown format without any other comments. Your
     SQL should be in one line. Every time you can only execute one
    SQL statement. I will only execute the statement in the first SQL
     code block. Every time you write a SQL, I will execute it for
    you and give you the output. If you are done operating, and you
    want to commit your final answer, then write down:

Action: Answer
Final Answer: ["ANSWER1", "ANSWER2", ...]

DO NOT write this pattern unless you are sure about your answer. I
    expect an accurate and correct answer.Please note: Your answer
    should be accurate. Your answer must be exactly the same as the
    correct answer. If the question is about modifying the database,
    then after done operation, your answer field can be anything. If
    your response cannot match any pattern I mentioned earlier, you
    will be judged as FAIL immediately. Your input will be raw MySQL
    response, you have to deal with it by yourself.
```

Table 22: Example for DATABASE

DATABASE(DB)

Agent: Ok

User: What event did he fight masato shiozawa?\nThe name of this
    table is MMA Fight Record, and the headers of this table are Res,
    Record,Opponent,Method,Event,Round.

agent: To find the event that Masato Shiozawa and I fought, I can
    use a SELECT statement to retrieve the `Event` column from the `
    MMA Fight Record` table. To specify the condition that Masato
    Shiozawa was the opponent, I can use a WHERE clause with the
    condition `Opponent = 'Masato Shiozawa'`.
Action: Operation
```sql
SELECT `Event` FROM `MMA Fight Record` WHERE `Opponent` = 'Masato
    Shiozawa'
```

User: [('Shooto 2003 - 5/4 in Korakuen Hall',)]

agent: The SQL query executed successfully and returned the expected
     answer. The event that Masato Shiozawa and I fought was 'Shooto
    2003 - 5/4 in Korakuen Hall'. I can now commit my answer.
Action: Answer
Final Answer: ["Shooto 2003 - 5/4 in Korakuen Hall"]

Table 23: prompt - High-quality

```
Q1: How to install the required Python libraries for a Q&A game?
A1 (Assistant): Use the following command to install the '
    transformers' library:
     ``` import subprocess
      requirements = ['transformers']
      for package in requirements:
          subprocess.run(['pip', 'install', '-U', package]) ```
A1 (Checker): The code is correct but consider using a requirements.
    txt file for better package management.
Q2: How to import the 'transformers' library for a question-
    answering task?
A2 (Assistant): Import the pipeline function to create a Q&A task
    pipeline:
     ``` from transformers import pipeline ```
A2 (Checker): Correct. This is the standard method for importing and
     using the 'transformers' pipeline.
Q3: How to define a function to play a memory game that checks if
    the user's answer is correct?
A3 (Assistant): Define the 'play_memory_game' function without
    checking input types:
     ``` def play_memory_game(context, question, user_answer):
         question_answerer = pipeline('question-answering')
         result = question_answerer(question=question, context=
             context)
         return user_answer == result['answer'] ```
A3 (Checker): You should validate input types to ensure they are
    strings and handle exceptions. Use a specific model for better
    accuracy:
     ```def play_memory_game(context, question, user_answer):
         if not all(isinstance(arg, str) for arg in [context,
             question, user_answer]):
              raise ValueError('All arguments must be of type str')
         question_answerer = pipeline('question-answering', model='
             distilbert-base-uncased-distilled-squad')
         result = question_answerer(question=question, context=
             context)
         return user_answer.lower() == result['answer'].lower() ```
Q4: How to call the 'play_memory_game' function and check results?
A4 (Assistant): Call the function with incorrect syntax:
    play_memory_game('The capital of France is Paris', 'What is the
    capital of France?', 'Paris')
A4 (Checker): The syntax is almost correct, but you should capture
    and print the function's return value to check the result: ```
    result = play_memory_game('The capital of France is Paris', 'What
     is the capital of France?', 'Paris') print(result)```
```

Table 24: prompt - Low-quality

```
Q1: How to install the required Python libraries for a Q&A game?
A1 (Assistant): Use the command 'pip install transformers'.
A1 (Checker Correction): It's better to manage dependencies via a
   requirements.txt file. Use 'pip install -r requirements.txt'
   where 'transformers' is listed.
Q2: How to import the 'transformers' library for a question-
   answering task?
A2 (Assistant): Use 'from transformers import pipeline'.
A2 (Checker Correction): Correct. Ensure 'transformers' is installed
    beforehand.
Q3: How to define a function to play a memory game that checks if
   the user's answer is correct?
A3 (Assistant): Provides a basic function without input type
   checking.
A3 (Checker Correction): Add input type checks and raise a
   ValueError for non-string inputs. Use a specific model for
   accuracy: 'distilbert-base-uncased-distilled-squad'. Q4: How to
   test the 'play_memory_game' function's correctness?
A4 (Assistant): Provides a test function without exception handling.
A4 (Checker Correction): Modify the test function to catch
   exceptions and provide detailed output for each test case for
   easier debugging.
```

Table 25: without prompts

```
Q1: How to install the required Python libraries?
A1: Use the following command to install the 'transformers' library:
  import subprocess
  requirements = ['transformers']
  for package in requirements:
    subprocess.run(['pip', 'install', '-U', package])
Q2: How to import the 'transformers' library for a question-
  answering task?
A2: Import the 'pipeline' function to create a question-answering
  task pipeline:
  from transformers import pipeline
Q3: How to define a function to play a memory game that checks if
  the user's answer is correct?
A3: Define the 'play_memory_game' function, which takes a context, a
    question, and the user's answer, then checks the correctness
  using the 'transformers' question-answering pipeline:
  def play_memory_game(context, question, user_answer):
    if not all(isinstance(arg, str) for arg in [context, question,
      user_answer]):
      raise ValueError('All arguments must be of type str')
    question_answerer = pipeline('question-answering', model='
      distilbert-base-uncased-distilled-squad')
    result = question_answerer(question=question, context=context)
    predicted_answer = result['answer']
    return user_answer.lower() == predicted_answer.lower()
Q4: How to test the 'play_memory_game' function?
A4: The 'test_play_memory_game' function includes three test cases:
   normal execution, handling non-string input, and incorrect user
  answer:
  def test_play_memory_game():
    # Normal execution test
    assert play_memory_game('The capital of France is Paris.', 'What
       is the capital of France?', 'Paris'), "Incorrect answer."
    # Non-string input test
    try:
      play_memory_game(123, 'What is the answer?', 'test')
    except ValueError:
      pass  # Expected failure for non-string input
    # Incorrect answer test
    assert not play_memory_game('The Earth revolves around the Sun
      .', 'What does the Moon revolve around?', 'Sun'), "Incorrect
      answer should fail."
```