Provably expressive temporal graph networks

Abstract

Temporal graph networks (TGNs) have gained prominence as models for embedding dynamic interactions, but little is known about their theoretical underpinnings. We establish fundamental results about the representational power and limits of the two main categories of TGNs: WA-TGNs that aggregate temporal walks, and MP-TGNs that augment local message passing with (recurrent) memory modules. Specifically, novel constructions reveal the inadequacy of MP-TGNs and WA-TGNs, proving that neither category subsumes the other. We extend the 1-WL (Weisfeiler-Leman) test to temporal graphs, and show that the most powerful MP-TGNs should use injective updates, as in this case they become as expressive as the temporal WL. Moreover, we elucidate that sufficiently deep MP-TGNs cannot benefit from memory, and MP-TGNs fail to compute graph properties such as girth.

These theoretical insights lead us to introduce PINT — a method provably more expressive than MP-TGN, WA-TGN, and temporal WL. Our experiments demonstrate that PINT outperforms existing TGNs on several real-world benchmarks.

1 Introduction

Graph neural networks (GNNs) [11, 30, 38] have recently led to breakthroughs in many applications [7, 28, 31] by resorting to message passing between neighboring nodes in input graphs. While message passing imposes an important inductive bias, it does not account for the dynamic nature of interactions in time-evolving graphs arising from many real-world domains such as social networks and bioinformatics [16, 39]. In several scenarios, these temporal graphs are only given as a sequence of timestamped events. Recently, temporal graph nets (TGNs) [16, 27, 32, 37, 41] have emerged as a prominent learning framework for temporal graphs and have become particularly popular due to their outstanding predictive performance. These models combine many building blocks, such as self-attention [33, 34], time encoders [15, 40], recurrent models [5, 13], and message passing [10]. Intuitively, these model components allow for capturing meaningful structural and temporal patterns.

Unraveling the learning capabilities of (temporal) graph networks is imperative to understanding their strengths and pitfalls, and designing better, more nuanced models that are both theoretically well-grounded and practically efficacious. For instance, the enhanced expressivity of higher-order GNNs has roots in the inadequacy of standard anonymous message-passing GNNs to separate graphs that are indistinguishable by the Weisfeiler-Leman isomorphism test, known as 1-WL test or color refinement algorithm [21, 22, 29, 36, 42].

Similarly, several other notable advances on GNNs have been made possible by untangling their ability to generalize [9, 17, 35], extrapolate [44], compute graph properties [4, 6, 9], and express Boolean node classifiers [1]; by uncovering their connections to distributed algorithms [19, 29], graph kernels [8], dynamic programming [43], diffusion processes [3], probabilistic graphical models [45], and combinatorial optimization [2]; and by analyzing their discriminative power [20, 23]. However, in stark contrast, the theoretical foundations of TGNs remain largely unexplored. For instance, unresolved questions include: *How does the expressive power of existing TGNs compare? When do TGNs fail? Can we improve the expressiveness of TGNs? What are the limits on the power of TGNs?*

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Overview of the theoretical results	
Relationship between CTDGs and DTDGs	Prop. 1
Injective MP-TGNs $\succeq$ MP-TGNs	Prop. 2
MP-TGNs with memory $\cong$ sufficiently deep MP-TGNs	Prop. 3
SOTA MP-TGNs $\prec$ Injective MP-TGNs	Prop. 4
MP-TGNs $\not\succ$ WA-TGNs and WA-TGNs $\not\succ$ MP-TGNs	Prop. 5
Injective MP-TGNs $\cong$ temporal-WL test	Prop. 6
MP-TGNs fail to recognize temporal graph properties	Prop. 7
Constructing injective temporal MP	Prop. 8
PINT (ours) $\succ$ both MP-TGNs and WA-TGNs	Prop. 9
Limitations of PINT	Prop. 10

Figure 1: Schematic diagram and summary of our contributions.

We establish a series of results to address these fundamental questions. We begin by showing that discrete-time dynamic graphs (DTDGs) can always be converted to continuous-time analogues (CTDGs) without loss of information (the converse holds under additional assumptions), so we can focus on analyzing the ability of TGNs to distinguish nodes/links of CTDGs. We consider a general framework for message-passing TGNs (MP-TGNs) [27] that subsumes a wide variety of methods [e.g., 16, 32, 41]. We prove that equipping MP-TGNs with injective aggregation and update functions leads to the class of most expressive anonymous TGNs. Extending the color-refinement algorithm to temporal settings, we show that these most powerful MP-TGNs are as expressive as the temporal WL method. Notably, existing MP-TGNs do not enforce injectivity and are strictly less expressive as we elucidate with novel constructions. Additionally, akin to GNNs [9], MP-TGNs cannot compute temporal graph properties such as diameter, girth, or number of cycles.

We also delineate the role of memory in MP-TGNs: nodes in a network with only a few layers of message passing fail to aggregate information from a sufficiently wide receptive field (i.e., from distant nodes), so memory serves to offset this highly local view with additional global information. In contrast, sufficiently deep architectures obviate the need for memory modules.

Different from MP-TGNs, walk-aggregating TGNs (WA-TGNs) such as CAW [37] obtain representations from anonymized temporal walks. We provide constructions that expose some shortcomings of each, establishing that WA-TGNs can distinguish links in cases where MP-TGNs fail and vice-versa. Consequently, neither class is more expressive than the other. Strikingly, our analysis unravels the subtle relationship between the walk computations in CAWs and the MP steps in MP-TGNs.

Equipped with these theoretical insights, we propose PINT (short for *position-encoding injective temporal graph net*), founded on a new temporal layer that leverages the strengths of both MP-TGNs and WA-TGNs. Like the most expressive MP-TGNs, PINT defines injective message passing and update steps. PINT also augments memory states with novel relative positional features, and these features can replicate all the discriminative benefits available to WA-TGNs. Interestingly, the time complexity of computing and communicating positional features can be considerably less than the related overheads in CAW, so PINT can often be trained faster than CAW. Importantly, we establish that PINT is provably more expressive than CAW as well as MP-TGNs.

Contributions. Our contributions are three-fold:

- a rigorous theoretical foundation for TGNs is laid - elucidating the role of memory, benefits of injective message passing, limits of existing TGN models, temporal extension of the 1-WL test and its implications, impossibility results about temporal graph properties, and the relationship between main classes of TGNs - as summarized in Figure 1,

- explicit injective temporal functions are introduced, and a novel method for temporal graphs is proposed that is provably more expressive than state-of-the-art TGNs,

- extensive empirical investigations underscore practical benefits of this work. The proposed method is either competitive or significantly better than existing models on several real benchmarks for dynamic link prediction, in transductive as well as inductive settings.

2 Preliminaries

We denote a *static graph* G as a tuple $(V, E, \mathcal{X}, \mathcal{E})$, where $V = \{1, 2, \ldots, n\}$ denotes the set of nodes and $E \subseteq V \times V$ the set of edges. Each node $u \in V$ has a feature vector $x_u \in \mathcal{X}$ and each edge $(u, v) \in E$ has a feature vector $e_{uv} \in \mathcal{E}$, where $\mathcal{X}$ and $\mathcal{E}$ are countable sets of features.

Dynamic graphs can be roughly split according to their discrete- or continuous-time nature [14]. A discrete-time dynamic graph (DTDG) is of a sequence of graph snapshots $(G_1, G_2, \ldots)$ usually sampled at regular intervals, each snapshot being a static graph $G_t = (V_t, E_t, \mathcal{X}_t, \mathcal{E}_t)$.

A *continuous-time dynamic graph* (CTDG) evolves with node- and edge-level *events*, such as addition and deletion. We represent a CTDG as a sequence of time-stamped graphs $(G(t_0), G(t_1), \ldots)$ such that $t_k < t_{k+1}$, and $G(t_{k+1})$ results from updating $G(t_k)$ with all events at time t_{k+1}. We assume no event occurs between t_k and t_{k+1}. We denote an interaction (i.e., edge addition event) between nodes u and v at time t as a tuple (u, v, t) associated with a feature vector $e_{uv}(t)$. Unless otherwise stated, interactions correspond to undirected edges, i.e., (u, v, t) is a shorthand for $(\{u, v\}, t)$.

Noting the CTDGs allow for finer (irregular) temporal resolution, we now formalize the intuition that DTDGs can be reduced to, and thus analyzed as CTDGs, but the converse does not always hold.

Proposition 1 (Relationship between DTDG and CTDG). *For any DTDG we can build a CTDG that contains the same information, i.e., we can reconstruct the original DTDG from the converted CTDG. The converse holds if the CTDG timestamps form a subset of a uniformly spaced countable set.*

Following the usual practice [16, 37, 41], we focus on CTDGs with edge addition events (see Appendix E for a discussion on deletion). Thus, we can represent temporal graphs as sets $\mathcal{G}(t) = \{(u_k, v_k, t_k) \mid t_k < t\}$. We also assume each distinct node v in $\mathcal{G}(t)$ has an initial feature vector x_v.

Message-passing temporal graph nets (MP-TGNs). Rossi et al. [27] introduced MP-TGN as a general representation learning framework for temporal graphs. The goal is to encode the graph dynamics into node embeddings, capturing information that is relevant for the task at hand. To achieve this, MP-TGNs rely on three main ingredients: memory, aggregation, and update. Memory comprises a set of vectors that summarizes the history of each node, and is updated using a recurrent model whenever an event occurs. The aggregation and update components resemble those in message-passing GNNs, where the embedding of each node is refined using messages from its neighbors.

We define the *temporal neighbohood* of node v at time t as $\mathcal{N}(v, t) = \{(u, e_{uv}(t'), t') \mid \exists (u, v, t') \in \mathcal{G}(t)\}$, i.e., the set of neighbor/feature/timestamp triplets from all interactions of node v prior to t. Also, let vector $s_v(t)$ denote the *state* of node v at time t. MP-TGNs compute the temporal representation $h_v^{(\ell)}(t)$ of v at layer ℓ by recursively applying

$$\tilde{h}_v^{(\ell)}(t) = \text{AGG}^{(\ell)}(\{\!\!\{ (h_u^{(\ell-1)}(t), t - t', e) \mid (u, e, t') \in \mathcal{N}(v, t) \}\!\!\}) \tag{1}$$

$$h_v^{(\ell)}(t) = \text{UPDATE}^{(\ell)}\left(h_v^{(\ell-1)}(t), \tilde{h}_v^{(\ell)}(t)\right), \tag{2}$$

where $\{\!\!\{\cdot\}\!\!\}$ denotes multisets, $h_v^{(0)}(t) = s_v(t)$, and $\text{AGG}^{(\ell)}$ and $\text{UPDATE}^{(\ell)}$ are arbitrary parameterized functions. The memory block updates the states as events occur. For instance, the event (u, v, t) begets updating nodes u and v. For ease of presentation, assume v interacts with only a single node u at t (see Appendix A.2 for a more general treatment). In this case, the state update of node v is

$$s_v(t) = \text{MEMORY}(s_v(t^-), s_u(t^-), t - t_v, e_{uv}(t)), \tag{3}$$

where $s_v(0) = x_v$ (initial node features), $s_v(t^-)$ denotes the state of v right before time t, and t_v denotes the time of the last update to v. The MEMORY function usually implements a gated recurrent unit (GRU) [5]. We note that some MP-TGNs do not use memory, or equivalently, they employ an *identity memory*, i.e., $s_v(t) = x_v$. We refer to Appendix A for further details.

Causal Anonymous Walks (CAWs). Wang et al. [37] proposed CAW as an effective approach for link prediction on temporal graphs. To predict if an event (u, v, t) occurs, CAW first obtains sets S_u and S_v of temporal walks starting at nodes u and v. An L-length *temporal walk* is represented as $W = ((w_1, t_1), (w_2, t_2), \ldots, (w_L, t_L))$, with $t_1 > t_2 > \cdots > t_L$ and $(w_{i-1}, w_i, t_i) \in \mathcal{G}(t)$ for all i. Then, CAW anonymizes walks replacing each node w with a set $I_{\text{CAW}}(w; S_u, S_v) = \{g(w; S_u), g(w; S_v)\}$ of two feature vectors. The ℓ-th entry of $g(w; S_u)$ stores how many times w appears at the ℓ-th position in a walk of S_u, i.e. $g(w, S_u)[\ell] = |\{W \in S_u : (w, t_\ell) = W_\ell\}|$ where W_ℓ is ℓ-th pair of W.

To encode a walk W with respect to the sets S_u and S_v, CAW applies $\text{ENC}(W; S_u, S_v) = \text{RNN}([f_1(I_{\text{CAW}}(w_i; S_u, S_v)) \| f_2(t_{i-1} - t_i)]_{i=1}^{L})$ where f_1 is a permutation-invariant function, f_2 is a time encoder, and $t_0 = t$. Finally, CAW combines the embeddings of each walk in $S_u \cup S_v$ using mean-pooling or self-attention to obtain the representation for the event (u, v, t).

In practice, TGNs often rely on sampling schemes for computational reasons. However we are concerned with the expressiveness of TGNs, so our analysis assumes complete structural information, i.e., S_u is the set of all temporal walks from u and MP-TGNs combine information from all neighbors.

3 The representational power and limits of TGNs

We now study the expressiveness of TGNs on node/edge-level prediction. We also establish connections to a variant of the WL test and show limits of specific TGN models. Proofs are in Appendix B.

3.1 Distinguishing nodes with MP-TGNs

We analyze MP-TGNs w.r.t. their ability to map different nodes to different locations in the embedding space. In particular, we say that an L-layer MP-TGN distinguishes two nodes u, v of a temporal graph at time t, if the last layer embeddings of u and v are different, i.e., $h_u^{(L)}(t) \neq h_v^{(L)}(t)$.

We can describe the MP computations of a node v at time t via its *temporal computation tree* (TCT) $T_v(t)$. $T_v(t)$ has v as its root and height equal to the number of TGN layers L. We will keep the dependence on depth L implicit for notational simplicity. For each element $(u, e, t') \in \mathcal{N}(v, t)$ associated with v, we have a node i_u in the next layer of the TCT linked to the root by an edge annotated with (e, t'). The remaining TCT layers are built recursively using the same mechanism. We denote by $\sharp_v$ the (possibly many-to-one) operator that maps nodes in $T_v(t)$ back to nodes in $\mathcal{G}(t)$, e.g., $\sharp_v i_u = u$. Each node i in $T_v(t)$ has a state vector $s_i = s_{\sharp_v i}(t)$. To get the embedding of the root v, information is propagated bottom-up, i.e., starting from the leaves all the way up to the root — each node aggregates the message from the layer below and updates its representation along the way.

We study the expressive power of MP-TGNs through the lens of functions on multisets adapted to temporal settings, i.e., comprising triplets of node states, edge features, and timestamps. Intuitively, injective functions 'preserve' the information as it is propagated, so should be essential for maximally expressive MP-TGNs. We formalize this idea in Lemma 1 and Proposition 2 via Definition 1.

Definition 1 (Isomorphic TCTs). *Two TCTs $T_z(t)$ and $T_{z'}(t)$ at time t are isomorphic if there is a bijection $f : V(T_z(t)) \to V(T_{z'}(t))$ between the nodes of the trees such that the following holds:*

$$(u, v, t') \in E(T_z(t)) \iff (f(u), f(v), t') \in E(T_{z'}(t))$$

$$\forall (u, v, t') \in E(T_z(t)) : e_{uv}(t') = e_{f(u)f(v)}(t') \text{ and } \forall u \in V(T_z(t)) : s_u = s_{f(u)} \text{ and } k_u = k_{f(u)}$$

Here, k_u denotes the level (depth) of node u in the tree. The root node has level 0, and for a node u with level k_u, the children of u have level $k_u + 1$.

Lemma 1. *If an MP-TGN Q with L layers distinguishes two nodes u, v of a dynamic graph $\mathcal{G}(t)$, then the L-depth TCTs $T_u(t)$ and $T_v(t)$ are not isomorphic.*

For non-isomorphic TCTs, Proposition 2 shows that improving MP-TGNs with *injective* message passing layers suffices to achieve node distinguishability, extending results from static GNNs [42].

Proposition 2 (Most expressive anonymous MP-TGNs). *If the L-depth TCTs of two nodes u, v of a temporal graph $\mathcal{G}(t)$ at time t are not isomorphic, then there exists an MP-TGN Q with L layers and injective aggregation and update functions at each layer that is able to distinguish nodes u and v.*

So far, we have considered TCTs with general memory modules, i.e., nodes are annotated with memory states. However, an important question remains: *How does the expressive power of MP-TGNs change as a function of the memory?* Our next result - Proposition 3 - shows that adding GRU-based memory does not increase the expressiveness of suitably deep MP-TGNs.

Proposition 3 (The role of memory). *Let $\mathcal{Q}_L^{[M]}$ denote the class of MP-TGNs with recurrent memory and L layers. Similarly, we denote by $\mathcal{Q}_L$ the family of memoryless MP-TGNs with L layers. Let Δ be the temporal diameter of $\mathcal{G}(t)$ (see Definition B1). Then, it holds that:*

    1. If $L < \Delta$: $\mathcal{Q}_L^{[M]}$ is strictly more powerful than $\mathcal{Q}_L$ in distinguishing nodes of $\mathcal{G}(t)$;

    2. For any L : $\mathcal{Q}_{L+\Delta}$ is at least as powerful as $\mathcal{Q}_L^{[M]}$ in distinguishing nodes of $\mathcal{G}(t)$.

Figure 2: **Limitations of TGNs**. [*Left*] Temporal graph with nodes u, v that TGN-Att/TGAT cannot distinguish. Colors are node features, edge features are identical, and $t_3 > t_2 > t_1$. [*Center*] TCTs of u and v are non-isomorphic. However, the attention layers of TGAT/TGN-Att compute weighted averages over a same multiset of values, returning identical messages for u and v. [*Right*] MP-TGNs fail to distinguish the events (u, v, t_3) and (u, z, t_3) as TCTs of z and u are isomorphic. Meanwhile, CAW cannot separate (v, z, t_3) and (u', z, t_3): the 3-depth TCTs of u and u' are not isomorphic, but the temporal walks from u and u' have length 1, keeping CAW from capturing structural differences.

174 The MP-TGN framework is rather general and subsumes many modern methods for temporal graphs
175 [e.g., 16, 32, 41]. We now analyze the theoretical limitations of two concrete instances of MP-TGNs:
176 TGAT [41] and TGN-Att [27]. Remarkably, these models are among the best-performing MP-TGNs.
177 Nonetheless, we can show that there are nodes of very simple temporal graphs that TGAT and
178 TGN-Att cannot distinguish (see Figure 2). We formalize this in Proposition 4 by establishing that
179 there are cases in which TGNs with injective layers can succeed, but TGAT and TGN-Att cannot.

180 **Proposition 4** (Limitations of TGAT/TGN-Att). *There exist temporal graphs containing nodes u, v*
181 *that have non-isomorphic TCTs, yet no TGAT nor TGN-Att can distinguish u and v.*

182 This limitation stems from the fact that the attention mechanism employed by TGAT and TGN-Att is
183 proportion invariant [26]. The memory module of TGN-Att cannot counteract this limitation due to
184 its mean-based message aggregation scheme. We provide more details in Appendix B.6.

3.2 Predicting temporal links

186 Models for dynamic graphs are usually trained and evaluated on temporal link prediction [18], which
187 consists in predicting whether an event would occur at a given time. To predict an event between
188 nodes u and v at t, MP-TGNs combine the node embeddings $h_u^{(L)}(t)$ and $h_v^{(L)}(t)$, and evaluate the
189 resulting vector using an MLP. On the other hand, CAW is originally designed for link prediction
190 tasks and directly computes edge embeddings, bypassing the computation of node representations.

191 We can extend the notion of node distinguishability to edges/events. We say that a model distinguishes
192 two synchronous events $\gamma = (u, v, t)$ and $\gamma' = (u', v', t)$ of a temporal graph if it assigns different
193 edge embeddings $h_\gamma \neq h_{\gamma'}$ for γ and γ'. The next result - Proposition 5 - asserts that CAWs are
194 not strictly more expressive than MP-TGNs, and vice-versa. Intuitively, CAW's advantage over
195 MP-TGNs lies in its ability to exploit node identities and capture correlation between walks. However,
196 CAW imposes temporal constraints on random walks, i.e., walks have timestamps in decreasing
197 order, which can limit its ability to distinguish events. Figure 2(Right) sketches constructions for
198 Proposition 5.

199 **Proposition 5** (Limitations of MP-TGNs and CAW). *There exist distinct synchronous events of a*
200 *temporal graph that CAW can distinguish but MP-TGNs with injective layers cannot, and vice-versa.*

3.3 Connections with the WL test

202 The Weisfeiler-Leman test (1-WL) has been used as a key tool to analyze the expressive power of
203 GNNs. We now study the power of MP-TGNs under a temporally-extended version of 1-WL, and
204 prove negative results regarding whether MP-TGN's can recognize properties of temporal graphs.

Temporal WL test. We can extend the WL test for temporal settings in a straightforward manner
206 by exploiting the equivalence between temporal graphs and multi-graphs with timestamped edges
207 [24]. In particular, the temporal variant of 1-WL assigns colors for all nodes in an input dynamic
208 graph $\mathcal{G}(t)$ by applying the following iterative procedure:

209 *Initialization*: The colors of all nodes in $\mathcal{G}(t)$ are initialized using the initial node features: $\forall v \in$
210 $V(\mathcal{G}(t)), c^0(v) = x_v$. If node features are not available, all nodes receive identical colors;
211 *Refinement*: At step ℓ, the colors of all nodes are refined using a hash (injective) function: for all
212 $v \in V(\mathcal{G}(t))$, we apply $c^{\ell+1}(v) = \text{HASH}(c^\ell(v), \{\!\{(c^\ell(u), e_{uv}(t'), t') : (u, v, t') \in \mathcal{G}(t)\}\!\})$;

213   *Termination*:   The test is carried out for two temporal graphs at time t in parallel and stops when
214   the multisets of corresponding colors diverge, returning non-isomorphic. If the algorithm
215   runs until the number of different colors stops increasing, the test is deemed inconclusive.

216   We note that the temporal WL test trivially reduces to the standard 1-WL test if all timestamps and
217   edge features are identical. The resemblance between MP-TGNs and GNNs and their corresponding
218   WL tests suggests that the power of MP-TGNs is bounded by the temporal WL test. Proposition 6
219   conveys that MP-TGNs with injective layers are as powerful as the temporal WL test.

220   **Proposition 6.** *Assume finite spaces of initial node features $\mathcal{X}$, edge features $\mathcal{E}$, and timestamps $\mathcal{T}$.*
221   *Let the number of events of any temporal graph be bounded by a fixed constant. Then, there is an*
222   *MP-TGN with suitable parameters using injective aggregation/update functions that outputs different*
223   *representations for two temporal graphs if and only if the temporal-WL test outputs 'non-isomorphic'.*

224   A natural consequence of the limited power of MP-TGNs is that even the most powerful anonymous
225   MP-TGNs fail to distinguish relevant graph properties (see Proposition 7). Again, this not only
226   exposes some limitations of MP-TGNs but also extends previous findings on static GNNs to TGNs.

227   **Proposition 7.** *There exist non-isomorphic temporal graphs differing in properties such as diameter,*
228   *girth, and total number of cycles, which cannot be differentiated by MP-TGNs of any depth.*

229   Figure 3 provides a construction for Proposition 7.
230   The temporal graphs $\mathcal{G}(t)$ and $\mathcal{G}'(t)$ differ in diameter
231   (∞ vs. 3), girth (3 vs. 6), and number of cycles (2
232   vs. 1). By inspecting the TCTs, one can observe that,
233   for any node in $\mathcal{G}(t)$, there is a corresponding one
234   in $\mathcal{G}'(t)$ whose TCTs are isomorphic, e.g., $T_{u_1}(t) \cong$
235   $T_{u'_1}(t)$ for $t > t_3$. As a result, the multisets of node
236   embeddings for these temporal graphs are identical.

Figure 3: Examples of temporal graphs for which MP-TGNs cannot distinguish the diameter, girth, and number of cycles.

4   Position-encoding injective temporal graph net

237   We now leverage insights from our analysis in Section 3 to build more powerful TGNs. First, we
238   discuss how to build injective aggregation and update functions in the temporal setting. Second, we
239   propose an efficient scheme to compute positional features based on counts from TCTs. In addition,
240   we show that the proposed method, called ***position-encoding injective temporal graph net*** (PINT), is
241   more powerful than both WA-TGNs and MP-TGNs in distinguishing events in temporal graphs.

242   **Injective temporal aggregation.** An important design principle in TGNs is to prioritize (give higher
243   importance to) events based on recency [37, 41]. Proposition 8 introduces an injective aggregation
244   scheme that captures this principle employing a linearly exponential time decay.

245   **Proposition 8** (Injective function on temporal neighborhood)**.** *Let $\mathcal{X}$ and $\mathcal{E}$ be countable, and $\mathcal{T}$*
246   *countable and bounded. There exists a function f and scalars α and β such that $\sum_i f(x_i, e_i)\alpha^{-\beta t_i}$*
247   *is unique on any multiset $M = \{\!\{(x_i, e_i, t_i)\}\!\} \subseteq \mathcal{X} \times \mathcal{E} \times \mathcal{T}$ with $|M| < N$, where N is a constant.*

249   Leveraging Proposition 8 and the approximation capabilities of multi-layer perceptrons (MLPs), we
250   propose *position-encoding injective temporal graph net* (PINT). In particular, PINT computes the
251   embedding of node v at time t and layer ℓ using the following message passing steps:

$$\tilde{h}_v^{(\ell)}(t) = \sum_{(u,e,t') \in \mathcal{N}(v,t)} \text{MLP}_{\text{agg}}^{(\ell)}\left(h_u^{(\ell-1)}(t) \parallel e\right) \alpha^{-\frac{\beta(t-t')}{\sqrt{|\mathcal{N}(v,t)|}}} \tag{4}$$

$$h_v^{(\ell)}(t) = \text{MLP}_{\text{upd}}^{(\ell)}\left(h_v^{(\ell-1)}(t) \parallel \tilde{h}_v^{(\ell)}(t)\right) \tag{5}$$

252   where $\parallel$ denotes concatenation, $h_v^{(0)} = s_v(t)$, α and β are scalar (hyper-)parameters, and $\text{MLP}_{\text{agg}}^{(\ell)}$
253   and $\text{MLP}_{\text{upd}}^{(\ell)}$ denote the nonlinear transformations of the aggregation and update steps, respectively.

254   We note that to guarantee that the MLPs in PINT implement injective aggregation/update, we must
255   further assume that the edge and node features (states) take values from some finite support. In
256   addition, we highlight that there may exist many other ways to achieve injective temporal MP - we
257   have presented a solution that captures the 'recency' inductive bias of real-world temporal networks.

Figure 4: **PINT.** Following the MP-TGN protocol, PINT updates memory states as events unroll. Meanwhile, we use Eqs. (6-10) to update positional features. To extract the embedding for node v, we build its TCT, annotate nodes with memory + positional features, and run (injective) MP.

Relative positional features. To boost the power of PINT, we propose augmenting memory states with *relative* positional features. These features count how many temporal walks of a given length exist between two nodes, or equivalently, how many times nodes appear at different levels of TCTs.

Formally, let P be the $d \times d$ matrix obtained by padding a $(d-1)$-dimensional identity matrix with zeros on its top row and its rightmost column. Also, let $r_{j \to u}^{(t)} \in \mathbb{N}^d$ denote the positional feature vector of node j relative to u's TCT at time t. For each event (u, v, t), with u and v not participating in other events at t, we recursively update the positional feature vectors as

$$\mathcal{V}_i^{(0)} = \{i\} \quad \forall i \tag{6}$$

$$\mathcal{V}_u^{(t)} = \mathcal{V}_v^{(t)} = \mathcal{V}_v^{(t^-)} \cup \mathcal{V}_u^{(t^-)} \tag{8}$$

$$r_{i \to j}^{(0)} = \begin{cases} [1, 0, \ldots, 0]^\top & \text{if } i = j \\ [0, 0, \ldots, 0]^\top & \text{if } i \neq j \end{cases} \tag{7}$$

$$r_{i \to v}^{(t)} = Pr_{i \to u}^{(t^-)} + r_{i \to v}^{(t^-)} \quad \forall i \in \mathcal{V}_u^{(t^-)} \tag{9}$$

$$r_{j \to u}^{(t)} = Pr_{j \to v}^{(t^-)} + r_{j \to u}^{(t^-)} \quad \forall j \in \mathcal{V}_v^{(t^-)} \tag{10}$$

where we use t^- to denote values "right before" t. The set $\mathcal{V}_i$ keeps track of the nodes for which we need to update positional features when i participates in an interaction. For simplicity, we have assumed that there are no other events involving u or v at time t. Appendix B.9 provides equations for the general case where nodes can participate in multiple events at the same timestamp.

The value $r_{i \to v}^{(t)}[k]$ (the k-th component of $r_{i \to v}^{(t)}$) corresponds to how many different ways we can get from v to i in k steps through temporal walks. Additionally, we provide in Lemma 2 an interpretation of relative positional features in terms of the so-called monotone TCTs (Definition 2).

Definition 2. *The monotone TCT of a node u at time t, denoted by $\tilde{T}_u(t)$, is the maximal subtree of the TCT of u s.t. for any path $p = (u, t_1, u_1, t_2, u_2, \ldots)$ from the root u to leaf nodes of $\tilde{T}_u(t)$ time monotonically decreases with respect to time, i.e., we have that $t_1 > t_2 > \ldots$.*

Lemma 2. *For any pair of nodes i, u of a temporal graph $\mathcal{G}(t)$, the k-th component of the positional feature vector $r_{i \to u}^{(t)}$ stores the number of times i appears at the k-th layer of the monotone TCT of u.*

Edge and node embeddings. To obtain the embedding h_γ for an event $\gamma = (u, v, t)$, an L-layer PINT computes embeddings for node u and v using L steps of temporal message passing. However, when computing the embedding $h_u^L(t)$ of u, we concatenate node states $s_j(t)$ with the positional features $r_{j \to u}^{(t)}$ and $r_{j \to v}^{(t)}$ for all node j in the L-hop temporal neighborhood of u. We apply the same procedure to obtain $h_v^L(t)$, and then combine $h_v^L(t)$ and $h_u^L(t)$ using a readout function.

Similarly, to compute representations for node-level prediction, for each node j in the L-hop neighborhood of u, we concatenate node states $s_j(t)$ with features $r_{j \to u}^{(t)}$. Then, we use our injective MP to combine the information stored in u and its neighboring nodes. Figure 4 illustrates the process.

Notably, Proposition 9 states that PINT is strictly more powerful than existing TGNs. In fact, the relative positional features mimic the discriminative power of WA-TGNs, while eliminate their temporal monotonicity constraints. Additionally, PINT can implement injective temporal message passing, achieving maximally-expressive MP-TGNs.

Proposition 9 (Expressiveness of PINT: link prediction). *PINT (with relative positional features) is strictly more powerful than both MP-TGNs and CAW in distinguishing events in temporal graphs.*

When does PINT fail?   Naturally, whenever the TCTs (annotated with positional features) for the endpoints of two edges (u, v, t) and (u', v', t) are pairwise isomorphic, PINT returns the same edge embedding and is not able to differentiate the events. Figure 5 shows an example in which this happens — we assume that all node/edge features are identical. Due to graph symmetries, u and z occur the same number of times in each level of v's monotone TCT. Also, the sets of temporal walks starting at u and z are identical if we swap the labels of these nodes. Importantly, CAWs and MP-TGNs also fail here, as stated in Proposition 9.

Figure 5: PINT cannot distinguish the events (u, v, t_3) and (v, z, t_3).

Proposition 10 (Limitations of PINT). *There are synchronous events of temporal graphs that PINT cannot distinguish (as seen in Figure 5).*

Implementation and computational cost.   The online updates for PINT's positional features have complexity $\mathcal{O}\left(d\,|\mathcal{V}_u^{(t^-)}| + d\,|\mathcal{V}_v^{(t^-)}|\right)$. Similarly to CAW's sampling procedure, our online update is a sequential process better done in CPUs. However, while CAW may require significant CPU-GPU memory exchange — proportional to both the number of walks and their depth —, we only communicate the positional features. We can also speed-up the training of PINT by pre-computing the positional features for each batch, avoiding redundant computations at each epoch. Apart from positional features, the computational cost of PINT is similar to that of TGN-Att. Following standard MP-TGN procedure, we control the branching factor of TCTs using neighborhood sampling.

Note that the positional features monotonically increase with time, which is undesirable for practical generalization purposes. Since our theoretical results hold for any fixed t, this issue can be solved by dividing the positional features by a time-dependent normalization factor. Nonetheless, we have found that employing L_1-normalization leads to good empirical results for all evaluated datasets.

5   Experiments

We now assess the performance of PINT on several popular and large-scale benchmarks for TGNs. We have implemented experiments using PyTorch [25] and code is available as additional material.

Tasks and datasets.   We evaluate PINT on dynamic link prediction, closely following the evaluation setup employed by Rossi et al. [27] and Xu et al. [41]. We use six popular benchmark datasets: Reddit, Wikipedia, Twitter, UCI, Enron, and LastFM [16, 27, 37, 41]. Notably, UCI, Enron, and LastFM are non-attributed networks, i.e., they do not contain feature vectors associated with the events. Node features are absent in all datasets, thus following previous works we set them to vectors of zeros [27, 41]. Since Twitter is not publicly available, we follow the guidelines by Rossi et al. [27] to create our version. We provide more details regarding datasets in the supplementary material.

Baselines.   We compare PINT against five prominent TGNs: Jodie [16], DyRep [32], TGAT [41], TGN-Att [27], and CAW [37]. For completeness, we also report results using two static GNNs: GAT [34] and GraphSage [12]. Since we adopt the same setup as TGN-Att, we use their table numbers for all baselines but CAW on Wikipedia and Reddit. The remaining results were obtained using the implementations and guidelines available from the official repositories. As an ablation study, we also include a version of PINT without relative positional features in the comparison. We provide detailed information about hyperparameters and the training of each model in the supplementary material.

Experimental setup.   We follow Xu et al. [41] and use a 70%-15%-15% (train-val-test) temporal split for all datasets. We adopt average precision (AP) as the performance metric. We also analyze separately predictions involving only nodes seen during training (transductive), and those involving novel nodes (inductive). We report mean and standard deviation of the AP over ten runs. For further details, see Appendix D. We provide additional results in the supplementary material.

Results.   Table 1 shows that PINT is the best-performing method on five out of six datasets for the transductive setting. Notably, the performance gap between PINT and TGN-Att amounts to over 15% AP on UCI. The gap is also relatively high compared to CAW on LastFM, Enron, and UCI; with CAW being the best model only on Enron. We also observe that many models achieve relatively high AP on the attributed networks (Reddit, Wikipedia, and Twitter). This aligns well with findings

Table 1: **Average Precision** (AP) results for link prediction. We denote the best-performing model (highest mean AP) in **blue**. In 5 out of 6 datasets, PINT achieves the highest AP in the transductive setting. For the inductive case, PINT outperforms previous MP-TGNs and competes with CAW. We also show the performance of PINT with and without relative positional features. For all datasets, adopting positional features leads to significant performance gains.

	Model	Reddit	Wikipedia	Twitter	UCI	Enron	LastFM
Transductive	GAT	97.33 ± 0.2	94.73 ± 0.2	-	-	-	-
	GraphSAGE	97.65 ± 0.2	93.56 ± 0.3	-	-	-	-
	Jodie	97.11 ± 0.3	94.62 ± 0.5	98.23 ± 0.1	86.73 ± 1.0	77.31 ± 4.2	69.32 ± 1.0
	DyRep	97.98 ± 0.1	94.59 ± 0.2	98.48 ± 0.1	54.60 ± 3.1	77.68 ± 1.6	69.24 ± 1.4
	TGAT	98.12 ± 0.2	95.34 ± 0.1	98.70 ± 0.1	77.51 ± 0.7	68.02 ± 0.1	54.77 ± 0.4
	TGN-Att	98.70 ± 0.1	98.46 ± 0.1	98.00 ± 0.1	80.40 ± 1.4	79.91 ± 1.3	80.69 ± 0.2
	CAW	98.39 ± 0.1	98.63 ± 0.1	98.72 ± 0.1	92.16 ± 0.1	$\textbf{92.09} \pm \textbf{0.7}$	81.29 ± 0.1
	PINT (w/o pos. feat.)	$98.62 \pm .04$	$98.43 \pm .04$	98.53 ± 0.1	92.68 ± 0.5	83.06 ± 2.1	81.35 ± 1.6
	PINT	$\textbf{99.03} \pm \textbf{.01}$	$\textbf{98.78} \pm \textbf{0.1}$	$\textbf{99.35} \pm \textbf{.01}$	$\textbf{96.01} \pm \textbf{0.1}$	88.71 ± 1.3	$\textbf{88.06} \pm \textbf{0.7}$
Inductive	GAT	95.37 ± 0.3	91.27 ± 0.4	-	-	-	-
	GraphSAGE	96.27 ± 0.2	91.09 ± 0.3	-	-	-	-
	Jodie	94.36 ± 1.1	93.11 ± 0.4	96.06 ± 0.1	75.26 ± 1.7	76.48 ± 3.5	80.32 ± 1.4
	DyRep	95.68 ± 0.2	92.05 ± 0.3	96.33 ± 0.2	50.96 ± 1.9	66.97 ± 3.8	82.03 ± 0.6
	TGAT	96.62 ± 0.3	93.99 ± 0.3	96.33 ± 0.1	70.54 ± 0.5	63.70 ± 0.2	56.76 ± 0.9
	TGN-Att	97.55 ± 0.1	97.81 ± 0.1	95.76 ± 0.1	74.70 ± 0.9	78.96 ± 0.5	84.66 ± 0.1
	CAW	97.81 ± 0.1	$\textbf{98.52} \pm \textbf{0.1}$	$\textbf{98.54} \pm \textbf{0.4}$	92.56 ± 0.1	$\textbf{91.74} \pm \textbf{1.7}$	85.67 ± 0.5
	PINT (w/o pos. feat.)	97.22 ± 0.2	97.81 ± 0.1	96.10 ± 0.1	90.25 ± 0.3	75.99 ± 2.3	88.44 ± 1.1
	PINT	$\textbf{98.25} \pm \textbf{.04}$	$98.38 \pm .04$	$98.20 \pm .03$	$\textbf{93.97} \pm \textbf{0.1}$	81.05 ± 2.4	$\textbf{91.76} \pm \textbf{0.7}$

from [37], where TGN-Att was shown to have competitive performance against CAW on Wikipedia and Reddit. The performance of GAT and TGAT (static GNNs) on Reddit and Wikipedia reinforces the hypothesis that the edge features add significantly to the discriminative power. On the other hand, PINT and CAW, which leverage relative identities, show superior performance relative to other methods when only time and degree information is available, i.e., on unattributed networks (UCI, Enron, and LastFM). Table 1 also shows the effect of using relative positional features. Our ablation study shows that while PINT outperforms other MP-TGNs even without positional features, adding these features boosts performance systematically. In the inductive case, we observe a similar behavior. Overall, PINT is consistently the best MP-TGN, and is better than CAW on 3/6 datasets.

Time comparison. Figure 6 compares the training times of PINT against other TGNs. For fairness, we use the same architecture (number of layers & neighbors) for all MP-TGNs: i.e., the best-performing PINT. For CAW, we use the one that yielded results in Table 1. As expected, TGAT is the fastest model. Note that the average time/epoch of PINT gets amortized since positional features are pre-computed. Without these features, PINT's runtime closely matches TGN-Att. When trained for over 25 epochs, PINT runs considerably faster than CAW. More details and results are provided in the Appendix.

Figure 6: Time comparison: PINT versus TGNs (in log-scale). The cost of pre-computing positional features is quickly diluted as the number of epochs increases.

6 Conclusion

We laid a rigorous theoretical foundation for TGNs, including the role of memory modules, relationship between classes of TGNs, and failure cases for MP-TGNs. Together, our theoretical results shed light on the representational capabilities of TGNs, and connections with their static counterparts. We also introduced a novel TGN method, provably more expressive than existing TGNs.

Key practical takeaways from this work: (a) temporal models should be designed to have injective update rules and to exploit both neighborhood and walk aggregation, and (b) deep architectures can likely be made more compute-friendly as the role of memory gets diminished with depth, provably.

References

[1] P. Barceló, E. V. Kostylev, M. Monet, J. Pérez, J. L. Reutter, and J.-P. Silva. The logical expressiveness of graph neural networks. In *International Conference on Learning Representations (ICLR)*, 2020.

[2] Q. Cappart, D. Chételat, E. B. Khalil, A. Lodi, C. Morris, and P. Velickovic. Combinatorial optimization and reasoning with graph neural networks. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2021.

[3] B. Chamberlain, J. Rowbottom, M. Gorinova, M. M. Bronstein, S. Webb, and E. Rossi. GRAND: graph neural diffusion. In *International Conference on Machine Learning (ICML)*, 2021.

[4] M. Chen, Z. Wei, Z. Huang, B. Ding, and Y. Li. Simple and deep graph convolutional networks. In *International Conference on Machine Learning (ICML)*, 2020.

[5] K. Cho, B. van Merriënboer, C. Gulcehre, D. Bahdanau, F. Bougares, H. Schwenk, and Y. Bengio. Learning phrase representations using RNN encoder–decoder for statistical machine translation. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2014.

[6] N. Dehmamy, A.-L. Barabási, and R. Yu. Understanding the representation power of graph neural networks in learning graph topology. In *Advances in neural information processing systems (NeurIPS)*, 2019.

[7] A. Derrow-Pinion, J. She, D. Wong, O. Lange, T. Hester, L. Perez, M. Nunkesser, S. Lee, X. Guo, B. Wiltshire, P. W. Battaglia, V. Gupta, A. Li, Z. Xu, A. Sanchez-Gonzalez, Y. Li, and P. Velickovic. Eta prediction with graph neural networks in google maps. In *Conference on Information and Knowledge Management (CIKM)*, 2021.

[8] Simon S. Du, Kangcheng Hou, Ruslan Salakhutdinov, Barnabás Póczos, Ruosong Wang, and Keyulu Xu. Graph neural tangent kernel: Fusing graph neural networks with graph kernels. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[9] V. Garg, S. Jegelka, and T. Jaakkola. Generalization and representational limits of graph neural networks. In *International Conference on Machine Learning (ICML)*, 2020.

[10] J. Gilmer, S. S. Schoenholz, P. F. Riley, O. Vinyals, and G. E. Dahl. Neural message passing for quantum chemistry. In *International Conference on Machine Learning (ICML)*, 2017.

[11] M. Gori, G. Monfardini, and F. Scarselli. A new model for learning in graph domains. In *IEEE International Joint Conference on Neural Networks (IJCNN)*, 2005.

[12] W. Hamilton, Z. Ying, and J. Leskovec. Inductive representation learning on large graphs. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

[13] S. Hochreiter and J. Schmidhuber. Long short-term memory. *Neural Computation*, 9(8):1735–1780, 1997.

[14] S. Kazemi, R. Goel, K. Jain, I. Kobyzev, A. Sethi, P. Forsyth, and P. Poupart. Representation learning for dynamic graphs: A survey. *Journal of Machine Learning Research*, 21(70):1–73, 2020.

[15] S. M. Kazemi, R. Goel, S. Eghbali, J. Ramanan, J. Sahota, S. Thakur, S. Wu, C. Smyth, P. Poupart, and M. Brubaker. Time2vec: Learning a vector representation of time. *ArXiv: 1907.05321*, 2019.

[16] S. Kumar, X. Zhang, and J. Leskovec. Predicting dynamic embedding trajectory in temporal interaction networks. In *International Conference on Knowledge Discovery & Data Mining (KDD)*, 2019.

[17] Renjie Liao, Raquel Urtasun, and Richard Zemel. A PAC-bayesian approach to generalization bounds for graph neural networks. In *International Conference on Learning Representations (ICLR)*, 2021.

[18] D. Liben-Nowell and J. Kleinberg. The link prediction problem for social networks. *Journal of the American Society for Information Science and Technology*, 58(7):1019–1031, 2007.

[19] A. Loukas. What graph neural networks cannot learn: depth vs width. In *International Conference on Learning Representations (ICLR)*, 2020.

[20] Andreas Loukas. How hard is to distinguish graphs with graph neural networks? In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[21] H. Maron, H. Ben-Hamu, H. Serviansky, and Y. Lipman. Provably powerful graph networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[22] C. Morris, M. Ritzert, M. Fey, W. L. Hamilton, J. E. Lenssen, G. Rattan, and M. Grohe. Weisfeiler and leman go neural: Higher-order graph neural networks. In *AAAI Conference on Artificial Intelligence (AAAI)*, 2019.

[23] H. Nguyen and T. Maehara. Graph homomorphism convolution. In *International Conference on Machine Learning (ICML)*, 2020.

[24] F. Orsini, P. Frasconi, and L. D. Raedt. Graph invariant kernels. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2015.

[25] A. Paszke, S. Gross, S. Chintala, G. Chanan, E. Yang, Z. DeVito, Z. Lin, A. Desmaison, L. Antiga, and A. Lerer. Automatic differentiation in pytorch. In *Advances in Neural Information Processing Systems (NeurIPS - Workshop)*, 2017.

[26] Jorge Pérez, Javier Marinković, and Pablo Barceló. On the turing completeness of modern neural network architectures. In *International Conference on Learning Representations (ICLR)*, 2019.

[27] Emanuele Rossi, Ben Chamberlain, Fabrizio Frasca, Davide Eynard, Federico Monti, and Michael Bronstein. Temporal graph networks for deep learning on dynamic graphs. In *ICML 2020 Workshop on Graph Representation Learning*, 2020.

[28] A. Sanchez-Gonzalez, J. Godwin, T. Pfaff, R. Ying, J. Leskovec, and P. Battaglia. Learning to simulate complex physics with graph networks. In *International Conference on Machine Learning (ICML)*, 2020.

[29] R. Sato, M. Yamada, and H. Kashima. Approximation ratios of graph neural networks for combinatorial problems. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[30] F. Scarselli, M. Gori, A. C. Tsoi, M. Hagenbuchner, and G. Monfardini. The graph neural network model. *IEEE Transactions on Neural Networks*, 20(1):61–80, 2009.

[31] J. M. Stokes, K. Yang, K. Swanson, W. Jin, A. Cubillos-Ruiz, N. M. Donghia, C. R. MacNair, S. French, L. A. Carfrae, Z. Bloom-Ackermann, V. M. Tran, A. Chiappino-Pepe, A. H. Badran, I. W. Andrews, E. J. Chory, G. M. Church, E. D. Brown, T. S. Jaakkola, R. Barzilay, and J. J. Collins. A deep learning approach to antibiotic discovery. *Cell*, 180(4):688 – 702, 2020.

[32] R. Trivedi, M. Farajtabar, P. Biswal, and H. Zha. DyRep: Learning representations over dynamic graphs. In *International Conference on Learning Representations (ICLR)*, 2019.

[33] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

[34] Petar Velickovic, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph Attention Networks. In *International Conference on Learning Representations (ICLR)*, 2018.

[35] S. Verma and Z.-L. Zhang. Stability and generalization of graph convolutional neural networks. In *International Conference on Knowledge Discovery & Data Mining (KDD)*, 2019.

[36] C. Vignac, A. Loukas, and P. Frossard. Building powerful and equivariant graph neural networks with structural message-passing. In *Neural Information Processing Systems (NeurIPS)*, 2020.

[37] Y. Wang, Y. Chang, Y. Liu, J. Leskovec, and P. Li. Inductive representation learning in temporal networks via causal anonymous walks. In *International Conference on Learning Representations (ICLR)*, 2021.

[38] Z. Wu, S. Pan, F. Chen, G. Long, C. Zhang, and P. S. Yu. A comprehensive survey on graph neural networks. *IEEE Transactions on Neural Networks and Learning Systems*, pages 1–21, 2020.

[39] D. Xu, W. Cheng, D. Luo, Y. Gu, X. Liu, J. Ni, B. Zong, H. Chen, and X. Zhang. Adaptive neural network for node classification in dynamic networks. In *IEEE International Conference on Data Mining (ICDM)*, 2019.

[40] D. Xu, C. Ruan, E. Korpeoglu, S. Kumar, and K. Achan. Self-attention with functional time representation learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[41] D. Xu, C. Ruan, E. Korpeoglu, S. Kumar, and K. Achan. Inductive representation learning on temporal graphs. In *International Conference on Learning Representations (ICLR)*, 2020.

[42] K. Xu, W. Hu, J. Leskovec, and S. Jegelka. How powerful are graph neural networks? In *International Conference on Learning Representations (ICLR)*, 2019.

[43] K. Xu, J. Li, M. Zhang, S. S. Du, K.-I. Kawarabayashi, and S. Jegelka. What can neural networks reason about? In *International Conference on Learning Representations (ICLR)*, 2020.

[44] K. Xu, M. Zhang, J. Li, S. S. Du, K.-I. Kawarabayashi, and S. Jegelka. How neural networks extrapolate: From feedforward to graph neural networks. In *International Conference on Learning Representations (ICLR)*, 2021.

[45] Z. Zhang, F. Wu, and W. S. Lee. Factor graph neural networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.