DOUBLE Q-LEARNING: NEW ANALYSIS AND SHARPER FINITE-TIME BOUND

ABSTRACT

Double Q-learning (Hasselt, 2010) has gained significant success in practice due to its effectiveness in overcoming the overestimation issue of Q-learning. However, theoretical understanding of double Q-learning is rather limited and the only existing finite-time analysis was recently established in Xiong et al. (2020) under a polynomial learning rate. This paper analyzes the more challenging case with a rescaled linear learning rate for which the previous method does not appear to be applicable. We develop new analytical tools that achieve an order-level better finite-time convergence rate than the previously established result. Specifically, we show that synchronous double Q-learning attains an ϵ-accurate global optimum with a time complexity of $\Omega\left(\frac{\ln D}{(1-\gamma)^7 \epsilon^2}\right)$, and the asynchronous algorithm attains a time complexity of $\Omega\left(\frac{L^6 \ln D}{(1-\gamma)^7 \epsilon^2}\right)$, where D is the cardinality of the state-action space, γ is the discount factor, and L is a parameter related to the sampling strategy for asynchronous double Q-learning. These results improve the order-level dependence of the convergence rate on all major parameters $(\epsilon, 1-\gamma, D, L)$ provided in Xiong et al. (2020). The new analysis in this paper presents a more direct and succinct approach for characterizing the finite-time convergence rate of double Q-learning.

1 INTRODUCTION

Double Q-learning proposed in Hasselt (2010) is a widely used model-free reinforcement learning (RL) algorithm in practice for searching for an optimal policy (Zhang et al., 2018a;b; Hessel et al., 2018). Compared to the vanilla Q-learning proposed in Watkins & Dayan (1992), double Q-learning uses two Q-estimators with their roles randomly selected at each iteration, respectively for estimating the maximum Q-function value and updating the Q-function. In this way, the overestimation of the action-value function in vanilla Q-learning can be effectively mitigated, especially when the reward is random or prone to errors (Hasselt, 2010; Hasselt et al., 2016; Xiong et al., 2020). Moreover, double Q-learning has been shown to have the desired performance in both finite state-action setting (Hasselt, 2010) and infinite setting (Hasselt et al., 2016) where it successfully improved the performance of deep Q-network (DQN), and thus inspired many variants (Zhang et al., 2017; Abed-alguni & Ottom, 2018) subsequently.

In parallel to its empirical success in practice, the theoretical convergence properties of double Q-learning has also been explored. Its asymptotic convergence was first established in Hasselt (2010). The asymptotic mean-square error for double Q-learning was studied in Weng et al. (2020c) under the assumption that the algorithm converges to a unique optimal policy. Furthermore, in Xiong et al. (2020), the finite-time convergence rate has been established for double Q-learning with a polynomial learning rate $\alpha = 1/t^\omega, \omega \in (0,1)$. Under such a choice for the learning rate, they showed that double Q-learning attains an ϵ-accurate optimal Q-function at a time complexity approaching to but never reaching $\Omega(\frac{1}{\epsilon^2})$ at the cost of an asymptotically large exponent on $\frac{1}{1-\gamma}$. However, a polynomial learning rate typically does not offer the best possible convergence rate, as having been shown for vanilla Q-learning that a so-called *rescaled linear learning rate* (with a form of $\alpha_t = \frac{a}{b+ct}$) achieves a better convergence rate (Wainwright, 2019a;b; Chen et al., 2020; Qu & Wierman, 2020). Therefore, a natural question arises as follows:

Can a rescaled linear learning rate improve the convergence rate of double Q-learning order-wisely? If yes, does it also improve the dependence of the convergence rate on other important parameters of the Markov decision process (MDP) such as the discount factor and the cardinality of the state and action spaces?

The answer to the above question does not follow immediately from Xiong et al. (2020), because the finite-time analysis framework in Xiong et al. (2020) does not handle a rescaled linear learning rate to yield a desirable result. This paper develops a novel analysis approach and provides affirmative answers to the above question.

1.1 OUR CONTRIBUTIONS

This paper establishes sharper finite-time bounds for double Q-learning with a rescaled linear learning rate, which are orderwisely better than the existing bounds in Xiong et al. (2020). We devise a different analysis approach from that in Xiong et al. (2020), which is more capable of handling variants of double Q-learning.

- For synchronous double Q-learning, where all state-action pairs are visited at each iteration, we apply a rescaled linear learning rate $\alpha_t = \frac{3}{3+(1-\gamma)t}$ and show that the algorithm can attain an ϵ-accurate global optimum with a time complexity of $\Omega\left(\frac{\ln D}{(1-\gamma)^7\epsilon^2}\right)$, where γ is the discount factor and $D = |\mathcal{S}||\mathcal{A}|$ is the cardinality of the finite state-action space. As a comparison, for the ϵ dominated regime (with relatively small γ), our result attains an ϵ-accurate optimal Q-function with a time complexity $\Omega(\frac{1}{\epsilon^2})$, whereas the result in Xiong et al. (2020) (see Table 1) does not exactly reach $\Omega(\frac{1}{\epsilon^2})$ and its approaching to such an order ($\eta \to 0$) is at an additional cost of an asymptotically large exponent on $\frac{1}{1-\gamma}$. For $1-\gamma$ dominated regime, our result improves on that in Xiong et al. (2020) (which has been optimized in the dependence on $1-\gamma$ in Table 1) by $\mathcal{O}\left(\left(\ln\frac{1}{1-\gamma}\right)^7\right)$.

- For asynchronous double Q-learning, where only one state-action pair is visited at each iteration, we apply a learning rate $\alpha_t = \frac{3L}{3L+(1-\gamma)t}$ and show that the algorithm can attain an ϵ-accurate global optimum with a time complexity of $\Omega\left(\frac{L^6\ln D}{(1-\gamma)^7\epsilon^2}\right)$, where L is a parameter related to the sampling strategy in Assumption 1. As can be seen from Table 1, our result still improves upon that in Xiong et al. (2020) order-wisely in terms of its dependence on ϵ and $1-\gamma$ as well as on L by at least $\mathcal{O}\left((\ln L)^{1.5}\right)$.

Our analysis takes a different approach from that in Xiong et al. (2020) in order to handle the rescaled linear learning rate. More specifically, to deal with a pair of nested stochastic approximation (SA) recursions, we directly establish the dependence bound of the error dynamics (of the outer SA) between the Q-estimator and the global optimum on the error propagation (of the inner SA) between the two Q-estimators. Then we develop a bound on the inner SA, integrate it into that on the outer SA as a noise term, and establish the final convergence bound. This is a very different yet more direct approach than that in Xiong et al. (2020), the latter of which captures the blockwise convergence by constructing two complicated block-wisely decreasing bounds for two SAs. The sharpness of the bound also requires careful selection of the rescaled learning rates and proper usage of their properties.

1.2 RELATED WORK

Theory on double Q-learning: Double Q-learning was proposed and proved to converge asymptotically in Hasselt (2010). In Weng et al. (2020c), the authors explored the properties of mean-square errors for double Q-learning both in the tabular case and with linear function approximation, under the assumption that a unique optimal policy exists and the algorithm can converge. The most relevant work to this paper is Xiong et al. (2020), which established the first finite-time convergence rate for tabular double Q-learning with a polynomial learning rate. This paper provides sharper finite-time convergence bounds for double Q-learning, which requires a different analysis approach.

Table 1: Comparison of time complexity for (a)synchronous double Q-learning. The choices $\omega \to 1, \omega = \frac{6}{7}$, and $\omega = \frac{2}{3}$ respectively optimize the dependence of time complexity on $\epsilon, 1 - \gamma$, and L in Xiong et al. (2020). We denote $a \vee b = \max\{a, b\}$.

SyncDQ	Stepsize	Time complexity		
Xiong et al. (2020)	$\frac{1}{t^\omega}, \omega \in (\frac{1}{3}, 1)$	$\omega = 1 - \eta \to 1$ $\tilde{\Omega}\left(\frac{1}{\epsilon^{2+\eta}} \vee \left(\frac{1}{1-\gamma}\right)^{\frac{1}{\eta}}\right)$	$\omega = 6/7$ $\tilde{\Omega}\left(\frac{1}{(1-\gamma)^7}\left(\frac{1}{\epsilon^{3.5}} \vee \left(\ln \frac{1}{1-\gamma}\right)^7\right)\right)$	
This work	$\frac{3}{3+(1-\gamma)t}$	$\Omega\left(\frac{1}{\epsilon^2}\right)$	$\Omega\left(\frac{1}{(1-\gamma)^7\epsilon^2}\right)$	
AsyncDQ	Stepsize	Time complexity		
Xiong et al. (2020)	$\frac{1}{t^\omega}, \omega \in (\frac{1}{3}, 1)$	$\omega = 1 - \eta \to 1$ $\tilde{\Omega}\left(\frac{1}{\epsilon^{2+\eta}} \vee \left(\frac{1}{1-\gamma}\right)^{\frac{1}{\eta}}\right)$	$\omega = 6/7$ $\tilde{\Omega}\left(\frac{1}{(1-\gamma)^7}\left(\frac{1}{\epsilon^{3.5}} \vee \left(\ln \frac{1}{1-\gamma}\right)^7\right)\right)$	$\omega = 2/3$ $\tilde{\Omega}\left(\frac{L^6(\ln L)^{1.5}}{(1-\gamma)^9\epsilon^3}\right)$
This work	$\frac{3L}{3L+(1-\gamma)t}$	$\Omega\left(\frac{1}{\epsilon^2}\right)$	$\Omega\left(\frac{1}{(1-\gamma)^7\epsilon^2}\right)$	$\Omega\left(\frac{L^6}{(1-\gamma)^7\epsilon^2}\right)$

Tabular Q-learning and convergence under various learning rates: Proposed in Watkins & Dayan (1992) under finite state-action space, Q-learning has aroused great interest in its theoretical study. Its asymptotic convergence has been established in Tsitsiklis (1994); Jaakkola et al. (1994); Borkar & Meyn (2000); Melo (2001); Lee & He (2019) by requiring the learning rates to satisfy $\sum_{t=0}^\infty \alpha_t = \infty$ and $\sum_{t=0}^\infty \alpha_t^2 < \infty$. Another line of research focuses on the finite-time analysis of Q-learning under different choices of the learning rates. Szepesvári (1998) captured the first convergence rate of Q-learning using a linear learning rate (i.e., $\alpha_t = \frac{1}{t}$). Under similar learning rates, Even-Dar & Mansour (2003) provided finite-time results for both synchronous and asynchronous Q-learning with a convergence rate being exponentially slow as a function of $\frac{1}{1-\gamma}$. Another popular choice is the polynomial learning rate which has been studied for synchronous Q-learning in Wainwright (2019b) and for both synchronous/asynchronous Q-learning in Even-Dar & Mansour (2003). With this learning rate, however, the convergence rate still has a gap with the lower bound of $\mathcal{O}(\frac{1}{\sqrt{T}})$ (Azar et al., 2013). To handle this, a more sophisticated rescaled linear learning rate was introduced for synchronous Q-learning (Wainwright, 2019b; Chen et al., 2020) and asynchronous Q-learning (Qu & Wierman, 2020), and thus yields a better convergence rate. The finite-time bounds for Q-learning were also given with constant stepsizes (Beck & Srikant, 2012; Chen et al., 2020; Li et al., 2020). In this paper, we focus on the rescaled linear learning rate and obtain sharper finite-time bounds for double Q-learning.

Q-learning with function approximation: When the state-action space is considerably large or even infinite, the Q-function is usually approximated by a class of parameterized functions. In such a case, Q-learning has been shown not to converge in general (Baird, 1995). Strong assumptions are typically needed to establish the convergence of Q-learning with linear function approximation (Bertsekas & Tsitsiklis, 1996; Zou et al., 2019; Chen et al., 2019; Du et al., 2019; Weng et al., 2020a;b) or neural network approximation (Cai et al., 2019; Xu & Gu, 2019). The convergence analysis of double Q-learning with function approximation raises new technical challenges and can be an interesting topic for future study.

2 PRELIMINARIES ON DOUBLE Q-LEARNING

We consider a Markov decision process (MDP) over a finite state space $\mathcal{S}$ and a finite action space $\mathcal{A}$ with the total cardinality given by $D := |\mathcal{S}||\mathcal{A}|$. The transition kernel of the MDP is given by $\mathbb{P} : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to [0, 1]$ denoted as $\mathbb{P}(\cdot|s, a)$. We denote the *random* reward function at time t as $R_t : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \mapsto [0, R_{max}]$, with $\mathbb{E}[R_t(s, a, s')] = R_{sa}^{s'}$. A policy $\pi := \pi(\cdot|s)$ captures the conditional probability distribution over the action space given state $s \in \mathcal{S}$. For a policy π, we define Q-function $Q^\pi \in \mathbb{R}^{|\mathcal{S}| \times |\mathcal{A}|}$ as

$$Q^\pi(s, a) := \mathbb{E}\left[\sum_{t=1}^\infty \gamma^t R_t(s_t, a_t, s_t') \Big| s_1 = s, a_1 = a\right], \tag{1}$$

where $\gamma \in (0,1)$ is the discount factor, $a_t \sim \pi(\cdot|s_t)$, and $s'_t \sim \mathbb{P}(\cdot|s_t, a_t)$.

Both vanilla Q-learning (Watkins & Dayan, 1992) and double Q-learning (Hasselt, 2010) aim to find the optimal Q-function Q^* which is the unique fixed point of the Bellman operator $\mathcal{T}$ (Bertsekas & Tsitsiklis, 1996) given by

$$\mathcal{T}Q(s,a) = \mathbb{E}_{s' \sim \mathbb{P}(\cdot|s,a)} \left[R_{sa}^{s'} + \gamma \max_{a' \in \mathcal{A}} Q(s',a') \right]. \tag{2}$$

Note that the Bellman operator $\mathcal{T}$ is γ-contractive which satisfies $\|\mathcal{T}Q - \mathcal{T}Q'\| \leq \gamma \|Q - Q'\|$ under the supremum norm $\|Q\| := \max_{s,a} |Q(s,a)|$.

The idea of double Q-learning is to keep two Q-tables (i.e., Q-function estimators) Q^A and Q^B, and randomly choose one Q-table to update at each iteration based on the Bellman operator computed from the other Q-table. We next describe synchronous and asynchronous double Q-learning algorithms in more detail.

Synchronous double Q-learning: Let $\{\beta_t\}_{t \geq 1}$ be a sequence of i.i.d. Bernoulli random variables satisfying $\mathbb{P}(\beta_t = 0) = 0.5, \mathbb{P}(\beta_t = 1) = 0.5$. At each time t, $\beta_t = 0$ indicates that Q^B is updated, and otherwise Q^A is updated. The update at time $t \geq 1$ can be written in a compact form as,

$$\begin{cases} Q_{t+1}^A(s,a) = (1 - \alpha_t \beta_t) Q_t^A(s,a) + \alpha_t \beta_t \left(R_t(s,a,s') + \gamma Q_t^B(s',a^*) \right), \\ Q_{t+1}^B(s,a) = (1 - \alpha_t(1 - \beta_t)) Q_t^B(s,a) + \alpha_t(1 - \beta_t) \left(R_t(s,a,s') + \gamma Q_t^A(s',b^*) \right), \end{cases} \tag{3}$$

for all $(s,a) \in \mathcal{S} \times \mathcal{A}$, where s' is sampled independently for each (s,a) by $s' \sim \mathbb{P}(\cdot|s,a)$, $a^* = \arg\max_{a \in \mathcal{A}} Q^A(s',a)$, $b^* = \arg\max_{a \in \mathcal{A}} Q^B(s',a)$ and α_t is the learning rate. Note that the rewards for both updates of Q_{t+1}^A and Q_{t+1}^B are the same copy of R_t.

Asynchronous double Q-learning: Different from synchronous double Q-learning, at each iteration the asynchronous version samples only one state-action pair to update the chosen Q-estimator. That is, at time t, only the chosen Q-estimator and its value at the sampled state-action pair (s_t, a_t) will be updated. We model this by introducing an indicator function $\tau_t := \tau_t(s,a) = \mathbb{1}_{\{(s_t, a_t) = (s,a)\}}$. Then the update at time $t \geq 1$ of asynchronous double Q-learning can be written in a compact form as

$$\begin{cases} Q_{t+1}^A(s,a) = (1 - \alpha_t \tau_t \beta_t) Q_t^A(s,a) + \alpha_t \tau_t \beta_t \left(R_t + \gamma Q_t^B(s',a^*) \right), \\ Q_{t+1}^B(s,a) = (1 - \alpha_t \tau_t(1 - \beta_t)) Q_t^B(s,a) + \alpha_t \tau_t(1 - \beta_t) \left(R_t + \gamma Q_t^A(s',b^*) \right), \end{cases} \tag{4}$$

for all $(s,a) \in \mathcal{S} \times \mathcal{A}$, where R_t is evaluated as $R_t(s,a,s')$.

In the above update rules (3) and (4), at each iteration only one of the two Q-tables is randomly chosen to be updated. This chosen Q-table generates a greedy optimal action, and the other Q-table is used for estimating the corresponding Bellman operator (or evaluating the greedy action) for updating the chosen table. Specifically, if Q^A is chosen to be updated, we use Q^A to obtain the optimal action a^* and then estimate the corresponding Bellman operator using Q^B to update Q^A. As shown in Hasselt (2010), $\mathbb{E}[Q^B(s',a^*)]$ is likely smaller than $\max_a \mathbb{E}[Q^A(s',a)]$, where the expectation is taken over the randomness of the reward for the same (s,a,s') tuple. Such a two-estimator framework adopted by double Q-learning can effectively reduce the overestimation.

Without loss of generality, we assume that Q^A and Q^B are initialized with the same value (usually both all-zero tables in practice). For both synchronous and asynchronous double Q-learning, it has been shown in Xiong et al. (2020) that either Q-estimator is uniformly bounded by $\frac{R_{\max}}{1-\gamma}$ throughout the learning process. Specifically, for either $i \in \{A, B\}$, we have $\|Q_t^i\| \leq \frac{R_{\max}}{1-\gamma}$ and $\|Q_t^i - Q^*\| \leq \frac{2R_{\max}}{1-\gamma} := V_{\max}$ for all $t \geq 1$. This boundedness property will be useful in our finite-time analysis.

3 FINITE-TIME CONVERGENCE ANALYSIS

In this section, we start with modeling the error dynamics to be nested SAs, following by a convergence result for a general SA that will be applicable for both SAs. Then we provide the finite-time results for both synchronous and asynchronous double Q-learning. Finally, we sketch the proof of the main theorem for the synchronous algorithm to help understand the technical proofs.

3.1 CHARACTERIZATION OF THE ERROR DYNAMICS

In this subsection, we characterize the (a)synchronous double Q-learning algorithms as a pair of nested SA recursions, where the outer SA recursion captures the error dynamics between the Q-estimator and the global optimum Q^*, and the inner SA captures the error propagation between the two Q-estimators which enters into the outer SA as a noise term. Such a characterization enjoys useful properties that will facilitate the finite-time analysis.

Outer SA: Denote the iteration error by $r_t = Q_t^A - Q^*$ and define the empirical Bellman operator $\widehat{\mathcal{T}}_t Q(s,a) := R_t(s,a,s') + \gamma \max_{a' \in \mathcal{A}} Q(s',a')$. Then we can have for all $t \geq 1$ (see Appendix A),

$$r_{t+1}(s,a) = (1 - \tilde{\alpha}_t)r_t(s,a) + \tilde{\alpha}_t \left(\mathcal{G}_t(r_t)(s,a) + \varepsilon_t(s,a) + \gamma \nu_t(s',a^*) \right), \tag{5}$$

where $\varepsilon_t := \widehat{\mathcal{T}}_t Q^* - Q^*$, $\nu_t := Q_t^B - Q_t^A$, $\mathcal{G}_t(r_t) := \widehat{\mathcal{T}}_t Q_t^A - \widehat{\mathcal{T}}_t Q^* = \widehat{\mathcal{T}}_t (r_t + Q^*) - \widehat{\mathcal{T}}_t Q^*$, and the equivalent learning rate $\tilde{\alpha}_t := \begin{cases} \alpha_t \beta_t, & \text{for synchronous version} \\ \alpha_t \tau_t \beta_t, & \text{for asynchronous version} \end{cases}$. Note that it is by design that we use the same sampled reward R_t in both $\widehat{\mathcal{T}}_t Q^*$ and $\widehat{\mathcal{T}}_t Q_t^A$ in the definition of $\mathcal{G}_t(r_t)$.

These newly introduced variables have several important properties. First of all, the noise term $\{\varepsilon_t\}_t$ is a sequence of i.i.d. random variables satisfying $\mathbb{E}\varepsilon_t = \mathbb{E}[\widehat{\mathcal{T}}_t Q^*] - Q^* = \mathcal{T} Q^* - Q^* = \mathbf{0} \in \mathbb{R}^D$. Furthermore, define the span seminorm of Q^* as $\|Q^*\|_{\text{span}} := \max_{(s,a) \in \mathcal{S} \times \mathcal{A}} Q^*(s,a) - \min_{(s,a) \in \mathcal{S} \times \mathcal{A}} Q^*(s,a)$. Then it can be shown that (see Appendix A)

$$\|\varepsilon_t\| \leq 2R_{\max} + \gamma \|Q^*\|_{\text{span}} := \kappa. \tag{6}$$

Moreover, it is easy to show that $\|\mathcal{G}_t(r_t)\| \leq \gamma \|r_t\|$, which follows from the contractive property of the empirical Bellman operator given the same next sate. We shall say that $\mathcal{G}_t$ is quasi-contractive in the sense that the γ-contraction inequality only holds with respect to the origin $\mathbf{0}$.

Inner SA: We further characterize the dynamics of $\nu_t = Q_t^B - Q_t^A$ as an SA recursion (see Appendix A):

$$\nu_{t+1}(s,a) = (1 - \hat{\alpha}_t)\nu_t(s,a) + \hat{\alpha}_t \left(\mathcal{H}_t(\nu_t)(s,a) + \mu_t(s,a) \right), \tag{7}$$

for all $t \geq 1$ where $\hat{\alpha}_t := \begin{cases} \alpha_t, & \text{for synchronous version} \\ \alpha_t \tau_t, & \text{for asynchronous version} \end{cases}$. It has been shown in Xiong et al. (2020) that $\mathcal{H}_t$ is quasi-contractive satisfying $\|\mathcal{H}_t(\nu_t)\| \leq \frac{1+\gamma}{2} \|\nu_t\|$, and $\{\mu_t\}_{t \geq 1}$ is a martingale difference sequence with respect to the filtration $\mathcal{F}_t$ defined by $\mathcal{F}_1 = \{\emptyset, \Omega\}$ where Ω denotes the underlying probability space and for $t \geq 2$,

$$\mathcal{F}_t = \begin{cases} \sigma \left(\{s'_{k-1}\}, \{R_{k-1}\}, \beta_{k-1}, 2 \leq k \leq t \right), & \text{for synchronous version,} \\ \sigma \left(s'_{k-1}, s_k, a_k, R_{k-1}, \beta_{k-1}, \tau_{k-1}, 2 \leq k \leq t \right), & \text{for asynchronous version,} \end{cases} \tag{8}$$

where we note that for synchronous sampling $\{s'_{k-1}\}$ and $\{R_{k-1}\}$ are the sampled next states and the sampled rewards respectively at time $k - 1$; while for asynchronous sampling, by design the pairs $\{(s_k, a_k)\}_{k \geq 2}$ are sampled independently and $s'_k \sim \mathbb{P}(\cdot|s_k, a_k)$ for $k \geq 1$ (which is therefore independent of s_{k+1}). In formula, we have $\mathbb{E}(\mu_t|\mathcal{F}_t) = 0$. It can be shown that $|\mu_t(s,a)| \leq (1 + \frac{\gamma}{2})V_{\max} := \tilde{V}_{\max}$. More details of the design and properties of μ_t can be found in Appendix A.

In the sequel, we will provide the finite-time convergence guarantee for (a)synchronous double Q-learning using the SA recursions described by (5) and (7).

3.2 FINITE-TIME BOUND FOR A GENERAL SA

In this subsection, we develop a convergence result for a general SA that will be applicable for both inner and outer SAs described in Section 3.1.

Consider the following general SA algorithm with the unique fixed point $\theta^* = 0$:

$$\theta_{t+1} = (1 - \alpha_t)\theta_t + \alpha_t \left(\mathcal{G}_t(\theta_t) + \varepsilon_t + \gamma \nu_t \right), \tag{9}$$

for all $t \geq 1$, where $\theta_t \in \mathbb{R}^n$ and we abuse the notation of a general learning rate $\alpha_t \in [0, 1)$. Then we bound θ_t in the following proposition, the proof of which is provided in Appendix B.

Proposition 1. *Consider an SA given in ([9]). Suppose $\mathcal{G}_t$ is quasi-contractive with a constant parameter γ, that is, $\|\mathcal{G}_t(\theta_t)\| \leq \gamma \|\theta_t\|$ where $\gamma \in (0,1)$. Then for any learning rate $\alpha_t \in [0,1)$, the iterates $\{\theta_t\}$ satisfy*

$$\|\theta_t\| \leq \prod_{k=1}^{t-1} (1 - (1-\gamma)\alpha_k) \|\theta_1\| + \gamma \alpha_{t-1} (\|W_{t-1}\| + \|\nu_{t-1}\|)$$

$$+ \gamma \sum_{k=1}^{t-2} \left\{ \prod_{l=k+1}^{t-1} (1 - (1-\gamma)\alpha_l) \right\} \alpha_k (\|W_k\| + \|\nu_k\|) + \|W_t\|, \tag{10}$$

where the sequence $\{W_t\}$ is given by $W_{t+1} = (1 - \alpha_t)W_t + \alpha_t \varepsilon_t$ with $W_1 = \mathbf{0}$.

We note that an SA with a similar form to that in ([9]) has been analyzed in Wainwright ([2019b]), which additionally requires a monotonicity assumption. In contrast, our analysis does not require this assumption. Moreover, distinct from Wainwright ([2019b]), we treat the noise terms ε_t and ν_t separately rather than bounding them together. This is because for double Q-learning, the noise term ν_t has its own dynamics which is significantly more complex than the i.i.d. noise ε_t. Bounding them as one noise term will yield more conservative results.

Note that the SA recursion ([7]) is a special case of ([9]) by setting $\nu_t = \mathbf{0}$. Therefore, Proposition [1] is readily applicable to both ([5]) and ([7]).

3.3 FINITE-TIME ANALYSIS OF SYNCHRONOUS DOUBLE Q-LEARNING

We apply the above bound for SA to synchronous double Q-learning and bound the error $\|r_t\| = \|Q_t^A - Q^*\|$. The first result is stated in the following theorem.

Theorem 1. *Fix $\gamma \in (0,1)$. Consider synchronous double Q-learning in ([3]) with a rescaled linear learning rate $\alpha_t = \frac{3}{3+(1-\gamma)t}, \forall t \geq 0$. Then the learning error $r_t = Q_t^A - Q^*$ satisfies*

$$\mathbb{E} \|r_{t+1}\| \leq \frac{3\|r_1\|}{(1-\gamma)t} + \frac{3\sqrt{3}\kappa\tilde{C}}{(1-\gamma)^{3/2}} \frac{1}{\sqrt{t}} + \frac{36\sqrt{3}V_{\max}\tilde{D}}{(1-\gamma)^{5/2}} \frac{1}{\sqrt{t}}, \tag{11}$$

where $\tilde{C} := 6\sqrt{\ln 2D} + 3\sqrt{\pi}, \tilde{D} := 2\sqrt{\ln 2D} + \sqrt{\pi}$. and κ is defined in ([6]) which is the uniform bound of $|\varepsilon_t|$.

Theorem [1] provides the finite-time error bound for synchronous double Q-learning. To understand Theorem [1], the first term on the RHS (right hand side) of ([11]) shows that the initial error decays sub-linearly with respect to the number of iterations. The second term arises due to the fluctuation of the noise term ε_t, which involves the problem specific quantity κ. The last item arises due to the fluctuation of the noise term μ_t in the ν_t-recursion ([7]), i.e., the difference between two Q-estimators.

Corollary 1. *The time complexity (i.e., the total number of iterations) to achieve an ϵ-accurate optimal Q-function (i.e., $\mathbb{E} \|r_T\| \leq \epsilon$) is given by $T(\epsilon, \gamma, D) = \Omega\left(\frac{\ln D}{(1-\gamma)^7 \epsilon^2}\right)$.*

Proof. The proof follows directly from Theorem [1] by noting that the middle term on the RHS of ([11]) scales as $\left(\frac{1}{1-\gamma}\right)^{\frac{5}{2}}$ since $\kappa = 2R_{\max} + \gamma \|Q^*\|_{\text{span}} \leq \frac{2R_{\max}}{1-\gamma} = V_{\max}$. $\qquad\square$

We next compare Corollary [1] with the time complexity of synchronous double Q-learning provided in Xiong et al. ([2020]), which is given by

$$T = \Omega\left(\left(\frac{1}{(1-\gamma)^6 \epsilon^2} \ln \frac{D}{(1-\gamma)^7 \epsilon^2}\right)^{\frac{1}{\omega}} + \left(\frac{1}{1-\gamma} \ln \frac{1}{(1-\gamma)^2 \epsilon}\right)^{\frac{1}{1-\omega}}\right), \tag{12}$$

where $\omega \in (\frac{1}{3}, 1)$. For the ϵ dominated regime (with relatively small γ), the result in ([12]) clearly cannot achieve the order of $\frac{1}{\epsilon^2}$ and $\ln D$ as our result does. Further, its approaching to such an order ($\eta \to 0$ in Table [1]) is also at an additional cost of an asymptotically large exponent on $\frac{1}{1-\gamma}$. For $1-\gamma$ dominated regime, the dependence on $1-\gamma$ can be optimized by taking $\omega = \frac{6}{7}$ in ([12]), compared to which our result achieves an improvement by a factor of $\mathcal{O}\left(\left(\ln \frac{1}{1-\gamma}\right)^7\right)$ (see Table [1]).

3.4 Finite-time Analysis of Asynchronous Double Q-learning

In this subsection, we provide the finite-time result for asynchronous double Q-learning. Differently from the synchronous version, at each iteration asynchronous double Q-learning only update one state-action pair of a randomly chosen Q-estimator. Thus the sampling strategy is important for the convergence analysis, for which we first make the following assumption.

Assumption 1. *The sampling of state-action pairs for different iterations is independent from each other. In addition, there exists a positive constant L, such that any fixed state-action pair (s, a) is visited with a probability of at least $\frac{1}{L}$ at each iteration. That is, for any time step t, we have $\mathbb{P}[(s_t, a_t) = (s, a)] \geq \frac{1}{L}$.*

It is easy to observe that $L \geq D = |\mathcal{S}||\mathcal{A}|$ where the equation holds when the sampling is uniform over the state-action space at each iteration.

We next clarify the connection between Assumption 1 and other assumptions made in relevant studies on asynchronous Q-learning/double Q-learning. First, Even-Dar & Mansour (2003) and Xiong et al. (2020) adopted a notation of the covering time t_{cover} and assumed that all state-action pairs can be visited at least once in t_{cover} iterations. It has been mentioned in Even-Dar & Mansour (2003); Xiong et al. (2020) that their analysis still applies when relaxing their assumption to a more general stochastic setting, where all the state-action pairs are visited with high probability in t_{cover} iterations. The latter stochastic sampling strategy is also assumed or can be implied by the ergodicity assumptions in Li et al. (2020); Qu & Wierman (2020). In fact, Assumption 1 implies a similar property. To see this, we observe that

$$\mathbb{P}(\mathcal{B}) \geq 1 - D\mathbb{P}(\mathcal{B}_0) \geq 1 - D\left(1 - \frac{1}{L}\right)^{t_{cover}},$$

where $\mathcal{B}$ denotes the event that all state-action pairs have been visited at least once in t_{cover} iterations, and $\mathcal{B}_0$ denotes the event such that a fixed state-action pair is not visited in t_{cover} iterations. Then, by letting $t_{cover} \geq L \ln(2D)$, we have $\mathbb{P}(\mathcal{B}) \geq \frac{1}{2}$. In other words, Assumption 1 implies the assumption on the covering time given in Li et al. (2020). Essentially, all the aforementioned assumptions including Assumption 1 require the sampling strategy to satisfy that all the state-action pairs are visited during a bounded period at least with high probability. This can be captured either by L in our study or by the covering time t_{cover} as in other studies.

Next, we provide the finite-time convergence bound for asynchronous double Q-learning in the following theorem.

Theorem 2. *Fix $\gamma \in (0, 1)$ and suppose that Assumption 1 holds. Consider asynchronous double Q-learning with a rescaled linear learning rate $\alpha_t = \frac{3L}{3L+(1-\gamma)t}, \forall t \geq 0$ where L is given in Assumption 1. Then the learning error $r_t = Q_t^A - Q^*$ satisfies*

$$\mathbb{E}\|r_{t+1}\| \leq \frac{3L\|r_1\|}{(1-\gamma)t} + \frac{4\sqrt{3}L^2\kappa\tilde{C}}{(1-\gamma)^{3/2}}\frac{1}{\sqrt{t}} + \frac{21\sqrt{3}L^3 V_{\max}\tilde{D}}{(1-\gamma)^{5/2}}\frac{1}{\sqrt{t}}, \tag{13}$$

where $\tilde{C} := 6\sqrt{\ln 2D} + 3\sqrt{\pi}$, $\tilde{D} := 8\sqrt{\ln 2D} + 4\sqrt{\pi}$ and κ is defined in (6).

Theorem 2 implies the following characterization on the time-complexity.

Corollary 2. *Asynchronous double Q-learning converges to an ϵ-accurate global optimum with a time complexity of $T(\epsilon, \gamma, D, L) = \Omega\left(\frac{L^6 \ln D}{(1-\gamma)^7\epsilon^2}\right)$.*

We next compare Corollary 2 with the result obtained in Xiong et al. (2020). In Xiong et al. (2020), the authors provided the time complexity for asynchronous double Q-learning as

$$T = \Omega\left(\left(\frac{t_{cover}^4}{(1-\gamma)^6\epsilon^2}\ln\frac{Dt_{cover}^4}{(1-\gamma)^7\epsilon^2}\right)^{\frac{1}{\omega}} + \left(\frac{t_{cover}^2}{1-\gamma}\ln\frac{1}{(1-\gamma)^2\epsilon}\right)^{\frac{1}{1-\omega}}\right). \tag{14}$$

where $\omega \in (\frac{1}{3}, 1)$. It can be observed that our result improves that in (14) with respect to the order of all key parameters $\epsilon, D, 1-\gamma, L$ (see Table 1). Specifically, the dependence on L in (14) can be optimized by choosing $\omega = \frac{2}{3}$, upon which Corollary 2 improves by a factor of $(\ln L)^{1.5}$ as illustrated in Table 1.

3.5 Proof Sketch of Theorem 1

In order to provide the convergence bound for double Q-learning under the rescaled linear learning rate, we develop a different analysis approach from that in Xiong et al. (2020), the latter of which does not handle the rescaled linear learning rate. More specifically, in order to analyze a pair of nested SA recursions, we directly bound both the error dynamics of the outer SA between the Q-estimator and the global optimum and the error propagation between the two Q-estimators captured by the inner SA. Then we integrate the bound on the inner SA into that on the outer SA as a noise term, and establish the final convergence bound. This is a very different yet more direct approach than the techniques in Xiong et al. (2020) that constructs two complicated block-wisely decreasing bounds for two SAs in order to characterize the block-wise convergence.

Our finite-time analysis for synchronous double Q-learning (i.e., Theorem 1) includes four steps.

Step I: Bounding outer SA dynamics $\mathbb{E}\|r_t\|$ **by inner SA dynamics** $\mathbb{E}\|\nu_t\|$**.** Here, $r_t := Q_t^A - Q^*$ captures the error dynamics between the Q-estimator and the global optimum, and $\nu_t := Q_t^A - Q_t^B$ captures the error propagation between the two Q-estimators. We apply Proposition 1 to the error dynamics (5) of r_t, take the expectation, and apply the properties of the chosen learning rate to obtain

$$\mathbb{E}\|r_t\| \leq \alpha_{t-1}\|r_1\| + \frac{\gamma}{2}\alpha_{t-1}\sum_{k=1}^{t-1}(\mathbb{E}\|W_k\| + \mathbb{E}\|\nu_k\|) + \mathbb{E}\|W_t\|, \tag{15}$$

where $W_{t+1} = (1 - \tilde{\alpha}_t)W_t + \tilde{\alpha}_t\varepsilon_t$, with initialization $W_1 = \mathbf{0}$.

Step II: Bounding $\mathbb{E}\|W_t\|$**.** We first construct a $\mathcal{F}_t$-martingale sequence $\{\tilde{W}_i\}_{1 \leq i \leq t+1}$ with $\tilde{W}_{t+1} = W_{t+1}$ and $\tilde{W}_1 = \mathbf{0}$. We next bound the squared difference sequence $\left(\tilde{W}_{i+1} - \tilde{W}_i\right)^2$ by $4V_{\max}^2\alpha_t^N/\alpha_i^{N-2}$, for $1 \leq i \leq t$, where we apply Lemma 1. Then we apply the Azuma-Hoeffding inequality (see Lemma 5) to $\{\tilde{W}_i\}_{1 \leq i \leq t+1}$ and further use Lemma 6 to obtain the bound on $\mathbb{E}\|W_t\|$ in Proposition 2 which is given by

$$\mathbb{E}\|W_{t+1}\| \leq \kappa\tilde{C}\sqrt{\alpha_t}, \tag{16}$$

where $\tilde{C} = 6\sqrt{\ln 2D} + 3\sqrt{\pi}$ and κ is defined in (6).

Step III: Bounding inner SA dynamics $\mathbb{E}\|\nu_t\|$**.** Similarly to Step I, we apply Proposition 1 to the ν_t-recursion (7), take the expectation, and apply the properties of the learning rate to obtain

$$\mathbb{E}\|\nu_t\| \leq \alpha_{t-1}\|\nu_1\| + \frac{1+\gamma}{2}\alpha_{t-1}\sum_{k=2}^{t-1}\mathbb{E}\|M_k\| + \mathbb{E}\|M_t\|, \tag{17}$$

where $M_{t+1} = (1 - \alpha_t)M_t + \alpha_t\mu_t$, with initialization $M_1 = \mathbf{0}$. Using a similar idea to Step II, we obtain the bound on $\mathbb{E}\|M_t\|$ in Proposition 3. Finally, we substitute the bound of $\mathbb{E}\|M_t\|$ back in (17) and use the fact $\|\nu_1\| = 0$ to obtain

$$\mathbb{E}\|\nu_t\| \leq \frac{6V_{\max}\tilde{D}}{1-\gamma}\sqrt{\alpha_{t-1}}, \tag{18}$$

where $\tilde{D} := 2\sqrt{\ln 2D} + \sqrt{\pi}$.

Step IV: Deriving finite-time bound. We substitute the bounds (16) and (18) into (15), and finally obtain (11).

4 Conclusion

In this paper, we derived sharper finite-time bounds for double Q-learning with rescaled linear learning rates. To achieve this, we developed a different approach to bound two nested stochastic approximation recursions. An important yet challenging future topic is the convergence guarantee for double Q-learning with function approximation. In addition to the lack of the contraction property of the Bellman operator in the function approximation setting, it is likely that neither of the two Q-estimators converges, or they do not converge to the same point even if they both converge. Characterizing the conditions under which double Q-learning with function approximation converges is still an open problem.

REFERENCES

Bilal H Abed-alguni and Mohammad Ashraf Ottom. Double delayed Q-learning. *International Journal of Artificial Intelligence*, 16(2):41–59, 2018.

Mohammad Gheshlaghi Azar, Rémi Munos, and Hilbert J Kappen. Minimax pac bounds on the sample complexity of reinforcement learning with a generative model. *Machine learning*, 91(3): 325–349, 2013.

Leemon Baird. Residual algorithms: Reinforcement learning with function approximation. In *Machine Learning Proceedings 1995*, pp. 30–37. Elsevier, 1995.

Carolyn L Beck and R Srikant. Error bounds for constant step-size Q-learning. *Systems & Control Letters*, 61(12):1203–1208, 2012.

Dimitri P. Bertsekas and John N Tsitsiklis. *Neuro-Dynamic Programming*, volume 5. Athena Scientific, 1996.

Vivek S Borkar and Sean P Meyn. The ODE method for convergence of stochastic approximation and reinforcement learning. *SIAM Journal on Control and Optimization*, 38(2):447–469, 2000.

Qi Cai, Zhuoran Yang, Jason D Lee, and Zhaoran Wang. Neural temporal-difference learning converges to global optima. In *Advances in Neural Information Processing Systems (NeurIPS)*, pp. 11312–11322, 2019.

Zaiwei Chen, Sheng Zhang, Thinh T. Doan, Siva Theja Maguluri, and John-Paul Clarke. Finite-time analysis of Q-learning with linear function approximation. *arXiv preprint arXiv:1905.11425*, 2019.

Zaiwei Chen, Siva Theja Maguluri, Sanjay Shakkottai, and Karthikeyan Shanmugam. Finite-sample analysis of stochastic approximation using smooth convex envelopes. *arXiv preprint arXiv:2002.00874*, 2020.

Simon S Du, Yuping Luo, Ruosong Wang, and Hanrui Zhang. Provably efficient Q-learning with function approximation via distribution shift error checking oracle. In *Advances in Neural Information Processing Systems (NeurIPS)*, pp. 8058–8068, 2019.

Eyal Even-Dar and Yishay Mansour. Learning rates for Q-learning. *Journal of Machine Learning Research*, 5(Dec):1–25, 2003.

Hado V Hasselt. Double Q-learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, pp. 2613–2621, 2010.

Hado van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. In *Proc. AAAI Conference on Artificial Intelligence (AAAI)*, 2016.

Matteo Hessel, Joseph Modayil, Hado Van Hasselt, Tom Schaul, Georg Ostrovski, Will Dabney, Dan Horgan, Bilal Piot, Mohammad Azar, and David Silver. Rainbow: Combining improvements in deep reinforcement learning. In *Proc. AAAI Conference on Artificial Intelligence (AAAI)*, 2018.

Tommi Jaakkola, Michael I Jordan, and Satinder P Singh. Convergence of stochastic iterative dynamic programming algorithms. In *Advances in Neural Information Processing Systems (NeurIPS)*, pp. 703–710, 1994.

Donghwan Lee and Niao He. A unified switching system perspective and ODE analysis of Q-learning algorithms. *arXiv preprint arXiv:1912.02270*, 2019.

Gen Li, Yuting Wei, Yuejie Chi, Yuantao Gu, and Yuxin Chen. Sample complexity of asynchronous Q-learning: Sharper analysis and variance reduction. *arXiv preprint arXiv:2006.03041*, 2020.

Francisco S Melo. Convergence of Q-learning: A simple proof. *Institute of Systems and Robotics, Tech. Rep*, pp. 1–4, 2001.

Guannan Qu and Adam Wierman. Finite-time analysis of asynchronous stochastic approximation and Q-learning. *arXiv preprint arXiv:2002.00260*, 2020.

Csaba Szepesvári. The asymptotic convergence-rate of Q-learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, pp. 1064–1070, 1998.

John N Tsitsiklis. Asynchronous stochastic approximation and Q-learning. *Machine Learning*, 16 (3):185–202, 1994.

Martin J. Wainwright. *High-Dimensional Statistics: A Non-Asymptotic Viewpoint*. Cambridge Series in Statistical and Probabilistic Mathematics. Cambridge University Press, 2019a. doi: 10.1017/9781108627771.

Martin J Wainwright. Stochastic approximation with cone-contractive operators: Sharp ℓ_∞-bounds for Q-learning. *arXiv preprint arXiv:1905.06265*, 2019b.

Christopher J.C.H. Watkins and Peter Dayan. Q-learning. *Machine Learning*, 8(3-4):279–292, 1992.

Bowen Weng, Huaqing Xiong, Yingbin Liang, and Wei Zhang. Analysis of Q-learning with adaptation and momentum restart for gradient descent. In *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence (IJCAI-20)*, pp. 3051–3057, 2020a.

Bowen Weng, Huaqing Xiong, Lin Zhao, Yingbin Liang, and Wei Zhang. Momentum Q-learning with finite-sample convergence guarantee. *arXiv preprint arXiv:2007.15418*, 2020b.

Wentao Weng, Harsh Gupta, Niao He, Lei Ying, and Srikant R. Provably-efficient double Q-learning. *arXiv preprint arXiv:arXiv:2007.05034*, 2020c.

Huaqing Xiong, Lin Zhao, Yingbin Liang, and Wei Zhang. Finite-time analysis for double Q-learning. *arXiv preprint arXiv:2009.14257*, 2020.

Pan Xu and Quanquan Gu. A finite-time analysis of Q-learning with neural network function approximation. *arXiv preprint arXiv:1912.04511*, 2019.

Qingchen Zhang, Man Lin, Laurence T Yang, Zhikui Chen, Samee U Khan, and Peng Li. A double deep Q-learning model for energy-efficient edge scheduling. *IEEE Transactions on Services Computing*, 12(5):739–749, 2018a.

Yi Zhang, Ping Sun, Yuhan Yin, Lin Lin, and Xuesong Wang. Human-like autonomous vehicle speed control by deep reinforcement learning with double Q-learning. In *Proc. IEEE Intelligent Vehicles Symposium (IV)*, pp. 1251–1256, 2018b.

Zongzhang Zhang, Zhiyuan Pan, and Mykel J Kochenderfer. Weighted double Q-learning. In *International Joint Conferences on Artificial Intelligence (IJCAI-17)*, pp. 3455–3461, 2017.

Shaofeng Zou, Tengyu Xu, and Yingbin Liang. Finite-sample analysis for SARSA with linear function approximation. In *Advances in Neural Information Processing Systems (NeurIPS)*, pp. 8665–8675, 2019.