Data Selection for Reward Labeling in Limited-Feedback Reinforcement Learning

Abstract

The ability of reinforcement learning (RL) algorithms to learn effective policies is determined by the rewards available during training. However, for practical problems, obtaining large quantities of reward labels is often infeasible due to computational or financial constraints, for instance, when relying on human feedback. When reinforcement learning must proceed with limited feedback—only a fraction of samples get reward labels—a fundamental question arises: *which* samples should be labeled for RL training to maximize policy performance? We formalize this problem of *reward selection* for reinforcement learning from limited feedback, introducing a new problem formulation that facilitates the study of strategies for selecting impactful rewards. Various types of selection strategies are investigated: (i) ones that rely on reward-free information such as state visitation and partial value functions, (ii) ones that perform near-optimal selection requiring prohibitive costs, and (iii) ones that trade off those costs for some loss in performance. We find that critical subsets of rewards are those that (1) guide the agent along optimal trajectories, and (2) support recovery toward near-optimal behavior after deviations. Effective selection methods yield near-optimal policies with significantly fewer reward labels than full supervision, establishing reward selection as a powerful paradigm for scaling reinforcement learning in feedback-limited settings.

1 Introduction

Various real-world scenarios of sequential decision-making share a striking asymmetry: while data is abundant (or cheaply generated), obtaining evaluative feedback is prohibitively costly and therefore limited by practical constraints. Consider the following examples: in reinforcement learning from human feedback (RLHF) for training large language models (LLMs), billions of tokens can be generated easily, but acquiring reliable human feedback carries significant operational overhead (Christiano et al., 2017; Ouyang et al., 2022; Bai et al., 2022; ABAKA AI, 2025). In the field of AI-driven drug discovery, modern generative models can enumerate billions of syntactically valid molecular graphs in silico, sweeping through an estimated chemical space of $\approx 10^{60}$ drug-like molecules (Reymond, 2015; Gómez-Bombarelli et al., 2018; Jin et al., 2019). Yet confirming that any one of those structures is synthesizable, binds to the intended target, and is non-toxic requires weeks of wet-lab assays and thousands of dollars per compound (DiMasi et al., 2016; Anon, 2023). In these and many similar discrete selection problems (Appendix A), where evaluative feedback is limited, it becomes critical to identify which subset of the abundant data should be selected for feedback in order to achieve maximal performance gain with minimal feedback.

Reinforcement learning (RL) is the widely adopted approach for solving sequential decision-making problems (Popova et al., 2018; Ouyang et al., 2022; Feng et al., 2023). In the RL framing of the above scenarios, feedback corresponds to rewards, but obtaining rewards for all data points is infeasible. In this work, we study the important question of *reward selection*—which subset of the data should be labeled with rewards to maximize the performance of the learned policy? Acquiring rewards for different subsets leads to policies of varying quality, and the goal is to select the parts of the dataset to be reward-labeled such that the resulting policy achieves the highest performance, as illustrated in Figure 1. The question of which data points to acquire rewards for is equivalent to selecting the states at which to observe rewards. Consequently, the problem is formulated as the selection of a subset of states at which to obtain rewards. We formulate

Figure 1: Each row represents a data sample; shaded green rows indicate samples that have been labeled with rewards. The strategy $\mathcal{Q}_i$ determines which states to select for reward labeling. In the limited feedback setup, only a subset of states can be labeled. Different choices of reward-labeled subsets yield learnt policies of varying performances. The objective is to identify the subset that leads to the highest-performing policy.

the reward selection problem wherein the only degree of freedom permitted is the selection of states (as input), and the outcome observed is the resultant policy (as output), as illustrated in Figure 2 and detailed in Section 2.2.

The reward selection strategies studied, by design, are agnostic to the specifics of the reinforcement learning under limited feedback (`RLLF`) methodology—particularly the reward generation protocols—allowing the formulation and analysis to generalize to future methods of reward generation. Furthermore, we consider `RLLF` on offline datasets to disentangle the conflating effects of online state reachability and exploration. That is, any selected states can be labeled with rewards for training, rather than only those than can be reached by an exploration policy. This contrasts with prior setups within active RL (Krueger et al., 2020) and partially observable rewards (Parisi et al., 2024b), which share similar motivations. To learn from partially reward-labeled data, we adapt an existing algorithm for incorporating unlabeled data with labeled data for (offline) RL (Yu et al., 2022). Alternatively, we also study a variant of Q-learning (in Appendix D.9) that defaults to imitating the data-collecting policy on unlabeled data.

We begin by developing evaluating a range of heuristic selection strategies, including one that adaptively balances between two heuristics (Section 3.1). Their effectiveness depends on domain traits, which we characterize in Section 4.1. For cases where feedback about the performance of intermediate policies is obtainable, we propose a training-phase formulation in which selection strategies themselves can be optimized (Section 3.2); using methods like evolutionary search and leveraging partial information, we study how such strategies improve with additional training cost and compare them to heuristic approaches (Section 4.2). Finally, we analyze the best (optimal) reward selections to identify structural patterns that explain which rewards matter most under limited feedback (Section 3.2). Effective reward selection yields near-optimal policies with far fewer reward labels than full supervision, highlighting both the potential and challenges of feedback-efficient reinforcement learning.

In this work, **our contributions** are:

1. Formulate the problem of *reward selection* for reinforcement learning under limited feedback, establishing a general, domain-agnostic framework with practical relevance across diverse applications such as RLHF for LLMs and AI-driven drug discovery.

2. Conduct a systematic investigation of the problem landscape by developing and evaluating a range of heuristic-based strategies, characterizing how different design principles influence downstream policy performance.

3. Introduce a training-phase in which strategies are finetuned by observing the performance of intermediate selections: developing a range of strategies from optimal ones, with prohibitive training cost, to approximate ones that trade off me cost for a drop in performance.

4. Provide a qualitative analysis of optimal reward selections, revealing structural factors that answer the central question: *which rewards matter?*—laying the groundwork for future algorithmic development.

2 Problem Formulation and Preliminaries

Preliminaries: An MDP is a tuple $M := (\mathcal{S}, \mathcal{A}, p, r, \gamma, \eta)$ where $\mathcal{S}$ is a finite set of states, S_t is the state at time $t \in \{0, 1, \dots\}$, $\mathcal{A}$ is a finite set of actions, A_t is the action at time t, $p : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to [0, 1]$ is the *transition function* that characterizes state transition dynamics according to $p(s, a, s') := \Pr(S_{t+1}=s'|S_t=s, A_t=a)$, $r : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is the *reward function* that characterizes rewards according to $r(s, a) := \mathbb{E}[R_t|S_t=s, A_t=a]$, $\gamma \in [0, 1]$ is the reward discount parameter, and $\eta : \mathcal{S} \to [0, 1]$ characterizes the initial state distribution according to $\eta(s) := \Pr(S_0=s)$. A policy $\pi : \mathcal{S} \times \mathcal{A} \to [0, 1]$ characterizes how actions can be selected given the current state according to $\pi(s, a) := \Pr(A_t=a|S_t=s)$. We consider finite horizon MDPs (Sutton & Barto, 2018) where episodes terminate by some (unspecified) time $T \in \mathbb{N}$.

2.1 Reinforcement Learning from Limited Feedback

We study the problem of reinforcement learning from limited feedback (`RLLF`) in the offline setting. An offline dataset $\mathcal{D}_n = \{(S_t, A_t, S_{t+1})^{(i)}\}_{i=1}^n$ of n samples is obtained by the interaction of a *data-collecting policy* π_D with M.[1] The dataset contains no reward, i.e., evaluative feedback. To simulate the limited feedback setting, the restriction imposed by the problem setup is that environment rewards are permitted to be obtained at only a subset B of the states. Let $\mathcal{S}_{[B]}$ denote the states that are reward-labeled. For samples in $\mathcal{D}$ where $S_t \in \mathcal{S}_{[B]}$, reward labels are assigned; the remaining samples in $\mathcal{D}$ are unlabeled. In practice, since the *labeling budget* is smaller than the total number of states $|\mathcal{S}|$, only a subset of the dataset can be reward-labeled.[2] The process of reward-labeling part of the dataset and learning a policy from the resulting partially labeled data is referred to as reinforcement learning from limited feedback, and is denoted by $\texttt{RLLF}(\mathcal{D}, \mathcal{S}_{[B]})$ (see the box in Figure 2). Different choices of $\mathcal{S}_{[B]}$ result in different policies learned from the partially labeled dataset, with varying performance (see Figure 5 in Appendix D.2).

Rather than passively learning a policy from a fixed partially labeled dataset, we study the problem of actively selecting the states to label with rewards in order to obtain the best-performing policy. Formally, the **reward selection** problem is to *identify a subset of states $\mathcal{S}_{[B]}$, subject to a labeling budget B, to be labeled with rewards such that the policy learned from the resulting partially labeled dataset achieves maximum performance.*

Policy Learning from Partially Reward-Labeled Data: The choice of policy update rule naturally impacts the effectiveness of different reward selection strategies, and thus, the conclusions drawn about which rewards matter most under limited feedback. Standard RL algorithms may be adapted in a variety of ways to learn from partially reward-labeled data: from discarding unlabeled data to having a protocol for ingesting it with assumed reward values. The latter has been studied in prior work, for value-based methods (Yu et al., 2022), and is the primary update rule we adopt in this chapter. We also study an alternative update rule of our own design, which is detailed in Appendix D.9.

Given a dataset where only a subset of samples are reward-labeled, we use the UDS algorithm (Yu et al., 2022) to learn a policy from the partially reward-labeled dataset. This algorithm follows a simple procedure: unknown rewards are replaced with zero (or $R_{\min}$), and a policy is learned using these imputed rewards. We adopt Q-learning as the policy update rule, as is standard in offline RL settings (Levine et al., 2020; Kostrikov et al., 2021). We also redo the same analysis for an alternative policy update rule of our own design, called adapted Q-learning, which is detailed in Appendix D.9. For that algorithm, for states where rewards are unavailable (i.e., $s \notin \mathcal{S}_{[B]}$), we make no assumptions and treat the reward as being *undefined*. As a result, this algorithm sets unknown Q-values to zero, in contrast to the UDS algorithm, which sets unknown reward values to zero. The conclusions of our analysis are consistent across both update rules, corroborating that our findings generalize across different policy learning algorithms.

Other methods for handling partially labeled data could also be employed, but the focus of this investigation is on identifying a reward selection strategy that is effective for this instantiation of `RLLF`, rather than proposing a new method for learning from partially reward-labeled data.

---

[1] The data-collecting policy π_D can be a single policy, or a mixture of policies of which the weighted average is denoted by π_D. For clarity, we drop the subscript n unless explicitly needed, and denote the dataset by $\mathcal{D}$.

[2] $\mathcal{S}$ denotes only the states logged in the offline dataset $\mathcal{D}$, which may may be a subset of the entire state set of M.

2.2 Reward Selection

The strategy for selecting the B states from $\mathcal{D}$ to label with rewards is denoted by $\mathcal{Q}^{(B)} : \mathcal{D} \to \mathcal{S}^B$. Formally, given a budget B, the set of states at which rewards are observed is defined as $\mathcal{S}_{[B]} = \mathcal{Q}^{(B)}(\mathcal{D})$. The resulting learned policy is denoted by $\pi_{[B]} = \texttt{RLLF}\left(\mathcal{D}, \mathcal{Q}^{(B)}(\mathcal{D})\right)$.[3] The effectiveness of a strategy $\mathcal{Q}^{(B)}$ is quantified by the expected return of the policy produced by $\texttt{RLLF}$ when trained using the rewards selected by $\mathcal{Q}^{(B)}$. The objective of a reward selection strategy, denoted by $P(\cdot)$, is to maximize the expected return of the resulting policy, $J(\pi) := \mathbb{E}_\pi \left[\sum_{t=0}^T \gamma^t R_t \right]$, averaged over possible datasets $\mathcal{D}$. That is, the reward selection problem can be formalized as identifying a sampling strategy $\mathcal{Q}^{(B)}$ such that:

$$\max_{\mathcal{Q}^{(B)}} P(\mathcal{Q}^{(B)}) := \max_{\mathcal{Q}^{(B)}} \mathbb{E}_\mathcal{D} \left[J\left(\pi_{[B]}\right) \right] = \max_{\mathcal{Q}^{(B)}} \mathbb{E}_\mathcal{D} \left[J\left(\texttt{RLLF}\left(\mathcal{D}, \mathcal{Q}^{(B)}(\mathcal{D})\right)\right) \right]. \tag{1}$$

Note that when $\mathcal{Q}^{(B)}$ is stochastic, the definition of $P(\cdot)$ includes an additional nested expectation over the possible outputs of $\mathcal{Q}^{(B)}$. Hereon, we overload the notation P to take as input the selection strategy $\mathcal{Q}^{(B)}$, or the state set $\mathcal{S}_{[B]}$ selected by $\mathcal{Q}^{(B)}$, or the policy $\pi_{[\mathcal{S}_{[B]}]}$ learned from the selected state set $\mathcal{S}_{[B]}$, in each case, to denote the performance of the resulting policy.

Optimality: Given a budget B, the *optimal* reward selection strategy $\mathcal{Q}^{(B)}$ maximizes the performance of the resultant policy $\pi_{[\mathcal{S}_{[B]}]}$. There are $\binom{|\mathcal{S}|}{B}$ candidate state sets that may be chosen by $\mathcal{Q}^{(B)}$, each of which induces policies with varying performances. The optimal strategy entails selecting a state set, denoted by $\mathcal{S}_{[B]}^*$, that results in a policy with the highest performance:

$$\mathcal{S}_{[B]}^* \in \underset{\mathcal{S}_{[B]} \subseteq \mathcal{S}, |\mathcal{S}_{[B]}| = B}{\arg\max} P(\pi_{[\mathcal{S}_{[B]}]}) = \underset{\mathcal{Q}^{(B)}(\mathcal{D}) \subseteq \mathcal{S}}{\arg\max} P(\texttt{RLLF}(\mathcal{D}, \mathcal{Q}^{(B)}(\mathcal{D}))). \tag{2}$$

It must be noted that $\mathcal{S}_{[B]}^*$ may not be a unique set, rather, it belongs to a set of *equally optimal state sets*. For ease of exposition, we pick one such state set. The efficacy of any other reward selection strategy, that selects a different state set $\mathcal{S}_{[B]}$, can be quantified by the *optimality gap*, i.e., the gap between the optimal performance of a policy achievable under the labeling budget $\pi_{[B]}^* = \pi_{[\mathcal{S}_{[B]}^*]}^*$, given by:

$$\text{OptimalityGap}(\mathcal{S}_{[B]}) := P(\pi_{[B]}^*) - P(\pi_{[\mathcal{S}_{[B]}]}). \tag{3}$$

Without insight into how reward-labeling specific states affects final policy performance, it is challenging to design effective reward selection strategies. To enable more informed design, we introduce an optional *training phase* in which the reward selection strategy $\mathcal{Q}^{(B)}$ leverages feedback from an *evaluator* Ξ. The evaluator only provides aggregate expected return information, but does not reveal finer information about individual state-action-reward values. In practice, this could correspond to deploying a policy trained on limited feedback and leveraging its observed performance as a signal to refine the reward selection strategy. Once trained, a strategy $\mathcal{Q}^{(B)}$ is evaluated in a *test phase*, where access to Ξ is no longer available. This setup is illustrated in Figure 2.

Figure 2: Problem setup for reward selection: The green arrows indicate the test phase, during which the reward selection strategy is evaluated. The blue arrows represent access to, and feedback from, an evaluator available within the training phase loop.

During the **training phase**, Ξ assesses policies induced by different state subsets selected by a candidate reward selection strategy, guiding updates to the selection strategy. The $\texttt{RLLF}$ procedure is treated as a black

---

[3]To make the dependence on $\mathcal{S}_{[B]}$ explicit, $\pi_{[B]}$ is equivalently denoted as $\pi_{[\mathcal{S}_{[B]}]}$ when relevant.

box: individual state-reward values and policy update mechanisms remain inaccessible. `RLLF` takes a set of states selected by $\mathcal{Q}^{(B)}$ and an unlabeled dataset as input and outputs a policy, which may optionally be evaluated by Ξ for training.

During the **test phase**, reward selection strategies are compared along two dimensions: (1) their performance, as defined in Equation equation 1, and (2) their training cost, measured by the number of calls to Ξ. An ideal strategy maximizes test performance while minimizing evaluator usage. Training data $\mathcal{D}_{\text{train}}$ are generated by a data-collecting policy π_D, while test datasets $\mathcal{D}_{\text{test}}$ come from policies $\Pi_{\text{test}} = \{\pi_1, \ldots, \pi_m\}$. The test performance of $\mathcal{Q}^{(B)}$ is averaged over $\mathcal{D}_{\text{test}}$, as in Equation equation 1.

3 Selection Strategies Investigated

In this section, we describe the reward selection strategies we develop, that fall into two categories. The first category consists of strategies guided by heuristics that are rule-based and do not rely on the training phase. Generally, these can be expected to perform well enough, though not optimally. Their primary purpose is to assess the utility of intuitive heuristics when applied to the problem of reward selection without access to any prior information. The second category includes strategies that incorporate a training phase prior to evaluation. Within this category, we study a spectrum of approaches: from strategies that identify the optimal reward-labeled state set $\mathcal{S}^*_{[B]}$, albeit at high training cost, to approximate strategies that reduce training overhead at the expense of marginal loss in performance.

Additionally, the strategies studied can be classified based on how they construct the reward-labeled state set: *batch strategies*, which select all B states at once, and *iterative strategies*, which select one state at a time over B iterations. Iterative strategies are indexed by $b \in \{1, \ldots, B\}$, with selected states and iteration-specific quantities indexed by b, for instance, the set of selected states is denoted by $\mathcal{S}_{[b]}$. See Appendix C for a detailed categorization and discussion of notation.

3.1 Heuristic-Based Selection: Training-Free Strategies

Given an offline dataset $\mathcal{D}$, in the absence of any feedback to inform how labeling different states with rewards impacts the performance of the policy, we must rely on reward-free heuristics to guide the selection of states to label with rewards. The state-visitation distribution of the data collecting policy π_D, estimated from the offline test dataset, serves as a useful signal to guide the selection of states for reward-labeling. Additionally, constructing the state set (of size B) iteratively, i.e., adding one state at a time, allows for intermediate updates (at iteration b) to the policy and the corresponding Q-values to inform subsequent selections. The heuristics investigated are:

(1) `visitation` sampling: This strategy encodes the intuitive notion that maximizing the fraction of the dataset that is reward-labeled is a good proxy for maximizing the expected return of the resultant policy. To do so, it samples the most commonly occurring states in the dataset without replacement from the state-visitation distribution d^{π_D}, i.e., $\mathcal{S}_{[B]} \sim \text{Sample}_{\text{w/o rep}}(\mathcal{S}, d^{\pi_D}, B)$.

    (a) If $\mathcal{S}_{[B]}$ is constructed in an *iterative* manner, i.e., adding one state at a time, as opposed to a *batch* manner as above, an additional *on-policy* variant of this strategy is studied, referred to as `visitation-on-policy`, where the state set $\mathcal{S}_{[B]}$ is constructed by sampling states from the state-visitation distribution of the updated policy $\pi_{[b-1]}$ at each iteration b.

(2) `uniform` sampling: This strategy samples B states without replacement from a uniform distribution over all unlabeled states, i.e., $\mathcal{S}_{[B]} \sim \text{UniformSample}_{\text{w/o rep}}(\mathcal{S}, B)$. Besides serving as a baseline for comparison with other strategies, this strategy turns out to be surprisingly effective in certain cases where states that are not frequently visited under π_D can have high utility when labeled with rewards.

(3) `guided` sampling: This is an iterative strategy that balances exploration and exploitation; it explores by sampling states from the state-visitation distribution, and exploits by sampling from the neighborhood of the current highest valued state. Specifically, at each iteration b, the strategy samples a state from

the distribution q_b defined as

$$q_b(\cdot|Q^{\pi_{[b-1]}}, b) \propto \alpha_b \underbrace{d^{\pi_D}(\cdot)}_{\text{explore}} + (1-\alpha_b) \underbrace{d^{\pi_D}_{\text{prev}}(\cdot \mid \arg\max_{s \in \mathcal{S}_{[b-1]}} \max_{a \in \mathcal{A}} Q^{\pi_{[b-1]}}(s,a))}_{\text{exploit: focus on states near the most promising Q-values}}, \quad (4)$$

where $\widehat{d}^{\pi_D}_{\text{prev}}(\cdot \mid s')$ is the sample estimate of the distribution of states that lead to state s' as the next state under π_D. The term $\arg\max_{s \in \mathcal{S}_{[b-1]}} \max_{a \in \mathcal{A}} Q^{\pi_{[b-1]}}(s,a)$ identifies the state with the maximum (state-)value based on the rewards obtained thus far. The tradeoff weight α_b initially places more weight on the exploratory term to maximize state coverage and then decays as b increases, with decreasing α_b as Q-values become more reliable, to select states that are likely to regions of the state space from which high returns can be achieved.

(a) Similar to the one described above, an on-policy variant of this strategy, `guided-on-policy`, is also studied.

We estimate the state visitation distribution(s) $d^{\pi_D}(\cdot)$ from the dataset $\mathcal{D}$, denoted by $\widehat{d}^{\pi_D}(\cdot)$, as $\widehat{d}^{\pi_D}(s) := \frac{N(s)}{\sum_{s' \in \mathcal{S}} N(s')}$, where $N(s)$ denotes the number of occurrences of state s in $\mathcal{D}$. For the on-policy variants, the transition function of the environment is estimated from the dataset, which is used to approximate the state visitation distribution of the updated policy $\pi_{[b-1]}$ at each iteration b.

3.2 Strategies Leveraging the Training Phase: Optimal to Approximate

For the set of strategies that leverage the training phase, the feedback from the evaluator provides a valuable insight: the impact of the selected states on the performance of the resultant policy, and, consequently, the performance of the strategy (Equation equation 1). This feedback can help finetune the selection strategy during the training phase. The cost of this training phase, prior to the strategy's evaluation, is quantified by the number of calls to the evaluator Ξ. The training cost represents the operational costs required for evaluating a policy in resource-intensive settings, for instance, online deployment of a production policy to evaluate its performance. The proposed **optimal and near-optimal** strategies are:

(1) `brute-force`: The most straightforward strategy is to exhaustively search over all possible subsets of B states during the training phase, and select the one that results in the highest performing policy. This approach is guaranteed to find the optimal state set $\mathcal{S}^*_{[B]}$, given sufficient coverage of the training data. However, since the number of all possible subsets of size B that must be evaluated is *combinatorially large*—$\binom{|\mathcal{S}|}{B} \approx O(|\mathcal{S}|^{\min\{|\mathcal{S}|-B,B\}}) \approx O(|\mathcal{S}|^B)$—the resulting **training cost** is impractical for any reasonably sized state space $\mathcal{S}$. We investigate this solely to obtain a theoretical upper bound for selection performance.

(2) `sequential-greedy`: To mitigate the training cost, we define an iterative strategy that constructs the state set $\mathcal{S}_{[B]}$ one state at a time. Specifically, define the *conditional marginal utility* of adding s to $\mathcal{S}_{[b]}$ as

$$\Delta(s|\mathcal{S}_{[b]}) := P(\pi_{[\mathcal{S}_{[b]} \cup \{s\}]}) - P(\pi_{[\mathcal{S}_{[b]}]}), \quad (5)$$

where P is the objective defined in Equation equation 1. This strategy greedily selects the state s that maximizes $\Delta(s|\mathcal{S}_{[b]})$ at each iteration b. Consequently, this strategy has a **training cost** of $O(B|\mathcal{S}|)$—significantly lower than the brute force strategy, yet high enough for large state sets.

In general, greedy maximization is likely to result in suboptimal selection performance. Despite that, in our empirical analysis we observe that the sequential-greedy strategy is approximately optimal in most cases. Furthermore, the result by Nemhauser et al. (1978) can be leveraged to provide a *lower bound on the performance of such greedy selection*, subject to certain conditions on P (Equation equation 1). Specifically, treating P as a set function, when P is non-negative, monotone and submodular, then

$$P(\mathcal{Q}^{(B)}_{\text{sequential-greedy}}) \geq \left(1 - \left(1 - \frac{1}{B}\right)^B\right) P(\pi^*_{[B]}). \quad (6)$$

The worst-case performance of this strategy is lower bounded from the optimal performance ($P(\pi^*_{[B]})$) by the above factor, and in practice is observed to be significantly higher. This result is formalized

in Theorem 1 along with its proof in Appendix C.3. The conditional marginal utility Δ (Equation equation 5) may not be monotonic and submodular in general.

Next, we describe the proposed **approximate** strategies. These are training-based reward selection strategies that reduce training cost at the expense of marginal loss in performance:

(1) `ES` : Instead of relying on a rule-based approach, this strategy optimizes the selection strategy $\mathcal{Q}^{(B)}$ using an evolutionary strategy (ES) (Rechenberg, 1989; Salimans et al., 2017). The selection strategy $\mathcal{Q}^{(B)}$ is parameterized by θ, i.e., $\mathcal{Q}^{(B)}_\theta$. The fitness of each state set $\mathcal{S}_{[b]}$ selected by $\mathcal{Q}^{(B)}_\theta$ is defined as the performance of the resulting policy $J(\pi_{[\mathcal{S}_b]})$. Each iteration of ES optimizes θ to maximize the expected fitness of the state sets selected by $\mathcal{Q}^{(B)}_\theta$. The population k in each iteration of ES, and the number of iterations m, determine the overall **training cost** $O(km)$ of this strategy.

(2) `adaptive-mixture` : This strategy uses the fact that in addition to the actual performance of the intermediate policy $\pi_{[b]}$ obtained from the evaluator, the per-iteration Q-values $Q^{\pi_{[b]}}$ provide *imperfect* estimate of the same policy's performance, denoted as J_{partial}. Specifically, since $Q^{\pi_{[b]}}$ are learned from the *partial reward function*, which is imputed to zero for unlabeled states (Section 2), the difference between $J_{\text{partial}}(\pi_{[b]}) := \sum_{s \in \mathcal{S}} \eta(s) \max_a Q^{\pi_{[b]}}(s,a)$ and the actual performance $J(\pi_{[b]})$ encodes the *unobserved reward mass* under the policy at iteration b. Specifically,

$$J(\pi_{[b]}) - J_{\text{partial}}(\pi_{[b]}) = \sum_{s \notin \mathcal{S}_{[b]}, a \in \mathcal{A}} \sum d^{\pi_{[b]}}(s,a) R(s,a), \tag{7}$$

where $d^{\pi_{[b]}}(s,a)$ is the discounted state-action visitation distribution under $\pi_{[b]}$. The expressions are derived in Appendix C.4. A large magnitude of this difference indicates that frequently visited states under $\pi_{[b]}$ have high unobserved reward values, which can be labeled by sampling $\propto d^{\pi_{[b]}}(s)$. Conversely, a small magnitude of this difference implies that J_{partial} approximates the actual performance well and the selection strategy must explore by sampling states not visited (or infrequently visited) by $\pi_{[b]}$, that is by selecting states *outside* the regions frequently visited by $\pi_{[b]}$. One way to accomplish that is by: setting the zeros of $d^{\pi_{[b]}}(s)$ to a small numerical value ϵ, taking the reciprocal of this updated $d^{\pi_{[b]}}(s)$, normalizing it to a valid probability distribution, and sampling proportional to it. Denote this distribution by $d^{\pi_{[b]}}_{\text{inv}}(s) \propto \frac{1}{d^{\pi_{[b]}}(s)}$. Accordingly, the mixture weight, denoted by w_b, is computed as $w_b := \exp\left(-\left|\frac{J(\pi_{[b]}) - J_{\text{partial}}(\pi_{[b]})}{\text{scaling-factor}}\right|\right)$ where 'scaling-factor' is a domain-specific constant hyperparameter set based on the range of returns so as not to saturate w_b at 1 or 0. The strategy samples iteratively from q_b defined as:

$$q_b(\cdot|b) \propto w_b \underbrace{d^{\pi_{[b]}}(\cdot)}_{\textit{within} \text{ policy's visitation}} + (1 - w_b) \underbrace{d^{\pi_{[b]}}_{\text{inv}}(\cdot)}_{\textit{outside} \text{ policy's visitation}}. \tag{8}$$

The two terms above may be readily replaced by a uniform distribution for sampling outside policy visitation and sampling around high-value states like in `guided` for sampling within policy vision. Further, $d^{\pi_{[b]}}$ is replaced by d^{π_D} when recomputating state visitation is infeasible. This strategy queries the evaluator only once per iteration, with a low **training cost** of $O(B)$.

A categorization of all selection strategies is presented in Appendix C.1. Next, we empiricially study the varying effectiveness of these selection strategies.

4 Empirical Analysis

This section evaluates the reward selection strategies across diverse domains. We empirically investigate the following questions: **(Q1**: Section 4.1**)** Which heuristics are effective proxies for reward selection and what factors shape their effectiveness? **(Q2**: Section 4.2**)** What performance benefits does a training phase

provide given its additional cost? **(Q3**: Section 4.3) What characteristics define high-impact rewards whose selection should be prioritized under limited budgets?

Domains: We evaluate performance across six prototypical domains and four large-scale MinAtar domains (Young & Tian, 2019) (Breakout, Freeway, Seaquest, Asterix). Of the prototypical domains, some (Graph, Tree, TwoRooms, TwoRooms-Trap) are purpose-built; others (FrozenLake, CliffWalk) are standard Gymnasium benchmarks (Brockman et al., 2016; Foundation, 2023). Additional domain details, transition dynamics, reward structures, expert policies, data collection, and further experiments on TwoRooms-Trap and FrozenLake are presented in Appendix D.1.

Evaluation: The primary evaluation metric is the **average episode return**, reported across all experiments. For small domains we average results over *100 trials*, while for larger domains we average over *10 trials*. Error bars reported in the tables and figures in this section represent the *standard error*. For heuristic-based selection, we additionally report the **optimality gap**, as defined in Equation 3. All reward acquisition budgets are expressed as percentage feedback relative to the total number of unique states $|\mathcal{S}|$ in each dataset, i.e., **Percentage Feedback = $B/|\mathcal{S}|$**, allowing for consistent comparison across domains.

4.1 Performance of Heuristic Reward Selection Depends on Domains Traits

Table 1: Comparison of `guided`, `visitation`, and `uniform` heuristic selection strategies on prototypical domains. For each domain, the table presents the optimality gap and the corresponding mean policy return ± standard error (in parentheses) across five feedback levels over 100 random seeds. Across all strategies and domains, the optimality gap decreases with increasing budget.

Domains	Percentage Feedback	guided	guided-on-policy	visitation	visitation-on-policy	uniform
Graph	0.1	3.3 [3.7 ± 0.1]	3.8 [3.2 ± 0.1]	**3.2 [3.8 ± 0.2]**	3.7 [3.3 ± 0.1]	4.1 [2.9 ± 0.1]
	0.3	2.2 [5.8 ± 0.1]	2.2 [5.8 ± 0.1]	**2.1 [5.9 ± 0.1]**	2.3 [5.7 ± 0.1]	3.4 [4.6 ± 0.2]
	0.5	0.9 [7.1 ± 0.1]	**0.3 [7.7 ± 0.1]**	0.8 [7.2 ± 0.1]	0.4 [7.6 ± 0.1]	2.0 [6.0 ± 0.1]
	0.7	0.2 [7.8 ± 0.0]	**0.0 [8.0 ± 0.0]**	0.4 [7.6 ± 0.1]	0.0 [8.0 ± 0.0]	1.1 [6.9 ± 0.1]
	0.9	**0.0 [8.0 ± 0.0]**	0.0 [8.0 ± 0.0]	0.0 [8.0 ± 0.0]	0.0 [8.0 ± 0.0]	0.0 [8.0 ± 0.0]
Tree	0.1	**9.1 [8.0 ± 0.5]**	9.7 [7.4 ± 0.9]	10.9 [6.1 ± 0.4]	12.4 [4.7 ± 0.4]	11.4 [5.7 ± 0.5]
	0.3	**4.9 [12.8 ± 0.4]**	5.0 [12.8 ± 0.6]	6.0 [11.8 ± 0.4]	5.2 [12.6 ± 0.4]	7.4 [10.3 ± 0.5]
	0.5	1.7 [16.1 ± 0.2]	**1.4 [16.4 ± 0.2]**	2.4 [15.4 ± 0.3]	1.4 [16.4 ± 0.2]	4.5 [13.2 ± 0.4]
	0.7	0.6 [17.2 ± 0.1]	**0.3 [17.4 ± 0.0]**	0.6 [17.1 ± 0.2]	0.6 [17.2 ± 0.1]	2.5 [15.3 ± 0.3]
	0.9	0.1 [17.7 ± 0.0]	**0.0 [17.7 ± 0.0]**	0.0 [17.6 ± 0.2]	0.2 [17.5 ± 0.1]	0.1 [17.7 ± 0.1]
CliffWalk	0.1	1152.9 [−1248.9 ± 117.3]	520.8 [−616.8 ± 105.6]	1166.1 [−1262.1 ± 119.2]	**296.1 [−392.0 ± 84.2]**	1061.0 [−1157.0 ± 61.0]
	0.3	285.9 [−370.0 ± 86.5]	9.6 [−93.6 ± 0.4]	378.5 [−462.5 ± 100.6]	**9.0 [−93.0 ± 0.4]**	1190.5 [−1274.6 ± 118.9]
	0.5	57.6 [−132.7 ± 32.8]	14.3 [−89.4 ± 0.8]	90.8 [−165.9 ± 46.2]	**11.7 [−86.7 ± 0.7]**	1160.8 [−1235.8 ± 137.4]
	0.7	32.7 [−98.9 ± 0.6]	8.6 [−74.8 ± 2.2]	33.8 [−100.0 ± 0.0]	**6.8 [−73.0 ± 1.9]**	890.0 [−956.2 ± 136.6]
	0.9	59.6 [−72.6 ± 3.9]	**25.6 [−38.6 ± 3.4]**	87.0 [−100.0 ± 0.0]	83.8 [−96.8 ± 1.5]	412.8 [−425.8 ± 99.2]
TwoRooms	0.1	1.0 [0.0 ± 0.0]	1.0 [0.0 ± 0.0]	1.0 [0.0 ± 0.0]	1.0 [0.0 ± 0.0]	**0.7 [0.3 ± 0.0]**
	0.3	0.9 [0.1 ± 0.0]	0.9 [0.1 ± 0.0]	0.9 [0.1 ± 0.0]	0.9 [0.1 ± 0.0]	**0.5 [0.5 ± 0.1]**
	0.5	0.8 [0.2 ± 0.0]	0.8 [0.2 ± 0.0]	0.8 [0.2 ± 0.0]	0.8 [0.2 ± 0.0]	**0.3 [0.7 ± 0.0]**
	0.7	0.7 [0.3 ± 0.0]	0.6 [0.4 ± 0.0]	0.5 [0.5 ± 0.1]	0.5 [0.5 ± 0.1]	**0.1 [0.9 ± 0.0]**
	0.9	0.3 [0.7 ± 0.0]	0.2 [0.8 ± 0.0]	0.1 [0.9 ± 0.0]	0.2 [0.8 ± 0.0]	**0.0 [1.0 ± 0.0]**

Our experiments suggest that the effectiveness of heuristic-based strategies is highly domain-dependent, and no single strategy consistently dominates. The results on prototypical domains are presented in Table 1 and on large-scale domains Figure 3. Additional experiments are deferred to Appendix D.3. The experiments for prototypical domains are averaged over 100 seeds, while results for large-scale domains are averaged over 10 seeds. Below, we highlight several key empirical findings:

1. **At low budgets:** When the reward labeling budget is small, the Q-values estimated from partially reward-labeled data are largely inaccurate. In such cases, `visitation` sampling generally provides an effective auxiliary signal for state selection. For example, in Graph, the visitation distribution induced by the data-collecting policy aligns well with the optimal selection even at low budgets, leading to improved performance. In CliffWalk, however, the on-policy visitation distribution proves to be more effective, as shown in Table 1.

2. **At high budgets:** As the budget increases, the learned Q-function becomes more accurate and informative. The *exploit*-term of `guided` sampling (see Equation 4) which relies on these Q-values to discover high-value states tends to aid performance and the `guided` strategy generally performs well. This trend is observed in 80% of the domains studied. Appendix D.8 outlines how the decay schedule and related

Figure 3: Comparison of three heuristic selection strategies `uniform`, `visitation`, and `guided`, and two training-phase strategies `ES 1000` and `adaptive-mixture`, on four large-scale domains: Breakout, Freeway, Seaquest, and Asterix. For each domain, the plot shows the mean policy return with error bars indicating the standard error over 10 random seeds.

parameters shape the exploration-exploitation tradeoff, and Appendix D.7 shows the strategy remains effective even with random warm-up samples.

3. **Impact of bottleneck structures:** In domains with bottleneck states—states that are chokepoints between regions of the environment, such as in TwoRooms and FrozenLake—sampling based on the visitation distribution under the data-collecting policy π_D may overlook these infrequently visited but critical states. The bottleneck states need to be reward-labeled early on to facilite effective policy learning as the budget grows. In such cases, `uniform` sampling has a higher likelihood of sampling these states and tends to outperforms other heuristics by providing broader coverage across the entire state set.

Takeaway: The `guided` sampling strategy balances the strengths of `visitation` sampling at low budgets with those of sampling near high-value states at high budgets, making it a useful heuristic. However, in general, training-free heuristic-based reward selection must rely on discernible domain traits (further elaborated in Section 4.3) and the available labeling budget. Rather than a single heuristic being universally effective, performance is maximized by combining different heuristics—adapting them to budget levels (e.g., `guided`) and to domain-specific characteristics.

4.2 Training Phase Facilitates Near-Optimal Performance

The selection strategies optimized using a training phase have higher performance than training-free strategies, with higher performance being achieved by a strategy with a higher training cost. The `brute-force` strategy, while being optimal, has a prohibitive training cost for even small state sets. For example, in a domain with $|\mathcal{S}| = 50$, exhaustively evaluating all possible state sets of size $B = 25$ would require $\binom{50}{25} \approx 10^{14}$ calls to the evaluator. Even at a rate of 2,000 calls per minute to the evaluator, completing this search would take about one hundred thousand years. We compare this strategy with others on prototypical domains, in Figure 4. An approximate version of the strategy with reduced training cost is benchmarked on the MinAtar domains in Appendix D.4.

The training cost of `sequential-greedy` scales linearly with the size of the state set and the budget ($O(B|\mathcal{S}|)$), while the training cost of `ES` is independent of the state set and the budget and is determined only by the population size per iteration m and number of iterations k. `ES` with cost $O(km)$ is denoted as `ES km`. On prototypical domains, we set $k = 10$ and evaluate two variants: `ES 50` ($m = 5$) and `ES 200` ($m = 20$). Additional ablations of k and m are provided in Appendix D.4, where for large-scale domains, we run `ES 1000` to accommodate the greater size of the state space. The training cost of `adaptive-mixture` is $O(B)$. The scaling factor in the mixture weight w_b is set to 2 for `Asterix` and `Seaquest`, 3 for `Freeway`, and 1 for all other domains. The selection performance of these strategies is benchmarked and reported in Figure 4 and Appendix D.4. The results imply following key findings:

- **sequential-greedy is near-optimal** with substantially lower training cost than brute-force, demonstrating that training cost *linear* in $|\mathcal{S}|$ suffices for near-optimal performance. Thus, greedy maximization of teh marginal utility (Equation 5) proves to be very effective, when feasible.

- **guided is a strong strategy considering zero-training cost** (Figure 4 and Table 8): it is comparable to low-cost ES and consistently outperforms adaptive-mixture, indicating that training-free guided sampling is more performant than low training cost strategies.

- **ES performance scales with training cost** (Figure 4 and Appendix D.4). As k and m increase, ES becomes an increasingly effective strategy. While adaptive-mixture is theoretically appealing, its empirical performance is subpar, likely due to high variance in the mixing weights.

- Optimal state sets identified on training datasets generalize well to test datasets from different data-collecting policies (Section 2), indicating **robustness to moderate dataset distribution shifts**. This is because for policies learned from Q-learning (as in RLLF), presence of a state in the dataset matters more than its frequency of occurrence, the latter may differ across datasets. An ablation study on varying data-collecting policies in Appendix D.6 further supports this observation.

Figure 4: Performance comparison of training-phase strategies and training-free guided on prototypical domains. Values show mean policy return over five test datasets (standard errors negligible). sequential-greedy achieves near-optimal performance, while guided is comparable to ES.

4.3 Common Structural Patterns in Optimal Reward Selections

As noted, effective selection methods can often induce near-optimal policies with significantly fewer reward labels than full supervision. In the RLLF setup considered, a reward-labeled state behaves as an anchor point for attracting the agent from nearby states when other states in the vicinity are not labeled, due to its combination of value-based policy learning and pessimistic labeling of unobserved rewards. We now conduct a qualitative post-hoc examination of the optimal state sets $(\mathcal{S}^*_{[B]})$ across domains to identify recurring structural patterns.

Pattern 1: Prioritizing Optimal Pathways. Optimal state sets include states that serve as anchor points to keep the agent on high-return paths in the domain. This is particularly evident in deterministic domains (like Graph), where at low budgets the goal state is selected first, after which $\mathcal{S}^*_{[B]}$ expands as the budget increases to include additional anchor points along the optimal policy's trajectory. In sparse reward domains, particularly those without hazardous or penalty states, optimal selection depends mainly on identifying states with high rewards: an example being paddle-ball alignment in Breakout as shown in Appendix D.5.

Pattern 2: Coverage of Near-Optimal Paths. Particulary for domains with stochastic transitions (like Tree), states in $\mathcal{S}^*_{[B]}$, i.e., states that get reward-labeled with high priority, include those that lie not just on but also in the vicinity of optimal trajectories of the domain. They serve to facilitate recovery back onto the optimal pathways from deviations that may occur due to stochastic transitions.

Pattern 3: Early Labeling of Penalty States. Penalty states (such as terminal or trap states in FrozenLake and TwoRooms-Trap) get reward-labeled early on, even at low budgets. This ensures that

resultant policies benefit by first learning to steer away from penalty states before learning to reach high reward states, serving the opposite role of anchor states.

Takeaway: These patterns indicate that optimal state sets follow intuitive structural roles: anchoring trajectories on high-return paths, supporting recovery in stochastic settings, and steering policies away from hazards. Overall, it matters that states on trajectories along which task-relevant reward information flows get selected. When such information is available a priori, through expert demonstrations or domain knowledge, design for effective reward selection strategies must explicitly emphasize these traits, in addition to the broader considerations of domain properties and budget levels discussed earlier for heuristic approaches.

5 Related Work

The problem of reward selection for `RLLF` remains largely unexplored. To motivation of selection under a budget constraint is shared prior work on *active learning* in supervised learning literature. Within the reinforcement learning paradigm, the closest formalization is by Parisi et al. (2024b), who consider **partially observable rewards** in online RL, but their setting conflates exploration with reward acquisition, making the focus different from our purely offline formulation. Zhan et al. (2023) propose a sampling approach for reward annotation but assume linear reward models, whereas our method does not impose such structural constraints. **Active RL** studies querying strategies under online exploration constraints, where agents must pay to observe rewards (Krueger et al., 2020; Schulze & Evans, 2018; Tucker et al., 2023). Our setting differs fundamentally: we study offline data with no additional exploration burden. Relatedly, Konyushova et al. (2021) address active off-policy data selection to improve policy evaluation, focusing on policy-level data collection rather than fine-grained reward state selection.

Works on **active reward learning** (Sadigh et al., 2017; Bıyık et al., 2019; Wilde et al., 2020; Daniel et al., 2015; Lindner et al., 2021) study how to query feedback that improves the generalization of a learned reward function. Our formulation differs fundamentally: because individual rewards are not retained, no reward model can be learned, and the focus shifts to improving policy learning rather than reward estimation. Other recent work explores reward modeling under uncertainty, for example, using priors over reward functions (Hu et al., 2023) or studying data influence (Munos & Moore, 2002; Koh & Liang, 2017; Gottesman et al., 2020). We complement these analyses by studying how selectively adding reward labels to previously unlabeled data influences the resulting policy performance.

The use of non reward labeled data has been studied for **online (state-based) exploration with unlabeled samples**. Some methods pseudo-label unlabeled samples to improve online exploration (Wilcoxson et al., 2024; Li et al., 2024), or develop exploration algorithms that operate under missing reward labels (Parisi et al., 2024a; Huang et al.). However, these primarily study exploration dynamics, whereas our focus is purely on optimizing offline reward label acquisition. A extended discussion of related work is provided in Appendix B.

6 Discussion and Conclusion

We introduce reward selection as a critical but underexplored challenge in `RLLF`. By decoupling selection of states for reward labeling from subsequent policy learning, we present the first systematic evaluation of zero-shot heuristics and optimized strategies across diverse environments, defining simple yet strong baselines and offering insights for future reward-efficient algorithms in domains such as RLHF and drug discovery. The effectiveness of reward selection varies with domain dynamics and reward structure: in deterministic settings with dense rewards, path-following heuristics perform well; in stochastic or sparse-reward domains, strategies that promote broader state coverage prove more effective. No single heuristic dominates across all cases, and effective selection must align with both the domain and learning algorithm. Our findings establish reward selection as a powerful paradigm for scaling reinforcement learning in limited feedback settings.

While our study focuses on value-based policy updates, extending selection strategies to policy-gradient methods is a promising direction. Additionally, our general framework abstracts away domain-specific structure; however, incorporating inductive biases, such as temporal correlations in time-series tasks, may further

aid selection strategies. Exploring how to integrate such structured priors offers an exciting path for future work.

References

ABAKA AI. Llm data cost breakdown: All you need to know about data costs for training an llm, 2025. URL https://www.abaka.ai/blog/llm-data-cost.

Anon. Ai's potential to accelerate drug discovery needs a reality check. *Nature*, 622:217, 2023.

Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*, 2022.

Erdem Bıyık, Malayandi Palan, Nicholas C Landolfi, Dylan P Losey, and Dorsa Sadigh. Asking easy questions: A user-friendly approach to active reward learning. *arXiv preprint arXiv:1910.04365*, 2019.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym, 2016. URL https://arxiv.org/abs/1606.01540.

Yevgen Chebotar, Ankur Handa, Viktor Makoviychuk, Miles Macklin, Jan Issac, Nathan Ratliff, and Dieter Fox. Closing the sim-to-real loop: Adapting simulation randomization with real world experience. In *2019 International Conference on Robotics and Automation (ICRA)*, pp. 8973–8979. IEEE, 2019.

Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. *Advances in neural information processing systems*, 30, 2017.

Christian Daniel, Oliver Kroemer, Malte Viering, Jan Metz, and Jan Peters. Active reward learning with a novel acquisition function. *Autonomous Robots*, 39(3):389–405, 2015.

Joseph A DiMasi, Henry G Grabowski, and Ronald W Hansen. Innovation in the pharmaceutical industry: new estimates of r&d costs. *Journal of health economics*, 47:20–33, 2016.

Alexey Dosovitskiy, German Ros, Felipe Codevilla, Antonio Lopez, and Vladlen Koltun. Carla: An open urban driving simulator. In *Conference on robot learning*, pp. 1–16. PMLR, 2017.

Shuo Feng, Haowei Sun, Xintao Yan, Haojie Zhu, Zhengxia Zou, Shengyin Shen, and Henry X Liu. Dense reinforcement learning for safety validation of autonomous vehicles. *Nature*, 615(7953):620–627, 2023.

Farama Foundation. Gymnasium. https://gymnasium.farama.org, 2023.

Rafael Gómez-Bombarelli, Jennifer N Wei, David Duvenaud, José Miguel Hernández-Lobato, Benjamín Sánchez-Lengeling, Dennis Sheberla, Jorge Aguilera-Iparraguirre, Timothy D Hirzel, Ryan P Adams, and Alán Aspuru-Guzik. Automatic chemical design using a data-driven continuous representation of molecules. *ACS central science*, 4(2):268–276, 2018.

Omer Gottesman, Joseph Futoma, Yao Liu, Sonali Parbhoo, Leo Celi, Emma Brunskill, and Finale Doshi-Velez. Interpretable off-policy evaluation in reinforcement learning by highlighting influential transitions. In *International Conference on Machine Learning*, pp. 3658–3667. PMLR, 2020.

Hao Hu, Yiqin Yang, Jianing Ye, Ziqing Mai, and Chongjie Zhang. Unsupervised behavior extraction via random intent priors. *Advances in Neural Information Processing Systems*, 36:51491–51514, 2023.

Audrey Huang, Mohammad Ghavamzadeh, Nan Jiang, and Marek Petrik. Non-adaptive online finetuning for offline reinforcement learning. In *NeurIPS 2023 Workshop on Generalization in Planning*.

Wengong Jin, Regina Barzilay, and Tommi Jaakkola. Hierarchical graph-to-graph translation for molecules. *arXiv preprint arXiv:1907.11223*, 2019.

Ying Jin, Zhuoran Yang, and Zhaoran Wang. Is pessimism provably efficient for offline rl? In *International Conference on Machine Learning*, pp. 5084–5096. PMLR, 2021.

Pang Wei Koh and Percy Liang. Understanding black-box predictions via influence functions. In *International conference on machine learning*, pp. 1885–1894. PMLR, 2017.

Ksenia Konyushova, Yutian Chen, Thomas Paine, Caglar Gulcehre, Cosmin Paduraru, Daniel J Mankowitz, Misha Denil, and Nando de Freitas. Active offline policy selection. *Advances in Neural Information Processing Systems*, 34:24631–24644, 2021.

Ilya Kostrikov, Ashvin Nair, and Sergey Levine. Offline reinforcement learning with implicit q-learning. *arXiv preprint arXiv:2110.06169*, 2021.

David Krueger, Jan Leike, Owain Evans, and John Salvatier. Active reinforcement learning: Observing rewards at a cost. *arXiv preprint arXiv:2011.06709*, 2020.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

Qiyang Li, Jason Zhang, Dibya Ghosh, Amy Zhang, and Sergey Levine. Accelerating exploration with unlabeled prior data. *Advances in Neural Information Processing Systems*, 36, 2024.

David Lindner, Matteo Turchetta, Sebastian Tschiatschek, Kamil Ciosek, and Andreas Krause. Information directed reward learning for reinforcement learning. *Advances in Neural Information Processing Systems*, 34:3850–3862, 2021.

Remi Munos and Andrew Moore. Variable resolution discretization in optimal control. *Machine learning*, 49:291–323, 2002.

George L Nemhauser, Laurence A Wolsey, and Marshall L Fisher. An analysis of approximations for maximizing submodular set functions—i. *Mathematical programming*, 14(1):265–294, 1978.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744, 2022.

Simone Parisi, Alireza Kazemipour, and Michael Bowling. Beyond optimism: Exploration with partially observable rewards. *arXiv preprint arXiv:2406.13909*, 2024a.

Simone Parisi, Montaser Mohammedalamen, Alireza Kazemipour, Matthew E Taylor, and Michael Bowling. Monitored markov decision processes. *arXiv preprint arXiv:2402.06819*, 2024b.

Mariya Popova, Olexandr Isayev, and Alexander Tropsha. Deep reinforcement learning for de novo drug design. *Science advances*, 4(7):eaap7885, 2018.

Aravind Rajeswaran, Vikash Kumar, Abhishek Gupta, Giulia Vezzani, John Schulman, Emanuel Todorov, and Sergey Levine. Learning complex dexterous manipulation with deep reinforcement learning and demonstrations. *arXiv preprint arXiv:1709.10087*, 2017.

Ingo Rechenberg. Evolution strategy: Nature's way of optimization. In *Optimization: Methods and Applications, Possibilities and Limitations: Proceedings of an International Seminar Organized by Deutsche Forschungsanstalt für Luft-und Raumfahrt (DLR), Bonn, June 1989*, pp. 106–126. Springer, 1989.

Jean-Louis Reymond. The chemical space project. *Accounts of chemical research*, 48(3):722–730, 2015.

Dorsa Sadigh, Anca Dragan, Shankar Sastry, and Sanjit Seshia. Active preference-based learning of reward functions. 2017.

Tim Salimans, Jonathan Ho, Xi Chen, Szymon Sidor, and Ilya Sutskever. Evolution strategies as a scalable alternative to reinforcement learning. *arXiv preprint arXiv:1703.03864*, 2017.

Sebastian Schulze and Owain Evans. Active reinforcement learning with monte-carlo tree search. *arXiv preprint arXiv:1803.04926*, 2018.

Richard S Sutton and Andrew G Barto. *Reinforcement Learning: An Introduction.* MIT Press, 2018.

Aaron D Tucker, Caleb Biddulph, Claire Wang, and Thorsten Joachims. Bandits with costly reward observations. In *Uncertainty in Artificial Intelligence*, pp. 2147–2156. PMLR, 2023.

Max Wilcoxson, Qiyang Li, Kevin Frans, and Sergey Levine. Leveraging skills from unlabeled prior data for efficient online exploration. *arXiv preprint arXiv:2410.18076*, 2024.

Nils Wilde, Dana Kulić, and Stephen L Smith. Active preference learning using maximum regret. In *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 10952–10959. IEEE, 2020.

Tengyang Xie, Ching-An Cheng, Nan Jiang, Paul Mineiro, and Alekh Agarwal. Bellman-consistent pessimism for offline reinforcement learning. *Advances in neural information processing systems*, 34:6683–6694, 2021.

Kenny Young and Tian Tian. Minatar: An atari-inspired testbed for thorough and reproducible reinforcement learning experiments. *arXiv preprint arXiv:1903.03176*, 2019.

Tianhe Yu, Aviral Kumar, Yevgen Chebotar, Karol Hausman, Chelsea Finn, and Sergey Levine. How to leverage unlabeled data in offline reinforcement learning. In *International Conference on Machine Learning*, pp. 25611–25635. PMLR, 2022.

Wenhao Zhan, Masatoshi Uehara, Wen Sun, and Jason D Lee. How to query human feedback efficiently in rl? 2023.

A Additional Motivating Examples

1. **Reinforcement Learning from Human Feedback (RLHF) in LLMs:** In training large language models (LLMs), model-generated outputs are plentiful, but high-quality human preference labels remain costly and scarce (Ouyang et al., 2022; Christiano et al., 2017). This creates a reward selection challenge: which model completions should be labeled with human feedback to best guide downstream policy improvement? This mirrors our setup, where a budgeted selection of feedback points must be made to train a performant policy while minimizing labeling operational cost (ABAKA AI, 2025).

2. **AI-driven Drug Discovery:** Generative models can propose vast libraries of candidate molecules (Gómez-Bombarelli et al., 2018; Reymond, 2015; Jin et al., 2019), but only a limited subset can be experimentally evaluated for synthesizability, bioactivity, and toxicity due to the cost and time of wet-lab trials (DiMasi et al., 2016). Reward selection here involves choosing which molecular candidates to evaluate, analogous to selecting states for reward labeling in our framework to maximize downstream performance within a practically limited evaluation budget.

3. **Autonomous Driving:** Simulation platforms can produce diverse driving trajectories across environments and policies at scale (Dosovitskiy et al., 2017), but obtaining expert evaluations—such as comfort, rule compliance, or safety—is resource-intensive (Feng et al., 2023). Thus, a reward selection strategy is needed to determine which trajectories to annotate to yield robust, deployable policies, much like our proposed approach to feedback-efficient learning.

4. **Robotics:** Simulated environments enable generation of numerous trajectories, but transferring and evaluating those policies in the real world involves expensive and time-consuming physical experiments (Rajeswaran et al., 2017; Chebotar et al., 2019). Reward selection in this domain involves prioritizing which simulated or real-world interactions to evaluate, paralleling our method's goal of selecting the most informative reward-labeled samples for efficient policy learning under cost constraints.

B Extended Related Work

The setup of active reward selection for `RLLF` has not been previously explored much. The closest formulation of this problem is in Parisi et al. (2024b), who provide a formulation for *partially observable rewards* in online RL and propose algorithms for that setting. The online formulation conflates the difficulty on online exploration with the utility of rewards, the latter being the focus of this work. sampling approach to acquiring exploratory trajectories that enable accurate learning of hidden reward functions before collecting any human feedback. Zhan et al. (2023) propose a sampling approach to acquire data to be reward-annotated, although their analysis assumes linearity of reward functions. Similar to discovering high-utility reward states, Konyushova et al. (2021) study active collection of online data to determine promising policies and improve their performance estimates, as active off-policy selection.

The topic of reward selection has been studied under *Active RL*, which is perhaps closest in its motivation to our setting: where the agent must pay a cost to observe the reward, although for an online setting, yet again conflating the difficulty of exploration with the utility of rewards. Krueger et al. (2020) study this in the bandit setting, while Tucker et al. (2023) extend it to structured settings but retain the bandit-style objective of identifying the best arm by using reward queries to increase confidence in the average (stochastic) outcomes of each arm. This differs from our problem in two major ways: the stochasticity of rewards for each arm forces repeated sampling, and the lack of sequentiality of actions (leading to different outcomes for repeated pulls of the same arm) shifts the focus from reward utility to uncertainty mitigation. In contrast, Schulze & Evans (2018) propose a Bayes-optimal algorithm using Monte Carlo Tree Search (MCTS) to actively select reward observations. Finally, approaches like Lindner et al. (2021) actively select queries to maximize information gain about the reward function for modeling it.

The use of non-reward-labeled data has been extensively explored in the context of *online state-based exploration with unlabeled samples*. Wilcoxson et al. (2024) propose assigning pseudolabels to unlabeled data to guide exploration, while Li et al. (2024) leverage prior offline datasets and online rewards to pseudo-label new data for improved exploration. Parisi et al. (2024a) examine exploration under partially observed rewards, a setting closely related to ours but focused on online interaction. Huang et al. introduce a data collection strategy combining online RL with offline datasets to approach the performance of the optimal policy. Yu et al. (2022) show that setting unknown rewards to zero can perform surprisingly well in certain offline RL settings, a finding we also confirm in our experiments. Hu et al. (2023) propose using unlabeled data by assuming priors over possible reward functions and optimizing over sampled realizations of those reward functions.

Beyond data-driven exploration, *influence functions* have been proposed as signals for high-utility rewards. Munos & Moore (2002) defines the influence of a reward on value as $\frac{\partial V^*(s)}{\partial R(s')}$, equivalent to the state visitation frequency under the optimal policy. Other works, such as Koh & Liang (2017) and Gottesman et al. (2020), analyze the effect of removing known datapoints on prediction performance. In contrast, we study the anticipated influence of adding partially unknown datapoints, requiring assumptions about their potential impact. Finally, Lindner et al. (2021) provide an algorithm for learning reward models independently of the reward querying process, which relates directly to the focus of our study.

C   Additional Notes on Selection Strategies

C.1   Categorization of Reward Selection Strategies Investigated

We categorize the reward state selection strategies introduced in Section 3 according to three key design dimensions: (i) whether selection during the test phase is performed in an *open-loop* or *closed-loop* manner, (ii) whether training-phase selection operates in a *batch* or *iterative* mode, and (iii) the degree to which each strategy utilizes the *evaluator* during training. Table 2 presents a high-level taxonomy across these dimensions.

Selection Strategy	Test: Open/Closed Loop	Train: Batch/Iterative	Train: Evaluator Use
Trained Strategies			
`brute-force`	Open loop	Batch	Yes
`sequential-greedy`	Open loop	Iterative	Yes
`evolutionary-strategy`	Open loop	Batch	Yes
`adaptive-mixture`	Closed loop	Iterative	Yes
Training-free Heuristics			
`guided`	Closed loop	Iterative	No
`guided-on-policy`	Closed loop	Iterative	No
`visitation`	Open loop	Batch	No
`visitation-on-policy`	Closed loop	Iterative	No
`uniform`	Open loop	Batch	No

Table 2: Categorization of reward selection methods by design dimensions. Columns are shaded to distinguish test-phase (green) and training-phase (blue) attributes. Methods are grouped based on whether they use the evaluator during training.

C.2   Description and Notation for Iterative Reward Selection Strategies

Iterative reward selection strategies construct the reward-labeled state set $\mathcal{S}_{[B]}$ in a sequential manner. At each step $b \in \{1, \ldots, B\}$, a new state $s_b \in \mathcal{S}$ is selected—conditioned on relevant information such as the current estimates of the Q-values of the policy or current policy's state-visitation distribution—and added to the selection set $\mathcal{S}_{[b-1]}$ to form $\mathcal{S}_{[B]}$. Relevant notation:

- $\mathcal{S}_{[b]}$: The set of selected states after b iterations, i.e., $\mathcal{S}_{[b]} = \mathcal{S}_{[b-1]} \cup \{s_b\}$.

- q_b: The selection strategy or distribution used to sample the next state s_b at iteration b, potentially conditioned on policy information or prior selections.

- $\pi_{[b]}$: The intermediate policy obtained after the b^{th} reward selection and updated via `RLLF`.

- $Q^{\pi_{[b-1]}}$: The Q-function corresponding to $\pi_{[b-1]}$ after the $(b-1)^{\text{th}}$ reward selection and update.

C.3   Lower Bound on the Optimality of `sequential-greedy` selection

Greedy maximization of the conditional marginal utility (Equation 5) is generally expected to result in suboptimality. Work in active learning by Nemhauser et al. (1978) provides a lower bound for the performance of such greedy selection, in terms of a multiple factor of the optimal performance, as described next.

The performance of the optimally selected subset of states at any budget b is denoted by $P(\pi_{[b]}^*)$. Let G_b denote the greedily selected state subset after b iterations, with $G_0 = \emptyset$. The `sequential-greedy` strategy

constructs a set G_B of size B by iteratively adding the state with maximum conditional marginal utiliy at each iteration b, i.e., $\arg\max_{s \in \mathcal{S} \setminus G_{b-1}} \Delta(s|G_{b-1})$, where $\Delta(s|G_b)$ is the marginal utility of adding state s to the current selection G_b as defined in Equation 5, rewritten as:

$$\Delta(s|G_b) := P(G_b \cup \{s\}) - P(G_b). \tag{9}$$

Definition C.1 (Monotonicity and Submodularity). A set function $P : 2^{\mathcal{S}} \to \mathbb{R}$ is *monotone* if $P(A) \leq P(B)$ for all $A \subseteq B$. It is *submodular* if for all $A \subseteq B \subseteq \mathcal{S}$ and all $s \in \mathcal{S} \setminus B$,

$$\Delta(s \mid A) \geq \Delta(s \mid B), \tag{10}$$

where $\Delta(s \mid A) := P(A \cup \{s\}) - P(A)$.

The following result (a special case of Nemhauser et al. (1978)) shows that, under monotonicity and submodularity of $P(\cdot)$, greedy maximization of the marginal utility achieves a constant-factor approximation to the optimal selection.

Theorem 1 (Greedy approximation guarantee; Nemhauser et al. (1978)). *Suppose $P : 2^{\mathcal{S}} \to \mathbb{R}_{\geq 0}$ is monotone and submodular. Let G_B be the state set returned by* `sequential-greedy`. *Let $\pi^*_{[B]}$ denote the optimal budget-B selection. Then*

$$P(G_B) \geq \left(1 - \left(1 - \tfrac{1}{B}\right)^B\right) P(\pi^*_{[B]}). \tag{11}$$

Moreover, for each $b \in \{0, 1, \ldots, B\}$,

$$P(G_b) \geq \left(1 - \left(1 - \tfrac{1}{B}\right)^b\right) P(\pi^*_{[B]}). \tag{12}$$

Proof. Let $\mathcal{S}^*_{[B]}$ be the optimal budget-B state subset and write $O := \mathcal{S}^*_{[B]}$ for brevity, so $|O| = B$ and $P(O) = P(\pi^*_{[B]})$. Let G_b be the greedy set after b iterations, with $G_0 = \emptyset$. We first lower bound the best marginal gain available at iteration b in terms of the current suboptimality gap.

Let $O \setminus G_b = \{o_1, \ldots, o_m\}$ where $m \leq B$. By telescoping,

$$P(G_b \cup O) - P(G_b) = \sum_{i=1}^{m} \Big(P(G_b \cup \{o_1, \ldots, o_i\}) - P(G_b \cup \{o_1, \ldots, o_{i-1}\}) \Big)$$

$$= \sum_{i=1}^{m} \Delta\big(o_i \mid G_b \cup \{o_1, \ldots, o_{i-1}\}\big). \tag{13}$$

Since $G_b \subseteq G_b \cup \{o_1, \ldots, o_{i-1}\}$ and $o_i \notin G_b \cup \{o_1, \ldots, o_{i-1}\}$, submodularity implies

$$\Delta\big(o_i \mid G_b \cup \{o_1, \ldots, o_{i-1}\}\big) \leq \Delta(o_i \mid G_b) \qquad \forall i. \tag{14}$$

Combining equation 13 and equation 14,

$$P(G_b \cup O) - P(G_b) \leq \sum_{i=1}^{m} \Delta(o_i \mid G_b) \leq m \cdot \max_{s \in \mathcal{S} \setminus G_b} \Delta(s \mid G_b) \leq B \cdot \max_{s \in \mathcal{S} \setminus G_b} \Delta(s \mid G_b). \tag{15}$$

Rearranging gives

$$\max_{s \in \mathcal{S} \setminus G_b} \Delta(s \mid G_b) \geq \frac{1}{B}\Big(P(G_b \cup O) - P(G_b) \Big). \tag{16}$$

By monotonicity, $P(G_b \cup O) \geq P(O)$, hence

$$\max_{s \in \mathcal{S} \setminus G_b} \Delta(s \mid G_b) \geq \frac{1}{B}\Big(P(O) - P(G_b) \Big). \tag{17}$$

By the greedy update rule, $\Delta(g_{b+1} \mid G_b) = \max_{s \in \mathcal{S} \setminus G_b} \Delta(s \mid G_b)$ for the selected g_{b+1}, so

$$P(G_{b+1}) - P(G_b) = \Delta(g_{b+1} \mid G_b) \geq \frac{1}{B}\Big(P(O) - P(G_b) \Big). \tag{18}$$

Define the gap $D_b := P(O) - P(G_b) \geq 0$. Then equation 18 is equivalent to

$$D_{b+1} \leq \left(1 - \frac{1}{B}\right) D_b. \tag{19}$$

Iterating,

$$D_b \leq \left(1 - \frac{1}{B}\right)^b D_0 \leq \left(1 - \frac{1}{B}\right)^b P(O), \tag{20}$$

where the last inequality uses $D_0 = P(O) - P(\emptyset) \leq P(O)$ since $P(\emptyset) \geq 0$. Therefore,

$$P(G_b) = P(O) - D_b \geq \left(1 - \left(1 - \tfrac{1}{B}\right)^b\right) P(O), \tag{21}$$

proving the stated prefix bound. Setting $b = B$ yields

$$P(G_B) \geq \left(1 - \left(1 - \tfrac{1}{B}\right)^B\right) P(O). \tag{22}$$

$\square$

That is, in the worst-case, `sequential-greedy` will achieve at least a $(1 - (1 - 1/B)^B)$-fraction of the optimal performance. In practice, we observe that the performance of `sequential-greedy` is often much closer to optimal than this worst-case bound, and in many cases is nearly indistinguishable from the optimal selection. It is worth noting that $P(\cdot)$ may not always satisfy Definition C.1 exactly.

C.4 Derivations for `adaptive-mixture` selection

Here we elaborate on the expressions involved in the discussion of the `adaptive-mixture` strategy in Section 3.

At each iteration, we set the unknown rewards to zero (as per the UDS algorithm (Yu et al., 2022)) and perform Q-learning. These Q-values can be used to estimate the performance of the current greedy-Q policy, albeit under the **partial** reward function. Specifically, define

$$J_{\text{partial}}(\pi_{[b]}) := \sum_{s \in \mathcal{S}} \eta(s) \max_a Q^{\pi_{[b]}}(s, a). \tag{23}$$

We also have access to the *true* performance of this policy, provided by the evaluator. The difference of these two quantities encodes the *unobserved reward mass*. Note that the expected return of π can expressed as

$$J(\pi) = \sum_{s \in \mathcal{S}, a \in \mathcal{A}} \sum_t d_t^{\pi_{[b]}}(s, a) R(s, a). \tag{24}$$

Subsequently, the performance under the partial reward function as obtained from $\max_a Q^{\pi_{[b]}}(s, a)$ is expressed as

$$J_{\text{partial}}(\pi_{[b]}) = \sum_{s \in \mathcal{S}, a \in \mathcal{A}} d^{\pi_{[b]}}(s, a) R_{\text{partial}}(s, a), \tag{25}$$

where

$$R_{\text{partial}}(s, a) = \begin{cases} R(s, a) & , s \in \mathcal{S}_{[b]} \\ 0 & , s \notin \mathcal{S}_{[b]} \end{cases}. \tag{26}$$

The difference between J_{partial} and J encodes

$$J(\pi_{[b]}) - J_{\text{partial}}(\pi_{[b]}) = \sum_{s \in \mathcal{S}, a \in \mathcal{A}} d^{\pi_{[b]}}(s, a) \left(R(s, a) - R_{\text{partial}}(s, a) \right) \tag{27}$$

$$= \sum_{s \notin \mathcal{S}_{[b]}, a \in \mathcal{A}} d^{\pi_{[b]}}(s, a) R(s, a). \tag{28}$$

That is, the difference represents the weighted sum of the rewards not yet observed under the current policy.

D Additional Experiments and Empirical Details

D.1 Domain Details

Table 3 summarizes the domains and their corresponding experimental setup. We study six prototypical domains (Graph, Tree, TwoRooms, TwoRooms-Trap, FrozenLake, and CliffWalk) and four large-scale MinAtar domains (Breakout, Freeway, Seaquest, and Asterix). The Graph, Tree, TwoRooms, and TwoRooms-Trap domains are custom-designed to expose structural properties relevant for analyzing reward selection strategies, while FrozenLake and CliffWalk are standard Gymnasium benchmarks (Brockman et al., 2016; Foundation, 2023).

Table 3: Summary of domains and their experimental setup.

	Prototypical Domains	**Large-scale Domains (MinAtar)**
Domain Names	Graph, Tree, TwoRooms, TwoRooms-Trap, FrozenLake, CliffWalk	Breakout, Freeway, Seaquest, Asterix
State Representation	Numeric (tabular)	Image-based (10×10 pixels)
Expert Policy	Value Iteration	Online DQN
Policy Learning Algorithm	Offline Q-learning	Implicit Q-learning (IQL)

Domain description Brief descriptions of all domains are provided below.

- **Graph**: A two-row graph structure with 8 nodes per row. In each adjacent column, the 2×2 nodes are fully connected. Transitions are deterministic; actions move the agent between rows or advance to the next column in the same row. States correspond to nodes; every movement yields a dense reward.

- **Tree**: A complete binary tree where actions correspond to moving left or right. Transitions are stochastic: the agent moves in the intended direction with 85% probability and in the alternate direction with 15%. Rewards are dense and provided at every step.

- **TwoRooms**: Two 5×5 gridworld rooms connected by a narrow bottleneck state. The agent starts in one room and must reach a goal located in the other. Rewards are sparse: zero everywhere except a reward of 1 at the goal state.

- **TwoRooms-Trap**: A variant of TwoRooms with six additional trap states. Entering a trap terminates the episode immediately with a penalty of -100. The environment otherwise shares the layout and reward structure of TwoRooms.

- **FrozenLake**: A standard Gymnasium benchmark (Brockman et al., 2016; Foundation, 2023). The agent navigates a slippery grid from start to goal, avoiding holes that cause termination. Transitions are stochastic and rewards are sparse (reward only at the goal).

- **CliffWalk**: Another Gymnasium benchmark. The agent must traverse a grid from start to goal while avoiding a high-penalty cliff region. Transitions are deterministic.

- **Minatar**: A set of simplified Atari-inspired environments with compact state and action spaces (Young & Tian, 2019). We evaluate on Breakout, Freeway, Seaquest, and Asterix.

Policy training For prototypical domains, expert policies are generated using value iteration and policies are trained with offline Q-learning. For large-scale MinAtar domains, expert policies are obtained by training online DQN agents, and offline learning uses implicit Q-learning (IQL). Prototypical domains use tabular Q-functions due to their discrete, low-dimensional state spaces, while large-scale domains rely on neural network approximators for Q-values, given their high-dimensional 10×10 image-based states.

Dataset collection Datasets are collected using a mixture-based data-collecting policy that combines expert and random actions. At each timestep, the agent follows the expert policy with probability ϵ and takes a uniformly random action with probability $1 - \epsilon$. For training, we use a single data-collecting policy with $\epsilon = 0.5$. For evaluation, five test data-collecting policies are created with $\epsilon \in \{0.55, 0.53, 0.51, 0.48, 0.45\}$ to study the robustness of learned policies under small distribution shifts.

Compute resources All experiments on prototypical domains were conducted on CPUs, while those on large-scale domains were run on GeForce RTX 2080 Tis.

D.2 Different reward-labeled-sets result in policies with varying performance

In Figure 1, we illustrate that different reward-labeled sets lead to policies with varying performance. We empirically validate this observation in two prototypical domains, Graph and Tree. For each domain, we select three percentage feedbacks (20%, 40%, and 60%), and report the average return of policies learned from all possible combinations at that budget. For example, in the Graph domain, which has 16 total states, selecting $b = 2$ yields $\binom{16}{2} = 120$ possible combinations; we report the average return across policies trained on datasets labeled by each of these 120 state sets. The results, shown in Figure 5, demonstrate that for a fixed budget, different combinations of labeled states can lead to significantly different policy performance.

Figure 5: Performance variability across different reward-labeled state sets at fixed budgets. The first row shows results for the Graph domain; the second row shows results for the Tree domain. Columns correspond to percentage feedback levels of 20%, 40%, and 60%, respectively. The results illustrate that at the same feedback level, the choice of which states are labeled strongly affects the resulting policy performance.

D.3 Additional Results for Heuristic-Based Selection

The heuristics results on all prototypical domains are shown in Table 4, which aligns with the findings we've got in Section 4.1. Results on FrozenLake and TwoRooms-Trap domains have a similar pattern to TwoRooms domain, as their reward function are all sparse, and have bottleneck states.

Table 4: Comparison of `guided`, `visitation`, and `uniform` heuristic selection strategies on prototypical domains. For each domain, the table presents the mean policy return ($\pm$ standard error) and the corresponding optimality gap (in parentheses) across five percentage feedback levels.

Domains	Percentage Feedback	guided	guided-on-policy	visitation	visitation-on-policy	uniform
Graph	0.1	3.701 ± 0.129 (3.302)	3.208 ± 0.139 (3.795)	$\mathbf{3.797 \pm 0.151}$ (**3.206**)	3.300 ± 0.142 (3.703)	2.949 ± 0.137 (4.054)
	0.3	5.831 ± 0.137 (2.169)	5.760 ± 0.127 (2.240)	$\mathbf{5.871 \pm 0.146}$ (**2.129**)	5.690 ± 0.146 (2.310)	4.617 ± 0.156 (3.383)
	0.5	7.110 ± 0.099 (0.890)	$\mathbf{7.690 \pm 0.070}$ (**0.310**)	7.199 ± 0.090 (0.801)	7.583 ± 0.086 (0.417)	5.978 ± 0.114 (2.022)
	0.7	7.830 ± 0.040 (0.170)	$\mathbf{8.000 \pm 0.000}$ (**0.000**)	7.599 ± 0.060 (0.401)	7.991 ± 0.009 (0.009)	6.920 ± 0.084 (1.080)
	0.9	$\mathbf{8.000 \pm 0.000}$ (**0.000**)	$\mathbf{8.000 \pm 0.000}$ (**0.000**)	$\mathbf{8.000 \pm 0.000}$ (**0.000**)	$\mathbf{8.000 \pm 0.000}$ (**0.000**)	$\mathbf{8.000 \pm 0.000}$ (**0.000**)
Tree	0.1	$\mathbf{8.003 \pm 0.468}$ (**9.053**)	7.403 ± 0.869 (9.653)	6.133 ± 0.428 (10.924)	4.658 ± 0.370 (12.398)	5.665 ± 0.532 (11.392)
	0.3	$\mathbf{12.846 \pm 0.373}$ (**4.921**)	12.755 ± 0.632 (5.013)	11.763 ± 0.427 (6.004)	12.601 ± 0.414 (5.167)	10.341 ± 0.524 (7.427)
	0.5	16.072 ± 0.205 (1.695)	$\mathbf{16.415 \pm 0.207}$ (**1.352**)	15.395 ± 0.297 (2.372)	16.379 ± 0.216 (1.388)	13.218 ± 0.430 (4.550)
	0.7	17.193 ± 0.083 (0.575)	$\mathbf{17.444 \pm 0.037}$ (**0.323**)	17.135 ± 0.153 (0.633)	17.174 ± 0.120 (0.594)	15.258 ± 0.312 (2.509)
	0.9	17.673 ± 0.013 (0.094)	$\mathbf{17.731 \pm 0.031}$ (**0.036**)	17.609 ± 0.158 (0.049)	17.521 ± 0.110 (0.246)	17.695 ± 0.141 (0.072)
CliffWalk	0.1	-1248.872 ± 117.272 (1152.914)	-616.760 ± 105.578 (520.803)	-1262.067 ± 119.207 (1166.109)	$\mathbf{-392.040 \pm 84.184}$ (**296.082**)	-1156.960 ± 61.025 (1061.002)
	0.3	-369.964 ± 86.539 (285.948)	-93.637 ± 0.373 (9.621)	-462.530 ± 100.633 (378.515)	$\mathbf{-92.981 \pm 0.358}$ (**8.965**)	-1274.561 ± 118.910 (1190.545)
	0.5	-132.671 ± 32.819 (57.629)	-89.390 ± 0.827 (14.348)	-165.870 ± 46.201 (90.828)	$\mathbf{-86.746 \pm 0.677}$ (**11.704**)	-1235.823 ± 137.366 (1160.781)
	0.7	-98.870 ± 0.647 (32.665)	-74.821 ± 2.171 (8.615)	-100.000 ± 0.000 (33.794)	$\mathbf{-72.995 \pm 1.872}$ (**6.790**)	-956.208 ± 136.611 (890.003)
	0.9	-72.646 ± 3.909 (59.646)	$\mathbf{-38.592 \pm 3.373}$ (**25.592**)	-100.000 ± 0.000 (87.000)	-96.819 ± 1.466 (83.819)	-425.837 ± 99.188 (412.837)
FrozenLake	0.1	0.021 ± 0.007 (-0.721)	0.056 ± 0.017 (-0.686)	0.028 ± 0.010 (-0.714)	0.020 ± 0.007 (-0.722)	$\mathbf{0.145 \pm 0.028}$ ($\mathbf{-0.598}$)
	0.3	0.087 ± 0.022 (-0.655)	0.078 ± 0.021 (-0.663)	0.079 ± 0.021 (-0.663)	0.050 ± 0.016 (-0.692)	$\mathbf{0.306 \pm 0.036}$ ($\mathbf{-0.436}$)
	0.5	0.165 ± 0.029 (-0.578)	0.127 ± 0.026 (-0.617)	0.171 ± 0.030 (-0.657)	0.086 ± 0.022 (-0.657)	$\mathbf{0.467 \pm 0.036}$ ($\mathbf{-0.276}$)
	0.7	0.261 ± 0.034 (-0.482)	0.251 ± 0.034 (-0.492)	0.326 ± 0.036 (-0.416)	0.160 ± 0.029 (-0.582)	$\mathbf{0.582 \pm 0.031}$ ($\mathbf{-0.160}$)
	0.9	0.477 ± 0.035 (-0.263)	0.508 ± 0.033 (-0.232)	0.566 ± 0.031 (-0.174)	0.427 ± 0.036 (-0.313)	$\mathbf{0.697 \pm 0.019}$ ($\mathbf{-0.043}$)
TwoRooms	0.1	0.012 ± 0.010 (0.988)	0.022 ± 0.014 (0.978)	0.042 ± 0.020 (0.959)	0.022 ± 0.014 (0.979)	$\mathbf{0.261 \pm 0.044}$ (**0.739**)
	0.3	0.077 ± 0.027 (0.923)	0.092 ± 0.029 (0.908)	0.071 ± 0.025 (0.929)	0.081 ± 0.027 (0.919)	$\mathbf{0.530 \pm 0.050}$ (**0.470**)
	0.5	0.173 ± 0.039 (0.827)	0.151 ± 0.036 (0.849)	0.182 ± 0.038 (0.818)	0.181 ± 0.038 (0.819)	$\mathbf{0.720 \pm 0.045}$ (**0.280**)
	0.7	0.270 ± 0.046 (0.730)	0.371 ± 0.048 (0.629)	0.481 ± 0.050 (0.519)	0.501 ± 0.050 (0.499)	$\mathbf{0.910 \pm 0.029}$ (**0.090**)
	0.9	0.732 ± 0.046 (0.268)	0.800 ± 0.040 (0.200)	0.870 ± 0.034 (0.130)	0.770 ± 0.042 (0.230)	$\mathbf{0.990 \pm 0.010}$ (**0.010**)
TwoRooms-Trap	0.1	-58.492 ± 0.642 (59.492)	-60.151 ± 0.673 (61.151)	-59.390 ± 1.156 (60.390)	-61.520 ± 0.723 (62.520)	$\mathbf{-46.850 \pm 2.884}$ (**47.850**)
	0.3	-45.692 ± 1.015 (46.692)	-47.391 ± 0.899 (48.391)	-47.130 ± 1.538 (48.130)	-49.960 ± 1.022 (50.960)	$\mathbf{-29.340 \pm 2.983}$ (**30.340**)
	0.5	-16.440 ± 0.968 (17.440)	-15.374 ± 0.874 (16.374)	-23.320 ± 1.396 (24.320)	-20.140 ± 0.934 (21.140)	$\mathbf{-13.270 \pm 2.261}$ (**14.270**)
	0.7	-0.336 ± 0.056 (1.336)	$\mathbf{-0.210 \pm 0.065}$ (**1.210**)	-0.300 ± 0.349 (1.300)	-0.700 ± 0.160 (1.700)	-1.600 ± 0.916 (2.600)
	0.9	$\mathbf{1.000 \pm 0.000}$ (**0.000**)	$\mathbf{1.000 \pm 0.000}$ (**0.000**)	$\mathbf{1.000 \pm 0.000}$ (**0.000**)	0.851 ± 0.040 (0.149)	$\mathbf{1.000 \pm 0.000}$ (**0.000**)

D.4 Additional Results for Training-Based Strategies

In sparse-reward environments, `brute-force` search can be accelerated by recognizing that only states with non-zero rewards must be labeled. This greatly reduces the number of combinations to consider, making exact evaluation tractable in small domains. The optimality results on all prototypical domains are shown in Table 5, where we further show the error bar of each experiment, which are omitted in Section 4.2, as the results between different seeds are almost the same, showing the robustness of optimal selection strategies.

Table 5: Performance comparison of `brute-force`, `sequential-greedy`, `adaptive-mixture` and `ES` on prototypical domains. Results are reported on training datasets, with test performance shown in parentheses (e.g., train score (test score)). Test scores are reported as mean ± standard error across five test datasets. `ES 200` corresponds to $k = 10, m = 20$ and `ES 50` to $k = 10, m = 5$.

Domains	Percentage Feedback	brute-force	sequential-greedy	ES 200	ES 50	adaptive-mixture	guided
Graph	0.1	$7.003(7.003 \pm 0.000)$	$7.003(7.003 \pm 0.000)$	$7.003(7.003 \pm 0.000)$	$4.999(4.996 \pm 0.000)$	$2.925(2.925 \pm 0.164)$	3.701
	0.3	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$6.000(6.000 \pm 0.000)$	$4.859(4.859 \pm 0.181)$	5.831
	0.5	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$7.003(7.003 \pm 0.000)$	$6.041(6.041 \pm 0.139)$	7.110
	0.7	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$6.881(6.881 \pm 0.091)$	7.830
	0.9	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	8.000
Tree	0.1	$17.056(16.773 \pm 0.000)$	$17.056(16.773 \pm 0.000)$	$12.990(12.978 \pm 0.000)$	$8.841(8.768 \pm 0.000)$	$4.573(4.528 \pm 0.408)$	8.003
	0.3	$17.767(17.592 \pm 0.017)$	$17.767(17.592 \pm 0.033)$	$17.198(17.157 \pm 0.000)$	$16.199(16.271 \pm 0.000)$	$10.720(10.614 \pm 0.463)$	12.846
	0.5	$17.767(17.629 \pm 0.020)$	$17.767(17.629 \pm 0.018)$	$17.781(17.680 \pm 0.000)$	$17.445(17.275 \pm 0.009)$	$14.190(14.049 \pm 0.357)$	16.072
	0.7	$17.767(17.649 \pm 0.000)$	$17.767(17.649 \pm 0.000)$	$17.777(17.623 \pm 0.000)$	$17.642(17.547 \pm 0.000)$	$16.343(16.181 \pm 0.218)$	17.193
	0.9	$17.767(17.657 \pm 0.000)$	$17.767(17.657 \pm 0.000)$	$17.736(17.639 \pm 0.000)$	$17.746(17.564 \pm 0.000)$	$17.661(17.486 \pm 0.100)$	17.673
CliffWalk	0.1	$-95.958(-96.081 \pm 0.001)$	$-95.958(-96.081 \pm 0.001)$	$-713.261(-714.600 \pm 0.019)$	$-1086.006(-1086.526 \pm 0.039)$	$-1119.302(-1119.302 \pm 119.548)$	-1248.872
	0.3	$-84.016(-83.986 \pm 0.001)$	$-84.016(-83.986 \pm 0.001)$	$-97.237(-97.276 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-396.573(-396.573 \pm 94.517)$	-369.964
	0.5	$-75.042(-75.059 \pm 0.001)$	$-75.042(-75.059 \pm 0.001)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-99.839(-99.839 \pm 0.084)$	-132.671
	0.7	$-66.206(-66.477 \pm 0.001)$	$-66.206(-66.477 \pm 0.001)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	-98.870
	0.9	$-13.000(-13.000 \pm 0.000)$	$-13.000(-13.000 \pm 0.000)$	$-13.000(-13.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	-72.646
FrozenLake	0.1	$0.746(0.729 \pm 0.010)$	$0.746(0.729 \pm 0.010)$	$0.742(0.728 \pm 0.009)$	$0.014(0.014 \pm 0.000)$	$0.164(0.161 \pm 0.029)$	0.021
	0.3	$0.746(0.736 \pm 0.006)$	$0.746(0.736 \pm 0.006)$	$0.738(0.702 \pm 0.010)$	$0.738(0.730 \pm 0.008)$	$0.410(0.401 \pm 0.036)$	0.087
	0.5	$0.746(0.719 \pm 0.012)$	$0.746(0.719 \pm 0.012)$	$0.740(0.731 \pm 0.009)$	$0.737(0.714 \pm 0.009)$	$0.666(0.651 \pm 0.023)$	0.165
	0.7	$0.746(0.728 \pm 0.007)$	$0.746(0.728 \pm 0.007)$	$0.733(0.730 \pm 0.010)$	$0.742(0.737 \pm 0.002)$	$0.731(0.714 \pm 0.008)$	0.261
	0.9	$0.746(0.719 \pm 0.008)$	$0.746(0.719 \pm 0.008)$	$0.739(0.740 \pm 0.001)$	$0.743(0.734 \pm 0.005)$	$0.749(0.732 \pm 0.003)$	0.477
TwoRooms	0.1	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$0.391(0.391 \pm 0.049)$	0.055
	0.3	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$0.920(0.920 \pm 0.027)$	0.109
	0.5	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$0.990(0.990 \pm 0.010)$	0.195
	0.7	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	0.270
	0.9	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	0.732
TwoRooms-Trap	0.1	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$-68.080(-68.080 \pm 0.055)$	-37.204
	0.3	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$-69.091(-69.091 \pm 0.547)$	-16.440
	0.5	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$-69.745(-69.745 \pm 0.702)$	-1.397
	0.7	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$-70.756(-70.756 \pm 0.819)$	0.966
	0.9	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$-74.307(-74.307 \pm 1.143)$	1.000

In addition to the two `ES` variants presented in Section 4.2, we provide an ablation study examining how performance varies with different numbers of samples per iteration m and iterations k. In Table 6, we fix $m = 20$ and vary k across $\{3, 5, 8, 10\}$. In Table 7, we fix $k = 10$ and vary m across $\{5, 10, 15, 20\}$. We find that larger values of $k \times m$ generally lead to better performance. Notably, increasing m (the number of samples per iteration) tends to have a greater impact than increasing k (the number of iterations), suggesting that sampling more candidates per iteration contributes more significantly to performance gains than simply running additional iterations.

Table 6: Ablation study of `ES` performance as a function of the number of iterations k (with $m = 20$ fixed). Results are reported as $k \times m$ for consistency with the main paper (e.g., `ES` 10×20 indicates $k = 10$ and $m = 20$).

Domains	Percentage Feedback	ES 10×20	ES 8×20	ES 5×20	ES 3×20
Graph	0.1	$7.003(7.003 \pm 0.000)$	$7.003(7.003 \pm 0.000)$	$7.003(7.003 \pm 0.000)$	$7.003(7.003 \pm 0.000)$
	0.3	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$
	0.5	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$
	0.7	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$
	0.9	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$
Tree	0.1	$12.990(12.978 \pm 0.000)$	$12.990(12.978 \pm 0.000)$	$12.880(12.884 \pm 0.000)$	$11.820(11.897 \pm 0.086)$
	0.3	$17.198(17.157 \pm 0.000)$	$17.329(17.111 \pm 0.000)$	$17.436(17.464 \pm 0.000)$	$16.357(16.161 \pm 0.000)$
	0.5	$17.781(17.680 \pm 0.000)$	$17.692(17.518 \pm 0.009)$	$17.583(17.535 \pm 0.000)$	$17.016(16.911 \pm 0.000)$
	0.7	$17.777(17.623 \pm 0.000)$	$17.763(17.603 \pm 0.000)$	$17.846(17.668 \pm 0.000)$	$17.721(17.552 \pm 0.000)$
	0.9	$17.736(17.639 \pm 0.000)$	$17.746(17.564 \pm 0.000)$	$17.746(17.564 \pm 0.000)$	$17.746(17.564 \pm 0.000)$
CliffWalk	0.1	$-713.261(-714.600 \pm 0.019)$	$-713.261(-714.567 \pm 0.012)$	$-767.641(-769.536 \pm 0.028)$	$-783.801(-786.146 \pm 0.021)$
	0.3	$-97.237(-97.276 \pm 0.000)$	$-97.329(-97.361 \pm 0.000)$	$-95.920(-95.841 \pm 0.001)$	$-100.000(-100.000 \pm 0.000)$
	0.5	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$
	0.7	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$
	0.9	$-13.000(-13.000 \pm 0.000)$	$-13.000(-13.000 \pm 0.000)$	$-13.000(-13.000 \pm 0.000)$	$-14.000(-13.996 \pm 0.000)$
FrozenLake	0.1	$0.742(0.728 \pm 0.009)$	$0.743(0.741 \pm 0.001)$	$0.740(0.740 \pm 0.001)$	$0.737(0.721 \pm 0.010)$
	0.3	$0.738(0.702 \pm 0.010)$	$0.740(0.727 \pm 0.006)$	$0.743(0.735 \pm 0.006)$	$0.738(0.735 \pm 0.006)$
	0.5	$0.740(0.731 \pm 0.009)$	$0.743(0.735 \pm 0.005)$	$0.740(0.710 \pm 0.011)$	$0.737(0.734 \pm 0.005)$
	0.7	$0.733(0.730 \pm 0.010)$	$0.740(0.714 \pm 0.014)$	$0.741(0.725 \pm 0.013)$	$0.739(0.710 \pm 0.008)$
	0.9	$0.739(0.740 \pm 0.001)$	$0.739(0.723 \pm 0.007)$	$0.742(0.710 \pm 0.013)$	$0.740(0.734 \pm 0.005)$
TwoRooms	0.1	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.3	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.5	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.7	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.9	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
TwoRooms-Trap	0.1	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.3	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.5	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.7	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.9	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$

Table 7: Ablation study of `ES` performance as a function of the number of samples per iteration m (with $k = 10$ fixed). Results are reported as $k \times m$ for consistency with the main paper (e.g., `ES` 10×20 indicates $k = 10$ and $m = 20$).

Domains	Percentage Feedback	ES 10×20	ES 10×15	ES 10×10	ES 10×5
Graph	0.1	$7.003(7.003 \pm 0.000)$	$5.999(6.001 \pm 0.000)$	$5.999(6.001 \pm 0.000)$	$4.999(4.996 \pm 0.000)$
	0.3	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$6.000(6.000 \pm 0.000)$
	0.5	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$7.003(7.003 \pm 0.000)$
	0.7	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$
	0.9	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$
Tree	0.1	$12.990(12.978 \pm 0.000)$	$12.754(12.301 \pm 0.116)$	$12.427(12.516 \pm 0.000)$	$8.841(8.768 \pm 0.000)$
	0.3	$17.198(17.157 \pm 0.000)$	$17.319(17.219 \pm 0.000)$	$17.082(17.015 \pm 0.002)$	$16.199(16.271 \pm 0.000)$
	0.5	$17.781(17.680 \pm 0.000)$	$17.454(17.334 \pm 0.000)$	$17.328(17.290 \pm 0.034)$	$17.445(17.275 \pm 0.009)$
	0.7	$17.777(17.623 \pm 0.000)$	$17.742(17.603 \pm 0.000)$	$17.727(17.726 \pm 0.000)$	$17.642(17.547 \pm 0.000)$
	0.9	$17.736(17.639 \pm 0.000)$	$17.736(17.639 \pm 0.000)$	$17.736(17.639 \pm 0.000)$	$17.746(17.564 \pm 0.000)$
CliffWalk	0.1	$-713.261(-714.600 \pm 0.019)$	$-755.425(-754.434 \pm 0.000)$	$-867.262(-865.682 \pm 0.021)$	$-1086.006(-1086.526 \pm 0.039)$
	0.3	$-97.237(-97.276 \pm 0.000)$	$-98.579(-98.576 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$
	0.5	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$
	0.7	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$
	0.9	$-13.000(-13.000 \pm 0.000)$	$-13.000(-13.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$
FrozenLake	0.1	$0.742(0.728 \pm 0.009)$	$0.739(0.698 \pm 0.011)$	$0.741(0.720 \pm 0.013)$	$0.014(0.014 \pm 0.000)$
	0.3	$0.738(0.702 \pm 0.010)$	$0.744(0.741 \pm 0.002)$	$0.740(0.728 \pm 0.007)$	$0.738(0.730 \pm 0.008)$
	0.5	$0.740(0.731 \pm 0.009)$	$0.739(0.723 \pm 0.009)$	$0.740(0.733 \pm 0.005)$	$0.737(0.714 \pm 0.009)$
	0.7	$0.733(0.730 \pm 0.010)$	$0.739(0.711 \pm 0.014)$	$0.739(0.722 \pm 0.006)$	$0.742(0.737 \pm 0.002)$
	0.9	$0.739(0.740 \pm 0.001)$	$0.738(0.737 \pm 0.005)$	$0.738(0.731 \pm 0.008)$	$0.743(0.734 \pm 0.005)$
TwoRooms	0.1	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.3	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.5	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.7	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.9	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
TwoRooms-Trap	0.34	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.48	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.61	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.75	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$
	0.89	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$

We also report `ES` results on large-scale MinAtar domains, using $k = 10, m = 100$ (`ES 1000`). Although the training computation of `ES` remains fixed, achieving accurate performance estimates still requires large $k \times m$ values. Even under this configuration, `ES` does not consistently outperform `guided`, illustrating the inherent difficulty of discovering optimal state sets in large state spaces even when an evaluator is available, as shown in Table 8.

In addition, Table 8 includes a column for reduced `brute-force`. By leveraging UDS, we only label the data points where rewards are non-zero. All four MinAtar domains exhibit sparse rewards, with fewer than 10% of states containing non-zero rewards. As a result, reduced `brute-force` is expected to identify a state set that achieves equivalent performance to the fully labeled dataset, while substantially reducing the labeling effort.

Table 8: Performance comparison of `ES 1000`, `adaptive-mixture` and `guided` for optimal state set selection on large-scale domains. Results are reported only on training datasets because the `guided` heuristic is defined with respect to the training dataset, and our comparison focuses on matching the settings for both methods. Although the training computation of `ES` is fixed, accurately evaluating its performance on large datasets remains costly, and small values of $k \times m$ yield poor results. Even with $k = 10, m = 100$ (denoted as `ES 1000`), `ES` does not consistently outperform `guided`. Scores are reported as mean $\pm$ standard error.

Domains	Percentage Feedback	Reduced brute-force	ES 1000	adaptive-mixture	guided
Breakout	0.15		17.75 ± 0.85	7.31 ± 0.15	7.13 ± 0.11
	0.30		17.66 ± 0.40	15.62 ± 0.29	14.12 ± 0.34
	0.45	17.75	17.75 ± 0.89	16.57 ± 0.32	17.39 ± 0.29
	0.60		17.32 ± 1.05	16.65 ± 0.33	17.60 ± 0.33
	0.75		17.46 ± 1.08	17.07 ± 0.35	16.17 ± 0.35
	0.90		17.40 ± 1.43	18.02 ± 0.34	17.06 ± 0.37
Freeway	0.15		43.44 ± 1.41	32.94 ± 0.64	42.31 ± 0.25
	0.30		55.82 ± 0.93	46.12 ± 0.39	54.01 ± 0.21
	0.45	58.28	58.28 ± 0.48	52.38 ± 0.22	58.02 ± 0.20
	0.60		58.28 ± 0.46	56.44 ± 0.17	58.28 ± 0.20
	0.75		58.28 ± 0.81	58.07 ± 0.15	58.28 ± 0.15
	0.90		58.28 ± 0.45	58.85 ± 0.20	58.28 ± 0.24
Seaquest	0.15		1.42 ± 0.26	2.09 ± 0.07	7.30 ± 0.23
	0.30		9.16 ± 1.09	4.85 ± 0.15	14.35 ± 0.47
	0.45	34.99	18.80 ± 2.25	9.50 ± 0.31	19.77 ± 0.71
	0.60		23.58 ± 3.00	16.36 ± 0.66	23.46 ± 0.80
	0.75		24.99 ± 3.44	20.75 ± 0.74	23.79 ± 0.88
	0.90		25.48 ± 3.31	24.98 ± 0.91	27.17 ± 1.04
Asterix	0.15		4.88 ± 0.74	2.60 ± 0.15	7.38 ± 0.34
	0.30		9.06 ± 1.10	7.26 ± 0.32	16.21 ± 0.65
	0.45	35.16	22.36 ± 2.45	13.86 ± 0.53	24.00 ± 0.84
	0.60		28.92 ± 2.52	25.11 ± 0.82	30.19 ± 0.91
	0.75		32.28 ± 3.03	30.50 ± 0.94	30.71 ± 0.94
	0.90		35.16 ± 2.96	33.60 ± 0.93	34.94 ± 1.01

D.5 Additional Pattern Analysis

In FrozenLake and TwoRooms-Trap, trap states can prematurely terminate episodes, leading to optimal sets focusing on avoiding trap states as well as reaching the goal. In CliffWalk, the large penalty for falling into the cliff causes optimal sets to include off-path states adjacent to the cliff, effectively constraining the agent's behavior. These effects are accentuated by the reward imputation strategy in UDS (Yu et al., 2022), which assumes unlabeled states have zero reward. Further ablation with alternative settings (e.g., Q-truncated) is shown in Appendix D.9.

To better understand the effectiveness of heuristic strategies in Breakout, we further analyze the state sets selected by `visitation` and `uniform` methods. As shown in Figure 3, `visitation` consistently outperforms `uniform` across all budget levels. To investigate this, we sampled 100 state sets from each strategy and calculated the cumulative reward present within the selected states.

Table 9 shows the average sum of rewards across these samples at varying feedback levels. The results indicate that state sets selected by `visitation` heuristics consistently contain a higher concentration of high-reward states compared to `uniform`. In Breakout, high-reward states often correspond to frames where the paddle is well-aligned with the ball to prevent it from being lost, which yields a reward of 1. The `visitation` heuristic is biased toward such frequently encountered high-value configurations during data collection, whereas `uniform` sampling provides more dispersed but less reward-focused coverage.

This quantitative observation directly supports the qualitative interpretation of the performance gap seen in Figure 3: `visitation`'s tendency to prioritize paddle-ball alignment states leads to a higher sum of rewards in the labeled dataset and therefore facilitates better value propagation during offline RL training.

Table 9: Sum of rewards in the state sets selected by `visitation` and `uniform` heuristics on Breakout. At each feedback level, we sample 100 state sets and report the mean ($\pm$ standard error) of total rewards present in the selected states. Higher values for `visitation` indicate its stronger tendency to select high-reward (paddle-ball alignment) states.

Percentage Feedback	visitation	uniform
0.146	60936.980 ± 49.963	10039.340 ± 368.025
0.291	65967.740 ± 15.982	20394.690 ± 514.998
0.437	67718.620 ± 9.163	30736.510 ± 609.436
0.583	68640.250 ± 4.266	39807.620 ± 668.318
0.728	69182.230 ± 2.760	51333.890 ± 522.632
0.874	69522.340 ± 1.531	61671.510 ± 347.499

D.6 Behaviour Policy Dependence

In the experiments below, we constructed five offline datasets in the Breakout domain using five different mixture ratios of an expert policy and a uniform-random policy, where the mixture ratio indicates the probability of following the expert policy (e.g., 0.3 means 30% expert and 70% random). We evaluate the `guided` selection strategy with both UDS (Section 2) and Adaptive Q-learning (Appendix D.9), confirming the Section 4.1 conclusion on coverage-driven performance across different datasets and including a Behavior Cloning (BC) comparison under Adaptive Q-learning.

The table below summarizes the number of unique states visited under each behavior policy ratio, which directly reflects dataset coverage:

Table 10: Unique states under different expert policy ratios.

Expert Policy Ratio	0.0	0.3	0.5	0.7	1.0
Unique States	99,254	26,255	13,731	7,110	3,535

For `guided` with UDS, we compare selective reward-labeling with a uniform-random baseline at 0%. UDS imputes all unlabeled rewards as zero, making uniform coverage an appropriate comparison for its behavior in the absence of reward labels. Guided selection quickly outperforms the naive uniform-random baseline

even at small labeling budgets, confirming the conclusion from Section 4.1, showing a robust trend across diverse datasets.

Table 11: Performance of different feedback levels under varying behavior policies with UDS.

Behavior Policy	Uniform-random (0%)	15%	30%	45%	60%	75%	90%	IQL (100%)
0.0	0.77 ± 0.06	0.51 ± 0.03	0.57 ± 0.03	0.53 ± 0.04	0.56 ± 0.04	0.70 ± 0.05	0.87 ± 0.05	0.84 ± 0.06
0.3	0.77 ± 0.06	16.27 ± 0.34	16.31 ± 0.37	17.53 ± 0.38	17.98 ± 0.34	17.83 ± 0.37	17.70 ± 0.38	17.82 ± 0.35
0.5	0.77 ± 0.06	7.13 ± 0.11	14.12 ± 0.34	17.39 ± 0.29	17.60 ± 0.33	17.17 ± 0.35	17.06 ± 0.37	17.75 ± 0.22
0.7	0.77 ± 0.06	4.26 ± 0.03	5.74 ± 0.07	6.44 ± 0.11	7.14 ± 0.10	7.27 ± 0.10	7.60 ± 0.10	7.59 ± 0.12
1.0	0.77 ± 0.06	3.24 ± 0.03	3.64 ± 0.04	5.51 ± 0.05	5.59 ± 0.06	5.64 ± 0.06	5.49 ± 0.06	5.60 ± 0.08

For `guided` with Adaptive Q-learning, we include Behavior Cloning (BC) at 0% as a reference point, representing fully supervised learning from raw trajectories without reward labeling. Guided selection with even small labeling budgets consistently outperforms BC—except when using datasets collected purely by uniform-random policies. These results also support the Section 4.1 conclusion.

Table 12: Performance of different feedback levels under varying behavior policies with Adaptive Q-learning.

Behavior Policy	BC (0%)	15%	30%	45%	60%	75%	90%	IQL (100%)
0.0	0.77 ± 0.06	0.48 ± 0.03	0.61 ± 0.05	0.81 ± 0.04	0.87 ± 0.05	0.87 ± 0.03	0.85 ± 0.06	0.82 ± 0.05
0.3	2.77 ± 1.04	16.53 ± 0.36	16.37 ± 0.38	16.88 ± 0.36	16.89 ± 0.36	16.97 ± 0.35	17.17 ± 0.36	17.77 ± 1.04
0.5	5.23 ± 0.46	14.12 ± 0.34	17.39 ± 0.29	17.60 ± 0.33	16.17 ± 0.35	17.06 ± 0.37	17.75 ± 0.22	17.49 ± 0.66
0.7	4.89 ± 0.07	5.71 ± 0.07	6.14 ± 0.09	6.69 ± 0.10	7.23 ± 0.11	7.10 ± 0.10	7.48 ± 0.11	7.98 ± 0.38
1.0	3.70 ± 0.05	4.31 ± 0.05	5.11 ± 0.05	5.47 ± 0.06	5.34 ± 0.06	5.52 ± 0.06	5.54 ± 0.06	5.46 ± 0.21

> **Takeaway**
>
> 1. The results above demonstrate that the learned policy does not degenerate to the behavior policy simply because frequently visited states are labeled. Instead, state coverage of the offline dataset is a dominant factor in final policy performance. Even when the behavior policy is weak, guided reward selection enables strong policy learning as long as coverage is sufficient.
>
> 2. Behavior Cloning (BC) is generally outperformed by guided reward selection with only 15% feedback. This confirms that the outcome of reward selection does not simply imitate the behavior policy, and that guided selection can leverage a small number of labeled rewards to learn a policy that outperforms BC, even when dataset coverage is limited, and performs even better when coverage is sufficient.

D.7 Initial Sample Sensitivity

To evaluate how the method responds to different initial state subset selections, we performed initial sample ratio experiments: a fraction of the total labeling budget was randomly allocated at the start, after which the remaining budget was spent according to the `guided` selection strategy (1st row). For comparison, we also evaluated two static baselines, `ES 50` (2nd row) and `ES 200` (3rd row), under the same initial sample ratios. Results are reported for both a dense reward domain (`Graph`, Table 13) and a sparse reward domain (`TwoRooms`, Table 14).

Across both domains, we observe that the optimal selection methods (`ES 200` and `ES 50`) generally outperform `guided` selection at equivalent budgets, as they are not penalized by suboptimal early queries and have access to the evaluator. However, the effect of initial random sampling differs by domain. In the sparse reward TwoRooms environment, larger initial samples improve early performance because random initialization has a better chance of labeling terminal states, which accelerates learning once `guided` selection begins. In contrast, in the dense reward Graph environment, larger initial samples degrade performance, as they waste labeling budget on states that `guided` selection would have efficiently deprioritized. These results

Table 13: Results across different initial sample ratios and feedback percentages on Graph domain with `guided` selection strategy.

Initial Sample Ratio	0.1	0.3	0.5	0.7	0.9
0	3.701 ± 0.129 5.001 ± 0.000 7.003 ± 0.000	5.831 ± 0.137 6.000 ± 0.000 8.000 ± 0.000	7.110 ± 0.099 7.003 ± 0.000 8.000 ± 0.000	7.830 ± 0.040 8.000 ± 0.000 8.000 ± 0.000	8.000 ± 0.000 8.000 ± 0.000 8.000 ± 0.000
0.1	3.406 ± 0.135 3.750 ± 0.140 4.120 ± 0.146	5.699 ± 0.130 5.311 ± 0.128 6.391 ± 0.127	7.041 ± 0.094 7.101 ± 0.121 7.081 ± 0.109	7.731 ± 0.049 7.532 ± 0.116 7.501 ± 0.114	8.000 ± 0.000 8.000 ± 0.000 8.000 ± 0.000
0.3	– – –	4.932 ± 0.164 6.011 ± 0.092 6.111 ± 0.087	6.531 ± 0.117 6.852 ± 0.079 7.172 ± 0.063	7.581 ± 0.062 7.401 ± 0.066 7.541 ± 0.057	8.000 ± 0.000 8.000 ± 0.000 8.000 ± 0.000
0.5	– – –	– – –	6.234 ± 0.114 6.502 ± 0.084 7.102 ± 0.067	7.399 ± 0.066 7.002 ± 0.065 7.451 ± 0.059	8.000 ± 0.000 8.000 ± 0.000 8.000 ± 0.000

Table 14: Results across different initial sample ratios and feedback percentages on the TwoRooms domain with `guided` selection strategy.

Initial Sample Ratio	0.1	0.3	0.5	0.7	0.9
0	0.012 ± 0.010 1.000 ± 0.000 1.000 ± 0.000	0.077 ± 0.027 1.000 ± 0.000 1.000 ± 0.000	0.173 ± 0.039 1.000 ± 0.000 1.000 ± 0.000	0.270 ± 0.046 1.000 ± 0.000 1.000 ± 0.000	0.732 ± 0.046 1.000 ± 0.000 1.000 ± 0.000
0.1	0.221 ± 0.041 0.321 ± 0.047 0.451 ± 0.050	0.251 ± 0.043 0.571 ± 0.049 0.770 ± 0.042	0.331 ± 0.047 0.700 ± 0.046 0.950 ± 0.022	0.511 ± 0.050 0.870 ± 0.034 0.970 ± 0.017	0.830 ± 0.038 1.000 ± 0.000 1.000 ± 0.000
0.3	– – –	– – –	0.601 ± 0.049 0.910 ± 0.029 0.950 ± 0.022	0.700 ± 0.046 0.980 ± 0.014 0.990 ± 0.010	0.880 ± 0.032 1.000 ± 0.000 1.000 ± 0.000
0.5	– – –	– – –	– – –	0.780 ± 0.041 0.850 ± 0.036 0.890 ± 0.031	0.920 ± 0.027 1.000 ± 0.000 1.000 ± 0.000

suggest that guided selection still converges to near-optimal performance once it has enough budget, even after suboptimal initial state selections.

Takeaway

The impact of initial state subset selection depends on the reward structure. In sparse reward settings, allocating more initial random labels can improve early performance by increasing the chance of covering terminal states, whereas in dense reward settings, it can hinder performance by diverting labels away from more informative regions. While `guided` selection may lag behind optimal methods a lot in the early stage, it recovers as more budget becomes available and converges to strong final policies.

D.8 Tradeoff Schedules

The `guided` strategy gradually shifts from **exploration** to **exploitation**. This shift is controlled by a **decay function** and related parameters:

1. **Decay function** determines how quickly exploration weight decreases over the course of the labeling budget.

   - **Linear decay:** exploration weight decreases at a constant rate from start to finish.
   - **Convex decay:** exploration weight decreases quickly at the start and then flattens out, prioritizing exploitation early.
   - **Concave decay:** exploration weight decreases slowly at the start and then drops quickly near the end, emphasizing exploration for longer before rapidly switching to exploitation.

2. **Decay temperature** controls how sharp or gentle the decay curve is for convex and concave schedules. A larger temperature means a steeper initial drop (for convex) or a flatter early phase (for concave).

3. **Fixed time threshold** specifies the fraction of total iterations after which exploration stops entirely, forcing the strategy to fully exploit. For example, `fixtime = 0.7` means exploration will stop only after rewards have been queried for at least 70% of all rewards in the dataset; if the total budget is smaller than that threshold, exploration is never fully turned off.

4. **Initial sample size** determines, respectively, how many states are chosen randomly before guided selection begins and how unqueried rewards are treated.

Takeaway

These parameters define how the `guided` strategy balances exploration and exploitation over time. We performed a combinational search over these settings and selected a configuration that provided good performance, which we use as the default in our experiments.

D.9 A Different Policy Update Rule

As illustrated in Figure 2, the core of this work is to propose and compare different reward selection strategies, which should be applicable to any `Alg`. While our main results focus on using UDS, in this section we apply the same selection strategies to an alternative `Alg` we propose.

D.9.1 Adapted Q-Learning

We use Q-learning—a value-based algorithm variants of which are widely used in offline settings (Levine et al., 2020; Kostrikov et al., 2021)—for policy updates in `Alg`. However, missing reward labels for some samples in `RLLF` pose a challenge: *how should the policy be updated when samples without rewards are encountered?* While assumptions might be made to facilitate modeling of unknown rewards, those reward estimates may be arbitrarily incorrect, especially in discrete domains.

Consequently, for states where rewards are unavailable (i.e., $s \notin \mathcal{S}_{[B]}$), we make no assumptions and treat the reward as being *undefined*. As a result, this algorithm sets unknown Q-values to zero, in contrast the UDS algorithm sets unknown reward values to zero. This approach aligns with the principle of *pessimism* in offline RL, which ensures that potentially erronous value estimates from *unseen* data are not used to update values of *seen* data—a strategy whose benefits are widely studied (Jin et al., 2021; Xie et al., 2021). To accommodate undefined rewards, we modify the vanilla Q-learning update rule as follows:

$$Q(s,a) \longleftarrow \begin{cases} Q(s,a) + \alpha \left(r(s,a) + \gamma * \max_{a'} Q(s',a') - Q(s,a) \right), & s \in \mathcal{S}_{[B]} \ \& \ s' \in \mathcal{S}_{[B]} \\ \alpha \, r(s,a), & s \in \mathcal{S}_{[B]} \ \& \ s' \notin \mathcal{S}_{[B]} \\ \underbrace{\text{undefined}}_{=0}, & s \notin \mathcal{S}_{[B]} \end{cases} \tag{29}$$

For $B = |\mathcal{S}|$, i.e., when all rewards are known for all states, this reduces to the standard Q-learning update rule (Sutton & Barto, 2018). For $B < |\mathcal{S}|$, this update rule yields a *truncated* estimate of the standard Q-values, with a corresponding *truncated* Bellman operator. To distinguish these Q-values from the standard definition, we use $\tilde{Q}$ to denote Q-values estimated from the update rule in Equation 29.

The values $\tilde{Q}(s,a)$ are only defined for states $s \in \mathcal{S}_{[B]}$. Consequently, a greedy policy derived from the truncated Q-values can only be defined for $s \in \mathcal{S}_{[B]}$. For states $s \notin \mathcal{S}_{[B]}$, there is no reward feedback is available and $\tilde{Q}(s,a)$ is undefined, and we cannot evaluate the varying effects of actions in those states. In the absence of any evaluative signal for actions, we default to the data collecting policy π_D at those states.

$$\pi_{[B]} = \pi_{[\mathcal{S}_{[B]}]} = \begin{cases} \arg\max_a \tilde{Q}(s,a), & s \in \mathcal{S}_{[B]} \\ \pi_D, & s \notin \mathcal{S}_{[B]} \end{cases} \tag{30}$$

This update scheme is denoted by `Alg`, and the policy output by `Alg`$(\mathcal{D}, \mathcal{S}_{[B]})$ is denoted by $\pi_{[B]}$, or equivalently, $\pi_{[\mathcal{S}_{[B]}]}$ when emphasizing the dependence on $\mathcal{S}_{[B]}$. Policy updates only occur at states $s \in \mathcal{S}_{[B]}$. Selecting a set of states to label with reward amounts determines states at which the policy gets updated—potentially to differ from the data-collecting policy—and the strategy for selecting these states $\mathcal{Q}^{(B)}$ to optimize Equation equation 1 is the focus of the following sections.

D.9.2 Performance of Heuristic-based Selection Strategies

We evaluate `guided`, `visitation`, and `uniform` selection strategies under Adapted Q-Learning on small domains as shown in the Table 15. The trends largely align with the findings in the main text and remain consistent with those observed under UDS. In domains such as Graph, Tree, CliffWalk, and TwoRooms-Trap, where the optimal policy follows a narrow set of trajectories, path-following methods (`guided` and `visitation`) perform best. In contrast, TwoRooms and FrozenLake contain multiple viable paths to the goal, making broader state coverage more advantageous; here, `uniform` selection achieves superior results. Adaptive Q-Learning confirms the strong dependence of heuristic effectiveness on domain characteristics, including transition determinism, reward sparsity, and bottleneck structures (as discussed in Section 4.1).

Table 15: Comparison of `guided`, `visitation`, and `uniform` heuristic selection strategies on prototypical domains. For each domain, the table presents the mean policy return (± standard error) and the corresponding optimality gap (in parentheses) across five percentage feedback levels.

Domains	Percentage Feedback	guided	visitation	uniform
Graph	0.1	**4.477 ± 0.040 (0.860)**	4.397 ± 0.036 (0.940)	4.171 ± 0.040 (1.166)
	0.3	**5.616 ± 0.069 (1.549)**	5.480 ± 0.068 (1.685)	5.048 ± 0.062 (2.117)
	0.5	**6.604 ± 0.098 (1.396)**	6.385 ± 0.101 (1.615)	5.697 ± 0.081 (2.303)
	0.7	**7.502 ± 0.086 (0.498)**	7.229 ± 0.093 (0.771)	6.019 ± 0.127 (1.981)
	0.9	**8.000 ± 0.000 (0.000)**	**8.000 ± 0.000 (0.000)**	**8.000 ± 0.000 (0.000)**
Tree	0.1	**8.300 ± 0.144 (3.424)**	8.059 ± 0.116 (3.665)	6.753 ± 0.076 (4.971)
	0.3	**13.317 ± 0.337 (3.608)**	12.126 ± 0.238 (4.798)	8.484 ± 0.134 (8.440)
	0.5	**16.120 ± 0.183 (1.340)**	14.917 ± 0.277 (2.543)	10.445 ± 0.240 (7.014)
	0.7	**17.354 ± 0.041 (0.269)**	16.870 ± 0.151 (0.753)	11.637 ± 0.343 (5.985)
	0.9	**17.689 ± 0.012 (0.030)**	17.675 ± 0.012 (0.016)	16.280 ± 0.292 (1.379)
CliffWalk	0.1	**−414.059 ± 7.923 (171.814)**	**−414.059 ± 7.923 (171.814)**	−488.198 ± 6.642 (245.953)
	0.3	**−236.441 ± 18.131 (136.441)**	−237.081 ± 18.171 (137.081)	−433.176 ± 15.181 (333.176)
	0.5	−155.088 ± 13.893 (55.088)	**−154.042 ± 13.888 (54.042)**	−409.481 ± 20.146 (309.481)
	0.7	−123.490 ± 7.651 (92.459)	**−100.437 ± 0.881 (69.406)**	−378.334 ± 24.350 (347.302)
	0.9	−146.676 ± 11.375 (132.023)	**−107.590 ± 5.313 (92.937)**	−341.785 ± 27.414 (327.131)
FrozenLake	0.1	0.024 ± 0.000 (0.010)	**0.024 ± 0.000 (0.010)**	0.024 ± 0.000 (0.010)
	0.3	0.024 ± 0.000 (0.048)	0.024 ± 0.000 (0.048)	**0.025 ± 0.001 (0.047)**
	0.5	0.024 ± 0.000 (0.222)	0.023 ± 0.000 (0.223)	**0.027 ± 0.001 (0.218)**
	0.7	0.073 ± 0.015 (0.595)	0.036 ± 0.007 (0.631)	**0.098 ± 0.014 (0.569)**
	0.9	**0.374 ± 0.030 (0.336)**	0.267 ± 0.025 (0.443)	0.368 ± 0.026 (0.341)
TwoRooms	0.1	0.025 ± 0.001 (0.289)	0.025 ± 0.001 (0.289)	**0.030 ± 0.001 (0.283)**
	0.3	0.013 ± 0.001 (0.939)	0.012 ± 0.001 (0.939)	**0.033 ± 0.003 (0.919)**
	0.5	0.007 ± 0.000 (0.992)	0.008 ± 0.000 (0.992)	**0.043 ± 0.005 (0.956)**
	0.7	0.159 ± 0.035 (0.841)	0.085 ± 0.027 (0.915)	**0.230 ± 0.034 (0.770)**
	0.9	0.721 ± 0.044 (0.279)	**0.761 ± 0.043 (0.239)**	0.720 ± 0.042 (0.280)
TwoRooms-Trap	0.1	**−55.947 ± 0.920 (32.444)**	−57.720 ± 0.628 (34.217)	−62.899 ± 0.487 (39.396)
	0.3	**−41.188 ± 1.123 (39.950)**	−44.392 ± 0.832 (43.154)	−53.528 ± 0.692 (52.290)
	0.5	**−14.334 ± 0.837 (14.872)**	−21.868 ± 0.894 (22.406)	−40.030 ± 0.837 (40.568)
	0.7	**−0.178 ± 0.057 (1.176)**	−1.001 ± 0.332 (1.999)	−26.138 ± 0.966 (27.136)
	0.9	**1.000 ± 0.000 (0.000)**	**1.000 ± 0.000 (0.000)**	−4.577 ± 0.689 (5.577)

D.9.3 Performance of Optimal Selection Strategy

We evaluate `brute-force`, `sequential-greedy`, `ES 200`, and `ES 50` under Adaptive Q-Learning with the same setting as in the main text shown in Table 16. The findings closely mirror those observed with UDS. `Sequential-greedy` consistently matches the performance of `brute-force`, validating its effectiveness as a scalable approximation to the true optimal state set. `ES 200` reliably outperforms `ES 50`, and both evolutionary variants generally exceed the performance of `guided` selection at moderate to high budgets. These results reaffirm the relative ordering and conclusions reported in the main text, demonstrating that the effectiveness of optimized selection strategies remains stable across different policy learning algorithms.

Table 16: Performance comparison of `brute-force`, `sequential-greedy`, `adaptive-mixture` and `ES` on prototypical domains. Results are reported on training datasets, with test performance shown in parentheses (e.g., train score (test score)). Test scores are reported as mean $\pm$ standard error across five test datasets. `ES 200` corresponds to $k = 10, m = 20$ and `ES 50` to $k = 10, m = 5$.

Domains	Percentage Feedback	brute-force	sequential-greedy	ES 200	ES 50	adaptive-mixture	guided
Graph	0.1	$5.337(3.032 \pm 0.213)$	$5.337(3.032 \pm 0.213)$	$5.308(3.014 \pm 0.211)$	$4.214(1.521 \pm 0.226)$	$4.575(4.357 \pm 0.042)$	4.477
	0.3	$7.165(6.004 \pm 0.128)$	$7.165(6.004 \pm 0.128)$	$7.157(5.994 \pm 0.124)$	$6.275(4.518 \pm 0.164)$	$5.574(5.465 \pm 0.071)$	5.616
	0.5	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$6.589(5.256 \pm 0.115)$	$6.257(6.195 \pm 0.108)$	6.604
	0.7	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$6.735(6.735 \pm 0.123)$	7.502
	0.9	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	$8.000(8.000 \pm 0.000)$	8.000
Tree	0.1	$11.724(8.092 \pm 0.276)$	$11.724(8.092 \pm 0.276)$	$11.724(8.092 \pm 0.276)$	$9.073(4.078 \pm 0.384)$	$8.447(8.201 \pm 0.107)$	8.300
	0.3	$16.925(16.349 \pm 0.056)$	$16.925(16.349 \pm 0.056)$	$13.282(10.283 \pm 0.238)$	$9.637(5.187 \pm 0.334)$	$12.526(12.280 \pm 0.249)$	13.317
	0.5	$17.460(17.406 \pm 0.017)$	$17.460(17.406 \pm 0.017)$	$17.235(16.982 \pm 0.025)$	$12.656(9.909 \pm 0.184)$	$15.088(14.939 \pm 0.254)$	16.120
	0.7	$17.623(17.627 \pm 0.006)$	$17.623(17.627 \pm 0.006)$	$17.513(17.489 \pm 0.009)$	$15.217(13.324 \pm 0.142)$	$16.792(16.792 \pm 0.154)$	17.354
	0.9	$17.659(17.788 \pm 0.001)$	$17.659(17.788 \pm 0.001)$	$17.678(17.777 \pm 0.000)$	$17.655(17.728 \pm 0.001)$	$17.588(17.588 \pm 0.017)$	17.689
CliffWalk	0.1	$-242.245(-231.272 \pm 6.042)$	$-242.245(-231.272 \pm 6.042)$	$-322.823(-347.828 \pm 12.005)$	$-409.384(-414.365 \pm 26.537)$	$-374.158(-374.158 \pm 7.375)$	-414.059
	0.3	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-150.081(-150.586 \pm 4.002)$	$-320.748(-308.868 \pm 13.555)$	$-222.695(-222.695 \pm 10.372)$	-236.441
	0.5	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-180.969(-189.833 \pm 3.670)$	$-142.029(-142.029 \pm 10.554)$	-155.088
	0.7	$-31.031(-31.142 \pm 1.045)$	$-31.031(-31.142 \pm 1.045)$	$-100.000(-100.000 \pm 0.000)$	$-186.756(-180.828 \pm 8.232)$	$-103.315(-103.315 \pm 2.346)$	-123.490
	0.9	$-14.653(-14.506 \pm 0.138)$	$-14.653(-14.506 \pm 0.138)$	$-100.000(-100.000 \pm 0.000)$	$-100.000(-100.000 \pm 0.000)$	$-99.329(-99.329 \pm 0.671)$	-146.676
FrozenLake	0.1	$0.034(0.032 \pm 0.001)$	$0.034(0.032 \pm 0.001)$	$0.031(0.030 \pm 0.000)$	$0.031(0.030 \pm 0.001)$	$0.025(0.024 \pm 0.000)$	0.024
	0.3	$0.072(0.049 \pm 0.003)$	$0.072(0.049 \pm 0.003)$	$0.036(0.032 \pm 0.001)$	$0.032(0.034 \pm 0.001)$	$0.027(0.026 \pm 0.001)$	0.024
	0.5	$0.246(0.347 \pm 0.029)$	$0.246(0.347 \pm 0.029)$	$0.067(0.057 \pm 0.004)$	$0.054(0.045 \pm 0.005)$	$0.048(0.047 \pm 0.002)$	0.024
	0.7	$0.667(0.629 \pm 0.011)$	$0.667(0.629 \pm 0.011)$	$0.199(0.212 \pm 0.006)$	$0.196(0.223 \pm 0.008)$	$0.136(0.132 \pm 0.013)$	0.073
	0.9	$0.710(0.688 \pm 0.013)$	$0.710(0.688 \pm 0.013)$	$0.679(0.703 \pm 0.006)$	$0.699(0.709 \pm 0.013)$	$0.405(0.397 \pm 0.022)$	0.374
TwoRooms	0.1	$0.314(0.321 \pm 0.031)$	$0.314(0.321 \pm 0.031)$	$0.063(0.073 \pm 0.014)$	$0.038(0.046 \pm 0.009)$	$0.041(0.041 \pm 0.001)$	0.025
	0.3	$0.952(0.952 \pm 0.005)$	$0.952(0.952 \pm 0.005)$	$0.310(0.314 \pm 0.029)$	$0.052(0.057 \pm 0.009)$	$0.083(0.083 \pm 0.003)$	0.013
	0.5	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$0.365(0.362 \pm 0.026)$	$0.270(0.270 \pm 0.022)$	$0.142(0.142 \pm 0.006)$	0.007
	0.7	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$0.999(1.000 \pm 0.000)$	$0.161(0.161 \pm 0.010)$	0.159
	0.9	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$0.227(0.227 \pm 0.025)$	0.721
TwoRooms-Trap	0.1	$-23.503(-23.047 \pm 0.319)$	$-23.503(-23.047 \pm 0.319)$	$-31.646(-32.431 \pm 0.736)$	$-53.449(-53.509 \pm 0.204)$	$-78.194(-78.194 \pm 0.260)$	-55.947
	0.3	$-1.238(-1.243 \pm 0.017)$	$-1.238(-1.243 \pm 0.017)$	$-11.259(-10.935 \pm 0.174)$	$-35.621(-35.996 \pm 0.556)$	$-74.272(-74.272 \pm 0.362)$	-41.188
	0.5	$0.538(0.540 \pm 0.016)$	$0.538(0.540 \pm 0.016)$	$-0.845(-0.793 \pm 0.030)$	$-17.590(-17.505 \pm 0.139)$	$-71.596(-71.596 \pm 0.271)$	-14.334
	0.7	$0.998(0.998 \pm 0.000)$	$0.998(0.998 \pm 0.000)$	$-0.233(-0.258 \pm 0.024)$	$-14.739(-14.826 \pm 0.245)$	$-70.275(-70.275 \pm 0.556)$	-0.178
	0.9	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$1.000(1.000 \pm 0.000)$	$0.862(0.845 \pm 0.010)$	$-74.351(-74.351 \pm 1.224)$	1.000