WHO IS YOUR RIGHT MIXUP PARTNER IN POSITIVE AND UNLABELED LEARNING

ABSTRACT

Positive and Unlabeled (PU) learning targets inducing a binary classifier from weak training datasets of positive and unlabeled instances, which arise in many real-world applications. In this paper, we propose a novel PU learning method, namely Positive and unlabeled learning with Partially Positive Mixup (P³Mix), which simultaneously benefits from data augmentation and supervision correction with a heuristic mixup technique. To be specific, we take inspiration from the directional boundary deviation phenomenon observed in our preliminary experiments, where the learned PU boundary tends to deviate from the fully supervised boundary towards the positive side. For the unlabeled instances with ambiguous predictive results, we select their mixup partners from the positive instances around the learned PU boundary, so as to transform them into augmented instances near to the boundary yet with more precise supervision. Accordingly, those augmented instances may push the learned PU boundary towards the fully supervised boundary, thereby improving the classification performance. Comprehensive experimental results demonstrate the effectiveness of the heuristic mixup technique in PU learning and show that P³Mix can consistently outperform the state-of-the-art PU learning methods.

1 INTRODUCTION

Positive and **U**nlabeled (**PU**) learning refers to a specific binary classification problem, where only a small number of positive training instances are manually annotated but all other instances are unlabeled (Liu et al., 2002). Such kind of datasets naturally arise in many significant real-world scenarios such as product recommendation (Hsieh et al., 2015), deceptive reviews detection (Ren et al., 2014), and medical diagnosis (Yang et al., 2012). For specific example, many diseases, *e.g.,* Alzheimer's disease, Amyotrophic Lateral Sclerosis, and Parkinson's disease, are very infrequent and with long latency, hence only few diagnosed patients are known but a much larger population of undiagnosed individuals may be either diseased or healthy. Treating the diagnosed ones as positive instances and the undiagnosed ones as unlabeled instances results in such PU datasets of medical diagnosis. To meet those practical demands, PU learning has drawn increasing interest from the machine learning community (Bekker & Davis, 2020).

Formally, let $\mathbf{x} \in \mathbb{R}^d$ and $y \in \{0, 1\}$ be the feature representation and category label, respectively, where the positive instance is indicated by $y = 1$ and the negative one by $y = 0$. In the context of PU learning, the training dataset is composed of the sets of positive instances $\mathcal{P} = \{(\mathbf{x}_i, y_i = 1)\}_{i=1}^{n_p}$ and unlabeled instances $\mathcal{U} = \{\mathbf{x}_i\}_{i=n_p+1}^{n_p+n_u}$, where $\mathcal{U}$ contains both positive and negative instances. The target is to learn a binary classifier based on such weak training dataset $\mathcal{P} \cup \mathcal{U}$.

During the past decades, many PU learning methods have been proposed, where, naturally, the essential idea is to estimate the negative instances from the set of unlabeled instances $\mathcal{U}$. Generally, most of existing PU learning methods can be divided into two categories, termed as sample-selection methods and cost-sensitive methods. The sample-selection methods, as the name suggests, mainly select reliable negative instances from $\mathcal{U}$ using various heuristic strategies, *e.g.,* Naïve Bayes (Liu et al., 2002), kNN (Zhang & Zuo, 2009), k-means (Chaudhari & Shevade, 2012), and reinforcement learning (Luo et al., 2021); and then apply supervised methods over positive and those reliable negative instances. In contrast, the cost-sensitive methods treat all unlabeled instances as corrupted negative ones, and correct the estimation bias of the objective by employing well-designed misclas-

Figure 1: Rates of training instances Predicted as Positive (PP rate) and error rates of disambiguation-free[1] and fully supervised objectives on (a) FashionMNIST and (b) CIFAR-10 (Xiao et al., 2017; Krizhevsky, 2016; Chen et al., 2020a). The disambiguation-free objective suffers from much lower PP rates than the real positive prior as well as the fully supervised objective. This implies the directional boundary deviation phenomenon, which results in higher error rates.

sification risks such as unbiased risk estimator (du Plessis et al., 2014; 2015; Kiryo et al., 2017) and maximum margin loss (Shi et al., 2018; Gong et al., 2019b; Zhang et al., 2019; Gong et al., 2019a).

Orthogonal to the aforementioned techniques, we note that some PU learning methods such as (Chen et al., 2020a; Wei et al., 2020) have made preliminary attempts to integrate with the art of mixup, *i.e.,* an economic-yet-effective data augmentation method (Zhang et al., 2018). Formally, mixup generates an augmented instance $(\widehat{\mathbf{x}}, \widehat{y})$ with the convex combination of any pair of instances $\{(\mathbf{x}_i, y_i), (\mathbf{x}_j, y_j)\}$ drawn from the training dataset:

$$\widehat{\mathbf{x}} = \lambda\mathbf{x}_i + (1-\lambda)\mathbf{x}_j, \quad \widehat{y} = \lambda y_i + (1-\lambda)y_j, \qquad \lambda \sim \text{Beta}(\alpha, \alpha), \ \alpha \in (0, \infty).$$

Previous studies have indicated that mixup is approximately equivalent to applying adversarial training (Zhang et al., 2021), enabling to improve robustness with even scarce and noisy supervision (Thulasidasan et al., 2019; Carratino et al., 2020; Zhang et al., 2021). Accordingly, it has been successfully used to solve various learning problems with weak supervision, *e.g.,* semi-supervised learning (Berthelot et al., 2019), noisy label learning (Li et al., 2020), and partial label learning (Yan & Guo, 2020).

Our story and contribution. Inspired by the recent success of mixup in learning with weak supervision, our original goal is to thoroughly investigate the impact of mixup in PU learning. To this end, we begin with a naive *disambiguation-free* objective of PU learning, where all unlabeled instances are treated as *pseudo-negative instances*, denoted by $\widetilde{\mathcal{U}} = \{(\mathbf{x}_i, y_i = 0)\}_{i=n_p+1}^{n_p+n_u}$, and the binary classifier is trained based on $\mathcal{P} \cup \widetilde{\mathcal{U}}$. In preliminary experiments, we found an interesting phenomenon, where the number of training instances predicted as positive by the disambiguation-free classifier tends to be smaller than usual as illustrated in Fig.1. This phenomenon implies that the disambiguation-free boundary tends to deviate from the fully supervised boundary towards the positive side, expressed by a toy example shown in Fig.2(a). We consider that the directional boundary deviation is mainly caused by the *marginal pseudo-negative instances*, which lie between the two boundaries. Such instances are more likely to be positive but actually annotated by negative.

---

[1]Specially, we apply the early learning regularization (Liu et al., 2020) into the objective to keep it stable.

Figure 2: Toy examples of (a) the directional boundary deviation phenomenon and (b) the proposed heuristic mixup for marginal pseudo-negative instances. Best viewed in color.

Motivated by this observation, we extend mixup to a specific heuristic version for PU learning, enabling to achieve data augmentation and supervision correction simultaneously. Its basic idea is to transform the marginal pseudo-negative instances into augmented instances which are partially positive and yet also lie between the two boundaries, so as to push the learned boundary towards the fully supervised one. This can be achieved by selecting the mixup partners for marginal pseudo-negative instances from the positive instances that are around the learned boundary, as expressed in Fig.2(b). With this insight, we propose a novel PU method, namely **P**ositive and unlabeled learning with **P**artially **P**ositive **Mix**up (**P³Mix**). Generally, P³Mix is easy-to-implement, where, specifically, we can define the marginal pseudo-negative instances using the predictive results and the positive instances around the boundary using the entropy values of predictive results. To evaluate the effectiveness of P³Mix, we conduct a number of experiments on benchmark datasets. Experimental results demonstrate that P³Mix can consistently outperform the state-of-the-art PU methods.

2 THE PROPOSED P³MIX METHOD

In this section, we introduce the proposed **P³Mix** method for PU learning. We first revisit and clarify some important notations: the set of positive instances $\mathcal{P} = \{(\mathbf{x}_i, y_i = 1)\}_{i=1}^{n_p}$ and the set of unlabeled instances $\mathcal{U} = \{\mathbf{x}_i\}_{i=n_p+1}^{n_p+n_u}$. By treating all unlabeled instances as negative, we translate $\mathcal{U}$ into the set of pseudo-negative instances $\widetilde{\mathcal{U}} = \{(\mathbf{x}_i, y_i = 0)\}_{i=n_p+1}^{n_p+n_u}$. Given batches $\mathcal{X}_p \subset \mathcal{P}$ and $\mathcal{X}_u \subset \widetilde{\mathcal{U}}$, the disambiguation-free objective of PU learning can be formulated as follows:

$$\mathcal{L}(\mathcal{X}_p, \mathcal{X}_u; \mathbf{\Theta}) = \frac{1}{|\mathcal{X}_p|} \sum_{(\mathbf{x},y) \in \mathcal{X}_p} \ell\big(f(\mathbf{x}; \mathbf{\Theta}), y\big) + \frac{\beta}{|\mathcal{X}_u|} \sum_{(\mathbf{x},y) \in \mathcal{X}_u} \ell\big(f(\mathbf{x}; \mathbf{\Theta}), y\big), \quad (1)$$

where $f(\cdot; \mathbf{\Theta})$ is a trainable neural network, *i.e.*, the binary classifier, parameterized by $\mathbf{\Theta}$; $\ell(\cdot, \cdot)$ is the loss function; and β is the coefficient parameter.

To achieve data augmentation and supervision correction simultaneously, P³Mix transforms $\mathcal{X}_p$ and $\mathcal{X}_u$ into the batches of augmented instances $\widehat{\mathcal{X}}_p$ and $\widehat{\mathcal{X}}_u$ using the proposed heuristic mixup technique. Accordingly, the objective of P³Mix is then expressed as follows:

$$\mathcal{L}(\widehat{\mathcal{X}}_p, \widehat{\mathcal{X}}_u; \mathbf{\Theta}) = \frac{1}{|\widehat{\mathcal{X}}_p|} \sum_{(\widehat{\mathbf{x}},\widehat{y}) \in \widehat{\mathcal{X}}_p} \ell\big(f(\widehat{\mathbf{x}}; \mathbf{\Theta}), \widehat{y}\big) + \frac{\beta}{|\widehat{\mathcal{X}}_u|} \sum_{(\widehat{\mathbf{x}},\widehat{y}) \in \widehat{\mathcal{X}}_u} \ell\big(f(\widehat{\mathbf{x}}; \mathbf{\Theta}), \widehat{y}\big), \quad (2)$$

$$\widehat{\mathcal{X}}_p, \widehat{\mathcal{X}}_u = \text{HeuristicMixup}(\mathcal{X}_p, \mathcal{X}_u, \alpha), \quad (3)$$

where $\alpha \in (0, \infty)$ is a hyperparameter of mixup. Next, we describe the details of heuristic mixup.

Algorithm 1 Training procedure of P^{3}Mix

Input:
  $\mathcal{P} \cup \mathcal{U}$: training instances; β: coefficient parameter; γ: thresholding parameter; k: size of the candidate mixup pool; α: hyperparameter of mixup

Output:
  $\boldsymbol{\Theta}$: binary classifier parameters

1: **Initialize $\boldsymbol{\Theta}$** and the candidate mixup pool $\mathcal{X}_{cnd}$ randomly, translate $\mathcal{U}$ into $\widetilde{\mathcal{U}}$;
2: **for** $t = 1, 2, \cdots, MaxEpoch$ **do**
3:     Shuffle $\mathcal{P} \cup \widetilde{\mathcal{U}}$ into I mini-batches and denote the i-th mini-batch by $(\mathcal{X}_p^i, \mathcal{X}_u^i)$;
4:     **for** $i = 1, 2, \cdots, I$ **do**
5:         Estimate marginal pseudo-negative instances $\mathcal{X}_{mpn}$ using Eq.(6);
6:         Select the mixup partners for each instance within $\mathcal{X}_p^i \cup \mathcal{X}_u^i$ using Eq.(5);
7:         Construct $\widehat{\mathcal{X}}_p^i \cup \widehat{\mathcal{X}}_u^i$ by applying Eq.(4) to $\mathcal{X}_p^i \cup \mathcal{X}_u^i$ and their mixup partners;
8:         Update $\boldsymbol{\Theta}$ by its gradient $\nabla_{\boldsymbol{\Theta}} \mathcal{L}(\widehat{\mathcal{X}}_p^i, \widehat{\mathcal{X}}_u^i; \boldsymbol{\Theta})$ with the Adam optimizer;
9:     **end for**
10:     Update $\mathcal{X}_{cnd}$ using Eq.(7);
11: **end for**

2.1 TRAINING WITH HEURISTIC MIXUP

Basically, for each instance $(\mathbf{x}_i, y_i) \in \mathcal{X}_p \cup \mathcal{X}_u$ we select a mixup partner $(\mathbf{x}_j, y_j)$ to generate an augmented instance $(\widehat{\mathbf{x}}_i, \widehat{y}_i)$ using the modified mixup operator[2] (Berthelot et al., 2019):

$$\widehat{\mathbf{x}}_i = \lambda' \mathbf{x}_i + (1 - \lambda') \mathbf{x}_j, \quad \widehat{y}_i = \lambda' y_i + (1 - \lambda') y_j, \quad \lambda' = \max(\lambda, 1 - \lambda),$$
$$\lambda \sim \text{Beta}(\alpha, \alpha), \quad \alpha \in (0, \infty), \quad (4)$$

accordingly forming the augmented instance sets $\widehat{\mathcal{X}}_p$ and $\widehat{\mathcal{X}}_u$.

Our heuristic mixup refers to a guidance of mixup partner selection to refine the imprecise supervision within $\mathcal{X}_u$. We take inspiration from the phenomenon, where the boundary learned by Eq.(1) tends to deviate from the fully supervised boundary towards the positive side as illustrated in Fig.2(a). The marginal pseudo-negative instances $\mathcal{X}_{mpn} \subset \mathcal{X}_u$ lie between the two boundaries, and they are more likely to be positive but actually annotated by negative. To resolve this problem, for each of them we uniformly select a mixup partner from the *candidate mixup pool* $\mathcal{X}_{cnd} \subset \mathcal{P}$ of positive instances that are around the current learned boundary, so as to generate an augmented instance which is partially positive and yet also lies between the two boundaries as expressed in Fig.2(b). Besides, for positive instances $\mathcal{X}_p$ and other pseudo-negative instances $\mathcal{X}_u \setminus \mathcal{X}_{mpn}$, we uniformly choose their mixup partners from $\mathcal{X}_p \cup \mathcal{X}_u$ The overall mixup partner selection is formulated as follows:

$$(\mathbf{x}_j, y_j) \sim \begin{cases} \text{Uniform}(\mathcal{X}_{cnd}) & \text{if } (\mathbf{x}_i, y_i) \in \mathcal{X}_{mpn}, \\ \\ \text{Uniform}(\mathcal{X}_p \cup \mathcal{X}_u) & \text{if } (\mathbf{x}_i, y_i) \in \mathcal{X}_p \cup \mathcal{X}_u \setminus \mathcal{X}_{mpn}. \end{cases} \quad (5)$$

In what follows, we introduce how to estimate the marginal pseudo-negative instances $\mathcal{X}_{mpn}$ and construct the candidate mixup pool $\mathcal{X}_{cnd}$.

Marginal pseudo-negative instance estimation. Because the fully supervised boundary is exactly unknown, we have to estimate the set of marginal pseudo-negative instances $\mathcal{X}_{mpn}$ from $\mathcal{X}_u$. In this work, we define them as the "unreliable" pseudo-negative instances measured by the predictive scores with thresholding parameter $\gamma \in [0.5, 1]$:

$$\mathcal{X}_{mpn} = \big\{ (\mathbf{x}, y = 0) | (\mathbf{x}, y = 0) \in \mathcal{X}_u, 1 - \gamma \leq f(\mathbf{x}; \boldsymbol{\Theta}) \leq \gamma \big\}, \quad (6)$$

where $\gamma = 0.5$ implies $\mathcal{X}_{mpn} = \emptyset$, and $\gamma = 1$ means $\mathcal{X}_{mpn} = \mathcal{X}_u$.

---

[2]Because we compute individual loss terms for positive instances and pseudo-negative ones in Eq.(2) appropriately, we define $\lambda' = \max(\lambda, 1 - \lambda)$ to guarantee that the feature of each augmented instance $\widehat{\mathbf{x}}_i$ is closer to $\mathbf{x}_i$ than the mixup partner $\mathbf{x}_j$.

Candidate mixup pool. We maintain a candidate mixup pool $\mathcal{X}_{cnd}$ containing the positive instances around the current learned boundary from $\mathcal{P}$. To be specific, for each positive instance we compute its entropy value of the predictive score, and update the candidate mixup pool with the top-k positive instances as follows:

$$\mathcal{X}_{cnd} = \left\{ (\mathbf{x}, y = 1) | (\mathbf{x}, y = 1) \in \mathcal{P}, \mathcal{H}(f(\mathbf{x}; \mathbf{\Theta})) \in \text{Rank}(\{\mathcal{H}(f(\mathbf{x}_i; \mathbf{\Theta}))\}_{i=1}^{n_p}) \right\}, \qquad (7)$$

where $\mathcal{H}(\cdot)$ is the entropy, and $\text{Rank}(\cdot)$ outputs a set of positive instances with the top-k maximum entropy values. For efficiency, we update $\mathcal{X}_{cnd}$ in every epoch. The full training procedure is shown in *Algorithm 1*.

2.2 ROBUSTNESS

The augmented instances within $\widehat{\mathcal{X}}_u$ also suffer from imprecise supervision even using the heuristic mixup. To make P³Mix more robust, we employ two tricks, *i.e.,* early-learning regularization (Liu et al., 2020) and pseudo-negative instance correction.

Early-learning regularization. We employ the early learning regularization to prevent the memorization of imprecise supervision (Liu et al., 2020). For each mixup instance within $\widehat{\mathcal{X}}_p \cup \widehat{\mathcal{X}}_u$, we estimate an auxiliary target vector $\widetilde{\mathbf{y}}$, and formulate the early-learning regularization below:

$$\mathcal{R}_{elr}(\{(\widehat{\mathbf{x}}_i, \widetilde{\mathbf{y}}_i)\}_{i=1}^{|\widehat{\mathcal{X}}_p|+|\widehat{\mathcal{X}}_u|}; \mathbf{\Theta}) = \frac{1}{|\widehat{\mathcal{X}}_p|+|\widehat{\mathcal{X}}_u|} \sum_{i=1}^{|\widehat{\mathcal{X}}_p|+|\widehat{\mathcal{X}}_u|} \log\left(1 - \langle f(\widehat{\mathbf{x}}_i; \mathbf{\Theta}), \widetilde{\mathbf{y}}_i \rangle\right) \qquad (8)$$

Here, we estimate the target vector $\widetilde{\mathbf{y}}$ of each instance by using the mean teacher technique (Tarvainen & Valpola, 2017), and incorporate Eq.(8) to Eq.(2).

Pseudo-negative instance correction. We concentrate on the pseudo-negative instances with high confidence to be positive $\{(\mathbf{x}, y = 0) | (\mathbf{x}, y = 0) \in \mathcal{X}_u, f(\mathbf{x}; \mathbf{\Theta}) > \gamma\}$. We directly revise their labels to positive before their corresponding mixup operators.

3 EXPERIMENT

3.1 EXPERIMENTAL SETTINGS

Datasets. In the experiments, we employ three prevalent benchmark datasets, including Fashion-MNIST (F-MNIST) (Xiao et al., 2017),[3] CIFAR-10 (Krizhevsky, 2016),[4] and STL-10 (Coates et al., 2011).[5] The dataset statistics are described in Table 1. Note that all benchmark datasets have 10 category labels, and we denote them with integers ranging from 0 to 9 following the default settings in torchvision 0.10.0. For each dataset, we group those category labels into two disjoint sets as positive or negative, and generate two synthetic PU datasets by reversing the definitions of positive and negative labels. Following the protocol of (Chen et al., 2020a), the specific definitions of labels ("positive" vs "negative") are as follows: F-MNIST-1: "1,4,7" vs "0,2,3,4,5,6,8,9", F-MNIST-2: "0,2,3,5,6,8,9" vs "1,4,7"; CIFAR-10-1: "0,1,8,9" vs "2,3,4,5,6,7", CIFAR-10-2: "2,3,4,5,6,7" vs "0,1,8,9"; STL-10-1: "0,2,3,8,9" vs "1,4,5,6,7", STL-10-2: "1,4,5,6,7" vs "0,2,3,8,9". For each dataset, we randomly select 1,000 positive instances from the training set, and 500 instances as the validation set.

Baseline methods. To verify the effectiveness of P³Mix, we utilize six PU learning baselines and also the supervised method for comparison. The details of baseline methods are presented below.

- **u**nbiased **PU** learning (**uPU**) (du Plessis et al., 2014): A cost-sensitive method based on unbiased risk estimation. We use the public code from the net.[6]

---

[3] https://github.com/zalandoresearch/fashion-mnist
[4] http://www.cs.toronto.edu/~kriz/cifar.html
[5] https://cs.stanford.edu/~acoates/stl10

Table 1: Specification of datasets and corresponding backbones.

Dataset	#Train	#Test	Input size	Backbone
F-MNIST	60,000	10,000	28×28	LeNet-5
CIFAR-10	50,000	10,000	$3\times32\times32$	7-layer CNN
STL-10	105,000	8,000	$3\times96\times96$	7-layer CNN

- **n**on-**n**egative **PU** learning (**nnPU**) (Kiryo et al., 2017): A cost-sensitive method based on non-negative risk estimation. We use the public code from the net.[6] [suggested settings: $\beta = 0$ and $\gamma = 1.0$]

- **Self-PU** (Chen et al., 2020b): A cost-sensitive method with self-supervision scheme. We use the public code from the net.[7] [suggest settings: $\alpha = 10.0$, $\beta = 0.3$, $\gamma = 1/16$, Pace1 $= 0.2$ and Pace2 $= 0.3$]

- **P**redictive **A**dversarial **N**etworks (**PAN**) (Hu et al., 2021): A GAN-based PU learning method with a discriminator and a classifier. We use the public code from the net.[8] [suggested settings: $\lambda = 1e - 4$]

- **V**ariational **PU** learning (**VPU**) (Chen et al., 2020a): A PU learning method based on the variational principle. We use the public code from the net.[9] [suggested settings: $\alpha = 0.3$, $\beta \in \{1e - 4, 3e - 4, 1e - 3, \cdots, 1, 3\}$]

- **P**ositive-**U**nlabeled **L**earning with effective **N**egative sample **S**elector (**PULNS**) (Luo et al., 2021): A sample-selection method with reinforcement learning. We implement an in-house python code with a 3-layer MLP selector suggested by the paper. [suggested settings: $\alpha = 1.0$ and $\beta \in \{0.4, 0.6, 0.8, 1.0\}$]

- **Supervised**: The classifiers trained on the fully supervised datasets.

For all comparing methods, we adopt the classifiers (including the discriminator of PAN) by LeNet-5 for F-MNIST, and 7-layer CNN for CIFAR-10 and STL-10. Specially, the baseline methods of uPU, nnPU and Self-PU require the prior knowledge of class proportion, however, the prior is actually unknown for STL-10 since it contains many "real" unlabeled instances. Accordingly, we estimate the class proportion of STL-10 by using the SOTA KM2 method (Ramaswamy et al., 2016) before evaluating uPU, nnPU, and Self-PU.

Implementation details of P^{3}Mix. We implement P^{3}Mix by using Pytorch (Paszke et al., 2019) with the Adam algorithm (Kingma & Ba, 2014). We call the versions with early-learning regularization and pseudo-negative instance correction as **P^{3}Mix-E** and **P^{3}Mix-C**, respectively. We employ the cross entropy function as the loss function ℓ of Eq.(2), fix the mixup hyperparameter α to 1 and the size k of the candidate mixup pool $\mathcal{X}_{cnd}$ to 100, and choose the coefficient parameter β from $\{0.8, 0.9, 1.0\}$, the thresholding parameter γ from $\{0.8, 0.85, 0.9\}$. We will make the sensitivity analysis on $\{\beta, \gamma\}$ later. Specially, the early-learning regularization parameter of P^{3}Mix-E is chosen from $\{1.0, 2.0, 3.0, 4.0, 5.0\}$.

3.2 Classification performance

For each dataset, we independently run each comparing method 5 times and report the average classification accuracy in Table 2. Generally, our P^{3}Mix-E and P^{3}Mix-C consistently outperform all PU learning baselines on all benchmark datasets, indicating their superior performance. Compared with VPU, which utilizes the typical mixup technique, both P^{3}Mix-E and P^{3}Mix-C achieve significant performance gain on all datasets, *i.e.,* about $1\% \sim 5\%$ improvements. These results imply that our proposed heuristic mixup benefits to the supervision correction within marginal pseudo-negative instances. Compared with the three cost-sensitive PU learning methods uPU, nnPU and Self-PU, P^{3}Mix-E and P^{3}Mix-C also outperform them by about $1\% \sim 4\%$ in all cases. Besides, we observe

---

[6]`https://github.com/kiryor/nnPUlearning`
[7]`https://github.com/TAMU-VITA/Self-PU`
[8]`https://github.com/morning-dews/PAN`
[9]`https://github.com/HC-Feynman/vpu`

Table 2: Results of classification accuracy (mean±std). The highest scores among PU learning methods are indicated in **bold**.

Dataset	F-MNIST-1	F-MNIST-2	CIFAR-10-1	CIFAR-10-2	STL-10-1	STL-10-2
uPU	71.3±1.4	84.0±4.0	76.5±2.5	71.6±1.4	76.7±3.8	78.2±4.1
nnPU	89.7±0.8	88.8±0.9	84.7±2.4	83.7±0.6	77.1±4.5	80.4±2.7
Self-PU	90.8±0.4	89.1±0.7	85.1±0.8	83.9±2.6	78.5±1.1	80.8±2.1
PAN	88.7±1.2	83.6±2.5	87.0±0.3	82.8±1.0	77.7±2.5	79.8±1.4
VPU	90.6±1.2	86.8±0.8	86.8±1.2	82.5±1.1	78.4±1.1	82.9±0.7
PULNS	90.7±0.5	87.9±0.5	87.2±0.6	83.7±2.9	80.2±0.8	83.6±0.7
P^3Mix-E	**91.9±0.3**	**89.5±0.5**	88.2±0.4	84.7±0.5	80.2±0.9	**83.7±0.7**
P^3Mix-C	**92.0±0.4**	**89.4±0.3**	**88.7±0.4**	**87.7±0.5**	**80.7±0.7**	**84.1±0.3**
Supervised	95.2±0.2	95.2±0.2	91.3±0.3	91.3±0.3	85.6±0.6	85.6±0.6

that all discriminative PU learning methods except uPU perform better than the GAN-based PU learning method PAN in most cases. The possible reason is that the imprecise supervision within unlabeled instances makes the identification of fake instances for the discriminator more difficult, resulting in a worse classifier.

3.3 ABLATION STUDY

To evaluate the effectiveness of our proposed heuristic mixup, we conduct the ablation experiments on all benchmark datasets. Specifically, we compare P^3Mix, P^3Mix-E and P^3Mix-C with the Disambiguation-Free (DF) objective of Eq.(1), DF+mixup, augmented by the typical mixup technique, and their versions with early-learning regularization ("-E") and pseudo-negative instance correction ("-C"). The experimental results are reported in Table 3. It clearly demonstrates that the proposed heuristic mixup can significantly improve the classification performance. This result is expected because the heuristic mixup can simultaneously achieve data augmentation and supervision correction by refining the imprecise supervision within marginal pseudo-negative instances. Besides, we can also observe that both early-learning regularization and pseudo-negative instance correction contribute to the improvement of the classification performance in all cases, proving the effectiveness of those two tricks in improving the robustness of models.

3.4 SENSITIVITY ANALYSIS

In this section, we examine the sensitivities of the coefficient parameter β and the thresholding parameter γ on F-MNIST-1, CIFAR-10-1 and STL-10-1.

Sensitivity of β. We examine the impact of different β values over the set $\{0.1, 0.2, \cdots, 1.0\}$ by P^3Mix-C and plot the experimental results in Fig.3. We omit the results of P^3Mix and P^3Mix-E due to their similar performance curves and also page-limitation. Obviously, the performance achieves the highest and is relatively stable when $\beta \geq 0.8$, and it sharply drops as the values become smaller especially on CIFAR-10-1 and STL-10-1. Notice that the coefficient parameter β is used to balance the importance of the positive and pseudo-negative parts in Eq.(2). The larger or smaller value of β will result in the indecent importance of the pseudo-negative part, leading to a unstable classifier. Therefore, we suggest tuning β over the set $\{0.8, 0.9, 1.0\}$ in practice.

Sensitivity of γ. Generally, the thresholding parameter γ is utilized to estimate the set of marginal pseudo-negative instances $\mathcal{X}_{mpn}$ from pseudo-negative instances. However, both the early-learning regularization and pseudo-negative instance correction may be affected to γ since they are mainly used to control the corrupted negative instances within $\mathcal{X}_u \setminus \mathcal{X}_{mpn}$. Accordingly, we perform the sensitivity analysis of γ by P^3Mix. Specifically, we vary the value of γ over the set $\{0.5, 0.55, \cdots, 1.0\}$. As shown in Fig.4, P^3Mix performs relatively worse when γ is too small or too large especially on F-MNIST-1 and CIFAR-10-1. This result is expected because the smaller value of γ implies that $\mathcal{X}_{mpn}$ contains fewer marginal pseudo-negative instances, e.g., $\mathcal{X}_{mpn} = \emptyset$ when $\gamma = 0.5$, and it will hurt the supervision correction of heuristic mixup. Besides, when γ becomes too large, too many pseudo-negative instances will be treated as marginal pseudo-negative ones, e.g., $\mathcal{X}_{mpn} = \mathcal{X}_u$ when

Table 3: Results of ablative study (mean±std). The highest scores among PU learning methods are indicated in **bold**.

Dataset	F-MNIST-1	F-MNIST-2	CIFAR-10-1	CIFAR-10-2	STL-10-1	STL-10-2
DF	75.2±1.2	62.7±2.8	72.0±3.2	57.4±3.7	78.1±0.6	80.6±2.4
DF+mixup	78.4±1.7	72.4±1.4	79.2±3.0	67.4±2.5	78.9±0.3	80.7±1.9
P^3Mix	87.0±1.1	78.4±1.4	84.2±2.5	78.5±2.3	79.2±0.6	83.3±0.9
DF-E	90.1±0.7	74.2±5.5	82.4±1.6	69.4±3.0	67.3±2.0	75.0±3.7
DF-E+mixup	90.6±0.7	86.1±2.5	85.7±0.7	76.4±0.9	78.3±1.1	79.3±2.3
P^3Mix-E	**91.9±0.3**	**89.5±0.5**	**88.2±0.4**	**84.7±0.5**	**80.2±0.9**	**83.7±0.7**
DF-C	89.6±1.8	87.4±2.4	87.2±0.8	84.7±1.1	80.2±3.0	82.7±2.6
DF-C+mixup	91.6±0.3	88.3±1.2	87.7±1.1	81.3±3.6	79.9±3.1	81.6±2.8
P^3Mix-C	**92.0±0.4**	**89.4±0.3**	**88.7±0.4**	**87.7±0.5**	**80.7±0.7**	**84.1±0.3**

Figure 3: Sensitivity analysis of the coefficient parameter β on F-MNIST-1 (left), CIFAR-10-1 (middle) and STL-10-1 (right).

$\gamma = 1.0$, resulting in the reduction of the variety of augmented instances. In summary, its suggested setting is given by $\{0.8, 0.85, 0.9, 0.95\}$.

4 RELATED WORK

In this section, we review the representative studies on PU learning, especially the ones most related to P^3Mix. Besides, we briefly introduce the recent studies of mixup for data augmentation.

4.1 PU LEARNING

As the name suggests, the basic idea of sample-selection methods is to select reliable negative instances from unlabeled instances to form pseudo-binary dataset before applying supervised methods. Existing methods have proposed various heuristic strategies for negative sample selection, *e.g.,* 1-DNF (Yu et al., 2002; 2004; Peng et al., 2008), Naïve Bayes (Liu et al., 2002), Rocchio extraction (Li & Liu, 2003), kNN (Zhang & Zuo, 2009), k-means (Chaudhari & Shevade, 2012), large margin method (Gong et al., 2018) and reinforcement learning (Luo et al., 2021). Early works based on sample-selection spirit mainly focus on exploiting various traditional classification and clustering approaches to construct the heuristic strategy. Recently, PULNS (Luo et al., 2021) employs a negative selector trained by a reinforcement learning framework, where the selector, the selection of negative instances, and the performance of the classifier are treated as the agent, action and reward, respectively. Then the classifier is induced from the mixture of positive instances and negative ones selected by the selector.

In contrast, the community of PU learning has recently paid more attention to the cost-sensitive methods, which directly treat all unlabeled instances as corrupted negative instances and correct the estimation bias of the objective by employing well-designed misclassificaation risks. The uPU (du Plessis et al., 2014; 2015) made an early attempt of unbiased risk estimation, which reformulates the misclassification risk as an equivalent and ubiased form depending only on PU datasets. However, as reported in (Kiryo et al., 2017), the risk of uPU would become negative due to overfitting when using the flexible and complex models such as deep networks. To remedy this issue, the authors of (Kiryo et al., 2017) suggest the nnPU method, *i.e.,* the non-negative version of uPU.

Figure 4: Sensitivity analysis of the thresholding parameter γ on F-MNIST-1 (left), CIFAR-10-1 (middle) and STL-10-1 (right).

Besides, the Self-PU (Chen et al., 2020b) further considers the learning capability of the model itself, and jointly employs three self-supervision techniques, *i.e.,* a self-paced strategy to discover confident positive and negative instances, a self-calibrated instance-aware loss to explore meaningful supervision over unconfident instances, and a self-supervision consistency by teacher-students learning. Other cost-sensitive methods are based on the maximum margin objective, and refine the bias of corrupted negative instances by various tricks, such as unbiased centroid estimation of unlabeled instances (Shi et al., 2018; Gong et al., 2019b), label calibration with a hat loss (Zhang et al., 2019), and margin-based label disambiguation (Gong et al., 2019a).

In parallel with the aforementioned methods, several GAN-based PU learning methods (Hou et al., 2018; Chiaroni et al., 2018; Guo et al., 2020; Na et al., 2020; Hu et al., 2021) have been proposed. The GenPU (Hou et al., 2018) generates positive and negative instances, and induces a classifier from those generated instances. The PAN (Hu et al., 2021) is based on adversarial learning on the probability distributions of a discriminator and a classifier.

Orthogonal to those PU learning methods, our P^3Mix concentrates on data augmentation and extends the well-established mixup technique (Zhang et al., 2018) to a specific heuristic version for PU learning, enabling to achieve data augmentation and supervision correction simultaneously. The recent PU learning works most related to P^3Mix are VPU (Chen et al., 2020a) and MixPUL (Wei et al., 2020), in which the mixup is used as a regularization to improve the robustness of classifiers and performed among labeled and unlabeled instances randomly. In contrast, our P^3Mix constructs a heuristic mixup partner selection to refine the imprecise supervision within unlabeled instances.

4.2 Mixup Augmentation

The mixup technique (Zhang et al., 2018) generates augmented instances with convex combinations of training instances. Despite its simplicity, it can effectively improve the robustness with even scarce and noisy supervision (Thulasidasan et al., 2019; Carratino et al., 2020; Zhang et al., 2021). Further, a number of modified mixup versions (Verma et al., 2019; Yun et al., 2019; Guo et al., 2019; Kim et al., 2020; Hendrycks et al., 2020) have been proposed, *e.g.,* manifold mixup that generates convex combinations on the latent feature space (Verma et al., 2019) and puzzle mixup that further explores the saliency information and underlying statistics of instances (Kim et al., 2020). In this work, we extend the typical mixup to a specific heuristic version for PU learning.

5 Conclusion

In this paper, we propose a novel PU learning method named P^3Mix, which extends the typical mixup technique to a heuristic version. The story begins with the observation of the directional boundary deviation phenomenon, which inspires us to propose a guidance of mixup partners selection, especially for the marginal pseudo-negative instances. Fortunately, this heuristic mixup technique can simultaneously achieve data augmentation and supervision correction for PU learning. Generally, our P^3Mix is easy-to-implement, and we also employ two tricks to improve the robustness of P^3Mix. We compare P^3Mix against a number of existing PU learning methods on benchmark datasets. Experimental results show the superior performance of P^3Mix and the effectiveness of the heuristic mixup technique.

REFERENCES

Jessa Bekker and Jesse Davis. Learning from positive and unlabeled data: A survey. *Machine Learning*, 109(4):719–760, 2020.

David Berthelot, Nicholas Carlini, Ian J. Goodfellow, Nicolas Papernot, Avital Oliver, and Colin Raffel. Mixmatch: A holistic approach to semi-supervised learning. In *Neural Information Processing Systems*, pp. 5050–5060. 2019.

Luigi Carratino, Moustapha Cissé, Rodolphe Jenatton, and Jean-Philippe Vert. On mixup regularization. *arXiv preprint arXiv:2006.06049*, 2020.

Sneha Chaudhari and Shirish K. Shevade. Learning from positive and unlabelled examples using maximum margin clustering. In *International Conference Neural Information Processing*, pp. 465–473. 2012.

Hui Chen, Fangqing Liu, Yin Wang, Liyue Zhao, and Hao Wu. A variational approach for learning from positive and unlabeled data. In *Neural Information Processing Systems*. 2020a.

Xuxi Chen, Wuyang Chen, Tianlong Chen, Ye Yuan, Chen Gong, Kewei Chen, and Zhangyang Wang. Self-pu: Self boosted and calibrated positive-unlabeled training. In *International Conference on Machine Learning*, pp. 1510–1519. 2020b.

Florent Chiaroni, Mohamed-Cherif Rahal, Nicolas Hueber, and Frédéric Dufaux. Learning with A generative adversarial network from a positive unlabeled dataset for image classification. In *IEEE International Conference on Image Processing*, pp. 1368–1372. 2018.

Adam Coates, Andrew Y. Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. In *International Conference on Artificial Intelligence and Statistics*, pp. 215–223. 2011.

Marthinus Christoffel du Plessis, Gang Niu, and Masashi Sugiyama. Analysis of learning from positive and unlabeled data. In *Neural Information Processing Systems*, pp. 703–711. 2014.

Marthinus Christoffel du Plessis, Gang Niu, and Masashi Sugiyama. Convex formulation for learning from positive and unlabeled data. In *International Conference on Machine Learning*, pp. 1386–1394. 2015.

Chen Gong, Tongliang Liu, Jian Yang, and Dacheng Tao. Large-margin label-calibrated support vector machines for positive and unlabeled learning. *IEEE Transactions on Neural Networks and Learning Systems*, 30(11):3471–3483, 2019a.

Chen Gong, Hong Shi, Tongliang Liu, Chuang Zhang, Jian Yang, and Dacheng Tao. Loss decomposition and centroid estimation for positive and unlabeled learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 43(3):918–932, 2019b.

Tieliang Gong, Guangtao Wang, Jieping Ye, Zongben Xu, and Ming Lin. Margin based PU learning. In *AAAI Conference on Artificial Intelligence*, pp. 3037–3044. 2018.

Hongyu Guo, Yongyi Mao, and Richong Zhang. Mixup as locally linear out-of-manifold regularization. In *AAAI Conference on Artificial Intelligence*, pp. 3714–3722. 2019.

Tianyu Guo, Chang Xu, Jiajun Huang, Yunhe Wang, Boxin Shi, Chao Xu, and Dacheng Tao. On positive-unlabeled classification in GAN. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8382–8390. 2020.

Dan Hendrycks, Norman Mu, Ekin Dogus Cubuk, Barret Zoph, Justin Gilmer, and Balaji Lakshminarayanan. Augmix: A simple data processing method to improve robustness and uncertainty. In *International Conference on Learning Representations*. 2020.

Ming Hou, Brahim Chaib-Draa, Chao Li, and Qibin Zhao. Generative adversarial positive-unlabeled learning. In *International Joint Conference on Artificial Intelligence*, pp. 2255–2261. 2018.

Cho-Jui Hsieh, Nagarajan Natarajan, and Inderjit S. Dhillon. PU learning for matrix completion. In *International Conference on Machine Learning*, pp. 2445–2453. 2015.

Wenpeng Hu, Ran Le, Bing Liu, Feng Ji, Jinwen Ma, Dongyan Zhao, and Rui Yan. Predictive adversarial learning from positive and unlabeled data. In *AAAI Conference on Artificial Intelligence*, pp. 7806–7814. 2021.

Jang-Hyun Kim, Wonho Choo, and Hyun Oh Song. Puzzle mix: Exploiting saliency and local statistics for optimal mixup. In *International Conference on Machine Learning*, pp. 5275–5285. 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Ryuichi Kiryo, Gang Niu, Marthinus Christoffel du Plessis, and Masashi Sugiyama. Positive-unlabeled learning with non-negative risk estimator. In *Neural Information Processing Systems*, pp. 1675–1685. 2017.

Alex Krizhevsky. *Learning Multiple Layers of Features from Tiny Images*. Technical report, University of Toronto, 2016.

Junnan Li, Richard Socher, and Steven C. H. Hoi. Dividemix: Learning with noisy labels as semi-supervised learning. In *International Conference on Learning Representations*. 2020.

Xiaoli Li and Bing Liu. Learning to classify texts using positive and unlabeled data. In *International Joint Conference on Artificial Intelligence*, pp. 587–594. 2003.

Bing Liu, Wee Sun Lee, Philip S. Yu, and Xiaoli Li. Partially supervised classification of text documents. In *International Conference Machine Learning*, pp. 387–394. 2002.

Sheng Liu, Jonathan Niles-Weed, Narges Razavian, and Carlos Fernandez-Granda. Early-learning regularization prevents memorization of noisy labels. In *Neural Information Processing Systems*. 2020.

Chuan Luo, Pu Zhao, Chen Chen, Bo Qiao, Chao Du, Hongyu Zhang, Wei Wu, Shaowei Cai, Bing He, Saravanakumar Rajmohan, and Qingwei Lin. PULNS: positive-unlabeled learning with effective negative sample selector. In *AAAI Conference on Artificial Intelligence*, pp. 8784–8792. 2021.

Byeonghu Na, Hyemi Kim, Kyungwoo Song, Weonyoung Joo, Yoon-Yeong Kim, and Il-Chul Moon. Deep generative positive-unlabeled learning under selection bias. In *ACM International Conference on Information and Knowledge Management*, pp. 1155–1164. 2020.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Köpf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *NeurIPS*, pp. 8024–8035. 2019.

Tao Peng, Wanli Zuo, and Fengling He. SVM based adaptive learning method for text classification from positive and unlabeled documents. *Knowledge and Information Systems*, 16(3):281–301, 2008.

Harish G. Ramaswamy, Clayton Scott, and Ambuj Tewari. Mixture proportion estimation via kernel embeddings of distributions. In *International Conference on Machine Learning*, pp. 2052–2060. 2016.

Yafeng Ren, Donghong Ji, and Hongbin Zhang. Positive unlabeled learning for deceptive reviews detection. In *Conference on Empirical Methods in Natural Language Processing*, pp. 488–498. 2014.

Hong Shi, Shaojun Pan, Jian Yang, and Chen Gong. Positive and unlabeled learning via loss decomposition and centroid estimation. In *International Joint Conference on Artificial Intelligence*, pp. 2689–2695. 2018.

Antti Tarvainen and Harri Valpola. Mean teachers are better role models: Weight-averaged consistency targets improve semi-supervised deep learning results. In *Neural Information Processing Systems*, pp. 1195–1204. 2017.

Sunil Thulasidasan, Gopinath Chennupati, Jeff A. Bilmes, Tanmoy Bhattacharya, and Sarah Michalak. On mixup training: Improved calibration and predictive uncertainty for deep neural networks. In *Neural Information Processing Systems*, pp. 13888–13899. 2019.

Vikas Verma, Alex Lamb, Christopher Beckham, Amir Najafi, Ioannis Mitliagkas, David Lopez-Paz, and Yoshua Bengio. Manifold mixup: Better representations by interpolating hidden states. In *International Conference on Machine Learning*, pp. 6438–6447. 2019.

Tong Wei, Feng Shi, Hai Wang, Wei-Wei Tu, and Yu-Feng Li. Mixpul: Consistency-based augmentation for positive and unlabeled learning. *arXiv preprint arXiv:2004.09388*, 2020.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017.

Yan Yan and Yuhong Guo. Partial label learning with batch label correction. In *AAAI Conference on Artificial Intelligence*, pp. 6575–6582. 2020.

Peng Yang, Xiaoli Li, Jian-Ping Mei, Chee Keong Kwoh, and See-Kiong Ng. Positive-unlabeled learning for disease gene identification. *Bioinformatics*, 28(20):2640–2647, 2012.

Hwanjo Yu, Jiawei Han, and Kevin Chen-Chuan Chang. PEBL: positive example based learning for web page classification using SVM. In *ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 239–248. 2002.

Hwanjo Yu, Jiawei Han, and Kevin Chen-Chuan Chang. PEBL: web page classification without negative examples. *IEEE Transactions on Knowledge and Data Engineering*, 16(1):70–81, 2004.

Sangdoo Yun, Dongyoon Han, Sanghyuk Chun, Seong Joon Oh, Youngjoon Yoo, and Junsuk Choe. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *IEEE/CVF International Conference on Computer Vision*, pp. 6022–6031. 2019.

Bangzuo Zhang and Wanli Zuo. Reliable negative extracting based on knn for learning from positive and unlabeled examples. *Journal of Computers*, 4(1):94–101, 2009.

Chuang Zhang, Dexin Ren, Tongliang Liu, Jian Yang, and Chen Gong. Positive and unlabeled learning with label disambiguation. In *International Joint Conference on Artificial Intelligence*, pp. 4250–4256. 2019.

Hongyi Zhang, Moustapha Cissé, Yann N. Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *International Conference on Learning Representations*. 2018.

Linjun Zhang, Zhun Deng, Kenji Kawaguchi, Amirata Ghorbani, and James Zou. How does mixup help with robustness and generalization? In *International Conference on Learning Representations*. 2021.