Improving Calibration through the Relationship with Adversarial Robustness

Abstract

Neural networks lack *adversarial robustness*, i.e., they are vulnerable to adversarial examples that through small perturbations to inputs cause incorrect predictions. Further, trust is undermined when models give *miscalibrated* uncertainty estimates, i.e., the predicted probability is not a good indicator of how much we should trust our model. In this paper, we study the connection between adversarial robustness and calibration and find that the inputs for which the model is sensitive to small perturbations (are easily attacked) are more likely to have poorly calibrated predictions. Based on this insight, we examine if calibration can be improved by addressing those adversarially unrobust inputs. To this end, we propose Adversarial Robustness based Adaptive Label Smoothing (`AR-AdaLS`) that integrates the correlations of adversarial robustness and uncertainty into training by adaptively softening labels for an example based on how easily it can be attacked by an adversary. We find that our method, taking the adversarial robustness of the in-distribution data into consideration, leads to better calibration over the model even under distributional shifts. In addition, `AR-AdaLS` can also be applied to an ensemble model to further improve model's calibration. All the codes in this work will be open-sourced.

1 Introduction

The robustness of machine learning algorithms is becoming increasingly important as ML systems are being used in higher-stakes applications. In one line of research, neural networks are shown to lack *adversarial robustness* – small perturbations to the input can successfully fool classifiers into making incorrect predictions (Szegedy et al., 2014; Goodfellow et al., 2014; Carlini & Wagner, 2017b; Madry et al., 2017; Qin et al., 2020). In largely separate lines of work, researchers have studied uncertainty in model's predictions. For example, models are often *miscalibrated* where the predicted confidence is not indicative of the true likelihood of the model being correct (Guo et al., 2017; Thulasidasan et al., 2019b; Lakshminarayanan et al., 2017; Wen et al., 2020; Kull et al., 2019). The calibration issue is exacerbated when models are asked to make predictions on data different from the training distribution (Snoek et al., 2019), which becomes an issue in practical settings where it is important that we can trust model predictions under distributional shift.

Despite robustness, in all its forms, being a popular area of research, the *relationship* between these perspectives has not been extensively explored previously. In this paper, we study the correlation between adversarial robustness and calibration. We discover that input data that are sensitive to small adversarial perturbations (are easily attacked) are more likely to have poorly calibrated predictions. This holds true on a number of network architectures for classification and on all the datasets that we consider: CIFAR-10 (Krizhevsky, 2009), CIFAR-100 (Krizhevsky, 2009) and ImageNet (Russakovsky et al., 2015). This suggests that the miscalibrated uncertainty estimates on those adversarially unrobust data greatly degrades the performance of a model's calibration. Based on

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

this insight, we hypothesize and study if calibration can be improved by giving different supervision to the model depending on adversarial robustness of each training data.

To this end, we propose **A**dversarial **R**obustness based **Ada**ptive **L**abel **S**moothing (`AR-AdaLS`) that integrates the correlations of adversarial robustness and calibration into training by adaptively smoothing the training labels conditioned on how unrobust an input is. Our method improves label smoothing (Szegedy et al., 2014) by explicitly teaching the model to differentiate the training data according to their adversarial robustness and then adaptively smooth their labels. By giving different supervision to the training data, our method leads to better calibration over the model without an increase of latency during inference. In particular, since adversarially unrobust data can be considered as an outlier of the underlying data distribution (Carlini et al., 2019), our method, by taking the adversarial robustness of the in-distribution data into consideration during training, can even greatly improve model's calibration on held-out shifted data. Further, we propose "`AR-AdaLS` of Ensemble" to combine our `AR-AdaLS` and deep ensembles (Lakshminarayanan et al., 2017), which is the state-of-the-art method especially under distributional shift (Snoek et al., 2019), to further improve the calibration performance for shifted data. Last, we find an additional benefit of `AR-AdaLS` is improving model stability (i.e., decreasing variance), which is valuable in practical applications where changes in predictions across runs (churn) is problematic and deploying ensembles is too costly (Milani Fard et al., 2016).

In summary, our main contributions are as follows:

- **Relationship among Robustness Metrics:** We find a significant correlation between adversarial robustness and calibration: inputs that are unrobust to adversarial attacks are more likely to have poorly calibrated predictions.

- **Algorithm:** We propose `AR-AdaLS` to automatically learn how much to soften the labels of training data based on their adersarial robustness. Further, we introduce "`AR-AdaLS` of Ensemble" to show how to apply `AR-AdaLS` to an ensemble model.

- **Experimental Analysis:** On CIFAR-10, CIFAR-100 and ImageNet, we find that `AR-AdaLS` is more effective than previous label smoothing methods in improving calibration, particularly for shifted data. Further, we find that while ensembling can be beneficial, applying `AR-AdaLS` to adaptively calibrate ensembles offers further improvements over calibration.

2 Related Work

Uncertainty Estimates How to better estimate a model's predictive uncertainty is an important research topic, since many models with a focus on accuracy may fall short in predictive uncertainty. A popular way to improve a model's predictive uncertainty is to make the model well-calibrated, e.g., post-hoc calibration by temperature scaling (Guo et al., 2017), and multiclass Dirichlet calibration (Kull et al., 2019). In addition, Bayesian neural networks, through learning a posterior distribution over network parameters, can also be used to quantify a model's predictive uncertainty, e.g., Graves (2011); Blundell et al. (2015); Welling & Teh (2011). Dropout-based variational inference (Gal & Ghahramani, 2016; Kingma et al., 2015) can help DNN models make less over-confident predictions and be better calibrated. Recently, mixup training (Zhang et al., 2018) has been shown to improve both models' generalization and calibration (Thulasidasan et al., 2019b), by preventing the model from being over-confident in its predictions. Despite the success of improving uncertainty estimates over in-distribution data, Snoek et al. (2019) argue that it does not usually translate to a better performance on data that shift from the training distribution. Among all the methods evaluated by Snoek et al. (2019) under distributional shift, ensemble of deep neural networks (Lakshminarayanan et al., 2017), is shown to be most robust to dataset shift, producing the best uncertainty estimates.

Adversarial Robustness On the other hand, machine learning models are known to be brittle (Xin et al., 2017) and vulnerable to adversarial examples (Athalye et al., 2018; Carlini & Wagner, 2017a,b; He et al., 2018). Many defenses have been proposed to improve model's adversarial robustness (Song et al., 2017; Yang et al., 2019; Goodfellow et al., 2018), however are further attacked by more advanced defense-aware attacks (Carlini & Wagner, 2017b; Athalye et al., 2018). Recently, Carlini et al. (2019); Stock & Cissé (2018) define adversarial robustness as the minimum distance in the input domain required to change the model's output prediction by constructing an adversarial attack. The most recent work that is close to ours, Carlini et al. (2019), makes the interesting observation that

Figure 1: Correlations between adversarial robustness and uncertainty estimates on the clean test set on CIFAR-10, CIFAR-100 and ImageNet. **Top:** Accuracy and confidence of the predicted class. **Bottom:** ECE and variance (lower is better)in each adversarial robustness subset. Higher adversarial robustness level means the input are more adversarially robust (harder to attack).

easily attackable data are often outliers in the underlying data distribution and then use adversarial robustness to determine an improved ordering for curriculum learning. Our work, instead, explores the relationship between adversarial robustness and calibration. In addition, we use adversarial robustness as an indicator to adaptively smooth the training labels to improve model's calibration.

Label Smoothing   Label smoothing is originally proposed in Szegedy et al. (2016) and is shown to be effective in improving the quality of uncertainty estimates in Müller et al. (2019); Thulasidasan et al. (2019b). Instead of minimizing the cross-entropy loss between the predicted probability $\hat{p}$ and the one-hot label p, label smoothing minimizes the cross-entropy between the predicted probability and a softened label $\widetilde{p} = p(1 - \epsilon) + \frac{\epsilon}{Z}$, where Z is the number of classes in the dataset and ϵ is a hyperparameter which controls the degree of the smoothing effect. Our work makes label smoothing adaptive and incorporates the correlation with adversarial robustness to further improve calibration.

3   Correlations between adversarial robustness and Calibration

To explore the relationship between adversarial robustness and calibration, we first introduce the metrics to evaluate each of them (arrows indicate which direction is better).

Adversarial robustness $\uparrow$ Adversarial robustness measures the minimum distance in the input domain required to change the model's output prediction by constructing an adversarial attack (Carlini et al., 2019; Stock & Cissé, 2018). Specifically, given an input x and a classifier $f(\cdot)$ that predicts the class for the input, the adversarial robustness is defined as the minimum adversarial perturbation δ that enables $f(x + \delta) \neq f(x)$. Following the work (Carlini et al., 2019), we construct the ℓ_2 based CW attack (Carlini & Wagner, 2017b) and then use the ℓ_2 norm of the adversarial perturbation $\|\delta\|_2$ to measure the distance to the decision boundary. Therefore, a more adversarially robust input requires a larger adversarial perturbation to change the model's prediction.

Calibration metric $\downarrow$ Model's calibration measures the alignment between the predicted probability and the accuracy. Well calibrated uncertainty estimates convey the information about how much we should trust a model's prediction. We follow the widely used expected calibration error (**ECE**) to measure the calibration performance of a network (Guo et al., 2017; Snoek et al., 2019). To compute the ECE, we need to first divide all the data into K buckets sorted by their predicted probability (confidence) of the predicted class. Let B_k represent the set of data in the k-th confidence bucket. Then the accuracy and the confidence of B_k are defined as $\mathrm{acc}(B_k) = \frac{1}{|B_k|} \sum_{i \in B_k} \mathbf{1}(\hat{y}_i =$

Algorithm 1 Training procedure for `AR-AdaLS`

Input: number of classes Z, number of training epochs T, number of adversarial robustness subset R, learning rate of adaptive label smoothing α.

For each adversarial robustness training subset, we initialize the soft label as the one-hot label $\widetilde{p}_{r,t} = p_r$, and initialize the soft label for the correct class $\widetilde{p}_{r,t}^{z=y} = 1$.

for $t = 1$ **to** T **do**

    Minimize cross-entropy loss between soft label and predicted probability $\frac{1}{R} \sum_r^R \mathcal{L}(\widetilde{p}_{r,t}, \hat{p}_{r,t})$

    for $r = 1$ **to** R **do**

        Update $\widetilde{p}_{r,t}^{z=y} \leftarrow \widetilde{p}_{r,t}^{z=y} - \alpha \cdot \{\text{conf}(S_r^{val})_t - \text{acc}(S_r^{val})_t\}$ ▷ Eqn. (3)

        Clip $\widetilde{p}_{r,t}^{z=y}$ to be within $(\frac{1}{Z}, 1]$

        Update $\epsilon_{r,t} \leftarrow (\widetilde{p}_{r,t}^{z=y} - 1) \cdot \frac{Z}{1-Z}$ ▷ Eqn. (4)

        Update $\widetilde{p}_{r,t} \leftarrow p_r(1 - \epsilon_{r,t}) + \frac{\epsilon_{r,t}}{Z}$ ▷ Eqn. (1)

    end for

end for

Table 1: Network architecture and accuracy used for each dataset.

Dataset	CIFAR-10	CIFAR-100	ImageNet
Network	ResNet-29	WRN-28-10	ResNet-101
Accuracy	91.4%	79.2%	77.7%

y_i) and $\text{conf}(B_k) = \frac{1}{|B_k|} \sum_{i \in B_k} \hat{p}_i^{\hat{y}_i}$, where $\hat{y}$ and y represent the predicted class and the true class respectively, and $\hat{p}^{\hat{y}}$ is the predicted probability of $\hat{y}$. The ECE is then defined as $\text{ECE} = \sum_{k=1}^{K} \frac{|B_k|}{N} |\text{acc}(B_k) - \text{conf}(B_k)|$, where N is the number of the data.

3.1 Correlations

In this section, we perform experiments on the clean test set across three datasets: CIFAR-10 (Krizhevsky, 2009), CIFAR-100 (Krizhevsky, 2009) and ImageNet (Russakovsky et al., 2015) with different networks, whose architecture and accuracy are shown in Table 1. We refer to these models as "Vanilla" for each dataset in the following discussion. The details for training each vanilla network are included in Section A in the Appendix.

To explore the relationship between adversarial robustness and calibration, we start with the relationship between adversarial robustness and confidence together with accuracy. Specifically, we rank the input data according to their adversarial robustness and then divide the dataset into R equally-sized subsets ($R = 10$ used in this paper). For each adversarial robustness subset, we compute the accuracy and the average confidence score of the predicted class. As shown in the first row in Figure 1, we can clearly see that both accuracy and confidence increase as adversarial robustness of the input data, and confidence is consistently higher than accuracy in each adversarial robustness subset across three datasets. This indicates that although vanilla classification models achieve the state-of-the-art accuracy, they tend to give over-confident predictions, especially for those unrobust data.

Based on this, to explore the relationship between adversarial robustness and calibration, we compute the expected calibration error (ECE) in each adversarial robustness subset, shown in the bottom row of Figure 1. In general, we find that those unrobust data in lower adversarial robustness levels are more likely to be over-confident and less well calibrated (larger ECE). For more robust examples, there is a better alignment between their confidence and accuracy, and the ECE over those examples is close to 0. On larger-scale ImageNet, while we still see the general trend that less robust examples are less well calibrated, the least robust examples are relatively well calibrated. We hypothesize this may be due to larger data and less overfitting.

Furthermore, we also find an interesting correlation between adversarial robustness and model stability, which is measured by the variance of the predicted probability across 5 independent runs. As shown in the bottom row of Figure 1, we see that those adversarially unrobust examples tend to have a much higher variance compared to the robust examples across all three datasets.

4 Method

Based on the correlation between adversarial robustness and calibration, we hypothesize and study if calibration can be improved by giving different supervision to the model depending on the adversarial robustness of training data. To this end, we propose a method named **A**dversarial **R**obustness based **Ada**ptive **L**abel **S**moothing (AR-AdaLS), which performs label smoothing at different degrees to the training data based on their adversarial robustness. Specifically, we sort and divide the training data into R small subsets with equal size according to their adversarial robustness[1] and then use ϵ_r to soften the labels in each training subset S_r^{train}. The soft labels can be formulated as:

$$\widetilde{p}_r = p_r(1 - \epsilon_r) + \frac{\epsilon_r}{Z}, \tag{1}$$

where $p_r^{z=y} = 1$ for the correct class y and $p_r^{z \neq y} = 0$ for the others, p_r stands for the one-hot label, and Z is the number of classes in the dataset. The parameter ϵ_r controls the degree of smoothing effect and allows for different levels of smoothing in each adversarial robustness subset. Generally, a relatively larger ϵ_r is desirable for lower adversarial robustness levels such that the model learns to make a lower confidence prediction. Instead of empirically setting the parameter ϵ_r in each adversarial robustness subset, we allow it to be adaptively updated according to the calibration performance on the validation set (discussed in Section 4.1). In this way, we explicitly train a network with different supervision based on the adversarial robustness of training data.

4.1 Adaptive learning mechanism

To find the best hyperparameter ϵ for label smoothing, previous methods (Szegedy et al., 2016; Thulasidasan et al., 2019b) sweep ϵ in a range and choose the one that has the best validation performance. However, in our setting, the number of combinations of ϵ_r increases exponentially with the number of adversarial robustness subsets R. To this end, we propose an adaptive learning mechanism to automatically learn the parameter ϵ_r in each adversarial robustness subset. The overall training procedure is summarized in Algorithm 1.

First, we denote the soft label for the correct class in the r-th adversarial robustness subset as $\widetilde{p}_r^{z=y}$. According to Eqn. (1), we can derive:

$$\widetilde{p}_r^{z=y} = 1 - \epsilon_r + \frac{\epsilon_r}{Z}. \tag{2}$$

Since well-calibrated uncertainty estimates should be aligned with the empirical accuracy, we use the calibration performance in the *validation set* to help update $\widetilde{p}_r^{z=y}$ for the *training data*. Specifically, we first rank the adversarial robustness of the validation data and split the validation set into R equally-sized subsets. Then, we use the difference between confidence and accuracy in the r-th adversarial robustness validation subset $\text{conf}(S_r^{val}) - \text{acc}(S_r^{val})$ to update the soft label for the correct class of training data in the r-th adversarial robustness training subset S_r^{train},

$$\widetilde{p}_{r,t+1}^{z=y} = \widetilde{p}_{r,t}^{z=y} - \alpha \cdot \{\text{conf}(S_r^{val})_t - \text{acc}(S_r^{val})_t\} \tag{3}$$

where $\widetilde{p}_{r,t}^{z=y}$ is the soft label of the correct class in the r-th adversarial robustness training subset at time step t. The accuracy and the confidence of S_r^{val} are defined as $\text{acc}(S_r^{val}) = \frac{1}{|S_r^{val}|} \sum_{i \in S_r^{val}} \mathbf{1}(\hat{y}_i = y_i)$ and $\text{conf}(S_r^{val}) = \frac{1}{|S_r^{val}|} \sum_{i \in S_r^{val}} \hat{p}_i^{z=\hat{y}_i}$, where $\hat{y}$ and y is the predicted class and the true class respectively, $\hat{p}^{z=\hat{y}}$ denotes the the predicted probability of the predicted class. The hyperparameter $\alpha > 0$ plays a role as a learning rate to update the soft label $\widetilde{p}_{r,t}^{z=y}$ based on the difference between the predicted confidence and accuracy in the valiadation set. Intuitively, if we assign a large $\widetilde{p}_r^{z=y}$ to training data, then the network tends to make a high confidence prediction and vice versa. Therefore, if the confidence is greater than the accuracy ($\text{conf}(S_r^{val}) > \text{acc}(S_r^{val})$)) in the validation set, we should reduce $\widetilde{p}_r^{z=y}$ to teach the network to be less confident. Otherwise, we should increase $\widetilde{p}_r^{z=y}$. In addition, we also need to constrain $\widetilde{p}_r^{z=y}$ to be within ($\frac{1}{Z}$, 1] after each update as it stands for the true probability of the correct class, where Z is the number of classes in the dataset.

For a given $\widetilde{p}_r^{z=y}$, we can easily obtain ϵ_r by reversing Eqn. (2):

$$\epsilon_r = (\widetilde{p}_r^{z=y} - 1) \cdot \frac{Z}{1 - Z}, \tag{4}$$

---

[1]Note, predicted confidence is not a good indicator for splitting the training dataset as the model can easily overfit to the training data and their predicted confidence are all close to 100%.

Figure 2: Comparison between LS and our `AR-AdaLS` on the clean test set of CIFAR-10. **(a)** and **(b):** Accuracy and confidence score of the predicted class in each adversarial robustness subset. **(c):** ECE of Vanilla, LS and `AR-AdaLS`.

Table 2: Expected calibration error (ECE) on CIFAR-10 and CIFAR-100. `AR-AdaLS` improves calibration and is only rivaled by domain-knowledge based data augmentation or larger ensemble models on CIFAR-100.

Method	CIFAR-10	CIFAR-100	Method	CIFAR-10	CIFAR-100
Single-model based			Data-augmentation based		
Vanilla	2.5	6.1	mixup	0.8	**1.8**
Temperature Scaling	0.8	4.3	CCAT	2.4	4.2
Label Smoothing	1.1	2.8	Ensemble based		
AdaLS	1.3	2.9	Mix-n-Match	1.0	2.8
`AR-AdaLS`	**0.6**	**2.3**	Ensemble of Vanilla	0.9	**2.2**

and the soft labels for all the classes $\widetilde{p}_r$ can be computed according to Eqn. (1). We update the soft labels after each training epoch in our experiments.

Note that this adaptive learning mechanism can be easily applied to standard label smoothing without adversarial robustness slicing ($R = 1$). In this case, we can replace sweeping the hyperparameter ϵ with this adaptive learning method, named as "**Ada**ptive **L**abel **S**moothing" (AdaLS). Our proposed `AdaLS` and `AR-AdaLS` does not increase the inference time: we test `AdaLS` and `AR-AdaLS` exactly the same as a vanilla model.

5 Experiments

Datasets We test our method on three datasets CIFAR-10, CIFAR-100 and ImageNet. In addition, we also report performance on the shifted datasets: CIFAR-10-C, CIFAR-100-C and ImageNet-C (Hendrycks & Dietterich, 2019), where there are different types of corruptions (19 types for CIFAR-10, 17 types for CIFAR-100 and 15 types for ImageNet), e.g., noise, blur, weather and digital categories that are frequently encountered in natural images. Each type of corruption has five levels of shift intensity, with higher levels having more corruption.

5.1 How does AR-AdaLS work?

To have a deeper understanding of how `AR-AdaLS` works, in Figure 2 we visualize the effect of label smoothing (LS) and our `AR-AdaLS`. Comparing Figure 2 (a) and (b), `AR-AdaLS` is better at calibrating the data than label smoothing, especially on the unrobust examples (lower adversarial robustness level). Further, we show plots of ECE in Figure 2 (c). Both label smoothing and `AR-AdaLS` improve model's calibration over vanilla model and `AR-AdaLS` has the best performance among three methods. Figure 2 suggests that `AR-AdaLS` is better at improving calibration in unrobust regions, not just on average.

5.2 AR-AdaLS improves calibration

Baselines We compare our proposed `AR-AdaLS` with the following 8 different methods: (1) Vanilla model trained with one-hot labels, (2) Temperature Scaling (Guo et al., 2017), a post-hoc calibration method where the predicted logits are divided by a temperature which is tuned on the hold-out

Table 3: Mean of ECE ($\times 10^{-2}$) across 19 types of shift for CIFAR-10-C and 15 types of shift for ImageNet-C. Smaller is better. ResNet-29 is used for CIFAR-10 and ResNet-101 is used for ImageNet. The best single model and ensemble model in each shift intensity is highlighted in **bold**.

Single-model based			Ensemble-based		
Methods	CIFAR-10-C	ImageNet-C	Methods	CIFAR-10-C	ImageNet-C
Vanilla	16.7	12.8	Ensemble of Vanilla	6.5	4.2
LS	10.1	8.2	Ensemble of LS	4.6	4.7
AdaLS	9.6	8.0	Ensemble of AdaLS	5.2	4.8
AR-AdaLS	**6.4**	**6.8**	Ensemble of AR-AdaLS	5.5	5.1
			AR-AdaLS of Ensemble	**4.4**	**4.0**

validation set, (3) label smoothing (**LS**) (Szegedy et al., 2016) that softs labels by sweeping the hyperparameter ϵ (the smoothing degree) in a range to find the best hyperparameter ϵ, (4) Adaptive Label Smoothing (**AdaLS**): we use our proposed adaptive learning mechanism introduced in Section 4.1 to automatically learn the hyperparameter ϵ rather than sweeping to find the best ϵ. (5) mixup, which is a data augmentation technique originally proposed in (Zhang et al., 2018) and recently found to be able to improve calibration in (Thulasidasan et al., 2019a), (6) Confidence-calibrated adversarial training (CCAT) (Stutz et al., 2020), a method builds on adversarial training by reducing the confidence in the labels of adversarial examples. Note that there is a significant difference between our AR-AdaLS and CCAT: CCAT trains a model on the generated adversarial examples to improve a model's adversarial robustness. In contrast, our AR-AdaLS, trained on the clean training data, is proposed to use the correlation between adversarial robustness and calibration to improve a model's calibration performance. (7) "Ensemble of Vanilla" (Lakshminarayanan et al., 2017), an ensemble of $M = 5$ vanilla models independently trained with random initialization. (8) Mix-n-Match (Zhang et al., 2020), an ensemble and compositional method proposed for calibration. All the methods are trained with the same network architectures and training hyperparameters: e.g., learning rate, batch size, number of training epochs, for fair comparison. Please refer to Appendix A for all the training details and hyperparameters[2].

Results The expected calibration error of all the methods on CIFAR-10 and CIFAR-100 are displayed in Table 2. The Wide-ResNet-28-10 (Zagoruyko & Komodakis, 2016) is used for all the methods on both datasets. We can clearly see that by differentiating the training data based on their adversarial robustness, AR-AdaLS effectively reduces the calibration error compared to other single-model based methods and it is only rivaled by mixup on CIFAR-100, which uses extra domain knowledge through data augmentation. Note that AR-AdaLS is only trained on the clean training data without any data augmentation compared to mixup (Thulasidasan et al., 2019a) and CCAT (Stutz et al., 2020).

5.3 Improve robustness under distributional shift

Improve calibration on shifted dataset Table 3 summarizes the mean calibration error (ECE) on the corrupted datasets: CIFAR-10-C and ImageNet-C (Hendrycks & Dietterich, 2019). Looking at all the *single-model* based methods, we can see that AR-AdaLS significantly outperforms other single-model based methods with the lowest ECE. Contrasting with LS and AdaLS, we see AR-AdaLS benefits greatly from the adversarial robustness slicing. As a result, our model learns to give smaller soft labels of the correct class to those adversarially unrobust training data, which can also be considered as outliers of the underlying data distribution (Carlini et al., 2019). Therefore, when tested on the shifted data that deep networks have been shown to produce pathologically over-confident predictions (Hendrycks & Dietterich, 2019), our model correctly learns to make a relatively lower confidence prediction, resulting in a better calibration performance.

In addition, we also compare AR-AdaLS with "Ensemble of Vanilla" (Lakshminarayanan et al., 2017), which is shown to be the best model for models' calibration under distributional shift (Snoek et al., 2019). The result of Ensemble of Vanilla is an ensemble of $M = 5$ vanilla models independently trained with random initialization. We can see that AR-AdaLS achieves comparable calibration

---

[2]The result of Mix-n-Match in Table 2 is from Table 1 reported in the original work (Zhang et al., 2020), which is trained with the same network architecture, WRN-28-10.

Figure 3: Histogram of predictive entropy on out-of-distribution data. Each model is trained on CIFAR-10 and tested on CIFAR-100.

Table 4: Mean of variance ($\times 10^{-2}$) across 19 types of shift for CIFAR-10-C and 15 types of shift for ImageNet-C. Best in **bold**.

Dataset	CIFAR10-C						ImageNet-C					
Shift Intensity	1	2	3	4	5	Mean	1	2	3	4	5	Mean
Vanilla	7.85	9.69	11.2	13.1	16.0	11.6	5.28	6.39	7.37	8.23	8.29	7.11
LS	5.54	6.95	8.11	9.65	11.8	8.41	4.86	5.84	6.78	7.55	7.41	6.49
AdaLS	5.47	6.87	7.95	9.44	11.5	8.25	4.79	5.77	6.66	7.51	7.56	6.46
AR-AdaLS	**4.21**	**5.06**	**5.73**	**6.66**	**8.24**	**5.98**	**4.53**	**5.49**	**6.12**	**6.76**	**6.66**	**5.91**

performance on CIFAR-10 and the ensemble is better under highly shifted data on ImageNet. Further, we discuss the following two ways to combine `AR-AdaLS` with ensembles:

- **Ensemble of `AR-AdaLS`:** As in Lakshminarayanan et al. (2017), we ensemble `AR-AdaLS` by training multiple independent `AR-AdaLS` models with random initialization, and average their predictions at inference.

- `AR-AdaLS` **of Ensemble:** Instead of computing soft labels independently for each `AR-AdaLS`, we perform `AR-AdaLS` on the ensembled predictions, i.e., in Eqn (3) we compute confidence and accuracy based on the average of $M = 5$ model predictions. Each model is then supervised with the same soft labels.

As shown in Table 3, naively combining deep ensembles with `AR-AdaLS` (Ensemble of `AR-AdaLS`) could not effectively improve models' calibration. In contrast, `AR-AdaLS` of Ensemble, which adaptively adjusts smoothing to keep the ensemble models well calibrated, performs the best under distributional on both CIFAR-10 an ImageNet.

Improvements on Out-of-Distribution Data We further study the performance of `AR-AdaLS` when predicting on out-of-distribution (OOD) data. In Figure 3, we compare the performance of Vanilla, Label Smoothing and `AR-AdaLS` by plotting the histogram of the entropy on the OOD data (higher entropy on OOD is better). Each model is trained on CIFAR-10 dataset and then tested on CIFAR-100 dataset. We can clearly see that `AR-AdaLS` significantly reduces the number of low-entropy predictions on OOD data, which demonstrates the effectiveness of `AR-AdaLS` even on fully out-of-distribution data.

5.4 Improve models' stability

Since we observe in Figure 1 that the most adversarially unrobust data are also very unstable, we test `AR-AdaLS` to see if it can help improve model stability, which is of great value in practice where high variance of a model is bad for churn and deploying ensembles is too costly (Milani Fard et al., 2016). In Table 4 we can see that `AR-AdaLS` can effectively reduce the variance of a model compared to a vanilla model and label smoothing on CIFAR-10 and ImageNet. Please refer to supplementary material for a full figure on both datasets.

Figure 4: ECE on CIFAR-10 and CIFAR-10-C of AR-AdaLS with varying number of adversarial robustness subset R. Note that when $R = 1$, `AR-AdaLS` becomes AdaLS.

Table 5: Ablation study of `AR-AdaLS` on CIFAR-100 and CIFAR100-C (corrupted). We report both accuracy and expected calibration error, denoted by **Acc** and **ECE** for the clean test set, and **cAcc** and **cECE** for CIFAR100-C. Arrow indicates the better direction; best calibration of single model is **bolded**.

Method	Vanilla	Label Smoothing	Temperature Scaling	AR-AdaLS (pre-compute)	AR-AdaLS (on-the-fly)
Acc/cAcc ($\uparrow$)	79.2/52.0	78.9/51.7	79.2/52.0	79.3/52.2	79.2/52.1
ECE/cECE ($\downarrow$)	6.1/18.2	2.8/16.3	4.3/14.0	2.6/14.2	**2.3/13.2**

5.5 Sensitivity Analysis

Sensitivity to the number of adversarial robustness subsets We perform a sensitivity analysis for the number of adversarial robustness subsets R. Specifically, we plot the calibration error of `AR-AdaLS` with a varying R on the clean CIFAR-10 and corrupted CIFAR-10-C in Figure 4. We can see that there is a significant drop in calibration error (ECE) when we increase the number of adversarial robustness subsets R from 1, where $R = 1$ denotes AdaLS. Further, the calibration error is robust when R is chosen within the range [4, 16]. Thus, we choose $R = 10$ for all results shown in this paper for `AR-AdaLS`.

Sensitivity to adversarial robustness To investigate this, we study the performance of `AR-AdaLS` using adversarial robustness generated via two different ways: One is "on-the-fly": we keep creating adversarial attacks during training, which provides a more precise adversarial robustness ranking but at the cost of great computing time. The other is to "pre-compute" adversarial robustness by attacking a vanilla model that is trained with one-hot labels. This is more efficient but at the sacrifice of the precision of adversarial robustness ranking. We perform experiments on CIFAR-100 as an example to compare the performance of `AR-AdaLS` based on the adversarial robustness that is "pre-computed" or "on-the-fly". As shown in Table 5, generating adversarial robustness "on-the-fly" can further help improve the calibration performance for `AR-AdaLS` on both clean and shifted datasets, compared to pre-computing adversarial robustness. Similar patterns are observed on CIFAR-10.[3]

Therefore, all results in this paper related to "`AR-AdaLS`" without further specification are based on pre-computed adversarial robustness for efficiency. This is because our main target is to show that the idea of differentiating the training data based on their adversarial robustness is promising to improve model's calibration rather than pushing the results to the best.

6 Conclusion

In this paper, we have explored the correlations between adversarial robustness and calibration. We find across three datasets that adversarially unrobust (easily attacked) data are more likely to have poorly calibrated and unstable predictions. Based on this insight, we propose `AR-AdaLS` to adaptively smooth the labels of the training data based on their adversarial robustness. In our experiments we see that `AR-AdaLS` is more effective than previous label smoothing methods in improving calibration, particularly for shifted data, and can offer improvements on top of already strong ensembling methods. We believe this is an exciting new use for adversarial robustness as a means to more generally improve model trustworthiness. We hope this spurs further work at the intersection of these areas of research.

---

[3] We did not run on-the-fly `AR-AdaLS` for ImageNet due to the computational intensity.

References

Athalye, A., Carlini, N., and Wagner, D. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *International Conference on Machine Learning*, 2018.

Blundell, C., Cornebise, J., Kavukcuoglu, K., and Wierstra, D. Weight uncertainty in neural network. volume 37 of *Proceedings of Machine Learning Research*, pp. 1613–1622, Lille, France, 07–09 Jul 2015. PMLR. URL http://proceedings.mlr.press/v37/blundell15.html.

Carlini, N. and Wagner, D. Adversarial examples are not easily detected: Bypassing ten detection methods. In *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security*, AISec '17, pp. 3–14, New York, NY, USA, 2017a. Association for Computing Machinery. ISBN 9781450352024. doi: 10.1145/3128572.3140444. URL https://doi.org/10.1145/3128572.3140444.

Carlini, N. and Wagner, D. Towards evaluating the robustness of neural networks. In *2017 IEEE Symposium on Security and Privacy (SP)*, pp. 39–57. IEEE, 2017b.

Carlini, N., Erlingsson, Ú., and Papernot, N. Distribution density, tails, and outliers in machine learning: Metrics and applications. *ArXiv*, abs/1910.13427, 2019.

Gal, Y. and Ghahramani, Z. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *International Conference on Machine Learning*, pp. 1050–1059, 2016.

Goodfellow, I., Shlens, J., and Szegedy, C. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations*, 2014.

Goodfellow, I., Qin, Y., and Berthelot, D. Evaluation methodology for attacks against confidence thresholding models. 2018.

Graves, A. Practical variational inference for neural networks. In Shawe-Taylor, J., Zemel, R. S., Bartlett, P. L., Pereira, F., and Weinberger, K. Q. (eds.), *Advances in Neural Information Processing Systems 24*, pp. 2348–2356. Curran Associates, Inc., 2011.

Guo, C., Pleiss, G., Sun, Y., and Weinberger, K. Q. On calibration of modern neural networks. In *International Conference on Machine Learning*, 2017.

He, K., Zhang, X., Ren, S., and Sun, J. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on Computer Vision and Pattern Recognition*, pp. 770–778, 2016a.

He, K., Zhang, X., Ren, S., and Sun, J. Identity mappings in deep residual networks. In *European Conference on Computer Vision*, pp. 630–645. Springer, 2016b.

He, W., Li, B., and Song, D. Decision boundary analysis of adversarial examples. In *International Conference on Learning Representations*, 2018.

Hendrycks, D. and Dietterich, T. G. Benchmarking neural network robustness to common corruptions and perturbations. *International Conference on Learning Representations*, 2019.

Kingma, D. P., Salimans, T., and Welling, M. Variational dropout and the local reparameterization trick. In *Advances in Neural Information Processing Systems*, pp. 2575–2583, 2015.

Krizhevsky, A. Learning multiple layers of features from tiny images. Technical report, University of Toronto, 2009.

Kull, M., Perello Nieto, M., Kängsepp, M., Silva Filho, T., Song, H., and Flach, P. Beyond temperature scaling: Obtaining well-calibrated multi-class probabilities with dirichlet calibration. In *Advances in Neural Information Processing Systems 32*, pp. 12316–12326, 2019.

Lakshminarayanan, B., Pritzel, A., and Blundell, C. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in Neural Information Processing Systems*, pp. 6405–6416. Curran Associates Inc., 2017. ISBN 9781510860964.

Madry, A., Makelov, A., Schmidt, L., Tsipras, D., and Vladu, A. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations*, 2017.

Milani Fard, M., Cormier, Q., Canini, K., and Gupta, M. Launch and iterate: Reducing prediction churn. In Lee, D. D., Sugiyama, M., Luxburg, U. V., Guyon, I., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems 29*, pp. 3179–3187. Curran Associates, Inc., 2016.

Müller, R., Kornblith, S., and Hinton, G. E. When does label smoothing help? In *Advances in Neural Information Processing Systems*, pp. 4694–4703, 2019.

Qin, Y., Frosst, N., Sabour, S., Raffel, C., Cottrell, G., and Hinton, G. Detecting and diagnosing adversarial images with class-conditional capsule reconstructions. *International Conference on Learning Representations*, 2020.

Russakovsky, O., Deng, J., Su, H., Krause, J., Satheesh, S., Ma, S., Huang, Z., Karpathy, A., Khosla, A., Bernstein, M. S., Berg, A. C., and Li, F.-F. Imagenet large scale visual recognition challenge. *International Journal of Computer Vision*, 115:211–252, 2015.

Snoek, J., Ovadia, Y., Fertig, E., Lakshminarayanan, B., Nowozin, S., Sculley, D., Dillon, J., Ren, J., and Nado, Z. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. In *Advances in Neural Information Processing Systems*, pp. 13969–13980, 2019.

Song, Y., Kim, T., Nowozin, S., Ermon, S., and Kushman, N. Pixeldefend: Leveraging generative models to understand and defend against adversarial examples. In *International Conference on Learning Representations*, 2017.

Stock, P. and Cissé, M. Convnets and imagenet beyond accuracy: Understanding mistakes and uncovering biases. In *European Conference on Computer Vision*, 2018.

Stutz, D., Hein, M., and Schiele, B. Confidence-calibrated adversarial training: Generalizing to unseen attacks. In *International Conference on Machine Learning*, pp. 9155–9166. PMLR, 2020.

Szegedy, C., Zaremba, W., Sutskever, I., Bruna, J., Erhan, D., Goodfellow, I. J., and Fergus, R. Intriguing properties of neural networks. In *International Conference on Learning Representations*, 2014. URL http://arxiv.org/abs/1312.6199.

Szegedy, C., Vanhoucke, V., Ioffe, S., Shlens, J., and Wojna, Z. Rethinking the inception architecture for computer vision. *2016 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2818–2826, 2016.

Thulasidasan, S., Chennupati, G., Bilmes, J. A., Bhattacharya, T., and Michalak, S. On mixup training: Improved calibration and predictive uncertainty for deep neural networks. In *Advances in Neural Information Processing Systems*, pp. 13888–13899, 2019a.

Thulasidasan, S., Chennupati, G., Bilmes, J. A., Bhattacharya, T., and Michalak, S. E. On mixup training: Improved calibration and predictive uncertainty for deep neural networks. In *Advances in Neural Information Processing Systems*, 2019b.

Welling, M. and Teh, Y. W. Bayesian learning via stochastic gradient langevin dynamics. In *Proceedings of the 28th International Conference on International Conference on Machine Learning*, ICML'11, pp. 681–688, Madison, WI, USA, 2011. Omnipress. ISBN 9781450306195.

Wen, Y., Tran, D., and Ba, J. Batchensemble: An alternative approach to efficient ensemble and lifelong learning. In *International Conference on Learning Representations*, 2020.

Xin, D., Mayoraz, N., Pham, H., Lakshmanan, K., and Anderson, J. R. Folding: Why good models sometimes make spurious recommendations. In *Proceedings of the Eleventh ACM Conference on Recommender Systems*, pp. 201–209, 2017.

Yang, Y., Zhang, G., Katabi, D., and Xu, Z. Me-net: Towards effective adversarial robustness with matrix estimation. In *International Conference on Machine Learning*, 2019.

Zagoruyko, S. and Komodakis, N. Wide residual networks. *ArXiv*, abs/1605.07146, 2016.

Zhang, H., Cissé, M., Dauphin, Y., and Lopez-Paz, D. Mixup: Beyond empirical risk minimization. In *International Conference on Learning Representation*, 2018.

Zhang, J., Kailkhura, B., and Han, T. Y.-J. Mix-n-match: Ensemble and compositional methods for uncertainty calibration in deep learning. In *International Conference on Machine Learning*, pp. 11117–11128. PMLR, 2020.

A   Implementation Details

A.1   CIFAR-10

All the experimental results on CIFAR-10 (other than Table 2 in the main text) were obtained with a ResNet-29 v2 (He et al., 2016b) with a batch size of 256. The network is trained with Adam optimizer (Kingma et al., 2015) for 200 epochs. The initial learning rate is 10^{-3} and decayed down to 10^{-4} after 80 epochs, 10^{-5} after 120 epochs, 10^{-6} after 160 epochs and 0.5×10^{-6} after 180 epochs. We adapted the following data augmentation and training script at `https://keras.io/examples/cifar10_resnet/`. The training mechanism is the same for all the methods that we compare in the main paper. We randomly split the training dataset into training data of 45000 images and 5000 images as the validation set. The test set has 10000 images.

For label smoothing (LS), we sweep the hyperparameter ϵ within the range [0, 0.1] with a step size 0.01 and find that the network has the best calibration performance on the validation set when $\epsilon = 0.02$.

For Adaptive Label Smoothing (AdaLS), there is a hyperparameter α which plays a role as learning rate in the adaptive learning mechanism. We choose hyperparameter α based on the calibration performance on the validation set. Specifically, we run experiments with $\alpha \in \{0.005, 0.01, 0.05, 0.1\}$ and find that $\alpha = 0.05$ achieve the best calibration performance.

Similarly, for Adversarial Robustness based Adaptive Label Smoothing (AR-AdaLS), we choose the hyperparameter α from the set $\{0.005, 0.01, 0.05\}$ and empirically set $\alpha = 0.005$ which has the best calibration performance on the validation set. We update the training labels after each epoch for all the experiments related to AR-AdaLS, including the experiments on CIFAR-100 and ImageNet. We use the same hyperparameter $\alpha = 0.005$ without further tuning for AR-AdaLS of Ensemble.

All the results of ensemble models are obtained via training 5 independent models with random initializations, same for CIFAR-100 and ImageNet.

A.2   CIFAR-100

We train a Wide ResNet-28-10 v2 (Zagoruyko & Komodakis, 2016) to obtain the state-of-the-art accuracy for CIFAR-100 (and CIFAR-10 results shown in Table 2 in the main text). We adapt the same training details and data augmentation at `https://github.com/google/edward2/blob/master/baselines/cifar/deterministic.py`.

For label smoothing, we e sweep the hyperparameter ϵ within the range [0, 0.1] with a step size 0.01 and find that the network has the best calibration performance on the validation set when $\epsilon = 0.07$.

The hyperparameter α is set to be 0.005 in AR-AdaLS. For AR-AdaLS that generated with on-the-fly adversarial examples, we recompute the adversarial robustness for training and validation sets after 65, 130 epochs.

A.3   ImageNet

All the experiments on ImageNet were obtained via training a ResNet-101 v1 (He et al., 2016a) following the training script at `https://github.com/google/edward2/blob/master/baselines/imagenet/deterministic.py`. The network is trained with a batch size of 128 for each TPU core with SGD optimizer for 90 epochs. The input image is normalized (divided by 255) to be within [0,1]. We randomly divide 50000 validation images into validation set with 25000 images and test set with 25000 images. Note that the same dataset and training mechanisms are used for all the methods that we compare in the main paper.

For Label Smoothing (LS), we sweep the hyperparameter ϵ within the range $[0, 0.1]$ with a step size 0.01 and find that the best calibration performance on the validation set is achieved by setting $\epsilon = 0.02$.

For Adaptive Label Smoothing (AdaLS), we sweep the hyperparameter α in the set $\{0.005, 0.01, 0.03, 0.05, 0.1\}$ and set it to be $\alpha = 0.03$ for the best calibration performance on the validation set.

We empirically set $\alpha = 0.001$ for `AR-AdaLS` in the first 60 epochs of the training and then increase it to 0.05 for the next 30 epochs. The same hyperparameter α is used for `AR-AdaLS` of Ensemble without further tuning.

A.4 CW attacks

To compute the adversarial robustness, we construct ℓ_2 based CW attacks (Carlini & Wagner, 2017b) following the code at `https://github.com/tensorflow/cleverhans/blob/master/cleverhans/attacks/carlini_wagner_l2.py`. Specifically, we set the binary search steps to be 3, max iterations to be 500 and learning rate to be 0.005. The generated untargeted CW attacks can achieve 100% success rate for all the datasets that we consider: CIFAR-10, CIFAR-100 and ImageNet. We set the number of adversarial robustness training subset and validation subset to be $R = 10$ respectively.

Figure 5: Comparison of ensembled models: ECE and Accuracy on both clean test data and shifted data on CIFAR-10 and ImageNet. For each intensity of shift, we show the results with a box plot summarizing the 25th, 50th, 75th quartiles across 19 types of shift on CIFAR-10-C and 15 types of shift on ImageNet-C. The error bars indicate the min and max value across different shift types.

B Calibration Performance: Additional Results

In Figure 5, we show ECE and accuracy of all the single-models and their corresponding ensembles on the clean test and shifted CIFAR-10 and ImageNet. The high-level conclusion is: 1) all the ensemble models that we compare have similar accuracies, which are higher than single-models. 2) all the ensemble methods perform relatively well for highly shifted data but ensembles of well calibrated models (Ensemble of LS, Ensemble of AdaLS, Ensemble of AR-AdaLS) perform much worse on less shifted and clean test data. 3) AR-AdaLS of Ensemble successfully learns to adaptively adjust its smoothing level to keep the ensemble well calibrated on both clean and shifted dataset.

Figure 6: Variance on clean test and shifted data on CIFAR-10 and ImageNet. For each shift intensity, we show the results with a box plot summarizing the 25th, 50th, 75th quartiles across 19 shift types on CIFAR10-C and 15 shift types on ImageNet-C. The error bars indicate the min and max value across different shift types.