Physically-Based Face Rendering for NIR-VIS Face Recognition

Abstract

Near infrared (NIR) to Visible (VIS) face matching is challenging due to the significant domain gaps as well as a lack of sufficient data for cross-modality model training. To overcome this problem, we propose a novel method for paired NIR-VIS facial images generation. Specifically, we reconstruct 3D face shape and reflectance from a large 2D facial dataset and introduce a novel method of transforming the VIS reflectance to NIR reflectance. We then use a physically-based renderer to generate a vast, high-resolution and photorealistic dataset consisting of various poses and identities in the NIR and VIS spectra. Moreover, to facilitate the identity feature learning, we propose an IDentity-based Maximum Mean Discrepancy (ID-MMD) loss, which not only reduces the modality gap between NIR and VIS images at the domain level but encourages the network to focus on the identity features instead of facial details, such as poses and accessories. Extensive experiments conducted on four challenging NIR-VIS face recognition benchmarks demonstrate that the proposed method can achieve comparable performance with the state-of-the-art (SOTA) methods without requiring any existing NIR-VIS face recognition datasets. With slightly fine-tuning on the target NIR-VIS face recognition datasets, our method can significantly surpass the SOTA performance.

1 Introduction

To overcome the problem that the conventional VISible (VIS) images face recognition methods generally fail to achieve a satisfactory performance under poor illumination, face recognition across Near InfraRed (NIR) images and VIS images has recently gained increasing attention in the computer vision community [18, 19, 11, 12]. However, due to the lack of sufficient NIR-VIS data, the training of the NIR-VIS face recognition network is prone to be over-fitting [19].

To alleviate overfitting, previous works attempt to generate large-scale NIR-VIS face images by transferring the VIS images to NIR ones [25, 32, 43, 41]. However, the image-to-image translation based methods are limited by the number of data in the source domain and the diversity of generated images [11]. Recently, unconditional generative models are employed to synthesize heterogeneous face image pairs from noise [11, 12] and achieve state-of-the-art performance by adopting the various intra-changes, such as poses and illumination, of the target NIR-VIS datasets during the generation. Although the intra-class diversity is considered, only one NIR-VIS pair is generated for each identity in [12], which limits the potential of synthesized face images in the NIR-VIS face recognition task. However, when generating multiple NIR-VIS image pairs for a given identity by using [12], we observe that the identity consistency cannot be well preserved, as shown in Fig. 1(a). Additionally, the appearance variations of generated images are based on the target NIR-VIS face recognition datasets,

(a) DVG-Face [12]

(b) Ours

Figure 1: (a) Multiple VIS (top row) and NIR (bottom row) face images of the same identity generated by DVG-Face [12], and (b) our method, using two subjects from the CelebA dataset [28].

which means, different facial images are synthesized to fit different target datasets. Such dataset-specific face generation degrades the generalizability of the NIR-VIS face recognition networks. To tackle the above problems, we propose a novel physically-based facial image generation method, where high-quality NIR-VIS facial image pairs are generated based on acquired renderable facial reflectance assets. Traditional photorealistic human rendering assets require tremendous manually work, either by scanning systems [30, 16] or artists [36]. The available public datasets are either small in size [2] or do not contain relightable reflectance maps [40, 3], such as the diffuse albedo, specular albedo and specular normals. Recent works [23, 24, 29, 9] have introduced methods that produce high-quality renderable assets from arbitrary facial images. Moreover, Wood *et al*. [36] showed that high-quality synthetic facial data, can be successfully used for computer vision tasks, including landmark localization and facial parsing. However, there exists no dataset or method capable of producing renderable 3D faces, in both VIS and NIR domains.

Utilizing a state-of-the-art facial reflectance acquisition method [24], we generate numerous such facial assets and transform them from VIS to NIR, and then render both under the same conditions, in order to generate high-quality training data. Since our novel transformation method is applied per-pixel on high-resolution reflectance maps, the identity of the subject is perfectly preserved in both cases. Faces generated by the proposed methods are illustrated in Fig. 1(b). As can be seen, our NIR-VIS face generation outperforms [12] (Fig. 1(a)) in preserving identity consistency as well as retaining the diversity of facial appearances.

The generated high-quality NIR-VIS facial image dataset is then used, along with a VIS face recognition dataset, to train the NIR-VIS face recognition network. To facilitate the identity feature learning as well as reduce the modality discrepancy, an IDentity-based Maximum Mean Discrepancy (ID-MMD) loss is proposed, which pulls the feature centroids of the same identity in the NIR domain and the VIS domain closer. Assisted by the ID-MMD loss, the gap between NIR images and VIS ones is bridged at the domain level, and meanwhile, the network is encouraged to focus on identity features rather than facial details of instances, such as poses and accessories. Overall, our main contributions can be summarized as:

- A method capable of generating vast amounts of paired NIR and VIS facial images, of various identities, poses and illumination via a novel VIS-to-NIR transformation for facial reflectance, is proposed.

- To bridge the gap between the NIR images and VIS images, we propose an IDentity-based Maximum Mean Discrepancy (ID-MMD) loss, which not only reduces the modality discrepancy at the domain level but encourages the network to attend to identity features instead of facial details.

- Extensive experiments on four NIR-VIS face recognition benchmarks demonstrate that the propose method achieves comparable performance with the state-of-the-art methods WITHOUT requiring any existing NIR-VIS face recognition dataset. With slightly fine-tuning the models on the target NIR-VIS face recognition datasets, our method significantly surpasses the SOTA performance.

2 Background and Related Work

NIR-VIS Face Recognition NIR-VIS face recognition aims to match the Near InfraRed (NIR) face images with the VISible (VIS) ones. Some research focuses on learning modality-invariant features [18, 19] to facilitate the NIR-VIS face recognition. [18] extracts features for NIR and VIS images via a shared feature extractor pretrained on large-scale VIS face images, where the modality-invariant identity information is then filtered out by applying an orthogonal constraint. To further reduce the gap between two modalities, [19] minimizes the Wasserstein distance of NIR and VIS feature distributions. However, due to the limited amount of NIR-VIS data, the aforementioned methods are generally in the mire of the over-fitting problem.

To address the problem, generative models are involved to facilitate the NIR-VIS face recognition task by transferring VIS face images to NIR ones via the image-to-image translation [25, 32, 43] or synthesizing heterogeneous face image pairs [12]. [25] produces VIS faces from NIR images via learning the patch-to-patch mapping between NIR-VIS image pairs. [32] transfers NIR face images to the corresponding VIS ones via a two-path Generative Adversarial Networks (GAN)-based framework. [43] proposes a multi-stream feature-level fusion technique based on GAN to synthesize visible images from polarimetric thermal images. However, the improvement brought by the "one-to-one" face synthesis strategy is limited by the number of images within the NIR-VIS face recognition datasets, as well as the lack of the attribute diversity of generated images. Henceforth, instead of adopting the conditional image generation, [12] employs the Variational AutoEncoders (VAE) to synthesize a paired NIR-VIS face images for a given new identity. The identity representations are obtained from an identity sampler, which is pre-trained on a large-scale face recognition dataset. Inspired by [12], generating a large number of paired NIR-VIS face images is beneficial to the NIR-VIS face recognition.

However, we notice that, when generating multiple NIR-VIS face image pairs from a given identity representation via [12], the identity consistency is not well preserved. Such disadvantage hinders the potential of generated face images boosting the recognition performance since they cannot provide an explicit guidance for identity features learning. We propose a novel NIR-VIS face image generation method, where a physically-based renderer is used to generate a vast photorealistic dataset.

NIR-VIS Rendering Synthetic datasets have long been used in face analysis problems with moderate success [13, 31], given tha significant domain gap between real and rendered facial images. A recent work by Wood *et al*. [36], achieves state-of-the-art performance in various facial analysis tasks, by using hand-crafted high-quality photorealistic facial avatars. 3D facial appearance methods [23, 24, 29, 9] leverage deep generative models and differentiable rendering to reconstruct facial assets that can be photorealistically rendered. Moreover, another work [4] projects incomplete renderings to the latent space of a deep generative model and reconstructs corresponding photorealistic facial images. Although potent in the VIS spectrum, such methods are not directly usable in NIR.

The literature around NIR rendering from VIS assets remains limited. Wu *et al*. [39] introduced a wavelength-dependent Bidirectional Reflectance Distribution Function (BRDF) for Mid-Wavelength Infrared (MWIR) landscape scene simulation. Moreover, Aguerre *et al*. [1] simulate urban thermal imaging. While closest to our work, none of the above can directly render photorealistic faces in NIR-VIS. In that manner, we employ the recent works in photorealistic synthetic facial data, and combine it our novel VIS-to-NIR transformation to unlock the potential for NIR-VIS facial matching.

3 Proposed Method

In the paper, to avoid the over-fitting problem caused by the small-scale NIR-VIS face recognition dataset, a vast, high-resolution and photorealistic dataset consisting of large-scale identities with various poses and illumination in the NIR and VIS spectra is generated (Sec. 3.1). Then, the generated

120   NIR-VIS facial image pairs, along with a large-scale VIS face recognition dataset, are used to train the NIR-VIS face recognition network, without the aid of any existing NIR-VIS datasets (Sec. 3.2).

Figure 2: We generate paired NIR-VIS facial images by a) acquiring facial VIS reflectance from public dataset of facial images ($\mathcal{A}$), b) transforming the VIS reflectance maps to NIR ($\mathcal{T}$) by exploiting the way human skin reacts to different spectra and c) rendering both VIS and NIR facial images in various poses and illumination conditions with the physically-based $\mathcal{R}_{VIS}$ and $\mathcal{R}_{NIR}$ renderers.

3.1   NIR-VIS Facial Rendering

We introduce a method able to generate vast amounts of photorealistic pairs of NIR-VIS face images, to facilitate the heterogeneous face recognition task. Instead of using 2D generative models, we reconstruct a set of 3D facial assets capable of photorealistic rendering in the VIS domain. Meanwhile, we transform these into the NIR domain with a novel method and render paired images, as described in the following sections. In this manner, we can create paired NIR-VIS facial images, of virtually unlimited identities, in arbitrary poses and illumination conditions.

VIS Reflectance Data Acquisition   Recent works [23, 24, 29, 9] have achieved high-quality render-ready VIS face reconstructions, from arbitrary faces. In that manner, we acquire CelebA [28], a dataset of over 200k facial images $\mathbf{I}_i$, and fit a textured 3D Morphable Model (3DMM) $\mathcal{F}$ using GANFIT [14], to acquire a reconstructed texture and mesh $\mathbf{S}_i$. We employ an image-to-image translation network $\mathcal{A}$, based on AvatarMe++ [24], that disentangles facial reflectance maps from the reconstructed 3DMM texture maps. In that manner, for each image $\mathbf{I}_i$, we acquire the shape $\mathbf{S}_i$, diffuse albedo $\mathbf{A}_{\mathbf{D}_i}^{\mathbf{VIS}}$, specular albedo $\mathbf{A}_{\mathbf{S}_i}^{\mathbf{VIS}}$ and specular normals $\mathbf{N}_{\mathbf{S}_i}^{\mathbf{VIS}}$, in the VIS domain:

$$\left[\mathbf{S}_i, \mathbf{A}_{\mathbf{D}_i}^{\mathbf{VIS}}, \mathbf{A}_{\mathbf{S}_i}^{\mathbf{VIS}}, \mathbf{N}_{\mathbf{S}_i}^{\mathbf{VIS}} \right] = \mathcal{A}(\mathcal{F}(\mathbf{I}_i)) \tag{1}$$

VIS to NIR Reflectance Transformation   Human skin is a dielectric material and exhibits both diffuse and specular reflectance. In the VIS spectrum, the diffuse albedo $\mathbf{A}_{\mathbf{D}}^{\mathbf{VIS}}$ describes the amount of light emitted per RGB channel when a medium is lit by uniform white illumination. On the other hand, the specular albedo $\mathbf{A}_{\mathbf{S}}^{\mathbf{VIS}}$ describes the intensity of the incoming illumination that is reflected, based on the direction of the specular normals $\mathbf{N}_{\mathbf{S}}^{\mathbf{VIS}}$. To transform these spatially-varying reflectance values to the NIR spectrum, we define the following empirical model, based on the assumption that the physical properties of the skin can be linearly described by the wavelength of the incident illumination, in the VIS ($380 - 700nm$) and a NIR illumination ($850nm$).

It is well-established that for specular normals measured under white illumination, shorter wavelength of incident illumination exhibit sharper surface details, due to the subsurface scattering of light in skin [30, 22]. For a green wavelength w^G and red-wavelength w^R we calculate the width σ of a gaussian kernel $\mathcal{G}$ required to minimize the error between the green channel $\mathbf{N}_{\mathbf{S}}^{\mathbf{G}}$ and red normals $\mathbf{N}_{\mathbf{S}}^{R}$ (Eq. 2). Then, for a NIR wavelength w^{NIR}, we linearly scale σ, based on the distance between the red and NIR wavelength and apply a gaussian kernel on VIS specular normals (green-channel) $\mathbf{N}_{\mathbf{S}}^{\mathbf{VIS}}$ to acquire the NIR specular normals $\mathbf{N}_{\mathbf{S}}^{\mathbf{NIR}}$:

$$\mathbf{N}_{\mathbf{S}}^{\mathbf{NIR}} = \mathcal{G}\left(\mathbf{N}_{\mathbf{S}}^{\mathbf{VIS}}, \frac{w^{NIR} - w^G}{w^R - w^G} \sigma \right), \quad \sigma = \arg\min_{\sigma} \left| \mathbf{N}_{\mathbf{S}}^{\mathbf{R}} - \mathcal{G}(\mathbf{N}_{\mathbf{S}}^{\mathbf{G}}, \sigma) \right|_2 \tag{2}$$

Figure 3: The comparisons between the traditional MMD loss, the Pairwise Mean Square Error (PMSE) and the proposed IDentity-based MMD (ID-MMD) loss. Different identities are represented by different colors (best viewed in color).

The NIR sensor is monochrome and its response is more similar to that of the VIS red channel. Given that a facial VIS diffuse albedo $\mathbf{A_D^{VIS}}$ is measured under uniform white light, its red channel $\mathbf{A_D^R}$ measures the skin's response to the red-wavelengths w^R. Assuming again a linear relationship between wavelength and spectral response between red and infrared, we define the NIR diffuse albedo $\mathbf{A_D^{NIR}}$, as the smoothed red channel albedo $\mathbf{A_D^R}$. In contrast to Eq. 2, here we use a Bilateral Filter [33], in order to preserve the edges of the facial details.

Finally, we retain the VIS specular albedo as $\mathbf{A_S^{VIS}} = \mathbf{A_S^{NIR}}$, since it is wavelength independent in the visible spectrum [30, 22]. However, we decrease the overall specular roughness, proportionally to the distance of the target NIR wavelength from the mean of the visible spectrum, following [39]. Following the above, we define the complete NIR-VIS transformation function as $\mathbf{A_D^{NIR}}, \mathbf{A_S^{NIR}}, \mathbf{N_S^{NIR}} = \mathcal{T}(\mathbf{A_D^{VIS}}, \mathbf{A_S^{VIS}}, \mathbf{N_S^{VIS}}, w^{NIR})$.

Paired NIR-VIS Rendering The importance of explicitly extracting diffuse and specular reflectance maps, lies in the fact that we can employ photorealistic rendering algorithms, such as GGX [34] in our case. We collect a set of n environment maps $\mathbf{E}_1, \ldots, \mathbf{E}_n \in \mathcal{E}$, that define omnidirectional incoming illumination of various realistic scenes [5]. We define a VIS physically-based rendering function $\mathcal{R}^{VIS}(\mathbf{S}, \mathbf{R^{VIS}}, \mathbf{M}, \mathbf{E}) \rightarrow \mathbf{I} \in \mathbb{R}^{h \times w \times 3}$, where h, w is the size of the rendered image, $\mathbf{S}$ is the facial shape, $\mathbf{R^{VIS}} = \left[\mathbf{A_D^{VIS}}, \mathbf{A_S^{VIS}}, \mathbf{N_S^{VIS}}\right]$ is the reflectance, $\mathbf{M}$ is a rotation matrix for the shape and $\mathbf{E}$ an environment map. For NIR rendering, we define a similar but monochrome rendering function $\mathcal{R}^{NIR}(\mathbf{S}, \mathbf{R^{NIR}}, \mathbf{M}, \mathbf{E}) \rightarrow \mathbf{I} \in \mathbb{R}^{h \times w \times 1}$. Finally, as NIR sensors typically rely on a flood illuminator placed adjacent to the lens, we create an environment map $\mathbf{E_f}$ with only a flood illuminator placed at the camera direction. Then, for a map $\mathbf{E_i}$, we define the equivalent NIR map as $\mathbf{E_i^{NIR}} = \frac{\mathbf{E_i} + \mathbf{E_f}}{||\mathbf{E_i} + \mathbf{E_f}||}$.

We then use the generated VIS and NIR facial assets and the VIS and NIR renderers, to generate sets of paired NIR-VIS facial images, under arbitrary illumination and pose. For each subject i and each pose-illumination set j, we use a random subject with shape $\mathbf{S_i}$ and reflectance $\mathbf{R_i^{VIS}}$ and $\mathbf{R_i^{NIR}}$, and sample a) a random environment map $\mathbf{E_j} \in \mathcal{E}$, which is rotated along the Y axis by a random angle $\theta_j \in [0, 360]$, b) a random rotation matrix $\mathbf{M_j}$ and render the paired images $\mathbf{I}_{i,j}^{VIS} = \mathcal{R}_i^{VIS}(\mathbf{S_i}, \mathbf{R_i^{VIS}}, \mathbf{M_j}, \mathbf{E_j})$ and $\mathbf{I}_{i,j}^{NIR} = \mathcal{R}_i^{NIR}(\mathbf{S_i}, \mathbf{R_i^{NIR}}, \mathbf{M_j}, \mathbf{E_j^{NIR}})$.

3.2 NIR-VIS Face Recognition

As a departure from most NIR-VIS face recognition works, the generated heterogeneous facial dataset is employed, along with a large-scale VIS face recognition dataset, to train a NIR-VIS face recognition network explicitly. Specifically, we present the large-scale VIS face recognition dataset containing C identities as $X = \{x_i\}_{i=1}^N$, and the corresponding identity label as $Y = \{y_i\}_{i=1}^C$. Similarly, the synthesized NIR-VIS dataset with C_s identities is denoted as $X_s = \{x_i\}_{i=1}^{N_s}$ with label $Y_s = \{y_i\}_{i=1}^{C_s}$. N and N_s denote the number of images in the VIS dataset and the synthesized NIR-VIS dataset, respectively. Note that, since the synthesized identities are from CelebA [28], there are no overlapped identities between the VIS face recognition dataset and the synthesized one. Given the final training set built by X and X_s, following [12], a widely-used face recognition network [37] is trained under the supervision of the identity loss and the proposed IDentity-based Maximum Mean Discrepancy (ID-MMD) loss. The NIR-VIS face recognition task is conducted with the identity features derived from the network.

Identity Loss To improve the discrimination power of the face recognition network, we employ the margin-based softmax loss [35] $\mathcal{L}_{id}$ during training, which is denoted as follows,

$$\mathcal{L}_{id} = -\frac{1}{N_r + N_s} \sum_i \log \frac{e^{s(\cos(\theta_{y_i},i)-m)}}{e^{s(\cos(\theta_{y_i},i)-m)} + \sum_{j \neq y_i} e^{s \cos \theta_{j,i}}}, \tag{3}$$

where $cos\theta_{j,i} = W_j^T f_i$, f_i is the normalized feature of i-th image, and W_j is the normalized weight vector of the j-th class. $\theta_{j,i}$ refers to the angle between W_j and f_i. m is the cosine margin and s is the feature scale. N_r and N_s are the training sample numbers of real VIS faces and synthesized NIR-VIS faces.

ID-MMD Loss To overcome the main challenge of the NIR-VIS face recognition task, *i.e.,* the cross-modality discrepancy, the Maximum Mean Discrepancy (MMD) loss [15] designed for the transfer learning task is adopted. Formally, given a mini-batch containing M NIR images and N VIS images, the MMD loss $\mathcal{L}_{mmd}$ is formulated as follows,

$$\mathcal{L}_{mmd} = \left\| \frac{1}{M} \sum_{i=1}^{M} \phi(x_i^{nir}) - \frac{1}{N} \sum_{j=1}^{N} \phi(x_j^{vis}) \right\|_{\mathcal{H}}^2, \tag{4}$$

where $\phi(\cdot)$ represents the kernel function that maps the original data to a Reproducing Kernel Hilbert Space (RKHS) $\mathcal{H}$. Although the MMD loss reduces the domain discrepancy by aligning NIR-VIS feature distributions, rigidly adopting such domain-level constraint to the NIR-VIS face recognition network training is sub-optimal, since it considers each modality as a whole and ignores the identity feature distribution within the modality, as shown in Fig 3.

To solve the problem, an explicit solution is reducing the distance between each NIR-VIS image pair of the same identity in the latent space, *i.e.,* minimizing the Pairwise Mean Square Error (PMSE) $\mathcal{L}_{pmse}$ between the NIR-VIS features. Concretely, random sampling P identities from the heterogeneous dataset, and for each identity, sampling K NIR images and K VIS images, to form the mini-batch with $2 \times PK$ images. The $\mathcal{L}_{pmse}$ is denoted as follows,

$$\mathcal{L}_{pmse} = \frac{1}{P} \frac{1}{K} \sum_{p=1}^{P} \sum_{k=1}^{K} \left\| f_{p,k}^{nir} - f_{p,k}^{vis} \right\|^2, \tag{5}$$

where $f_{p,k}^{nir/vis}$ denotes the normalized feature of k-th NIR/VIS image of p-th identity. Although the identity distribution is considered, such pairwise loss reduces the modality discrepancy at the instance level, where the network is highly likely to focus on facial details, such as poses and accessories, rather than identity features. Taking the girl wearing glasses in Fig. 3 as an example, the PMSE loss may reduce the feature distance between the NIR-VIS image pair by encouraging the network to attend to the frontal pose or the glasses, instead of the identity features.

To address the problems of the domain-based (MMD loss) and the instance-based (PMSE) modality discrepancy reduction loss, we propose an ID-based MMD loss $\mathcal{L}_{idmmd}$, which bridges the modality gap by reducing the distance between the NIR-VIS feature centroids of the same identity in the RKHS. Formally, for the given mini-batch, the proposed $\mathcal{L}_{idmmd}$ is denoted as follows,

$$\mathcal{L}_{idmmd} = \frac{1}{P} \sum_{p=1}^{P} \left\| \phi(\frac{1}{K} \sum_{k=1}^{K} f_{p,k}^{nir}) - \phi(\frac{1}{K} \sum_{k=1}^{K} f_{p,k}^{vis}) \right\|_{\mathcal{H}}^2. \tag{6}$$

The proposed identity-based modality discrepancy reduction loss not only reduces the modality gap between NIR and VIS images, but also encourages the features of the same identity within each modality to be compactly distributed, *i.e.,* reducing the intra-modality discrepancy. Overall, the objective of the NIR-VIS face recognition network is denoted as,

$$\mathcal{L} = \mathcal{L}_{id} + \lambda * \mathcal{L}_{idmmd}, \tag{7}$$

where λ is the balancing parameter, which is set as 100 during training.

4 Experiments

4.1 Databases and Protocols

Four NIR-VIS face recognition datasets are used to evaluate the proposed method. Specifically, the CASIA NIR-VIS 2.0 [26] (725 identities) and the LAMP-HQ [41] (573 identities) are the most challenging NIR-VIS face recognition datasets due to the huge facial appearance diversity in poses, illumination, and ages. Following [26, 41], the ten-fold experiments are conducted on both datasets. For each fold, approximately 50% identities are randomly selected as the training set and the rest are adopted as the testing set. Note that, there is no overlap between the training and testing sets. Following [12, 41], the verification rate (VR)@false accept rate (FAR)=0.01%, VR@FAR=0.1%, and the Rank-1 accuracy, are employed for evaluation. In terms of two low-shot NIR-VIS face recognition datasets: the Oulu-CASIA NIR-VIS [21] and the BUAA-VisNir [20], the identities within the datasets are split as 20/20 and 50/100, respectively, for the setting of the training/testing set. Considering the small data scale, the VR@FAR=0.1% and the Rank-1 accuracy are adopted as the evaluation metrics.

4.2 Experimental Details

NIR-VIS Face Generation. To acquire the 3D facial assets, we use AvatarMe++[24], trained with RealFaceDB [23] at textures of 1024×1024 pixels, on a GANFIT [14] base. The dataset used is CelebA [28], however other 2D facial datasets can be used to extend generalization. For the rendering, we employ highly parameterizable commercial rendering software named Marmoset. For each identity from CelebA, we synthesize 20 VIS faces and 20 NIR faces under different poses and illumination.

NIR-VIS Face Recognition Following [12], we utilize both LightCNN-9 and LightCNN-29 [37] as the NIR-VIS face recognition backbones. The large-scale VIS face recognition dataset used for training is the WebFace260M [44] dataset. To make a fair comparison with [12], which adopts about 5 million images from the MS-Celeb-1M [17] dataset for pre-training, we randomly choose 4 million images of 200k identities from the WebFace260M dataset to form a new VIS dataset for training, namely WebFace4M. Additionally, instead of using 128×128 facial images as inputs, all the face images are aligned and cropped to 112×112 [6] in the paper.

During training, we first train the network with identity loss $\mathcal{L}_{id}$ for 20 epochs on the WebFace4M and the synthesized dataset. Then, we fine-tune the network on the synthesized images with both identity loss $\mathcal{L}_{id}$ and ID-MMD loss $\mathcal{L}_{idmmd}$ for 5 epochs. The batch size is set as 512. During fine-tuning, 32 identities are randomly selected to form a mini-batch, and for each identity, 8 VIS and 8 NIR images are randomly selected. Stochastic gradient descent (SGD) is adopted as the optimizer, where the momentum is set to 0.9 and the weight decay is set to $1e$-4. The learning rate is set to $1e$-2 initially and decays by a factor of 0.5 per 10 epochs.

4.3 Ablation Study

NIR Reflectance Generation. We show the importance of each component in our proposed NIR reflectance generation method, by reconstructing subjects from LAMP-HQ [41] and showing the effectiveness of our algorithm against alternative approaches. In Fig. 4 and Tab. 1, we compare our method with monochrome rendering of VIS assets or remove some of our transformations. Not only our method is capable of producing photorealistic NIR renderings, but can do is in various poses while preserving the subject identity, since it is based on rendering 3D assets.

	Gray $\mathcal{R}^{\mathcal{VIS}}$	$\mathcal{R}^{\mathcal{NIR}}$	+$\mathbf{N_S^{NIR}}$	Ours
PSNR	16.61	17.32	17.34	**21.03**
MSE	0.021	0.018	0.018	**0.007**

Table 1: NIR rendering ablation study, showing average MSE and PSNR, for LAMP-HQ [41] reconstructions with our method and the ablation alternatives shown in Fig. 4.

Method	LightCNN-9		LightCNN-29	
	VIS	NIR	VIS	NIR
DVG-Face	1.46	1.35	1.43	1.32
Ours	1.10	1.08	0.99	0.96

Table 2: The quantitative comparisons of the Mean Identity feature Distance (MID) of multiple NIR and VIS images generated for the same identity. Lower is better.

Identity Consistency. To illustrate that our face generation method is able to preserve the identity among multiple generated NIR-VIS image pairs of the same identity, we compare the Mean Identity

(a) GT [41] (b) Gr. $\mathcal{R}^{\mathcal{VIS}}$ (c) $\mathcal{R}^{\mathcal{NIR}}$ (d) $+\mathbf{N_S^{NIR}}$ (e) Ours (f) Ours, 2nd (g) Ours, 3rd

Figure 4: From left to right: a) Ground Truth sample from LAMP-HQ[41], b) grayscale rendering with VIS Renderer $\mathcal{R}^{\mathcal{VIS}}$ and VIS assets, c) rendering with NIR Renderer $\mathcal{R}^{\mathcal{NIR}}$ of VIS assets with $\mathbf{E^{NIR}}$, d) NIR Renderer $\mathcal{R}^{\mathcal{NIR}}$ with our NIR-transformed normals $\mathbf{N_S^{NIR}}$, e) our complete method, including $\mathcal{R}^{\mathcal{NIR}}$, $\mathbf{N_S^{NIR}}$ and our transformed diffuse albedo $\mathbf{A_D}^{NIR}$ and f), g) additional poses.

feature Distance (MID) of NIR-VIS images generated by a state-of-the-art method, *i.e.,* DVG-Face [12], and the proposed method. Specifically, for each method, we randomly select 1000 identities from the generated dataset, and for each identity, 16 NIR images and 16 VIS images are randomly selected. We calculate the average distance between identity features of each person in each modality, which are extracted by the backbone face recognition networks, *i.e.,* LightCNN-9 and LightCNN-29, respectively. The results are reported in Table 2. As can be seen, the MID of faces generated by our method are lower than that by DVG-Face, which proves that our face generation method outperforms the generative model-based ones in terms of preserving the identity consistency.

Effectiveness of Generated Data. To prove that the NIR-VIS images generated by the proposed face generation method can significantly facilitate the NIR-VIS face recognition, we compare the performances of models trained without or with (+Fake) the generated dataset on four benchmark datasets in Table 4. As can be seen, the generated NIR-VIS faces contribute to an improvement of 8.2% on VR@FAR=0.01% with the backbone network LightCNN-9, and 7.5% with LightCNN-29 on the CASIA NIR-VIS 2.0 dataset. Also, with the help of the proposed Identity-based Maximum Mean Discrepancy (ID-MMD) loss, the performances are further boosted by 9.8% and 5% in terms of VR@FAR=0.01% with LightCNN-9 and LightCNN-29, respectively. Similar improvements are found on the other three datasets.

Comparisons of Domain Adaption Losses. To compare our ID-MMD loss with other modality discrepancy reduction losses, the ablation studies are conducted on LAMP-HQ dataset [41]. Specifically, MMD loss, PMSE loss, and ID-MMD loss, are employed to supervise the learning of the NIR-VIS face recognition network. The corresponding recognition performances are reported in Table 3. It can be observed that, the network achieves the best performance when optimizing by the proposed ID-MMD loss, surpassing the PMSE loss by 1.56% and the MMD loss by 1.04% in terms of VR@FAR=0.01%.

4.4 Comparisons with State-of-the-art Methods

We extensively compare our method with the state-of-the-art (SOTA) methods on four NIR-VIS face recognition benchmarks. The performances of SOTA methods, including TRIVET [27], IDR [18], W-CNN [19], ADFL [32], RCN [8], PCFH [42], MC-CNN [7], PACH [10], DVR [38], DVG [11], LAMP-HQ [41], and DVG-Face [12], are reported in Table 4. Following [12], we set the NIR-VIS face recognition baselines based on LightCNN-9 and LightCNN-29 [37]. Unlike [12], our baseline models, 1) are trained on the WebFace4M [44], 2) take 112×112 face images as input, 3) are trained under the margin-based softmax loss [35]. As can be seen in Table 4, our baseline models achieve a comparable performance with [37] at a lower computational cost.

We show that, with the aid of the synthesized NIR-VIS face images and the modality discrepancy reduction loss, our method greatly improves the baseline performances. On CASIA NIR-VIS 2.0,

	FAR=0.01%	FAR=0.1%	FAR=1%	Rank-1
$\mathcal{L}_{\text{pmse}}$	90.41 ± 1.5	96.88 ± 0.2	98.85 ± 0.2	97.85 ± 0.3
$\mathcal{L}_{\text{mmd}}$	90.93 ± 1.6	97.27 ± 0.3	99.09 ± 0.2	98.04 ± 0.3
$\mathcal{L}_{\text{idmmd}}$	$\mathbf{91.97 \pm 1.5}$	$\mathbf{97.96 \pm 0.3}$	$\mathbf{99.32 \pm 0.2}$	$\mathbf{98.87 \pm 0.3}$

Table 3: The comparisons between the performances of the backbone network (LightCNN-29) trained with different modality discrepancy reduction losses on the LAMP-HQ dataset.

Method	CASIA NIR-VIS 2.0			LAMP-HQ			Oulu-CASIA NIR-VIS		BUAA-VisNir	
	FAR=0.01%	FAR=0.1%	Rank-1	FAR=0.01%	FAR=0.1%	Rank-1	FAR=0.1%	Rank-1	FAR=0.1%	Rank-1
TRIVET [27]	74.5 ± 0.7	91.0 ± 1.3	95.7 ± 0.5	-	-	-	33.6	92.2	80.9	93.9
IDR [18]	-	95.7 ± 0.7	97.3 ± 0.4	-	-	-	46.2	94.3	84.7	94.3
W-CNN [19]	94.3 ± 0.4	98.4 ± 0.4	98.7 ± 0.3	-	-	-	54.6	98.0	91.9	97.4
ADFL [32]	-	97.2 ± 0.5	98.2 ± 0.3	-	73.3 ± 2.2	95.1 ± 0.5	60.7	95.5	88.0	95.2
RCN [8]	-	98.7 ± 0.2	99.3 ± 0.2	-	-	-	-	-	-	-
PCFH [42]	-	97.7 ± 0.3	98.8 ± 0.3	-	75.1 ± 1.8	95.3 ± 0.5	86.6	100.0	92.4	98.4
MC-CNN [7]	-	99.3 ± 0.1	99.4 ± 0.1	-	-	-	-	-	-	-
PACH [10]	-	98.3 ± 0.2	98.9 ± 0.2	-	75.3 ± 1.7	95.4 ± 0.5	88.2	100.0	93.5	98.6
DVR [38]	98.6 ± 0.3	99.6 ± 0.3	99.7 ± 0.1	-	-	-	84.9	100.0	96.9	99.2
DVG [11]	98.8 ± 0.2	99.8 ± 0.1	99.8 ± 0.1	-	-	-	92.9	100.0	97.3	99.3
LAMP-HQ [41]	-	98.2 ± 0.2	99.2 ± 0.0	-	78.2 ± 3.0	97.3 ± 0.2	89.0	100.0	93.4	98.8
DVG-Face [12]	99.2 ± 0.1	99.9 ± 0.0	99.9 ± 0.1	-	-	-	97.3	100.0	99.1	99.9
LC-9 [37]	-	93.7 ± 0.8	97.1 ± 0.7	-	71.61	89.77	43.8	93.8	83.5	94.8
LC$-9^{\dagger}$ ($\mathcal{L}_{id}$)	78.2 ± 2.1	91.5 ± 0.8	93.4 ± 0.9	77.1 ± 1.4	95.5 ± 0.4	95.0 ± 0.6	80.3	99.6	94.0	98.9
LC$-9^{\dagger}$ + Fake ($\mathcal{L}_{id}$)	86.4 ± 1.6	93.4 ± 0.4	97.0 ± 0.3	70.7 ± 2.4	88.1 ± 1.3	97.7 ± 0.4	86.2	99.7	97.4	99.4
LC$-9^{\dagger}$ + Fake ($\mathcal{L}_{id} + \mathcal{L}_{idmmd}$)	96.2 ± 0.4	99.0 ± 0.2	99.5 ± 0.1	80.7 ± 2.1	93.5 ± 1.0	98.3 ± 0.3	91.2	100.0	99.0	99.8
LC-29 [37]	-	97.4 ± 0.5	98.1 ± 0.4	-	75.6 ± 1.9	94.6 ± 0.3	68.3	99.0	89.4	96.8
LC$-29^{\dagger}$ ($\mathcal{L}_{id}$)	85.0 ± 1.9	95.0 ± 0.7	96.2 ± 0.7	67.3 ± 1.9	85.3 ± 1.0	96.1 ± 0.2	85.1	100.0	96.7	99.0
LC$-29^{\dagger}$ + Fake ($\mathcal{L}_{id}$)	92.5 ± 0.8	98.6 ± 0.4	98.8 ± 0.3	84.9 ± 1.6	96.1 ± 0.4	98.4 ± 0.3	91.8	100.0	99.4	99.9
LC$-29^{\dagger}$ + Fake ($\mathcal{L}_{id} + \mathcal{L}_{idmmd}$)	97.5 ± 0.5	99.6 ± 0.5	99.6 ± 0.1	92.0 ± 1.5	98.0 ± 0.3	98.9 ± 0.3	94.5	100.0	99.8	100.0
* LC-9 ($\mathcal{L}_{id}$)	98.3 ± 0.3	99.6 ± 0.2	99.8 ± 0.1	90.5 ± 2.0	97.6 ± 0.5	98.6 ± 0.3	93.7	100.0	99.3	100.0
* LC-9 ($\mathcal{L}_{id} + \mathcal{L}_{idmmd}$)	99.7 ± 0.2	99.9 ± 0.0	99.9 ± 0.1	98.1 ± 0.3	99.2 ± 0.3	99.0 ± 0.3	98.0	100.0	99.5	100.0
* LC-29 ($\mathcal{L}_{id}$)	98.8 ± 0.2	99.7 ± 0.2	99.8 ± 0.1	94.5 ± 0.8	98.7 ± 0.4	99.0 ± 0.3	95.2	100.0	100.0	100.0
* LC-29 ($\mathcal{L}_{id} + \mathcal{L}_{idmmd}$)	99.9 ± 0.1	100.0 ± 0.0	99.9 ± 0.1	98.6 ± 0.4	99.4 ± 0.3	99.1 ± 0.3	99.1	100.0	99.9	100.0

Table 4: Comparisons with the state-of-the-art NIR-VIS face recognition methods on the CASIA NIR-VIS 2.0, LAMP-HQ, Oulu-CASIA NIR-VIS, and BUAA-VisNir datasets. LC-9(29): Adopting the network structure of LightCNN-9(29). †: Our baseline models. Fake: The synthesized images being included during training. $\mathcal{L}_{id}$, $\mathcal{L}_{idmmd}$: The objective(s) used during training/fine-tuning. *: Fine-tuning on the target NIR-VIS datasets with the our NIR-VIS face recognition networks, *i.e.,* LC$-9\,(29)^{\dagger}$ + Fake* ($\mathcal{L}_{id} + \mathcal{L}_{idmmd}$).

VR@FAR=0.01% increases from 78.2% to 96.2% and Rank-1 accuracy increases from 93.4% to 99.5% with LightCNN-9. In terms of LightCNN-29, VR@FAR=0.01% increases from 85.0% to 97.5% and Rank-1 accuracy increases from 96.2% to 99.6%. As can be seen, without requiring any existing NIR-VIS face recognition datasets, our method has achieved comparable performances with the SOTA methods on the CASIA NIR-VIS 2.0 and the Oulu-CASIA NIR-VIS datasets, and has surpassed the SOTA performance by a large margin on the other two. Especially, on the challenging LAMP-HQ dataset, our method outperforms the SOTA method [41] by 19.8% and 1.6% in terms of VR@FAR=0.1% and the Rank-1 accuracy.

The performances can be further boosted after slightly fine-tuning the models on the target datasets. Specifically, as reported in the last four rows of Table 4, by adopting the identity loss ($\mathcal{L}_{id}$) during fine-tuning, VR@FAR=0.01% increases from 80.7% to 90.5% with LightCNN-9 and increases from 92.0% to 94.5% with LightCNN-29 on the LAMP-HQ dataset. After imposing the proposed ID-MMD loss ($\mathcal{L}_{idmmd}$) during the fine-tuning on target NIR-VIS face recognition datasets, the performances are further boosted. Concretely, an improvement of 7.6% and 4.1% on the VR@FAR=0.01% can be observed on the LAMP-HQ dataset, with LightCNN-9 and LightCNN-29, respectively. Additionally, on the two low-shot NIR-VIS face recognition datasets that fewer identities are contained, *i.e.,* the Oulu-CASIA NIR-VIS and BUAA-VisNir datasets, we surpass the second best method [12] by 1.8% and 0.8% in terms of VR@FAR=0.1%, respectively. In summary, after fine-tuning on the target NIR-VIS face recognition datasets, our method outperforms all other competitors on four benchmarks.

5   Conclusion

To address the problem of insufficient NIR-VIS data for the cross-modality face recognition network training, this paper proposes a novel NIR-VIS face generation method, which enables the generation of vast amounts of photorealistic paired NIR-VIS facial images with various poses and illumination while preserving the identity consistency. Such merit enables the use of the generated dataset, along with a large-scale VIS face recognition dataset, to train the NIR-VIS face recognition network, which can achieve comparable performance with the state-of-the-arts without requiring any existing NIR-VIS face recognition datasets. Additionally, to bridge the domain gap between NIR images and VIS images during training, an IDentity-based Maximum Mean Discrepancy (ID-MMD) loss is proposed, which reduces the modality discrepancy at the domain level and encourages the network to focus on identity features rather than facial details. Qualitative and quantitative experiment results on four NIR-VIS face recognition benchmarks show the superiority of the proposed method. Finally, understanding the **social impacts** of facial recognition, our method is modeled for and limited to mobile phone NIR sensors, and thus its use is aimed at more user-friendly experience for such devices.

References

[1] José Pedro Aguerre, Elena García-Nevado, Jairo Acuña Paz y Miño, Eduardo Fernández, and Benoit Beckers. Physically based simulation and rendering of urban thermography. In *Computer Graphics Forum*, volume 39, pages 377–391. Wiley Online Library, 2020.

[2] Oleg Alexander, Mike Rogers, William Lambeth, Jen-Yuan Chiang, Wan-Chun Ma, Chuan-Chang Wang, and Paul Debevec. The digital emily project: Achieving a photorealistic digital actor. *IEEE Computer Graphics and Applications*, 30(4):20–31, 2010.

[3] Andrew D Bagdanov, Alberto Del Bimbo, and Iacopo Masi. The florence 2d/3d hybrid face dataset. In *Proceedings of the 2011 joint ACM workshop on Human gesture and behavior understanding*, pages 79–80, 2011.

[4] Prashanth Chandran, Sebastian Winberg, Gaspard Zoss, Jérémy Riviere, Markus Gross, Paulo Gotardo, and Derek Bradley. Rendering with style: combining traditional and neural approaches for high-quality face rendering. *ACM Transactions on Graphics (TOG)*, 40(6):1–14, 2021.

[5] Paul Debevec. Rendering synthetic objects into real scenes: Bridging traditional and image-based graphics with global illumination and high dynamic range photography. In *Acm siggraph 2008 classes*, pages 1–10. 2008.

[6] Jiankang Deng, Jia Guo, Xue Niannan, and Stefanos Zafeiriou. Arcface: Additive angular margin loss for deep face recognition. In *CVPR*, 2019.

[7] Zhongying Deng, Xiaojiang Peng, Zhifeng Li, and Yu Qiao. Mutual component convolutional neural networks for heterogeneous face recognition. *TIP*, 2019.

[8] Zhongying Deng, Xiaojiang Peng, and Yu Qiao. Residual compensation networks for heterogeneous face recognition. In *AAAI*, 2019.

[9] Abdallah Dib, Cedric Thebault, Junghyun Ahn, Philippe-Henri Gosselin, Christian Theobalt, and Louis Chevallier. Towards high fidelity monocular face reconstruction with rich reflectance using self-supervised learning and ray tracing. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 12819–12829, 2021.

[10] Boyan Duan, Chaoyou Fu, Yi Li, Xingguang Song, and Ran He. Cross-spectral face hallucination via disentangling independent factors. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7930–7938, 2020.

[11] Chaoyou Fu, Xiang Wu, Yibo Hu, Huaibo Huang, and Ran He. Dual variational generation for low shot heterogeneous face recognition. *Advances in Neural Information Processing Systems*, 32, 2019.

[12] Chaoyou Fu, Xiang Wu, Yibo Hu, Huaibo Huang, and Ran He. Dvg-face: Dual variational generation for heterogeneous face recognition. *IEEE transactions on pattern analysis and machine intelligence*, 2021.

[13] Baris Gecer, Alexandros Lattas, Stylianos Ploumpis, Jiankang Deng, Athanasios Papaioannou, Stylianos Moschoglou, and Stefanos Zafeiriou. Synthesizing coupled 3d face modalities by trunk-branch generative adversarial networks. In *European conference on computer vision*, pages 415–433. Springer, 2020.

[14] Baris Gecer, Stylianos Ploumpis, Irene Kotsia, and Stefanos Zafeiriou. Ganfit: Generative adversarial network fitting for high fidelity 3d face reconstruction. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 1155–1164, 2019.

[15] Muhammad Ghifary, W Bastiaan Kleijn, and Mengjie Zhang. Domain adaptive neural networks for object recognition. In *Pacific Rim international conference on artificial intelligence*, pages 898–904. Springer, 2014.

[16] Abhijeet Ghosh, Graham Fyffe, Borom Tunwattanapong, Jay Busch, Xueming Yu, and Paul Debevec. Multiview face capture using polarized spherical gradient illumination. In *Proceedings of the 2011 SIGGRAPH Asia Conference*, pages 1–10, 2011.

[17] Yandong Guo, Lei Zhang, Yuxiao Hu, Xiaodong He, and Jianfeng Gao. Ms-celeb-1m: A dataset and benchmark for large-scale face recognition. In *European conference on computer vision*, pages 87–102. Springer, 2016.

[18] Ran He, Xiang Wu, Zhenan Sun, and Tieniu Tan. Learning invariant deep representation for NIR-VIS face recognition. In *AAAI*, 2017.

[19] Ran He, Xiang Wu, Zhenan Sun, and Tieniu Tan. Wasserstein cnn: Learning invariant features for nir-vis face recognition. *IEEE transactions on pattern analysis and machine intelligence*, 41(7):1761–1773, 2018.

[20] Di Huang, Jia Sun, and Yunhong Wang. The buaa-visnir face database instructions. 2012.

[21] Jie Chen, D. Yi, Jimei Yang, Guoying Zhao, S. Z. Li, and M. Pietikainen. Learning mappings for face synthesis from near infrared to visual light images. In *CVPR*, 2009.

[22] Christos Kampouris, Stefanos Zafeiriou, and Abhijeet Ghosh. Diffuse-specular separation using binary spherical gradient illumination. In *EGSR (EI&I)*, pages 1–10, 2018.

[23] Alexandros Lattas, Stylianos Moschoglou, Baris Gecer, Stylianos Ploumpis, Vasileios Triantafyllou, Abhijeet Ghosh, and Stefanos Zafeiriou. Avatarme: Realistically renderable 3d facial reconstruction" in-the-wild". In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 760–769, 2020.

[24] Alexandros Lattas, Stylianos Moschoglou, Stylianos Ploumpis, Baris Gecer, Abhijeet Ghosh, and Stefanos P Zafeiriou. Avatarme++: Facial shape and brdf inference with photorealistic rendering-aware gans. *IEEE Transactions on Pattern Analysis & Machine Intelligence*, (01):1–1, 2021.

[25] José Lezama, Qiang Qiu, and Guillermo Sapiro. Not afraid of the dark: Nir-vis face recognition via cross-spectral hallucination and low-rank embedding. In *Proceedings of the IEEE conference on computer*

vision and pattern recognition, pages 6628–6637, 2017.

[26] Stan Li, Dong Yi, Zhen Lei, and Shengcai Liao. The casia nir-vis 2.0 face database. In *Proceedings of the IEEE conference on computer vision and pattern recognition workshops*, pages 348–353, 2013.

[27] Xiaoxiang Liu, Lingxiao Song, Xiang Wu, and Tieniu Tan. Transferring deep representation for nir-vis heterogeneous face recognition. In *ICB*, 2016.

[28] Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

[29] Huiwen Luo, Koki Nagano, Han-Wei Kung, Qingguo Xu, Zejian Wang, Lingyu Wei, Liwen Hu, and Hao Li. Normalized avatar synthesis using stylegan and perceptual refinement. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11662–11672, 2021.

[30] Wan-Chun Ma, Tim Hawkins, Pieter Peers, Charles-Felix Chabert, Malte Weiss, Paul E Debevec, et al. Rapid acquisition of specular and diffuse normal maps from polarized spherical gradient illumination. *Rendering Techniques*, 2007(9):10, 2007.

[31] Soumyadip Sengupta, Angjoo Kanazawa, Carlos D Castillo, and David W Jacobs. Sfsnet: Learning shape, reflectance and illuminance of facesin the wild'. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 6296–6305, 2018.

[32] Lingxiao Song, Man Zhang, Xiang Wu, and Ran He. Adversarial discriminative heterogeneous face recognition. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

[33] Carlo Tomasi and Roberto Manduchi. Bilateral filtering for gray and color images. In *Sixth international conference on computer vision (IEEE Cat. No. 98CH36271)*, pages 839–846. IEEE, 1998.

[34] Bruce Walter, Stephen R Marschner, Hongsong Li, and Kenneth E Torrance. Microfacet models for refraction through rough surfaces. *Rendering techniques*, 2007:18th, 2007.

[35] Hao Wang, Yitong Wang, Zheng Zhou, Xing Ji, Dihong Gong, Jingchao Zhou, Zhifeng Li, and Wei Liu. Cosface: Large margin cosine loss for deep face recognition. In *CVPR*, 2018.

[36] Erroll Wood, Tadas Baltrušaitis, Charlie Hewitt, Sebastian Dziadzio, Thomas J Cashman, and Jamie Shotton. Fake it till you make it: Face analysis in the wild using synthetic data alone. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 3681–3691, 2021.

[37] Xiang Wu, Ran He, Zhenan Sun, and Tieniu Tan. A light cnn for deep face representation with noisy labels. *TIFS*, 2018.

[38] Xiang Wu, Huaibo Huang, Vishal M Patel, Ran He, and Zhenan Sun. Disentangled variational representation for heterogeneous face recognition. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pages 9005–9012, 2019.

[39] Xin Wu, Jianqi Zhang, Yang Chen, and Xi Huang. Real-time mid-wavelength infrared scene rendering with a feasible brdf model. *Infrared Physics & Technology*, 68:124–133, 2015.

[40] Haotian Yang, Hao Zhu, Yanru Wang, Mingkai Huang, Qiu Shen, Ruigang Yang, and Xun Cao. Facescape: a large-scale high quality 3d face dataset and detailed riggable 3d face prediction. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 601–610, 2020.

[41] Aijing Yu, Haoxue Wu, Huaibo Huang, Zhen Lei, and Ran He. Lamp-hq: A large-scale multi-pose high-quality database and benchmark for nir-vis face recognition. *International Journal of Computer Vision*, 129(5):1467–1483, 2021.

[42] Junchi Yu, Jie Cao, Yi Li, Xiaofei Jia, and Ran He. Pose-preserving cross spectral face hallucination. In *IJCAI*, pages 1018–1024, 2019.

[43] He Zhang, Benjamin S Riggan, Shuowen Hu, Nathaniel J Short, and Vishal M Patel. Synthesis of high-quality visible faces from polarimetric thermal faces using generative adversarial networks. *International Journal of Computer Vision*, 127(6):845–862, 2019.

[44] Zheng Zhu, Guan Huang, Jiankang Deng, Yun Ye, Junjie Huang, Xinze Chen, Jiagang Zhu, Tian Yang, Jiwen Lu, Dalong Du, et al. Webface260m: A benchmark unveiling the power of million-scale deep face recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10492–10502, 2021.