Multimodal Analogical Reasoning over Knowledge Graphs

Abstract

Analogical reasoning is fundamental to human cognition and holds an important place in various fields. However, previous studies mainly focus on single-modal analogical reasoning and ignore taking advantage of structure knowledge. Notably, the research in cognitive psychology has demonstrated that information from multimodal sources always brings more powerful cognitive transfer than single modality sources. To this end, we introduce the new task of multimodal analogical reasoning over knowledge graphs, which requires multimodal reasoning ability with the help of background knowledge. Specifically, we construct a **M**ultimodal **A**nalogical **R**easoning data**S**et (**MARS**) and a multimodal knowledge graph **MarKG**. We evaluate with multimodal knowledge graph embedding and pre-trained Transformer baselines, illustrating the potential challenges of the proposed task. We further propose a novel model-agnostic **M**ultimodal **a**nalogical **r**easoning framework with **T**ransformer (**MarT**) motivated by the structure mapping theory, which can obtain better performance. We hope our work can deliver benefits and inspire future research[1].

1 Introduction

Analogical reasoning – the ability to perceive and use relational similarity between two situations or events – holds an important place in human cognition (Johnson-Laird, 2006; Wu et al., 2020; Bengio et al., 2021; Chen et al., 2022a) and can provide back-end support for various fields such as education (Thagard, 1992), creativity (Goel, 1997), thus appealing to the AI community. Early, Mikolov et al. (2013b); Gladkova et al. (2016a); Ethayarajh et al. (2019a) propose visual analogical reasoning aiming at lifting machine intelligence in Computer Vision (CV) by associating vision with relational, structural, and analogical reasoning. Meanwhile, researchers of Natural Language Processing (NLP) hold the connectionist assumption (Gentner, 1983) of linear analogy (Ethayarajh et al., 2019b); for example, the relation between two words can be inferred through vector arithmetic of word embeddings. However, it is still an open question whether artificial neural networks are also capable of recognizing analogies among different modalities.

Note that humans can quickly acquire new abilities based on finding a common relational system between two exemplars, situations, or domains. Based on Mayer's Cognitive Theory of multimedia learning (Hegarty & Just, 1993; Mayer, 2002), human learners often perform better on tests with analogy when they have learned from multimodal sources than single-modal sources. Evolving from recognizing single-modal analogies to exploring multimodal reasoning for neural models, we emphasize the importance of a new kind of analogical reasoning task with Knowledge Graphs (KGs).

In this paper, we introduce the task of multimodal analogical reasoning over knowledge graphs to fill this blank. Unlike the previous multiple-choice QA setting, we directly predict the analogical target and formulate the task as **link prediction without explicitly providing relations**. Specifically, the task can be formalized as $(e_h, e_t) : (e_q, ?)$ with the help of background multimodal knowledge graph $\mathcal{G}$, in which e_h, e_t or e_q have different modalities. We collect a **M**ultimodal **A**nalogical **R**easoning data**S**et (**MARS**) and a multimodal knowledge graph **MarKG** to support this task. These data are collected and annotated from seed entities and relations in E-KAR (Chen et al., 2022a) and BATs (Gladkova et al., 2016a), with linked external entities in Wikidata and images from Laion-5B (Schuhmann et al., 2021).

---

[1]Data and code are in the supplementary materials and will be released.

To evaluate the multimodal analogical reasoning process, we follow the guidelines from psychological theories and conduct comprehensive experiments on MARS with multimodal knowledge graph embedding baselines and multimodal pre-trained Transformer baselines. We further propose a novel **M**ultimodal **a**nalogical **r**easoning framework with **T**ransformer, namely **MarT**, which is readily pluggable into any multimodal pre-trained Transformer models and can yield better performance.

To summarize, our contributions are three-fold: (1) We advance the traditional setting of analogy learning by introducing a new multimodal analogical reasoning task. Our work may open up new avenues for improving analogical reasoning through multimodal resources. (2) We collect and build a dataset MARS with a multimodal knowledge graph MarKG, which can be served as a scaffold for investigating the multimodal analogy reasoning ability of neural networks. (3) We report the performance of various multimodal knowledge graph embedding, multimodal pre-trained Transformer baselines, and our proposed framework MarT. We further discuss the potential of this task and hope it facilitates future research on zero-shot learning and domain generalization in both CV and NLP.

2 BACKGROUND

2.1 ANALOGICAL REASONING IN PSYCHOLOGICAL

To better understand analogical reasoning, we introduce some crucial theories from cognitive psychology, which we take as guidelines for designing the multimodal analogical reasoning task.

Structure Mapping Theory (SMT) (Gentner, 1983)**.** SMT is a theory that takes a fundamental position in analogical reasoning. Specifically, SMT emphasizes that humans conduct analogical reasoning depending on the shared *relations* structure rather than the superficial *attributes* of domains and distinguishes analogical reasoning with literal similarity. Minnameier (2010) further develops the inferential process of analogy into three steps: abduction, mapping and induction, which inspires us to design benchmark baselines for multimodal analogical reasoning.

Mayer's Cognitive Theory (Hegarty & Just, 1993; Mayer, 2002)**.** Humans live in a multi-source heterogeneous world and spontaneously engage in analogical reasoning to make sense of unfamiliar situations in everyday life (Vamvakoussi, 2019). Mayer's Cognitive Theory shows that human learners often perform better on tests of recall and transfer when they have learned from multimodal sources than single-modal sources. However, relatively little attention has been paid to multimodal analogical reasoning, and it is still unknown whether neural network models have the ability of multimodal analogical reasoning.

2.2 ANALOGICAL REASONING IN CV AND NLP

Visual Analogical Reasoning. Analogical reasoning in CV aims at lifting machine intelligence by associating vision with relational, structural, and analogical reasoning (Johnson et al., 2017; Prade & Richard, 2021; Hu et al., 2021; Malkinski & Mandziuk, 2022). Some datasets built in the context of Raven's Progressive Matrices (RPM) are constructed, including PGM (Santoro et al., 2018) and RAVEN (Zhang et al., 2019). Meanwhile, Hill et al. (2019) demonstrates that incorporating structural differences with structure mapping in analogical visual reasoning benefits the machine learning models. Hayes & Kanan (2021) investigates online continual analogical reasoning and demonstrates the importance of the selective replay strategy. However, these aforementioned works still focus on analogy reasoning among visual objects while ignoring the role of complex texts.

Natural Language Analogical Reasoning. In the NLP area, early attempts devote to word analogy recognition (Mikolov et al., 2013b; Gladkova et al., 2016a; Jurgens et al., 2012; Ethayarajh et al., 2019a; Gladkova et al., 2016b) which can often be effectively solved by vector arithmetic for neural word embeddings Word2Vec (Mikolov et al., 2013a) and Glove (Pennington et al., 2014). Recent studies have also evaluated on the pre-trained language models (Devlin et al., 2019; Brown et al., 2020; Ushio et al., 2021). However, word analogies mainly measure the quality of word representations and do not explore the analogical reasoning ability of models. Thus, Chen et al. (2022a) builds a knowledge-intensive benchmark to evaluate the analogical reasoning ability of neural models. Nevertheless, Chen et al. (2022a) mainly focuses on reasoning in the textual domain and does not consider using external knowledge graphs. In this work, we take the first step to investigate multimodal analogical reasoning over knowledge graphs.

Figure 1: Overview of the Multimodal Analogical Reasoning task. We divide the task into single and blended settings with a multimodal knowledge graph. Note that the relation marked by dashed arrows (--→) and the text around parentheses under images are **only for annotation** and **not provided in the input**.

3 THE MULTIMODAL ANALOGICAL REASONING TASK

3.1 TASK DEFINITION

In this section, we introduce the task of Multimodal Analogical Reasoning that can be formulated as link prediction **without explicitly providing relations**. As shown in Figure 1, given an analogy example (e_h, e_t) and a question-answer entity pair $(e_q, ?)$ where $e_h, e_t, e_q \in \mathcal{E}_a$ and $\mathcal{E}_a \in \mathcal{E}$, the goal of analogical reasoning is to predict the missing answer entity $e_a \in \mathcal{E}_a$. Moreover, multimodal analogical reasoning is based on background multimodal knowledge graph $\mathcal{G} = (\mathcal{E}, \mathcal{R}, \mathcal{I}, \mathcal{T})$, where $\mathcal{E}$ and $\mathcal{R}$ are sets of entities and relations, $\mathcal{I}$ and $\mathcal{T}$ represent images and textual descriptions of entities. Note that the relations of (e_h, e_t) and (e_q, e_a) are identical but unavailable, and the relation structure can be analogized implicitly from the source domain to the target domain without knowing the relations. Specifically, the task can be formalized as $(e_h, e_t) : (e_q, ?)$, and further divided into *Single Analogical Reasoning* and *Blended Analogical Reasoning* according to the different modalities of e_h, e_t, e_q and e_a.

Single Analogical Reasoning. In this setting, the analogy example and the question-answer entity pair involve only one modality. As shown in the middle column of Figure 1, the modalities of the analogy example (e_h, e_t) are identical and opposite to the analogy question-answer pair (e_q, e_a). Based on both visual and textual modalities, this setting can be further divided into $(I_h, I_t) : (T_q, ?)$ and $(T_h, T_t) : (I_q, ?)$ where I_h, T_h represent the modality of e_h is visual or textual respectively.

Blended Analogical Reasoning. In the setting, the modality of analogy example (e_h, e_t) are unidentical, which is similar to real-world human cognition and perception[2]. Note that Mayer's theory indicates that humans can have powerful transfer and knowledge recall abilities in multimodal scenarios. Inspired by this, we propose the blended analogical reasoning that can be formalized as $(I_h, T_t) : (I_q, ?)$, which means the modalities between e_h (e_q) and e_t (e_a) are different.

3.2 DATA COLLECTION AND PREPROCESSING

We briefly introduce the construction process of the dataset in Figure 2. Firstly, we collect a multimodal knowledge graph dataset MarKG and a multimodal analogical reasoning dataset MARS, which are developed from seed entities and relations in E-KAR (Chen et al., 2022a) and BATs (Gladkova et al., 2016a). Secondly, we link these seed entities into the free and open knowledge base Wikidata[3] for formalization and normalization. Thirdly, to acquire the image data, we further search from the Google engine and query from the multimodal data Laion-5B (Schuhmann et al., 2021) by the text descriptions of entities. Then, an image validation strategy is applied to filter

---

[2]For example, humans invented hieroglyphics by analogy from the concrete world.
[3]https://www.wikidata.org/wiki/Wikidata:Main_Page

Figure 2: An illustration of data collection and processing steps to create MARS and MarKG.

Dataset	Size (train / dev / test)	KB	Modality	# Entity	# Relation	# Images	Knowledge Intensive	Task Format
RAVEN	42,000 / 14,000 / 14,000	✗	Vision	-	8	1,120,000	✗	Classification
SAT	0 / 37 / 337	✗	Text	-	19	-	✗	Linear Word Analogy
Google	0 / 50 / 500	✗	Text	919	14	-	✗	Linear Word Analogy
BATs	0 / 199 / 1,799	✗	Text	6,218	40	-	✗	Linear Word Analogy
E-KAR	870 / 119 / 262	✗	Text	2,651	28	-	✔	Multiple Choice QA
MARS	10,685 / 1,228 / 1,415	MarKG	Vision+Text	2,063	27	13,398	✔	Entity Prediction

Table 1: Comparison between MARS and previous analogical reasoning datasets. "KB" refers to the knowledge base, and # denotes the number. "Knowledge Intensive" means reasoning requires external knowledge. Our MarKG focuses on knowledge-intensive reasoning across multiple modalities.

low-quality images. Lastly, we sample high-quality analogy data to construct MARS. A detailed description of the data collection and processing to create our datasets are in Appendix B.1 and B.2.

3.3 DATASET STATISTICS

MARS is the evaluation dataset of the multimodal analogical reasoning task that contains analogy instances, while MarKG can provide the relative structure information of those analogy entities retrieved from Wikidata. The statistics of MARS and MarKG are shown in Table 1 and Table 5. MarKG has 11,292 entities, 192 relations and 76,424 images, include 2,063 analogy entities and 27 analogy relations. MARS has 10,685 training, 1,228 validation and 1,415 test instances, which are more significant than previous language analogy datasets. More details including **quality control** can be found in Appendix B.3.

3.4 EVALUATION METRICS

Previous study (Chen et al., 2022a) adopts the multiple-choice QA to conduct analogical reasoning and leverage the accuracy metric for evaluation. However, the multiple-choice QA setting may struggle to handle the *one-to-more entities*[4], which is very common in real-world analogy scenarios. Thus, we formulate the task as link prediction that directly predicts the answer entity $e_a \in \mathcal{E}_a$. Our evaluation metrics include Hits@k scores (proportion of valid entities ranked in top k) and MRR (reciprocal value of the mean rank of correct entities). More details can be found in Appendix B.4.

4 BENCHMARK METHODS

In this section, we introduce some baselines to establish the initial benchmark results on MARS, including multimodal knowledge graph embedding baselines and multimodal pre-trained Transformer baselines. We further propose MarT: a multimodal analogical reasoning framework with Transformer, which can capture fine-grained associations between one analogy example and one analogy question-answer pair for better multimodal analogy abilities.

---

[4]One entity may be an instance of multiple super-entities, but multiple-choice QA can only have one golden answer entity.

Figure 3: Overview of baseline methods. (a) Pipeline of MKGE methods for multimodal analogical reasoning. (b) and (c) are two stages of multimodal pre-trained Transformer (MPT) baselines.

4.1 Multimodal Knowledge Graph Embedding Baselines

We consider three multimodal knowledge embedding (MKGE) approaches as our baselines, including **IKRL** (Xie et al., 2017), **TransAE** (Wang et al., 2019), and **RSME** (Wang et al., 2021). These methods are typically based on TransE (Bordes et al., 2013) or ComplEx (Trouillon et al., 2016) and combine with visual encoders to encode images for multimodal knowledge representation learning. They can not be directly applied to the multimodal analogical reasoning task. To successfully utilize MKGE methods, we first pre-train them on MarKG to obtain entity embeddings and then follow the structure-mapping theory (Minnameier, 2010) to leverage the *Abudction-Mapping-Induction* as **explicit pipline** steps for MKGE methods. As shown in Figure 3.a, *Abduction* aims to predict the relation r of (e_h, e_t) similar to the relation classification task, *Mapping* represents that the structural relation is mapped onto entity candidates, analogous to template-filling, and *Induction* utilizes the relation r to predict the tail entity of $(e_q, r, ?)$ similar to the link prediction task.

Despite the previous MKGE methods achieving excellent performance for KG-related tasks, the backbone, such as TransE, is not designed for analogy reasoning, which may hinder performance. Thus, we replace the backbone of MKGE methods with ANALOGY Liu et al. (2017) that models analogical structure explicitly as baselines.

4.2 Multimodal Pre-trained Transformer Baselines

We select multimodal pre-trained Transformer (MPT) approaches including the single-stream models **VisualBERT** (Li et al., 2019), **ViLT** (Kim et al., 2021), the dual-stream model **ViLBERT** (Lu et al., 2019), and the mixed-stream model **FLAVA** (Singh et al., 2021) and **MKGformer** Chen et al. (2022b) as the strong baselines. However, the current multimodal pre-trained Transformer cannot directly deal with analogical reasoning. To address the bottleneck above, we devise an **end-to-end** approach to empower the MPT with analogical reasoning ability. As shown in Figure 3, we first leverage MarKG to pre-train the model over sparse MarKG to obtain the representation of entities and relations. We then present the prompt-based analogical reasoning over MARS.

4.2.1 Pre-train over MarKG

We represent the entities $e \in \mathcal{E}$ and relations $r \in \mathcal{R}$ as special tokens and denote E as the learnable embedding of these special tokens in the word vocabulary of language models. In the pre-train stage, we design masked entity and relation prediction like the Masked Language Modeling (MLM) task to learn the embeddings of the special tokens over the MarKG dataset. As shown in Figure 3.b, we devise a prompt template to convert the input as predicting the missing entity and relation via [MASK] token. In addition, we mix missing relation and entity prediction in the pre-train stage and consider different modalities of input entities. Specifically, we represent the visual entity e_h by its image I_h and special entity embedding E_{e_h}, and the text entity e_t by its text description T_t and special entity embedding E_{e_t}, respectively. Benefiting from the mixed entity and relation prediction

with the multimodal entity in the pre-train stage, we can obtain KG embedding with multimodal semantics over the current knowledge graph MarKG.

4.2.2 PROMPT-BASED ANALOGICAL REASONING

Based on the above-pre-trained entity and relation embeddings over MarKG, we propose prompt-based analogical reasoning with implicit structure mapping on downstream MARS.

Taking the blended analogical reasoning as an example, we feed the analogy example (I_h, T_t) and analogy question-answer pair $(I_q, ?)$ as input, and the goal is to predict the missing answer entity $e_a \in \mathcal{E}_a$. We leverage an analogical prompt template to convert the input as follows:

$$\mathcal{T}_{(I_h, T_t, I_q)} = \mathcal{T}_{\mathcal{E}} \parallel \mathcal{T}_{\mathcal{A}} = I_h \, I_q \, [\texttt{CLS}] \, e_h \, [\texttt{R}] \, T_t \, e_t \, [\texttt{SEP}] \parallel e_q \, [\texttt{R}] \, [\texttt{MASK}] \, [\texttt{SEP}], \quad (1)$$

where $\parallel$ represents concatenate operation in the template input, I_h and I_q represents the images of the entity e_h and e_q, T_t is the text description of the entity e_t. After the word embedding layer, the e_* will be encoded to E_{e_*}. Since the relations are not explicitly provided in the actual analogical reasoning task, we assign $[\texttt{R}]$ as a special token to denote the explicit relation between (I_h, T_t), which is initialized with the average relation embeddings.

Remark 1 *We summarize the two parts of $\mathcal{T}_{\mathcal{E}}$ and $\mathcal{T}_{\mathcal{A}}$ in the template as the implicit Abduction and Induction respectively, which are unified in an end-to-end learning manner with prompt tuning. In addition, the analogical reasoning is reformulated as predicting the* $[\texttt{MASK}]$ *over the multimodal analogy entity embeddings to obtain e_a.*

4.3 MART: A MULTIMODAL ANALOGICAL REASONING FRAMEWORK WITH TRANSFORMER

Figure 4: The MarT framework.

Although the approach above-mentioned can enable multimodal pre-trained Transformer models to multimodal analogical reasoning, they only superficially consider implicit *Abduction* and *Induction*, ignoring the fine-grained associations between the analogy example and analogy question-answer pair.

Adaptive Interaction Across Analogy. Since the analogy question may interfere with the representation of the analogy example and the inevitable noise data issue, we propose adaptive interaction across analogy in the encoding process, to interact between the analogy example and question-answer pair adaptively, as shown in Figure 4. Denote the input to a Transformer layer as $X = [X_{\mathcal{E}} \parallel X_{\mathcal{A}}]$, where $X_{\mathcal{E}}$ and $X_{\mathcal{A}}$ denote the hidden representation of analogy example $\mathcal{T}_{\mathcal{E}}$ and analogy question-answer pair $\mathcal{T}_{\mathcal{A}}$ respectively. In each attention head of the layer, the query and key representation can be formalized as:

$$Q = XW^Q = \begin{pmatrix} X_{\mathcal{E}} \\ X_{\mathcal{A}} \end{pmatrix} W^Q = \begin{pmatrix} Q_{\mathcal{E}} \\ Q_{\mathcal{A}} \end{pmatrix}, K = XW^K = \begin{pmatrix} X_{\mathcal{E}} \\ X_{\mathcal{A}} \end{pmatrix} W^K = \begin{pmatrix} K_{\mathcal{E}} \\ K_{\mathcal{A}} \end{pmatrix}, \quad (2)$$

where W^Q, W^K are project matrices. A similar expression also holds for values V. Then the attention probability matrix P can be defined in terms of four sub-matrices:

$$P = QK^\top = \begin{pmatrix} Q_{\mathcal{E}} \\ Q_{\mathcal{A}} \end{pmatrix} (K_{\mathcal{E}}^\top, K_{\mathcal{A}}^\top) = \begin{pmatrix} Q_{\mathcal{E}} K_{\mathcal{E}}^\top & Q_{\mathcal{E}} K_{\mathcal{A}}^\top \\ Q_{\mathcal{A}} K_{\mathcal{E}}^\top & Q_{\mathcal{A}} K_{\mathcal{A}}^\top \end{pmatrix} = \begin{pmatrix} P_{\mathcal{E}\mathcal{E}} & P_{\mathcal{E}\mathcal{A}} \\ P_{\mathcal{A}\mathcal{E}} & P_{\mathcal{A}\mathcal{A}} \end{pmatrix} \quad (3)$$

where $P_{\mathcal{E}\mathcal{E}}, P_{\mathcal{A}\mathcal{A}}$ (diagonal of P) are intra-analogy attentions and $P_{\mathcal{E}\mathcal{A}}, P_{\mathcal{A}\mathcal{E}}$ (anti-diagonal of P) are inter-analogy attentions. We use the gate G to regulate the inter-analogy interactions adaptively:

$$P' = G \odot P = \begin{pmatrix} 1 & g_{\mathcal{E}\mathcal{A}} \\ g_{\mathcal{A}\mathcal{E}} & 1 \end{pmatrix} \odot \begin{pmatrix} P_{\mathcal{E}\mathcal{E}} & P_{\mathcal{E}\mathcal{A}} \\ P_{\mathcal{A}\mathcal{E}} & P_{\mathcal{A}\mathcal{A}} \end{pmatrix} = \begin{pmatrix} P_{\mathcal{E}\mathcal{E}} & g_{\mathcal{E}\mathcal{A}} P_{\mathcal{E}\mathcal{A}} \\ g_{\mathcal{A}\mathcal{E}} P_{\mathcal{A}\mathcal{E}} & P_{\mathcal{A}\mathcal{A}} \end{pmatrix} \quad (4)$$

where $G \in \mathbb{R}^{2 \times 2}$ is adaptive association gate which has two learnable variables $g_{\mathcal{E}\mathcal{A}}, g_{\mathcal{A}\mathcal{E}} \in [0, 1]$.

Remark 2 *On the one hand, the query example from $\mathcal{T}_{\mathcal{A}}$ may interfere with the example from $\mathcal{T}_{\mathcal{E}}$. On the other hand, $\mathcal{T}_{\mathcal{E}}$ may have a weaker impact on $\mathcal{T}_{\mathcal{A}}$ in noise data. Adaptive association gates can increase and decrease the inter-analogy interactions automatically based on the intimacy of $\mathcal{T}_{\mathcal{E}}$ and $\mathcal{T}_{\mathcal{A}}$.*

Method	Baselines	Backbone	Hits@1	Hits@3	Hits@5	Hits@10	MRR
MKGE	IKRL	TransE	0.254	0.285	0.290	0.304	0.274
	TransAE	TransE	0.203	0.233	0.241	0.253	0.223
	RSME	ComplEx	0.255	0.274	0.282	0.291	0.268
	IKRL	ANALOGY	0.266	0.294	0.301	0.310	0.283
	TransAE	ANALOGY	0.261	0.285	0.289	0.293	0.276
	RSME	ANALOGY	0.266	0.298	0.307	0.311	0.285
MPT	VisualBERT	Single-Stream	0.247	0.281	0.289	0.303	0.269
	ViLT	Single-Stream	0.235	0.266	0.274	0.286	0.257
	ViLBERT	Dual-Stream	0.252	0.308	0.320	0.338	0.287
	FLAVA	Mixed-Stream	0.257	0.299	0.312	0.325	0.284
	MKGformer	Mixed-Stream	0.293	0.335	0.344	0.367	0.321
	MarT_VisualBERT	Single-Stream	0.261	0.292	0.308	0.321	0.284
	MarT_ViLT	Single-Stream	0.245	0.275	0.287	0.303	0.266
	MarT_ViLBERT	Dual-Stream	0.256	0.312	0.327	0.347	0.292
	MarT_FLAVA	Mixed-Stream	0.264	0.303	0.309	0.319	0.288
	MarT_MKGformer	Mixed-Stream	**0.301**	**0.367**	**0.380**	**0.408**	**0.341**

Table 2: The main performance results on MARS. We report pipeline baselines with multimodal knowledge graph embedding (MKGE) methods and replace their backbone models with analogy-aware model ANALOGY. We also utilize our MarT on end-to-end baselines with multimodal pre-trained Transformer (MPT) methods and obtain the best performance in MarT_MKGformer.

Relation-Oriented Structure Mapping. The structure mapping theory described that *relations between objects, rather than attributes of objects, are mopped from base to target.* For example, *battery* can make an analogy to *reservoir* because they both store potential, rather than their shapes being cylindrical. Motivated by this, we propose the **relaxation loss** to bring the relations closer and alienate the entities:

$$\mathcal{L}_{\text{rel}} = \frac{1}{|\mathcal{S}|} \sum_i^{|\mathcal{S}|} (\underbrace{1 - \text{sim}(h_{[\text{R}]}^{\mathcal{E}}, h_{[\text{R}]}^{\mathcal{A}})}_{\text{close relations}} + \underbrace{\max(0, \text{sim}(h_{e_h}, h_{e_q}))}_{\text{alienate entities}})) \tag{5}$$

where $|\mathcal{S}|$ is the total number of the training set $\mathcal{S}$, $h_{[\text{R}]}^{\mathcal{E}}$ is the hidden feature of $[\text{R}]$ in analogy example $\mathcal{T}_{\mathcal{E}}$ output from the MLM head, $\text{sim}(\cdot)$ is the cosine similarity. We leverage the masked entity prediction task to obtain the answer entity e_a with a cross-entropy loss:

$$\mathcal{L}_{\text{mem}} = -\frac{1}{|\mathcal{S}|} \sum_{(e_h, e_t, e_q, e_a) \in \mathcal{S}} \log(p([\text{MASK}] = e_a) | \mathcal{T}_{(e_h, e_t, e_q)}) \tag{6}$$

Afterwards, we interpolate the relaxation loss $\mathcal{L}_{\text{rel}}$ and the masked entity prediction loss $\mathcal{L}_{\text{mem}}$ using parameter λ to produce the final loss $\mathcal{L}$:

$$\mathcal{L} = \lambda \mathcal{L}_{\text{rel}} + (1 - \lambda) \mathcal{L}_{\text{mem}} \tag{7}$$

Remark 3 *The relaxation loss is composed of pull-in and pull-away that correspond to the close relation and alienate entity terms, respectively, which can constrain the model's focus on relation structure transfer and implicitly realize the Structure Mapping process.*

5 RESULTS AND ANALYSIS

5.1 MAIN RESULTS

The main performance results of all benchmark methods can be seen in Table 2. In general, we find the performance of multimodal knowledge graph embedding (MKGE) baselines and multimodal pre-trained Transformer (MPT) baselines is comparable except MKGformer, which establishes a competitive baseline of MARS. In addition, when replacing the backbone of MKGE methods with

Model	Hits@1	Hits@3	Hits@5	Hits@10	MRR
TransAE	0.203	0.233	0.241	0.253	0.223
w/o MarKG	0.191	0.224	0.235	0.245	0.214
MarT_ViLBERT	0.256	0.312	0.327	0.347	0.292
w/o MarKG	0.253	0.292	0.297	0.310	0.270
MarT_MKGformer	**0.301**	**0.367**	**0.380**	**0.408**	**0.341**
w/o MarKG	0.270	0.305	0.309	0.315	0.289
w/o Relaxation loss	0.295	0.349	0.373	0.399	0.332
w/o Adaptive interaction	0.285	0.345	0.365	0.395	0.324
w/o MarT	0.293	0.335	0.344	0.367	0.321

Table 4: Ablation experiments on MARS. *w/o MarKG* refers to the model without pre-training on MarKG dataset. w/o MarT refers to ablate all components of MarT that equivalents to MKGformer.

ANALOGY that models analogical structure explicitly, the performance is significantly improved. Meanwhile, the MPT models without analogy-related structures obtain substantial performance with the analogical reasoning ability enhanced by MarT. For example, although MKGformer achieves outstanding performance, MarT_MKGformer further improves and obtains state-of-the-art performance, exceeding other methods by 4.9%-12.4% points in the MRR metric. It reveals that the MarT framework stimulates the ability of the Transformer-based model for multimodal analogical reasoning. We also report the pre-training results on MarKG in Appendix C.2.

5.2 GENERALIZE TO NOVEL RELATION

Making analogies from one domain to another novel domain is a fundamental ingredient for human creativity. In this section, we conduct a novel relation transfer experiment (including both task settings) to measure how well the models generalize by analogy to unfamiliar relations. Specifically, we randomly split the 27 analogy relations into the source and target relations. The models are then trained on the source and tested on the novel target relations. As shown in Table 3, we observe that MarT_MKGformer can indeed learn to make

Model	Novel Relation Transfer			
	Hits@1	Hits@3	Hits@10	MRR
MarT_MKGformer	0.254	0.285	0.292	0.273
w/o MarKG	0.217	0.228	0.231	0.224
w/ Full MARS	0.365	0.419	0.433	0.395

Table 3: Results of novel relation generalization, we test the most strong baseline MKGformer on novel target relations data. "w/ Full MARS" is the result trained with full data (upper bound).

sense of unfamiliar relations, respectively. We further evaluate the model without pre-training on MarKG and find the performance decreased, which indicates that the structure knowledge provided by MarKG is critical for generalization. Note that the novel relation transfer setting is somewhat similar to zero-shot or domain generalization, and we hope our work can benefit other communities.

5.3 ABLATION STUDY

To validate the effectiveness of MarKG and MarT, we conduct an ablation study as shown in Table 4. We observe that discarding pre-train on MarKG results in worse performance for both MKGE and MPT baselines. It indicates that the knowledge structure information provided by MarKG helps learn the representation of entities and relations, further benefiting analogical reasoning. We also find that the performance clearly drops when ablating each component of MarT and reaches the valley when ablating all, proving the effectiveness of each analogical component of our MarT.

5.4 ANALYSIS

Analysis across Different Sub-Tasks. In previous Table 2, we are amazed by ANALOGY significantly improving the performance of MKGE baselines. Therefore, we further compare the performance of vanilla baselines to the addition of analogical components in different sub-task settings. As shown in Figure 5, we observe that vanilla TransAE performs poorly in the blended task setting. However, when replacing the backbone TransE with ANALOGY, TransAE is competent in blended analogical reasoning setting and even outperforms the single setting. On the other side, RSME with

Task Setting	Analogical Example	Question-Answer Pair	Top-3 Entity				Gold Rank
(I_h, I_t) ↓ $(T_q, ?)$	Qinghai Lake *correspond to* Inland Lake	campaign *correspond to* ? battle	MKGformer	film	increment	scheme	207
			MKGformer*	**battle**	war	siege	1
			TransAE	life	aircraft	ocean	254
			TransAE*	**battle**	reaction	court	1
(I_h, T_t) ↓ $(I_q, ?)$	Panax notoginseng *instance of* Traditional Chinese Medicine	Apple *instance of* ? fruit	MKGformer	bread	capital	phone	80
			MKGformer*	**fruit**	dried fruit	citrus	1
			TransAE	Citrus	grain	shipping	125
			TransAE*	plant	Citrus	dessert	6

Figure 6: Case examples of MARS. We show the analogy example and analogy question-answer pair with their implicit relations. "Top-3 Entity" means top-3 ranking entities in the prediction. "Gold Rank" refers to the rank of the gold answer entity in the prediction. * denotes the baseline model with analogical components (MarT or ANALOGY).

ComplEx as backbone can handle the blended setting reluctantly but perform worse than the single setting. ANALOGY improves the performance of RSME in this situation. Meanwhile, MarT further explores the potential of MKGformer and improves its performance in various tasks. All in all, the analogical components consistently improve the multimodal analogical reasoning ability of all baseline methods, especially in blended analogical reasoning, which proves Mayer's theory (Mayer, 2002) that **analogical reasoning is more affinity for multimodal scenarios**.

Figure 5: Performance on MARS in different sub-task settings.

Case Analysis. As shown in Figure 6, we provide case analysis and observe that the top ranking entities (film, life, etc.) of the baselines without analogical components are usually irrelevant to the question entity "campaign". Analogical components make the predictions more reasonable and successfully predict the answer entity "battle". In the difficult blended analogical reasoning setting, the blended modal input of visual and text is challenging. We find that vanilla MKGformer and TransAE fail to understand the visual semantic of "apple" and incorrectly linked with "capital, phone, shipping" that related to "Apple Company". We also notice that TransAE with ANALOGY as backbone significantly decreases the prediction error but incorrectly predicts "plant" as the top-1 entity due to the inter-ference of "Panax notoginseng". On the contrary, MarT_MKGformer with relaxation loss can alienate the entities and focus on relation structures transfer and obtain reasonable predictions. These observations reveal that multimodal analogical reasoning is a highly challenging task, and analogy-aware components could enhance the analogical ability of models. Besides, we discuss **limitations** in Appendix A and provide a comprehensive error analysis in Appendix D.

6 DISCUSSION AND CONCLUSION

In this work, we introduce the new task of multimodal analogical reasoning over knowledge graphs with a new dataset and multimodal knowledge graph. Preliminary experiments show that this task brings a rather difficult challenge and is worth further exploration. Besides evaluating the analogical reasoning ability of models, there are some potential applications to explore: (1) knowledge graph completion with analogies, (2) transfer learning and zero-shot learning by analogy and (3) analogical question answering. We hope our work inspires future research on analogical reasoning and applications, especially in the multimodal world.

REPRODUCIBILITY STATEMENT

The source MARS and MarKG datasets are in the supplementary materials and will certainly be released. In order to provide support to reproduce our experiments in Section 5, we provide the detailed source code of all pipeline baselines (IKRL, TransAE, RSME) and end-to-end baselines (VisualBERT, ViLBERT, ViLT, FLAVA, MKGformer) in the supplementary materials with all scripts and hyper-parameters. We also provide a README script to instruct how to run the codes.

REFERENCES

Yoshua Bengio, Yann LeCun, and Geoffrey E. Hinton. Deep learning for AI. *Commun. ACM*, 64 (7):58–65, 2021. doi: 10.1145/3448250. URL https://doi.org/10.1145/3448250.

Antoine Bordes, Nicolas Usunier, Alberto García-Durán, Jason Weston, and Oksana Yakhnenko. Translating embeddings for modeling multi-relational data. In Christopher J. C. Burges, Léon Bottou, Zoubin Ghahramani, and Kilian Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 26: 27th Annual Conference on Neural Information Processing Systems 2013. Proceedings of a meeting held December 5-8, 2013, Lake Tahoe, Nevada, United States*, pp. 2787–2795, 2013. URL https://proceedings.neurips.cc/paper/2013/hash/1cecc7a77928ca8133fa24680a88d2f9-Abstract.html.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/1457c0d6bfcb4967418bfb8ac142f64a-Abstract.html.

Jiangjie Chen, Rui Xu, Ziquan Fu, Wei Shi, Zhongqiao Li, Xinbo Zhang, Changzhi Sun, Lei Li, Yanghua Xiao, and Hao Zhou. E-KAR: A benchmark for rationalizing natural language analogical reasoning. In Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (eds.), *Findings of the Association for Computational Linguistics: ACL 2022, Dublin, Ireland, May 22-27, 2022*, pp. 3941–3955. Association for Computational Linguistics, 2022a. doi: 10.18653/v1/2022.findings-acl.311. URL https://doi.org/10.18653/v1/2022.findings-acl.311.

Xiang Chen, Ningyu Zhang, Lei Li, Shumin Deng, Chuanqi Tan, Changliang Xu, Fei Huang, Luo Si, and Huajun Chen. Hybrid transformer with multi-level fusion for multimodal knowledge graph completion. In Enrique Amigó, Pablo Castells, Julio Gonzalo, Ben Carterette, J. Shane Culpepper, and Gabriella Kazai (eds.), *SIGIR '22: The 45th International ACM SIGIR Conference on Research and Development in Information Retrieval, Madrid, Spain, July 11 - 15, 2022*, pp. 904–915. ACM, 2022b. doi: 10.1145/3477495.3531992. URL https://doi.org/10.1145/3477495.3531992.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. In Jill Burstein, Christy Doran, and Thamar Solorio (eds.), *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)*, pp. 4171–4186. Association for Computational Linguistics, 2019. doi: 10.18653/v1/n19-1423. URL https://doi.org/10.18653/v1/n19-1423.

Kawin Ethayarajh, David Duvenaud, and Graeme Hirst. Towards understanding linear word analogies. In Anna Korhonen, David R. Traum, and Lluís Màrquez (eds.), *Proceedings of the 57th Conference of the Association for Computational Linguistics, ACL 2019, Florence, Italy, July 28- Au-*

gust 2, 2019, Volume 1: Long Papers, pp. 3253–3262. Association for Computational Linguistics, 2019a. doi: 10.18653/v1/p19-1315. URL https://doi.org/10.18653/v1/p19-1315.

Kawin Ethayarajh, David Duvenaud, and Graeme Hirst. Towards understanding linear word analogies. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 3253–3262, Florence, Italy, July 2019b. Association for Computational Linguistics. doi: 10.18653/v1/P19-1315. URL https://aclanthology.org/P19-1315.

Dedre Gentner. Structure-mapping: A theoretical framework for analogy. *Cogn. Sci.*, 7(2):155–170, 1983. doi: 10.1207/s15516709cog0702_3. URL https://doi.org/10.1207/s15516709cog0702_3.

Anna Gladkova, Aleksandr Drozd, and Satoshi Matsuoka. Analogy-based detection of morphological and semantic relations with word embeddings: what works and what doesn't. In *Proceedings of the Student Research Workshop, SRW@HLT-NAACL 2016, The 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, San Diego California, USA, June 12-17, 2016*, pp. 8–15. The Association for Computational Linguistics, 2016a. doi: 10.18653/v1/n16-2002. URL https://doi.org/10.18653/v1/n16-2002.

Anna Gladkova, Aleksandr Drozd, and Satoshi Matsuoka. Analogy-based detection of morphological and semantic relations with word embeddings: what works and what doesn't. In *Proceedings of the Student Research Workshop, SRW@HLT-NAACL 2016, The 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, San Diego California, USA, June 12-17, 2016*, pp. 8–15. The Association for Computational Linguistics, 2016b. doi: 10.18653/v1/n16-2002. URL https://doi.org/10.18653/v1/n16-2002.

Ashok K Goel. Design, analogy, and creativity. *IEEE expert*, 12(3):62–70, 1997.

Tyler L. Hayes and Christopher Kanan. Selective replay enhances learning in online continual analogical reasoning. In *IEEE Conference on Computer Vision and Pattern Recognition Workshops, CVPR Workshops 2021, virtual, June 19-25, 2021*, pp. 3502–3512. Computer Vision Foundation / IEEE, 2021. doi: 10.1109/CVPRW53098.2021.00389. URL https://openaccess.thecvf.com/content/CVPR2021W/CLVision/html/Hayes_Selective_Replay_Enhances_Learning_in_Online_Continual_Analogical_Reasoning_CVPRW_2021_paper.html.

Mary Hegarty and Marcel-Adam Just. Constructing mental models of machines from text and diagrams. *Journal of memory and language*, 32(6):717–742, 1993.

Felix Hill, Adam Santoro, David G. T. Barrett, Ari S. Morcos, and Timothy P. Lillicrap. Learning to make analogies by contrasting abstract relational structure. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019. URL https://openreview.net/forum?id=SylLYsCcFm.

Sheng Hu, Yuqing Ma, Xianglong Liu, Yanlu Wei, and Shihao Bai. Stratified rule-aware network for abstract visual reasoning. In *Thirty-Fifth AAAI Conference on Artificial Intelligence, AAAI 2021, Thirty-Third Conference on Innovative Applications of Artificial Intelligence, IAAI 2021, The Eleventh Symposium on Educational Advances in Artificial Intelligence, EAAI 2021, Virtual Event, February 2-9, 2021*, pp. 1567–1574. AAAI Press, 2021. URL https://ojs.aaai.org/index.php/AAAI/article/view/16248.

Justin Johnson, Bharath Hariharan, Laurens van der Maaten, Li Fei-Fei, C. Lawrence Zitnick, and Ross B. Girshick. CLEVR: A diagnostic dataset for compositional language and elementary visual reasoning. In *2017 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, Honolulu, HI, USA, July 21-26, 2017*, pp. 1988–1997. IEEE Computer Society, 2017. doi: 10.1109/CVPR.2017.215. URL https://doi.org/10.1109/CVPR.2017.215.

Philip N. Johnson-Laird. Models and heterogeneous reasoning. *J. Exp. Theor. Artif. Intell.*, 18(2): 121–148, 2006. doi: 10.1080/09528130600558091. URL https://doi.org/10.1080/09528130600558091.

David Jurgens, Saif M. Mohammad, Peter D. Turney, and Keith J. Holyoak. Semeval-2012 task 2: Measuring degrees of relational similarity. In Eneko Agirre, Johan Bos, and Mona T. Diab (eds.), *Proceedings of the 6th International Workshop on Semantic Evaluation, SemEval@NAACL-HLT 2012, Montréal, Canada, June 7-8, 2012*, pp. 356–364. The Association for Computer Linguistics, 2012. URL `https://aclanthology.org/S12-1047/`.

Wonjae Kim, Bokyung Son, and Ildoo Kim. Vilt: Vision-and-language transformer without convolution or region supervision. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 5583–5594. PMLR, 2021. URL `http://proceedings.mlr.press/v139/kim21k.html`.

Liunian Harold Li, Mark Yatskar, Da Yin, Cho-Jui Hsieh, and Kai-Wei Chang. Visualbert: A simple and performant baseline for vision and language. *CoRR*, abs/1908.03557, 2019. URL `http://arxiv.org/abs/1908.03557`.

Hanxiao Liu, Yuexin Wu, and Yiming Yang. Analogical inference for multi-relational embeddings. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, volume 70 of *Proceedings of Machine Learning Research*, pp. 2168–2178. PMLR, 2017. URL `http://proceedings.mlr.press/v70/liu17d.html`.

Ye Liu, Hui Li, Alberto García-Durán, Mathias Niepert, Daniel Oñoro-Rubio, and David S. Rosenblum. MMKG: multi-modal knowledge graphs. In Pascal Hitzler, Miriam Fernández, Krzysztof Janowicz, Amrapali Zaveri, Alasdair J. G. Gray, Vanessa López, Armin Haller, and Karl Hammar (eds.), *The Semantic Web - 16th International Conference, ESWC 2019, Portorož, Slovenia, June 2-6, 2019, Proceedings*, volume 11503 of *Lecture Notes in Computer Science*, pp. 459–474. Springer, 2019. doi: 10.1007/978-3-030-21348-0_30. URL `https://doi.org/10.1007/978-3-030-21348-0_30`.

Jiasen Lu, Dhruv Batra, Devi Parikh, and Stefan Lee. Vilbert: Pretraining task-agnostic visiolinguistic representations for vision-and-language tasks. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 13–23, 2019. URL `https://proceedings.neurips.cc/paper/2019/hash/c74d97b01eae257e44aa9d5bade97baf-Abstract.html`.

Mikolaj Malkinski and Jacek Mandziuk. Deep learning methods for abstract visual reasoning: A survey on raven's progressive matrices. *CoRR*, abs/2201.12382, 2022. URL `https://arxiv.org/abs/2201.12382`.

Richard E Mayer. Multimedia learning. In *Psychology of learning and motivation*, volume 41, pp. 85–139. Elsevier, 2002.

Tomás Mikolov, Ilya Sutskever, Kai Chen, Gregory S. Corrado, and Jeffrey Dean. Distributed representations of words and phrases and their compositionality. In Christopher J. C. Burges, Léon Bottou, Zoubin Ghahramani, and Kilian Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 26: 27th Annual Conference on Neural Information Processing Systems 2013. Proceedings of a meeting held December 5-8, 2013, Lake Tahoe, Nevada, United States*, pp. 3111–3119, 2013a. URL `https://proceedings.neurips.cc/paper/2013/hash/9aa42b31882ec039965f3c4923ce901b-Abstract.html`.

Tomas Mikolov, Wen-tau Yih, and Geoffrey Zweig. Linguistic regularities in continuous space word representations. In *Proceedings of the 2013 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 746–751, Atlanta, Georgia, June 2013b. Association for Computational Linguistics. URL `https://aclanthology.org/N13-1090`.

Gerhard Minnameier. Abduction, induction, and analogy. In *Model-based reasoning in science and technology*, pp. 107–119. Springer, 2010.

Xiaokang Peng, Yake Wei, Andong Deng, Dong Wang, and Di Hu. Balanced multimodal learning via on-the-fly gradient modulation. *CoRR*, abs/2203.15332, 2022. doi: 10.48550/arXiv.2203. 15332. URL https://doi.org/10.48550/arXiv.2203.15332.

Jeffrey Pennington, Richard Socher, and Christopher D. Manning. Glove: Global vectors for word representation. In Alessandro Moschitti, Bo Pang, and Walter Daelemans (eds.), *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing, EMNLP 2014, October 25-29, 2014, Doha, Qatar, A meeting of SIGDAT, a Special Interest Group of the ACL*, pp. 1532–1543. ACL, 2014. doi: 10.3115/v1/d14-1162. URL https://doi.org/10.3115/v1/d14-1162.

Henri Prade and Gilles Richard. Analogical proportions: Why they are useful in AI. In Zhi-Hua Zhou (ed.), *Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence, IJCAI 2021, Virtual Event / Montreal, Canada, 19-27 August 2021*, pp. 4568–4576. ijcai.org, 2021. doi: 10.24963/ijcai.2021/621. URL https://doi.org/10.24963/ijcai.2021/621.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 8748–8763. PMLR, 2021. URL http://proceedings.mlr.press/v139/radford21a.html.

Adam Santoro, Felix Hill, David G. T. Barrett, Ari S. Morcos, and Timothy P. Lillicrap. Measuring abstract reasoning in neural networks. In Jennifer G. Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pp. 4477–4486. PMLR, 2018. URL http://proceedings.mlr.press/v80/santoro18a.html.

Christoph Schuhmann, Richard Vencu, Romain Beaumont, Robert Kaczmarczyk, Clayton Mullis, Aarush Katta, Theo Coombes, Jenia Jitsev, and Aran Komatsuzaki. LAION-400M: open dataset of clip-filtered 400 million image-text pairs. *CoRR*, abs/2111.02114, 2021. URL https://arxiv.org/abs/2111.02114.

Amanpreet Singh, Ronghang Hu, Vedanuj Goswami, Guillaume Couairon, Wojciech Galuba, Marcus Rohrbach, and Douwe Kiela. FLAVA: A foundational language and vision alignment model. *CoRR*, abs/2112.04482, 2021. URL https://arxiv.org/abs/2112.04482.

Paul Thagard. Analogy, explanation, and education. *Journal of Research in science Teaching*, 29 (6):537–544, 1992.

Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. Complex embeddings for simple link prediction. In Maria-Florina Balcan and Kilian Q. Weinberger (eds.), *Proceedings of the 33nd International Conference on Machine Learning, ICML 2016, New York City, NY, USA, June 19-24, 2016*, volume 48 of *JMLR Workshop and Conference Proceedings*, pp. 2071–2080. JMLR.org, 2016. URL http://proceedings.mlr.press/v48/trouillon16.html.

Asahi Ushio, Luis Espinosa Anke, Steven Schockaert, and José Camacho-Collados. BERT is to NLP what alexnet is to CV: can pre-trained language models identify analogies? In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing, ACL/IJCNLP 2021, (Volume 1: Long Papers), Virtual Event, August 1-6, 2021*, pp. 3609–3624. Association for Computational Linguistics, 2021. doi: 10.18653/v1/2021. acl-long.280. URL https://doi.org/10.18653/v1/2021.acl-long.280.

Xenia Vamvakoussi. The use of analogies in mathematics instruction: Affordances and challenges. In *Cognitive foundations for improving mathematical learning*, pp. 247–268. Elsevier, 2019.

Meng Wang, Sen Wang, Han Yang, Zheng Zhang, Xi Chen, and Guilin Qi. Is visual context really helpful for knowledge graph? A representation learning perspective. In Heng Tao Shen, Yueting Zhuang, John R. Smith, Yang Yang, Pablo Cesar, Florian Metze, and Balakrishnan Prabhakaran (eds.), *MM '21: ACM Multimedia Conference, Virtual Event, China, October 20 - 24, 2021*, pp. 2735–2743. ACM, 2021. doi: 10.1145/3474085.3475470. URL `https://doi.org/10.1145/3474085.3475470`.

Weiyao Wang, Du Tran, and Matt Feiszli. What makes training multi-modal classification networks hard? In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, pp. 12692–12702. Computer Vision Foundation / IEEE, 2020. doi: 10.1109/CVPR42600.2020.01271. URL `https://openaccess.thecvf.com/content_CVPR_2020/html/Wang_What_Makes_Training_Multi-Modal_Classification_Networks_Hard_CVPR_2020_paper.html`.

Zikang Wang, Linjing Li, Qiudan Li, and Daniel Zeng. Multimodal data enhanced representation learning for knowledge graphs. In *International Joint Conference on Neural Networks, IJCNN 2019 Budapest, Hungary, July 14-19, 2019*, pp. 1–8. IEEE, 2019. doi: 10.1109/IJCNN.2019.8852079. URL `https://doi.org/10.1109/IJCNN.2019.8852079`.

Bo Wu, Haoyu Qin, Alireza Zareian, Carl Vondrick, and Shih-Fu Chang. Analogical reasoning for visually grounded language acquisition. *CoRR*, abs/2007.11668, 2020. URL `https://arxiv.org/abs/2007.11668`.

Ruobing Xie, Zhiyuan Liu, Huanbo Luan, and Maosong Sun. Image-embodied knowledge representation learning. In Carles Sierra (ed.), *Proceedings of the Twenty-Sixth International Joint Conference on Artificial Intelligence, IJCAI 2017, Melbourne, Australia, August 19-25, 2017*, pp. 3140–3146. ijcai.org, 2017. doi: 10.24963/ijcai.2017/438. URL `https://doi.org/10.24963/ijcai.2017/438`.

Chi Zhang, Feng Gao, Baoxiong Jia, Yixin Zhu, and Song-Chun Zhu. Raven: A dataset for relational and analogical visual reasoning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 5317–5327, 2019.

Xiangru Zhu, Zhixu Li, Xiaodan Wang, Xueyao Jiang, Penglei Sun, Xuwu Wang, Yanghua Xiao, and Nicholas Jing Yuan. Multi-modal knowledge graph construction and application: A survey. *CoRR*, abs/2202.05786, 2022. URL `https://arxiv.org/abs/2202.05786`.

A LIMITATIONS

The proposed work still has some limitations. We try to simulate the real-world multimodal analogy reasoning setting; however, it still can not predict analogical entities that are **not existing** in the multimodal knowledge graph. Such an issue is also known as inductive knowledge graph completion, and we leave this for future works. Besides, we have not evaluated the very large-scale pre-trained models on the MARS due to the GPU resources, and it is well worth investigating whether large-scale pre-trained models can emerge the multimodal analogy reasoning ability.

B ADDITIONAL DATASETS INFORMATION

B.1 DATASET CONSTRUCTION

Step 1: Collect Analogy Entities and Relations. Since E-KAR and BATs are widely used text analogy datasets with high-quality and semantically specific entities, we collect the analogy seed entities $\mathcal{E}_a$ and relations from them according to the following criteria: (1) the relation must imply analogical knowledge reasoning rather than simple word linear analogy, (2) the entity must be visualizable and realistic. After filtering, we obtained 2,063 seed entities and 27 relations.

Step 2: Link to Wikidata and Retrieve Neighbors. Consider that complex analogical reasoning is difficult through individual information (descriptions or images) of entities. We link the seed entities

to Wikidata by Mediawiki API [5] and retrieve the one-hop neighbors of seed entities as well as the possible relationships between the seed entities to obtain their neighbor structure information.

Step 3: Acquire and Validate Images. We collect images from two sources: Google Engine and Laion-5B query service[6]. We search from Google Engine with the descriptions of entities and crawl 5 images per entity. Laion-5B service depends on Clip retrieval and query by *k*nn index; we leverage the clip text embedding of the description and also query 5 images for each entity. Then we apply four filters to the above images: (1) we check the format of the images and filter invalid files, (2) we remove corrupted, low-quality and duplicate images, (3) we use CLIP (Radford et al., 2021) to remove the images with outlier visual embeddings, (4) we delete unreasonable images manually.

Step 4: Sample Analogical Reasoning Data. From Step 1 to Step 3, we obtain the MarKG, which includes 2,063 analogy entities, 8,881 neighbor entities, 27 analogy relations and 165 other relations. To construct the MARS dataset, we sample analogy example (e_h, r, e_t) and analogy question-answer pair (e_q, r, e_a) with the same relation r from 2,063 analogy entities, but we do not explicitly provide the relation in the input. Then we split the data into different task settings evenly. More details about the sample strategy of MARS can be seen in Section B.2.

B.2 SAMPLE STRATEGY OF MARS

In Section B.1, we obtain the analogy seed entities $\mathcal{E}_a$ and the analogy relations between $\mathcal{E}_a$. Then we sample analogy example (e_h, e_t) and analogy question-answer pair (e_q, e_a) from $\mathcal{E}_a$. Guided by SMT, we make sure that (e_h, e_t) and (e_q, e_a) have the same relation r. Specifically, we divide the entity pairs that share the same relation into two categories to avoid overlap issues. Then we randomly sample the analogy examples from one category and the analogy question-answer pairs from another to construct analogy input instances. Last, we split the instances into different task settings evenly.

B.3 DATASET DETAILS

	# entity	# relation	# triple	# image	source
WN9-IMG	6,555	9	14,319	65,550	WordNet
FB15k-IMG	11,757	1,231	350,293	107,570	Freebase
MarKG	11,292	192	34,420	76,424	Wikidata

Table 5: Data statistics of MarKG. # refers to the number of.

Figure 7: Relation distribution of MARS.

The statistical comparison of MarKG with two multimodal knowledge graph datasets WN9-IMG (Xie et al., 2017) and FB15k-IMG (Liu et al., 2019) as shown in Table 5, we report the number of entity, relation, triple, image and the data source. Note that WN9-IMG and FB15k-IMG aim for knowledge completion and triple classification tasks while our MarKG aims to support MARS to do

---

[5] https://www.wikidata.org/w/api.php
[6] https://knn5.laion.ai/

multimodal analogical reasoning. We also show the complete relations of our MARS in Table 6 and the distribution of relation categories in Figure 7.

Relations	Definition	Example
part of	Object of which the subject is a part.	mouse : computer
corresponds to	Terms generally correspond to each other.	entrepreneur : laborer
juxtaposition to	Two terms belong to the same hypernym or have the same properties or functions.	child : minor
synonym	Sense of another lexeme with the same meaning as this sense.	tired : exhausted
made from material	Material the subject or the object is made of or derived from.	building : cement
antonym	Sense of a lexeme with the opposite meaning to this sense.	warm : cool
has cause	Underlying cause, thing that ultimately resulted in this effect.	cleaning : tidy
opposite of	Item that is the opposite of this item.	black : white
follow	The terms have a chronological or other sequential relationship, but one term does not cause the other.	implement : evaluate
intersection to	The extension of the two terms intersects.	odd : integer
takes place in	A term takes place in the other.	doctor : hospital
prerequisite	Prior event or achievement that a person or team needs to complete before joining or obtaining the item topic.	aim : shoot
subject-object	The originator and receiver of an action.	school : education
contradictory to	Two term are contradictory to each other.	english : chinese
identical to	The meanings of two terms are identical.	highway : road
head-modifier	The preceding term modifies the other.	affluence : living
different from	Item that is different from another item, with which it may be confused.	apple : nuts
probabilistic attribute	One term is probably the attribute of the other.	liquid : fluidity
instance of	That class of which this subject is a particular example and member.	coffee : drink
has use	Main use of the subject.	ballot : election
location	Location of the object, structure or event.	student : classroom
verb-object	The action and the object on which the action acts.	drilling : petroleum
has quality	The entity has an inherent or distinguishing non-material characteristic.	knife : sharp
tool of	One term is the tool of the other.	piano : play
subject-predicate	The originator of the action and the action itself.	stone : throwing
target of	One term is the target of the other.	harvest : sow
metaphor	A term is the metaphor of the other, reflecting something abstract indirectly.	pigeon : peace

Table 6: The complete relations with definitions, examples of MARS. Some relations and definitions refer to (Chen et al., 2022a) and Wikidata Properties.

Quality Control of Datasets We devise some quality control strategies while construct our MarKG and MARS datasets: (1) Entity and relation formalization and normalization. We link the analogy entities collected from E-KAR and SAT to Wikidata and filter non-link items. Since Wikidata is a knowledge base with quality-assured, some rare or worthless entities are excluded. (2) Image validation mechanism. We devise complex image filter strategies to control the robustness of image data, as mentioned in Section B.1. (3) Control of text description. We take the description in Wikidata as the textual information of entities.

B.4   DETAILED EVALUATION METRICS

The evaluation method of (Chen et al., 2022a) can not reflect one-to-more entities and does not fully explore the internal knowledge in the models due to the limited search space. Thus, we follow the link prediction task and choose Hits@k and MRR as our evaluation metrics. Both metrics are in the range $[0, 1]$. The bigger, the better performance. The Hits at k metric (Hits@k) is acquired by counting the number of times the golden entity appears at the first k positions in the predictions.

Given the prediction score of each entity in the candidate entity set, we sort the score and obtain the ranking of each entity. Denote the rank of the gold entity of i triple as $rank_i$, and the reciprocal rank is $1/rank_i$. The Mean Reciprocal Rank (MRR) is the average of the reciprocal ranks across all triples in the knowledge graph:

$$\text{MRR} = \frac{1}{|\mathcal{S}|} \sum_{i}^{|\mathcal{S}|} \frac{1}{rank_i} \tag{8}$$

where $|\mathcal{S}|$ is the total number of the training set.

C   ADDITIONAL OF EXPERIMENTS

C.1   IMPLEMENTATION DETAILS

Hyper-parameters	MKGE Baselines	MPT Baselines
epoch	{300, 1000}	15
sequence length	-	128
learning rate	{1e-2, 5e-3}	{3e-5, 4e-5, 5e-5}
batch size	1000	64
optimizer	{Adagrad, SGD}	AdamW
adam epsilon	-	1e-8
λ	-	{0.38, 0.43, 0.45}

Table 7: Hyper-parameter settings. We use the same parameter settings of MKGE baseline methods as the original paper except for the learning rate.

This section detail the training procedures and hyper-parameters for various models. For multimodal knowledge representation methods, we first use MarKG to do knowledge representation learning and obtain the entity and relation matrix embeddings. Then we apply abduction and induction processes to continue training the models on the MARS dataset. Note that these processes are serial and share models. For multimodal pre-trained Transformer models, we also use MarKG to pre-train the models and then fine-tune on MARS end-to-end with our analogy prompt tuning strategy. We utilize Pytorch to conduct all experiments with 1 Nvidia 3090 GPU. The details of hyper-parameters can be seen in Table 7.

C.2   RESULTS OF PRE-TRAINING ON MARKG.

Method	Baselines	Entity Prediction				Relation Prediction			
		Hits@1	Hits@3	Hits@10	MRR	Hits@1	Hits@3	Hits@10	MRR
MKGE	IKRL	0.157	0.257	0.338	0.272	-	-	-	-
	TransAE	0.307	0.361	0.442	0.353	-	-	-	-
	RSME	0.417	0.460	0.520	0.452	-	-	-	-
MPT	MarT_VisualBERT	0.466	0.598	0.692	0.546	0.758	0.873	0.927	0.822
	MarT_ViLT	0.466	0.586	0.675	0.539	0.737	0.847	0.902	0.799
	MarT_ViLBERT	0.489	0.621	0.711	0.569	0.764	0.876	**0.930**	0.827
	MarT_FLAVA	0.506	0.634	0.716	0.582	**0.771**	**0.877**	0.921	**0.829**
	MarT_MKGformer	**0.527**	**0.670**	**0.779**	**0.616**	0.762	0.870	0.923	0.823

Table 8: Pre-training results on MarKG. Note that these results are from the training process as we do not divide MarKG. Since we follow the link prediction task to pre-train the models for MKGE baselines, we only report the entity prediction results.

Figure 8: The results of pre-training on MarKG and fine-tuning on MARS. * refers to the baseline model applied MarT.

We report the pre-train results on MarKG in Table 8. We find that MPT baselines perform better than MKGE baselines consistently. It reveals the strong fit ability of Transformer-based models. As

Figure 9: Error case examples.

shown in Figure 8, we can observe that pre-training and fine-tuning stages trends are roughly the same, especially in the same type of baselines, which indicates that pre-train on MarKG benefits analogical reasoning on MARS.

D   ERROR CASE ANALYSIS

In this section, we conduct an error case study on MARS in Figure 9. From the error cases, we can see the hardship of the multimodal analogical reasoning task: 1) **Imbalance of multimodal.** The semantic scales of images and text are inconsistent, which leads to incorrect matching (Zhu et al., 2022). Although we filter some hard-to-visualize entities in data collection in Section B.1, the high semantic entities exist. As shown in example (a), "management" and "control" are abstract entities that are difficult to find equivalent images. Moreover, the uncoordinated convergence problem in multimodal learning further exacerbates the difficulty of the multimodal analogical reasoning task (Peng et al., 2022; Wang et al., 2020). 2) **One-to-more problem.** It is challenging for the models to solve one-to-more entities. In example (b), "Memba" is an instance of both "snake" and "animal", which is confusing to MKGformer. 3) **Unintuitive relations.** In our MARS dataset, some relations are not intuitive, requiring models to have strong relation reasoning ability. As shown in example (c), the relation "intersection to" means the extension of the head and tail entity intersects. All four models are struggling and far away from the golden answer entity.