Beyond Regrets:
Geometric Metrics for Bayesian Optimization

Abstract

Bayesian optimization is a principled optimization strategy for a black-box objective function. It shows its effectiveness in a wide variety of real-world applications such as scientific discovery and experimental design. In general, the performance of Bayesian optimization is assessed by regret-based metrics such as instantaneous, simple, and cumulative regrets. These metrics only rely on function evaluations, so that they do not consider geometric relationships between query points and global solutions, or query points themselves. Notably, they cannot discriminate if multiple global solutions are successfully found. Moreover, they do not evaluate Bayesian optimization's abilities to exploit and explore a search space given. To tackle these issues, we propose four new geometric metrics, i.e., precision, recall, average degree, and average distance. These metrics allow us to compare Bayesian optimization algorithms considering the geometry of both query points and global optima, or query points. However, they are accompanied by an extra parameter, which needs to be carefully determined. We therefore devise the parameter-free forms of the respective metrics by integrating out the additional parameter. Finally, we empirically validate that our proposed metrics can provide more convincing interpretation and understanding of Bayesian optimization algorithms from distinct perspectives, compared to the conventional metrics.

1 Introduction

Bayesian optimization (Garnett, 2023) is a principled optimization strategy with a probabilistic regression model for a black-box objective function. It demonstrates its effectiveness and validity in a wide variety of real-world applications such as scientific discovery (Griffiths & Hernández-Lobato, 2020; Kim et al., 2022; 2024) and experimental design (Attia et al., 2020; Shields et al., 2021; Ament et al., 2023). These applications sometimes require not only finding a global optimum in terms of function evaluations but also diversifying the candidates of global solutions on a search space given.

On the other hand, to measure the performance of Bayesian optimization, we generally utilize instantaneous, simple, and cumulative regrets; each definition can be found in Section 2. These performance metrics all focus on measuring how the function value of some query point is close to the function value of a global solution (or potentially global solutions). However, they only assess a solution quality in terms of function evaluations, so that they do not consider relationships between query points and global solutions, or query points themselves. In particular, if the finding of multiple global optima is crucial, these regret-based metrics often fail in discriminating global solution candidates that can diversify the candidates. In addition, it is difficult to evaluate the exploitation and exploration abilities of Bayesian optimization.

To tackle the issues on the drawbacks of regret-based metrics for Bayesian optimization, we propose new geometric metrics beyond the conventional metrics for Bayesian optimization. In particular, four categories of our new metrics, i.e., *precision*, *recall*, *average degree*, and *average distance*, are designed to evaluate how many query points are close to multiple global solutions, and vice versa, or how query points are distributed. However, these metrics are accompanied by an additional parameter. For example, precision, recall, and average degree are needed to determine the size of ball query, and average distance requires the selection of the number of nearest neighbors we are interested in. To alleviate the need to choose the additional

Table 1: Comparisons between metrics for Bayesian optimization supposing that the corresponding metric is computed at iteration t where s is the number of global optima. GO Info., Multiple GO, and Additional Parameter indicate a requirement of global optimum information, consideration to multiple global optima, and need for an additional parameter, respectively. $\mathbf{x}$ and $\mathbf{x}^*$ represent a query point and a global optimum, respectively, and PF stands for parameter-free.

Metric	Inputs	GO Info.	Multiple GO	Additional Parameter
Instantaneous regret	$f(\mathbf{x}_t), f(\mathbf{x}^*)$	✓		
Simple regret	$f(\mathbf{x}_1), f(\mathbf{x}_2), \ldots, f(\mathbf{x}_t), f(\mathbf{x}^*)$	✓		
Cumulative regret	$f(\mathbf{x}_1), f(\mathbf{x}_2), \ldots, f(\mathbf{x}_t), f(\mathbf{x}^*)$	✓		
Precision	$\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t, \mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*$	✓	✓	✓
Recall	$\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t, \mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*$	✓	✓	✓
Average degree	$\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t$			✓
Average distance	$\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t$			✓
PF precision	$\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t, \mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*$	✓	✓	
PF recall	$\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t, \mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*$	✓	✓	
PF average degree	$\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t$			
PF average distance	$\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t$			

parameter, the parameter-free forms of the respective metrics are also proposed. The additional parameter is integrated out by sampling it from a particular distribution. The characteristics of diverse metrics are compared in Table 1.

To explain a procedure of Bayesian optimization briefly, we cover Bayesian optimization first.

Bayesian Optimization. We are supposed to solve the following minimization problem:

$$\mathbf{x}^+ = \arg\min_{\mathbf{x} \in \mathcal{X}} f(\mathbf{x}), \tag{1}$$

where $\mathcal{X} \subset \mathbb{R}^d$ is a d-dimensional search space and f is a black-box function. We deal with f using a history of query points and their evaluations in Bayesian optimization, so that we rely on a probabilistic regression model to estimate the unknown function. In particular, we can choose one of generic probabilistic regression models such as Gaussian processes (Rasmussen & Williams, 2006), Student-t processes (Shah et al., 2014; Martinez-Cantin et al., 2018), deep neural networks (Snoek et al., 2015), Bayesian neural networks (Springenberg et al., 2016; Li et al., 2023), and tree-based regression models (Hutter et al., 2011; Kim & Choi, 2022). These regression models are capable of producing function value estimates over query points in a search space and their uncertainty estimates, which are able to be used to balance exploitation and exploration. By employing the regression models, an acquisition function to sample the next solution candidate is defined. Probability of improvement (Kushner, 1964), expected improvement (Jones et al., 1998), and Gaussian process upper confidence bound (Srinivas et al., 2010) are often used as an acquisition function. Bayesian optimization eventually determines the next query point by maximizing the acquisition function. We can sequentially find a better solution repeating these steps in determining and evaluating the query point. By the sample-efficient nature of Bayesian optimization, it is beneficial for optimizing a black-box function that is costly to evaluate.

Before describing the details of metrics for Bayesian optimization, we summarize the contributions of this work as follows:

(i) We identify the drawbacks of the conventional regret-based metrics, i.e., instantaneous, simple, and cumulative regrets, for Bayesian optimization;

(ii) We propose four geometric metrics, i.e., precision, recall, average degree, and average distance, and their parameter-free forms;

(iii) We show that our new metrics enable us to interpret and understand the performance of Bayesian optimization from distinct perspectives.

We will release our implementation upon publication.

2 Instantaneous, Simple, and Cumulative Regrets

In Bayesian optimization, instantaneous, simple, and cumulative regrets are often used to report its performance (Garnett, 2023). Given a global optimum $\mathbf{x}^*$ and a query point $\mathbf{x}_t$ at iteration t, an instantaneous regret is defined as the following:

$$r_t^{\text{ins}} = f(\mathbf{x}_t) - f(\mathbf{x}^*). \tag{2}$$

It is noteworthy that this metric does not need to take into account multiple global optima because function evaluations are only involved in the metric. The instantaneous regret (2) represents the quality of every immediate decision. Due to the property of a trade-off between exploitation and exploration in Bayesian optimization, a series of instantaneous regrets in a single round tends to oscillate. Such oscillation comes from exploration-focused and exploitation-focused decisions; rigorously speaking, it is hard to identify whether a particular function evaluation is led by exploration-focused or exploitation-focused decision, but a dominant factor, i.e., either exploration or exploitation, may exist when a query point is selected. Moreover, while the oscillation of instantaneous regrets does not imply that exploration-focused evaluations always differ from exploitation-focused ones, exploration-focused decisions are likely to obtain unexpected function evaluations that are far from the best evaluation until the current iteration. For these reasons, it is unlikely to consider the instantaneous regret as a solid performance metric to show the performance of Bayesian optimization. As a straightforward alternative to the instantaneous regret, a simple regret is defined as the following:

$$r_t^{\text{sim}} = \min_{i=1}^{t} f(\mathbf{x}_i) - f(\mathbf{x}^*), \tag{3}$$

where $\mathbf{x}_1, \ldots, \mathbf{x}_t$ are t query points. The simple regret (3) is equivalent to the minimum of instantaneous regrets until t iterations, which can represent the best solution out of t solution candidates $\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t$. Unlike the instantaneous regret, the simple regret is monotonically decreasing by the definition of (3). The common goal of Bayesian optimization is to seek a solution that makes (3) zero, which implies that the best solution found by Bayesian optimization coincides with a global solution; if there exist multiple global solutions, we cannot verify that all global solutions are sought by Bayesian optimization. Furthermore, using (2), we can readily define a cumulative regret until iteration t:

$$R_t = \sum_{i=1}^{t} r_i^{\text{ins}}, \tag{4}$$

which is also used as the metric of Bayesian optimization. Since $r_i^{\text{ins}} \geq 0$, the cumulative regret is always monotonically increasing.

Although instantaneous, simple, and cumulative regrets are representative metrics for showing the performance of Bayesian optimization, it is challenging to consider geometric relationships between query points and global solutions, or query points themselves, verify whether multiple global optima are successfully discovered or not, and measure the degrees of exploration and exploitation. To mitigate the aforementioned challenges and provide the better understanding of Bayesian optimization outcomes, we propose new geometric metrics for Bayesian optimization in Section 3.

3 Geometric Metrics for Bayesian Optimization

In this section we introduce new geometric metrics for Bayesian optimization beyond instantaneous, simple, and cumulative regrets.

Suppose that we are given t query points $\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t$ and s global solutions $\mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*$. An indicator function $\mathbb{I}(z)$ returns 1 if z is true and 0 otherwise.

Figure 1: Examples of precision (upper panels) and recall (lower panels) for the Branin function where three global optima (red x) and ten query points (green +) are given. Selected points (blue dot) are marked if they are located in the vicinity (yellow circle) of query points.

Figure 2: Examples of precision (upper panels) and recall (lower panels) for the Branin function where three global optima (red x) and twenty query points (green +) are given. Selected points (blue dot) are marked if they are located in the vicinity (yellow circle) of query points.

Table 2: Quantitative results on the examples shown in Figures 1 and 2. IR, SR, CR indicate instantaneous, simple, and cumulative regrets, respectively.

Example	IR	SR	CR	Precision			Recall			Average Degree			Average Distance		
				$\delta = 2$	$\delta = 4$	$\delta = 6$	$\delta = 2$	$\delta = 4$	$\delta = 6$	$\delta = 2$	$\delta = 4$	$\delta = 6$	$k = 2$	$k = 4$	$k = 6$
Figure 1	15.892	15.892	657.097	0.100	0.400	0.700	0.333	0.667	1.000	0.400	1.600	3.000	3.646	5.163	6.818
Figure 2	166.061	3.963	1278.801	0.200	0.350	0.750	0.667	0.667	1.000	1.000	4.700	8.200	2.114	2.790	3.347

3.1 Precision

We first define precision over $\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t$ and $\mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*$:

$$\text{precision}_\delta(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}, \{\mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*\}) = \frac{\sum_{i=1}^{t} \vee_{j=1}^{s} \mathbb{I}(\|\mathbf{x}_i - \mathbf{x}_j^*\|_2^2 \le \delta^2)}{t}, \quad (5)$$

where δ is the size of ball query. The goal of this metric is to count the number of query points in the vicinity of global optima. If a metric value is close to one, most query points are located in the close region of global optima.

3.2 Recall

Recall over $\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t$ and $\mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*$ is given by the following:

$$\text{recall}_\delta(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}, \{\mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*\}) = \frac{\sum_{i=1}^{s} \vee_{j=1}^{t} \mathbb{I}(\|\mathbf{x}_i^* - \mathbf{x}_j\|_2^2 \le \delta^2)}{s}, \quad (6)$$

where δ is the size of ball query. Its goal is to count the number of global optima in the vicinity of query points. If a metric value is one, all global optima are located in close proximity to some query points.

3.3 Average Degree

Average degree over $\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t$ computes the average of degrees over all query points:

$$\text{average-degree}_\delta(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}) = \frac{\sum_{i=1}^{t} \sum_{j=1}^{t} \mathbb{I}(\|\mathbf{x}_i - \mathbf{x}_j\|_2^2 \le \delta^2) - 1}{t}, \quad (7)$$

where δ is the size of ball query. The goal of this metric is to show how many points are mutually close and eventually express an exploitation degree.

3.4 Average Distance

Average distance over $\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t$ is defined as the following:

$$\text{average-distance}_k(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}) = \frac{\sum_{i=1}^{t} \sum_{j=1}^{t} \|\mathbf{x}_i - \mathbf{x}_j\|_2 \mathbb{I}(\mathbf{x}_j \in \text{NN}_k(\mathbf{x}_i))}{kt}, \quad (8)$$

where $\text{NN}_k(\mathbf{x}_i)$ is a k-nearest neighbor function to obtain k nearest neighbors based on the Euclidean distance. It is to calculate how query points are distributed.

As presented in Figures 1 and 2 and Table 2, we show two examples of four geometric metrics as well as three conventional metrics for Bayesian optimization. The Branin function, which is employed in these examples, has three global optimum (red ✕), and its search space is $[[-5, 10], [0, 15]]$. By using a fixed number of random points (green +), i.e., 10 for Figure 1 and 20 for Figure 2, metric values are reported in Table 2. As expected, our proposed geometric metrics are capable of considering geometric relationships between query points and global optima, while instantaneous, simple, and cumulative regrets only take into account the function evaluations of query points. However, as shown in the results with $\delta = 2, 4, 6$ or $k = 2, 4, 6$, the metric values are sensitive to δ or k. To resolve such an issue, we introduce the parameter-free forms of our metrics in Section 3.5.

Figure 3: Bayesian optimization results versus iterations for the Branin function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

3.5 Parameter-Free Forms of New Metrics

To propose new metrics without additional parameters, which are hard to determine, we define the parameter-free forms of four metrics, i.e., precision, recall, average degree, and average distance. In general, we integrate out δ or k by sampling it from a particular distribution. Firstly, we describe parameter-free precision and parameter-free recall:

$$\text{precision}(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}, \{\mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*\}) = \mathbb{E}_\delta \left[\text{precision}_\delta(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}, \{\mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*\}) \right]$$
$$= \frac{1}{M} \sum_{i=1}^{M} \text{precision}_{\delta_i}(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}, \{\mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*\}), \quad (9)$$

$$\text{recall}(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}, \{\mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*\}) = \mathbb{E}_\delta \left[\text{recall}_\delta(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}, \{\mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*\}) \right]$$
$$= \frac{1}{M} \sum_{i=1}^{M} \text{recall}_{\delta_i}(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}, \{\mathbf{x}_1^*, \mathbf{x}_2^*, \ldots, \mathbf{x}_s^*\}), \quad (10)$$

Figure 4: Bayesian optimization results versus iterations for the Zakharov 4D function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

where every δ is sampled from the exponential distribution with a rate parameter $1/d$: $\delta \sim \text{Exponential}(1/d)$ and M is the number of samples. Similarly, parameter-free average degree is also defined:

$$\text{average-degree}(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}) = \mathbb{E}_\delta\left[\text{average-degree}_\delta(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\})\right]$$

$$= \frac{1}{M}\sum_{i=1}^{M}\text{average-degree}_{\delta_i}(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}), \quad (11)$$

where $\delta_1, \delta_2, \ldots, \delta_M \sim \text{Exponential}(1/d)$. Moreover, parameter-free average distance is defined:

$$\text{average-distance}(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}) = \mathbb{E}_\delta\left[\text{average-distance}_k(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\})\right]$$

$$= \frac{1}{M}\sum_{i=1}^{M}\text{average-distance}_{k_i}(\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_t\}), \quad (12)$$

where every k is sampled from the geometric distribution with a success rate 0.5: $k_i \sim \text{Geometric}(0.5)$ for $i \in [M]$, and M is the number of samples.

Figure 5: Bayesian optimization results versus iterations for the Zakharov 16D function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

4 Numerical Analysis

To exhibit the characteristics of our proposed metrics, we conduct numerical analysis on our metrics in diverse popular benchmark functions. This analysis is designed to compare our geometric metrics to the conventional metrics such as instantaneous, simple, and cumulative regrets. In particular, we will visualize metric values over iterations for different metrics, and then show the Spearman's rank correlation coefficients between metrics, based on the results of the metric values over iterations. For the geometric metrics defined with δ, $\delta = \text{max-dist}(\mathcal{X})/10$ where $\text{max-dist}(\mathcal{X})$ is the maximum distance of a search space $\mathcal{X}$. If $\mathcal{X} = [[0, 10], [-5, 10], [-10, 10]]$, $\text{max-dist}(\mathcal{X}) = \sqrt{725}$. In addition, we use $k = \min(\max(t/5, 1), 5)$ for the average distance. For our parameter-free metrics, $M = 1000$. Moreover, we evaluate 500 points for each algorithm where 5 initial points sampled from the uniform distribution are given, and repeat each algorithm 50 times for all experiments.

Baseline Methods. Surrogate models of all methods are implemented with Gaussian processes with Matérn 5/2 kernels (Rasmussen & Williams, 2006) and we use either expected improvement (Jones et al., 1998) or Gaussian process upper confidence bound (Srinivas et al., 2010) for the acquisition function of each baseline method. To find kernel parameters of the Gaussian process regression model, marginal likelihood is

(a) Branin   (b) Zakharov 4D   (c) Zakharov 16D

Figure 6: Spearman's rank correlation coefficients between metrics for different benchmark functions such as the Branin, Zakharov 4D, and Zakharov 16D functions. Red regions indicate the coefficients with NaN values. More results are depicted in Figures 24 and 25.

(a) BO, EI   (b) BBO Random, EI   (c) BBO Constant, EI

(d) BBO Prediction, EI   (e) BBO PE, EI   (f) BBO LP, EI

Figure 7: Spearman's rank correlation coefficients between metrics for different Bayesian optimization algorithms with the expected improvement.

maximized using BFGS (Nocedal & Wright, 2006). Moreover, L-BFGS-B (Byrd et al., 1995) is employed in optimizing an acquisition function with 128 initial points. We utilize the following baseline strategies:

(i) Random search: This is a random algorithm to select points from the uniform distribution;

(ii) Bayesian optimization: It is a vanilla Bayesian optimization algorithm, which is denoted as BO;

(iii) Batch Bayesian optimization with random search: This approach, which is denoted as BBO Random, selects a single point using the vanilla Bayesian optimization and the other points using random search;

Figure 8: Spearman's rank correlation coefficients between metrics for different Bayesian optimization algorithms with the Gaussian process upper confidence bound.

(iv) Batch Bayesian optimization with a constant (Ginsbourger et al., 2010): It sequentially selects each point in a batch where a fake evaluation with a particular constant is provided every acquisition. The fixed constant is set as 100 and this method is denoted as BBO Constant;

(v) Batch Bayesian optimization with predicted function values (Ginsbourger et al., 2010): This strategy is similar to BBO Constant, but the evaluations of select points are set as the posterior means of Gaussian process regression. It is denoted as BBO Prediction;

(vi) Batch Bayesian optimization with pure exploration (Contal et al., 2013): This method, which is denoted as BBO PE, sequentially chooses points to evaluate using Bayesian optimization with pure exploration, while the first query point is selected by the vanilla Bayesian optimization. Since the posterior variances of Gaussian process regression do not depend on function evaluations, the acquisition strategy of pure exploration can be run without evaluating query points;

(vii) Batch Bayesian optimization with local penalization (González et al., 2016): This algorithm, which is denoted as BBO LP, sequentially determines a batch of query points by penalizing an acquisition function with a local penalization function.

We do not necessitate confining Bayesian optimization methods to batch Bayesian optimization. However, in order to show difference between metrics by utilizing the inherent nature of batch Bayesian optimization methods on the diversification of query points, we adopt them as baseline methods.

4.1 Analysis on Metric Values over Iterations

We report the arithmetic means of metric values and their standard errors of the sample mean, as illustrated in Figures 3, 4, and 5 and Figures 10 to 23, which are included in the appendices. Empirical analysis with a total of 11 metrics is demonstrated by optimizing several benchmark functions through Bayesian

optimization. We find that the metric values of instantaneous regret, simple regret, average distance, and parameter-free average distance generally decrease as Bayesian optimization iterates. On the other hand, the metric values of the other metrics such as cumulative regret, precision, recall, average degree, parameter-free precision, parameter-free recall, and parameter-free average degree tend to increase, as iterations proceed. These results are expected because of the goals of the respective metrics.

As shown in Figure 3, although the metric values of the simple regret become closer to zero and the values of the cumulative regret also converge to specific values for some algorithms, the values of the parameter-free recall do not reach to one. It implies that the algorithms used in this analysis fail to find multiple global solutions. Such results are not demonstrated by the use of the conventional regret-based metrics. Also, the metric values of the average degree, average distance, and parameter-free forms of the average degree and average distance for BBO Random and BBO PE are closer to their values for random search, compared to the results of the simple and cumulative regrets. We presume that the components of random search and pure exploration in the respective algorithms make those values more similar to the values for random search. This observation supports our motivation on the development of geometric metrics for measuring the degrees of exploration and exploitation.

Interestingly, the precision, recall, and average degree struggle to measure the performance of Bayesian optimization algorithms in higher-dimensional problems; see the 16-dimensional case shown in Figure 5. To ensure that these metrics work appropriately, we need to carefully select δ in their definitions. However, this parameter selection task is almost infeasible due to the problem formulation that a black-box function is optimized. In contrast to these metrics involved with an additional parameter, our parameter-free metrics successfully compare distinct optimization algorithms as presented in Figure 5.

One drawback of our parameter-free metrics excluding the parameter-free average distance is that their values are prone to oscillating. Since the calculation of the parameter-free metrics include a step for sampling M parameters, this consequence occurs. To reduce the stochasticity of our metrics, a larger M should be used. However, the use of a larger M makes the calculation slower. Therefore, we need to take into account such a trade-off in the process of selecting M.

4.2 Analysis on the Spearman's Rank Correlation Coefficients between Metrics

We investigate the Spearman's rank correlation coefficients between diverse metrics, in order to reveal relationships between metrics. Given the means of metric values over 50 rounds, the Spearman's rank correlation coefficients are calculated:

$$r_s = \frac{\mathrm{cov}(\mathrm{rank}(X), \mathrm{rank}(Y))}{\sigma_{\mathrm{rank}(X)}\sigma_{\mathrm{rank}(Y)}}, \qquad (13)$$

where $\mathrm{rank}(X)$ is a function to produce the rank of a given variable X, $\mathrm{cov}(X_1, X_2)$ indicates the covariance of two input variables X_1, X_2, and σ_X corresponds to the standard deviation of a given variable X.

We conduct two empirical analyses using the Spearman's rank correlation coefficients: the coefficients between metrics for each benchmark function and for each optimization algorithm. As shown in Figure 6 and Figures 24 and 25 of the appendices, the simple regret is highly correlated with the average distance and parameter-free average dis-

Figure 9: Spearman's rank correlation coefficients between metrics for the random search method.

tance in general. Moreover, the precision, recall, average degree, parameter-free precision, parameter-free recall, and parameter-free average degree are positively correlated with each other. On the contrary, the average distance and parameter-free average distance are negatively correlated with the precision, recall, average degree, parameter-free precision, parameter-free recall, and parameter-free average degree. In addition, the coefficients with NaN values appear in higher-dimensional cases, since metric values are all identical; see the results of the precision and recall in 16-dimensional examples. These results can be thought of as the evidence of the need to propose parameter-free metrics.

As presented in Figures 7, 8, and 9, the patterns similar to the results for different benchmark functions are observed. The precision, recall, average degree, and their parameter-free forms are positively correlated with each other, while they are negatively correlated with the average distance and its parameter-free form. In this analysis, the relationships between instantaneous, simple, and cumulative regrets are clearly affirmed. Specifically, the instantaneous and cumulative regrets are highly correlated with each other, and they are loosely correlated with the simple regret.

5 Conclusion

We have proposed new geometric metrics that can be used to measure the performance of Bayesian optimization. By utilizing information on the geometry of acquired points and potentially global solutions, the precision, recall, average degree, and average distance are defined. Moreover, to mitigate the need to use an additional parameter for the geometric metrics, we also suggested their parameter-free forms. In the end, we provided numerical analysis on metric values over optimization iterations and the Spearman's rank correlation coefficients between various metrics, by testing several Bayesian optimization algorithms as well as random search on a variety of benchmark functions.

Broader Impact Statement

This work does not have a direct broader impact in that it suggests new metrics for Bayesian optimization. However, from the perspective of the development of optimization algorithms, our work can be used to identify solutions of harmful and unethical optimization tasks. In response to such an issue, we should be aware of how Bayesian optimization algorithms can be applied in unethical tasks when we devise optimization strategies using our geometric metrics.

References

S. Ament, A. Witte, N. Garg, and J. Kusuma. Sustainable concrete via Bayesian optimization. *arXiv preprint arXiv:2310.18288*, 2023.

P. M. Attia, A. Grover, N. Jin, K. A. Severson, T. M. Markov, Y.-H. Liao, M. H. Chen, B. Cheong, N. Perkins, Z. Yang, P. K. Herring, M. Aykol, S. J. Harris, R. D. Braatz, S. Ermon, and W. C. Chueh. Closed-loop optimization of fast-charging protocols for batteries with machine learning. *Nature*, 578(7795):397–402, 2020.

R. H. Byrd, P. Lu, J. Nocedal, and C. Zhu. A limited memory algorithm for bound constrained optimization. *SIAM Journal on Scientific Computing*, 16(5):1190–1208, 1995.

E. Contal, D. Buffoni, A. Robicquet, and N. Vayatis. Parallel Gaussian process optimization with upper confidence bound and pure exploration. In *Proceedings of the European Conference on Machine Learning and Principles and Practice of Knowledge Discovery in Databases (ECML-PKDD)*, pp. 225–240, Prague, Czech Republic, 2013.

R. Garnett. *Bayesian Optimization*. Cambridge University Press, 2023.

D. Ginsbourger, R. Le Riche, and L. Carraro. Kriging is well-suited to parallelize optimization. In *Computational intelligence in expensive optimization problems*, pp. 131–162. Springer, 2010.

J. González, Z. Dai, P. Hennig, and N. Lawrence. Batch Bayesian optimization via local penalization. In *Proceedings of the International Conference on Artificial Intelligence and Statistics (AISTATS)*, pp. 648–657, Cadiz, Spain, 2016.

R.-R. Griffiths and J. M. Hernández-Lobato. Constrained Bayesian optimization for automatic chemical design using variational autoencoders. *Chemical science*, 11(2):577–586, 2020.

F. Hutter, H. H. Hoos, and K. Leyton-Brown. Sequential model-based optimization for general algorithm configuration. In *Proceedings of the International Conference on Learning and Intelligent Optimization (LION)*, pp. 507–523, Rome, Italy, 2011.

D. R. Jones, M. Schonlau, and W. J. Welch. Efficient global optimization of expensive black-box functions. *Journal of Global Optimization*, 13:455–492, 1998.

J. Kim and S. Choi. On uncertainty estimation by tree-based surrogate models in sequential model-based optimization. In *Proceedings of the International Conference on Artificial Intelligence and Statistics (AISTATS)*, pp. 4359–4375, Virtual, 2022.

J. Kim, M. Li, Y. Li, A. Gómez, O. Hinder, and P. W. Leu. Multi-BOWS: Multi-fidelity multi-objective Bayesian optimization with warm starts for nanophotonic structure design. *Digital Discovery*, 2024.

S. Kim, P. Y. Lu, C. Loh, J. Smith, J. Snoek, and M. Soljacic. Deep learning for Bayesian optimization of scientific problems with high-dimensional structure. *Transactions on Machine Learning Research*, 2022.

H. J. Kushner. A new method of locating the maximum point of an arbitrary multipeak curve in the presence of noise. *Journal of Basic Engineering*, 86(1):97–106, 1964.

Y. L. Li, T. G. J. Rudner, and A. G. Wilson. A study of Bayesian neural network surrogates for Bayesian optimization. *arXiv preprint arXiv:2305.20028*, 2023.

R. Martinez-Cantin, K. Tee, and M. McCourt. Practical Bayesian optimization in the presence of outliers. In *Proceedings of the International Conference on Artificial Intelligence and Statistics (AISTATS)*, pp. 1722–1731, Lanzarote, Canary Islands, Spain, 2018.

J. Nocedal and S. J. Wright. *Numerical Optimization*. Springer, 2006.

C. E. Rasmussen and C. K. I. Williams. *Gaussian Processes for Machine Learning*. MIT Press, 2006.

A. Shah, A. G. Wilson, and Z. Ghahramani. Student-*t* processes as alternatives to Gaussian processes. In *Proceedings of the International Conference on Artificial Intelligence and Statistics (AISTATS)*, pp. 877–885, Reykjavik, Iceland, 2014.

B. J. Shields, J. Stevens, J. Li, M. Parasram, F. Damani, J. I. M. Alvarado, J. M. Janey, R. P. Adams, and A. G. Doyle. Bayesian reaction optimization as a tool for chemical synthesis. *Nature*, 590(7844):89–96, 2021.

J. Snoek, O. Rippel, K. Swersky, R. Kiros, N. Satish, N. Sundaram, M. A. Patwary, Prabhat, and R. P. Adams. Scalable Bayesian optimization using deep neural networks. In *Proceedings of the International Conference on Machine Learning (ICML)*, pp. 2171–2180, Lille, France, 2015.

J. T. Springenberg, A. Klein, S. Falkner, and F. Hutter. Bayesian optimization with robust Bayesian neural networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 29, pp. 4134–4142, Barcelona, Spain, 2016.

N. Srinivas, A. Krause, S. Kakade, and M. Seeger. Gaussian process optimization in the bandit setting: No regret and experimental design. In *Proceedings of the International Conference on Machine Learning (ICML)*, pp. 1015–1022, Haifa, Israel, 2010.

A Additional Analysis on Metric Values over Iterations

(a) Instantaneous regret   (b) Simple regret   (c) Cumulative regret

(d) Precision   (e) Recall   (f) Average degree   (g) Average distance

(h) PF precision   (i) PF recall   (j) PF average degree   (k) PF average distance

Figure 10: Bayesian optimization results versus iterations for the Ackley 4D function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

In addition to the results reported in the main article, we present more analysis on metric values over iterations in Figures 10 to 23. The experimental settings of these results are the same as the corresponding settings described in the main article.

(a) Instantaneous regret   (b) Simple regret   (c) Cumulative regret

(d) Precision   (e) Recall   (f) Average degree   (g) Average distance

(h) PF precision   (i) PF recall   (j) PF average degree   (k) PF average distance

Figure 11: Bayesian optimization results versus iterations for the Ackley 16D function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

Figure 12: Bayesian optimization results versus iterations for the Beale function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

Figure 13: Bayesian optimization results versus iterations for the Bohachevsky function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

Figure 14: Bayesian optimization results versus iterations for the Bukin 6 function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

Figure 15: Bayesian optimization results versus iterations for the Colville function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

(a) Instantaneous regret   (b) Simple regret   (c) Cumulative regret

(d) Precision   (e) Recall   (f) Average degree   (g) Average distance

(h) PF precision   (i) PF recall   (j) PF average degree   (k) PF average distance

Figure 16: Bayesian optimization results versus iterations for the De Jong 5 function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

Figure 17: Bayesian optimization results versus iterations for the Eggholder function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

Figure 18: Bayesian optimization results versus iterations for the Hartmann 3D function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

Figure 19: Bayesian optimization results versus iterations for the Hartmann 6D function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

Figure 20: Bayesian optimization results versus iterations for the Levy 4D function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

(a) Instantaneous regret   (b) Simple regret   (c) Cumulative regret

(d) Precision   (e) Recall   (f) Average degree   (g) Average distance

(h) PF precision   (i) PF recall   (j) PF average degree   (k) PF average distance

Figure 21: Bayesian optimization results versus iterations for the Levy 16D function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

Figure 22: Bayesian optimization results versus iterations for the Six-Hump Camel function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

Figure 23: Bayesian optimization results versus iterations for the Three-Hump Camel function. Sample means over 50 rounds and the standard errors of the sample mean over 50 rounds are depicted. PF stands for parameter-free.

B   Additional Analysis on the Spearman's Rank Correlation Coefficients between Metrics

Figure 24: Spearman's rank correlation coefficients between metrics for different benchmark functions such as the Ackley 4D, Ackley 16D, Beale, Bohachevsky, Bukin 6, Colville, De Jong 5, Eggholder, and Hatmann 3D functions. Red regions indicate the coefficients with NaN values.

We visualize the Spearman's rank correlation coefficients between metrics for diverse benchmark functions in Figures 24 and 25. These results are obtained by using the same settings detailed in the main article.

Figure 25: Spearman's rank correlation coefficients between metrics for different benchmark functions such as the Hartmann 6D, Levy 4D, Levy 16D, Six-Hump Camel, and Three-Hump Camel functions. Red regions indicate the coefficients with NaN values.