Efficient Exploration in Multi-Agent Reinforcement Learning via Farsighted Self-Direction

Abstract

Multi-agent reinforcement learning faces greater challenges with efficient exploration compared to single-agent counterparts, primarily due to the exponential growth in state and action spaces. Methods based on intrinsic rewards have been proven to enhance exploration efficiency in multi-agent scenarios effectively. However, these methods are plagued by instability during training and biases in exploration direction. To address these challenges, we propose Farsighted Self-Direction (FSD), a novel model-free method that utilizes a long-term exploration bonus to achieve coordinated exploration. Since prediction error against individual Q-values indicates a potential bonus for committed exploration, it is taken into account in action selection to directly guide the coordinated exploration. Further, we also use clipped double Q-learning to reduce noise in prediction error. We validate the method on didactic examples and demonstrate the outperformance of our method on challenging StarCraft II micromanagement tasks.

1 Introduction

Currently, multi-agent reinforcement learning (MARL) has been applied in multiple fields, such as autonomous driving (Wu et al., 2019) and traffic control (Zhang et al., 2019). In the field of games, where ample training data is more readily available, it has demonstrated its powerful potential, reaching human top-level performance in StarCraft II (Vinyals et al., 2019), Quake III Arena (Jaderberg et al., 2019), and Dota 2 (Berner et al., 2019). To facilitate the practical implementation of MARL, centralized training with decentralized execution (CTDE) has been widely adopted as a MARL paradigm. It leverages global information during training, alleviating the non-stationarity problem (Gronauer & Diepold, 2022) while agents only rely on local observation history during execution, enabling distributed deployment. Under the CTDE framework, value decomposition methods have been continuously explored and refined(Sunehag et al., 2018; Rashid et al., 2018; Wang et al., 2021b; Xu et al., 2023), demonstrating excellent performance in numerous tasks.

Despite the current success, it has been found that with the simple ϵ-greedy exploration strategy, these methods are sample-inefficient to solve complex tasks, especially those that require coordinated and persistent exploration (Wang et al., 2021b; Zheng et al., 2021). In the single-agent domain, there have been plenty of extensive studies, including uncertainty-oriented methods (Janz et al., 2019; Lee et al., 2021) and intrinsic motivation-oriented methods (Mohamed & Rezende, 2015; Pathak et al., 2017; Fox et al., 2018; Burda et al., 2019; Badia et al., 2020). Unfortunately, these methods cannot be directly applied to multi-agent systems due to the exponential growth of state and action spaces, partial observability, and the requirement for coordinated exploration (Zheng et al., 2021; Jiang et al., 2024).

To address the limitation, the intrinsic reward is designed as the prediction error of the individual Q-value(Zheng et al., 2021; Zhang & Yu, 2023) for value decomposition methods, promoting efficient coordinated exploration. To avoid excessive coupling between intrinsic reward generation and policy learning, these curiosity-driven methods typically employ an exploiter-explorer structure where the exploiter learns the policy used to interact with the environment, and the explorer is only for intrinsic reward generation along with another predictor. Despite the impressive performance in the experiments, they still have two main draw-

backs: (1) *instability during training.* The intrinsic reward varies as the training processes; thereby, agents face non-stationary environmental dynamics during training, which increase the risk of training instability. (2) *biases in exploration direction.* The explorer learns solely using extrinsic rewards, while the exploiter uses extrinsic and intrinsic rewards. Within such a framework, the strategies of the exploiter and the explorer inevitably differ, and using the intrinsic rewards generated by the explorer to guide the exploiter can lead to biased, even wrong, exploration direction. Just as when we seek advice from others, their suggestions often do not suit us best due to differences in values or other stuff.

Thereby, we propose a novel multi-agent exploration framework named Farsighted Self-Direction (FSD). The first distinction from previous curiosity-driven methods is that we forgo the explorer. The framework contains only two network components: the controller Q (similar to the exploiter in previous curiosity-driven methods) and the predictor Q. We use the prediction error against the controller's individual Q-values by the predictor Q to measure the potential exploration bonus. By eliminating the intermediary explorer, FSD avoids the exploration direction bias resulting from the strategy discrepancy. Furthermore, we only use extrinsic rewards to update the parameter of the controller, circumventing the instability caused by time-varying intrinsic rewards. The usage of prediction error leads to our second distinction: we do not treat prediction error as an immediate intrinsic reward. Instead, we consider it as a long-term potential exploration gain, referred to as Q_i^{int}. Q_i^{int} is added with controller Q-values, together dominating action selection. Intuitively, as training progresses, both the controller Q and the predictor Q will gradually converge, causing the prediction error to become small enough (mainly dependent on the fluctuation of the controller Q). Thus, it can be reasonably assumed that the prediction error represents the current estimation of the upper bound of the benefits that can be obtained through exploration in subsequent training.

FSD uses the prediction error to directly bias the action selection, which requires our prediction error to accurately reflect the novelty of the state-action pair and the strength of the agents' interdependence in the current state. Similar to the approach used in the Twin Delayed Deep Deterministic Policy Gradient (TD3) (Fujimoto et al., 2018), we introduce clipped double Q-learning to mitigate the overestimation problem of the controller Q, thereby reducing the noise in Q_i^{int} caused by original Q function approximation error.

We validate our method on didactic examples used in EMC (Zheng et al., 2021). By illustrating the distribution of agents' positions at different times during training, we demonstrate that our method can effectively guide agents to explore states with greater potential value. Subsequently, we evaluated FSD on Predator Prey (Rashid et al., 2020) and several challenging StarCraft II micromanagement tasks (Samvelyan et al., 2019). Empirical results show that FSD achieves state-of-the-art performance compared to several widely adopted baseline methods. Notably, unlike previous curiosity-driven methods, FSD does not use an explorer, thereby saving a considerable amount of computational resources. Additionally, we demonstrate the effectiveness of Q_i^{int} and clipped double Q-learning separately through ablation studies.

Contributions. (1) We introduce FSD, a novel approach that utilizes the prediction error against the controller Q as the long-term exploration bonus to achieve farsighted exploration and forgoes the explorer Q to conserve computational resources and achieve self-directed exploration. (2) We provide an intuitive analysis of the prediction error and demonstrate the soundness of FSD along with clipped double Q-learning. (3) We show that FSD can be seamlessly combined with value decomposition approaches to enhance their performance, conducting experiments on Simultaneous Arrival, Predator Prey, and several challenging tasks in the StarCraft II micromanagement benchmark.

2 Background

Decentralized Partially Observable Markov Decision Process. In practice, the full state of the environment is often unavailable to agents, and agents can only have observations of the environment. In such cases, a cooperative multi-agent task can be modeled as a Decentralized Partially Observable Markov Decision Process (Dec-POMDP) (Oliehoek & Amato, 2016). Dec-POMDP can be described by a tuple $G = <\mathcal{I}, \mathcal{S}, \mathcal{A}, P, \Omega, O, R, n, \gamma>$ where $\mathcal{I}$ represents the set of n agents, $\mathcal{S}$ is the global state space and $\mathcal{A}$ is the action space. At each time step, agent $i \in I$ observes $o_i \in \Omega$ determined by observation function $O(s, i)$ and its action-observation history will be updated as $\tau_i \in \tau \equiv (\Omega \times \mathcal{A})^* \times \Omega$. Then agent i selects an action a_i according to its policy π_i, which aims to maximize the long-term team reward jointly. After the joint

action $\boldsymbol{a} \equiv [a_i]_{i=1}^n \in \boldsymbol{\mathcal{A}} \equiv \mathcal{A}^n$ has been conducted, all agents receive the feedback from the environment, which includes a shared reward $r = R(s, \boldsymbol{a})$ and new agent-specific observation $o_i' = O(s', i)$. s' is the new state determined by transition probability function $P(s'|s, \boldsymbol{a})$. The objective of agents is to find the joint policy $\boldsymbol{\pi}$ that maximize the expectation of discounted cumulative team reward $\mathbb{E}[\sum_{t=0}^{\infty} \gamma^t r_t | s = s_0, \boldsymbol{\pi}]$, or simply denoted as the joint value function $V^{\boldsymbol{\pi}}(s)$, where $\gamma \in [0, 1]$ is the discount factor.

Centralized Training with Decentralized Execution (CTDE). In this paradigm, global information is utilized during training, guiding agents in learning superior strategies while circumventing the non-stationarity problem inherent in independent learning, thus allowing for the convenient use of replay buffer to enhance sample efficiency. During execution, agents' policies rely solely on local action-observation history. Except for decentralized actor, centralized critic approaches based on actor-critic framework (Lowe et al., 2017; Yu et al., 2022), value decomposition approaches (Sunehag et al., 2018; Rashid et al., 2018; Son et al., 2019; Wang et al., 2021b) are the mainstream methods for the CTDE paradigm, where the global Q value is decomposed into a combination of local Q-values:

$$Q_{tot}(\boldsymbol{\tau}, \boldsymbol{a}) = f(Q_1(\tau_1, a_1), ..., Q_n(\tau_n, a_n)). \tag{1}$$

Q_{tot} is trained to minimize the expected TD error:

$$\mathcal{L}(\boldsymbol{\theta}) = \mathbb{E}_{\boldsymbol{\tau}, \boldsymbol{a}, r, \boldsymbol{\tau}' \in D} \left[r + \gamma \max_{\boldsymbol{a}'} Q_{tot}^{\boldsymbol{\theta}^-}(\boldsymbol{\tau}', \cdot) - Q_{tot}^{\boldsymbol{\theta}}(\boldsymbol{\tau}, \boldsymbol{a}) \right]^2, \tag{2}$$

where D represents the replay buffer and $\boldsymbol{\theta}^-$ is the parameter for the target network. $\boldsymbol{\theta}^-$ is regularly updated by $\boldsymbol{\theta}$, serving as a latent and stable follower of $\boldsymbol{\theta}$. After training, the execution policy is derived from Q_i.

VDN (Sunehag et al., 2018) is the earliest method based on value decomposition, which simply factorizes Q_{tot} into the sum of individual Q-values. QMIX (Rashid et al., 2018) highlights that, for value decomposition approaches, it is essential to ensure the following consistency between Q_{tot} and individual Q_i:

$$\arg\max_{\boldsymbol{a}} Q_{tot}(\boldsymbol{\tau}, \boldsymbol{a}) = \begin{Bmatrix} \arg\max_{a_1} Q_1(\tau_1, a_1) \\ ... \\ \arg\max_{a_n} Q_n(\tau_t, a_n) \end{Bmatrix}, \tag{3}$$

which is later denoted as IGM principle (Son et al., 2019). Consequently, QMIX introduces a hypernetwork f as eq. 1 and ensures that $\frac{\partial f}{\partial Q_i} \geq 0, \forall i \in \mathcal{I}$. Subsequently, more algorithms (Son et al., 2019; Wang et al., 2021b; Xu et al., 2023) have been proposed to improve performance, and QMIX, as a classic method, usually provides stable and satisfactory performance.

3 Related Work

Single-agent exploration. In the single-agent domain, how to achieve effective exploration has been extensively studied. Recent literature (Aubret et al., 2019; Hao et al., 2024) has already provided a comprehensive summary of the topic, especially on intrinsic motivation-oriented methods, also known as curiosity-driven methods (Zheng et al., 2021). Intuitively, the novelty of certain states can be measured by the visit times to those states, and intrinsic rewards can be calculated accordingly. To extend these methods to large state space, various methods with pseudo-count have been introduced (Bellemare et al., 2016; Fox et al., 2018) where DORA (Fox et al., 2018) suggests leveraging the pseudo-count as the long-term exploratory value. RND (Burda et al., 2019), on the other hand, assesses state novelty through the prediction error of the next state embedding, which is obtained from a randomly initialized, fixed network and predicted by another network with the same structure but learnable. Moreover, VIMIM (Mohamed & Rezende, 2015) encourages agents to explore states with higher empowerment, calculated using the mutual information between action sequences and states. VIME (Houthooft et al., 2016) also utilizes information theory, encouraging agents to maximize information gain about the environment dynamics with each step, thus satisfying the agent's curiosity about the environment. ICM (Pathak et al., 2017) uses an inverse model for better state embedding, allowing the forward model to be less affected by the "noisy TV" problem (Burda et al., 2019) when predicting the next state. Recently, NGU (Badia et al., 2020) leverages both episode and inter-episode intrinsic rewards, achieving better performance in long-sequence problems.

Multi-agent exploration. Unlike exploration in the single-agent setting, efficient coordinated exploration is crucial in multi-agent environment. Jaques et al. (2019) proposes calculating intrinsic rewards for agents' chosen action by assessing its influence on other agents' action selection. Subsequently, EITI and EDTI (Wang et al., 2020) incorporate agents' interaction values as regularization terms in policy optimization, where EITI encourages exploration of states that influence other agents' transition dynamics while EDTI focuses on states that affect other agents' decision-making. IIE (Liu et al., 2024) leverages transformer models to identify interaction states and guides agents to start exploration from these high-influence states. MACE (Jiang et al., 2024) is a method under the distributed learning setting with limited communication, facilitating coordinated exploration by sharing local novelty and hindsight influence estimation.

On the other hand, MAVEN (Mahajan et al., 2019) introduces a latent variable to learn hierarchical policies, enabling committed exploration through diverse exploration strategies. CDS(Li et al., 2021) encourages agents to exhibit diverse exploratory behaviors by incorporating mutual information between agents as a regularization term. EMAX (Schäfer et al., 2024) explicitly uses ensemble value functions to estimate the variance among Q-values and follows the UCB(Auer et al., 2002) exploration policy.

EMC (Zheng et al., 2021) is the first to use the prediction error of individual Q-values as intrinsic rewards. Since value decomposition methods achieve implicit credit assignment Wang et al. (2021a), the prediction error of the individual Q-value function is also influenced by other agents; thereby, agents are encouraged to visit states where careful coordination is required. Building on this, EXPODE (Zhang & Yu, 2023) uses twin QMIX and intricately designs the intrinsic reward as the prediction error against the higher Q-value. However, the exploiter-explorer structure used in both EMC and EXPODE inevitably leads to deviation in the exploiter's exploration direction.

4 Method

This section introduces FSD, a novel model-free method for efficient multi-agent exploration. FSD takes prediction error against individual controller Q-values as Q_i^{int}, which is combined with controller Q-values to determine action selection during sample collection. First, we describe the method in detail; then, we analyze the sources of prediction error to verify the significance of Q_i^{int} and why clipped double Q-learning can help reduce noise in prediction error.

Figure 1: An overview of FSD's framework

4.1 Farsighted Self-Direction

The prediction error against individual Q-values contains not only information about local exploration but also global exploration status due to implicit credit assignment (Zheng et al., 2021; Wang et al., 2021a). Thus, we use the prediction error against individual Q-values as the signal to guide agents in coordinated exploration. As shown in Fig. 1, FSD contains two network components, namely the controller and the predictor, where the controller represents the strategy of agent interaction with the environment, and the predictor is trained to approximate the controller. The prediction error between the predictor and the controller serves as the signal for directing coordinated exploration.

Additionally, FSD considers the prediction error as potential long-term exploration gain Q_i^{int} in a farsighted manner rather than immediate reward gained from exploration. Over the long term, the controller and the predictor gradually converge after sufficient exploration, and the prediction error will eventually become a value small enough. Thus, to some extent, the prediction error represents the long-term exploration bonus that can be obtained from exploration starting from the current state-action pair. In the action selection phase, FSD calculates $Q_i^{int}(\tau_i, \cdot)$, which, along with the controller $Q_i^\phi(\tau_i, \cdot)$, guides the action selection process:

$$Q_i^{act}(\tau_i, \cdot) = Q_i^\phi(\tau_i, \cdot) + \alpha Q_i^{int}(\tau_i, \cdot), \tag{4}$$

where α is used to control the magnitude of exploration. Subsequently, ϵ-greedy strategy based on Q_i^{act} determines the final selected action.

Let the predictor be denoted by Q^ψ, Q_i^{int} is calculated as the distance between the controller and the predictor:

$$Q_i^{int}(\tau, \cdot) = \left| Q_i^\phi(\tau_i, \cdot) - Q_i^\psi(\tau_i, \cdot) \right|, \tag{5}$$

As analyzed in section 4.2, larger $Q_i^{int}(\tau_i, a_i)$ with specific a_i indicates more insufficient visits to the state-action pair or stronger interdependence among agents existing in the next state after a_i is taken, which makes the action more worth taking and the next state more worth exploring. With Q_i^{int} biasing agents into coordinated exploration, more valuable experience is collected, and agents are likely to achieve a better policy.

QMIX (Rashid et al., 2018), a classic method performing well across a multitude of tasks, is selected as the backbone. It's worth noting that our method can be embedded into any value decomposition method. As shown in eq. 5, we directly use the pointwise prediction error, which requires that our prediction error accurately reflects the information for coordinated exploration. The inherent over-estimation problem in Q-learning can lead to fluctuations in the controller Q-values, which constitutes a significant source of noise in the prediction error. To reduce noise, FSD introduces clipped double Q-learning similar to TD3 (Fujimoto et al., 2018), mitigating the over-estimation problem by taking the smaller target Q to format the TD target.

Specifically, the controller includes two networks with the same structure but different initializations, Q^{ϕ_1} and Q^{ϕ_2}, where Q^{ϕ_1} learns the policy to interact with the environment (referred to as Q^ϕ in eq. 4 and eq. 5) while Q^{ϕ_2} is only used during training. Correspondingly, two target networks, $Q^{\phi_1'}$ and $Q^{\phi_2'}$ are used to stabilize training, and the smaller target Q-value is used to calculate the one-step TD target:

$$\boldsymbol{a_k'} = \arg\max_{\boldsymbol{a}} Q_{tot}^{\phi_k}(\boldsymbol{\tau'}, \cdot), \qquad k = 1, 2 \tag{6}$$

$$\mathcal{L}_{controller}(\phi_k) = \left[r + \gamma \min_{k'=1,2} Q_{tot}^{\phi_{k'}'}(\boldsymbol{\tau'}, \boldsymbol{a_{k'}'}) - Q_{tot}^{\phi_k}(\boldsymbol{\tau}, \boldsymbol{a}) \right]^2, \qquad k = 1, 2 \tag{7}$$

$$\phi_k' \leftarrow (1 - \xi)\phi_k' + \xi\phi_k, \qquad k = 1, 2 \tag{8}$$

The predictor has the same network structure with the local Q_i^ϕ and is trained concurrently with the controller to approach it:

$$\mathcal{L}_{predictor}(\psi) = \frac{1}{n} \sum_{i=1}^n \left\| Q_i^\psi(\tau_i', \cdot) - \min_{k'=1,2} Q_i^{\phi_{k'}'}(\tau_i', \cdot) \right\|_2. \tag{9}$$

4.2 Reduce Noise in Prediction Error

The prediction error of the individual controller Q-values stems from two main sources:

1. *Moving target.* As the optimization target for the predictor, the individual controller Q-values are continually changing along with the advancement of the training, which makes the target difficult to approach.

2. *Error in approaching a fixed target.* Even if the individual controller Q-values were fixed, there would still be an approximation error between the predictor and the fixed target.

Since both the predictor and controller share the same local Q_i network structure, the error in approaching a fixed target primarily depends on how frequently a particular state-action pair (or its neighboring spaces) is visited, which indicates the novelty of the state-action pair.

The fluctuations in the individual controller Q-values can be further broken down into three major components:

1. *Infrequent visits to a particular state-action pair.* Few visits to some state-action pair make the estimation of its value unstable.

2. *Strong interdependence among agents in some states.* If strong interdependence lies among agents in some states, the estimation of individual Q-values will be highly susceptible to the actions chosen by other agents during their exploration.

3. *Overestimation in Q-learning.* It has been known that Q-value is easily overestimated in training, and such positive bias becomes more pronounced as error accumulate (Liang et al., 2022).

Figure 2: Strong interdependence lies between agents in the state.

To better illustrate the second component, let's consider the scenario shown in Fig. 2: two agents in red are required to arrive at the blue target simultaneously, and any individual arrival would be punished. If Agent 1 moves up, the reward may be positive if Agent 2 moves right, or negative otherwise. On the other hand, if Agent 1 takes other actions, the reward may be negative if Agent 2 moves right, or zero otherwise. Compared to the other actions, the move-up action of Agent 1 in the current state is more influenced by the other agent. And the fluctuation of the controller $Q_1(\tau_1, a_{up})$ is likely larger, which leads to a higher $Q_1^{int}(\tau_1, a_{up})$, guiding the agent to actively try to reach the target. Besides, Q_i^{int} also guides the agents toward similar states with strong agent interdependence.

EXPODE (Zhang & Yu, 2023) also uses twin QMIX, however, EXPODE primarily aims to leverage the min-max operator to construct better intrinsic rewards where the max operator is employed in generating intrinsic rewards. In contrast, our approach solely focuses on reducing noise in prediction error, and we simply use the prediction error between the predictor Q and the smaller target controller Q-value, which is consistent with the update of controller Q in TD target formation.

5 Results

In this section, we conduct a set of empirical experiments and demonstrate the performance of FSD in Simultaneous Arrival (Zheng et al., 2021), Predator Prey (Rashid et al., 2020), and StarCraft II micromanagement (Samvelyan et al., 2019). QMIX is the default backbone if not specified. Experiments are conducted on eight NVIDIA RTX 4090s, with training time ranging from half an hour to 10 hours, depending on the complexity of the task and the number of agents involved. Baselines are trained using their open-source codes, with some results derived from the open-source results of EXPODE (Zhang & Yu, 2023). During training, we consistently set $\alpha = 0.1$ for all the results presented. As for evaluation, action is selected greedily based on the controller Q_i^ϕ. All experiments have been repeated for five runs over different random seeds. In the ablation study section, we separately showcase the effectiveness of Q_i^{int} and clipped double Q-learning.

Figure 3: The performance on Simultaneous Arrival

Figure 4: The visitation frequency heat map on Simultaneous Arrival during the training of FSD-VDN

5.1 Simultaneous Arrival

Simultaneous Arrival is introduced by Zheng et al. (2021) as a didactic example. In this task, two agents are separated from the middle, and they can only observe each other when they are near their corresponding targets. A positive reward is given only if both agents arrive at their corresponding targets simultaneously, while a negative reward $-p$ is given if only one agent reaches its target. Otherwise, agents receive no reward. In our experiments, we set p to a relatively high value of 3. The success of the task requires a high level of coordinated exploration from the agents, and its grid-world environment also facilitates visualization.

It has been validated that EMC-VDN performs better than its counterparts in this task, so our comparison is conducted among methods using VDN as the backbone. The tested methods include FSD-VDN, FSD-sgl-VDN denoting no clipped double q-learning is used, FSD-woin-VDN denoting no Q_i^{int} is used, EXPODE-VDN, EMC-VDN, and VDN.

As illustrated in Fig. 3, both FSD-VDN and EMC-VDN achieve success in this task. However, EXPODE-VDN and FSD-sgl-VDN frequently fail in this task despite occasional successes. Similar to VDN, FSD-woin-VDN consistently fails to complete the task. These results affirm the necessity of Q_i^{int} for FSD in the Simultaneous Arrival task. Notably, the standard setting of the scenario lacks randomness, meaning that during evaluation, the win rate is either 0 or 1 for a fixed policy, and the curves essentially represent the proportion of wins across five different runs.

Besides, as shown in Fig. 4, we have plotted the heat map of the frequency of visitation to various locations by agents at different times during the training of FSD-VDN. In the very early stages of training, the agents broadly explore their surrounding environment, while in this case, each agent primarily moves around the starting point, upper left and lower right corners of the map, respectively. Directed by Q_i^{int}, agents gradually move closer to the center of the map, where the targets are located. By the 150k time steps, the agents are almost always successful in completing the task, reaching the targets on row 5 simultaneously. The heat

map shows that the agent on the right side visits the area near its target more frequently than the agent on the left, indicating that it has learned a strategy to wait for the other agent before reaching the target.

5.2 Predator Prey

Predator Prey is a challenging, partially observable multi-agent game where predators must cooperate to capture prey and receive rewards, with penalties imposed for individual captures. This scenario features a larger number of agents (eight) and includes mobile prey, making it more challenging than the simultaneous arrival task. We conducted comparisons of the FSD against several baseline algorithms, including EXPODE, EMC, QPLEX(Wang et al., 2021b), WQMIX(Rashid et al., 2020), QMIX, and VDN.

Figure 5: The performance on Predator Prey

As shown in Fig. 5, FSD-VDN and FSD-sgl-VDN both achieve comparable performance to state-of-the-art methods, including EMC and EXPODE. Similar to EXPODE-QMIX, FSD-QMIX fails in the task and tends toward a local optimum where predators do not capture prey at all. Among other baseline methods, WQMIX is noted for its ability to focus on learning the value of $Q(s, a^*)$ where $a^* = \arg\max_a Q(s, a)$, thus also finds the optimal policy. VDN also succeeds in the task, albeit much less efficiently. Other methods like QMIX and QPLEX, which are based on the IGM assumption, fail in the task due to their non-monotonic reward structure.

5.3 SMAC Benchmark

Figure 6: Results on SMAC benchmark

StarCraft II Micromanagement (SMAC) is a commonly used benchmark in the field of multi-agent reinforcement learning (Wang et al., 2021b; Zheng et al., 2021; Zhang & Yu, 2023). In SMAC, agents trained by the evaluated methods have only partial observation of the environment, while their opponents are driven by the built-in AI. We tested FSD on two super hard maps: 6h_vs_8z and MMM2, and one hard map: 5m_vs_6m. Baseline algorithms include EXPODE, EMC, CDS, QMIX, QPLEX, VDN and WQMIX. As illustrated in Fig. 6, FSD has achieved state-of-the-art performance.

Figure 7: Ablation studies performed on SMAC

CDS fosters better exploration by encouraging diversity among agents. EMC, with the compact expressive capabilities of QPLEX, utilizes intrinsic rewards and episodic memory to direct coordinated exploration and make the best use of experience, demonstrating strong performance in the SMAC benchmark. EXPODE further improves performance through the design of intrinsic rewards and enhanced learning of the predictor network.

In 6h_vs_8z, FSD exhibits the fastest learning rate, and in 5m_vs_6m, it achieves the highest win rate, while in MMM2, FSD achieves performance indistinguishable that of EXPODE. FSD leverages the prediction error against the controller Q to directly formalize Q_i^{int} and reduce the noise in Q_i^{int} through the implementation of clipped double q-learning, thereby more accurately directing agents in coordinated exploration.

5.4 Ablation Study

We conducted ablation studies on the super hard 6h_vs_8z and MMM2 maps to specifically assess the impacts of Q_i^{int} and clipped double Q-learning. Note that removing these two components reduces our algorithm to QMIX. FSD without Q_i^{int} is denoted as FSD-wo-in, and FSD without clipped double Q-learning is denoted as FSD-sgl. It can be observed from Fig. 7 that clipped double Q-learning is crucial for agents to learn effective strategies on these maps due to the complex environments where over-estimation issues can destabilize training. Q_i^{int} also plays an important role, as FSD-sgl showed performance improvements over QMIX on both maps; additionally, FSD achieved better and more stable performance compared to FSD-wo-in. Overall, clipped double Q learning boosts learning efficiency by eliminating the overestimation problem and thereby reducing noise in Q_i^{int}.

From the results in both the Simultaneous Arrival and Predator Prey, it's evident that in relatively simpler scenarios that require highly coordinated exploration, clipped double Q-learning alone does not significantly impact. On the other hand, Q_i^{int} can help find the optimal policy by directly enhancing coordinated exploration.

Across both the complex SMAC tasks and the simpler previous tasks, combining clipped double Q-learning with Q_i^{int} maximizes the effect of Q_i^{int}, more accurately directing agents in coordinated exploration and achieving high performance stably.

6 Conclusion

This paper introduces FSD, a simple yet effective method for enhancing efficient multi-agent exploration through farsighted self-direction. FSD leverages a long-term exploration bonus, tailored for the agent, as a directional signal, which is denoised using clipped double Q-learning. With this efficient exploration method, our approach has outperformed a wide range of widely adopted baseline methods on the challenging SMAC II benchmark. The limitation of our work lies in the lack of robustness against fluctuation in prediction

error. For future work, we may consider using methods that adaptively adjust exploration magnitude to enhance robustness. Additionally, we will evaluate our method on other influential benchmarks or different application scenarios.

References

Arthur Aubret, Laetitia Matignon, and Salima Hassas. A survey on intrinsic motivation in reinforcement learning, 2019.

Peter Auer, Nicolò Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Mach. Learn.*, 47(2-3):235–256, 2002.

Adrià Puigdomènech Badia, Pablo Sprechmann, Alex Vitvitskyi, Zhaohan Daniel Guo, Bilal Piot, Steven Kapturowski, Olivier Tieleman, Martín Arjovsky, Alexander Pritzel, Andrew Bolt, et al. Never give up: Learning directed exploration strategies. In *8th International Conference on Learning Representations*, 2020.

Marc G. Bellemare, Sriram Srinivasan, Georg Ostrovski, Tom Schaul, David Saxton, and Rémi Munos. Unifying count-based exploration and intrinsic motivation. In *Advances in Neural Information Processing Systems*, pp. 1471–1479, 2016.

Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Dębiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. Dota 2 with large scale deep reinforcement learning, 2019. URL https://arxiv.org/abs/1912.06680.

Yuri Burda, Harrison Edwards, Amos J. Storkey, and Oleg Klimov. Exploration by random network distillation. In *7th International Conference on Learning Representations*, 2019.

Lior Fox, Leshem Choshen, and Yonatan Loewenstein. DORA the explorer: Directed outreaching reinforcement action-selection. In *6th International Conference on Learning Representations*, 2018.

Scott Fujimoto, Herke van Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 1582–1591. PMLR, 2018. URL http://proceedings.mlr.press/v80/fujimoto18a.html.

Sven Gronauer and Klaus Diepold. Multi-agent deep reinforcement learning: a survey. *Artif. Intell. Rev.*, 55 (2):895–943, feb 2022. ISSN 0269-2821. doi: 10.1007/s10462-021-09996-w. URL https://doi.org/10.1007/s10462-021-09996-w.

Jianye Hao, Tianpei Yang, Hongyao Tang, Chenjia Bai, Jinyi Liu, Zhaopeng Meng, Peng Liu, and Zhen Wang. Exploration in deep reinforcement learning: From single-agent to multiagent domain. *IEEE Trans. Neural Networks Learn. Syst.*, 35(7):8762–8782, 2024.

Rein Houthooft, Xi Chen, Yan Duan, John Schulman, Filip De Turck, and Pieter Abbeel. VIME: variational information maximizing exploration. In *Advances in Neural Information Processing Systems*, pp. 1109–1117, 2016.

Max Jaderberg, Wojciech M. Czarnecki, Iain Dunning, Luke Marris, Guy Lever, Antonio Garcia Castañeda, Charles Beattie, Neil C. Rabinowitz, Ari S. Morcos, Avraham Ruderman, Nicolas Sonnerat, Tim Green, Louise Deason, Joel Z. Leibo, David Silver, Demis Hassabis, Koray Kavukcuoglu, and Thore Graepel. Human-level performance in 3d multiplayer games with population-based reinforcement learning. *Science*, 364(6443):859–865, 2019. doi: 10.1126/science.aau6249. URL https://www.science.org/doi/abs/10.1126/science.aau6249.

David Janz, Jiri Hron, Przemyslaw Mazur, Katja Hofmann, José Miguel Hernández-Lobato, and Sebastian Tschiatschek. Successor uncertainties: Exploration and uncertainty in temporal difference learning. In *Advances in Neural Information Processing Systems*, pp. 4509–4518, 2019.

Natasha Jaques, Angeliki Lazaridou, Edward Hughes, Çaglar Gülçehre, Pedro A. Ortega, DJ Strouse, Joel Z. Leibo, and Nando de Freitas. Social influence as intrinsic motivation for multi-agent deep reinforcement learning. In *Proceedings of the 36th International Conference on Machine Learning*, pp. 3040–3049. PMLR, 2019.

Haobin Jiang, Ziluo Ding, and Zongqing Lu. Settling decentralized multi-agent coordinated exploration by novelty sharing. In *Thirty-Eighth AAAI Conference on Artificial Intelligence*, pp. 17444–17452. AAAI Press, 2024.

Kimin Lee, Michael Laskin, Aravind Srinivas, and Pieter Abbeel. SUNRISE: A simple unified framework for ensemble learning in deep reinforcement learning. In *Proceedings of the 38th International Conference on Machine Learning*, pp. 6131–6141. PMLR, 2021.

Chenghao Li, Tonghan Wang, Chengjie Wu, Qianchuan Zhao, Jun Yang, and Chongjie Zhang. Celebrating diversity in shared multi-agent reinforcement learning. In *Advances in Neural Information Processing Systems*, pp. 3991–4002, 2021.

Litian Liang, Yaosheng Xu, Stephen McAleer, Dailin Hu, Alexander Ihler, Pieter Abbeel, and Roy Fox. Reducing variance in temporal-difference value estimation via ensemble of deep networks. In *International Conference on Machine Learning*, pp. 13285–13301. PMLR, 2022.

Zeyang Liu, Lipeng Wan, Xinrui Yang, Zhuoran Chen, Xingyu Chen, and Xuguang Lan. Imagine, initialize, and explore: An effective exploration method in multi-agent reinforcement learning. In *Thirty-Eighth AAAI Conference on Artificial Intelligence*, pp. 17487–17495, 2024.

Ryan Lowe, Yi Wu, Aviv Tamar, Jean Harb, Pieter Abbeel, and Igor Mordatch. Multi-agent actor-critic for mixed cooperative-competitive environments. In *Advances in Neural Information Processing Systems*, pp. 6379–6390, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/68a9750337a418a86fe06c1991a1d64c-Abstract.html.

Anuj Mahajan, Tabish Rashid, Mikayel Samvelyan, and Shimon Whiteson. MAVEN: multi-agent variational exploration. In *Advances in Neural Information Processing Systems*, pp. 7611–7622, 2019.

Shakir Mohamed and Danilo Jimenez Rezende. Variational information maximisation for intrinsically motivated reinforcement learning. In *Advances in Neural Information Processing Systems*, pp. 2125–2133, 2015.

Frans A. Oliehoek and Christopher Amato. *A Concise Introduction to Decentralized POMDPs*. Springer Briefs in Intelligent Systems. Springer, 2016. ISBN 978-3-319-28927-4. doi: 10.1007/978-3-319-28929-8. URL https://doi.org/10.1007/978-3-319-28929-8.

Deepak Pathak, Pulkit Agrawal, Alexei A. Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *Proceedings of the 34th International Conference on Machine Learning*, pp. 2778–2787. PMLR, 2017.

Tabish Rashid, Mikayel Samvelyan, Christian Schröder de Witt, Gregory Farquhar, Jakob N. Foerster, and Shimon Whiteson. QMIX: monotonic value function factorisation for deep multi-agent reinforcement learning. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 4292–4301. PMLR, 2018.

Tabish Rashid, Gregory Farquhar, Bei Peng, and Shimon Whiteson. Weighted QMIX: expanding monotonic value function factorisation for deep multi-agent reinforcement learning. In *Advances in Neural Information Processing Systems*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/73a427badebe0e32caa2e1fc7530b7f3-Abstract.html.

Mikayel Samvelyan, Tabish Rashid, Christian Schröder de Witt, Gregory Farquhar, Nantas Nardelli, Tim G. J. Rudner, Chia-Man Hung, Philip H. S. Torr, Jakob N. Foerster, and Shimon Whiteson. The starcraft multi-agent challenge. In *Proceedings of the 18th International Conference on Autonomous Agents and MultiAgent Systems*, pp. 2186–2188. International Foundation for Autonomous Agents and Multiagent Systems, 2019. URL http://dl.acm.org/citation.cfm?id=3332052.

Lukas Schäfer, Oliver Slumbers, Stephen McAleer, Yali Du, Stefano V. Albrecht, and David Mguni. Ensemble value functions for efficient exploration in multi-agent reinforcement learning, 2024.

Kyunghwan Son, Daewoo Kim, Wan Ju Kang, David Hostallero, and Yung Yi. QTRAN: learning to factorize with transformation for cooperative multi-agent reinforcement learning. In *Proceedings of the 36th International Conference on Machine Learning*, pp. 5887–5896. PMLR, 2019.

Peter Sunehag, Guy Lever, Audrunas Gruslys, Wojciech Marian Czarnecki, Vinícius Flores Zambaldi, Max Jaderberg, Marc Lanctot, Nicolas Sonnerat, Joel Z. Leibo, Karl Tuyls, et al. Value-decomposition networks for cooperative multi-agent learning based on team reward. In *Proceedings of the 17th International Conference on Autonomous Agents and MultiAgent Systems*, pp. 2085–2087, 2018.

Oriol Vinyals, Igor Babuschkin, Wojciech M. Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H. Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft II using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019. doi: 10.1038/S41586-019-1724-Z. URL https://doi.org/10.1038/s41586-019-1724-z.

Jianhao Wang, Zhizhou Ren, Beining Han, Jianing Ye, and Chongjie Zhang. Towards understanding cooperative multi-agent q-learning with value factorization. In *Advances in Neural Information Processing Systems*, pp. 29142–29155, 2021a. URL https://proceedings.neurips.cc/paper/2021/hash/f3f1fa1e4348bfbebdeee8c80a04c3b9-Abstract.html.

Jianhao Wang, Zhizhou Ren, Terry Liu, Yang Yu, and Chongjie Zhang. QPLEX: duplex dueling multi-agent q-learning. In *9th International Conference on Learning Representation*, 2021b.

Tonghan Wang, Jianhao Wang, Yi Wu, and Chongjie Zhang. Influence-based multi-agent exploration. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=BJgy96EYvr.

Yuanyuan Wu, Haipeng Chen, and Feng Zhu. Dcl-aim: Decentralized coordination learning of autonomous intersection management for connected and automated vehicles. *Transportation Research Part C: Emerging Technologies*, 103:246–260, 2019.

Zhiwei Xu, Bin Zhang, Dapeng Li, Guangchong Zhou, Zeren Zhang, and Guoliang Fan. Dual self-awareness value decomposition framework without individual global max for cooperative MARL. In *Advances in Neural Information Processing Systems*, 2023.

Chao Yu, Akash Velu, Eugene Vinitsky, Jiaxuan Gao, Yu Wang, Alexandre M. Bayen, and Yi Wu. The surprising effectiveness of PPO in cooperative multi-agent games. In *Advances in Neural Information Processing Systems*, 2022.

Huichu Zhang, Siyuan Feng, Chang Liu, Yaoyao Ding, Yichen Zhu, Zihan Zhou, Weinan Zhang, Yong Yu, Haiming Jin, and Zhenhui Li. Cityflow: A multi-agent reinforcement learning environment for large scale city traffic scenario. In *The World Wide Web Conference, WWW 2019, San Francisco, CA, USA, May 13-17, 2019*, pp. 3620–3624. ACM, 2019.

Yucong Zhang and Chao Yu. EXPODE: exploiting policy discrepancy for efficient exploration in multi-agent reinforcement learning. In *Proceedings of the 2023 International Conference on Autonomous Agents and Multiagent Systems*, pp. 58–66. ACM, 2023. doi: 10.5555/3545946.3598619. URL https://dl.acm.org/doi/10.5555/3545946.3598619.

Lulu Zheng, Jiarui Chen, Jianhao Wang, Jiamin He, Yujing Hu, Yingfeng Chen, Changjie Fan, Yang Gao, and Chongjie Zhang. Episodic multi-agent reinforcement learning with curiosity-driven exploration. In *Advances in Neural Information Processing Systems*, pp. 3757–3769, 2021.