From *em*-Projections to Variational Auto-Encoder

Abstract

This paper reviews the *em*-projections in information geometry and the recent understanding of variational auto-encoder, and explains that they share a common formulation as joint minimization of the Kullback-Leibler divergence between two manifolds of probability distributions, and the joint minimization can be implemented by alternating projections or alternating gradient descent.

1 Introduction

Generative modeling is a principled framework for unsupervised learning from unlabeled data as well as semi-supervised learning from both unlabeled and labeled data. Taking advantage of the approximation capacity of deep networks [12, 17, 18], deep generative models have achieved impressive successes in unsupervised and semi-supervised learning. A popular deep generative model is the generator model [9, 16], which assumes that the observed example is generated by a latent vector via a top-down network, and the latent vector follows a known prior distribution. The down-down network can be interpreted as a decoder, and it is usually jointly trained with a bottom-up inference network that can be interpreted as an encoder in the framework of variational auto-encoder (VAE) [16].

Generative models can be understood within the framework of information geometry, where each probability distribution is treated as a point, and different families of probability distributions form different manifolds. Information geometry characterizes the geometric structures of manifolds of probability distributions, and has been widely applied to statistics, information science, dynamic systems, etc. [4, 1]. Projections from a probability distribution to a manifold can be formulated as minimizing certain divergence between probability distributions, such as the commonly used Kullback-Leibler (KL) divergence [6].

This paper reviews the information geometric *em*-algorithm which is realized by projections along *e*-geodesic and *m*-geodesic alternatively [7, 2]. We shall also review the recent understanding of variational auto-encoder (VAE) [11]. We explain that *em*-projections and VAE share a common formulation as joint minimization of the Kullback-Leibler divergence between two manifolds of probability distributions, and the joint minimization can be implemented by alternating projections or alternating gradient descent.

2 *em*-Projections

Consider the probability model $p_\theta(x, z)$ with trainable parameters θ, where x is the observed example, and z is the latent vector. Let $P = \{p_\theta(x, z), \forall \theta\}$ be the manifold formed by the model. We may call P the model manifold.

Submitted to 34th Conference on Neural Information Processing Systems (NeurIPS 2020). Do not distribute.

The information geometric *em*-algorithm considers the class of exponential family model

$$p(x, z; \lambda) = \frac{1}{Z(\lambda)} \exp(\langle \lambda, s(x, z) \rangle), \tag{1}$$

where $s(x, z)$ denotes the sufficient statistics, λ denotes the natural parameters, and $Z(\lambda)$ is the normalizing constant.

It is assumed that $p_\theta(x, z) = p(x, z; \lambda(\theta))$ for some parametrization of λ, where $\lambda(\theta)$ may not be invertible, and the resulting model is a curved exponential family model.

The exponential family model (1) can also be parametrized by its mean parameters $\mu(\lambda) = \mathbb{E}_{p_\lambda}[s(x, z)]$, which is a function of λ. Assuming $\mu(\lambda)$ is invertible, we can write $p(x, z \mid \mu) = p(x, z; \lambda)$ if $\mu = \mu(\lambda)$. Note here we use the generic notation p, but we write p_θ, $p(\cdot; \lambda)$ and $p(\cdot \mid \mu)$ in different styles to distinguish the three different parametrizations.

Define $Q = \{p(x, z|\mu), \mu = s(x_{\mathrm{obs}}, z_{\mathrm{im}}), \forall z_{\mathrm{im}}\}$ where x_{obs} is fixed at the observed value of x, and z_{im} is the potential imputed value of z

The information geometric *em*-algorithm [2, 3] solves the following joint minimization problem:

$$\min_{p \in P, q \in Q} \mathbb{D}_{\mathrm{KL}}(q\|p). \tag{2}$$

The algorithm is formulated as follows: initialize at a $p \in P$, and alternate the following two projections:

- ***e*-projection**: e-project the current p to Q by minimizing $\mathbb{D}_{\mathrm{KL}}(q\|p)$ over $q \in Q$.

- ***m*-projection**: m-project the current q to P by minimizing $\mathbb{D}_{\mathrm{KL}}(q\|p)$ over $p \in P$.

e- and m-projections derive their names from the manifold of exponential family distributions and the manifold of mixture distributions respectively. The two manifolds have different notions of flatness.

The *em*-algorithm is closely related to the Expectation-Maximization (EM) algorithm [8, 21]. If we define $Q = \{p(x, z|\mu), \mu = \mathbb{E}_{q(z_{\mathrm{im}}|x_{\mathrm{obs}})}[s(x_{\mathrm{obs}}, z_{\mathrm{im}})], \forall q(z|x)\}$, where $q(z|x)$ is an arbitrary imputation distribution, then the *em*-algorithm becomes the EM algorithm.

In the above, we gloss over the difference between a single observation and repeated observations.

Moving beyond exponential family models. The original *em* and EM algorithms are formulated within the framework of exponential family models (1). For modern deep generative models, such a framework is rather limited. In the following, we shall not limit ourselves to exponential family models, and we shall re-define the Q manifold. We shall focus on the key insight of joint minimization (2) and alternating projections. In what follows, we shall connect this insight to the recent understanding of VAE [11].

3   VAE as alternating projections

3.1   Generator model

The generator model [9, 16] is a non-linear generalization of factor analysis:

$$z \sim \mathrm{N}(0, I_d); \ x = g_\theta(z) + \epsilon, \tag{3}$$

where x is an image, or a sentence, or in general a high-dimensional example, z is a d-dimensional latent vector. I_d is the d-dimensional identity matrix. $g_\theta(z)$ is a top-down deep network, where θ consists of all the weight and bias terms. ϵ is usually assumed to be Gaussian white noise with mean 0 and variance σ^2. Thus $p_\theta(x|z)$ is $\mathrm{N}(g_\theta(z), \sigma^2 I_D)$, where D is the dimensionality of x. The generator model defines the joint probability model or the *complete-data model* $p_\theta(x, z) = p(z)p_\theta(x|z)$, where $p(z)$ is the known prior model. We define $P = \{p_\theta(x, z), \forall \theta\}$ to be the *model distribution manifold*. The marginal density or the observed-data model is $p_\theta(x) = \int p_\theta(x, z)dz$, which is analytically implicit due to the intractable integral.

Let $p_{\mathrm{data}}(x)$ be the data distribution that generates the observed x. The learning of $p_\theta(x)$ can be based on $\min_\theta \mathbb{D}_{\mathrm{KL}}(p_{\mathrm{data}}(x)\|p_\theta(x))$. If we observe training examples $\{x_i, i = 1, ..., n\} \sim p_{\mathrm{data}}(x)$,

the above minimization can be approximated by maximizing the log-likelihood

$$L(\theta) = \frac{1}{n}\sum_{i=1}^{n}\log p_\theta(x_i) \doteq \mathbb{E}_{p_{\text{data}}}[\log p_\theta(x)], \tag{4}$$

which leads to maximum likelihood estimate (MLE). In this paper, we assume the sample size n is large enough so that the sample average over $\{x_i, i = 1, ..., n\}$ is essentially the same as expectation with respect to p_{data}.

3.2 EM

The EM algorithm can be understood by perturbing the KL-divergence for MLE. Define $D(\theta) = \mathbb{D}_{\text{KL}}(p_{\text{data}}(x)\|p_\theta(x))$. Then $\min_\theta D(\theta)$ is equivalent to $\max_\theta L(\theta)$. Let θ_t be the estimate at iteration t of EM. Let us consider the following perturbation of $D(\theta)$,

$$
\begin{aligned}
S(\theta) &= D(\theta) + \mathbb{D}_{\text{KL}}(p_{\theta_t}(z|x)\|p_\theta(z|x)) \\
&= \mathbb{D}_{\text{KL}}(p_{\text{data}}(x)\|p_\theta(x)) + \mathbb{D}_{\text{KL}}(p_{\theta_t}(z|x)\|p_\theta(z|x)) \\
&= \mathbb{D}_{\text{KL}}(p_{\text{data},\theta_t}(x,z)\|p_\theta(x,z)),
\end{aligned} \tag{5}
$$

where we define $p_{\text{data},\theta_t}(x,z) = p_{\text{data}}(x)p_{\theta_t}(z|x)$ as the complete-data distribution at iteration t. $S(\theta)$ is a surrogate for $D(\theta)$ at iteration t, and $S(\theta)$ is simpler than $D(\theta)$ because $S(\theta)$ is based on the joint distributions of (x,z) instead of the implicit marginal distribution of x as in $D(\theta)$.

Figure 1: Illustration of EM. The surrogate S majorizes (upper bounds) D, and they touch each other at θ_t with the same tangent.

The perturbation term $\mathbb{D}_{\text{KL}}(p_{\theta_t}(z|x)\|p_\theta(z|x))$, as a function of θ, achieves its minimum 0 at $\theta = \theta_t$. Being a minimum, its derivative at $\theta = \theta_t$ is zero. Thus $S(\theta) \geq D(\theta)$, i.e., S majorizes D, and they touch each other at θ_t, where they share the same gradient at θ_t, i.e., $D'(\theta_t) = S'(\theta_t)$. The EM algorithm finds $\theta_{t+1} = \arg\min_\theta S(\theta)$. Since $S(\theta_{t+1}) \leq S(\theta_t)$, and S majorizes D, we have $D(\theta_{t+1}) \leq D(\theta_t)$, which is the monotonicity of EM.

The above also underlies the gradient descent algorithm, in particular, the alternating back-propagation algorithm of [10], where $D'(\theta_t)$ is computed by $S'(\theta_t)$.

3.3 EM as alternating projections

Define $q(x,z) = p_{\text{data}}(x)q(z|x)$, and re-define $Q = \{q(x,z) = p_{\text{data}}(x)q(z|x).\forall q(z|x)\}$, where $p_{\text{data}}(x)$ is fixed, and $q(z|x)$ can be any conditional distribution of z given x. We may call $q(z|x)$ the inference distribution or imputation distribution that imputes the latent z based on x. $q(x,z)$ is the *complete-data distribution*. Q is the *data distribution manifold*.

The EM algorithm alternates the following projections:

- **expectation-projection**: Given the current p, $\min_q \mathbb{D}_{\text{KL}}(q\|p)$ over $q \in Q$.
- **m-projection**: Given the current q, $\min_p \mathbb{D}_{\text{KL}}(q\|p)$ over $p \in P$.

The m-projection remains the same as in the *em*-projections. The expectation-projection underlies the E-step. In the expectation-projection at iteration t with θ_t, we can write

$$\mathbb{D}_{\text{KL}}(q(x,z)\|p_{\theta_t}(x,z)) = \mathbb{D}_{\text{KL}}(p_{\text{data}}(x)\|p_{\theta_t}(x)) + \mathbb{D}_{\text{KL}}(q(z|x)\|p_{\theta_t}(z|x)), \tag{6}$$

where the conditional KL divergence is defined as

$$\mathbb{D}_{\text{KL}}(q(z|x)\|p(z|x)) = \mathbb{E}_{p_{\text{data}}(x)}\mathbb{E}_{q(z|x)}\left[\log \frac{q(z|x)}{p(z|x)}\right],$$

with the outer expectation with respect to p_{data}. Clearly the minimization in expectation-projection is achieved at $q(z|x) = p_{\theta_t}(z|x)$. The minimization of the *m*-projection is to minimize $S(\theta)$ above.

3.4 VAE

The generator model is commonly trained by variational auto-encoder (VAE) [16]. VAE assumes an inference model $q_\phi(z|x)$ as an approximation to the true posterior distribution $p_\theta(z|x)$. In VAE, $q_\phi(z|x)$ is $N(\mu_\phi(x), V_\phi(x))$, where the mean vector μ_ϕ and the diagonal variance-covariance matrix V_ϕ are parametrized by bottom-up inference networks with a new set of parameters ϕ. For $z \sim q_\phi(z|x)$, we can write $z = \mu_\phi(x) + V_\phi(x)^{1/2}w$, where $w \sim N(0, I_d)$ is Gaussian white noise. Thus expectation with respect to $z \sim q_\phi(z|x)$ can be written as expectation with respect to w. This reparameterization trick [16] helps reduce the variance in Monte Carlo integration. $q_\phi(z|x)$ is the learned inferential computation that approximately samples from $p_\theta(z|x)$. Different from traditional variational inference [15, 19, 5], the parameters ϕ in $q_\phi(z|x)$ are shared by all the training examples x. ϕ and θ can be trained together by jointly maximizing a lower bound of the log-likelihood.

3.5 VAE as alternating projections

Figure 2: Illustration of variational auto-encoder as alternating projections between model manifold P of complete-data models and data manifold Q of complete-data distributions.

Now we re-define $q_{\text{data},\phi}(x, z) = p_{\text{data}}(x)q_\phi(z|x)$, and re-define $Q = \{q_{\text{data},\phi}(x, z) = p_{\text{data}}(x)q_\phi(z|x), \forall \phi\}$. We can formulate VAE as joint minimization $\min_{p \in P, q \in Q} \mathbb{D}_{\text{KL}}(q\|p)$, where

$$\mathbb{D}_{\text{KL}}(q_{\text{data},\phi}(x, z)\|p_\theta(x, z)) = \mathbb{D}_{\text{KL}}(p_{\text{data}}(x)\|p_\theta(x)) + \mathbb{D}_{\text{KL}}(q_\phi(z|x)\|p_\theta(z|x)), \tag{7}$$

On the right hand side, $D(\theta) = \mathbb{D}_{\text{KL}}(p_{\text{data}}(x)\|p_\theta(x))$ leads to the log-likelihood, and $S(\theta, \phi) = \mathbb{D}_{\text{KL}}(q_{\text{data},\phi}(x, z)\|p_\theta(x, z)) = D(\theta) + \mathbb{D}_{\text{KL}}(q_\phi(z|x)\|p_\theta(z|x))$ is a perturbation of $D(\theta)$. Minimizing $S(\theta, \phi)$ is equivalent to maximizing the evidence lower bound of the log-likelihood.

The minimization can be accomplished by alternating projections:

- **encoder-projection**: Given the current p, $\min_q \mathbb{D}_{\text{KL}}(q\|p)$ over $q \in Q$.
- ***m*-projection**: Given the current q, $\min_p \mathbb{D}_{\text{KL}}(q\|p)$ over $p \in P$.

Again the *m*-projection remains the same as in the *em*-algorithm. The encoder-projection in VAE is the same as the expectation-projection in EM, except that it is minimization over the inference model or the encoder model $q_\phi(z|x)$, instead of arbitrary $q(z|x)$ as in EM. The optimization is variational inference optimization [15, 19, 5], and the optimized $q_\phi(z|x)$ may have a gap from the true posterior $p_\theta(z|x)$. Figure 2 illustrates the alternating projections. In practice, the alternating projections can be implemented by alternating gradient descent.

The wake-sleep algorithm [14, 13] is similar to VAE, except that it updates ϕ by $\min_q \mathbb{D}_{\text{KL}}(P\|Q)$ based on sleep data generated from P. Compared to encoder-projection, the order in KL divergence is reversed. As is well known, reversing the order of KL divergence in minimization leads to different behaviors.

4 Conclusion

This paper reviews the information geometric *em*-algorithm and the recent understanding of VAE. While VAE does not share the framework of exponential family models with the *em*-algorithm, they share the same theoretical framework of joint minimization of KL divergence between two manifolds of distributions, as well as alternating projections (or alternating gradient descent) computation.

See [11] for an information geometric understanding of adversarial learning within the framework of energy-based models, and its integration with variational learning explained in this paper.

References

[1] Shun-ichi Amari. Dualistic geometry of the manifold of higher-order neurons. *Neural Networks*, 4(4):443–451, 1991.

[2] Shun-ichi Amari. The em algorithm and information geometry in neural network learning. *Neural Computation*, 7(1):13–18, 1995.

[3] Shun-Ichi Amari. Information geometry of the em and em algorithms for neural networks. *Neural networks*, 8(9):1379–1408, 1995.

[4] S-I Amari and Te Sun Han. Statistical inference under multiterminal rate restrictions: A differential geometric approach. *IEEE Transactions on Information Theory*, 35(2):217–227, 1989.

[5] David M Blei, Alp Kucukelbir, and Jon D McAuliffe. Variational inference: A review for statisticians. *Journal of the American statistical Association*, 112(518):859–877, 2017.

[6] Thomas M. Cover and Joy A. Thomas. *Elements of information theory (2. ed.)*. Wiley, 2006.

[7] Imre Csiszár. Information geometry and alternating minimization procedures. *Statistics and decisions*, 1:205–237, 1984.

[8] Arthur P Dempster, Nan M Laird, and Donald B Rubin. Maximum likelihood from incomplete data via the EM algorithm. *Journal of the royal statistical society. Series B (methodological)*, pages 1–38, 1977.

[9] Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron C. Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in Neural Information Processing Systems 27: Annual Conference on Neural Information Processing Systems 2014, December 8-13 2014, Montreal, Quebec, Canada*, pages 2672–2680, 2014.

[10] Tian Han, Yang Lu, Song-Chun Zhu, and Ying Nian Wu. Alternating back-propagation for generator network. In *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence, February 4-9, 2017, San Francisco, California, USA.*, pages 1976–1984, 2017.

[11] Tian Han, Erik Nijkamp, Xiaolin Fang, Mitch Hill, Song-Chun Zhu, and Ying Nian Wu. Divergence triangle for joint training of generator model, energy-based model, and inferential model. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

[12] Geoffrey Hinton, Yann LeCun, and Yoshua Bengio. Deep learning. *Nature*, 521(7553):436–444, 2015.

[13] Geoffrey E Hinton, Peter Dayan, Brendan J Frey, and Radford M Neal. The" wake-sleep" algorithm for unsupervised neural networks. *Science*, 268(5214):1158–1161, 1995.

[14] Shiro Ikeda, Shun-ichi Amari, and Hiroyuki Nakahara. Convergence of the wake-sleep algorithm. In *Advances in neural information processing systems*, pages 239–245, 1999.

[15] Michael I Jordan, Zoubin Ghahramani, Tommi S Jaakkola, and Lawrence K Saul. An introduction to variational methods for graphical models. *Machine learning*, 37(2):183–233, 1999.

[16] Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014.

[17] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E. Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems 25: 26th Annual Conference on Neural Information Processing Systems 2012. Proceedings of a meeting held December 3-6, 2012, Lake Tahoe, Nevada, United States*, pages 1106–1114, 2012.

[18] Yann LeCun, Yoshua Bengio, et al. Convolutional networks for images, speech, and time series. *The handbook of brain theory and neural networks*, 3361(10):1995, 1995.

[19] Radford M Neal and Geoffrey E Hinton. A view of the em algorithm that justifies incremental, sparse, and other variants. In *Learning in graphical models*, pages 355–368. Springer, 1998.

[20] Erik Nijkamp, Bo Pang, Tian Han, Alex Zhou, Song-Chun Zhu, and Ying Nian Wu. Learning deep generative models with short run inference dynamics. *arXiv preprint arXiv:1912.01909*, 2019.

[21] Donald B Rubin and Dorothy T Thayer. EM algorithms for ML factor analysis. *Psychometrika*, 47(1):69–76, 1982.

Appendix: Short-run inference

Between EM and VAE, we can strike a middle ground, where we use the short-run MCMC for approximate inference [20]. Specifically, for the true posterior $p_\theta(z|x)$, we can use Langevin dynamics for short-run MCMC:

$$z_0 \sim p(z), \ z_{k+1} = z_k + s\frac{\partial}{\partial z}\log p_\theta(z_k|x) + \sqrt{2s}e_k, \ k = 1, ..., K, \tag{8}$$

where we initialize the dynamics from the fixed prior distribution of z, i.e., $p(z) \sim \mathrm{N}(0, I_d)$, and $e_k \sim \mathrm{N}(0, I_d)$ is the Gaussian white noise. The dynamics runs a fixed number of K steps with step size s. We use $q_\theta(z|x)$ to represent the distribution of z_K. Then the learning with short-run inference is based on

$$\begin{aligned} S(\theta) &= \mathbb{D}_{\mathrm{KL}}(p_{\mathrm{data}}(x)\|p_\theta(x)) + \mathbb{D}_{\mathrm{KL}}(q_{\theta_t}(z|x)\|p_\theta(z|x)) \\ &= \mathbb{D}_{\mathrm{KL}}(p_{\mathrm{data}}(x)q_{\theta_t}(z|x)\|p_\theta(z, x)). \end{aligned} \tag{9}$$

With θ_t fixed at iteration t, θ_{t+1} is obtained by gradient descent on $S(\theta)$. The learning algorithm is a perturbation of maximum likelihood gradient ascent, where the perturbation is $\mathbb{D}_{\mathrm{KL}}(q_{\theta_t}(z|x)\|p_\theta(z|x))$. As $K \to \infty$, $\mathbb{D}_{\mathrm{KL}}(q_\theta(z|x)\|p_\theta(z|x)) \to 0$ monotonically [6].

Unlike VAE, $q_\theta(z|x)$ does not involve a new set of variational parameters ϕ. It is still based on the parameters θ of the generator model. However, we can optimize the small number of algorithmic parameters such as step size by minimizing $\mathbb{D}_{\mathrm{KL}}(q_{\theta_t}(z|x)\|p_\theta(z|x))$ [20].