Safe Neurosymbolic Learning with Differentiable Symbolic Execution

Abstract

We study the problem of learning worst-case-safe parameters for programs that use neural networks as well as symbolic, human-written code. Such *neurosymbolic* programs arise in many safety-critical domains. However, because they need not be continuous, let alone differentiable, they cannot be learned using existing gradient-based approaches to safe learning. Our method, *Differentiable Symbolic Execution* (DSE), learns such programs by sampling code paths using symbolic execution, constructing gradients of a worst-case "safety loss" along these paths, and then backpropagating these gradients through program operations using a generalization of the REINFORCE estimator. We evaluate the method on a mix of synthetic tasks and real-world benchmarks. Our experiments show that DSE significantly outperforms the state-of-the-art DIFFAI method on these tasks.

1 Introduction

Safety on worst-case inputs has recently emerged as a key challenge in deep learning research. Formal verification of neural networks (Albarghouthi, 2021) is an established response to this challenge. In particular, an exciting body of recent work (Mirman et al., 2018; Madry et al., 2017; Cohen et al., 2019; Singh et al., 2018) has sought to incorporate formal verification into the training of neural networks. DIFFAI, among the most prominent of such approaches, uses a neural network verifier to construct a differentiable, worst-case safety loss for the learner. This loss is used to regularize a standard data-driven loss, biasing the learner towards parameters that are both performant and safe.

A weakness of these methods is that they only consider functional properties (such as adversarial robustness) of isolated neural networks. By contrast, in real-world applications, neural networks are often embedded within human-written symbolic code, and correctness requirements apply to the entire neurosymbolic composition. For example, consider a car directed by a neural controller (Qin & Badgwell, 2000). Safety properties for the car are functions of its trajectories, and these trajectories depend not just on the controller but also the symbolic equations that define the environment. While recent work (Christakis et al., 2021) has studied the verification of such neurosymbolic programs, there is no prior work on integrating verification and learning for such systems.

In this paper, we present the first steps towards such an integration. The fundamental technical challenge here is that while a neural network is differentiable over its parameters, the code surrounding may be non-differentiable or even discontinuous. This puts our problem beyond the scope of existing methods for integrated learning and verification.

We overcome this difficulty using a new method, *Differentiable Symbolic Execution* (DSE), for estimating gradients of worst-case safety losses of nondifferentiable neurosymbolic programs. DSE is based on a generalization of the classic REINFORCE estimator, which backpropagates gradients through non-differentiable operations by approximating integrals with sampling. In our problem, the integral is the aggregate of the safety losses along symbolic control flow paths in the program. To apply REINFORCE-like ideas here, we need to represent and sample paths in a symbolic way. We do so through an adaptation of the classic method of *symbolic execution*.

We evaluate DSE through several case studies in the embedded control and navigation domains. Our baselines include an extended version of DIFFAI, the current state of the art, and an ablation that does not use an explicit safety loss. Our experiments show that DSE significantly outperforms the

```
1   Example(x):  // x ∈ [−5, 5]
2       y := NNθ(x)
3       if y ≤ 1.0:
4           z := x + 10.0
5       else :
6           z := x − 5.0
7       assert (z <= 1)
```

$Loc = \{\ell_2, \ell_3, \ell_7\}, X = \{x, y, z\}, l_0 = \{\ell_2\}$
$Init = (-5 \leq x \leq 5)$
$Safe(l_7) = (z \leq 1), Safe(l_2) = \textbf{True}, Safe(l_3) = \textbf{True}$
$Trans_\theta = \{(\ell_2, \textbf{True}, \langle y := NN_\theta(x) \rangle, \ell_3),$
$\qquad\qquad (\ell_3, (y \leq 1.0), \langle z := x + 10.0 \rangle, \ell_7),$
$\qquad\qquad (\ell_3, (y > 1.0), \langle z := x - 5.0 \rangle, \ell_7)$

Figure 1: (Left) An example program. NN_θ is a neural network with parameters θ. DIFFAI fails to learn safe parameters for this program. (Right) The program as an STS. The location ℓ_i in the STS corresponds to line i in the program. We abbreviate the updates by only showing the variable that changes value.

baselines in finding safe and high-performance model parameters. We also do a series of synthetic experiments that highlight the practical difficulty that DIFFAI-style approaches face in our setting.

To summarize, our main contributions are:

- We present the first approach to worst-case-safe parameter learning for neural networks embedded within nondifferentiable, symbolic programs.

- As part of our learning algorithm, we give a new way to bring together symbolic execution and stochastic gradient estimators that might have applications outside our immediate task.

- We present experimental results that indicate the advantages of DSE over the state-of-the-art in verified learning.

2   PROBLEM FORMULATION

Programs. We define programs with embedded neural networks as *symbolic transition systems* (STS) (Manna & Pnueli, 2012). Formally, a program F_θ is a tuple $(Loc, X, l_0, Init, Safe, Trans_\theta)$. Here, Loc is a finite set of *(control) locations*, $X = \{x_1, \ldots, x_m\}$ is a set of real-valued variables, and $l_0 \in Loc$ is the *initial location*. $Init$, a boolean formula over X, is an initial condition for the program. $Safe$ is a map from locations to constraints over X; intuitively, $Safe(l)$ is a safety requirement asserted at location l. Finally, $Trans_\theta$ is a *transition relation* consisting of *transitions* (l, G, U_θ, l') such that: (i) l is the *source location* and l' is the *destination location*; (ii) the *guard* G is a constraint over X; and (iii) the *update* U_θ is a vector $\langle U_{1,\theta}, \ldots, U_{m,\theta} \rangle$, where each $U_{i,\theta}$ is a real-valued expression over X constructed using standard symbolic operators and neural networks with parameters θ. Intuitively, $U_{i,\theta}$ represents the update to the i-th variable. We assume that each $U_{i,\theta}$ is differentiable in θ. Also, we assume that the programs are *deterministic*. That is, if G and G' are guards for two distinct transitions from the same source state, then $G \wedge G'$ is unsatisfiable.

Programs in higher-level languages can be translated to the STS notation in a standard way. For example, Figure 1 (left) shows a simple high-level program. The STS for this program appears in Figure 1 (right). Remarkably, while the program is simple, the state-of-the-art DIFFAI approach to verified learning fails to learn safe parameters for it.

Safety Semantics. In classical formal methods, a program is considered to be safe if all of its executions satisfy a logical constraint. However, in learning settings, it helps to know not only whether a program is unsafe, but also the *extent* to which it is unsafe. Consequently, we define the safety semantics of programs in a quantitative way, in terms of a *(worst-case) safety loss* that quantifies the extent program's safeness.

Formally, let a *state* of F_θ be a pair $s = (l, v)$, where l is a location and $v \in \mathbb{R}^m$ is an *assignment* of values to the variables (i.e., $v(i)$ is the value of x_i). Such a state is said to be *at* location l. For boolean constraints B and assignments v to variables in B, let us write $B(v)$ if v satisfies B. A state (l_0, v), where $Init(v)$, is an *initial state*. A state (l, v) is *safe* if $(Safe(l))(v)$.

Let $v \in \mathbb{R}^m$ be an assignment to the variables. For a real-valued expression E over X, let $E(v)$ be the value of E when x_i is substituted by $v(i)$. For an update $U = \langle U_1, \ldots, U_n \rangle$, we define $U(v)$ as the assignment $\langle U_1(v), \ldots, U_n(v) \rangle$. A length-$n$ *trajectory* of F_θ is a sequence $\tau = \langle s_0, \ldots, s_n \rangle$, with $s_i = (l_i, v_i)$, such that: (i) s_0 is an initial state; and (ii) for each i, there is a transition (l_i, G, U, l_{i+1}) such that $G(v_i)$ and $v_{i+1} = U(v_i)$.

Let us fix a size bound N for trajectories. A trajectory $\tau = \langle s_0, \ldots, s_n \rangle$ is *maximal* if it has length N, or if there is no trajectory $\tau' = \langle s_0, \ldots, s_n, s_{n+1} \rangle$ with length $\leq N$. Because our programs are deterministic, there is a unique maximal trajectory from each s_0. We denote this trajectory by $\tau(s_0)$.

Let us assume a real-valued loss $Unsafe(s)$ that quantifies the *unsafeness* of each state s. We require $Unsafe(s) = 0$ if s is safe and $Unsafe(s) > 0$ otherwise. We lift this measure to trajectories τ by letting $Unsafe(\tau) = \sum_{s \text{ appears in } \tau} Unsafe(s)$. The *safety loss* $C(\theta)$ for F_θ is now defined as:

$$C(\theta) = \max_{s \text{ is an initial state}} Unsafe(\tau(s)). \tag{1}$$

Thus, $C(\theta) = 0$ if and only if all program trajectories are safe.

Problem Statement. Our learning problem formalizes a setting in which we have training data for neural networks inside a program F_θ. While training the networks with respect to this data, we must ensure that the overall program satisfies its safety requirements.

To ensure that the parameters of the different neural networks in F_θ are not incorrectly entangled, we assume that only one of these networks, $\mathbf{NN}_\theta$, has trainable parameters.[1] We expect as input a training set of i.i.d. samples from an unknown distribution over the inputs and outputs of $\mathbf{NN}_\theta$, and a differentiable *data loss* $Q(\theta)$ that quantifies the network's fidelity to this training set. Our learning goal is to solve the following constrained optimization problem:

$$\min_\theta Q(\theta) \qquad \text{s.t. } C(\theta) \leq 0. \tag{2}$$

3   Learning Algorithm

Our learning approach is based on two ideas. First, we directly apply a recently-developed equivalence between constrained and regularized learning (Agarwal et al., 2018; Le et al., 2019) to reduce Equation (2) to a series of unconstrained optimization problems. Second, we use the novel technique of *Differentiable Symbolic Execution* (DSE) to solve these unconstrained problems.

At the highest level, we *convexify* the class of programs F_θ by allowing stochastic combination of programs. That is, we now allow programs of the form $F_{\hat\theta} = \sum_{t=1}^T \alpha_t F_{\theta_t}$, where $\sum_i \alpha_t = 1$. To execute the program F_θ from a given initial state, one samples a specific program F_{θ_t} from the distribution $(\alpha_1, \ldots, \alpha_t)$ and then executes it from that state.

Equation (2) can now be written into the problem $\max_{\lambda \in \mathbb{R}^+} \min_{\hat\theta} Q(\hat\theta) + \lambda C(\hat\theta)$, which in turn can be solved using a classic algorithm (Freund & Schapire, 1999) for computing equilibria in a two-player game. We omit further details about this algorithm because it follows Le et al. (2019). (For more details, see Appendix A.1).

A key feature of our high-level algorithm is that it repeatedly solves the optimization problem

$$\min_\theta Q(\theta) + \lambda C(\theta) \tag{3}$$

for fixed values of λ. This problem is challenging because while $Q(\theta)$ is differentiable in θ, $C(\theta)$ depends on the entirety of F_θ and may not even be continuous. As we demonstrate in Section 5, this makes it difficult to apply state-of-the-art gradient-based approaches to worst-case safe learning.

DSE, our main contribution, addresses this challenge by estimating gradients $\nabla_\theta C^\#(\theta)$ of a differentiable approximation $C^\#(\theta)$ of $C(\theta)$. We present the details of this method in the next section.

4   Differentiable Symbolic Execution

Background on Symbolic Execution. DSE is a refinement of *symbolic execution* (Baldoni et al., 2018), a classic technique for systematic formal analysis of programs. Symbolic execution has been

---

[1]Note that some of our experimental benchmarks have $k > 1$ trainable neural modules. In these tasks, each neural module comes with its own training data; thus, in effect, we have k instances of the learning problem. Our implementation learns the modules simultaneously by interleaving their gradient updates. However, the gradient of Q for each module is only influenced by its own data.

recently used to analyze the safety of neural networks (Gopinath et al., 2018). However, we are not aware of any prior attempt to incorporate symbolic execution into neural network training.

A symbolic executor systematically searches the set of *symbolic trajectories* of programs, which we now define. Consider a program $F_\theta = (Loc, X = \{x_1, \ldots, x_m\}, l_0, Init, Safe, Trans_\theta)$ as in Section 2. First, we fix a syntactically restricted class $\mathcal{V}_\theta$ of boolean constraints over the variables X and parameters θ. $\mathcal{V}_\theta$ is required to be closed under conjunction. For example, in our implementation, $\mathcal{V}_\theta$ consists of formulas that specify closed or open intervals, with bounds given by expressions over parameters, in which each variable lies.

A *symbolic state* of F_θ is a pair $\sigma_\theta = (l, V_\theta)$, where l is a location and $V_\theta \in \mathcal{V}_\theta$. Intuitively, σ_θ represents the set of states of F_θ that are at location l and satisfy the property V_θ.

In particular, we designate a finite set of *initial symbolic states* $(l_0, V_0^1), \ldots, (l_p, V_0^p)$. It is required that $\bigvee_i V_0^i \Rightarrow Init$. Intuitively, these initial symbolic states "cover" all the possible initial states of the program F_θ.

We also construct an *overapproximate update* $U_\theta^\# : \mathcal{V}_\theta \to \mathcal{V}_\theta$ for each update U_θ in F_θ. For all $V \in \mathcal{V}_\theta$, we have $U_\theta^\#(V) \Rightarrow Post$, where $Post(v)$ is the formula $\exists v' : V(v') \wedge (U(v') = v)$. Intuitively, $U_\theta^\#(V)$ is an overapproximate representation of the set of states reached by applying U_θ to a state that satisfies V.

Let us call a transition $t = (l, G, U, l')$ *enabled* at a symbolic state (l, V) if $(G \wedge V)$ is satisfiable. A *symbolic trajectory* of F_θ is a sequence $\tau_\theta^\# = \langle \sigma_0, \ldots, \sigma_n \rangle$ with the following properties:

- σ_0 is an initial symbolic state.
- Let $\sigma_i = (l_i, V_i)$. Then there exists a transition $t = (l_i, G_i, U_i, l_{i+1})$ such that: (i) t is enabled at σ_i, and (ii) $V_{i+1} = U^\#(G_i \wedge V_i)$. In this case, we write $\sigma_{i+1} = t(\sigma_i)$.

Intuitively, $\tau_\theta^\#$ represents an overapproximation of the set of concrete trajectories of F_θ that pass through the "control path" $\langle l_0, \ldots, l_n \rangle$.

The above symbolic trajectory is *safe* if for all i, $V_i \Rightarrow Safe(l_i)$. Intuitively, in this case, all concrete trajectories that the symbolic trajectory represents follow the program's safety requirements.

Example(Cont.) Consider the example program in Figure 1. Let us assume a single initial symbolic state where $x \in [-5, 5]$ and $\mathbf{NN}_\theta \in [-2, 2]$ when $x \in [-5, 5]$. The program has two symbolic trajectories from this state:

- $\tau_1^\# = \langle (\ell_2, x \in [-5, 5]), (\ell_3, x \in [-5, 5] \wedge y \in [-2, 2]), (\ell_7, x \in [-5, 5] \wedge y \in [-2, 1] \wedge z \in [5, 15]) \rangle$
- $\tau_2^\# = \langle (\ell_2, x \in [-5, 5]), (\ell_3, x \in [-5, 5] \wedge y \in [-2, 2]), (\ell_7, x \in [-5, 5] \wedge y \in (1, 2] \wedge z \in [-10, 0]) \rangle$.

We note that only $\tau_2^\#$ is safe.

Probabilistic Symbolic Execution. A key difficulty with using symbolic execution to estimate the safety loss $C(\theta)$ is that our programs need not be differentiable, or even continuous. To understand the issues here, consider our running example once again. Here, the parameter θ is used to calculate the variable y, which is used in a discontinuous conditional statement that assigns very different values to the variable z in its two branches. Additionally, a slight change in θ can sometimes cause the guard G of the conditional to go from being **True** on *some* values of y, to being **False** on *all* values of y. In the second case, the updated θ would have one, rather than two, symbolic trajectories. If the symbolic trajectory $\tau^\#$ in which G is **True** serves as an edge case to judge whether a program is worst-case-safe, learning safe parameters would be difficult, as there would be no gradient guiding the optimizer back to the case in which G is **True**.

DSE overcomes these difficulties using a probabilistic approach to symbolic execution. Specifically, at a symbolic state $\sigma_i = (l_i, V_i)$, the symbolic executor in DSE *samples* its next action following a probability distribution $p_\theta(t \mid \sigma_i)$, where t ranges over program transitions or a special action $Stop$.

For a boolean expression V_θ over the program variables and parameters, let $\mathbf{Vol}(V_\theta)$ denote the *volume* of the assignments to X that satisfy V_θ. Then we define:

- If there is a unique program transition t that is enabled at σ_i, then $p_\theta(t|\sigma_i) = 1$.

- If there is no transition t that is enabled at σ_i, then $p_\theta(Stop|\sigma_i) = 1$.

- Otherwise, let $t_1, \ldots, t_k$ be the transitions that are enabled at σ_i, with $t_i = (l_i, G_i, U_i, l_{i+1})$. Then $p_\theta(t_j|\sigma_i) = \frac{\mathbf{Vol}(G_j \wedge V_i)}{\mathbf{Vol}(V_i)}$.

We also define a volume-weighted probability distribution $p(\sigma_0)$ over the (finite set of) initial symbolic states σ_0^i. Specifically, for each $\sigma_0^i = (l_0, V_0^i)$, we have

$$p(\sigma_0^i) = \frac{\mathbf{Vol}(V_0^i)}{\sum_j \mathbf{Vol}(V_0^j)}. \tag{4}$$

DSE uses the distributions $p_\theta(t|\sigma_i)$ and $p(\sigma_0)$ to sample symbolic trajectories. Let $\tau_\theta^\# = \langle \sigma_0, \ldots, \sigma_n \rangle$, with $\sigma_{i+1} = t_i(\sigma_i)$. The probability of sampling $\tau^\#$ is

$$p_\theta(\tau_\theta^\#) = p(\sigma_0) \prod_i p_\theta(t_i|\sigma_{i-1}). \tag{5}$$

We note that p_θ is differentiable in θ.

Approximate Safety Loss. A key decision in DSE is to approximate the overall worst-case loss $C(\theta)$ by the *expectation* of a differentiable safety loss computed per sampled symbolic trajectory. Recall the safety loss $Unsafe(s)$ for individual states. For $\sigma = (l, V)$, we define $Unsafe_\theta(\sigma)$ as a differentiable approximation of the worst-case loss $\max_{s \text{ satisfies } V} Unsafe(s)$. We lift this loss to symbolic trajectories $\tau_\theta^\# = \langle \sigma_0, \ldots, \sigma_n \rangle$ by defining $Unsafe_\theta(\tau^\#) = \sum_i Unsafe_\theta(\sigma_i)$. We observe that $Unsafe_\theta$ is differentiable in θ.

Our approximation to the safety loss is now given by:

$$C^\#(\theta) = \mathbf{E}_{\tau^\# \sim p_\theta(\tau^\#)} Unsafe_\theta(\tau^\#). \tag{6}$$

Note that a low value of $C^\#(\theta)$ does not always guarantee worst-case safety. To take an extreme example, the safety loss for a trajectory whose symbolic states have near-zero volumes will be close to zero as well. However, as we show in Section 5, DSE commonly finds parameters that are safe with respect to the true safety criterion in spite of these approximations employed during learning.

Example(Cont.) Consider the trajectories $\tau_1^\#$ and $\tau_2^\#$ in our running example. We have $p(\tau_1^\#) = p(t_2|\sigma_2)$, as the other transitions in $\tau_1^\#$ have probability 1. We compute $p(t_2|\sigma_2) = \frac{\mathbf{Vol}([-2,1])}{\mathbf{Vol}([-2,2])} = 0.75$. Thus, $p(\tau_1^\#) = 0.75$ and similarly, $p(\tau_2^\#) = 0.25$.

Gradient Estimation. Our ultimate goal is to compute the gradient $\nabla_\theta C^\#(\theta)$ of the approximate safety loss. At first sight, the classic REINFORCE estimator, or its lower-variance refinements, seems suitable for this task, given that they can differentiate an integral over sampled "paths". However, a subtlety in our setting is that the losses for individual paths (symbolic trajectories) is a function of θ. This calls for a generalization of traditional REINFORCE-like estimators.

More precisely, we adapt the derivation of REINFORCE to our setting as follows:

$$
\begin{aligned}
\nabla_\theta(C^\#(\theta)) &= \nabla_\theta \mathbf{E}_{\tau^\# \sim p_\theta(\tau^\#)} Unsafe_\theta(\tau^\#) \\
&= \nabla_\theta \int_{\tau^\# \sim p_\theta(\tau^\#)} p_\theta(\tau^\#) Unsafe_\theta(\tau^\#) d\tau^\# \\
&= \int_{\tau^\# \sim p_\theta(\tau^\#)} p_\theta(\tau^\#) * \nabla_\theta Unsafe_\theta(\tau^\#) + \nabla_\theta p_\theta(\tau^\#) * Unsafe_\theta(\tau^\#) d\tau^\# \\
&= \mathbf{E}_{\tau^\# \sim p_\theta(\tau^\#)}[Unsafe_\theta(\tau^\#) * \nabla_\theta(\log p_\theta(\tau^\#))] + \mathbf{E}_{\tau^\# \sim p_\theta(\tau^\#)}[\nabla_\theta Unsafe_\theta(\tau^\#)]
\end{aligned}
$$

The above derivation can be further refined to incorporate the variance reduction techniques for REINFORCE that are commonly employed in generative modeling and reinforcement learning. The use of such techniques is orthogonal to our main contribution, and we ignore it in this paper.

5 EVALUATION

Our experimental evaluation seeks to to answer the following research questions:

(RQ1): How does DSE compare with the state of the art in its ability to learn safe and performant parameters?

(RQ2): How does data size influence DSE and baselines?

(RQ3): How well does DSE scale as the program being learned gets more complex?

5.1 EXPERIMENTAL SETUP

System Setup. Our framework is built on top of PyTorch (Paszke et al., 2019). We use the Adam Optimizer (Kingma & Ba, 2014) for all the experiments with default parameters and a weight decay of 0.000001. For training and testing of the data loss, we use a batch size of 512. We ran all the experiments using a single-thread implementation on a Linux system with Intel Xeon Gold 5218 2.30GHz CPUs and GeForce RTX 2080 Ti GPUs.

Baselines. We use two types of baselines: (i) *Ablation*, which ignores the safety constraint and learns only from data; (ii) DIFFAI+, an extended version of the original DIFFAI method (Mirman et al., 2018). DIFFAI does not directly fit our setting of neurosymbolic programs as it does not handle general conditional statements. DIFFAI+ extends DIFFAI by adding the meet and join operations following the abstract interpretation framework (Cousot & Cousot, 1977). Notably, the parts of DIFFAI that propagate losses and their gradients through neural networks remain the same in DIFFAI+.

Our implementations of DIFFAI+ and DSE are allowed to split the input set into several initial symbolic states to increase the precision of symbolic execution of each trajectory. Specifically, as there is a join operation for each trajectory in DIFFAI+, DIFFAI+ splits the program's initial condition into hundreds of component initial states (100 if not specified) during experiments to increase the precision. We use the box (interval) domain for both DSE and DIFFAI+ in all the experiments. DSE samples 50 symbolic trajectories for each starting component.

Template	Model	Provably Safe Portion	
		DIFFAI+	DSE
Pattern1	NNSmall	0.0	1.0
	NNMed	0.0	1.0
	NNBig	0.0	1.0
Pattern2	NNSmall	0.0	0.70
	NNMed	0.0	0.78
	NNBig	0.0	0.73
Pattern3	NNSmall	1.0	1.0
	NNMed	1.0	1.0
	NNBig	1.0	1.0
Pattern4	NNSmall	0.0	0.76
	NNMed	0.0	0.80
	NNBig	0.58	0.97
Pattern5	NNSmall	0.0	1.0
	NNMed	0.0	1.0
	NNBig	0.0	1.0

Figure 2: Results of synthetic microbenchmarks of DSE and DIFFAI+.

Benchmarks. Our evaluation uses 5 synthetic microbenchmarks and 3 case studies. The microbenchmarks (Appendix A.5) are small programs consisting of basic neural network modules, arithmetic function assignment and conditional branches and are designed to highlight the relationship between DIFFAI+ and DSE. The case studies, described below, involve more complicated programs (see Appendix A.4 for more details):

- In *Thermostat*, we want to learn safe parameters for two neural networks that control the temperature of a room.
- *Racetrack* is a navigation benchmark (Barto et al., 1995; Christakis et al., 2021). Two vehicles are trained by path planners separately. The racetrack system is expected to learn two safe controllers so that vehicles do not crash into walls or into each other.

(a) Thermostat[Safety] (b) AC[Safety] (c) Racetrack[Safety]

(d) Thermostat[Test Data Loss] (e) AC[Test Data Loss] (f) Racetrack[Test Data Loss]

Figure 3: The provably safe portion and the test data loss of Ablation, DIFFAI+ and DSE when varying the size of the data to train.

- In *Aircraft-Collision*(AC), the goal is to learn safe parameters for an airplane that performs maneuvers to avoid a collision with a second plane.

For each benchmark, we first write a ground-truth program that does not include neural networks and provably satisfies a safety requirement. We identify certain modules of these programs as candidates for learning. Then we replace the modules with neural networks with trainable parameters.

For all benchmarks with the exception of Racetrack, we execute the ground-truth programs on uniformly sampled inputs to collect input-output datasets for each of these modules. As for Racetrack, recall that this benchmark involves two simulated vehicles with neural controllers; learned parameters for these controllers are safe if the vehicles do not crash into each other or a wall. To model real-world navigation, we generate the training data for the controllers from a ground-truth trajectory constructed using a path planner. This path planner only tries to avoid the walls in the map and does not have a representation of distances from other vehicles. Thus, in this problem, even a very large data set does not contain all the information needed for learning safe parameters.

Evaluation of Safety and Data Loss. Once training is over, we expect the learned program to fare well in terms of safety and data loss values. We evaluate the *test data loss* by running the learned program on 10000 initial states that were not seen during training. We evaluate the safety loss using an abstract interpreter (Cousot & Cousot, 1977) that splits the initial condition into 10000 intervals, then constructs symbolic trajectories from these programs. This analysis is sound (unlike the approximate loss employed during DSE training) , meaning that the program is safe if the safety loss evaluates to 0. Our safety metric is the *provably safe portion*, which is the fraction of these 10000 trajectories that are safe.

5.2 RESULTS

RQ1: Overall Quality of Learned Parameters. Figure 2 exhibits the provably safe portion of DIFFAI+ and DSE on our microbenchmarks. Here, the first two patterns only use neural modules in the condition part and the last three benchmarks use the neural modules both in the conditional statement and the assignment statement which is directly related to the final safety representation. We see that DIFFAI+ cannot learn safe highly non-differentiable modules (pattern1, pattern2) while DSE can. For the cases where optimization across branches is not required to give safe programs, DIFFAI+ can handle them (pattern3). For the patterns with neural assignments, DIFFAI+ finds it hard to learn to jump from one conditional branch to another to increase safety (pattern4, pattern5).

(a) Ablation(Final) (b) DIFFAI+ (Final) (c) DSE (Middle) (d) DSE (Final)

(e) Ablation(Final) (f) DIFFAI+ (Final) (g) DSE (Middle) (h) DSE (Final)

(i) Ablation(Final)[pos] (j) DIFFAI+ (Final)[pos] (k) DSE (Middle)[pos] (l) DSE (Final)[pos]

(m) Ablation(Final) [dist] (n) DIFFAI+ (Final) [dist] (o) DSE (Middle) [dist] (p) DSE (Final) [dist]

Figure 4: Trajectories during training. Each row exhibits the concrete trajectories and symbolic trajectories of one case from different methods. From top to bottom, the cases are Thermostat (Figure. 4a, 4b, 4c, 4d), AC (Figure. 4e, 4f, 4g, 4h), Racetrack with position property (Figure. 4i, 4j, 4k, 4p) and distance property (Figure. 4m, 4n, 4o, 4p). Each figure shows the trajectories (concrete: red, symbolic: green) of programs learnt by the method from different training stages, which is denoted by "Middle" and "Final". We separate the input state set into 100 components evenly to plot the symbolic trajectories clearly. During evaluation, we separate the input set into 10000 components evenly to get more accurate symbolic trajectories measurement.

We show the training-time and test-time safety and data losses for our larger benchmarks in Figure 3. From Figure 3a, 3b, 3c, we exhibit that DSE can learn programs with 0.99 provably safe portion even with 200 data points and the results keep when the number of training data points is increased. Meanwhile, both DIFFAI+ and Ablation fail to provide safe programs for AC and Racetrack. For Thermostat, Ablation and DIFFAI+ can achieve a provably safe portion of 0.8 only when using 5000 and 10000 data points to train.

Our test data loss is sometimes larger yet comparable with the Ablation and DIFFAI+ from Figure 3d, 3f. For AC specifically, the safety constraint can help the learner overcome some local optimal yet unsafe areas to get a safer result with more accurate behaviors.

Overall, we find that DSE outperforms DIFFAI+ when neural modules are used in the conditional statement and the interaction between neural modules is important for the safety property. This is the case in our larger benchmarks. For example, in Thermostat and AC, the neural modules' outputs decide the actions that the neural module to take in the next steps. In Racetrack, the distance between two neural modules regulates each step of the vehicles' controllers.

We display representative symbolic trajectories from the programs learned by Ablation, DIFFAI+ and DSE in Figure 4. The larger portion of the symbolic trajectories is provably safe from DSE than the ones from baselines, which is indicated by the less overlapping between the green trajectories and the gray area. Because the symbolic trajectories are overapproximate, we also depict some representative concrete trajectories for each approach. We note that more concrete trajectories of Thermostat, AC, and the distance property of Racetrack from DSE fall into the safe area compared with DIFFAI+ and Ablation.

RQ2: Impact of Data Size. Figure 3 compares the different methods' performance on the test metrics as the number of training data points is changed. The Ablation and DIFFAI+ can reach 0.95 provably safe portion with 10000 data points for Thermostat. However, the variance of results is large, as the minimum provably safe portion across training can reach 0.74 and 0.0 for Ablation and DIFFAI+. In the Thermostat benchmark, DIFFAI+'s performance mainly comes from the guidance from the data loss rather than the safety loss. For the other two cases, a larger training data set cannot help the Ablation and DIFFAI+ to give much safer programs. For AC, as is in Figure 4e, the program learnt from Ablation is very close to the safe area but the Ablation is still not accurate enough to give a safe program in the third step. In Racetrack, increasing the data size to train the vehicles' controllers can only satisfy the requirement of "not crashing into walls". The networks

cannot learn to satisfy the property of not crashing into other vehicles as this information is not available in the training data.

RQ3: Scalability.   As our solution for the safety loss does not rely on the number of data points, the solution is scalable in terms of both data size and neural network size. In Figure 2, we use the three types of neural networks: (i) NNSmall (with about 33000 parameters); (ii) NNMed (with over 0.5 million parameters); (iii) NNBig (with over 2 million parameters), the training time per epoch is 0.09 sec, 0.10sec, 0.11sec for NNSmall, NNMed, NNBig separately. For the synthetic benchmarks, the program can converge within about 200 epochs which takes 18 sec, 20sec, and 22 sec.

Our Thermostat, AC and Racetrack benchmarks consist of neural networks with 4933, 8836 and 4547 parameters respectively, and loops with 20, 15 and 20 iterations respectively. There are 2, 1 and 2 neural modules (respectively) in each benchmark. The training times for DIFFAI+ and DSE are comparable on these benchmarks. Specifically, for Thermostat, AC, and Racetrack, the total training time of DSE is less than 1 hour, less than 90 minutes, and around 13 hours. The corresponding numbers are over 90 minutes, more than 2 hours, and more than 17 hours for DIFFAI+.

6   RELATED WORK

Verification of Neural and Neurosymbolic Models.   There are many recent papers on the verification of worst-case properties of neural networks (Anderson et al., 2019; Gehr et al., 2018; Katz et al., 2017; Elboher et al., 2020; Wang et al., 2018). There are also several recent papers (Ivanov et al., 2019; Tran et al., 2020; Sun et al., 2019; Christakis et al., 2021) on the verification of compositions of neural networks and symbolic systems (for example, plant models). To our knowledge, the present effort is the first to integrate a method of this sort — propagation of worst-case intervals through neurosymbolic program — with the gradient-based training of neurosymbolic programs.

Verified Deep Learning.   There is a growing literature on methods that incorporate worst-case objectives (safety, robustness, or stability) into the training loops of neural networks (Zhang et al., 2019; Mirman et al., 2018; Madry et al., 2017; Cohen et al., 2019; Singh et al., 2018). Most prior work on this topic focuses on the training of single neural networks. There are a few domain-specific efforts that consider the environment of the neural networks being trained. For example, (Shi et al., 2019) uses spectral normalization to constrain the neural network module of a neurosymbolic controller and ensure that it respects certain stability properties. Unlike DSE, the training process in these methods treat the neural network in an isolated way and does not consider the interactions between the neural network modules and surrounding human-written code (Stone et al., 2016; Qin & Badgwell, 2000; Nassi et al., 2020; Katz et al., 2021).

Verified Parameter Synthesis for Symbolic Code.   There is a large body of work on parameter synthesis for traditional symbolic code (Alur et al., 2013; Chaudhuri et al., 2014) with respect to worst-case correctness constraints. However, because these methods do not use contemporary gradient-based learning, scaling them to programs with neural modules is impractical.

7   CONCLUSION

We presented DSE, the first approach to worst-case-safe parameter learning for neurosymbolic programs that embed neural networks inside potentially discontinuous symbol code. Our key innovation is that we design and implement a new way to bridge symbolic execution and stochastic gradient estimator to represent and learn the loss of symbolic properties. We exhibit that DSE outperforms a state-of-the-art approach to worst-case-safe deep learning.

Our current implementation of DSE uses an interval representation of symbolic states. Future work should explore more precise representations such as zonotopes. Incorporating modern variance reduction techniques in our gradient estimator is another natural next step. Finally, one challenge in DSE is that learning here can get harder as the symbolic state representation gets more precise. In particular, if we increase the number of initial symbolic states beyond a point, each state would only lead to a unique symbolic trajectory, and there would be no gradient signal to adjust the relative weights of the different symbolic trajectories. Future work should seek to identify good, possible adaptive, tradeoffs between precision of symbolic states and ease of learning.

REFERENCES

Alekh Agarwal, Alina Beygelzimer, Miroslav Dudík, John Langford, and Hanna Wallach. A reductions approach to fair classification. In *International Conference on Machine Learning*, pp. 60–69. PMLR, 2018.

Aws Albarghouthi. Introduction to neural network verification. *arXiv preprint arXiv:2109.10317*, 2021.

Rajeev Alur, Rastislav Bodik, Garvit Juniwal, Milo MK Martin, Mukund Raghothaman, Sanjit A Seshia, Rishabh Singh, Armando Solar-Lezama, Emina Torlak, and Abhishek Udupa. *Syntax-guided synthesis*. IEEE, 2013.

Greg Anderson, Shankara Pailoor, Isil Dillig, and Swarat Chaudhuri. Optimization and abstraction: a synergistic approach for analyzing neural network robustness. In *Proceedings of the 40th ACM SIGPLAN Conference on Programming Language Design and Implementation*, pp. 731–744, 2019.

Roberto Baldoni, Emilio Coppa, Daniele Cono D'elia, Camil Demetrescu, and Irene Finocchi. A survey of symbolic execution techniques. *ACM Computing Surveys (CSUR)*, 51(3):1–39, 2018.

Andrew G Barto, Steven J Bradtke, and Satinder P Singh. Learning to act using real-time dynamic programming. *Artificial intelligence*, 72(1-2):81–138, 1995.

Swarat Chaudhuri, Martin Clochard, and Armando Solar-Lezama. Bridging boolean and quantitative synthesis using smoothed proof search. In *Proceedings of the 41st ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, pp. 207–220, 2014.

Maria Christakis, Hasan Ferit Eniser, Holger Hermanns, Jörg Hoffmann, Yugesh Kothari, Jianlin Li, Jorge A Navas, and Valentin Wüstholz. Automated safety verification of programs invoking neural networks. In *International Conference on Computer Aided Verification*, pp. 201–224. Springer, 2021.

Jeremy Cohen, Elan Rosenfeld, and Zico Kolter. Certified adversarial robustness via randomized smoothing. In *International Conference on Machine Learning*, pp. 1310–1320. PMLR, 2019.

Patrick Cousot and Radhia Cousot. Abstract interpretation: a unified lattice model for static analysis of programs by construction or approximation of fixpoints. In *Proceedings of the 4th ACM SIGACT-SIGPLAN symposium on Principles of programming languages*, pp. 238–252, 1977.

Yizhak Yisrael Elboher, Justin Gottschlich, and Guy Katz. An abstraction-based framework for neural network verification. In *International Conference on Computer Aided Verification*, pp. 43–65. Springer, 2020.

Yoav Freund and Robert E Schapire. Game theory, on-line prediction and boosting. In *Proceedings of the ninth annual conference on Computational learning theory*, pp. 325–332, 1996.

Yoav Freund and Robert E Schapire. Adaptive game playing using multiplicative weights. *Games and Economic Behavior*, 29(1-2):79–103, 1999.

Timon Gehr, Matthew Mirman, Dana Drachsler-Cohen, Petar Tsankov, Swarat Chaudhuri, and Martin Vechev. Ai2: Safety and robustness certification of neural networks with abstract interpretation. In *2018 IEEE Symposium on Security and Privacy (SP)*, pp. 3–18. IEEE, 2018.

Divya Gopinath, Kaiyuan Wang, Mengshi Zhang, Corina S Pasareanu, and Sarfraz Khurshid. Symbolic execution for deep neural networks. *arXiv preprint arXiv:1807.10439*, 2018.

Radoslav Ivanov, James Weimer, Rajeev Alur, George J Pappas, and Insup Lee. Verisig: verifying safety properties of hybrid systems with neural network controllers. In *Proceedings of the 22nd ACM International Conference on Hybrid Systems: Computation and Control*, pp. 169–178, 2019.

Guy Katz, Clark Barrett, David L Dill, Kyle Julian, and Mykel J Kochenderfer. Reluplex: An efficient smt solver for verifying deep neural networks. In *International Conference on Computer Aided Verification*, pp. 97–117. Springer, 2017.

Michael Katz, Kavitha Srinivas, Shirin Sohrabi, Mark Feblowitz, Octavian Udrea, and Oktie Hassanzadeh. Scenario planning in the wild: A neuro-symbolic approach. *FinPlan 2021*, pp. 15, 2021.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Hoang Le, Cameron Voloshin, and Yisong Yue. Batch policy learning under constraints. In *International Conference on Machine Learning*, pp. 3703–3712. PMLR, 2019.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Zohar Manna and Amir Pnueli. *Temporal verification of reactive systems: safety*. Springer Science & Business Media, 2012.

Matthew Mirman, Timon Gehr, and Martin Vechev. Differentiable abstract interpretation for provably robust neural networks. In *International Conference on Machine Learning*, pp. 3578–3586. PMLR, 2018.

Ben Nassi, Yisroel Mirsky, Dudi Nassi, Raz Ben-Netanel, Oleg Drokin, and Yuval Elovici. Phantom of the adas: Securing advanced driver-assistance systems from split-second phantom attacks. In *Proceedings of the 2020 ACM SIGSAC Conference on Computer and Communications Security*, pp. 293–308, 2020.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019.

S Joe Qin and Thomas A Badgwell. An overview of nonlinear model predictive control applications. *Nonlinear model predictive control*, pp. 369–392, 2000.

Guanya Shi, Xichen Shi, Michael O'Connell, Rose Yu, Kamyar Azizzadenesheli, Animashree Anandkumar, Yisong Yue, and Soon-Jo Chung. Neural lander: Stable drone landing control using learned dynamics. In *2019 International Conference on Robotics and Automation (ICRA)*, pp. 9784–9790. IEEE, 2019.

Gagandeep Singh, Timon Gehr, Matthew Mirman, Markus Püschel, and Martin T Vechev. Fast and effective robustness certification. *NeurIPS*, 1(4):6, 2018.

Peter Stone, Rodney Brooks, Erik Brynjolfsson, Ryan Calo, Oren Etzioni, Greg Hager, Julia Hirschberg, Shivaram Kalyanakrishnan, Ece Kamar, Sarit Kraus, et al. Artificial intelligence and life in 2030: the one hundred year study on artificial intelligence. 2016.

Xiaowu Sun, Haitham Khedr, and Yasser Shoukry. Formal verification of neural network controlled autonomous systems. In *Proceedings of the 22nd ACM International Conference on Hybrid Systems: Computation and Control*, pp. 147–156, 2019.

Hoang-Dung Tran, Xiaodong Yang, Diego Manzanas Lopez, Patrick Musau, Luan Viet Nguyen, Weiming Xiang, Stanley Bak, and Taylor T Johnson. Nnv: The neural network verification tool for deep neural networks and learning-enabled cyber-physical systems. In *International Conference on Computer Aided Verification*, pp. 3–17. Springer, 2020.

Shiqi Wang, Kexin Pei, Justin Whitehouse, Junfeng Yang, and Suman Jana. Formal security analysis of neural networks using symbolic intervals. In *27th {USENIX} Security Symposium ({USENIX} Security 18)*, pp. 1599–1614, 2018.

Huan Zhang, Hongge Chen, Chaowei Xiao, Sven Gowal, Robert Stanforth, Bo Li, Duane Boning, and Cho-Jui Hsieh. Towards stable and efficient training of verifiably robust neural networks. *arXiv preprint arXiv:1906.06316*, 2019.

Algorithm 1: Learning Safe, Optimal Parameter Mixtures (Agarwal et al., 2018; Le et al., 2019)

---

for $t = 1, ..., N$ **do**

    $\theta_t \leftarrow \mathbf{Best}_\theta(\lambda_t)$

    $\hat{\theta}_t \leftarrow \mathbf{Uniform}(\theta_1, \ldots, \theta_t),\ \hat{\lambda}_t \leftarrow \frac{1}{t} \sum \lambda_t$

    $L_{\max} \leftarrow L(\hat{\theta}, \mathbf{Best}_\lambda(\hat{\theta}))$

    $L_{\min} \leftarrow L(\mathbf{Best}_\theta(\hat{\lambda}_t), \hat{\lambda}_t)$

    if $L_{\max} - L_{\min} < \nu$ **then return** $(\hat{\theta}_t, \hat{\lambda}_t)$;

    $\lambda_{t+1} \leftarrow \boldsymbol{\lambda}\textbf{-Update}(\theta_1, \ldots, \theta_t)$

A APPENDIX

A.1 LEARNING FRAMEWORK

We use an equivalence between constrained and regularized learning that (Agarwal et al., 2018; Le et al., 2019), among others, have recently developed in other learning settings, we reduce our problem to a series of unconstrained optimization tasks.

We convexify the program set $\{F_\theta : \theta \in \mathbb{R}^k\}$ by considering stochastic mixtures (Le et al., 2019) and represent the convexified set as a probabilistic function $F_{\hat{\theta}}$. Following DSE, we rewrite Equation 2 in terms of these mixtures:

$$\hat{\theta}^* \quad = \quad \arg\min_{\hat{\theta}} Q(\hat{\theta}) \qquad \text{s.t.}\ \ C^{\#}(\hat{\theta}) \leq 0 \tag{7}$$

We convert Equation 7 to a Lagrangian function

$$L(\hat{\theta}, \lambda) = Q(\hat{\theta}) + \lambda C^{\#}(\hat{\theta}) \tag{8}$$

$$\tag{9}$$

, where $\lambda \in \mathbb{R}^+$ is a *Lagrange multiplier*. Following the equilibrium computation technique by Freund & Schapire (1996), Equation 7 can be rewritten as

$$\max_{\lambda \in \mathbb{R}^+} \min_{\hat{\theta}} L(\hat{\theta}, \lambda). \tag{10}$$

Solutions to this problem can be interpreted as equilibria of a game between a λ-player and a $\hat{\theta}$-player in which the $\hat{\theta}$-player minimizes $L(\hat{\theta}, \lambda)$ given the current λ, and the λ-player maximizes $L(\hat{\theta}, \lambda)$ given the current $\hat{\theta}$. Our overall algorithm is shown in Algorithm 1. In this pseudocode, ν is a predefined positive real. $\mathbf{Uniform}(\theta_1, \ldots, \theta_t)$ is the mixture that selects a θ_i out of $\{\theta_1, \ldots, \theta_t\}$ uniformly at random.

$\mathbf{Best}_\theta(\lambda)$ refers to the $\hat{\theta}$ player's *best response* for a given value of λ (it can be shown that this best response is a single parameter value, rather than a mixture of parameters). Computing this best response amounts to solving the unconstrained optimization problem $\min_\theta L(\theta, \lambda)$, i.e.,

$$\mathbf{Best}_\theta(\lambda) = \min_\theta Q(\theta) + \lambda C^{\#}(\theta). \tag{11}$$

$\mathbf{Best}_\lambda(\hat{\theta})$ is the λ-player's best response to a particular parameter mixture $\hat{\theta}$. We define this function as

$$\mathbf{Best}_\lambda(\hat{\theta}) = \begin{cases} 0 & \text{if } C^{\#}(\hat{\theta}) \leq 0 \\ S & \text{otherwise} \end{cases} \tag{12}$$

where S is the upper bound on λ. Intuitively, when $C^{\#}(\hat{\theta})$ is non-positive, the current parameter mixture is safe. As L is a linear function of λ, the minimum value of L is achieved in this case when λ is zero. For other cases, the minimum L is reached by setting λ to the maximum value S.

Finally, $\boldsymbol{\lambda}\textbf{-Update}(\theta_t)$ computes, in constant time, a new value of λ based on the most recent best response by $\hat{\theta}$ player. We do not describe this function in detail; please see (Agarwal et al., 2018) for more details.

Following prior work, we can show that Algorithm 1 converges to a value $(\hat{\theta}, \hat{\lambda})$ that is within additive distance ν from a saddle point for Equation 10. To solve our original problem (Equation 2),

we take the returned $\hat{\theta}$ and then return the real-valued parameter θ_i to which this mixture assigns the highest probability. It is easy to see that this value is an approximate solution to Equation 2.

A.2 ABSTRACT UPDATE FOR NEURAL NETWORK MODULES

We consider the box domain in the implementation. For a program with m variables, each component in the domain represents a m-dimensional box. Each component of the domain is a pair $b = \langle b_c, b_e \rangle$, where $b_c \in \mathbb{R}^m$ is the center of the box and $b_e \in \mathbb{R}^m_{\geq 0}$ represents the non-negative deviations. The interval concretization of the i-th dimension variable of b is given by

$$[(b_c)_i - (b_e)_i, (b_c)_i + (b_e)_i].$$

Now we give the abstract update for the box domain following Mirman et al. (2018).

Add. For a concrete function f that replaces the i-th element in the input vector $x \in \mathbb{R}^m$ by the sum of the j-th and k-th element:

$$f(x) = (x_1, \ldots, x_{i-1}, x_j + x_k, x_{i+1}, \ldots x_m)^T.$$

The abstraction function of f is given by:

$$f^{\#}(b) = \langle M \cdot b_c, M \cdot b_e \rangle,$$

where $M \in \mathbb{R}^{m \times m}$ can replace the i-th element of x by the sum of the j-th and k-th element by $M \cdot b_c$.

Multiplication. For a concrete function f that multiplies the i-th element in the input vector $x \in \mathbb{R}^m$ by a constant w:

$$f(x) = (x_1, \ldots, x_{i-1}, w \cdot x_i, x_{i+1}, \ldots, x_m)^T.$$

The abstraction function of f is given by:

$$f^{\#}(b) = \langle M_w \cdot b_c, M_{|w|} \cdot b_e \rangle,$$

where $M_w \cdot b_c$ multiplies the i-th element of b_c by w and $M_{|w|} \cdot b_e$ multiplies the i-th element of b_e with $|w|$.

Matrix Multiplication. For a concrete function f that multiplies the input $x \in \mathbb{R}^m$ by a fixed matrix $M \in \mathbb{R}^{m' \times m}$:

$$f(x) = M \cdot x.$$

The abstraction function of f is given by:

$$f^{\#}(b) = \langle M \cdot b_c, |M| \cdot b_e \rangle,$$

where M is an element-wise absolute value operation. Convolutions follow the same approach, as they are also linear operations.

ReLU. For a concrete element-wise ReLU operation over $x \in \mathbb{R}^m$:

$$\text{ReLU}(x) = (\max(x_1, 0), \ldots, \max(x_m, 0))^T,$$

the abstraction function of ReLU is given by:

$$\text{ReLU}^{\#}(b) = \langle \frac{\text{ReLU}(b_c + b_e) + \text{ReLU}(b_c - b_e)}{2}, \frac{\text{ReLU}(b_c + b_e) - \text{ReLU}(b_c - b_e)}{2} \rangle.$$

where $b_c + b_e$ and $b_c - b_e$ denotes the element-wise sum and element-wise subtraction between b_c and b_e.

Sigmoid. As Sigmoid and ReLU are both monotonic functions, the abstraction functions follow the same approach. For a concrete element-wise Sigmoid operation over $x \in \mathbb{R}^m$:

$$\text{Sigmoid}(x) = (\frac{1}{1 + \exp(-x_1)}, \ldots, \frac{1}{1 + \exp(-x_m)})^T,$$

the abstraction function of Sigmoid is given by:

$$\text{Sigmoid}^{\#}(b) = \langle \frac{\text{Sigmoid}(b_c + b_e) + \text{Sigmoid}(b_c - b_e)}{2}, \frac{\text{Sigmoid}(b_c + b_e) - \text{Sigmoid}(b_c - b_e)}{2} \rangle.$$

where $b_c + b_e$ and $b_c - b_e$ denotes the element-wise sum and element-wise subtraction between b_c and b_e. All the above abstract updates can be easily differentiable and parallelized on the GPU.

A.3 Instantiation of the *Unsafe* Function

In general, the $Unsafe(s)$ function over individual states can be any differentiable distance function between a point and a set which satisfies the property that $Unsafe(s) = 0$ if s is in the safe set, $\mathcal{A}$, and $Unsafe(s) > 0$ if s is not in $\mathcal{A}$. We give the following instantiation as the unsafeness score over individual states:

$$Unsafe(s) = \begin{cases} \min_{x \in \mathcal{A}} \text{DIST}(s, x) & \text{if } s \notin \mathcal{A} \\ 0 & \text{if } s \in \mathcal{A} \end{cases}$$

where DIST denotes the euclidean distance between two points.

Similarly, the $Unsafe(\sigma)$ function over symbolic states can be any differentiable distance function between two sets which satisfies the property that $Unsafe(\sigma) = 0$ if V is in $\mathcal{A}$, and $Unsafe(\sigma) > 0$ if V is not in $\mathcal{A}$. We give the following instantiation as a differentiable approximation of the worst-case loss $\max_{s \text{ satisfies } V} Unsafe(s)$ in our implementation:

$$Unsafe(\sigma) = \begin{cases} \min_{s \text{ satisfies } V} Unsafe(s) + 1 & \text{if } V \wedge \mathcal{A} = \emptyset \\ 1 - \frac{\mathbf{Vol}(V \wedge \mathcal{A})}{\mathbf{Vol}(V)} & \text{if } V \wedge \mathcal{A} \neq \emptyset \end{cases}$$

A.4 Benchmarks for Case Studies

The detailed programs describing Aircraft Collision, Thermostat and Racetrack are in Figure 5, 6 and 7. The π_θ of Aircraft Collision and π_θ^{cool}, π_θ^{heat} in Thermostat are a 3 layer feed forward net with 64 nodes in each and a ReLU after each layer except the last one. A sigmoid layer serves as the last layer. Both the $\pi_\theta^{\text{agent1}}$ and $\pi_\theta^{\text{agent2}}$ in Racetrack are a 3 layer feed forward net with 64 nodes in each and a ReLU after each layer.

```
1   aircraftcollision(x):
2       x1, y1 := x, -15.0
3       x2, y2 := 0.0, 0.0
4       steps := 15
5       i = 0
6       while i < steps:
7           p0, p1, p2, p3, step := πθ(x1, y1, x2, y2, step, stage)
8           stage := argmax(p0, p1, p2, p3)
9           if stage == CRUISE:
10              x1, y1 := MOVE_CRUISE(x1, y1)
11          else if stage == LEFT:
12              x1, y1 := MOVE_LEFT(x1, y1)
13          else if stage == STRAIGHT:
14              x1, y1 := MOVE_STRAIGHT(x1, y1)
15          else:
16              x1, y1 := MOVE_RIGHT(x1, y1)
17
18          x2, y2 := MOVE_2(x2, y2)
19          i := i + 1
20          assert (!IS_CRASH(x1, y1, x2, y2))
21      return
```

Figure 5: Aircraft Collision

A.5 Synthetic Microbenchmarks

Figure 8 exhibits the 5 synthetic microbenchmarks in our evaluation. Specifically, the neural network modules are used as conditions in pattern 1 and pattern 2. The neural network modules serve as both conditions and the assignment variable in pattern 3, pattern 4 and pattern 5. To highlight the impact from the safety loss, we only train with safety loss for synthetic microbenchmarks.

```
1   thermostat(x):
2       steps = 20
3       isOn = 0.0
4       i = 0
5       while i < steps:
6           if isOn ≤ 0.5:
7               isOn := π_θ^cool(x)
8               x := COOLING(x)
9           else:
10              isOn, heat := π_θ^heat(x)
11              x := WARMING(x, heat)
12          i := i + 1
13          assert(!EXTREME_TEMPERATURE(x))
14
15      return
```

Figure 6: Thermostat

```
1   racetrack(x):
2       x1, y1, x2, y2 := x, 0.0, x, 0.0
3       steps := 20
4       while i < steps:
5           p10, p11, p12 := π_θ^agent1(x1, y1)
6           p20, p21, p22 := π_θ^agent2(x2, y2)
7           action1 := argmax(p10, p11, p12)
8           action2 := argmax(p20, p21, p22)
9           x1, y1 := MOVE(x1, y1, action1)
10          x2, y2 := MOVE(x2, y2, action2)
11          i := i + 1
12          assert(!CRASH_WALL(x1, y1) && !CRASH_WALL(x2, y2)
13              && !CRASH(x1, y1, x2, y2))
14
15      return
```

Figure 7: Racetrack

A.6 TRAINING PERFORMANCE

Figure 9 illustrates the training performance of safety loss when we use 200 data points to train for DIFFAI + and DSE. We can see that the safety loss of DSE can converge while the variance of the safety loss of DIFFAI + is quite large for these three cases and can not converge to a small safety loss.

```
1  pattern1(x):
2      # x ∈ [-5, 5]
3      y := π_θ(x)
4      if y ≤ 1.0:
5          z := 10
6      else:
7          z: = 1
8      assert(z ≤ 1)
9      return z
```

```
1  pattern2(x):
2      # x ∈ [-5, 5]
3      y := π_θ(x)
4      if y ≤ 1.0:
5          z := x + 10
6      else:
7          z: = x - 5
8      assert(z ≤ 1)
9      return z
```

```
1  pattern3(x):
2      # x ∈ [-5, 5]
3      y := π_θ(x)
4      if y ≤ 1.0:
5          z := 10 - y
6      else:
7          z: = 1
8      assert(z ≤ 1)
9      return z
```

(a) Pattern1   (b) Pattern2   (c) Pattern3

```
1  pattern4(x):
2      # x ∈ [-5, 5]
3      y := π_θ(x)
4      if y ≤ -1.0:
5          z := 1
6      else:
7          z: = 2 + y * y
8      assert(z ≤ 1)
9      return z
```

```
1  pattern5(x):
2      # x ∈ [-1, 1]
3      y := π_θ(x)
4      if y ≤ 1.0:
5          z := y
6      else:
7          z: = -10
8      assert(z ≤ 0 && z ≥ -5)
9      return z
```

(d) Pattern4   (e) Pattern5

Figure 8: Programs for Patterns

(a) Thermostat   (b) Aircraft Collision   (c) Racetrack

Figure 9: Training performance on different benchmarks. The y-axis represents the safety loss $(C^{\#}(\theta))$ and the x-axis gives the number of training epochs.