PARAMETER AVERAGING FOR FEATURE RANKING

ABSTRACT

Neural Networks are known to be sensitive to initialisation. The methods that rely on neural networks for feature ranking are not robust since they can have variations in their ranking when the model is initialized and trained with different random seeds. In this work, we introduce a novel method based on parameter averaging to estimate accurate and robust feature importance in tabular data setting, referred as XTab. We first initialize and train multiple instances of a shallow network (referred as local masks) with *different random seeds* for a downstream task. We then obtain a global mask model by *averaging the parameters* of local masks. We show that although the parameter averaging might result in a global model with higher loss, it still leads to the discovery of the ground-truth feature importance more consistently than an individual model does. We conduct extensive experiments on a variety of synthetic and real-world data, demonstrating that the XTab can be used to obtain the global feature importance that is not sensitive to sub-optimal model initialisation.

1 INTRODUCTION

Neural networks (NNs) have gained wide adaption across many fields and applications. However, one of the major drawback of NNs is their sensitivity to weight initialisation (McMahan et al., 2017). This drawback is not critical for most classification and regression tasks, and is less obvious in applications such as explainability in most computer vision (CV) tasks. The problem is more obvious in settings, in which we pay attention to individual features (e.g., a feature in tabular data, or a pixel in the image) rather than group of features (e.g., a region in the image). And it becomes critical in settings, in which we might need to make costly decisions based the explanation that the model gives for its outcomes. Few such applications include disease diagnosis in clinical setting, drug repurposing in drug discovery, and sub-population discovery for clinical trials, in all of which the discovery of important features is critical. In this work, we investigate the robustness of neural networks to model initialisation in the context of feature ranking, and conduct our experiments in tabular data setting.

The methods developed to explain predictions should ideally be robust to model initialisation. This is especially important to build trust with stakeholders in fields such as healthcare. In this work, we define the "robustness" as one, in which the feature ranking from the model is not sensitive to sub-optimal model initialisation. Some examples of robust models are seen in tree-based approaches such as the random forest (Breiman, 2001) and XGBoost (Chen & Guestrin, 2016), especially when they are used together with methods such as permutation importance. In these methods, each tree is grown by splitting samples on each decision point by using an impurity metric such as Gini index for the classification task. The importance of a feature in a single tree is typically computed by how much splitting on a particular feature reduces the impurity, which is also weighted by the number of samples the node is responsible for. The importance scores of the features are then averaged across all of the trees within the model to get their final scores. It is this averaging that might be one of the reasons why these models are robust and consistent when used for feature ranking. However, we should make a distinction between the robustness of a method and the correctness of its feature ranking as tree-based methods are known to have their shortcomings when estimating the feature importance (Strobl et al., 2007). To get a robust explanation using neural networks, we could use an ensemble approach by training multiple neural network-based models to get feature importance, and use the majority rule to rank them. However, the ranking of features by using the ensemble of models may still not be easy in cases where the same feature(s) get ranked equally likely across different positions by the models. Moreover, the ensemble approach requires us to store all models so that we can use them to explain a prediction at test time, which is not ideal. Instead, in this work, we propose a novel

Figure 1: **Left:** Framework; **a)** Train the models K-times with different random seeds, **b)** Obtain the global mask, **c)** Final training by using global mask (frozen weights) and a new local mask (trained). **Right:** Details of each training instance; **d)** Generating mask from input, **e)** Feature bagging using masked input, **f)** Aggregating the embeddings of the subsets. **E:** Encoder, **M:** Mask, **C:** Classifier.

method, in which we obtain a single global mask model that is based on *averaging the parameters of multiple instances (local masks) of the same model*. We take advantage of the sensitivity of NNs to initialization by initializing and training each local mask *with a different random seed*. We show that although the global model might have a higher loss than an individual model, it ranks features more correctly and consistently, and hence can be used to extract the feature importance.

Our primary contributions in this work are the following: We obtain a global model by averaging the parameters of multiple instances of a *shallow* neural network trained *with different random initialisation* and use it to extract feature importance. The global model obtained in this manner might have a higher loss than any of the individual models (McMahan et al., 2017). We show that although this is true, the global model is still able to discover the ground-truth feature importance more consistently than an individual model does. We also demonstrate that weight regularization such as dropout and weight-clipping can improve the robustness and consistency of the global model. We show that the existing the state of the art (SOTA) methods proposed for feature ranking or selection are not robust to model initialisation. Finally, we provide insights via extensive empirical study of parameter averaging using both synthetic and real tabular datasets.

2 METHOD

Parameter averaging is extensively studied in the context of Federated Learning (McMahan et al., 2017), in which individual models are trained on datasets stored in different devices, and a global model is obtained by averaging individual models in various ways. For example, the naive parameter averaging is shown to give a lower loss on full training set than any individual model trained on a different subset of the data *when the individual models are initialized with same random seed* (McMahan et al., 2017). It is well known that the loss surface for typical neural networks is non-convex (McMahan et al., 2017) and, hence, averaging parameters of models could result in a sub-optimal global model, especially when their parameters are initialised differently. However, the loss surfaces of over-parameterized NNs are shown to be well behaved and less prone to bad local minima in practice (Choromanska et al., 2015; Dauphin et al., 2014; Goodfellow et al., 2014). In light of these observations, we investigate settings, in which we can combine multiple models *that are initialized and trained with different random seeds* to obtain a global model that is less sensitive to sub-optimal initialisation of any individual model. So, in this work, we propose a framework to obtain such a global model that can be used for both feature ranking and selection. We show that global model is able to extract feature importance correctly and consistently especially *when the network architecture is shallow*. We also show that this behaviour breaks down for deep architectures although regularizing their weights still helps improve them.

2.1 TRAINING

Figure 1 shows our framework, in which we use a shallow neural network as mask generator that in turn is used to learn important features and their weights for a downstream task. In this work, without the loss of generality, we use the classification task for the experiments as shown in Figure 1 (right).

High-level overview: A mask generator, an encoder and a classifier are trained K times using the same training set. K training runs can be parallelized in a distributed setting, or can be run in series on the same machine. At the beginning of each run, we change the random seed before initialising all models (i.e. mask, encoder, and classifier) using Kaiming He uniform initialization (He et al., 2015) with the gain of $\sqrt{5}$ for linear layers. At the end of each training run, we keep the learned weights of the mask model referred as the *local* mask. So we have K different set of weights for the same mask model at the end of K runs. Then, we average the parameters of K local mask models to obtain the weights of the global mask model. In Section 3.4, we show that the global mask is good at extracting feature importance, but it can be sub-optimal for the classification task since it has a higher loss than an individual model as shown in Figure 5. Thus, we initialise and train the models one final time, during which we combine the output of global mask model (weights frozen) with the one from a local mask (trained). The local mask is trained to gain back any potential loss in classification performance. We should note that one can also choose to fine-tune the global mask, but we prefer to use it as a reference to improve on in the final training.

Training to obtain a local mask: We train a local mask generator, a classifier and an encoder for a downstream task. Mask generator, M_l, gets data X, and generates a mask $m = m_l$. We then mask the input X by using an entry-wise multiplication with m^2 to generate a masked input X_M. We use m^2 instead of m to push low values in m towards zero. In our experiments, we observed that using m^2 works better than m.

$$m = M_l(X), \text{ and } X_M = m^2 \odot X \tag{1}$$

Inspired by the proposal for subsetting features in SubTab (Ucar et al., 2021), we then generate subsets of data by dividing the features of X_M: $x_i, x_j, x_k, \cdots = generate\_subsets(X_M)$. Learning from subsets of features is shown to be effective in learning good representations for downstream tasks such as classification while enabling parameter sharing between the features of the tabular data (Ucar et al., 2021). We also add noise to randomly selected features in each subset since we observe that adding noise improves classification performance and the robustness of feature ranking as discussed in Section J of the Appendix. To add noise, we first generate a binomial mask, β, and a noise matrix, ϵ, both of which have the same shape as the subsets, and are re-sampled for each subset. The entries of the mask are assigned to 1 with probability p, and to 0 otherwise. As an example, the corrupted version, x_{ic} of subset x_i is generated as following:

$$x_{ic} = (1 - \beta) \odot x_i + \beta \odot \epsilon, \quad \text{where } i \in \{1, 2, ...\}. \tag{2}$$

Please note that different noise types can be used to generate ϵ. In this paper, we mainly experiment with Gaussian noise, $\mathcal{N}(0, \sigma^2)$, except for SynRank100 dataset, for which we use swap noise (Ucar et al., 2021). The encoder takes each of the corrupted subsets $\{x_{ic}, x_{jc}, x_{kc}, ...\}$, and projects them up to generate corresponding embeddings, $\{h_i, h_j, h_k, ...\}$. As in SubTab (Ucar et al., 2021), we aggregate the embeddings by using mean aggregation to get the joint embedding, h, as shown in Figure 1. Finally, the classifier makes a prediction using the joint embedding h. We minimize the total loss by using the objective function in Equation 3 that consists of two loss functions; i) Cross entropy for the classification task (Equation 4), ii) Mask loss consisting of Gini index and an extra term taking the mean over the entries of the generated mask to induce sparsity (Equation 5):

$$\mathcal{L}_{total} = \mathcal{L}_{task} + \mathcal{L}_{mask} \tag{3}$$

$$\mathcal{L}_{task} = \frac{1}{N} \sum_{i=1}^{N} -y_i * log(\hat{y}_i) - (1 - y_i) * log(1 - \hat{y}_i) \tag{4}$$

$$\mathcal{L}_{mask} = \frac{1}{N} \sum_{i=1}^{N} \frac{1}{D} \sum_{j=1}^{D} g_{ij} + \frac{1}{N} \sum_{i=1}^{N} \frac{1}{D} \sum_{j=1}^{D} m_{ij}, \quad \text{where } g = 1 - m^2 - (1 - m)^2 \tag{5}$$

We update the parameters of the local mask, encoder, and classifier using the total loss (Equation 3). At the end of each k^{th} training run, we collect the parameters of the local mask, M_{l_k}.

Final training: Once the K training runs are completed, we obtain a global mask model by averaging the parameters of K individual local masks as shown in Equation 6:

$$\boldsymbol{M_g} = \frac{1}{K} \sum_{k=1}^{K} \boldsymbol{M_{l_k}} \qquad (6)$$

where $\boldsymbol{M_{l_k}}$ is the local mask generator collected at k^{th} run, and $\boldsymbol{M_g}$ is the global mask. $\boldsymbol{M_g}$ might give sub-optimal performance in downstream task since it is shown to result in higher loss than a local mask model (Section 3.4). But, we do not want to lose the benefits that come with averaging the parameters in $\boldsymbol{M_g}$ by fine-tuning it. So, to avoid the potential degradation in performance, we do one final training. We change the random seed, and initialize all the models. In this step, we don't train the global mask, but rather train a new local mask together with the encoder and classifier as before. However, the difference from the previous training instances is that the mask used for masking the input data is obtained by summing the output of global mask (with frozen weights) and local mask (being trained), followed by scaling this output to make sure that the maximum entry in the mask is 1 as shown in Equations 7, and 8:

$$m_g = M_g(\boldsymbol{X}) \text{ and } m_l = M_l(\boldsymbol{X}) \qquad (7)$$
$$m_f = (m_g + m_l)/C \text{ where } C = max(m_g + m_l) \text{ and } \boldsymbol{X_M} = m_f{}^2 \odot \boldsymbol{X}. \qquad (8)$$

We should note that C is a scaler, i.e. maximum entry in $m_g + m_l$ sum. We use the same loss functions described in equations 3, 4 and 5 to update the parameters of the local mask, encoder and classifier. We should note that m_f can be computed in various ways such as using a gating mechanism similar to input and forget gates in LSTMs (Hochreiter & Schmidhuber, 1997). We can also choose to keep updating $\boldsymbol{M_g}$ in a sequential manner rather than averaging parameters of multiple models all at once. We leave these ideas as future work. Our method is summarized in the Algorithms 1 and 2 in the Appendix.

2.2 TEST TIME

At test time, we use $\boldsymbol{m_g}$ shown in Equations 7 to infer the feature importance. $\boldsymbol{m_g}$ is shown to give a robust global ranking of features in our experiments. In XTab, the importance score for a feature is the mask weight in the final generated mask. The mask weight indicates the feature's relative importance, and we rank the features based on their mask weights. We extract the global feature importances for test set by getting mask values for all samples and computing the mean values over the samples for each feature:

$$\hat{\boldsymbol{f}_i} = M_g(\boldsymbol{x_i}) \text{ and } \hat{\boldsymbol{F}} = \frac{1}{N} \sum_{i=1}^{N} \hat{\boldsymbol{f}_i}, \qquad (9)$$

where $\hat{\boldsymbol{f_i}} \in R^d$ represents mask weights (i.e. feature importance) for the d number of features in sample $\boldsymbol{x_i} \in R^d$, hence $\hat{\boldsymbol{f_i}}$ gives an instance-wise feature importance for i^{th} sample. $\hat{\boldsymbol{F}} \in R^d$ gives the mean of mask weights over N samples and we use it when computing the global feature importance. Finally, when ranking the categorical features, we can rank individual one-hot encoded features to show importance of each sub-category. We can also sum the weights of each one-hot encoded feature to get the overall weight for the parent category. We use both in our experiments when comparing our method to other methods in Sections J.4 and J.5 of the Appendix.

3 EXPERIMENTS

We conduct extensive experiments on diverse set of tabular datasets including six syntetic datasets as well as real world datasets such as UCI Adult Income (Income) (Kohavi, 1996), and UCI BlogFeed-back (Blog) (Buza, 2014). We conduct our initial experiments on synthetic datasets since their ground-truth important features are known. We also compare global feature rankings obtained by the proposed method for synthetic datasets to those given by some of the popular methods such as permutation feature importance used together with random forest (Breiman, 2001) and gradient boosting

classifier (Pedregosa et al., 2011) as well as recently published neural network-based methods such as Invase (Yoon et al., 2018), L2X (Chen et al., 2018), TabNet (Arık & Pfister, 2021), Saliency Maps (Simonyan et al., 2013), and Integrated Gradients (Sundararajan et al., 2017). In our framework, we use a shallow, overcomplete encoder architecture with 1024 units in hidden layer and leakyReLU as activation function for all datasets (Ucar et al., 2021). The summary of model architectures and hyper-parameters such as the number of subsets, the percentage of features shared between subsets, masking ratio, noise variance etc. is in Section C.1 and Table A1 in the Appendix. We report the detailed results on Income and Blog datasets in Sections J and K while additional experiments using synthetic datasets from L2X (Chen et al., 2018) are in Sections I of the Appendix respectively.

3.1 DATA

SynRank dataset: We generate a synthetic dataset, referred as SynRank, consisting of training and test sets with 10k samples each for a binary classification to evaluate whether our method can rank important features in correct order. We first generate data $\boldsymbol{X}$ from 10-dimensional standard Gaussian with no correlations across the features $\mathcal{N}(\boldsymbol{0}, \boldsymbol{I})$. We then shift the sixth feature , f_6, to be centered around -10 for the first 45% of samples. For the next 35% of the samples, we shift the first feature f_1 to be centered around 10. The remaining 20% of the samples are kept same as is. We generate the label $\boldsymbol{Y}$ by sampling it as a Bernoulli random variable with $P(Y = 1|\boldsymbol{X}) = 1/(1 + g(\boldsymbol{X}))$. In this case, $g(\boldsymbol{X})$ is defined as $exp(f_6)$, $exp(f_1)$ and $exp(f_2)$ for the 45%, 35% and 20% of the samples respectively. So the first 45% and 35% of the samples will be labeled as 1 and 0 with a high probability, respectively. For the remaining 20% samples, we can expect the proportions of class labels to be similar since f_2 is from a standard Gaussian with $\mu = 0$. Based on this dataset, we expect that our method discovers the global feature importance ranking as $f_6 > f_1 > f_2$.

SynRank100 dataset: This dataset is same as the SynRank, but it has 100 features instead of 10. The features f_{100}, f_1, and f_{75} are the equivalents of f_6, f_1, f_2 in SynRank respectively, and hence the feature ranking is $f_{100} > f_1 > f_{75}$ while the remaining 97 features are uninformative.

Income: Income is a public dataset based on the 1994 Census database (Kohavi, 1996). It is used for a classification task of predicting whether the income of a person exceeds $50K/yr by using heterogeneous features such as age, gender, education level and so on. It contains 32.5k and 16k samples for training and test sets respectively. The dataset has 14 attributes consisting of 8 categorical and 6 continuous features. We dropped the rows with missing values, and encoded categorical features using one-hot encoding. Once we encode the categorical features as one-hot, we end up with 105 features in total.

BlogFeedback: Referred as Blog in this work, it is a UCI dataset (Dua & Graff, 2017) and contains the number of comments in the upcoming 24 hours for blog posts. It includes 281 variables consisting of 280 integer and real valued features and 1 target variable indicating the number of comments a blog post received in the next 24 hours relative to the basetime. We converted the target to a binary variable to use the data for a classification task of predicting whether there is a comment for a post.

The more details on Income, Blog and the synthetic datasets from L2X (Chen et al., 2018) are added in Section B of the Appendix.

3.2 COMPARING GLOBAL MODEL TO LOCAL MODELS

We start our experiments with the classification task on SynRank dataset to get insights into how parameter averaging works for extracting feature importance[1] as shown in Figure 2. The results for L2X datasets (Chen et al., 2018) can be found in Section G while the details on hyperparameters such as p used for generating the binomial mask, β, and the variance of Gaussian noise, $\epsilon \sim \mathcal{N}(0, \sigma^2)$, can be found in Section C.1 of the Appendix. We train our models on the whole training set for the downstream task 10 times, each time with *a different random seed*. We store the parameters of the trained masks, referred as local masks, from each training and denote them as $\{M_{l_1}, M_{l_2}, \ldots, M_{l_{10}}\}$. We examine the feature importance obtained from each of 10 local masks for the test set (Figure 2a). We observe that each local mask gives a slightly different ranking. More specifically, we could have different ranking, depending on which seed is used when training the models. The main reason for this variation is the model initialisation since everything else are kept same across local models. We

---

[1]Unless specified otherwise, when we say feature importance, we refer to global feature importance.

(a)   (b)   (c)

Figure 2: **SynRank dataset: a)** Feature rankings from each of 10 local masks M_{l_k}, referred as l_k in the figure, obtained at a particular training run for 10 separate runs. **b)** Feature rankings from the global model, obtained by averaging the parameters of individual models up to a specific run i.e. cumulative average (CA). For example, g_3 corresponds to the global model obtained by averaging the parameters of first 3 local masks (l_1, l_2, l_3). **c)** The feature importance weights from M_g obtained by averaging the parameters of all local masks.

then evaluate the effect of averaging over the parameters of the local masks on feature ranking in a progressive way. To do this, we obtain a global mask M_{g_k} as a cumulative average (CA) over the k local masks, i.e. $M_{g_k} = 1/k \sum_{i=1}^{k} M_{l_k}$ as shown in Figure 2b. For example, M_{g_3} corresponds to averaging the parameters of the first three local masks i.e., $M_{l_1}, M_{l_2}, M_{l_3}$ shown in Figure 2a. We refer to $M_{g_{10}}$ as M_g for simplicity in the rest of the paper. We can see that the feature ranking becomes more stable as we use more local masks in the parameter averaging to obtain the global mask model (Figure 2b).

3.3 EVALUATING THE CORRECTNESS OF FEATURE RANKING

Figure 2c shows the feature weights obtained from $M_g = M_{g_{10}}$. We first note that the weights of the features are correlated with the frequency and position of their ranks across all local masks. Specifically, f_6 is ranked a little higher on average than f_1 is (since f_1 occasionally takes 3^{rd} rank). Hence, M_g correctly gives f_6 a little more weight than f_1 and suggests f_2 as the 3^{rd} most important feature as shown in Figure 2c. Similar observations can be made using the results for L2X datasets in Section G of the Appendix. Moreover, we investigate the instance-wise feature importance for XTab. Since we optimize our models using a global objective function (Equation 3), we expect M_g to be biased towards globally important features when estimating the feature importance for an individual sample as confirmed in Section E.1 of the Appendix.

3.4 THE ROBUSTNESS AND CONSISTENCY OF PARAMETER AVERAGING

We compare the robustness and consistency of the global feature importance extracted from various methods by running each method 10 times with different random seeds on SynRank dataset in Table 1. XTab discovers the top three features as "$f_6 > f_1 > f_2$" consistently. This ranking is same as the one obtained by using permutation importance on random forest and gradient boosting classifier, two of the most commonly used models. However, the rankings from TabNet (Arık & Pfister, 2021), Invase (Yoon et al., 2018), L2X (Chen et al., 2018) and Saliency Maps (Simonyan et al., 2013) are not robust to initialisation although they perform well in terms of accuracy. For example, TabNet sometimes confuses the ranking of the important features (e.g., Run# 1, 2 and 8), or ranks uninformative features such as f_3 and f_8 as important (Run# 5, 6, 7). Similar observations can be made for other models (incorrect rankings shown in bold), indicating their susceptibility to model initialisation. Please note that Invase and L2X are originally proposed as feature selection methods, and that we use the feature-selection probabilities and the number of times a feature is selected across all test samples when computing the rankings for Invase and L2X, respectively. In our experiments with other datasets, we observe that the gradient-based approaches such as Saliency Maps (Simonyan et al., 2013) and IG (Sundararajan et al., 2017) give more consistent rankings across multiple runs compared to the ones that explicitly generate a mask for feature selection, or ranking (e.g., TabNet (Arık & Pfister, 2021), Invase (Yoon et al., 2018)). The details of the training for other models as well as the comparison of

the ranking results for L2X Nonlinear Additive and Switch datasets can be found in Sections C and I of the Appendix, respectively.

The effect of weight regularization on the robustness. We run additional experiments on SynRank under three conditions: We apply i) No weight regularization to the weights of the mask model i.e., our original setting so far, ii) Dropout with $p = 0.2$ for the layers with leaky ReLU activation, iii) Weight-clipping ($[-0.2, 0.2]$) to limit the magnitude of the weights in each layer. For each of the three cases, we train 20 separate models and compare two different settings. In the first setting, we compute the variation in the feature rankings given by 20 local mask models (top row in Figure 3a-c). In the second setting, we obtain 100 global models, each of which is obtained by averaging the parameters of 10 local models *bootstrapped* from 20 models. We compare the variation in feature rankings given by global models (second setting – bottom row in Figure 3a-c) to that of 20 local models (first setting – top row). We observe that: i) Regularization methods such as dropout and weight-clipping has a little effect in improving the variation across 20 local models (e.g., comparing f_1, f_2 and f_6 across three cases at the top row). ii) Similarly, they do not improve the robustness of the parameter averaging significantly (e.g., comparing same features across three cases at the bottom row). iii) Parameter averaging results in more robust estimation of feature rankings (comparing top and bottom rows). Overall, the global models are able to discover important features in the correct order (e.g., $f6 > f1 > f2$), and the variation in feature ranking across global models is small (almost zero) for ground truth important features (e.g., f_1, f_2 and f_6 at the bottom row in Figure 3c). We should note that we conduct the same experiment for SynRank100 (Figure 3d), L2X Switch, Income, and Blog datasets, for the latter three of which the weight regularization helps improve robustness of parameter averaging (Figures A7, A17, and A21 in the Appendix respectively). Thus, the weight regularization can help improve the robustness and weight-clipping works better than dropout

Table 1: Comparison of feature ranking obtained from 10 runs of different methods for SynRank. Expected ranking is **f6**>**f1**>**f2**, and incorrect rankings are shown in bold.

					SynRank dataset						
			Ranking from XTab (no weight regularization is used)								
Runs	1	2	3	4	5	6	7	8	9	10	Test Acc.
1	f6	f1	f2	f9	f5	f4	f3	f8	f7	f10	0.9971
2	f6	f1	f2	f9	f5	f3	f8	f4	f7	f10	0.9965
3	f6	f1	f2	f5	f9	f3	f4	f8	f7	f10	0.9969
4	f6	f1	f2	f9	f5	f4	f3	f8	f7	f10	0.9951
5	f6	f1	f2	f9	f5	f4	f3	f8	f10	f7	0.9955
6	f6	f1	f2	f5	f9	f3	f4	f8	f7	f10	0.9972
7	f6	f1	f2	f9	f5	f3	f4	f8	f10	f7	0.9964
8	f6	f1	f2	f5	f9	f4	f3	f8	f7	f10	0.9964
9	f6	f1	f2	f5	f9	f4	f3	f8	f7	f10	0.9971
10	f6	f1	f2	f9	f5	f3	f4	f8	f7	f10	0.9973
			Rankings from GBCP & RFP								
GBCP	f6	f1	f2	f10	f9	f8	f7	f5	f4	f3	0.9996
RFP	f6	f1	f2	f10	f9	f8	f7	f5	f4	f3	0.9999
			Rankings from TabNet								
1	**f1**	**f6**	**f2**	f5	f8	f7	f9	f10	f4	f3	0.9990
2	**f1**	**f6**	**f2**	f8	f7	f3	f10	f5	f4	f9	0.9988
3	f6	f1	f2	f10	f9	f3	f5	f8	f4	f7	0.9980
4	f6	f1	f2	f4	f7	f10	f9	f5	f3	f8	0.9978
5	**f6**	**f1**	**f8**	f2	f3	f10	f9	f4	f5	f7	0.9984
6	**f6**	**f1**	**f3**	f2	f4	f8	f10	f5	f9	f7	0.9988
7	**f6**	**f1**	**f3**	f2	f7	f9	f10	f8	f5	f4	0.9999
8	**f1**	**f2**	**f6**	f8	f9	f7	f10	f3	f4	f5	0.9963
9	f6	f1	f2	f9	f5	f8	f10	f4	f7	f3	0.9995
10	f6	f1	f2	f7	f3	f5	f10	f4	f8	f9	0.9979
			Rankings from Invase								
1	**f1**	**f6**	**f2**	f5	f8	f3	f10	f9	f4	f7	0.9988
2	**f1**	**f6**	**f2**	f5	f9	f4	f10	f3	f7	f8	0.9989
3	**f1**	**f6**	**f2**	f3	f8	f4	f5	f9	f7	f10	0.9989
4	f6	f1	f2	f7	f8	f4	f10	f9	f5	f3	0.9986
5	f6	f1	f2	f4	f5	f8	f10	f7	f9	f3	0.9989
6	**f1**	**f6**	**f2**	f3	f7	f4	f8	f9	f10	f5	0.9992
7	**f1**	**f6**	**f2**	f9	f7	f4	f5	f10	f8	f3	0.9985
8	**f1**	**f6**	**f2**	f4	f5	f9	f3	f7	f10	f8	0.9993
9	**f1**	**f6**	**f2**	f10	f3	f5	f7	f8	f4	f9	0.9996
10	f6	f1	f2	f4	f3	f5	f8	f9	f10	f7	0.9991
			Rankings from L2X								
1	**f1**	**f2**	**f6**	f5	f3	f4	f7	f8	f9	f10	0.9977
2	**f1**	**f2**	**f6**	f3	f5	f10	f4	f7	f8	f9	0.9983
3	**f1**	**f2**	**f6**	f4	f10	f3	f9	f5	f7	f8	0.9969
4	**f1**	**f2**	**f6**	f3	f5	f10	f4	f7	f8	f9	0.9975
5	**f1**	**f2**	**f6**	f3	f5	f7	f4	f8	f9	f10	0.9976
6	**f1**	**f6**	**f2**	f3	f4	f5	f7	f8	f9	f10	0.9978
7	**f1**	**f2**	**f6**	f5	f3	f4	f7	f8	f9	f10	0.9985
8	**f1**	**f2**	**f6**	f3	f5	f8	f4	f7	f9	f10	0.9976
9	**f1**	**f6**	**f2**	f4	f10	f8	f5	f3	f7	f9	0.9984
10	**f1**	**f2**	**f6**	f3	f5	f8	f4	f7	f9	f10	0.9979
			Rankings from Saliency Maps								
1	f6	f1	f2	f5	f4	f7	f3	f9	f10	f8	0.9817
2	**f1**	**f6**	**f2**	f10	f3	f5	f7	f8	f4	f9	0.9820
3	**f1**	**f6**	**f2**	f10	f3	f8	f7	f9	f5	f4	0.9816
4	f6	f1	f2	f10	f8	f4	f5	f3	f7	f9	0.9824
5	**f1**	**f6**	**f2**	f9	f8	f3	f10	f5	f7	f4	0.9812
6	f6	f1	f2	f3	f5	f8	f7	f4	f9	f10	0.9817
7	**f1**	**f6**	**f2**	f5	f7	f4	f9	f3	f10	f8	0.9814
8	**f1**	**f6**	**f2**	f5	f10	f3	f4	f8	f7	f9	0.9817
9	f6	f1	f2	f8	f5	f10	f7	f9	f3	f4	0.9821
10	f6	f1	f2	f3	f8	f7	f5	f10	f4	f9	0.9813

in our experiments. We also observe that the parameter averaging itself pushes the magnitude of the weights towards a tight range around zero as shown in Figure A8 (Section H.1 of the Appendix), indicating a potential relationship between robustness and a tighter weight distribution.

Exploring the mask generator with deeper architecture. We re-run the robustness experiments by replacing the shallow mask model with a deeper model (5 hidden layers) and show that the weight regularization also helps with the robustness of parameter averaging in deeper networks although the parameter averaging does not work as well as the shallow networks especially if weight regularization is not used (see Figure A15(f) for Income dataset in the Appendix). Additional results for SynRank, L2X Switch, and Income can be found in Section E.3, H.2 and J.3 of the Appendix respectively.

Comparing the loss and solution space of local and global models. We consider two sets of parameters: θ_l for a local model and θ_g for the global model. We can compare the possible loss and solution space by interpolating from local to the global model: $\theta^* = (1 - \alpha) * \theta_l + \alpha * \theta_g$, where α is swept from 0 to 1 in 50 steps. Figure 5a-b shows two separate examples of such interpolation done using SynRank dataset. In Figure 5a, the local model ($\alpha = 0$) has the wrong feature ranking of $f1 > f6 > f2$. As we move from local model ($\alpha = 0$) to the global model ($\alpha = 1$), the estimate

| (a) No regularization | (b) Dropout (p=0.2) | (c) Weight-clipping (WC) | (d) WC - SynRank100 |

Figure 3: **SynRank and SynRank100 datasets:** The important features are $f_6 > f_1 > f_2$ and $f_{100} > f_1 > f_{75}$ for SynRank and SynRank100 respectively while the rest of the features is not informative. **Top row:** Variations in feature rankings across 20 local mask models when we apply **a)** no weight regularization, **b)** Dropout ($p = 0.2$), and **c)** Weight-clipping ($[-0.2, 0.2]$) for SynRank dataset. **Bottom row**: Variations in feature rankings in 100 global models, each of which is obtained by averaging the parameters of 10 models bootstrapped from 20 local models for the same three cases. **d)** Same as **(c)** i.e. weight-clipping (WC), but the experiment is repeated for SynRank100 dataset.

| (a) Income-Local | (b) Income-Global | (c) Blog-Local | (d) Blog-Global |

Figure 4: **Income and Blog datasets:** Repeat of the experiment in Figure 3c for Income and Blog, showing variations in feature rankings across 20 local mask models in **(a)** and **(c)** as well as variations across 100 global models in **(b)** and **(d)** (Please see Section J.3 and K.1 for more results). Abbreviations used for features in Income are; **ms:** marital status, **en:** education-num, **cg:** capital-gain, **hpw:** hours-per-week, **occ:** occupation, **rel:** relationship, **cl:** capital-loss, **nc:** native-country.

of feature ranking gets better. The global model estimates the ranking correctly ($f6 > f1 > f2$). Similarly, in Figure 5b, a different local model has the wrong feature ranking of $f6 > f2 > f1$ while the global model again gives the correct ranking. Moreover, for SynRank, the expected global feature importance weights are $\boldsymbol{F} = [\boldsymbol{F_1}, \boldsymbol{F_2}, ..., \boldsymbol{F_6}, ..., \boldsymbol{F_{10}}] = [0.35, 0.2, 0, ..., 0.45, ..., 0]$. So, we can compute the loss of the mask model by using mean squared error between expected weights and the model's estimate: $\mathcal{L} = \frac{1}{10} \sum_{d=1}^{10} (\boldsymbol{F_d} - \hat{\boldsymbol{F}}_d)^2$, where $\hat{\boldsymbol{F}}$ is defined in Equation 9. Thus, we plot how this loss changes as we interpolate from local to global model in Figure 5c, which corresponds to the interpolations in Figure 5a-b. It indicates that the loss increases as we move towards the global model, which is mainly due to the fact that the noise floor (**nf**) increases in both cases as shown in Figure 5a-b and that the weight of $f6$ moves away from 0.45 in the case of Figure 5b. Averaging parameters of the multiple models with different initialisation is known to give a global model that might have a higher loss than any of the local models (McMahan et al., 2017). However, we show that the global model is still better at estimating feature ranking and more robust than the local models.

4 RELATED WORKS

Parameter averaging Averaging parameters to get a global model has been extensively studied in the Federated Learning setting under different assumptions; i) The convex optimisation under IID

(a)   (b)   (c)

Figure 5: **SynRank: (a-b)**: Two examples showing the changes in the weights of features estimated by a model that is obtained by interpolating between a single local model and the global model: $\theta^* = (1 - \alpha) * \theta_l + \alpha * \theta_g$. As we move from local model ($\alpha = 0$) to the global model ($\alpha = 1$), the estimate of feature ranking gets better (i.e., $f6 > f1 > f2$) even though the loss of the model gets worse as shown in **(c)**. **nf:** Noise floor, referring to average weight of the rest of the uninformative features i.e., $f3 - f5, f7 - f10$. The plots show the mean and 95% confidence intervals computed by repeating the experiments with 100 global models, each of which is obtained by bootstrapping 10 out of 20 local models. In (a-b), global models are interpolated with two different local models.

data assumption, in which it is shown that the global model is no better than a single model in the worst-case (Arjevani & Shamir, 2015; Zinkevich et al., 2010; Zhang et al., 2012). ii) The non-convex optimisation under IID and non-IID data assumptions, in which individual models are initialized from *the same random initialization* to avoid bad local minima before training each independently (McMahan et al., 2017). Parameter averaging using models with same initialisation is studied under different contexts as well (Wortsman et al., 2022; Polyak & Juditsky, 1992; Izmailov et al., 2018). In Wortsman et al. (2022), the authors average the parameters of multiple models, each of which is obtained by fine-tuning a pre-trained model by using different hyper-parameters. In this case, the fine-tuning process starts from the same initial model i.e., pre-trained model. The parameter averaging in (Polyak & Juditsky, 1992; Izmailov et al., 2018) is done by averaging the parameters of the same model along the trajectory of stochastic optimisation during the training. Moreover, dropout method is previously shown to approximate model averaging implicitly (Srivastava et al., 2014; Goodfellow et al., 2013). However, we show that the dropout alone is not enough to achieve robustness in Section 3.4. In this work, we study non-convex setting under the IID assumption, and consider averaging model parameters obtained across multiple training runs to produce the final global model. What differentiates our method from aforementioned works is that we initialise the models with *different random seeds*. Although averaging the parameters of the models trained with *different random seeds* is shown to lead to a bad local minima (McMahan et al., 2017), we show that the global model obtained in this way gives a robust estimate of the feature importance and can be used for feature ranking. We review other related works in Section D of the Appendix.

5 CONCLUSION

In this work, we show that a global model obtained by averaging the parameters of multiple instances of a shallow network trained with different random seeds can be used to estimate global feature importance and that its estimates are not sensitive to sub-optimal initialisation of individual models. Furthermore, regularization methods can enhance the robustness of parameter averaging. We give insights into how parameter averaging can be useful for feature ranking through extensive experiments using synthetic and real tabular datasets. Our method can also be extended to other modalities such as images, graph etc. and we leave it as a future work. Finally, the following are some of the shortcomings of our approach; i) The global model is biased towards globally important features and hence instance-wise feature importance will be biased, ii) We still need to do hyper-parameter search for feature bagging, noise etc., iii) The features in the real world datasets can have more intricate relationships such as multicollinearity, making the ranking of the features difficult, in which case our method can be used for feature selection rather than feature ranking, and iv) Our method needs additional compute during training, but this can be eliminated by integrating our method into K-fold cross validation, assuming $K \geq 10$.

REFERENCES

Sercan O Arık and Tomas Pfister. Tabnet: Attentive interpretable tabular learning. In *AAAI*, volume 35, pp. 6679–6687, 2021.

Yossi Arjevani and Ohad Shamir. Communication complexity of distributed convex learning and optimization. *Advances in neural information processing systems*, 28, 2015.

Leo Breiman. Random forests. *Machine learning*, 45(1):5–32, 2001.

Krisztian Buza. Feedback prediction for blogs. In *Data analysis, machine learning and knowledge discovery*, pp. 145–152. Springer, 2014.

Jianbo Chen, Le Song, Martin Wainwright, and Michael Jordan. Learning to explain: An information-theoretic perspective on model interpretation. In *International Conference on Machine Learning*, pp. 883–892. PMLR, 2018.

Tianqi Chen and Carlos Guestrin. XGBoost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '16, pp. 785–794, New York, NY, USA, 2016. ACM. ISBN 978-1-4503-4232-2. doi: 10.1145/2939672.2939785. URL http://doi.acm.org/10.1145/2939672.2939785.

Anna Choromanska, Mikael Henaff, Michael Mathieu, Gérard Ben Arous, and Yann LeCun. The loss surfaces of multilayer networks. In *Artificial intelligence and statistics*, pp. 192–204. PMLR, 2015.

Yann N Dauphin, Razvan Pascanu, Caglar Gulcehre, Kyunghyun Cho, Surya Ganguli, and Yoshua Bengio. Identifying and attacking the saddle point problem in high-dimensional non-convex optimization. *Advances in neural information processing systems*, 27, 2014.

Dheeru Dua and Casey Graff. Uci machine learning repository, 2017. URL http://archive.ics.uci.edu/ml.

Jerome H Friedman. Greedy function approximation: a gradient boosting machine. *Annals of statistics*, pp. 1189–1232, 2001.

Ian Goodfellow, David Warde-Farley, Mehdi Mirza, Aaron Courville, and Yoshua Bengio. Maxout networks. In *International conference on machine learning*, pp. 1319–1327. PMLR, 2013.

Ian J Goodfellow, Oriol Vinyals, and Andrew M Saxe. Qualitatively characterizing neural network optimization problems. *arXiv preprint arXiv:1412.6544*, 2014.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pp. 1026–1034, 2015.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Pavel Izmailov, Dmitrii Podoprikhin, Timur Garipov, Dmitry Vetrov, and Andrew Gordon Wilson. Averaging weights leads to wider optima and better generalization. *arXiv preprint arXiv:1803.05407*, 2018.

Ron Kohavi. Scaling up the accuracy of naive-bayes classifiers: A decision-tree hybrid. In *Kdd*, volume 96, pp. 202–207, 1996.

Pantelis Linardatos, Vasilis Papastefanopoulos, and Sotiris Kotsiantis. Explainable ai: A review of machine learning interpretability methods. *Entropy*, 23(1):18, 2020.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial intelligence and statistics*, pp. 1273–1282. PMLR, 2017.

Ian E Nielsen, Dimah Dera, Ghulam Rasool, Nidhal Bouaynaya, and Ravi P Ramachandran. Robust explainability: A tutorial on gradient-based attribution methods for deep neural networks. *arXiv preprint arXiv:2107.11400*, 2021.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019. URL http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Boris T Polyak and Anatoli B Juditsky. Acceleration of stochastic approximation by averaging. *SIAM journal on control and optimization*, 30(4):838–855, 1992.

Ali Raza, Kim Phuc Tran, Ludovic Koehl, and Shujun Li. Designing ecg monitoring healthcare system with federated transfer learning and explainable ai. *Knowledge-Based Systems*, 236:107763, 2022.

Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pp. 618–626, 2017.

Karen Simonyan, Andrea Vedaldi, and Andrew Zisserman. Deep inside convolutional networks: Visualising image classification models and saliency maps. *arXiv preprint arXiv:1312.6034*, 2013.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

Carolin Strobl, Anne-Laure Boulesteix, Achim Zeileis, and Torsten Hothorn. Bias in random forest variable importance measures: Illustrations, sources and a solution. *BMC bioinformatics*, 8(1):1–21, 2007.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *International conference on machine learning*, pp. 3319–3328. PMLR, 2017.

Erico Tjoa and Cuntai Guan. A survey on explainable artificial intelligence (xai): Toward medical xai. *IEEE transactions on neural networks and learning systems*, 32(11):4793–4813, 2020.

Talip Ucar, Ehsan Hajiramezanali, and Lindsay Edwards. Subtab: Subsetting features of tabular data for self-supervised representation learning. *Advances in Neural Information Processing Systems*, 34, 2021.

Mitchell Wortsman, Gabriel Ilharco, Samir Ya Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes, Ari S Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, et al. Model soups: averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. In *International Conference on Machine Learning*, pp. 23965–23998. PMLR, 2022.

Jinsung Yoon, James Jordon, and Mihaela van der Schaar. Invase: Instance-wise variable selection using neural networks. In *International Conference on Learning Representations*, 2018.

Yuchen Zhang, Martin J Wainwright, and John C Duchi. Communication-efficient algorithms for statistical optimization. *Advances in neural information processing systems*, 25, 2012.

Martin Zinkevich, Markus Weimer, Lihong Li, and Alex Smola. Parallelized stochastic gradient descent. *Advances in neural information processing systems*, 23, 2010.

A   ALGORITHM

Algorithm 1: Main learning algorithm

---

input: batch size N, the structure of encoder (e), classifier (c), mask (m);

```
# Set the seed and do train-test split
```
$seed = 57$;
```
# Training and test sets.
```
$X_{train}, X_{test} = get\_data(random\_seed = seed)$;
```
# Initialize a list to hold mask models from each of K-training
instances.
```
$masks\_list = []$;

```
# Train models K-times, each time with a different random seed.
```
for i_k *in* $\{K\}$ **do**
    ```# Change random seed and initialize models```
    $seed = seed + 17$;
    initialize all models (e, c, m) with new seed;
    ```# Train mask, classifier & encoder and return trained mask```
    ```model.```
    $\_, \_, M_{l_k}, \_ = train\_for\_downstream(training = (X_{train}, y_{train}))$
    ```# Collect parameters of the local mask model.```
    $masks\_list.append(M_{l_k})$;
end

```
# Average the parameters of the masks collected to obtain
global mask
```
$M_g = \frac{1}{K} \sum_{k=1}^{K} M_{l_k}$;
```
# Change the random seed and initialize models
```
$seed = seed + 17$;
initialize all models (e, c, m) with new seed;
```
# Train mask, classifer and encoder while using global mask
(frozen)
```
$\boldsymbol{e, c, M_l, M_g} = train\_for\_downstream(training = (X_{train}, y_{train}), M_g = M_g)$;
```
# Return Encoder (e), Classifier (c), Local and Global masks
```
return $\boldsymbol{e, c, M_l, M_g}$;

Algorithm 2: Training routine used for the downstream task

---

def train_for_downstream(training, val=None, $\boldsymbol{M_g}$=None)

    $X_{train}, y_{train} = training$

    foreach *epoch* $e \in Epochs$ **do**

        foreach *batch* $(X_b, y_b) \in (X_{train}, y_{train})$ **do**

            `# Get the output from the local mask`

            $m = M_l(X_b)$

            `# If the global mask is provided, get its output`

            if $M_g \neq None$: **then**

                with no gradient:

                    $m_g = M_g(X_b).detach()$

                `# Final mask is the sum of local and global masks,`

                `scaled by the max entry in the sum.`

                $m = (m + m_g)/max(m + m_g)$

            `# Get the masked input using the square of the mask`

            $X_M = m^2 \odot X_b$

            `# Generate subsets of data (i.e.  feature bagging)`

            $x_i, x_j, x_k, ... = generate\_subsets(X_M)$

            `# Obtain embeddings`

            $h_i, h_j, h_k, ... = [encoder(x) \quad for \quad x \quad in \quad [x_i, x_j, x_k, ...]]$

            `# Aggregate embeddings to get the joint embedding`

            $h = aggregate(h_i, h_j, h_k, ...)$

            `# Get predictions using the joint embedding`

            $y_{pred} = classifier(h)$

            `# Compute losses`

            $L_{task} = CrossEntropy(y_{pred}, y_b)$

            $L_{mask} = Gini(m)$

            $L = L_{task} + L_{mask}$

            `# Update models.  Note that the global mask is not`

            `trained.`

            backprop and update **local mask**, **encoder** and **classifier**

        `# If validation set is provided, run validation using the`

        `steps above (no loss computation).`

    `# Return Encoder, Classifier, Local and Global masks`

    return $encoder, classifier, \boldsymbol{M_l}, \boldsymbol{M_g}$

B DATA

B.1 ADULT INCOME DATASET

Adult Income (Income) is a public dataset based on the 1994 Census database (Kohavi, 1996). It is used for a classification task of predicting whether the income of a person exceeds \$50K/yr by using heterogeneous features such as age, gender, education level and so on. It contains 32.5k and 16k samples for training and test sets respectively.

Train-Validation-Test Split: Training and test sets are provided separately (Kohavi, 1996). We split the training set into training and validation sets using 80-20% split to search for hyper-parameters. Once hyper-parameters was fixed, we trained the model on the whole training set.

Features: The dataset has 14 attributes consisting of 8 categorical and 6 continuous features. We dropped the rows with missing values, and encoded categorical features using one-hot encoding. Once we encode the categorical features as one-hot, we end up with 105 features in total. Features are normalized by subtracting the mean and dividing by the standard deviation, both of which are computed using training set.

Class imbalance: It is an imbalanced dataset, with only 25% of the samples being positive.

B.2 UCI BLOGFEEDBACK DATASET

Referred as Blog in this work, it contains the number of comments in the upcoming 24 hours for blog posts. Although the dataset can be used for regression, we turn it to a binary classification task to predict whether there is a comment for a post or not.

Train-Validation-Test Split: UCI (Dua & Graff, 2017) provides one training set, and 60 small test sets. We combined all the test sets into one test set. We split training set to training and validation using 80-20% split to search for hyper-parameters. We trained the final model using all of the training set.

Features: It includes 281 variables consisting of 280 integer and real valued features and 1 target variable indicating the number of comments a blog post received in the next 24 hours relative to the basetime. We converted the target (the last column in the dataset) to a binary variable, in which 0/1 indicates whether the blog post received any comments. Similarly to Income dataset, we used standard scaling to normalize the features.

Class imbalance: $\sim 36\%$ of the samples are positive in training set while it is $\sim 30\%$ in the test set.

B.3 SYNTHETIC DATASETS FROM L2X:

We run experiments on four synthetic datasets used for binary classification in L2X (Chen et al., 2018). For each dataset, we have 10k training and 10k test set. In first three datasets, we generate data $\boldsymbol{X}$ from 10-dimensional standard Gaussian and assign labels using $P(Y = 1|\boldsymbol{X}) = 1/(1 + g(\boldsymbol{X}))$ in each dataset, where $g(\boldsymbol{X})$ is defined in the following way: **i) *XOR*:** $exp(f_1 * f_2)$, **ii) *Orange Skin*:** $exp(\sum_{i=1}^{4} f_i{}^2 - 4)$, and **iii) *Nonlinear Additive*:** $exp(-100 * sin(2 * f_1) + 2 * |f_2| + f_3 + exp(-f_4))$. In the fourth dataset, **iv) *Switch*:** We generate f_{10} from a mixture of two Gaussians centered at ± 3 respectively with equal probability. If f_{10} is from the $\mathcal{N}(3, 1)$, then we use $\{f_1, f_2, f_3, f_4\}$ to generate Y from the Orange Skin model. Otherwise, we use $\{f_5, f_6, f_7, f_8\}$ to generate Y from the Nonlinear Additive model. f_9 is not used when generating labels.

B.4 DATA LICENSE

Aduld Income and **BlogFeedback** are under Open Data Commons Public Domain Dedication and License (PDDL).

C   DETAILS OF THE EXPERIMENTS IN THE MAIN PAPER

C.1   MODEL ARCHITECTURES AND HYPER-PARAMETERS FOR XTAB

The classifier has three linear layers, two of which are followed by a leakyReLU and dropout (p=0.2). For the mask generator, we use two architectures; i) **shallow:** A linear layer followed by leakyReLU and a final linear layer, ii) **deep:** five linear layers, each followed by leakyReLU, and a final linear layer. The last layer for both mask generator and classifier uses sigmoid activation. The number of hidden units in each layer in the mask generator is same as the number of features in the input while we use 1024 units in each hidden layers of classifier. During training, a learning rate of 0.001 is used for all experiments and we optimize the batch size and total number of epochs.

Table A1: Architectures & hyper-parameters used in our framework for each dataset. Abbreviations are; σ: Standard deviation used for Gaussian noise, **MR:** Mask ratio p.

Dataset	Mask	Encoder	Classifier	Subsets / Overlap	σ/MR (p)	Noise	Batch/Epoch
SynRank	[10, 10]	[1024]	[1024, 1024, 1024]	3 / 75%	0.5/0.5	Gaussian	1024, 40
SynRank100	[100, 100]	[1024]	[1024, 1024, 1024]	2 / 75%	NA/0.5	Swap	1024, 40
Income	[105, 105]	[1024]	[1024, 1024, 1024]	3 / 25%	0.3/0.2	Gaussian	1024, 40
Blog	[280, 280]	[1024]	[1024, 1024, 1024]	7 / 75%	0.3/0.2	Gaussian	256, 20
L2X XOR	[10, 10]	[1024]	[1024, 1024, 1024]	2 / 75%	0.05/0.2	Gaussian	1024, 40
L2X Orange	[10, 10]	[1024]	[1024, 1024, 1024]	2 / 75%	0.05/0.2	Gaussian	1024, 40
L2X N. Additive	[10, 10]	[1024]	[1024, 1024, 1024]	2 / 75%	0.01/0.2	Gaussian	1024, 40
L2X Switch	[10, 10]	[1024]	[1024, 1024, 1024]	2 / 75%	0.05/0.3	Gaussian	1024, 40

C.2   IMPLEMENTATION AND RESOURCES

We implemented our work using PyTorch (Paszke et al., 2019). AdamW optimizer (Loshchilov & Hutter, 2017) with $betas = (0.9, 0.999)$ and $eps = 1e - 07$ is used for all of our experiments. We used a compute cluster consisting of Volta GPUs throughout this work.

C.3   DETAILS FOR TRAINING L2X, INVASE, TABNET, SALIENCY MAPS AND INTEGRATED GRADIENTS (IG)

L2X: We used the official implementation of L2X[2]. We set all of hyperparameters, following the instruction in L2X paper (Chen et al., 2018). For each data set, we trained a neural network model with three hidden layers. The explainer is a neural network composed of two hidden layers. The variational family is based on three hidden layers. All layers are linear with dimension 200. The number of desired features is set to the number of true features. We fixed the step size to be 0.001 across experiments. The temperature for Gumbel-softmax approximation is fixed to be 0.1. Since the model is proposed for feature selection, we used the average number of selected features for each sample in the test set to rank them.

Invase: We followed the hyperparameter selection as instructed in Invase paper (Yoon et al., 2018) and all the experiments are based on the official Keras implementation[3]. We fixed the learning rate and λ as 0.0001 and 0.1, respectively. The actor and critic models are three layer neural networks with hidden state dimensions 100 and 200, respectively. L2 regularization is set to be 0.001 and activation function is ReLU. We used the feature selection probability, which is the output of the actor model, to rank the features.

TabNet: We used the well established PyTorch implementation of TabNet[4]. We set the hyperparameters as $N_a = N_b = 8$, $\lambda_{sparse} = 0.001$, $B = 1024$, $B_v = 128$, $\gamma = 0.3$, and learning rate $= 0.02$. For all experiments, we used sparsemax as the masking function and OneCycleLR as the learning rate scheduler. The other parameters are set to be same as the default choices.

Saliency Maps and Integrated Gradients (IG): For Saliency Maps (Simonyan et al., 2013) and IG (Sundararajan et al., 2017), we used the same architecture as XTab and trained the models using SGD

---

[2]https://github.com/Jianbo-Lab/L2X

[3]https://github.com/jsyoon0823/INVASE

[4]https://github.com/dreamquark-ai/tabnet

with learning rate of 0.01. For Saliency Map, we considered absolute value of each sample gradient for ranking. For IG, we used Captum PyTorch library[5].

D MORE ON RELATED WORKS

Explainability The literature in explainability and model interpretation is extensive and we refer the reader to the survey papers (Linardatos et al., 2020; Nielsen et al., 2021; Tjoa & Guan, 2020) for a more complete review. In this work, we compare our method to the commonly used methods (Random Forest (Breiman, 2001), Gradient Boosting Classifier (Friedman, 2001; Pedregosa et al., 2011)), to those based on the gradients and/or activations (Saliency Maps (Simonyan et al., 2013) and Integrated Gradients (IG) (Sundararajan et al., 2017)), to the ones that rely on the learnable masks (TabNet (Arık & Pfister, 2021), Invase (Yoon et al., 2018)) and to some of the recently published feature selection methods (L2X (Chen et al., 2018), Invase (Yoon et al., 2018)). What distinguishes our work from the aforementioned works is that we focus on the sensitivity of the feature rankings to model initialisation in neural networks. Our goal is to achieve the robustness of tree-based methods such as Random Forest (Breiman, 2001) in neural network setting. In this regard, we compare our results to neural network-based methods both in the main paper as well as in the Appendix.

Explainability in Federated Learning There is some recent work in the intersection of explainable AI (XAI) and Federated Learning (FL) such as the application of Gradient-weighted Class Activation Mapping (Grad-CAM) (Selvaraju et al., 2017) to explain the classification results in electrocardiography (ECG) monitoring healthcare system (Raza et al., 2022). However, it still remains to be an open problem. Lastly, although our method is not proposed for Federated Learning setting, we believe that it can still be used in this area.

---

[5]https://github.com/pytorch/captum

E   ADDITIONAL RESULTS FOR SYNRANK DATASET

E.1   THE RESULTS FOR INSTANCE-WISE FEATURE IMPORTANCE

Figure A1: **SynRank dataset:** Comparing ground-truth top feature to predicted top feature from M_g for two separate runs. We see that M_g is biased towards the globally important features, and fails to rank f_2 as the most important feature for 20% of the samples in the test set, for which we generated labels using $P(Y = 1|\boldsymbol{X}) = 1/(1 + exp(f_2))$ and f_2 is sampled from $\mathcal{N}(0, 1)$. Similarly, we can see the bias toward f_6 when estimating the most important feature for samples, for which we generated the labels using f_1 although it is less severe compared to the case of f_2.

E.2   RESULTS FOR SHALLOW NETWORK

(a) No regularization   (b) Dropout (p=0.2)   (c) Weight-clipping

Figure A2: Measuring the weight distribution for shallow networks when we apply **a)** no weight regularization, **b)** Dropout ($p = 0.2$), and **c)** Weight-clipping ($[-0.2, 0.2]$). **Top row:** The weight distribution of a single local mask model selected at random. **Bottom row:** The weight distribution of a global mask model obtained by averaging the parameters of 10 models bootstrapped from 20 local models.

E.3 RESULTS FOR DEEP NETWORK

(a) No regularization   (b) Dropout (p=0.2)   (c) Weight-clipping ([-0.2, 0.2])

Figure A3: Measuring the robustness of parameter averaging for deep networks (5 layers). We use SynRank dataset, in which the important features are $f_6 > f_1 > f_2$ while the rest is not informative. **Top row:** Variations in feature rankings across 20 local mask models when we apply **a)** no weight regularization, **b)** Dropout ($p = 0.2$), and **c)** Weight-clipping ($[-0.2, 0.2]$). **Bottom row**: Variations in feature rankings in 100 global models, each of which is obtained by averaging the parameters of 10 models bootstrapped from 20 local models for the same three cases. Weight-clipping helps global models discover important features in the correct order consistently (see the last column, bottom row)

(a) No regularization   (b) Dropout (p=0.2)   (c) Weight-clipping

Figure A4: Measuring the weight distribution for deep networks (5 layers) when we apply **a)** no weight regularization, **b)** Dropout ($p = 0.2$), and **c)** Weight-clipping ($[-0.2, 0.2]$). **Top row:** The weight distribution of a single local mask model selected at random. **Bottom row:** The weight distribution of a global mask model obtained by averaging the parameters of 10 models bootstrapped from 20 local models.

F ADDITIONAL RESULTS FOR SYNRANK100

(a) No regularization   (b) Dropout (p=0.2)   (c) Weight-clipping ([-0.2, 0.2])

Figure A5: **SynRank100 dataset:** The important features are $f_{100} > f_1 > f_{75}$ while the rest of the features is not informative. **Top row:** Variations in feature rankings across 20 local mask models when we apply **a)** no weight regularization, **b)** Dropout ($p = 0.2$), and **c)** Weight-clipping ($[-0.2, 0.2]$). **Bottom row**: Variations in feature rankings in 100 global models, each of which is obtained by averaging the parameters of 10 models bootstrapped from 20 local models for the same three cases. We use a shallow network for the mask model.

G   FEATURE IMPORTANCE RESULTS FOR L2X DATASETS

Figure A6: **Top row:** Feature rankings from each of 10 local masks M_{l_k}, referred as l_k in the figure, obtained at a particular training run for 10 separate runs. **Middle row**: Feature rankings from the global model, obtained by averaging the parameters of individual models up to a specific run i.e. cumulative average (CA). For example, g_3 corresponds to the global model obtained by averaging the parameters of first 3 local masks (l_1, l_2, l_3). **Bottom row**: The feature importance weights from M_g obtained by averaging the parameters of all local masks.

We note that the weights of the features are correlated with the frequency and position of their ranks across all local masks. Specifically, f_1 and f_2 in L2X XOR dataset keep switching positions between 1^{st} and 2^{nd} ranks across all ten runs (top row in Figure A6(a)). Therefore, M_g computes their importance weights to be similar, giving a slight edge to f_2 since it is ranked as #1 by six out of ten local masks (the first and third rows in Figure A6(a)).

In the L2X Switch dataset, f_{10} is used as the switch feature to change whether the label is determined by the features $f_1 - f_4$ or by $f_5 - f_8$ and is discovered as the most important global feature by M_g (the bottom row in Figure A6(d)). Please note that this is the hardest synthetic dataset in a way that the effect of f_{10} on the sample labels is not direct, rather it influences the labels indirectly by deciding which features to be used for label generation. This might be the main reason why a commonly used method such as permutation feature importance fails, ranking f_1 as the most important feature in our experiments with random forest and gradient boosting classifier used together with permutation feature importance (please see the results in Section I.1 of the Appendix). Consistent with the ground truth, M_g also discovers f_9 as an uninformative feature (bottom row in Figure A6(d)).

In L2X Orange dataset, our method correctly discovers the first four features as the most important ones with almost equal weights while it indicates f_1 and f_4 as the most important features in L2X Nonlinear Additive.

H ADDITIONAL RESULTS FOR L2X SWITCH

H.1 RESULTS FOR SHALLOW NETWORK

We run additional experiments on L2X Switch under three conditions: We apply i) No weight regularization to the weights of the mask model, ii) Dropout with $p = 0.2$ for the layers with leaky ReLU activation, iii) Weight-clipping ($[−0.2, 0.2]$) to limit the magnitude of the weights in each layer. For each of the three cases, we train 20 separate models and compare two different settings. In the first setting, we compute the variation in the feature rankings given by 20 local mask models (top row in Figure A7). In the second setting, we obtain 100 global models, each of which is obtained by averaging the parameters of 10 local models *bootstrapped* from 20 models. We compare the variation in feature rankings given by global models (second setting – bottom row in Figure A7) to that of 20 local models (first setting – top row). We observe that: i) Regularization methods such as dropout and weight-clipping help improve the variation across 20 local models, but the improvement is not substantial (e.g., comparing f_9 and f_{10} across three cases at the top row). ii) However, they help improve the robustness of the parameter averaging significantly (e.g., comparing f_9 and f_{10} across three cases at the bottom row). We also observe that the parameter averaging itself pushes the magnitude of the weights towards a tight range around zero as shown in Figure A8 (Section H.1 of the Appendix), indicating a potential relationship between robustness and a tighter weight distribution. Overall, the global models are able to discover important features in the correct order, and the variation in feature ranking across global models is small (almost zero) for ground truth important features when we apply weight regularization (please see f_9 and f_{10} at the bottom row in Figure A7b and Figure A7c). iii) Weight-clipping works better than dropout in our experiments, but dropout results could perhaps be improved by hyper-parameter search on the p variable.

Figure A7: Measuring the robustness of parameter averaging for shallow networks. We use L2X Switch dataset, in which the most and the least important features are f_{10} and f_9 respectively. **Top row:** Variations in feature rankings across 20 local mask models when we apply **a)** no weight regularization, **b)** Dropout ($p = 0.2$), and **c)** Weight-clipping ($[−0.2, 0.2]$). **Bottom row**: Variations in feature rankings in 100 global models, each of which is obtained by averaging the parameters of 10 models bootstrapped from 20 local models for the same three cases.

(a) No regularization (b) Dropout (p=0.2) (c) Weight-clipping

Figure A8: The weight distribution for shallow networks when we apply **a)** no weight regularization, **b)** Dropout ($p = 0.2$), and **c)** Weight-clipping ($[-0.2, 0.2]$). **Top row:** The weight distribution of a single local mask model selected at random. **Bottom row:** The weight distribution of a global mask model obtained by averaging the parameters of 10 models bootstrapped from 20 local models.

Figure A9: Two separate examples showing the weights of the features from a model that is obtained by interpolating between a single local model and the global model, which is obtained by bootstrapping 10 local models out of 20: $\theta^* = (1 - \alpha) * \theta_l + \alpha * \theta_g$, where α is swept from 0 to 1 in 50 steps. The figure on the left uses a local model that ranks features as $f1 > f10 > rest > f9$ while the one on the right uses a local model that ranks features as $f10 > f1 > rest > f9$. As we move from local model ($\alpha = 0$) to the global model ($\alpha = 1$), the estimate of feature ranking gets better (Expected feature rank: $f10 > f1 > rest > f9$). The plots show the mean and 95% confidence intervals for the weights of the features obtained by repeating the experiments with 100 bootstrapped global models, each of which is interpolated with the same local model. In both examples, we see that the global model predicts the rankings of the features correctly even when the initial ranking from the local model might be incorrect (e.g., left plot). **"rest"** refers to average weight of the rest of the informative features i.e., $f2 - f8$.

H.2 RESULTS FOR DEEPER NETWORK

(a) No regularization   (b) Dropout (p=0.2)   (c) Weight-clipping ([-0.2, 0.2])

Figure A10: Measuring the robustness of parameter averaging for deeper networks (5 layers). We use L2X Switch dataset, in which the most and the least important features are f_{10} and f_9 respectively. **Top row:** Variations in feature rankings across 20 local mask models when we apply **a)** no weight regularization, **b)** Dropout ($p = 0.2$), and **c)** Weight-clipping ($[-0.2, 0.2]$). **Bottom row:** Variations in feature rankings in 100 global models, each of which is obtained by averaging the parameters of 10 models bootstrapped from 20 local models for the same three cases. Although the weight regularization helps improve the robustness, we still see variations for feature f_{10} when the model is deep (see last two columns at the bottom row). Also, weight-clipping works better than dropout again.

(a) No regularization   (b) Dropout (p=0.2)   (c) Weight-clipping

Figure A11: Measuring the weight distribution for deep networks (5 layers) when we apply **a)** no weight regularization, **b)** Dropout ($p = 0.2$), and **c)** Weight-clipping ($[-0.2, 0.2]$). **Top row:** The weight distribution of a single local mask model selected at random. **Bottom row:** The weight distribution of a global mask model obtained by averaging the parameters of 10 models bootstrapped from 20 local models.

H.3   THE EFFECT OF NOISE ON THE TEST ACCURACY AND FEATURE RANKING

(a) Test accuracy   (b) Feature ranking from M_g

Figure A12: **L2X Switch dataset:** At each noise level, we ran our framework 10 times with different set of random seeds to compare how **a)** the test accuracy and **b)** the rankings of the top two features from M_g, i.e. f_{10} and f_1, changes. Test accuracy improves when Gaussian noise with low variance is added. Compared to some other datasets, the feature ranking is stable with no, or low noise. Please note that we show 95% confidence interval only for feature f_{10} for clarity.

I   MORE RESULTS FOR SYNTHETIC DATASETS FROM L2X

In this section, we show the robustness of our method, **XTab**, by listing the global feature importance from M_g using *test set* for L2X (Chen et al., 2018) datasets across 10 separate runs of our method. *Please note that we don't use weight regularization for XTab in any of these experiments.* We also list global feature importance obtained by using permutation importance together with random forest (RFP), and gradient boosting classifier (GBCP). For L2X Nonlinear Additive and L2X Switch datasets, we also compare **XTab** to other approaches such as TabNet(Arık & Pfister, 2021), Invase(Yoon et al., 2018), L2X(Chen et al., 2018), Saliency Maps(Simonyan et al., 2013), and Integrated Gradients(Sundararajan et al., 2017) for comparison.

I.1   COMPARING XTAB TO OTHER METHODS USING L2X SWITCH DATASET

Table A2: Comparing XTab to other methods using L2X Switch dataset by listing global feature importance rankings across 10 separate runs with different set of random seeds.

	L2X Switch										
Ranking from XTab (no weight regularization is used)											
Runs	1	2	3	4	5	6	7	8	9	10	**Test Acc.**
1	f10	f1	f2	f4	f5	f3	f7	f6	f8	f9	0.9768
2	f10	f2	f5	f1	f4	f3	f7	f8	f6	f9	0.975
3	f10	f1	f2	f5	f4	f3	f7	f8	f6	f9	0.9742
4	f10	f1	f2	f4	f5	f3	f7	f6	f8	f9	0.9733
5	f10	f5	f1	f2	f4	f3	f6	f7	f8	f9	0.9737
6	f10	f1	f4	f5	f2	f3	f7	f6	f8	f9	0.9741
7	f10	f1	f2	f5	f4	f3	f7	f9	f8	f6	0.9729
8	f10	f1	f2	f4	f5	f3	f7	f8	f6	f9	0.9682
9	f10	f1	f5	f4	f2	f3	f7	f6	f8	f9	0.9725
10	f10	f1	f2	f4	f5	f3	f7	f6	f8	f9	0.9757
GBCP	f1	f10	f4	f2	f3	f5	f7	f8	f6	f9	0.9676
RFP	f1	f10	f5	f4	f3	f2	f8	f7	f6	f9	0.9575
Ranking from TabNet											
Runs	1	2	3	4	5	6	7	8	9	10	**Test Acc.**
1	f4	f1	f10	f2	f3	f5	f6	f8	f9	f7	0.9606
2	f5	f10	f4	f1	f2	f3	f7	f9	f8	f6	0.9733
3	f4	f1	f10	f2	f3	f9	f8	f5	f7	f6	0.9646
4	f1	f4	f2	f10	f5	f3	f6	f7	f9	f8	0.9723
5	f10	f5	f2	f4	f3	f7	f1	f9	f6	f8	0.9623
6	f1	f2	f4	f10	f3	f5	f9	f6	f8	f7	0.9669
7	f1	f2	f4	f3	f10	f5	6	f8	f7	f9	0.9723
8	f10	f4	f3	f1	f5	f2	f8	f7	f6	f9	0.9683
9	f4	f1	f2	f10	f3	f5	f9	f6	f7	f8	0.9695
10	f1	f10	f3	f4	f2	f5	f8	f7	f6	f9	0.9723
Ranking from Invase											
Runs	1	2	3	4	5	6	7	8	9	10	**Test Acc.**
1	f4	f10	f2	f1	f3	f5	f6	f8	f9	f7	0.982
2	f3	f4	f10	f2	f1	f5	f9	f8	f6	f7	0.978
3	f1	f10	f3	f2	f4	f5	f8	f9	f7	f6	0.979
4	f10	f1	f2	f3	f4	f5	f8	f9	f6	f7	0.979
5	f10	f2	f1	f3	f4	f5	f9	f6	f8	f7	0.981
6	f10	f2	f4	f1	f3	f5	f9	f8	f6	f7	0.979
7	f10	f4	f3	f1	f2	f5	f7	f6	f9	f8	0.982
8	f4	f3	f10	f1	f2	f5	f9	f7	f8	f6	0.981
9	f10	f1	f4	f3	f2	f5	f6	f7	f9	f8	0.982
10	f10	f2	f4	f1	f3	f5	f7	f8	f6	f9	0.982
Ranking from L2X											
Runs	1	2	3	4	5	6	7	8	9	10	**Test Acc.**
1	f1	f4	f7	f3	f5	f2	f10	f9	f6	f8	0.9869
2	f1	f9	f2	f7	f3	f4	f10	f8	f6	f5	0.9913
3	f1	f4	f2	f3	f9	f5	f10	f6	f7	f8	0.9943
4	f1	f4	f2	f8	f3	f10	f9	f7	f6	f5	0.9876
5	f1	f3	f2	f4	f10	f8	f7	f5	f6	f9	0.9891
6	f1	f10	f5	f2	f4	f3	f8	f7	f6	f9	0.9925
7	f1	f4	f3	f5	f2	f7	f6	f10	f9	f8	0.9896
8	f1	f4	f8	f2	f3	f10	f9	f6	f7	f5	0.9905
9	f1	f4	f2	f8	f3	f7	f9	f6	f10	f5	0.9923
10	f1	f4	f2	f3	f6	f10	f7	f5	f8	f9	0.9906
Ranking from Saliency Maps											
Runs	1	2	3	4	5	6	7	8	9	10	**Test Acc.**
1	f1	f10	f5	f4	f2	f3	f8	f7	f6	f9	0.9334
2	f1	f10	f5	f2	f4	f3	f7	f6	f8	f9	0.9355
3	f1	f10	f5	f4	f2	f3	f7	f6	f8	f9	0.9378
4	f1	f10	f5	f4	f2	f3	f7	f6	f8	f9	0.9372
5	f1	f10	f5	f4	f2	f3	f7	f8	f6	f9	0.9372
6	f1	f10	f5	f4	f2	f3	f7	f8	f6	f9	0.9378
7	f1	f10	f5	f4	f2	f3	f7	f6	f8	f9	0.9346
8	f1	f10	f5	f4	f2	f3	f7	f8	f6	f9	0.9337
9	f1	f10	f5	f4	f2	f3	f7	f8	f6	f9	0.9377
10	f1	f10	f5	f2	f4	f3	f8	f7	f6	f9	0.9331
Ranking from Integrated Gradients (IG)											
Runs	1	2	3	4	5	6	7	8	9	10	**Test Acc.**
1	f2	f5	f1	f4	f8	f3	f6	f7	f10	f9	0.9334
2	f2	f5	f1	f3	f4	f6	f7	f8	f10	f9	0.9355
3	f2	f5	f1	f3	f4	f8	f6	f10	f7	f9	0.9378
4	f2	f5	f1	f3	f6	f4	f7	f8	f10	f9	0.9372
5	f2	f5	f4	f1	f3	f6	f8	f10	f7	f9	0.9372
6	f2	f5	f4	f1	f8	f3	f10	f7	f6	f9	0.9378
7	f2	f5	f1	f3	f4	f10	f7	f8	f6	f9	0.9346
8	f2	f5	f1	f4	f3	f6	f8	f7	f10	f9	0.9337
9	f5	f2	f4	f1	f8	f3	f6	f7	f10	f9	0.9377
10	f2	f5	f1	f4	f3	f8	f6	f10	f7	f9	0.9331

I.2 Comparing XTab to other methods using L2X Non-Linear Additive dataset

Table A3: Comparing XTab to other methods using L2X Non-Linear Additive dataset by listing feature importance rankings across 10 separate runs with different set of random seeds.

L2X Nonlinear Additive

Ranking from XTab (no weight regularization is used)

Runs	1	2	3	4	5	6	7	8	9	10	Test Acc.
1	f1	f4	f3	f5	f7	f9	f2	f8	f6	f10	0.9805
2	f1	f4	f3	f5	f9	f7	f8	f2	f6	f10	0.9775
3	f1	f4	f3	f5	f8	f2	f9	f7	f10	f6	0.9814
4	f1	f4	f3	f2	f5	f9	f7	f8	f6	f10	0.9854
5	f1	f4	f3	f5	f7	f9	f8	f6	f2	f10	0.9844
6	f1	f4	f3	f5	f9	f7	f8	f2	f6	f10	0.9835
7	f1	f4	f3	f7	f5	f8	f9	f2	f6	f10	0.9822
8	f1	f4	f3	f5	f9	f7	f2	f6	f10	f8	0.9761
9	f1	f4	f3	f5	f7	f9	f8	f2	f6	f10	0.9835
10	f1	f4	f3	f5	f9	f2	f7	f6	f8	f10	0.9775
GBCP	f1	f4	f3	f2	f10	f6	f5	f9	f8	f7	0.9924
RFP	f1	f4	f3	f2	f10	f5	f7	f9	f6	f8	0.9853

Ranking from TabNet

Runs	1	2	3	4	5	6	7	8	9	10	Test Acc.
1	f1	f4	f5	f6	f8	f10	f2	f7	f3	f9	0.9785
2	f1	f4	f5	f6	f3	f8	f9	f7	f2	f10	0.9752
3	f1	f5	f4	f6	f8	f10	f2	f3	f9	f7	0.9751
4	f1	f4	f5	f6	f8	f3	f2	f10	f7	f9	0.9785
5	f1	f5	f4	f6	f8	f10	f2	f3	f9	f7	0.9737
6	f1	f5	f4	f3	f6	f8	f2	f10	f9	f7	0.9758
7	f1	f5	f4	f6	f3	f2	f8	f10	f7	f9	0.9760
8	f1	f4	f5	f6	f8	f10	f2	f7	f3	f9	0.9758
9	f1	f4	f6	f5	f2	f10	f8	f3	f9	f7	0.9758
10	f1	f5	f4	f6	f3	f2	f8	f10	f7	f9	0.9751

Ranking from Invase

Runs	1	2	3	4	5	6	7	8	9	10	Test Acc.
1	f1	f4	f3	f2	f7	f9	f8	f10	f6	f5	0.987
2	f1	f4	f3	f2	f5	f9	f6	f10	f7	f8	0.987
3	f1	f4	f3	f2	f8	f10	f9	f6	f5	f7	0.986
4	f1	f4	f3	f2	f9	f8	f7	f5	f6	f10	0.987
5	f1	f3	f4	f2	f8	f7	f6	f5	f9	f10	0.987
6	f1	f4	f3	f2	f9	f8	f10	f5	f6	f7	0.988
7	f1	f4	f3	f2	f8	f7	f10	f6	f9	f5	0.988
8	f1	f4	f3	f2	f8	f9	f6	f7	f5	f10	0.988
9	f1	f4	f3	f2	f9	f10	f8	f5	f7	f6	0.986
10	f1	f4	f3	f2	f7	f5	f8	f9	f10	f6	0.986

Ranking from L2X

Runs	1	2	3	4	5	6	7	8	9	10	Test Acc.
1	f1	f4	f5	f6	f8	f10	f2	f7	f3	f9	0.9785
2	f1	f4	f5	f6	f3	f8	f9	f7	f2	f10	0.9752
3	f1	f5	f4	f6	f8	f10	f2	f3	f9	f7	0.9751
4	f1	f4	f5	f6	f8	f3	f2	f10	f7	f9	0.9785
5	f1	f5	f4	f6	f8	f10	f2	f3	f9	f7	0.9737
6	f1	f5	f4	f3	f6	f8	f2	f10	f9	f7	0.9758
7	f1	f5	f4	f6	f3	f2	f8	f10	f7	f9	0.9760
8	f1	f4	f5	f6	f8	f10	f2	f7	f3	f9	0.9758
9	f1	f4	f6	f5	f2	f10	f8	f3	f9	f7	0.9758
10	f1	f5	f4	f6	f3	f2	f8	f10	f7	f9	0.9751

Ranking from Saliency Maps

Runs	1	2	3	4	5	6	7	8	9	10	Test Acc.
1	f1	f3	f2	f4	f10	f5	f7	f9	f8	f6	0.9884
2	f1	f3	f2	f4	f5	f10	f9	f6	f7	f8	0.9870
3	f1	f3	f4	f2	f10	f9	f5	f6	f7	f8	0.9876
4	f1	f3	f4	f5	f7	f10	f2	f6	f8	f9	0.9878
5	f1	f3	f2	f4	f5	f7	f10	f6	f9	f8	0.9880
6	f1	f3	f4	f2	f10	f7	f5	f6	f9	f8	0.9874
7	f1	f3	f2	f4	f7	f9	f10	f6	f5	f8	0.9881
8	f1	f3	f4	f5	f2	f10	f6	f9	f7	f8	0.9869
9	f1	f3	f4	f5	f2	f10	f6	f9	f7	f8	0.9883
10	f1	f3	f4	f7	f10	f5	f2	f9	f6	f8	0.9880

Ranking from Integrated Gradients (IG)

Runs	1	2	3	4	5	6	7	8	9	10	Test Acc.
1	f1	f4	f3	f2	f8	f5	f9	f6	f10	f7	0.9884
2	f1	f4	f3	f2	f5	f7	f9	f6	f10	f8	0.9870
3	f1	f4	f3	f2	f6	f9	f7	f10	f8	f5	0.9876
4	f1	f4	f3	f8	f2	f6	f10	f7	f9	f5	0.9878
5	f1	f4	f3	f9	f2	f8	f6	f10	f5	f7	0.9880
6	f1	f4	f3	f2	f9	f8	f6	f10	f7	f5	0.9874
7	f1	f4	f3	f10	f2	f6	f9	f8	f7	f5	0.9881
8	f1	f4	f3	f5	f2	f6	f10	f9	f8	f7	0.9869
9	f1	f4	f3	f2	f9	f8	f5	f10	f6	f7	0.9883
10	f1	f3	f4	f2	f6	f9	f10	f5	f7	f8	0.9880

I.3 THE RESULTS FROM L2X XOR AND ORANGE DATASETS FOR XTAB

Table A4: Showing the robustness of our method, **XTab**, by listing the global feature importance from M_g using *test set* for L2X XOR and Orange datasets across 10 separate runs of our method. We also listed global feature importance obtained by using permutation importance together with random forest (RFP), and gradient boosting classifier (GBCP) for comparison. In L2X XOR, we expect f_1 and f_2 to be equally likely to be top 1 and 2 features and vice versa. For L2X Orange, we expect the first four features to be the top four features in no particular order.

L2X XOR

Runs	\multicolumn{10}{c}{Ranking from XTab (no weight regularization is used)}										Test Acc.
	1	2	3	4	5	6	7	8	9	10	
1	f1	f2	f4	f3	f6	f8	f5	f7	f9	f10	0.9911
2	f1	f2	f4	f3	f5	f6	f8	f7	f9	f10	0.9924
3	f1	f2	f4	f3	f8	f5	f6	f7	f9	f10	0.9922
4	f1	f2	f4	f3	f5	f8	f6	f9	f7	f10	0.9865
5	f1	f2	f4	f3	f5	f8	f6	f7	f9	f10	0.9843
6	f1	f2	f4	f3	f8	f5	f9	f6	f7	f10	0.9926
7	f1	f2	f4	f3	f8	f7	f5	f6	f9	f10	0.986
8	f1	f2	f4	f3	f5	f6	f8	f7	f9	f10	0.9797
9	f1	f2	f4	f3	f5	f8	f7	f6	f9	f10	0.9915
10	f1	f2	f4	f3	f6	f5	f8	f9	f7	f10	0.989
GBCP	f1	f2	f10	f9	f8	f7	f6	f5	f4	f3	0.9999
RFP	f1	f2	f8	f7	f9	f10	f4	f3	f6	f5	0.9995

L2X Orange

Runs	\multicolumn{10}{c}{Ranking from XTab (no weight regularization is used)}										Test Acc.
	1	2	3	4	5	6	7	8	9	10	
1	f1	f4	f2	f3	f7	f6	f8	f9	f5	f10	0.954
2	f1	f4	f2	f3	f7	f9	f8	f6	f5	f10	0.9471
3	f1	f4	f2	f3	f8	f7	f9	f6	f5	f10	0.9695
4	f1	f4	f2	f3	f9	f5	f8	f6	f7	f10	0.9747
5	f1	f4	f2	f3	f7	f8	f5	f9	f6	f10	0.9598
6	f1	f4	f2	f3	f8	f7	f9	f5	f6	f10	0.9689
7	f1	f4	f2	f3	f8	f7	f9	f6	f5	f10	0.9658
8	f1	f4	f2	f3	f7	f6	f5	f8	f9	f10	0.9718
9	f1	f4	f2	f3	f8	f7	f9	f5	f6	f10	0.9691
10	f1	f4	f2	f3	f8	f9	f7	f6	f5	f10	0.9735
GBCP	f3	f1	f4	f2	f9	f8	f6	f5	f10	f7	0.9752
RFP	f3	f1	f4	f2	f10	f9	f7	f6	f5	f8	0.9461

J EXPERIMENTS ON ADULT INCOME DATASET

J.1 ARCHITECTURE SEARCH VIA CROSS-VALIDATION AND FINAL TEST ACCURACY RESULTS

(a) # of layers in the Mask   (b) # of hidden units in the Classifier   (c) Final test accuracy

Figure A13: a) Comparing average cross validation accuracy for 10-fold cross validation (CV) by using mask generator architectures with different number of hidden layers. 10-fold CV is repeated ten times with different starting random seeds i.e. each run corresponds to one 10-fold CV run. 'Linear' means that the mask model has a single linear layer while '2xLReLU' means two hidden layers with leaky ReLU activation. In all cases, the final layer of the mask is a linear layer with sigmoid activation. b) Same experiment repeated for the 1xLReLU mask generator while increasing the number of the hidden units used in the classifier. c) The final test accuracy obtained once we settled on 1xLReLu mask and classifier with 1024 units in hidden layers and *re-run the experiments using our framework* i.e. training models on the full training set multiple times. For comparison, we included the results for other architectural choices for the mask.

We first search for the optimum number of layers for mask generator, keeping the classifier architecture fixed as [1024, 1024, 1024]. The classifer has three linear layers, two of which are followed by a leaky ReLU and dropout(p=0.2). The last layer uses sigmoid activation. We compare four choices for mask generator; i) A single linear layer with sigmoid activation, ii) A linear layer followed by leaky ReLU and another linear layer with sigmoid activation (referred as 1xLReLU) iii) two linear layers, each of which is followed by leaky ReLU, and one linear layer with sigmoid, i.e. 2xLReLU and iv) 3xLReLU. The number of hidden units in each layer in the mask generator is same as the number of features in the input (i.e. 105 in the case of Income dataset). We modified our framework to accommodate K-fold cross validation (CV). We first generated a 10-fold CV dataset from the training set. For each fold, we changed the random seed before initialising and training our models on the training fold. We obtained the validation accuracy using the corresponding validation fold. This is a slight change to our original framework, in which we train models K-times on the *same training set*. We repeated this experiment with 10-fold CV for 10 times with different set of random seeds. As shown in Figure A13a, 1xLReLU gives the best performance for all 10 repeated experiments. Please note that we also ran experiments on 1xLReLU with wider hidden layer and observed that the standard deviation in validation accuracy increases with wider mask model (not shown). Thus, we choose the number of hidden units to be same as the number of input features for all datasets and experiments throughout the paper.

We then repeated the first experiment. In this case, we used the mask generator with 1xLReLU, and varied the number of units for the hidden layers of the classifier. With everything else kept same, over-parameterised classifiers with 1024 and 2048 hidden units give the best performance. We used 1024 for the remainder of our experiments. These choices for the mask generator and the classifier are used for all other datasets and experiments since they work well as shown and discussed in the main and supplementary sections of the paper.

Figure A14: Using a shallow mask architecture for Income dataset. Feature importance extracted from a) Each local mask model M_{l_k}, referred as l_k in the figure, obtained at a particular training run for 10 separate runs, b) Global model obtained by averaging the parameters of individual models up to specific run i.e. cumulative average (CA). For example, g_3 corresponds to averaging the parameters of first 3 local masks (l_1, l_2, l_3) to obtain the global mask, from which we obtain the feature importance, c) Feature importance from the global mask model obtained by averaging all 10 individual models, i.e. M_g in (b), d) Feature importance from M_f.

Figure A15: **First Row:** Same experiment as in Figure A14, but without noise at the input. Removing noise makes the rankings less robust. **Second Row:** Same experiment as in Figure A14, i.e. using noisy input, but the mask architecture is deeper (5 hidden layers). Parameter averaging breaks down with deeper mask model architecture (e-h).

J.2 AVERAGING PARAMETERS OF SHALLOW NETWORKS

We start our experiments with the classification task on Income dataset to get insights into how parameter averaging works on a well-studied, real world dataset for extracting feature importance[6]. We used $p = 0.2$ when generating the binomial mask, β, and considered $\epsilon \sim \mathcal{N}(0, \sigma^2)$ with $\sigma = 0.3$.

---

[6]Unless specified otherwise, when we say feature importance, we refer to global feature importance.

As shown in Figure 1, we train our models on the whole training set for the downstream task 10 times, each time with a different random seed. We store the parameters of the trained masks, referred as local masks, from each training and denote them as $\{M_{l_1}, M_{l_2}, \ldots, M_{l_{10}}\}$. We examine the feature importance obtained from each of 10 local masks across all samples for the test set (Figure A14a). We observe that each local mask gives a slightly different ranking, especially for lower ranked features. More specifically, we could have different ranking (e.g., "age">"marital-status" vs "marital-status">"age" as top two features), depending on which seed is used when training the models. The possible reasons of this variation can be both the model initialisation as well as multicollinearity among the features of the Income dataset.

We then evaluate the effect of averaging over the parameters of the local masks on feature importance in a progressive way. To do this, we obtain a global mask M_{g_k} as a cumulative average (CA) over the k local masks, i.e. $M_{g_k} = 1/k \sum_{i=1}^{k} M_{l_k}$. For example, M_{g_3} corresponds to averaging the parameters of the first three local masks (i.e. $M_{l_1}, M_{l_2}, M_{l_3}$ in Figure A14a). We refer to $M_{g_{10}}$ as M_g for simplicity in the rest of the paper. Figure A14b shows the results for the global masks M_{g_k}, in which we can observe that the feature ranking becomes more stable as we use more local masks in the parameter averaging.

Figures A14c and A14d show the feature importance from $M_g = M_{g_{10}}$ and the final mask M_f, respectively. We first note that the weights of the features are correlated with the frequency and position of their ranks across all local masks. For example, "age" is ranked at the top more often than "marital-status" in Figure A14a, hence its weight given by M_g is relatively higher than that of "marital-status". We also observe that M_f moves both "capital-gain" and "capital-loss" up in the ranking.

Effect of noise. We further investigate the effect of removing Gaussian noise from the subsets of the masked input in Equation 2. To this end, we set $\beta = 0$, and follow the same procedure described above (Figure A14a-d). Comparing Figures A14b and A15b, we can conclude that adding noise to the input makes the global rankings more robust (a detailed comparison is in Section J.6 of the Appendix).

J.3 ROBUSTNESS OF PARAMETER AVERAGING

(a) No regularization   (b) Dropout (p=0.2)   (c) Weight-clipping

Figure A16: **Shallow network - Top row:** Variations in feature rankings across 20 local mask models when we apply **a)** no weight regularization, **b)** Dropout ($p = 0.2$), and **c)** Weight-clipping ($[−0.2, 0.2]$). **Bottom row**: Variations in feature rankings in 100 global models, each of which is obtained by averaging the parameters of 10 models bootstrapped from 20 local models for the same three cases.

(a) No regularization   (b) Dropout (p=0.2)   (c) Weight-clipping

Figure A17: **Deep network - Top row:** Variations in feature rankings across 20 local mask models when we apply **a)** no weight regularization, **b)** Dropout ($p = 0.2$), and **c)** Weight-clipping ($[−0.2, 0.2]$). **Bottom row**: Variations in feature rankings in 100 global models, each of which is obtained by averaging the parameters of 10 models bootstrapped from 20 local models for the same three cases. Please note that the global model in the case of deeper networks results in a feature ranking that is not consistent with local model estimations, indicating that the parameter averaging does not work as well as it does for the shallow networks.

J.4 VARIATIONS IN GLOBAL FEATURE IMPORTANCE OBTAINED FROM M_g AND COMPARING IT TO THE ONES FROM TABNET(ARIK & PFISTER, 2021)

Table A5: Comparing variations in global feature importance obtained from M_g across 10 different runs of our framework with different sets of random seeds to those obtained from TabNet. The rankings from TabNet are not as consistent across multiple training runs as ours. Abbreviations are; **ms:** marital status, **en:** education-num, **cg:** capital-gain, **hpw:** hours-per-week, **race:** race, **occ:** occupation, **rel:** relationship, **cl:** capital-loss, **nc:** native-country. Please note that no weight regularization is used for XTab.

	Global Feature Importance from M_g of XTab									
Runs	1	2	3	4	5	6	7	8	9	10
1	age	ms	hpw	en	cg	occ	race	rel	cl	nc
2	age	ms	hpw	en	cg	occ	race	rel	cl	nc
3	age	ms	hpw	en	cg	occ	race	rel	cl	nc
4	age	ms	hpw	en	cg	occ	race	rel	cl	nc
5	age	ms	hpw	en	cg	occ	race	rel	cl	nc
6	age	ms	hpw	en	cg	occ	race	rel	cl	nc
7	age	ms	hpw	en	cg	occ	race	rel	cl	nc
8	age	ms	hpw	en	cg	occ	race	cl	rel	nc
9	age	ms	hpw	cg	en	race	occ	rel	cl	nc
10	age	ms	hpw	cg	en	occ	race	rel	cl	nc

	Global Feature Importance from TabNet									
Runs	1	2	3	4	5	6	7	8	9	10
1	age	cg	en	rel	hpw	ms	sex	cl	occ	wc
2	en	ms	cg	age	cl	occ	hpw	fw	sex	race
3	en	ms	cg	sex	rel	cl	ed	age	nc	hpw
4	ms	ed	en	rel	cg	occ	cl	hpw	age	race
5	cl	ms	cg	rel	age	occ	en	hpw	wc	nc
6	ms	cg	rel	fw	en	nc	cl	race	wc	sex
7	ms	cg	en	rel	wc	occ	nc	hpw	cl	sex
8	ms	rel	occ	cg	ed	hpw	en	cl	race	nc
9	ms	cg	age	rel	occ	en	cl	hpw	race	nc
10	ms	rel	cg	wc	cl	nc	en	sex	ed	hpw

Please note that we choose to compare Xtab and TabNet here since we can compute the rankings of the high-level categorical features in both methods. For the remaining methods, it is not easy to compute the importance score of a parent category such as "maritial-status", so we instead rank the individual categories (e.g., "single" or "married") directly as shown in Section J.5 of the Appendix.

J.5 COMPARING XTAB TO OTHER METHODS FOR ADULT INCOME DATASET

Please note that, for categorical features, since it is difficult to compute the importance of a parent category from its one-hot encoded features for other methods, we compare the rankings by the individual categories (e.g., showing the importance of "single", or "married" instead of the importance of their parent category "maritial-status"). Abbreviations in the tables are; **mcs:** Married civ spouse, **en:** education-num, **cg:** capital-gain, **hpw:** hours-per-week, **cl:** capital-loss, **em:** Exec-managerial, **nm:** never-married, **oc:** own-child, **os:** other-service, **fw:** Final-Weight, **mx:** Mexico, **hn:** Holand-Netherlands, **unm:** unmarried, **nm:** never-married, **phl:** Philippines, **tt:** Trinadad&Tobago, **nif:** not-in-family, **ts:** tech-support , **seni:** self-emp-not-inc.

Global Feature Importance using XTab (No weight regularization is used)									
Runs	1	2	3	4	5	6	7	8	9	10
1	age	mcs	hpw	cg	en	em	cl	white	husband	nm
2	age	mcs	hpw	cg	en	cl	em	white	husband	nm
3	age	mcs	hpw	cg	en	em	cl	white	husband	nm
4	age	mcs	hpw	en	cg	cl	em	white	husband	nm
5	age	mcs	hpw	cg	en	cl	em	white	husband	nm
6	age	mcs	hpw	cg	en	em	cl	white	husband	nm
7	age	mcs	hpw	cg	en	cl	em	white	husband	nm
8	age	mcs	hpw	cg	en	cl	em	white	husband	nm
9	age	mcs	hpw	cg	en	cl	em	white	husband	nm
10	age	mcs	hpw	cg	en	em	cl	white	husband	nm

Global Feature Importance using Saliency Maps									
Runs	1	2	3	4	5	6	7	8	9	10
1	mcs	cg	en	age	cl	hpw	em	ps	seni	os
2	cg	hpw	age	mcs	nm	oc	wife	en	os	cl
3	cg	age	hpw	nm	oc	mcs	wife	os	em	cl
4	cg	age	hpw	nm	oc	en	mcs	wife	os	cl
5	cg	age	hpw	mcs	oc	nm	wife	cl	en	os
6	cg	hpw	age	nm	mcs	oc	wife	cl	os	ps
7	cg	hpw	age	mcs	nm	wife	oc	os	cl	en
8	cg	age	hpw	oc	mcs	wife	husband	os	cl	em
9	cg	age	mcs	nm	os	oc	wife	en	cl	husband
10	cg	age	mcs	hpw	nm	en	oc	wife	os	cl

Global Feature Importance using Integrated Gradient									
Runs	1	2	3	4	5	6	7	8	9	10
1	cg	mcs	age	nm	husband	hpw	en	oc	male	os
2	cg	mcs	age	nm	hpw	husband	oc	en	female	os
3	cg	mcs	age	nm	hpw	en	husband	oc	os	male
4	cg	mcs	nm	age	hpw	en	husband	oc	os	female
5	cg	mcs	age	nm	en	hpw	husband	oc	male	os
6	cg	mcs	age	hpw	nm	husband	oc	en	female	os
7	cg	mcs	age	hpw	nm	en	husband	oc	female	os
8	cg	mcs	nm	age	hpw	en	husband	oc	female	male
9	cg	mcs	nm	age	hpw	en	husband	oc	female	male
10	cg	mcs	age	nm	husband	hpw	en	oc	female	os

Global Feature Importance using L2X									
Runs	1	2	3	4	5	6	7	8	9	10
1	cg	nm	divorced	female	mcs	en	mx	male	uk	us
2	hpw	age	divorced	nm	en	hs-grad	nif	unm	mcs	Greece
3	cg	mcs	Columbia	en	nm	oc	unm	Italy	phl	Honduras
4	cg	age	hpw	nm	em	os	fg	male	hn	Italy
5	cg	age	nm	hpw	en	South	mcs	female	Italy	phl
6	nm	mafs	cg	female	Cambodia	em	Iran	Poland	Italy	phl
7	cg	nm	oc	ts	en	male	tt	ps	mcs	hc
8	cg	os	age	nm	en	ff	divorced	af	mx	Italy
9	cg	age	nm	hpw	en	South	mcs	female	Italy	phl
10	cg	oc	age	unm	en	Doctorate	Hong	nm	hn	South

Global Feature Importance using INVASE									
Runs	1	2	3	4	5	6	7	8	9	10
1	mcs	cg	age	en	hpw	husband	private	em	wife	cl
2	en	age	mcs	cg	hpw	husband	private	cl	fw	em
3	cg	en	age	hpw	female	wife	nif	divorced	us	cl
4	mcs	cg	en	age	hpw	em	private	male	cl	fl
5	cg	mcs	en	age	hpw	us	em	private	nif	cl
6	cg	mcs	en	age	hpw	fw	em	female	husband	bachelor
7	cg	age	en	hpw	mcs	female	us	wife	em	husband
8	cg	em	mcs	hpw	age	cl	private	husband	em	seni
9	en	cg	age	hpw	mcs	white	husband	fw	nm	private
10	mcs	em	age	cg	private	hpw	female	fw	husband	em

J.6   COMPARING VARIATIONS IN GLOBAL FEATURE IMPORTANCE OBTAINED FROM M_g WITH AND WITHOUT NOISE AT THE INPUT

Table A6: Consistency of the ranking across multiple runs of our framework using the following two cases; Gaussian noise added to the input (top table) and the input without the noise (bottom table). Abbreviations are; **ms:** marital status, **en:** education-num, **cg:** capital-gain, **hpw:** hours-per-week, **race:** race, **occ:** occupation, **rel:** relationship, **cl:** capital-loss, **nc:** native-country

Runs	\multicolumn{10}{c}{**Gaussian noise,** $p = 0.2$ **&** $\mathcal{N}(0, \sigma = 0.3)$**, added to the input**}									
	1	2	3	4	5	6	7	8	9	10
1	age	ms	hpw	en	cg	occ	race	rel	cl	nc
2	age	ms	hpw	en	cg	occ	race	rel	cl	nc
3	age	ms	hpw	en	cg	occ	race	rel	cl	nc
4	age	ms	hpw	en	cg	occ	race	rel	cl	nc
5	age	ms	hpw	en	cg	occ	race	rel	cl	nc
6	age	ms	hpw	en	cg	occ	race	rel	cl	nc
7	age	ms	hpw	en	cg	occ	race	rel	cl	nc
8	age	ms	hpw	en	cg	occ	race	cl	rel	nc
9	age	ms	hpw	cg	en	race	occ	rel	cl	nc
10	age	ms	hpw	cg	en	occ	race	rel	cl	nc

Runs	\multicolumn{10}{c}{**No noise added to the input**}									
	1	2	3	4	5	6	7	8	9	10
1	cg	age	ms	hpw	en	occ	race	cl	rel	nc
2	cg	ms	age	hpw	en	occ	cl	rel	race	nc
3	cg	age	ms	hpw	en	race	occ	cl	rel	nc
4	ms	age	cg	hpw	en	occ	race	rel	nc	cl
5	cg	ms	age	hpw	en	occ	race	cl	rel	nc
6	age	ms	cg	hpw	en	occ	race	rel	cl	nc
7	ms	age	cg	hpw	en	occ	race	rel	cl	nc
8	ms	age	cg	hpw	en	occ	cl	race	rel	nc
9	ms	age	cg	hpw	en	occ	cl	rel	race	nc
10	cg	ms	age	hpw	en	occ	race	rel	cl	nc

J.7   EXAMPLES OF INSTANCE-WISE IMPORTANCE FROM M_f FOR SIX SAMPLES FROM ADULT INCOME

Figure A18: Examples of instance-wise feature importance for five random samples from Adult Income dataset.

J.8 SHOWING ROBUSTNESS FOR THE INSTANCE-WISE IMPORTANCE FROM M_f FOR A SINGLE SAMPLE FROM ADULT INCOME ACROSS 10 DIFFERENT EXPERIMENTS

Figure A19: The robustness for the instance-wise importance from M_f for a single sample from Adult Income across 10 different experiments

K RESULTS FOR BLOG DATASET.

(a) Local Masks   (b) Global Mask as CA   (c) M_g

Figure A20: **Blog dataset:** Repeating the experiment with Income dataset (i.e. using shallow network, noisy input data) in Figure A14 (a-c) for Blog dataset. We also use weight-clipping ($[-0.2, 0.2]$).

We repeated the experiment that we did for Income dataset (using shallow network and noisy input data) in Figure A14 (a-d) for Blog dataset. Looking at the Figure A20 (a-c), features **f52** (number of comments in the last 24 hours before the basetime), **f54** (number of comments in the first 24 hours after the publication of the blog post, but before basetime), **f51** (total number of comments before basetime), and **f20** (the median of **f54**) are discovered to be the most important for classifying whether a blog post would receive a comment.

K.1 ROBUSTNESS OF PARAMETER AVERAGING

(a) No regularization   (b) Dropout (p=0.2)   (c) Weight-clipping

Figure A21: **Shallow network - Top row:** Variations in feature rankings across 20 local mask models when we apply **a)** no weight regularization, **b)** Dropout ($p = 0.2$), and **c)** Weight-clipping ($[-0.2, 0.2]$). **Bottom row**: Variations in feature rankings in 100 global models, each of which is obtained by averaging the parameters of 10 models bootstrapped from 20 local models for the same three cases.

L OTHER WAYS OF IMPLEMENTING OUR PROPOSED METHOD

In the final training in our framework, we use M_g as a reference mask while introducing another mask model to compensate for the potential sub-optimality introduced in M_g:

$$m_g = M_g(X) \text{ and } m_l = M_l(X) \tag{10}$$

$$m_f = (m_g + m_l)/C \text{ where } C = max(m_g + m_l) \text{ and } X_M = m_f{}^2 \odot X \tag{11}$$

However, the final mask, m_f, is only a scaled summation of the outputs from M_g and M_l. A better way to do this update can be using a gating mechanism similar to input and forget gates in LSTM (Hochreiter & Schmidhuber, 1997). This would enable the model to forget the weights of some features in m_g while adding more weights to others through m_l in the following way:

$$m_f = \sigma(f \odot m_g + i \odot m_l) \tag{12}$$

where σ is the sigmoid function. We leave the idea of gated masks as a future work.

M BROADER IMPACT

The estimation of feature ranking in many areas such as in healthcare, finance and insurance is critical in decision making process. While taking advantage of neural nets in these applications is important, we should be mindful of consistency and robustness of our methods. Our proposed method makes a contribution towards achieving a robust estimation of feature ranking. However, we should be aware of the limits and shortcomings of our approach as well as other similar approaches.