Extracting Strong Policies for Robotics Tasks from Zero-Order Trajectory Optimizers

ABSTRACT

Solving high-dimensional, continuous robotic tasks is a challenging optimization problem. Model-based methods that rely on zero-order optimizers like the cross-entropy method (CEM) have so far shown strong performance and are considered state-of-the-art in the model-based reinforcement learning community. However, this success comes at the cost of high computational complexity, being therefore not suitable for real-time control. In this paper, we propose a technique to jointly optimize the trajectory and distill a policy, which is essential for fast execution in real robotic systems. Our method builds upon standard approaches, like guidance cost and dataset aggregation, and introduces a novel adaptive factor which prevents the optimizer from collapsing to the learner's behavior at the beginning of the training. The extracted policies reach unprecedented performance on challenging tasks like making a humanoid stand up and opening a door without reward shaping.

Figure 1: Environments and exemplary behaviors of the learned policy using APEX. From left to right: FETCH PICK&PLACE (sparse reward), DOOR (sparse reward), and HUMANOID STANDUP.

1 INTRODUCTION

The general purpose of model-based and model-free reinforcement learning (RL) is to optimize a trajectory or find a policy that is fast and accurate enough to be deployed on real robotic systems.

Policies optimized by model-free RL algorithms achieve outstanding results for many challenging domains (Heess et al., 2017; Andrychowicz et al., 2020), however, in order to converge to the final performance, they require a large amount of interactions with the environment and can hardly be used on real robots, which have a limited lifespan. Moreover, real robotic systems are high-dimensional and have a highly non-convex optimization landscape which makes policy gradient methods prone to converge to locally optimal solutions. In addition, model-free RL methods only gather task-specific information which inherently limits their generalization performance to new situations.

On the other hand, recent advances in model-based RL show that it is possible to match model-free performances by learning uncertainty-aware system dynamics (Chua et al., 2018; Deisenroth & Rasmussen, 2011; Du et al., 2019). The learned model can then be used within a model-predictive control framework for trajectory optimization. Zero-order optimizers are gaining a lot of traction in the model-based RL community (Chua et al., 2018; Wang & Ba, 2020; Williams et al., 2015) since they can be used with any choice of model and cost function, and can be surprisingly effective in finding high-performance solutions (Pinneri et al., 2020) (close to a global optimum) in contrast to their gradient based counterparts, which are often highly dependent on hyperparameter tuning (Henderson et al., 2017). One of the most popular optimizers is the Cross-Entropy Method (CEM), originally introduced in the 90s by Rubinstein & Davidson (1999).

Despite their achievements, using zero-order methods for generating action sequences is highly time inefficient in complex high-dimensional environments, due to the extensive sampling, making it impossible to deploy them for real-time applications.

Extracting a policy from powerful zero-order optimizers like CEM would bridge the gap between model-based RL in simulation and real-time robotics. As of today, this is still an open challenge (Wang & Ba, 2020).

We analyse this issue and showcase several approaches for policy extraction from CEM. In particular, we will use the sample-efficient modification of CEM (iCEM) presented in Pinneri et al. (2020). In order to isolate the problem of bringing policy performance close to the expert's one, we consider the true simulation dynamics as our forward model.

Our contributions can be summarized as follows:

- pinpointing the issues that arise when trying to distill a policy from a multimodal, stochastic teacher;
- introducing APEX, an Adaptive Policy EXtraction procedure that integrates iCEM with DAgger and a novel adaptive variant of Guided Policy Search;
- producing an improving adaptive teacher, with higher performance than the original iCEM optimizer;
- obtaining strong policies for hard robotic tasks in simulation (HUMANOID STANDUP, FETCH PICK&PLACE, HALFCHEETAH RUNNING, DOOR), where model-free policies would usually just converge to local optima.

Videos showing extracted policies' performances can be found at `https://sites.google.com/view/adaptive-policy-extraction`. The source code will be made available with the final version of the paper.

2 RELATED WORK

Our objective is to extract high-performing policies from CEM experts that can operate with few planning samples in order to make iterative learning fast. Other kinds of zero-order optimizers have been used to generate control sequences (Williams et al., 2015; Lowrey et al., 2019) but they still have to evaluate thousands of trajectories for each time step. Even simple random shooting has been used as a trajectory optimizer to bootstrap a model-free policy (Nagabandi et al., 2018).

In order to train policies from optimal control solutions, it was shown that the expert optimizers need to be guided towards the learning policy – known as guided policy search (GPS) (Levine & Koltun, 2013; Levine & Abbeel, 2014). In our work, the expert does not come from optimal control, but is the stochastic iCEM optimizer, which we will also refer to as teacher. We apply GPS in a model model-predictive control setting, as done in Levine & Koltun (2013); Mordatch & Todorov (2014); Mordatch et al. (2015); Zhang et al. (2016); Kahn et al. (2017); Sun et al. (2018) using local trajectory optimization to generate a dataset for training a global policy through imitation learning. These approaches alternate between training a policy and creating new data with a model-based supervisor guided towards the learner, which was formalized in Sun et al. (2018).

Stochastic experts require particular guidance strategies, such as an **adaptive cost** formulation that we propose here and warm-starting, as done in Wang & Ba (2020).

Recently, approaches like simple point-to-point supervised training as Behavioral Cloning (BC), or Generative Adversarial Network training (GAN) have been explored (Wang & Ba, 2020) for policy distillation from CEM, but only largely sub-optimal policies could be extracted. When the policy is used alone at test time and not in combination with the MPC-CEM optimizer, its performance drops significantly, becoming almost random for some environments. We argue that the reason behind the difficulty in distilling a policy from CEM expert data is the multimodality of the CEM solution space and its inherent stochasticity due to the sampling, which we address below.

Another possibility to train higher-performance policies from experts is DAgger (Ross & Bagnell, 2010), which is an on-policy method, asking the expert to relabel/correct policy actions. Nevertheless, as we will show in the following sections, DAgger alone is not sufficient to extract high-performing

policies in our setting. In order to solve this problem, we use a guiding cost in combination with DAgger. A combination of GPS and DAgger-style relabeling was proposed in PLATO (Kahn et al., 2017), however for the purpose of creating unbiased training data from iLQG experts. Since unguided DAgger is not appropriate with CEM, PLATO is not successful in our setting either. The components of our algorithm will be explained in the following sections.

3 METHODS

The aim of trajectory optimization is to find a suitable action sequence $\vec{a}_t = (a_t, a_{t+1}, \ldots, a_{t+h})$ of horizon h that minimizes a cost function $f(\vec{a}_t, s_t)$, where s_t is the current state of the system. i.e.

$$\vec{a}_t^\star \leftarrow \arg\min_{\vec{a}_t} f(\vec{a}_t, s_t). \tag{1}$$

The cost function f encodes the task. Optimal control is obtained if f is the trajectory cost until step h plus the cost-to-go under the optimal policy for an infinite-horizon problem, evaluated at the last state in the finite horizon trajectory.

3.1 IMPROVED CROSS-ENTROPY METHOD FOR MPC

To optimize Eq. 1 we use a variant of the Cross-Entropy Method. Although originally introduced as an adaptive importance sampling procedure to estimate rare-event probabilities, it was recently employed in model-based RL (Chua et al., 2018; Wang & Ba, 2020) as a trajectory optimizer.

A practical implementation of CEM uses a Gaussian proposal distribution over the optimization variables $\vec{a}$, $\mathcal{N}(\mu, \sigma)$, evaluates the cost function $f(\vec{a})$, and refits this distribution iteratively by using the top-k samples. It finds low-cost regions of f and high-performing samples of the variable $\vec{a}$. The cost function can be either expressed through a learned value function or through the dynamics model of the system, which in turn can be learned from data or in analytical form. In the model-predictive control (MPC) framework, CEM can be used at every time-step to generate the optimal action plan, of which only the first action is executed, and the whole procedure is repeated for the next steps until task completion.

In this paper we will make use of iCEM, a sample-efficient improvement of CEM by Pinneri et al. (2020) that makes use of *colored-noise* and memory. In particular, it generates correlated action sequences with a non-flat frequency spectrum, differently from the flat Gaussian noise of CEM. This, together with the memory addition, results in an order of magnitude sample reduction.

3.1.1 USING A POLICY TO INFORM THE OPTIMIZATION: iCEM$_\pi$

Unguided search for action sequences can be hard, in particular if the cost function has large flat regions (sparse rewards). Since we aim at extracting a policy $\pi(s)$, we can expect that after some examples the policy can be used to guide the search into the right region. Thus, we warm-start the mean μ of the iCEM Gaussian distribution with the policy actions. In particular, at time $t = 0$ where no prior information exists, the mean is initialized from rolling out the trajectory with the policy until the planning horizon: $\mu \leftarrow (\pi(s_0), \pi(s_1), \ldots \pi(s_h))$. Whenever the action for a new step is computed, iCEM uses shift initialization of the mean, and only the mean-action at the end of the horizon is initialized from the policy. The warm-started iCEM algorithm is called iCEM$_\pi$ and is shown in Alg. 1.

3.2 OFF- AND ON-POLICY IMITATION LEARNING

How difficult is to clone a policy from iCEM$_\pi$? Using a basic off-policy method like Behavioral Cloning (BC), which simply does point-to-point L2 loss minimization, does not work out-of-the-box. This is because during test time, the policy visits state-space regions for which it never received any expert feedback, and it consequently fails. This problem is also known as "covariate shift". The performance gap (difference in cost to go) between the expert and the policy scales quadratically in time due to the covariate shift (Ross & Bagnell, 2010).

A classical way to address this problem is with on-policy imitation learning. DAgger (Dataset Aggregation) by Ross et al. (2011) is the most popular example. DAgger works by iteratively rolling

Algorithm 1: Improved Cross-Entropy Method with warm-starting from policy π: (iCEM$_\pi$).
Color blue marks the policy warm-starting.

Input: $f(\vec{a}, s)$: cost function; π: policy; N: # of samples; h: planning horizon; k: elite-set size; β: colored-noise exponent; σ_{init}: noise strength; *iter*: # of iterations; γ: reduction factor.

1   $\tau \leftarrow \emptyset$
2   **for** $t = 0$ *to* $T{-}1$ **do**
3     $s \leftarrow$ get current state from environment
4   **if** $t == 0$ **then**
5       $\mu_0 \leftarrow h$-steps rollout of model with π starting from s
6   **else**
7       $\mu_t \leftarrow$ shifted μ_{t-1} with last time-step action given by π
8     $\sigma_t \leftarrow$ constant vector in $\mathbb{R}^{d \times h}$ with values σ_{init}
9   **for** $i = 0$ *to* *iter*-1 **do**
10       $N_i \leftarrow \max(N \cdot \gamma^{-i}, 2 \cdot k)$
11   samples $\leftarrow N_i$ samples from clip$(\mu_t + \mathcal{C}^\beta(d, h) \odot \sigma_t^2)$;   // with $\mathcal{C}^\beta(d, h)$ colored-noise
             Normal distribution with noise-exponent β and dimension (d, h)
12   add fraction of shifted/reused elite-set to samples
13   **if** $i == last\text{-}iter$ **then**
14   add μ_i to samples
15   add policy actions to samples ;   // h-step rollout with policy from current state s
16   costs $\leftarrow$ cost function $f(\vec{a}, s)$ for $\vec{a}$ in samples
17   elite-set$_t \leftarrow$ best k samples according to costs
18       $\mu_t, \sigma_t \leftarrow$ fit Gaussian distribution to elite-set$_t$ with momentum
19     $a \leftarrow$ first action of best elite sequence
20   add (s, a) to τ
21   execute a
22   **return** τ;   // return the trajectory

Figure 2: Variance of DAgger actions when relabeling 10 times the same trajectory in case of unguided iCEM (a) vs. guided iCEM$_\pi$(b), for the FETCH PICK&PLACE task. The action variance of iCEM is considerably higher than the one of iCEM$_\pi$-GPS guided by the shown policy (std-dev=0.30 vs 0.13). The policy π is trained from a single expert rollout.

out the current policy, querying the expert for the correct actions (also called relabeling) on the states visited by the policy, and training the policy on the aggregate dataset across all iterations. The covariate shift is alleviated by populating the data with states visited by previous iterations of the policy.

ISSUES OF STOCHASTIC TEACHERS: Nevertheless, some problems arise when considering population-based optimizers as experts, both for BC alone or in combination with DAgger. The optimized action sequence of CEM might converge to different solutions every time it is asked to relabel the policy actions. Naturally, there are many actions that can result in an equally high-performing solution. As an example: in the Fetch Pick & Place task, well before grasping the box, the action of opening or closing the gripper can be arbitrary, as long as the action of opening the gripper is executed on time. To illustrate this problem we analyze the variance of the relabeled actions produced by the same expert on a fixed state sequence. The variance is high, spanning over a third of the action-space, as can be seen in Fig. 2(a).

3.3 GUIDED POLICY SEARCH

In order to lift some of the aforementioned problems the expert can be guided using the current policy. For high-dimensional control tasks, in addition to the high variance (Fig. 2(a)), zero-order optimizers may also find multiple different solutions, leading to multi-modal training data. This prohibits a successful policy extraction through supervised learning. To address these issues, the cost function f in Eq. 1 becomes the main cost J (task) plus a guidance cost to bias the optimizer's solution towards the policy:

$$\vec{a}_t^\star \leftarrow \arg\min_{\vec{a}_t} J_t(\vec{a}_t, s_t) + \lambda D_{\mathrm{KL}}(\pi_\theta || \vec{a}_t), \tag{2}$$

which is also known as Guided Policy Search (GPS) (Levine & Koltun, 2013). When competing solutions arise, the one closer to the policy is preferred, tackling in this way the problem of multi-modality and creating much more consistent training data. As a remark, in our experiments we use deterministic policies which reduces the KL-divergence to a squared difference between the actions.

In addition to Eq. 2, we further guide iCEM by warm-starting it from the policy, as implemented in iCEM$_\pi$ (Alg. 1). As a consequence, both together lead to a reduced action variance, as seen in Fig. 2(b). For an illustrative state sequence, the standard deviation of expert actions drops from $\sigma = 0.30$ without guidance to $\sigma = 0.13$.

When combining GPS with DAgger we use the same cost-function (Eq. 2) for both expert rollouts and actions relabeling. This is in contrast to PLATO (Kahn et al., 2017), designed for iLQG experts, where the guidance cost is only for the expert. Also, in PLATO the policy is not executed to collect new data, but only the guided expert is relabeled using the expert with an unmodified cost to collect optimal training data. For zero-order optimizers, unguided solutions are not helpful as shown above. Without relabeling the actual policy rollouts, we found PLATO not to work in our settings.

The hyperparameter λ in Eq. 2 is difficult to choose. It might be adapted according to learning progress or other heuristics. However, when using the guided cost in CEM other considerations also have to be made which lead to a simple adaptation scheme introduced in the next section.

3.4 ADAPTIVE AUXILIARY COST WEIGHTING

The purpose of λ is to trade-off the potential loss in cost by staying close to the policy. Generalizing Eq. 2, we can phrase the cost function f in Eq. 1 as the sum of the main cost J and a set of auxiliary costs C_j^{aux}:

$$\vec{a}_t^\star \leftarrow \arg\min_{\vec{a}_t} J_t(\vec{a}_t, s_t) + \sum_j \lambda_j C_j^{\mathrm{aux}}(\vec{a}_t, s_t) \tag{3}$$

Examples of the auxiliary costs are the guidance cost as in Eq. 2 and the action norm $\|\vec{a}\|$ to prefer small action magnitudes. We follow the philosophy that the auxiliary costs are subordinate and should only bias the solutions without causing a large performance drop. This leads to the idea that the auxiliary costs should never dominate the optimization. Since the costs might vary by orders of magnitude, we opt for a formulation where the auxiliary costs can maximally lead to a fixed fractional loss in performance.

As a motivating example, let us consider hard tasks that present flat regions in the cost function: in this case a non-zero λ can lead to a failure of guided CEM to find any good solution. How is that possible? Let us consider the Fetch Pick & Place task as shown in Fig. 1. When none of the sampled action-sequences moves the box (which is quite likely in the first CEM iteration) then all sequences are equivalent under the main cost. Elites (Alg. 1 line 17) are only selected based on the auxiliary costs which leads to a quick reduction in sampling variance and no good solution is ever found. To illustrate this phenomenon, Fig. 3 displays the sampling distribution of iCEM$_\pi$ over the course of the optimization iterations (line 9 in Alg. 1). Using a fixed λ (iCEM$_\pi$-fixed λ) typically converges to the policy action which is often unsuccessful in a new situation or when the policy is still weak.

We propose the following adaptation of λ_j:

$$\lambda_j = c_j \frac{\mathcal{R}(J)}{\mathcal{R}(C_j^{\mathrm{aux}}) + \epsilon} \tag{4}$$

Figure 3: Adaptively guided iCEM$_\pi$ successfully solves challenging object manipulation task with partially sparse reward. **(a)** Effect of adaptive λ on CEM proposal distributions for the Pick & Place task. The action sampling distribution is shown over the iCEM-iterations (at a predefined time-step) and one of the 4 action-dimensions when guiding with a weak policy. Dashed lines indicate the action of the policy and of a high compute-budget iCEM expert. Only with adaptive λ the search of a low compute-budget iCEM is converging to a good action. Fixed λ shifts the distribution too early, resulting in a collapse to the policy behavior and failure to find a good solution. **(b)** Average success rate of low compute-budget iCEM$_\pi$ expert over 800 episodes. Fixed λ severely hampers the performance. Adaptive λ can yield the desired effect that the guided iCEM finds better solutions than the unguided one.

where c_j is the new hyperparameter, $0 < \epsilon$ is a small regularization to avoid amplifying tiny auxiliary costs, and $\mathcal{R}(C)$ represents the cost-range of C in the elite set:

$$\mathcal{R}(C) = \max_{\text{elite-set}} C - \min_{\text{elite-set}} C \,. \tag{5}$$

This formulation ensure that λ_i is zero if the main cost J cannot be improved by the preliminary elite-set (as in the example above). When an actual improvement is possible and the cost landscape is not flat ($R(J) > 0$), the auxiliary cost influences up to a fixed fraction (c_j) of the cost-range. Thus, the sampling distribution for the adaptive case will converge only if a good solution is found, as visualized in Fig. 3 (a) (iCEM$_\pi$-GPS adaptive λ) for one auxiliary cost being the KL-term as in Eq. 2.

TEACHER IMPROVEMENT: Another effect of the adaptive guidance is the improvement of the same teacher, which is not common nor expected in standard imitation learning. The increased success-rate is shown in Fig. 3 (b). As we can see from the plot, the guidance alone is not sufficient to reach the original iCEM expert performance: when the auxiliary cost becomes adaptive, the iCEM benefits from the policy and is able to exploit it only in crucial moments.

3.5 PUTTING THE PIECES TOGETHER: APEX

Our method, named Adaptive Policy EXtraction (APEX), uses adaptive policy-guided iCEM$_\pi$ and DAgger using the same expert to create data for successful training of policies in an iterative fashion.

The main steps are: create data from guided expert, update the policy, rollout the policy and relabel the actions using the same expert (DAgger), add the relabeled data to the dataset and update the policy. This iterates until the desired performance is reached. More details are found in the pseudo-code in Alg. 2.

4 RESULTS

Can strong policies be obtained from model-based planning and imitation learning? By considering high-dimensional challenging robotics environments, some of them with sparse rewards, we test APEX and find that the answer is yes. In some cases we considerably improve the state-of-the-art currently held by model-free methods.

We perform our experiments on a selection of 4 environments, listed below, which use the MuJoCo (Todorov et al., 2012) physics engine:

Algorithm 2: Adaptive Policy EXtraction procedure (APEX)

Input: iCEM$_\pi$; π_θ: policy network; n: # rollouts per iteration

1 init θ randomly
2 $\mathcal{D} \leftarrow \emptyset$
3 $i \leftarrow 1$
4 **while** *not converged* **do**
5 $\quad f(\vec{a}, s) \leftarrow J_t(\vec{a}, s_t) + \lambda_1 D_{\text{KL}}(\pi_\theta \| \vec{a}) + \lambda_2 \|\vec{a}\|$;   // see Eqns. 2, 3, and 4
6 $\quad \tau_{\text{CEM}} \leftarrow n$ Rollout with iCEM$_\pi(f(\vec{a}, s), \pi_\theta)$;   // τ is the resulting trajectory
7 $\quad$ add τ_{CEM} to $\mathcal{D}$
8 $\quad \theta \leftarrow$ train policy π_θ on $\mathcal{D}$
9 $\quad \tau_\pi \leftarrow$ Rollout with π_θ
10 $\quad \tau_{\text{DAgger}} \leftarrow$ relabel actions in τ_π with iCEM$_\pi(f(\vec{a}, s), \pi_\theta)$;   // DAgger
11 $\quad$ add τ_{DAgger} to $\mathcal{D}$
12 $\quad \theta \leftarrow$ train policy π_θ on $\mathcal{D}$
13 $\quad i \leftarrow i + 1$;   // one APEX iteration
14 **return** π_θ

HUMANOID STANDUP: (OpenAI Gym Brockman et al. (2016) v2) A humanoid robot is initialized in a laying position. The goal is to stand-up without falling, i.e. reaching as high as possible with the head. We use a task horizon of 500.

FETCH PICK&PLACE (sparse reward): (OpenAI Gym v1) A robotic manipulator has to move a box, randomly placed on a table, to a randomly selected target location. The reward is only the negative Euclidean distance between box and target location, so without moving the box there is no reward.

DOOR (sparse reward): (DAPG[1] project Rajeswaran et al. (2018)) A simulated 24 degrees of freedom ShadowHand has to open a door with a handle. The reward is the sum of door opening, a quadratic penalty on the velocities, and a bounty for opening the door (in contrast to Rajeswaran et al. (2018) there is guidance of the hand to the handle).

HALFCHEETAH RUNNING: (OpenAI Gym v3) A half-cheetah agent should maximize its velocity in the positive x-direction. In contrast to the standard setting, we prohibit a rolling motion of the cheetah by heavily penalizing large absolute angles of the root joint. In the standard setting numeric instabilities in the simulator are exploited by iCEM.

In Fig. 4, we compare APEX against several imitation learning baselines: Behavioral Cloning (BC) (iCEM BC), DAgger (iCEM DAgger), and BC from iCEM$_\pi$ with guidance cost (fixed λ) and warm-starting (iCEM$_\pi$-GPS). For reference, we also provide performance of SAC[2] (Haarnoja et al., 2018) as a model-free RL baseline, to get an idea of the difficulty of the learning tasks. Note that we use partially sparse rewards settings in FETCH PICK&PLACE (only box to goal reward) and DOOR (sparse reward) (no hand-to-handle reward) which makes them particularly challenging. However, for FETCH PICK&PLACE, a specialized method for goal-reaching tasks using hindsight relabeling (DDPG+HER) (Andrychowicz et al., 2017) is able to solve the task. In HUMANOID STANDUP the performance of SAC marks the behavior of just sitting. This is a local optima and is hard to escape for gradient based methods. APEX manages to stand up but cannot balance for long, presumably because there is a large variety in the ways the robot can fall. Notably, the DOOR environment, with its 24 DoF Shadow hand, is solved by our method with high success-rate.

A very interesting effect of our approach is that the iCEM$_\pi$ expert working inside of APEX improves with the policy, as seen in Fig. 4 (right). As expected, with raising compute-budget of iCEM, the unguided experts get high performance. However, when guided with a policy the performance raises (dashed blue lines) with the policy performance, even if the policies themselves are not very strong yet. Together, APEX is able to shrink the gap between expert and policy performance and yields strong results, see also the illustrative behaviors in Fig. 1.

---

[1] https://github.com/aravindr93/hand_dapg
[2] We took the implementation from https://github.com/vitchyr/rlkit

Figure 4: Policy performance on the test environments for APEX and baselines. SAC performance is provided for reference. Right panels show the performance of the policy and the expert (dashed lines) for 3 different compute-budgets, marked with $(-, +)$. Due to warm-starting, experts improve with the policy.

Figure 5: Ablation experiments. We remove different components of the APEX algorithm, see legend.

Are all components of APEX required? We perform several ablations to investigate this question. Figure 5 shows the performance when removing each individual component from APEX. Using the adaptive guidance cost instead of a *fixed* λ is only important in the sparse reward environments, as expected. Removing warm-starting has a drastic effect in all environments. Not adding policy samples to the optimization has counter-intuitive effects in HALFCHEETAH RUNNING: it performs initially better than with adding the samples, but the experts do not improve with the policy in this case such that the asymptotic performance is lower. APEX without DAgger is also much worse. Not using GPS is not shown, but has very low performance.

5 CONCLUSIONS

We study the problem of policy extraction from model-based trajectory optimizers using CEM – a zero-order blackbox method – popular in recent model-based RL. Our method (APEX) is able to extract strong policies for hard robotic tasks which are especially challenging for model-free RL methods. This is achieved by imitation learning from a guided CEM expert, where both policy and expert mutually propel themselves to higher performances.

With this work, we want to propose a promising stepping stone towards learning high-performing policies for real robots, where speed and minimal interaction with the system are more important than asymptotic performance. Model-based RL methods have been shown to be very sample efficient (Chua et al., 2018; Wang & Ba, 2020) in terms of actual environment interactions, but are too slow to run realtime yet. With the recently proposed improved CEM (Pinneri et al., 2020), the possibility for real-time planning became feasible, but still needs huge computational resources. Extracting high performing policies is a promising route to success, where we provide here an important ingredient. Although we are using the simulator as internal model to study the policy extraction problem in isolation, we believe our method will transfer to the model-based RL setup with learned models. For real systems, models and policies could also be pretrained in simulation and then adapt to the real system.

REFERENCES

Marcin Andrychowicz, Filip Wolski, Alex Ray, Jonas Schneider, Rachel Fong, Peter Welinder, Bob McGrew, Josh Tobin, OpenAI Pieter Abbeel, and Wojciech Zaremba. Hindsight experience replay. In *Advances in Neural Information Processing Systems*, pp. 5048–5058, 2017.

OpenAI: Marcin Andrychowicz, Bowen Baker, Maciek Chociej, Rafal Jozefowicz, Bob McGrew, Jakub Pachocki, Arthur Petron, Matthias Plappert, Glenn Powell, Alex Ray, et al. Learning dexterous in-hand manipulation. *The International Journal of Robotics Research*, 39(1):3–20, 2020.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. OpenAI gym. *arXiv preprint arXiv:1606.01540*, 2016.

Kurtland Chua, Roberto Calandra, Rowan McAllister, and Sergey Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. In *NeurIPS*, 2018.

Marc Peter Deisenroth and Carl Edward Rasmussen. Pilco: A model-based and data-efficient approach to policy search. In *International Conference on Machine Learning (ICML)*, 2011.

Yilun Du, Toru Lin, and Igor Mordatch. Model based planning with energy based models. *Conference on Robot Learning (CoRL)*, 2019.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, volume abs/1801.01290, pp. 1856–1865, 2018.

Nicolas Heess, Dhruva TB, Srinivasan Sriram, Jay Lemmon, Josh Merel, Greg Wayne, Yuval Tassa, Tom Erez, Ziyu Wang, SM Eslami, et al. Emergence of locomotion behaviours in rich environments. *arXiv preprint arXiv:1707.02286*, 2017.

Peter Henderson, Riashat Islam, Philip Bachman, Joelle Pineau, Doina Precup, and David Meger. Deep reinforcement learning that matters, 2017. cite arxiv:1709.06560Comment: Accepted to the Thirthy-Second AAAI Conference On Artificial Intelligence (AAAI), 2018.

Gregory Kahn, Tianhao Zhang, Sergey Levine, and Pieter Abbeel. Plato: Policy learning using adaptive trajectory optimization. In *IEEE International Conference on Robotics and Automation (ICRA)*, 2017.

Sergey Levine and Pieter Abbeel. Learning neural network policies with guided policy search under unknown dynamics. In Z. Ghahramani, M. Welling, C. Cortes, N. D. Lawrence, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 27*, pp. 1071–1079. Curran Associates, Inc., 2014.

Sergey Levine and Vladlen Koltun. Guided policy search. In *International Conference on Machine Learning (ICML)*, 2013.

Kendall Lowrey, Aravind Rajeswaran, Sham Kakade, Emanuel Todorov, and Igor Mordatch. Plan online, learn offline: Efficient learning and exploration via model-based control. In *International Conference on Learning Representations (ICLR)*, 2019.

Igor Mordatch and Emanuel Todorov. Combining the benefits of function approximation and trajectory optimization. In *Robotics: Science and Systems*, 2014.

Igor Mordatch, Kendall Lowrey, Galen Andrew, Zoran Popovic, and Emanuel V. Todorov. Interactive control of diverse complex characters with neural networks. In C. Cortes, N. D. Lawrence, D. D. Lee, M. Sugiyama, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, NeurIPS'15, pp. 3132–3140. 2015.

A. Nagabandi, G. Kahn, R. S. Fearing, and S. Levine. Neural network dynamics for model-based deep reinforcement learning with model-free fine-tuning. In *IEEE International Conference on Robotics and Automation (ICRA)*, pp. 7559–7566, May 2018.

Cristina Pinneri, Shambhuraj Sawant, Sebastian Blaes, Jan Achterhold, Joerg Stueckler, Michal Rolinek, and Georg Martius. Sample-efficient cross-entropy method for real-time planning, 2020.

Aravind Rajeswaran, Vikash Kumar, Abhishek Gupta, Giulia Vezzani, John Schulman, Emanuel Todorov, and Sergey Levine. Learning Complex Dexterous Manipulation with Deep Reinforcement Learning and Demonstrations. In *Proceedings of Robotics: Science and Systems (RSS)*, 2018.

Stéphane Ross and Drew Bagnell. Efficient reductions for imitation learning. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 661–668, 2010.

Stéphane Ross, Geoffrey Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 627–635, 2011.

Reuven Rubinstein and William Davidson. The cross-entropy method for combinatorial and continuous optimization, 1999.

Wen Sun, Geoffrey J. Gordon, Byron Boots, and J. Andrew Bagnell. Dual policy iteration. In *NeurIPS*, 2018.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 5026–5033. IEEE, 2012.

Tingwu Wang and Jimmy Ba. Exploring model-based planning with policy networks. In *International Conference on Learning Representations (ICLR)*, 2020.

Grady Williams, Andrew Aldrich, and Evangelos Theodorou. Model predictive path integral control using covariance variable importance sampling. *ArXiv*, abs/1509.01149, 2015.

Tianhao Zhang, Gregory Kahn, Sergey Levine, and Pieter Abbeel. Learning deep control policies for autonomous aerial vehicles with mpc-guided policy search. In *IEEE International Conference on Robotics and Automation (ICRA)*, pp. 528–535, 2016.

APPENDIX

We report the performance numbers for our experiments in Tab. 1, while the expert/teacher settings are indicated in Tab. 2, and policy settings are in Tab. 3.

Table 1: Performances for all environments for APEX and APEX policy. We report the cumulative reward (marked with [1]) and the success rate (marked with [2]). For an explanation about the budget, see Pinneri et al. (2020),

Envs	APEX $^-$ (budget 45)		APEX (budget 100)		APEX $^+$ (budget 300)	
	Expert	Policy	Expert	Policy	Expert	Policy
HALFCHEETAH RUNNING[1]	5.26k	4.27k	7.11k	4.69k	9.1k	5.2k
HUMANOID STANDUP[1]	147.8k	72.7k	182.6k	81.4k	203.9k	78.7k
FETCH PICK&PLACE[2]	0.876	0.51	0.94	0.59		
DOOR[2]	1.0	0.95				

Table 2: APEX Expert settings (The values for colored noise exponent for different environments are taken from (Pinneri et al., 2020))

	# elites K	initial std. σ_{init}	momentum α	decay γ	fraction reused elites ζ	Guidance scaling constant c
iCEM	10	0.5	0.1	1.25	0.3	0.025
0.01 (FETCH PICK&PLACE)
iCEM$_\pi$	10	0.5	0.1	1.25	0.3	0.025
0.01 (FETCH PICK&PLACE)

	# rollouts per iteration n	Warm Start	Add Policy Sample	horizon h
iCEM	1 (HALFCHEETAH RUNNING)
1 (HUMANOID STANDUP)
10 (DOOR), 25 (FETCH PICK&PLACE)	False	False	30
iCEM$_\pi$	1 (HALFCHEETAH RUNNING)
1 (HUMANOID STANDUP)
10 (DOOR), 25 (FETCH PICK&PLACE)	True	True	30

Table 3: Policy settings

	# layers	size	Activation fn	l1 reg.	l2 reg.
iCEM$_\pi$/APEX	3	128	ReLu	0.000001	0.00001

	optimizer	learning rate	batch size	iterations	Length of rollout buffer
iCEM$_\pi$/APEX	Adam	0.0005	1024	1000	50 (HALFCHEETAH RUNNING)
100 (HUMANOID STANDUP)
150 (FETCH PICK&PLACE)
100 (DOOR)