SHAPE OR TEXTURE: UNDERSTANDING DISCRIMINATIVE FEATURES IN CNNS

ABSTRACT

Contrasting the previous evidence that neurons in the later layers of a Convolutional Neural Network (CNN) respond to complex object shapes, recent studies have shown that CNNs actually exhibit a 'texture bias': given an image with both texture and shape cues (e.g., a stylized image), a CNN is biased towards predicting the category corresponding to the texture. However, these previous studies conduct experiments on the *final classification output* of the network, and fail to robustly evaluate the bias contained (i) in the latent representations, and (ii) on a per-pixel level. In this paper, we design a series of experiments that overcome these issues. We do this with the goal of better understanding what type of shape information contained in the network is discriminative, where shape information is encoded, as well as when the network learns about object shape during training. We show that a network learns the majority of overall shape information at the first few epochs of training and that this information is largely encoded in the last few layers of a CNN. Finally, we show that the encoding of shape does not imply the encoding of localized per-pixel semantic information. The experimental results and findings provide a more accurate understanding of the behaviour of current CNNs, thus helping to inform future design choices.

1 INTRODUCTION

Convolutional neural networks (CNNs) have achieved unprecedented performance in various computer vision tasks, such as image classification (Krizhevsky et al., 2012; Simonyan & Zisserman, 2015; He et al., 2016), video classification (Karpathy et al., 2014; Yue-Hei Ng et al., 2015), object detection (Ren et al., 2015; He et al., 2017) and semantic segmentation (Long et al., 2015; Chen et al., 2017). Despite their black box nature, various studies have shown that early layers in CNNs activate for low-level patterns, like edges and blobs, while deeper layers activate for more complex and high-level patterns (Zeiler & Fergus, 2014; Springenberg et al., 2014). The intuition is that this hierarchical learning of latent representations allows CNNs to recognize complex object shapes to correctly classify images (Kriegeskorte, 2015). In contrast, recent works (Brendel & Bethge, 2019; Hermann & Lampinen, 2020) have argued that CNNs trained on ImageNet (IN) (Deng et al., 2009) classify images mainly according to their *texture*, rather than object *shape*. These conflicting results have large implications for the field of computer vision as it suggests that CNNs trained for image classification might be making decisions based largely off spurious correlations rather than a full understanding of different object categories.

One example of these spurious correlations is how the Inception CNN (Szegedy et al., 2015) recognizes the difference between 'Wolf' and 'Husky', based on whether there is snow in the background (Tulio Ribeiro et al., 2016). Recognizing object shapes is important for the generalization to out-of-domain examples (e.g., few-shot learning), as shape is more discriminative than texture when texture-affecting phenomena arise, such as lighting, shading, weather, motion blur, or when switching between synthetic and real data. In addition to performance, identifying the discriminative features that CNNs use for decision making is critical for the transparency and further improvements of computer vision models. While the model may achieve good performance for a certain task, it cannot communicate to the user about the *reasons* it made certain predictions. In other words, successful models need to be good, and interpretable (Lipton, 2019). This is crucial for many domains where causal mechanisms should play a significant role in short or long-term decision making such as healthcare (e.g., what in the MRI indicates a patient has cancer?).

Additionally, if researchers intend for their algorithms to be deployed, there must be a certain degree of *trust* in the decision making algorithm as public stakeholders are wary of systems which they cannot fully understand (Stack, 2011; Tulio Ribeiro et al., 2016), limiting the capability of CNNs to have real world impact.

One downside of the increasing abstraction capabilities of deep CNNs is the lack of interpretability of the latent

Stylized image   GT   Shape   Semantic

Figure 1: A shape biased model (trained on Stylized ImageNet) makes decisions based on the object's *shape*, or does it? Extracting binary and semantic segmentation features with a one convolutional layer read-out module shows that, while the model encodes the full object *shape*, it fails to attribute the correct *semantic* category to all pixel regions.

representations due to hidden layer activations coding semantic concepts in a distributed fashion (Fong & Vedaldi, 2018). It has therefore been difficult to precisely quantify the type of information contained in the latent representations of CNNs. Some methods have looked at ways to analyze the latent representations of CNNs on a neuron-to-neuron level. For instance, (Bau et al., 2017) quantify the number of interpretable neurons for a CNN by evaluating the semantic segmentation performance of an individual neuron from an upsampled latent representation. Later work (Fong & Vedaldi, 2018) then removed the assumption that each neuron encodes a single semantic concept. These works successfully quantify the number of filters that recognize textures or specific objects in a CNN, but do not identify *shape* information within these representations.

The most similar works to ours are those that aim to directly quantify the shape information in CNNs. For example, (Geirhos et al., 2018) analyzed the outputs of CNNs on images with conflicting shape and texture cues. By using image stylization (Huang & Belongie, 2017), they generated the Stylized ImageNet dataset (SIN), where each image has an associated shape *and* texture label. They then measured the 'shape bias' and 'texture bias' of a CNN by calculating the percentage of images a CNN predicts as either the shape or texture label, respectively. They conclude that CNNs are 'texture biased' and make predictions mainly from texture in an image. This metric has been used in subsequent work exploring shape and texture bias in CNNs (Hermann & Kornblith, 2019); however, the method only compares the *output* of a CNN, and fails to robustly quantify the amount of shape information contained in the *latent representations* (note that they refer to 'shape' as the entire 3D form of an object, including contours that are not part of the silhouette, while in our work, we define 'shape' as the 2D class-agnostic silhouette of an object). This is problematic as CNNs may still encode a significant amount of shape information while predicting an output based mostly on the texture. Further, as their metric for *shape* relies solely on the semantic class label, it precludes them from evaluating the encoded shape and associated categorical information on a per-pixel level. For instance, we show in Fig. 1 that shape biased models (i.e., models trained on stylized images) do not classify images based on the entire object shape: even though the CNN correctly classifies the image as a bird, *and* while the full binary mask (i.e., 'shape') can be extracted from the latent representations, it cannot attribute the correct class label to the *entire object region* (i.e., semantic segmentation mask).

Contributions. To address these issues, we present a systematic study of how much shape information is contained in a CNN, in terms of the capacity and quality of the latent representation's shape encoding. To quantify these two aspects, we first approximate the mutual information of latent representations between pairs of semantically related images which allows us to estimate the number of dimensions in the feature space dedicated to encoding shape and texture. We then propose a simple strategy to evaluate the amount of shape information contained in the internal representations of a CNN, on a per-pixel level. The latter technique is utilized to distinguish the quality of different shape encodings, regardless of the number of neurons used in each encoding. After showing the efficacy of the two methods, we reveal a number of meaningful properties of CNNs with respect to their ability to encode shape information, including the following: **(i)** Biasing a CNN towards shape predominantly changes the number of shape encoding neurons in the last feature encoding stage. **(ii)** When a CNN is trained on ImageNet, the majority of shape information is learned during the first few epochs. **(iii)** A significant amount of shape is encoded in the early layers of CNNs, which can be utilized to extract additional shape information from the network, by combining with shape encodings from deeper layers. **(iv)** Encoding the shape and class of an object does not imply the useful encoding of localized per-pixel categorical information. All code will be released to reproduce data and results.

Figure 2: The two techniques used to quantify shape used in this paper. **(A)** Estimating the dimensionality of semantic concepts in latent representations: We stylize each image with five textures to generate image pairs which share the semantic concepts *shape* (right pair) and *texture* (left pair). We feed these image pairs (shown is *shape*) to an encoder, $E(\cdot)$, and calculate the mutual information between the two latent representations, z^a and z^b, to estimate the dimensionality, $|z_{\text{shape}}|$. **(B)** We quantify the shape information encoded in a convolutional neural network by freezing the weights, and then training a small read-out module (i.e., three 3×3 convolutional layers) on the latent representation to predict either a binary or semantic segmentation map.

2 DO CNNS SPEND MORE LEARNING CAPACITY ON SHAPE OR TEXTURE?

With the goal of revealing the characteristics of *where*, *when*, and *how much* shape information is encoded in CNNs, we first aim to quantify the number of dimensions which encode shape in a CNN's latent representation. This analysis on the latent representations will allow us to determine *where* the network spends learning capacity on shape, while other methods that focus solely on the network outputs have difficulty measuring the difference in shape information between convolutional layers.

2.1 ESTIMATING SHAPE AND TEXTURE DIMENSIONALITY

Previous works (Bau et al., 2017; Esser et al., 2020) proposed various mechanisms to reveal the semantic concepts encoded in latent representations of CNNs. To quantify the amount of texture and shape information, we follow the approach of (Esser et al., 2020), where the number of neurons that represent a certain semantic concept is estimated. Given a pretrained CNN encoder, $E(I) = z$, where z is a latent representation, we aim to estimate the dimensionality of the semantic concepts shape and texture within z. The main idea is that the mutual information between image pairs, I^a and I^b, which are similar in a semantic concept, will be preserved in a neuron z_i only if the neuron encodes that specific semantic concept. Hence, the mutual information between the corresponding neuron pairs, $z_i^a = E(I^a)$ and $z_i^b = E(I^b)$, can be used to quantify the degree to which a semantic concept is represented by the neuron. A simple and efficient estimate for their mutual information $\text{MI}(z_i^a, z_i^b)$ can be obtained based on the correlation coefficient ρ_i. Indeed, under the assumption that the marginal distribution of the neuron z_i is Gaussian, the correlation coefficient ρ_i provides a lower bound on the true mutual information through the following relationship which becomes tight for jointly Gaussian z_i^a, z_i^b (Kraskov et al., 2004; Foster & Grassberger, 2011).

$$\text{MI}(z_i^a, z_i^b) \geq -\frac{1}{2}\log(1 - \rho_i^2), \quad \text{where } \rho_i = \frac{\text{Cov}(z_i^a, z_i^b)}{\sqrt{\text{Var}(z_i^a)\,\text{Var}(z_i^b)}}. \tag{1}$$

To quantify how well a concept k is represented in terms of the number of neurons $|z_k|$ that encode the concept, we compute a score for each concept and the relative number of neurons is determined with a softmax over these scores and a baseline score. The latter is given by the number of neurons $|z|$, and shape and texture scores are given by the sum of their respective correlation coefficients ρ_i^{shape} and ρ_i^{texture}, which are computed according to Eq. 1 with statistics taken over image pairs that are similar in shape and texture, respectively. Note that $k \in \{1, 2\}$ in our case, and the remaining dimensions not captured in any of the two semantic factors are allocated to the *residual* semantic factor, which by definition captures all other variability in the latent representation, z.

Table 1: **Dimensionality estimation** of semantic factors $|z_k|$. Note that the total dimension of the latent representation, $|z|$, is 2048 for all networks, and that the remaining dimensions are allocated to the 'residual' factor. (a) ResNet50 compared with BagNets. BagNets have more neurons which encode *texture* than *shape* due to their restricted receptive field. (b) Networks with varying levels of shape bias. The number of neurons which encode shape correlates with shape bias. (c) Deeper networks contain more *shape* encoding neurons.

Model	Factor $|z_k|$			Training Data	Factor $|z_k|$			Model	Factor $|z_k|$	
	Shape	Texture			Shape	Texture			Shape	Texture
ResNet50	**349**	692		IN	349	**692**		ResNet50	349	**692**
BagNet33	284	825		SIN	**536**	477		ResNet101	365	667
BagNet17	278	839		(SIN+IN)→IN	376	640		ResNet152	**371**	661
BagNet9	276	**841**								

Stylized PASCAL VOC 2012 Dataset. Our goal is to estimate the dimensionality of two semantic concepts: (i) *shape* and (ii) *texture*, and analyze pixel-wise shape information. Therefore we must generate a dataset that we can sample image pairs which share the semantic factors shape or texture, and have per-pixel object annotations. To accomplish this goal, we create the *Stylized PASCAL VOC 2012* (SVOC) dataset. Similar to SIN, we use the AdaIN style transfer algorithm (Huang & Belongie, 2017) to generate stylized images from the PASCAL VOC 2012 dataset (Everingham et al., 2010) with the same settings and hyperparameters as in the original paper (Huang & Belongie, 2017). We choose five random textures from the Describable Textures Dataset (Cimpoi et al., 2014) as the styles and we stylize every PASCAL VOC image with all five of these textures. For a fair comparison with models trained on ImageNet variants, we take only the images from PASCAL VOC which contain a single object. With the SVOC dataset, we can now sample image pairs which are similar in *texture*, by using two images from different categories but stylized with the same texture (Fig. 2(A) left), or *shape*, by using the same image stylized with two different textures (Fig. 2(A) right).

2.2 RESULTS

We now evaluate the efficacy of the dimensionality estimation method by comparing two networks which differ significantly in their ability to encode shape information. The first is a standard ResNet50 (He et al., 2016) architecture and the second is the recently proposed BagNet (Brendel & Bethge, 2019). BagNets are a modified version of ResNet50 that restrict the height and width of the effective receptive field of the CNN to be a fixed maximum, i.e., either 9, 17, or 33 pixels. This patch-based construction precludes BagNets from classifying images based on extended shape cues. The results of this comparison are presented in Table 1(a) where both the ResNet50 and the BagNet variants are trained on IN. As expected, BagNets have more neurons encoding texture than the ResNet50 and there is a clear correlation between the receptive field of the network and the amount of shape encoded. As the receptive field decreases, the number of neurons encoding texture increases even further, while the number of neurons encoding shape decreases.

We now examine whether the 'shape bias' metric (Geirhos et al., 2018) correlates with the number of shape encoding neurons. Table 1(b) compares the estimated dimensionality of a ResNet50 trained on ImageNet against networks which are biased towards shape using two different training strategies: (i) training solely on SIN and (ii) training on SIN and IN simultaneously followed by fine-tuning on IN (denoted as (SIN+IN)→IN, which achieves the best accuracy on ImageNet top-1% out of the three variations (Geirhos et al., 2018)). ResNet50 trained on IN has far more neurons dedicated to encoding texture than shape. There is a large difference when training a ResNet solely on SIN, where it has less neurons which encode texture than shape. When trained and fine-tuned on (SIN+IN) and IN, respectively, there is an increase in the number of neurons which encode shape compared to IN.

We consider if there is any pattern in the number of neurons encoding shape or texture as the network depth increases. We compare ResNets with 50, 101, and 152 layers, as they share the underlying layer structure and dimensionality in the final latent representation. As can be seen in Table 1(c), networks have more shape and less texture neurons as depth increases. This may be due to the increase in learning capacity of the deeper networks, as more hierarchical representations allow for the network to learn increasingly complex shapes compared to the shallower networks. Further, deeper networks have stronger long range connections due to a larger effective receptive field potentially resulting in additional shape encoding neurons. The increase in shape understanding could be one of the reasons why deeper networks achieve better performance on various tasks, e.g., image classification.

Finally, we assess the consistency between the dimensionality estimation technique and network dissection (Bau et al., 2017), another method which estimates the number of neurons representing different concepts (described in Sec. A.1). Since network dissection cannot estimate shape dimensionalities, the comparison is limited to the texture

Table 2: Comparing dimensionality estimations for the *texture* factor between two methods. Both methods show that more texture neurons are found in representations with smaller receptive fields.

Method	Res152	Res101	Res50	Bag33	Bag17	Bag9
Net. Diss.	433	481	499	592	623	537
Dim. est.	661	667	692	825	839	841

dimensions shown in Table 2. Except for the case of BagNet9 and a difference in the absolute numbers of neurons (discussed in Sec. A.1), both methods agree about the correlation between texture dimensionality and the receptive field, which provides further evidence that dimensionality estimates quantify the relevance of semantic concepts faithfully.

Stage-Wise Analysis of Shape and Texture Dimensionality We now explore *where* CNNs encode shape by applying the dimensionality estimation method with the latent representations from ResNet50 stages two to five with different amounts of shape bias. Due to the different dimensions at each of these stages, we present the results as the percentage of dimensions encoding the particular semantic factor, $|z_k|/|z|$, where $|z|$ refers to length of the latent representation. Table 3 shows that *all stages of the network* encode shape with an increase in the last two stages. Further, biasing the models towards shape only changes the percentage of shape encoding in the final two stages. Beginning at the fourth stage, there is a significant jump in the number of shape dimensions for all three models with the shape

Table 3: Percentage of neurons ($|z_k|/|z|$) encoding different semantic concepts, k, for different stages of ResNet50 trained for various levels of shape bias. While a moderate percentage of neurons encode shape in stages f_2 and f_3, the majority of shape neurons are found in stage f_5. Networks with shape bias learn additional shape information in stage f_5.

Stage	IN		SIN		(SIN+IN)→IN	
	Factor $|z_k|/|z|$		Factor $|z_k|/|z|$		Factor $|z_k|/|z|$	
	Shape	Texture	Shape	Texture	Shape	Texture
f_2	14.1%	40.2%	14.1%	40.6%	14.1%	40.6%
f_3	14.6%	39.5%	14.8%	39.5%	14.8%	39.5%
f_4	15.3%	37.9%	17.7%	34.7%	17.7%	34.8%
f_5	17.0%	33.8%	26.2%	23.3%	18.4%	31.2%

biased models having a larger increase. At the final stage, latent representations encode even more shape, where SIN in particular has a large increase of 8.5%. This indicates that biasing a model towards shape mainly affects the last two stages of the network, suggesting that future work could focus on improving the shape bias of earlier layers. An increase in shape dimensions is *inversely proportional* to the amount of texture dimensions. Notably, from stage four to stage five, there is a large drop in the amount of texture dimensions for all networks.

When Does Shape Become Relevant During ImageNet Training? To answer the question 'When do models learn to encode shape and texture during training?', we capture the changes of *shape* and *texture* occurring over the course of training a classifier on ImageNet. We obtain 18 different instances of a ResNet50 model during training on ImageNet, each representing a checkpoint between epochs 0 and 90 (equally distributed). For each checkpoint, we measure the dimensionality of shape and texture semantic factors and plot the results in Fig. 3. We see that the *shape* factor becomes increasingly more relevant when we use the latent dimension from stage-5 (Fig. 3 (right)), while the texture factor decreases as the training progresses. In the case of the stage-4 latent representation (Fig. 3 (left)), the dimensionality of shape encoding does not increase as training progresses. This further reveals that a large proportion of shape information is encoded at the deepest layer.

3 HOW MUCH SHAPE INFORMATION DO CNNS ENCODE?

The previous section measured the dimensionality of shape encodings for various CNNs and settings. We now aim to evaluate the quality of these encodings, and whether more shape encoding neurons implies that more robust shape information can be extracted from these latent representations. Hermann & Kornblith (2019) measured the quality of shape encodings in a CNN's latent representations by training a linear classifier on the CNN's late-stage features to predict the shape label of SIN images. Quantifying shape information by using image level labels does not allow for the per-pixel evaluation of the encoded shape, and its relation to the associated categorical label, two key components for fully evaluating the shape information contained in a particular encoding.

Figure 3: Analyzing the number of dimensions in a ResNet50 which encode shape ($|z_{shape}|$) and texture ($|z_{texture}|$) over the course of ImageNet training. Dimensions are estimated using stage four (Left, $|z^{(4)}| = 1024$) and stage five (Right, $|z^{(5)}| = 2048$) latent representations. When training begins, z is very sensitive to *texture* but over the course of training learns to focus on the *shape* instead. The vertical lines represent multiplying the learning rate by a factor of 0.1.

3.1 QUANTIFYING SHAPE INFORMATION IN CNN LATENT REPRESENTATIONS

To overcome the aforementioned issues, we consider two tasks which require a detailed understanding of object shape: *binary* and *semantic* segmentation. A 'shape encoding network' (SEN), the network being analyzed, consists of a CNN with fixed weights. We then train a shallow read-out module that takes a latent representation from the SEN, to predict a segmentation map (i.e., binary or semantic). If the read-out module can accurately segment objects with *a binary mask*, we conclude the SEN encodes the precise shape of the objects of interest. Further, the read-out modules ability to perform *semantic* segmentation, measures how much of this encoded shape is successfully localized with per-pixel categorical information. We use ResNet networks of various depths (i.e., 34, 50, and 101) as SENs with a readout module containing either one or three convolution layers with 3×3 kernels. We use the *trainaug* and *val* split of the VOC 2012 dataset to train and test the read-out module, respectively. The binary segmentation ground truth labels are generated by converting all semantic categories to a single 'object' class.

3.2 RESULTS

Table 4 presents the results in terms of mean-Intersection-over-Union (mIoU) under different initialization settings with; 'IN': a SEN trained for ImageNet classification, 'None': a SEN with random weight initialization and without any training, 'End-to-End': the SEN and readout module trained in an end-to-end manner on either the binary (*Bin*) or semantic (*Sem*) segmentation ground truth. The None and End-to-End networks represent lower and upper bounds for encoding shape, respectively. All read-out modules in this section are trained on the last layer's latent representations. Interestingly, three convolutional layers can extract similar amounts of shape information from the IN-SEN as the End-to-End-SEN. For example, training the ResNet101 End-to-End-SEN for *Bin* improves the mIoU by merely 2.5% compared to the IN-SEN. ImageNet trained CNNs also contain shape encodings which successfully localize per-pixel categorical information as well, which can be seen when comparing the performance of the IN-SEN and End-to-End SEN, e.g., for ResNet50, the IN-SEN and End-to-End-SEN achieve 61.6% and 68.1%, respectively. This is an interesting result considering the difficulty of semantic segmentation and that *none* of the IN-SEN weights are trained for pixel-wise objectives. Shape information also increases relative to the depth of the network which supports the dimensionality estimation results presented in Table 1(c). As expected, the End-to-End-SEN and

Table 4: **Left:** We measure the amount of shape encoded in frozen CNN by training a read-out module on either binary (*Bin*) or semantic segmentation (*Sem*) under different training settings. 'None': random initialization, 'End-to-End': network is not frozen and trained with the read-out module, 'IN': pre-trained on ImageNet. **Right:** Shape information contained in various shape biased models.

Training	1 Layer Readout						3 Layers Readout							Training	ResNet50	
	ResNet34		ResNet50		ResNet101		ResNet34		ResNet50		ResNet101				Bin	Sem
	Bin	Sem	Bin	Sem	Bin	Sem	Bin	Sem	Bin	Sem	Bin	Sem				
None	46.5	5.2	48.0	6.1	44.9	5.1	58.0	7.2	58.0	6.0	55.0	4.8		IN	79.8	61.6
End-to-End	80.2	63.4	80.2	62.7	81.0	65.8	82.1	67.7	82.2	68.1	82.9	71.5		SIN	76.4	53.7
IN	66.3	48.1	70.6	50.9	72.1	51.9	78.9	59.1	79.8	61.6	80.4	63.4		(SIN+IN)→IN	77.8	58.0

Table 5: Shape encoding results for different stages of ResNet networks trained on ImageNet. Combining features from early stages significantly increases shape encoding.

f_2	f_3	f_4	f_5	ResNet50		ResNet101	
				Bin	*Sem*	*Bin*	*Sem*
✓				52.7	6.4	53.0	5.6
	✓			59.6	10.9	57.7	9.4
		✓		70.8	33.9	**73.2**	43.6
			✓	**70.6**	**50.9**	72.1	**51.9**
✓	✓			66.0	16.6	63.8	13.5
✓	✓	✓		74.5	42.2	76.8	49.8
✓	✓	✓	✓	**77.3**	**53.7**	**78.2**	**56.2**

Figure 4: Stage-wise predictions of read-out module on binary (*Bin*) and semantic (*Sem*) segmentation.

IN-SEN contain significantly more shape information in their latent representations than the baseline None-SEN.

We now evaluate the shape information encoded in networks which have different levels of shape bias. We compare the *Bin* and *Sem* performance of the read-out module trained on the features of three different SENs trained on IN, SIN, and (SIN+IN)→IN. As the validation is on non-stylized images, SIN-SEN has slightly lower performance for *Bin*, and significantly less performance on *Sem*. Such a large difference in performance implies that while the boundary of the object is known, it is difficult for the network to correctly assign per-pixel *categorical* information, a phenomenon further explored in Sec. 3.2.1. Interestingly, the (SIN+IN)→IN-SEN also has slightly lower performance than the IN-SEN for *Bin*, but does not suffer in performance as much as the SIN-SEN in the case of *Sem*.

Where is Shape Information Stored? We now examine if the large amount of *shape* information contained in ImageNet pretrained models is equally distributed across different stages of the CNN. In this experiment, we train read-out modules on features from different stages, (f_2, f_3, f_4, f_5), of the SEN to examine which stage of a CNN encodes shape information. Note that we only use one layer readout modules for this experiment. As shown in Table 5, the read-out module trained on the last stage features, (f_4, f_5), achieves higher performance compared to the earlier stage features, (f_2, f_3), for both *Bin* and *Sem*. This is to be expected, as feature maps from later stages have higher channel dimensions and larger effective receptive fields compared to the feature maps extracted from earlier layers. A surprising amount of shape information (i.e., *Bin*) can be extracted from stages f_2 and f_3; however, these features lack high-level *semantics* to correlate with this shape information, which can be observed as the corresponding *Sem* performance is much lower. Figure 4 reveals this phenomenon; the *horse* and *person* are outlined even for the early stage binary masks, but are only labelled with correct per-pixel categorical assignments in the later stages. Considering the non-trivial amount of shape information contained in the early stages, we investigate if aggregating multi-stage features encodes more shape compared to the last stage feature, (f_5). Table 5 (bottom) shows that training a readout module on multi-stage features significantly improves the *Bin* and *Sem* performance, suggesting that tasks requiring shape information may benefit from hypercolumn style architectures (Hariharan et al., 2015). This indicates that some *shape* information is encoded in earlier layers but not captured in the late stages, which agrees with the dimensionality estimation results in Table 3, as around 14% of neurons encode shape in the first two stages.

Figure 5: Quantifying the shape and semantic information encoded by a CNN over the course of ImageNet training. A separate read-out module is trained on the frozen CNN weights for each snapshot. Vertical lines represent the learning rate decay.

When do CNNs Encode Shape During ImageNet Training? Now we quantify the amount of shape encoded in the latent representations over the same ImageNet training snapshots as in Sec. 2.1. Fig. 5 shows the performance of the read-out module trained on the frozen SEN every five epochs, as well as the ResNet50's validation accuracy on ImageNet classification. Note that we train a separate

Table 6: Shape encoding results for shape biased ResNet50s on *stylized* VOC12 validation set.

Training Data	ResNet50	
	Bin.	Sem.
IN	45.7	8.5
SIN	60.3	26.4
(SIN+IN)→ IN	44.5	9.0

Figure 6: Binary and semantic segmentation masks extracted from CNNs trained on ImageNet (**IN**) and Stylized ImageNet (**SIN**).

read-out module for every snapshot. Similar to the findings in Fig. 3, we see that the majority of both binary and semantic shape information is learned within the first 10 epochs i.e., $\frac{77.1\%}{79.4\%} = 97.1\%$ of the final *Bin* mIoU and $\frac{52.9\%}{60.0\%} = 88.2\%$ of the final *Sem* mIoU is obtained by the read-out module after only 10 epochs. Contrasting purely shape related information (i.e., *Bin*), a small but significant portion of *per-pixel categorical* information is learned after the initial 10 epochs, when the learning rate decay is employed.

3.2.1 DOES KNOWING AN OBJECT'S SHAPE IMPLY KNOWING ITS SEMANTIC CLASS?

The results in Secs. 3.2 and 2.1 suggest that encoding the full object *shape* may not imply the network also captures the object *class* on a per-pixel level. Table 4(b) showed that shape biased models lose their ability to relate *categorical* activations to localized object regions. The stage-wise results from Table 5 further demonstrate that a modest amount of shape information is contained in early stage features but that categorical information can only be correctly assigned to pixels at the last two stages, which can also be seen in Fig. 4.

To further test this hypothesis, we validate various SENs and their read-out modules on stylized VOC12 *val* images rather than non-stylized images. Note that the validation images are stylized by a single randomly selected texture from the same set of textures used in Sec. 2.1. This ensures that the networks must rely solely on the object's shape rather than the texture to make predictions. The *difference* in performance between the *Bin* mIoU and *Sem* mIoU can therefore approximate the amount of shape information that is *not* correlated to its corresponding *semantic* class. As shown in Table 6, the large difference in performance between *Bin* and *Sem* suggests that these SENs capture the shape of the object but lack the ability to correctly assign per-pixel semantic labels to these objects, even in the last layer of the network. Qualitative results are presented in Fig. 6; note how the binary mask (presented as likelihood heatmaps) for the SIN trained model reasonably segments the objects, while the semantic masks fail to resemble realistic predictions, i.e., *multiple* object categories are placed spuriously over and around the object of interest.

4 CONCLUSION

In this paper, we presented a systematic study of the capacity and quality of shape encoded in a CNNs latent representations. The main shortcoming of previous work in this regard is a *lack* of ability to quantify shape information contained in a CNN, as well as the capacity spent encoding shape. Approximating the mutual information between stylized PASCAL VOC images allowed us to estimate the dimensionality of the semantic concepts shape and texture (Sec. 2.1). We also designed a simple strategy for determining *how much* shape information is encoded in these latent representations, by training a read-out module on per-pixel binary segmentation ground truth labels. Additionally, we perform semantic segmentation to quantify how much of this shape encoding can be correctly attributed to per-pixel categorical information. We showed that a model pre-trained on ImageNet has weights that contain *almost* all the shape and categorical information needed to perform binary or semantic segmentation from the late stage features. We showed that CNNs encode a surprising amount of shape information at all stages of the network, but correctly assigning categorical labels to the corresponding shape only occurs at the last layers of the network, and that removing the image's texture information severely hurts this correspondence. These findings reveal important mechanisms which characterize a network's ability to encode shape information. We anticipate these findings will be valuable for designing more robust and trustworthy computer vision algorithms.

REFERENCES

David Bau, Bolei Zhou, Aditya Khosla, Aude Oliva, and Antonio Torralba. Network dissection: Quantifying interpretability of deep visual representations. In *CVPR*, 2017.

Wieland Brendel and Matthias Bethge. Approximating CNNs with bag-of-local-features models works surprisingly well on imagenet. In *ICLR*, 2019.

Liang-Chieh Chen, George Papandreou, Florian Schroff, and Hartwig Adam. Rethinking atrous convolution for semantic image segmentation. *arXiv:1706.05587*, 2017.

Mircea Cimpoi, Subhransu Maji, Iasonas Kokkinos, Sammy Mohamed, and Andrea Vedaldi. Describing textures in the wild. In *CVPR*, 2014.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009.

Patrick Esser, Robin Rombach, and Björn Ommer. A disentangling invertible interpretation network for explaining latent representations. In *CVPR*, 2020.

M. Everingham, L. Van Gool, C. K. I. Williams, J. Winn, and A. Zisserman. The PASCAL Visual Object Classes Challenge 2010 (VOC2010) Results. http://www.pascal-network.org/challenges/VOC/voc2010/workshop/index.html, 2010.

Ruth Fong and Andrea Vedaldi. Net2vec: Quantifying and explaining how concepts are encoded by filters in deep neural networks. In *CVPR*, 2018.

David Foster and Peter Grassberger. Lower bounds on mutual information. *Physical review. E, Statistical, nonlinear, and soft matter physics*, 83:010101, 01 2011. doi: 10.1103/PhysRevE.83. 010101.

Robert Geirhos, Patricia Rubisch, Claudio Michaelis, Matthias Bethge, Felix A Wichmann, and Wieland Brendel. Imagenet-trained CNNs are biased towards texture; increasing shape bias improves accuracy and robustness. In *ICLR*, 2018.

Bharath Hariharan, Pablo Arbeláez, Ross Girshick, and Jitendra Malik. Hypercolumns for object segmentation and fine-grained localization. In *CVPR*, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask R-CNN. In *ICCV*, 2017.

Katherine L Hermann and Simon Kornblith. Exploring the origins and prevalence of texture bias in convolutional neural networks. *arXiv preprint arXiv:1911.09071*, 2019.

Katherine L Hermann and Andrew K Lampinen. What shapes feature representations? exploring datasets, architectures, and training. In *NeurIPS*, 2020.

Xun Huang and Serge Belongie. Arbitrary style transfer in real-time with adaptive instance normalization. In *ICCV*, pp. 1501–1510, 2017.

Andrej Karpathy, George Toderici, Sanketh Shetty, Thomas Leung, Rahul Sukthankar, and Li Fei-Fei. Large-scale video classification with convolutional neural networks. In *CVPR*, 2014.

Alexander Kraskov, Harald Stögbauer, and Peter Grassberger. Estimating mutual information. *Phys. Rev. E*, 69:066138, 2004.

Nikolaus Kriegeskorte. Deep neural networks: a new framework for modeling biological vision and brain information processing. *Annual review of vision science*, 1:417–446, 2015.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. ImageNet classification with deep convolutional neural networks. In *NIPS*, 2012.

ZC Lipton. The mythos of model interpretability. arxiv 2016. *arXiv preprint arXiv:1606.03490*, 2019.

Jonathan Long, Evan Shelhamer, and Trevor Darrell. Fully convolutional networks for semantic segmentation. In *CVPR*, 2015.

Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster R-CNN: Towards real-time object detection with region proposal networks. In *NIPS*, 2015.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. In *ICLR*, 2015.

Jost Tobias Springenberg, Alexey Dosovitskiy, Thomas Brox, and Martin Riedmiller. Striving for simplicity: The all convolutional net. In *ICLRW*, 2014.

Jason Stack. Automation for underwater mine recognition: current trends and future strategy. In *Detection and Sensing of Mines, Explosive Objects, and Obscured Targets XVI*, volume 8017, pp. 80170K. International Society for Optics and Photonics, 2011.

Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *CVPR*, 2015.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. " Why Should I Trust You?": Explaining the predictions of any classifier. *arXiv*, pp. arXiv–1602, 2016.

Joe Yue-Hei Ng, Matthew Hausknecht, Sudheendra Vijayanarasimhan, Oriol Vinyals, Rajat Monga, and George Toderici. Beyond short snippets: Deep networks for video classification. In *CVPR*, 2015.

Matthew D Zeiler and Rob Fergus. Visualizing and understanding convolutional networks. In *ECCV*, 2014.

Hengshuang Zhao, Jiaya Jia, and Vladlen Koltun. Exploring self-attention for image recognition. In *CVPR*, 2020.

A APPENDIX

A.1 CONSISTENCY OF DIMENSIONALITY ESTIMATION

Sec. 2.1 analyzed the consistency between the dimensionality estimate of Esser et al. (2020) and that of Bau et al. (2017). In order to quantify interpretability, the latter evaluates the alignment between neurons and semantic concepts using the Broden dataset, which consists of images with pixel-wise labelings of different semantic concepts. For each neuron z_i, it determines the top quantile level T_i such that the activation value of z_i exceeds T_i only in 0.5% of all observed cases over the dataset, i.e. $p(z_i > T_i) = 0.005$. Feature maps are then upsampled to the original image resolution and each neuron is thresholded according to its quantile T_i to obtain a binary segmentation mask. A neuron is then termed a detector for a concept, if its segmentation mask has the highest intersection over union score (IoU) for this concept, and the IoU exceeds a threshold of 0.04.

Because the Broden dataset contains no shape concepts, the comparison in Tab. 2 is limited to estimates on the number of neurons encoding texture, which is determined by the number of detectors for concepts from the categories material, texture and color of the Broden validation dataset.

We observe that both methods predict an inverse relationship between the estimated texture dimension-alities and the receptive field, except for the case of BagNet9, where a sudden drop in the number of texture detectors is observed for network dissection. Besides this qualitative agreement, the predicted absolute numbers differ. There are two main sources for the incompatibility in the absolute number of neurons. First, both approaches rely on hyperparameters,u i.e. the baseline score and the choice of the normalization function in the case of dimensionality estimation, and the chosen quantile and IoU threshold in the case of network dissection. Second, the semantic meaning of texture depends on the data, i.e. dimensionality estimation relies on the image pairs of SVOC, whereas network dissection relies on texture images of Broden. This might also explain the drop in detectors for BagNet9 if its receptive field is too small for some of the Broden textures. While absolute numbers depend on hyperparameters, results obtained with both methods are comparable across networks.

A.2 ESTIMATING SHAPE AND TEXTURE DIMENSIONALITY OF DIFFERENT NETWORKS TRAINED ON STYLIZED IMAGENET

We further estimate the dimensionality of shape and texture semantic concepts of different networks in Table 7 to test the consistency of the results reported in Table 1 on different architectures. We run the dimensionality estimation experiment (see Sec. 2.1) on AlexNet (Krizhevsky et al., 2012) and VGG-16 (Simonyan & Zisserman, 2015), trained on IN and SIN. Consistent with the findings for ResNet50, Table 7 shows that training on SIN increases the number of dimensions encoding shape and concurrently decreases the number of dimensions encoding texture: **AlexNet-IN**: [*Shape*=729, *Texture*=1299], **AlexNet-SIN**: [1119, 870]. **VGG-16-IN:** [710, 1321], **VGG-16-SIN**: [1090, 879].

Table 7: Comparison of shape bias and shape dimensionality for different networks.

Network	IN				SIN			
	Factor $\|z_k\|$		Bias		Factor $\|z_k\|$		Bias	
	Shape	Texture	Shape	Texture	Shape	Texture	Shape	Texture
ResNet-50	14.1%	40.2%	22.1%	87.9%	26.2%	23.3%	81.0%	19.0%
AlexNet	14.6%	39.5%	25.3%	74.7%	27.3%	21.2%	75.5%	24.5%
VGG-16	15.3%	37.9%	9.2%	90.8%	26.6%	21.5%	77.4%	22.6%

A.3 ESTIMATING SHAPE AND TEXTURE DIMENSIONALITY OF SELF-ATTENTION NETWORKS

We also experiment with the recently proposed Self-Attention Networks Zhao et al. (2020), which replace convolutional layers with self-attention layers. Three different depths of Self-Attention Networks (SANs) were proposed. For fair comparison, we experiment with SAN-19, which the authors claim is the most similar size to ResNet50, in terms of the number of parameters in the network. Additional, SANs come with two types of layer operations, patch-based and pair-based. The

Table 8: Comparing the number of shape encoding neurons and texture encoding neurons for self-attention networks (Zhao et al., 2020).

Model	Factor $|z_k|$		Factor $|z_k|/|z|$	
	Shape	Texture	Shape	Texture
ResNet50	349	692	17.0%	33.8%
SAN-19 (patch)	384	610	18.8%	29.8%
SAN-19 (pair)	304	764	14.9%	37.3%

patch-based SAN compares patches of pixels within the attention operations, while the pair-based SAN compares individual pixels and achieves lower performance on ImageNet. Due to the lower effective receptive field of the pair-based SAN compared to the patch-based SAN, we expect to see a larger number of neurons encoding shape in the patch-based SAN. The results are shown in Table 8. The patch-based SAN19 has the largest number of shape encoding dimensions and lowest number of texture encoding dimensions, when compared to the pair-based SAN19 and ResNet50.