Toward Robust Spiking Neural Network Against Adversarial Perturbation

Abstract

As spiking neural networks (SNNs) are deployed increasingly in real-world efficiency critical applications, the security concerns in SNNs attract more attention. Currently, researchers have already demonstrated an SNN can be attacked with adversarial examples. How to build a robust SNN becomes an urgent issue. Recently, many studies apply certified training in artificial neural networks (ANNs), which can improve the robustness of an NN model promisely. However, existing certifications cannot transfer to SNNs directly because of the distinct neuron behavior and input formats for SNNs. In this work, we first design S-IBP and S-CROWN that tackle the non-linear functions in SNNs' neuron modeling. Then, we formalize the boundaries for both digital and spike inputs. Finally, we demonstrate the efficiency of our proposed robust training method in different datasets and model architectures. Based on our experiment, we can achieve a maximum 37.7% attack error reduction with 3.7% original accuracy loss. To the best of our knowledge, this is the first analysis on robust training of SNNs.

1 Introduction

Spiking neural networks (SNNs) are a class of models that have the potential ability to simulate the behavior of neuron circuits in the brain. Among the rich biological characters of SNNs, the event-driven information propagation mechanism makes SNNs easy to deploy with limited computation resources. Many neuromorphic chips are designed to achieve low power SNN inference, such as TrueNorth (Akopyan et al., 2015), Loihi(Davies et al., 2018), SpinalFlow (Narayanan et al., 2020) and H2Learn (Liang et al., 2021b).

With more attention to the study of SNNs, the security issues also raise concerns in the community. Adversarial attack (Szegedy et al., 2013; Carlini & Wagner, 2017; Athalye et al., 2018; Xu et al., 2020b) is one of the most intuitive ways to evaluate the robustness of a model. In adversarial attacks, the attacker generates adversarial examples to fool a model predicting wrong. Currently, SNNs are demonstrated can be attacked through adversarial examples (Sharmin et al., 2019; Liang et al., 2021a; Büchel et al., 2021b; Marchisio et al., 2021). It is urgent to explore an efficient way to improve the robustness of SNN models.

Previously, researchers have investigated the impact of hyper-parameter selection (El-Allami et al., 2021) and input filtering (Marchisio et al., 2021) on the adversarial attack in SNNs. However, these methods do not directly promote the classification behavior of a given SNN model. (Büchel et al., 2021a) proposes a robust training method that relies on the adversarial attack in the parameter space. Unlike SNNs, how to improve the robustness of an artificial neural network (ANN) is well studied. Recently, trianing a neural network model with certified defense methods (Wong & Kolter, 2018; Mirman et al., 2018; Zhang et al., 2020; Xu et al., 2020a) show remarkable guarantee to improve the model's robustness. CROWN-IBP (Zhang et al., 2020) is one of the most promising certified training methods with polynomial computianal cost compared with natural training. The CROWN-IBP method will compute the output boundary for a given bounded input. However, the current CROWN-IBP method cannot be directly applied to SNNs. Firstly, the neuron dynamic in SNNs is

more complicated. Hence, new boundary functions should be defined. Secondly, SNNs accept both
spike and digital inputs, which requires additional boundary generalization for different input types.

Enlightened by certification training in ANNs, we designed an end-to-end robust training method to
improve the robustness of an SNN model against adversarial attacks. Specifically, our contributions
can be summarized as follows:

- We design S-IBP and S-CROWN to tackle the non-linear fire function and temporal update
  in SNNs which firstly introduce SNNs to the linear relaxation based verification family.
- We formalized ℓ_0-norm and ℓ_∞-norm boundaries for spike and digital inputs, respectively.
- Our proposed methods are evaluated on MNIST (LeCun et al., 1998), FMNIST (Xiao et al.,
  2017) and NMNIST (Orchard et al., 2015) datasets. The experinetal results show that we
  can achieve a maximum 37.7% attack error reduction with 3.7% original accuracy loss.

2   Preliminary and Related Work

2.1   Spiking Neural Netowks (SNNs)

Neuron Modeling: Usually, SNNs are designed to simulate the neuron behavior in the brain. In this
work, we adopt the well-studied leaky integrated-and-fire (LIF) (Gerstner et al., 2014) for the neuron
modeling as Figure 1(a). The state of a neuron at each time step is determined by its membrane
potential m and its spike status s. Specifically, a neuron will $fire$ a spike to the post-synaptic neurons
once its membrane potential is greater than a threshold th and its membrane potential will be reset
to 0 at the same time. An example of a neuron dynamic is shown in Figure 1(b) which simulates a
neuron's behavior in 5 time steps. The spike status of a neuron can be formulated as

$$s_t[k] = fire(m_t[k] - th). \tag{1}$$

$$fire(x) = \begin{cases} 1, x \geq 0 \\ 0, \text{ otherwise.} \end{cases} \tag{2}$$

We use $m_t[k]$ and $s_t[k]$ to represent neurons' membrane potentials and spike status at t-th time
step and k-th layer. $fire(\cdot)$ is the Heaviside step function. The membrane potential of a neuron is
composed of spatial and temporal update that follows

$$m_t[k] = \underbrace{\sum_t w[k-1] \otimes s_t[k-1]}_{spatial} + \underbrace{\alpha m_{t-1}[k] \cdot (1 - s_{t-1}[k])}_{temporal}. \tag{3}$$

The spatial update is a Convolution or Fully Connected or Pooling operation between the weight and
the spike events in previous layer. The temporal update is determined by the neuron's membrane
potential and spike status in the previous time step. Here, α is a scaling factor to control the decay.

Figure 1: Introduction of SNNs: (a) neuron modeling; (b) computing model of a neuron; (c)
spatiotemporal flow of an SNN model; (d) input formats of an SNN.

Network Structure: SNNs are built with input layer, hidden layers, and output layer as Figure1(c). In
SNNs, the input layer receives spike inputs. The hidden layers are CONV/FC/POOL that correspond
to the spatial update in the neuron modeling. Compared to ANNs, SNNs involve an additional
temporal axis that passes the neurons' status along with time steps. The final recognition of an SNN
is determined by the spike events of the output layer. In this work, we adopt the rate coding, i.e., the
neuron that fires the most spikes indicates the classification result.

Input Format: In this work, we focus on the image recognition tasks. The input of an SNN can be
spike events captured by DVS devices (Patrick et al., 2008). Also, SNNs can take a digital image as

input with an additional sampling. In this work we adopt Bernoulli sampling (Deng et al., 2020) for digital inputs that follows

$$P(\dot{x}_t[i] = 1) = \hat{x}[i]. \tag{4}$$

We use $\dot{x}_t$ to represent the spike input at time step t. $\hat{x}$ is the digital input after normalization to $[0, 1]$. The example of spike and digital inputs are shown in Figure 1 (d).

Training Method: Recently, supervised learning via backpropagation through time (BPTT) has been adopted in SNN training (Wu et al., 2018). The BPTT-based training method can achieve a higher accuracy and scalability compared to the unsupervised learning algorithms. Also, the SNNs trained with BPTT require fewer time steps, which is more hardware friendly in the real deployment. Thus, in this work, we focus on the SNNs trained with BPTT-based learning method.

2.2 Adversarial Attack in SNN

Adversarial attack is one of the most powerful threat models that affect a model's security. In this work, we use the adversarial attack as an assessment tool to evaluate the robustness of an SNN model. Specifically, in this work we adopt a gradient-based attack method (Liang et al., 2021a) for SNNs.

Untargeted White-box Gradient-based Attack: In adversarial attack, the attacker adds imperceptible noise on inputs to fool the model predicting wrong results. In untargeted attack, the model predicts the adversarial example as any other classes except the ground-truth, which can be formulated as

$$\underset{\delta}{\mathrm{argmin}} \|\delta\|_p, \ s.t. \ f(x + \delta) \neq f(x). \tag{5}$$

Here, $f(\cdot)$ is the prediction result, x is the original input, and δ is the noise added on the input. In this work, we adopt white-box attack, which means the attacker knows all of the model information

The gradient-based attacks are the most efficient ways to generate adversarial examples. In SNNs, the gradient-based attack for the spike and digital inputs can be formulated as

$$\begin{cases} \dot{x}'_{n+1} = \dot{x}'_n + F[\nabla_{\dot{x}'_n} L(\theta, \dot{x}'_n, y_{org})], & \text{spike input,} \\[2ex] \hat{x}'_{n+1} = \hat{x}'_n + \dfrac{\sum_t F[\nabla_{\dot{x}'_n} L(\theta, \dot{x}'_n, y_{org})]}{T}, & \text{digital input.} \end{cases} \tag{6}$$

We use $\dot{x}'$ and $\hat{x}'$ to represent the spike and digital adversarial examples, i.e., $x' = x + \delta$. L and θ are the loss function and parameters of the model, respectively. The adversarial example is constructed by adding the gradient of inputs with the original label (y_{org}) in loss function. F is a filter function that samples, clips, and generates spike compatible noise. During the attack, attackers can compute the adversarial examples iteratively. We use n to denote the attack iteration.

2.3 Certified Training

Recently, the certified training (Gowal et al., 2018; Zhang et al., 2020; Xu et al., 2020a) has been demonstrated to improve the guaranteed robustness of a neural network. In this work, we leverage the CROWN-IBP method (Zhang et al., 2020), one of the state-of-the-art certified training that can achieve tighter bounds in accepctable training cost. Considering a digital input data bounded with ℓ_∞-norm, the goal of CROWN-IBP is to identify whether arbitrary input data within the boundary can fool the model. The CROWN-IBP contains two parts of bounding methods: IBP (Gowal et al., 2018) and CROWN (Zhang et al., 2018).

IBP: In IBP processing, the lower and upper bounds of each layer's feature map are computed along the forward propagation. During the bound computation, the linear operation can be easily bounded once we know the maximum and minimum values of input. However, the upper and lower bound after the non-linear operations need to be dedicated to analysis. Once we acquire the bounds of output we can evaluate the robustness of the model for the given input purbation set.

CROWN: Unlike IBP, CROWN bounds the model in a backward propagation manner recursively. The goal of CROWN is to formulate the output bounds as a linear equation of input. In order to achieve this goal, every operation in an NN model should be bounded by two linear equations.

Although CROWN can achieve very tight bounds, the computinal cost is remarkably higher than IBP. So CROWN-IBP, by combining the fast IBP bounds in a forward bounding pass and CROWN

in a backward bounding pass can efficiently and consistently outperforms IBP baselines on training
verifiably robust neural networks.

Integrate with Other Approaches: One of the promising characteristics of certified training is that
it can be integrated with other algorithms. For example, the combination of certified training and
adversarial training can further improve the robustness of a model (Balunović & Vechev, 2020; Fan
& Li, 2021). For the operations which can improve the performance of a model and only involve
linear operations, the certified training algorithm can be directly applied without causing additional
relaxation losing (Tsuzuku et al., 2018; Wang et al., 2021). Currently, the adversarial training (Kundu
et al., 2021) and batch normalization (Kim & Panda, 2020, 2021; Bhattacharjee et al., 2022) are
demonstrated the effectiveness to improve the robustness of an SNN model, which have the potential
to be integrated into our proposed design in future.

3 Methodology

3.1 S-IBP & S-CROWN

As described in Section 2.3, the core mission of certification training is to find the bound of IBP and
CROWN for each function. The information propagation in SNNs includes $fire$, temporal update
and spatial update as shown in Figure 1(a). In this subsection, we detail the upper bound and lower
bound of S-IBP and S-CROWN for each function. During the bound formulation of a function, we
assume the S-IBP bounds for function inputs have been acquired.

Fire: The $fire$ function describes the relation between the membrane potential m_t and spike s_t of a
neuron as Equation 1 and 2, i.e. once the neuron's membrane potential is greater than a threshold th,
the neuron will fire a spike. Assume we have already acquired the S-IBP upper bound m_t^u and lower
bound m_t^l for membrane potential, the S-IBP bounds for spike can be calculated with

$$s_t^u = fire(m_t^u - th), \ \ s_t^l = fire(m_t^l - th). \tag{7}$$

During S-CROWN, we need to find two linear equations to bound the $fire$ function. When the
S-IBP upper bound of membrane potential m_t^u is smaller than the threshold th, we can conclude
that the neuron must not fire. Also, when the S-IBP lower bound m_t^l is greater than the threshold,
we can make sure the neuron must fire. Thus, we mainly need to consider the unstable case, i.e.,
$m_t^l < th \leq m_t^u$. In order to achieve the lowest bound relaxation, we design two boundary systems as
Figure 2(a) and (b). We use the red line to represent the $fire$ function. The blue and yellow lines
represent the boundary functions. When the S-IBP lower bound of membrane potential m_t^l far smaller
than th, we set the S-CROWN lower bound to $s_t = 0$ and the S-CROWN upper bound is a line that
crosses $(m_t^l, 0)$ and $(th, 1)$. On the contrary, when m_t^u is far larger than th, we set the S-CROWN
upper bound to $s_t = 1$ and the S-CROWN lower bound is a line that passes $(th, 0)$ and $(m_t^u, 1)$.
Overall, the S-CROWN boundary for the $fire$ function under different cases can be summarized as

$$\begin{cases} 0 \leq s_t \leq 0, & m_t^u < th, \\ 1 \leq s_t \leq 1, & m_t^l \geq th, \\ 0 \leq s_t \leq \frac{m_t - m_t^l}{th - m_t^l}, & 0 \leq m_t^u - th < th - m_t^l \\ \frac{m_t - th}{m_t^u - th} \leq s_t \leq 1, & m_t^u - th \geq th - m_t^l > 0 \end{cases} \tag{8}$$

Figure 2: S-CROWN upper and lower bounds for the $fire$ function when (a) m_t^l far smaller than
th and (b) m_t^u far larger than th. (c) Non-linear temporal part of memory potential update. (d)
S-CROWN upper and lower bounds for the temporal part of memory potential update (unstable case).

Temporal Update: According to Equation 3, the temporal update of membrane potential can be formalized as $\alpha m_t(1 - s_t)$. Since α is a constant factor, in this subsection we do not include it in the boundary analysis. Assume $z_t = m_t(1 - s_t)$, and the S-IBP upper and lower bound for membrane potential at time step t has been acquired. The relation between m_t and z_t can be described through Figure 2(c). Based on the LIF model, the membrane potential will be reset to 0 once its value acrosses the pre-defined threshold th. Thus, the S-IBP bounds for z_t can be computed with

$$
\begin{cases}
z_t^u = m_t^u, \;\; z_t^l = m_t^l, & m_t^u < th, \\
z_t^u = z_t^l = 0, & m_t^l \geq th, \\
z_t^u = th, \; z_t^l = min(0, m_t^l), & m_t^l < th \leq m_t^u.
\end{cases}
\tag{9}
$$

When $m_t^u < th$ or $m_t^l \geq th$, there is no boundary relaxation in S-IBP. We only need to consider the boundary when $m_t^l < th \leq m_t^u$ (unstable case), where $z_t \in [min(0, m_t^l), th)$ for unstable case.

During S-CROWN, z_t can be also bounded without relaxation when $m_t^u < th$ and $m_t^l \geq th$. The S-CROWN upper bound (blue plane) and lower bound (yellow plane) for z_t when $m_t^l < th \leq m_t^u$ is shown in Figure 2(d). Here we use an additional $(1 - s_t)$ axis to help us build the boundary. Note that the membrane potential is related to the spike status. Once $s_t = 1 \rightarrow (1 - s_t) = 0$, m_t must greater than th and $z_t = 0$. When $s_t = 0 \rightarrow (1 - s_t) = 1$, m_t must smaller than th and $z_t = m_t$. Thus we need to find two planes to bound these two function (red lines in Figure 2(d)). In summary, the S-CROWN boundary for the temporal update can be formulated as

$$
\begin{cases}
m_t \leq z_t \leq m_t, & m_t^u < th, \\
0 \;\; \leq z_t \leq 0, & m_t^l \geq th, \\
(1 - s_t)m_t^l < z_t < (1 - s_t)th, & m_t^l < th \leq m_t^u.
\end{cases}
\tag{10}
$$

Spatial Update

The spatial update in SNNs is shown in Equation 3. Similar to ANNs, the spatial update in SNNs is composed of CONV/FC/POOL (in this work we focus on the CONV and FC). In SNNs CONV/FC takes spike events and weight as input. Since the spike events are in binary format, the S-IBP of spatial update can be implemented with

$$
\begin{cases}
center = w[k] \otimes s_t^l[k] + b[k], \\
sp_t^u[k + 1] = center + w[k]^+ \otimes (s_t^l[k] = 0 \cap s_t^u[k] = 1), \\
sp_t^l[k + 1] \; = center + w[k]^- \otimes (s_t^l[k] = 0 \cap s_t^u[k] = 1).
\end{cases}
\tag{11}
$$

We use sp_t to represent the result of the spatial update. $\otimes$ denotes CONV/FC operation. In Equation 11, $s_t^l[k] = 1$ represents those pre-synaptic neurons in layer k who are must fire. The stable fired pre-synaptic neurons contribute the same for both S-IBP upper and lower bound of sp_t. The unstabled pre-synaptic neurons can be represented with $(s_t^l[k] = 0 \cap s_t^u[k] = 1)$, whose upper and lower bound for spike status are 1 and 0. These unstable pre-synaptic neurons will perform CONV/FC with the positive and negative weights to affect the S-IBP upper and lower bound of sp_t.

Since the spatial update is a linear operation, the S-CRWON for spatial update does not have relaxation. We do not need to design boundary functions to bound the spatial update in SNNs.

3.2 Input Boundary Formalization

In SNNs, the input layer of an SNN model only accept binary spike. The special data format for the input layer leads to different boundary formalizations for spike and digital images.

Spike Input: An example of spike input is shown in Figure 1(d). All elements in a spike data are in binary format. For each element $\dot{x}_t[i]$ in a spike input, the boundary of that element can be either stable cases: $\dot{x}_t^u[i] = \dot{x}_t^l[i] = 0$; $\dot{x}_t^u[i] = \dot{x}_t^l[i] = 1$ or unstable case: $\dot{x}_t^u[i] = 1, \dot{x}_t^l[i] = 0$. For a spike input with uncertainty noise, we can only control how many data points in the spike input are unstable. Thus, the boundary for a spike input can be formulated with ℓ_0-norm. Specifically, we can pick $size(\dot{x}) \times \epsilon$ elements from a spike input and set them as unstable points. Also, the l0-norm boundary can be interpreted as the probability of an unstable element, which can be formulated as

$$
P(\dot{x}_t^u[i] = 1, \dot{x}_t^l[i] = 0) = \epsilon \;\Leftrightarrow\; |\dot{x}' - \dot{x}|_0 \leq size(\dot{x}) \times \epsilon
\tag{12}
$$

189   Here, $\dot{x}'$ is an arbitrary adversarial example that has at most $size(\dot{x}) \times \epsilon$ data points different from $\dot{x}$.

190   Note that we can only certify the robustness of a spike input after we have picked the unstable data
191   points. Under our robustness formulation, we cannot guarantee the robustness of a spike input under
192   a given ℓ_0-norm. The reason is that the search space for ℓ_0-norm cannot be bounded.

Figure 3: Relation between ℓ_∞-norm digital input boundary and ℓ_0-norm spike input boundary. In this example, $\epsilon = 0.2$.

193   **Digital Input**:

194   Digital inputs need an additional sampling before feeding the data to the input layer as Equation 4.
195   Note that we have defined the ℓ_0-norm boundary for a spike input. We need to further explore how to
196   define a boundary for a digital input when its sampled data is bounded with ℓ_0-norm. Based on our
197   analysis, we find that the corresponding digital input boundary can be formalized with ℓ_∞-norm as
198   Figure 3. We use $rand_t$ to represent a rand mask to achieve Bernoulli sampling for each time step:

$$\dot{x}_t[i] = \begin{cases} 1, & \hat{x}[i] > rand_t[i], \\ 0, & \text{otherwise.} \end{cases} \tag{13}$$

199   After we bound the digital input with ℓ_∞-norm, the upper bound of digital image becomes $\hat{x}^u =$
200    $\hat{x} + \epsilon/2$ and the lower bound is $\hat{x}^l = \hat{x} - \epsilon/2$. For all elements in $\hat{x}$, the difference between the upper
201   bound and the lower bound is ϵ, i.e., $\hat{x}^u[i] - \hat{x}^l[i] = \epsilon$. For each time step, $\hat{x}^u$ and $\hat{x}^l$ use the identical
202   random map $rand_t$ to sample the corresponding spike inputs $\dot{x}_t^u$ and $\dot{x}_t^l$. Based on the sampling
203   processing, the probability of an element in input layer is unstable can be formulated as

$$P(\dot{x}_t^u[i] = 1, \dot{x}_t^l[i] = 0) = \hat{x}^u[i] - \hat{x}^l[i] = \epsilon. \tag{14}$$

204   From the static perspective, the ℓ_∞-norm boundary for digital input is equivalent to the ℓ_0-norm
205   boundary for spike input.

206   For digital inputs, although we apply ℓ_∞-norm on input boundary, we cannot guarantee the robustness
207   of the input under such boundary. Since for an digital input, the possible sampled results are equivalent
208   to the entire space (each element in the spike input can be 1 or 0), which cannot be bounded.

209   For both spike and digital inputs, we need to carefully select ϵ for robust training. An extremely small
210   ϵ will cause the upper and lower bound identical which does not consistent with linear relaxation. A
211   large ϵ may cause the following robust training to diverge. In this work, ϵ is selected based on the
212   noise magnitude in adversarial attacks and some empirical experiments.

213   ### 3.3   Robust Training Algorithm

214   In this subsection, we present the end-to-end robust training for an SNN. For the overall flow, our
215   method will first run S-IBP to get the boundary of intermediate data. Then we apply the S-CROWN
216   which needs the S-IBP bound. Finally, we apply the certification-based robust training.

217   **Flexible Time Steps**: We note that for each SNN layer, the parameters are shared among different
218   time steps. Thus, we can set arbitrary time steps T' for the robust training.

219   **S-IBP**: During the robust training, the inputs first pass the S-IBP as Algorithm 1. At the beginning,
220   the input is bounded according to the input type. Then, the intermediate data are bounded along the
221   forward direction. Finally, the upper and lower bound of all intermediate data are stored which will
222   be used during the S-CROWN phase.

Algorithm 1 S-IBP

Input:
spike input $\dot{x}$ or digital input $\hat{x}$; input boundary ϵ; robust training time steps T';
Func:
for $t = 1$ **to** T' **do**
   // input boundary formalization
   if $\hat{x}$ **then**
      generate random map $rand_t$;
      $\dot{x}_t^u = (\hat{x} + \epsilon/2) - rand_t > 0\ ?\ 1 : 0;$
      $\dot{x}_t^l = (\hat{x} - \epsilon/2) - rand_t > 0\ ?\ 1 : 0;$
   else
      Randomly pick $size(\dot{x}_t) \times \epsilon$ elements from $\dot{x}_t$ and label the picked elements with $pick_t$;
      $\dot{x}_t^u = \dot{x}_t^l = \dot{x}_t;\ \ \dot{x}_t^u[pick_t] = 1;\ \ \dot{x}_t^l[pick_t] = 0;$
   end if
   $s_t^u[0] = \dot{x}_t^u;\ \ s_t^l[0] = \dot{x}_t^l;$

   inital $m_t^u[k] = m_t^l[k] = 0$ for all layers.
   //S-IBP
   for $k = 1$ **to** K **do**
      //spatial update (Equation 11)
      $m_t^u[k] + = sp_t^u[k];\ \ \ m_t^l[k] + = sp_t^l[k]$
      //temporal update (Equation 9)
      if $t < T'$ **then**
         $m_{t+1}^u[k] = \alpha * z_t^u;\ \ \ m_{t+1}^l[k] = \alpha * z_t^l;$
      end if
      //fire (Equation 7)
      $s_t^u[k] = fire(m_t^u[k] - th);\ \ \ s_t^l[k] = fire(m_t^l[k] - th);$
   end for
end for
Return upper and lower bound of intermediate data $\dot{x}_t^u, \dot{x}_t^l, m_t^u, m_t^l, s_t^u, s_t^l$

---

223 **S-CROWN**: Note that the goal of S-CROWN is to formulate the output bounds of a model as linear
224 equations of input's upper and lower bounds. The boundary of S-CROWN is computed from the
225 backward direction, and the detail is shown in Algorithm 2. Finally, we can follow the robust training
226 method in (Zhang et al., 2020) and use the lower bound of S-CROWN to train the SNN model.

Algorithm 2 S-CROWN

Input:
$\dot{x}_t^u, \dot{x}_t^l, m_t^u, m_t^l, s_t^u, s_t^l$ from S-IBP;   robust training time steps T';
Func:
//S-CROWN
build identity I matrix; $As_t[K] = I/T';$
for $k = K$ **to** 1 **do**
   initial $Am_t[k] = 0$ for all time steps
   for $t = T'$ **to** 1 **do**
      //fire (Equation 8)
      build $m_t[k] * d1^l + b1^l \le s_t[k] \le m_t[k] * d1^u + b1^u;$
      $Am_t[k] + = As_t[k]^- * d1^u + As_t[k]^+ * d1^l;$
      $bias\ \ \ \ + = As_t[k]^- * b1^u + As_t[k]^+ * b1^l;$
      //temporal update (Equation 10)
      if $t > 1$ **then**
         build $m_{t-1}[k] * d2^l + (1 - s_{t-1}[k]) * d3^l \le z_{t-1}[k];$
         build $m_{t-1}[k] * d2^u + (1 - s_{t-1}[k]) * d3^u \ge z_{t-1}[k];$
         $Am_{t-1}[k] = \alpha * (Am_t^-[k] * d2^u + Am_t^+[k] * d2^l);$
         $tmp_s\ \ \ \ = \alpha * (Am_t^-[k] * d3^u + Am_t^+[k] * d3^l);$
         $As_{t-1}[k] - = tmp_s;\ \ \ bias + = sum(tmp_s);$
      end if
      //spatial update;
      $As_t[k-1] = Am_t[k] * w[k-1];\ \ \ \ bias + = Am_t[k] * b[k-1];$
   end for
end for
Return $\sum_t \left(As_t[0] * (\dot{x}_t^u + \dot{x}_t^l)/2 - |As_t[0]| * (\dot{x}_t^u - \dot{x}_t^l)/2 \right) + bias$

---

4 Experiment

4.1 Experiment Setup

Dataset and Network Structure: In this work, we evaluate our robust training method on three
datasets: MNIST (LeCun et al., 1998), FMNIST (Xiao et al., 2017) and NMNIST (Orchard et al.,

2015). MNIST and FMNIST are digital datasets and NMNIST is spike dataset. For each dataset, we use two network structures in experiments. The detailed setting for datasets and network structures are shown in Table 1. We set the firing threshold th and decay factor α to 0.25 in Equation 1 and 3. Our experiments are conducted by Pytorch 3.8. The hardware we use is GPU V100.

Table 1: Datasets and network structure

	Input Type	Size	Time Step	FC Acc	CONV Acc
MNIST	digital	1*28*28	10	98.45%	99.09%
FMNIST	digital	1*28*28	10	87.58%	89.53%
NMNIST	spike	2*34*34	10	98.30%	99.05%
FC	X-FC512-FC256-FC10				
CONV	X-C64K3S2-C128K3S2-FC256-FC10				

Original and Robust Training: In original training, we adopt BPTT based training (Wu et al., 2018). We train 80 epochs for each SNN model. The learning rate is set to 0.01 at the beginning, it decays to 0.001 at the 55^{th} epoch. In robust training, we use the lower bound of S-CROWN as the loss function. During robust training, we set ϵ to 0 at the beginning. It will increase linearly to the final ϵ during the first 250 training epochs. In the last 50 training epochs, ϵ is unchanged.

Adversarial Attack: In this work we adopt the untargeted white-box gradient-based attack (Liang et al., 2021a) in SNN. In our experiment, we select 300 examples for each dataset to apply adversarial attack. In order to bound the noise of adversarial examples, we involve additional constraints during the attack. Specifically, for digital inputs, we clip the adversarial example for each attack iteration to make the adversarial example stay in the boundary. For spike inputs, each attack iteration we limit the amount of changed elements to $size(\hat{x}) * \epsilon/2$ and $size(\hat{x}) * \epsilon/6$ for FC and CONV networks to achieve the highest attack efficiency.

Figure 4: Impact of robust training time steps T' on (a) original accuracy and (b) S-CROWN loss. (CONV model; MNIST dataset; $\epsilon = 0.12$)

Figure 5: Original accuracy, S-CROWN loss and S-CROWN robust error during robust training under (a) MNIST; (b) FMNIST and (C) NMNIST datasets with different network structures and ϵ.

4.2 Robust Training in SNNs

Selection of Robust Training Time Steps T': We do not follow the original time steps during the robust training. Because the spatial computations in SNNs share the same parameters between

Table 2: Comparing untargeted white-box gradient-based attack between the original model and the model after robustness training.

| | | MNIST (FC-ϵ=0.12, CONV-ϵ=0.12) | | | | | FMNIST (FC-ϵ=0.01, CONV-ϵ=0.005) | | | | | NMNIST (FC-ϵ=0.005, CONV-ϵ=0.005) | | | |
| | attack | original network | | robust network | | attack | original network | | robust network | | attack | original network | | robust network | |
	ϵ	org err	attack err	org err	attack err	ϵ	org err	attack err	org err	attack err	ϵ	org err	attack err	org err	attack err
FC	0.104	0.3%	19.3%	4.7%	16.6% (-2.7%)	0.040	13.0%	20.7%	13.6%	20.0%(-0.7%)	0.0007	3.7%	21.0%	3.7%	10.0%(-11.0%)
	0.124	0.3%	29.7%	4.7%	20.3% (-9.4%)	0.070	13.0%	29.7%	13.3%	24.0%(-5.7%)	0.0009	3.7%	30.7%	3.7%	12.3%(-18.4%)
	0.140	0.3%	39.0%	4.7%	23.3%(-15.7%)	0.100	11.7%	41.3%	14.0%	32.0%(-9.3%)	0.0012	3.7%	41.3%	3.7%	16.7%(-24.6%)
	0.154	0.3%	50.0%	5.0%	24.3%(-25.7%)	0.114	13.3%	49.7%	13.6%	38.7%(-11.0%)	0.0014	3.7%	48.7%	3.7%	18.3%(-30.4%)
CONV	0.120	0.3%	18.7%	3.7%	8.3%(-10.4%)	0.040	10.0%	19.7%	18.0%	22.0%(+0.3%)	0.0008	1.3%	20.0%	4.3%	7.0%(-13.0%)
	0.140	0.3%	29.0%	4.0%	9.0%(-20.0%)	0.060	10.3%	28.3%	17.3%	23.0%(-5.3%)	0.0010	1.3%	33.7%	4.3%	11.0%(-22.7%)
	0.170	0.3%	40.7%	3.3%	10.7%(-30.0%)	0.080	10.0%	41.3%	17.0%	25.7%(-15.6%)	0.0012	1.3%	41.0%	4.3%	11.0%(-30.0%)
	0.190	0.3%	50.7%	4.0%	13.0%(-37.7%)	0.100	10.3%	52.3%	16.7%	34.3%(-18.0%)	0.0015	1.3%	49.0%	4.3%	12.0%(-37.0%)

different time steps, we can use arbitrary robust training time steps T'. In Figure 4 we analyzed the impact of T' on original accuracy and S-CROWN loss. Note that we would like to keep a higher original accuracy but reduce the S-CROWN loss after the robust training. From the result, we can find that $T' = 3$ gives the optimal solution. It implies that a too smaller T' cannot capture the temporal dynamics of SNNs and a larger T' may cause the boundary functions in S-CROWN to become too loose. Also we find that the robust training time for each epoch is $2.6\times$, $7.7\times$, and $12.9\times$ with respect to the original plain training when we set T' to 1, 3, and 5. Thus, the selection of T' also affects the robust training efficiency. In the rest of our evaluations, we set $T' = 3$ for all robust training.

Robust Training on Variaous Datasets: The analysis of robust training on different datasets with various ϵ and network structures is shown in Figure 5. From the result, we have the following observations: 1. During the robust training, it is more stable for a fully connected network(yellow curves are smoother than blue curves) because of the simpler network structure. 2. With a larger ϵ, the original accuracy is dropped more after the robust training. Also, it is more difficult to achieve a smaller robust error with larger ϵ. 3. In the MNIST dataset, when the network structure is CONV, the robust training is more stable as ϵ becomes larger. The potential reason is that when ϵ is small, the flipped regions in spike inputs are more diverse. 4. In FMNIST and NMNIST datasets, when the network structure is CONV, the robust training is much more fluctuating. For FMNIST dataset, the unstable may be caused by the more complicated input data (cloths) and the lower convergence in original training (final accuracy is 89.53%). For NMNIST dataset, the unstable may come from the larger input data size. A larger input size indicates the potential input regions that can be attacked becomes more. By considering the original accuracy and S-CROWN result after the robust training, we select the ϵ as shown in Table 2. We use FC-ϵ and CONV-ϵ to represent the noise boundary we selected for different network structures during robust training.

4.3 Network Robustness Evaluation

We use untargeted white-box adversarial attack to compare the robustness between the original model and the model after robust training. The robustness comparison is shown in Table 2. We use the original error rate to reflect the accuracy of a model on the 300 test data. The original error may have variance during the evaluation for the digital image dataset because of the input sampling mechanism. In our experiment, we select the attack ϵ to achieve approximately 20%, 30%, 40%, and 50% attack error rate on the original model. From the result, we can find that after the robust training, the models are harder to be attacked with adversarial example in all cases. We also find that the model after robust training is more secure when the attack ϵ is larger, even though the ϵ for robust training is far smaller. The potential reason is that the binary behavior of the spike events causes the boundary propagation to diverge quickly, which makes the final boundary cover more noisy inputs. Finally, we find that model robustness can be improved more when the network structure is CONV, since more paramters can be adjusted under the CONV model. From the result, we find that the CONV model in MNIST achieves the highest robustness improvement, i.e. the attack error rate reduces 37.7% with 3.7% original accuracy loss when the attack ϵ equals 0.190.

5 Discussion & Conclusion

In this work, we aim to design an efficient robust training method for SNNs based on the certified methods. Specifically, we design S-IBP and S-CROWN to tackle the distinct non-linear neuron behaviors in SNNs. Also, we formulate the input boundary for different input types. Based on our results, we can achieve at most 37.7% attack error reduction with 3.7% original accuracy loss, which demonstrates the efficiency of our proposed method.

Border Impact

SNN is a class of neural networks that inherit the biological model of the neuron dynamics in the brain. As the accuracy of SNNs becomes higher, the security issue attracts more attention. In this work, we design S-IBP and S-CROWN that apply certification-based robust training to improve the robustness of an SNN model. Our work can help to improve the misclassification rate of an SNN in real-world deployments. We believe our work can provide a positive impact on the performance of the SNN models. Also, we encourage researchers to seek other techniques and factors that can potentially affect the performance of an SNN model.

References

Akopyan, F., Sawada, J., Cassidy, A., Alvarez-Icaza, R., Arthur, J., Merolla, P., Imam, N., Nakamura, Y., Datta, P., Nam, G.-J., et al. Truenorth: Design and tool flow of a 65 mw 1 million neuron programmable neurosynaptic chip. *IEEE transactions on computer-aided design of integrated circuits and systems*, 34(10):1537–1557, 2015.

Athalye, A., Carlini, N., and Wagner, D. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *International conference on machine learning*, pp. 274–283. PMLR, 2018.

Balunović, M. and Vechev, M. Adversarial training and provable defenses: Bridging the gap. In *8th International Conference on Learning Representations (ICLR 2020)(virtual)*. International Conference on Learning Representations, 2020.

Bhattacharjee, A., Kim, Y., Moitra, A., and Panda, P. Examining the robustness of spiking neural networks on non-ideal memristive crossbars. *arXiv preprint arXiv:2206.09599*, 2022.

Büchel, J., Faber, F., and Muir, D. R. Network insensitivity to parameter noise via adversarial regularization. *arXiv preprint arXiv:2106.05009*, 2021a.

Büchel, J., Lenz, G., Hu, Y., Sheik, S., and Sorbaro, M. Adversarial attacks on spiking convolutional networks for event-based vision. *arXiv preprint arXiv:2110.02929*, 2021b.

Carlini, N. and Wagner, D. Towards evaluating the robustness of neural networks. In *2017 ieee symposium on security and privacy (sp)*, pp. 39–57. IEEE, 2017.

Davies, M., Srinivasa, N., Lin, T.-H., Chinya, G., Cao, Y., Choday, S. H., Dimou, G., Joshi, P., Imam, N., Jain, S., et al. Loihi: A neuromorphic manycore processor with on-chip learning. *Ieee Micro*, 38(1):82–99, 2018.

Deng, L., Wu, Y., Hu, X., Liang, L., Ding, Y., Li, G., Zhao, G., Li, P., and Xie, Y. Rethinking the performance comparison between snns and anns. *Neural Networks*, 121:294–307, 2020.

El-Allami, R., Marchisio, A., Shafique, M., and Alouani, I. Securing deep spiking neural networks against adversarial attacks through inherent structural parameters. In *2021 Design, Automation & Test in Europe Conference & Exhibition (DATE)*, pp. 774–779. IEEE, 2021.

Fan, J. and Li, W. Adversarial training and provable robustness: A tale of two objectives. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 7367–7376, 2021.

Gerstner, W., Kistler, W. M., Naud, R., and Paninski, L. *Neuronal dynamics: From single neurons to networks and models of cognition*. Cambridge University Press, 2014.

Gowal, S., Dvijotham, K., Stanforth, R., Bunel, R., Qin, C., Uesato, J., Arandjelovic, R., Mann, T., and Kohli, P. On the effectiveness of interval bound propagation for training verifiably robust models. *arXiv preprint arXiv:1810.12715*, 2018.

Kim, Y. and Panda, P. Revisiting batch normalization for training low-latency deep spiking neural networks from scratch. *Frontiers in neuroscience*, pp. 1638, 2020.

Kim, Y. and Panda, P. Visual explanations from spiking neural networks using inter-spike intervals. *Scientific reports*, 11(1):1–14, 2021.

Kim, Y., Park, H., Moitra, A., Bhattacharjee, A., Venkatesha, Y., and Panda, P. Rate coding or direct coding: Which one is better for accurate, robust, and energy-efficient spiking neural networks? In *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 71–75. IEEE, 2022.

Kundu, S., Pedram, M., and Beerel, P. A. Hire-snn: Harnessing the inherent robustness of energy-efficient deep spiking neural networks by training with crafted input noise. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 5209–5218, 2021.

LeCun, Y., Bottou, L., Bengio, Y., and Haffner, P. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Liang, L., Hu, X., Deng, L., Wu, Y., Li, G., Ding, Y., Li, P., and Xie, Y. Exploring adversarial attack in spiking neural networks with spike-compatible gradient. *IEEE Transactions on Neural Networks and Learning Systems*, 2021a.

Liang, L., Qu, Z., Chen, Z., Tu, F., Wu, Y., Deng, L., Li, G., Li, P., and Xie, Y. H2learn: High-efficiency learning accelerator for high-accuracy spiking neural networks. *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems*, 2021b.

Marchisio, A., Pira, G., Martina, M., Masera, G., and Shafique, M. Dvs-attacks: Adversarial attacks on dynamic vision sensors for spiking neural networks. In *2021 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–9. IEEE, 2021.

Mirman, M., Gehr, T., and Vechev, M. Differentiable abstract interpretation for provably robust neural networks. In *International Conference on Machine Learning*, pp. 3575–3583, 2018.

Narayanan, S., Taht, K., Balasubramonian, R., Giacomin, E., and Gaillardon, P.-E. Spinalflow: an architecture and dataflow tailored for spiking neural networks. In *2020 ACM/IEEE 47th Annual International Symposium on Computer Architecture (ISCA)*, pp. 349–362. IEEE, 2020.

Orchard, G., Jayawant, A., Cohen, G. K., and Thakor, N. Converting static image datasets to spiking neuromorphic datasets using saccades. *Frontiers in neuroscience*, 9:437, 2015.

Patrick, L., Posch, C., and Delbruck, T. A 128x 128 120 db 15μ s latency asynchronous temporal contrast vision sensor. *IEEE journal of solid-state circuits*, 43:566–576, 2008.

Sharmin, S., Panda, P., Sarwar, S. S., Lee, C., Ponghiran, W., and Roy, K. A comprehensive analysis on adversarial robustness of spiking neural networks. In *2019 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–8. IEEE, 2019.

Szegedy, C., Zaremba, W., Sutskever, I., Bruna, J., Erhan, D., Goodfellow, I., and Fergus, R. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Tsuzuku, Y., Sato, I., and Sugiyama, M. Lipschitz-margin training: Scalable certification of perturbation invariance for deep neural networks. *Advances in neural information processing systems*, 31, 2018.

Wang, S., Zhang, H., Xu, K., Lin, X., Jana, S., Hsieh, C.-J., and Kolter, J. Z. Beta-crown: Efficient bound propagation with per-neuron split constraints for neural network robustness verification. *Advances in Neural Information Processing Systems*, 34:29909–29921, 2021.

Wong, E. and Kolter, J. Z. Provable defenses against adversarial examples via the convex outer adversarial polytope. In *International Conference on Machine Learning*, 2018.

Wu, Y., Deng, L., Li, G., Zhu, J., and Shi, L. Spatio-temporal backpropagation for training high-performance spiking neural networks. *Frontiers in neuroscience*, 12, 2018.

Xiao, H., Rasul, K., and Vollgraf, R. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017.

Xu, K., Shi, Z., Zhang, H., Wang, Y., Chang, K.-W., Huang, M., Kailkhura, B., Lin, X., and Hsieh, C.-J. Automatic perturbation analysis for scalable certified robustness and beyond. *Advances in Neural Information Processing Systems*, 33, 2020a.

Xu, K., Zhang, G., Liu, S., Fan, Q., Sun, M., Chen, H., Chen, P.-Y., Wang, Y., and Lin, X. Adversarial t-shirt! evading person detectors in a physical world. In *European Conference on Computer Vision*, pp. 665–681. Springer, 2020b.

Zhang, H., Weng, T.-W., Chen, P.-Y., Hsieh, C.-J., and Daniel, L. Efficient neural network robustness certification with general activation functions. *arXiv preprint arXiv:1811.00866*, 2018.

Zhang, H., Chen, H., Xiao, C., Gowal, S., Stanforth, R., Li, B., Boning, D., and Hsieh, C.-J. Towards stable and efficient training of verifiably robust neural networks. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=Skxuk1rFwB`.

 Appendix

A   S-CROWN on Directed Encoding

Figure 6: Original accuracy, S-CROWN loss and S-CROWN robust error during robust training under MNIST database with direct encoding.

Instead of rate-coding, directed encoding is another popular input coding mechanism that directly applies a CONV or FC layer on the original digital as the first layer (Wu et al., 2018; Kim et al., 2022). Currently, the directed encoding only takes digital inputs. Since the input does not involve sampling or binary patterns, we can apply ℓ_∞ norm to build the input bounds. The results of certification-based robust training are shown in Figure 6. From the result, we can find that the indicators (original acc, S-CROWN loss, S-CROWN robust error) during training follow a similar trend as the rate-coding.

Table 3: Untargeted white-box gradient-based attack on MNIST database with directed encoding.

	attack	original network		robust network	
		MNIST (FC-ϵ=0.12 CONV-ϵ=0.20)			
	ϵ	org err	attack err	org err	attack err
FC	0.060	1.3%	21.0%	7.7%	22.7% (+1.7%)
	0.070	1.3%	30.3%	7.7%	24.3% (-6.0%)
	0.080	1.3%	38.0%	7.7%	26.3% (-15.7%)
	0.092	1.3%	49.0%	7.7%	30.7% (-18.3%)
CONV	0.150	0.0%	21.3%	7.3%	11.7% (-9.6%)
	0.180	0.0%	33.3%	7.3%	13.3% (-20.0%)
	0.200	0.0%	42.0%	7.3%	15.0% (-27.0%)
	0.210	0.0%	50.3%	7.3%	20.7% (-29.6%)

Next, we evaluate the model robustness against adversarial training in Table 3. As the result, our method can at most achieve 29.6% error rate reduced with 7.3% original accuracy loss, which demonstrated the effectiveness of our proposed method on directed encoding.

B   Example of Input Bounds

Figure 7: A visual example of bounds for one time step in the MNIST database: (a) the original digital image; (b) the sampled result based on the original image (c) the sampled upper bound and (d) the sampled lower bound.

An example of input bounds after sampling for the MNIST database is shown in Figure 7. Here, we show the upper and lower bounds for one time step. After we applied the bounding method in Section 3.2 the background of the lower bound image before sampling is the same as the original image whose gray values are 0. In contrast, the skeleton of the content in the upper bound image before sampling is unchanged compared to the original image. The gray values of the skeleton are 1. Note that the unstable points are located in the region where the gray values in the bounded image differ from the original image. Thus, the number of unstable points in the upper bound after sampling is more, most of them located in the background.