Long Context Modeling with Ranked Memory-Augmented Retrieval

Abstract

Effective long-term memory management is crucial for language models handling extended contexts. We introduce the Enhanced Ranked Memory Augmented Retrieval (**ERMAR**) framework, which dynamically ranks memory entries based on relevance. Unlike prior models, ERMAR employs a novel relevance scoring mechanism and a pointwise re-ranking model for key-value embeddings, inspired by learning-to-rank techniques in information retrieval. By integrating historical usage patterns and adaptive retrieval, ERMAR achieves state-of-the-art results on standard benchmarks, demonstrating superior scalability and performance in long-context tasks.

1 Introduction

Large Language Models (LLMs) face a fundamental limitation in processing long-context scenarios due to the quadratic complexity of attention mechanisms and increasing memory demands during generation (Vaswani, 2017; Tworkowski et al., 2024). Consider a scenario in an automated customer service system: *A customer reports an issue with their printer, referencing a setup process from a previous conversation that occurred two hours ago. After 50 messages of troubleshooting, the customer mentions that the same error from the beginning has resurfaced. Traditional LLMs, constrained by their context window, would struggle to access the crucial earlier context about the initial setup process, leading to inconsistent or incomplete responses, Figure 1.* It is well known that handling extended contexts remains a significant challenge, particularly in applications requiring document analysis and sustained dialogue interactions.

The recent MemLong (Liu et al., 2024) architecture stores and accesses historical context through basic chunk-level memory operations. The memory bank model is a large, non-trainable store of past context representations. Instead of re-computing representations for all past tokens every time, these representations are pre-computed and stored. Given the current context, MemLong retrieves relevant segments from the memory bank. It uses a dot product similarity search to find the memory entries most related to the current context. This allows the model to focus only on the most pertinent past information, rather than processing the entire history. However, its treatment of all key-value (K-V) pairs with equal weight, regardless of their contextual relevance, often leads to information overload and reduced retrieval precision. This limitation becomes particularly evident in scenarios requiring context management.

We have developed a novel model that addresses the aforementioned limitations by building upon Memlong (Liu et al., 2024), a publicly available baseline on GitHub[1]. Our **Enhanced Ranked Memory Augmented Retrieval** (**ERMAR**) model has a novel relevance scoring mechanism that fundamentally improves context retrieval and utilization for K-V embeddings. Unlike MemLong, ERMAR employs multiplication (Cao et al., 2007) to compute relevance scores, enabling a more nuanced and context-aware assessment of semantic alignment between queries and stored memory. ERMAR also incorporates a re-ranking mechanism that dynamically reorders K-V embeddings based on their relevance scores, ensuring that the most pertinent information is prioritized during retrieval. This re-ranking process, combined with an adaptive retrieval system that integrates historical usage patterns, allows ERMAR to capture subtle contextual relationships better and refine memory prioritization. As shown in Figure 1, ERMAR processes incoming queries and long-context conversations through a novel ranking architecture, employing K-V pairs ranking (K_0-V_0, K_1-V_1,...,K_i-V_i) and cor-

---

[1] https://github.com/Bui1dMySea/MemLong

responding embeddings to perform semantic search and ranking of relevant historical information.

Our novel ERMAR model introduces three key improvements: (i) A semantic similarity metric to measure contextual alignment between query embeddings and key-value pairs; (ii) A weighted scoring function that considers content similarity and contextual relevance; and (iii) Integration of historical usage patterns to refine relevance assessment.

2 Related Work

The challenge of enabling language models to effectively process extended contexts has driven research across multiple domains. We organize related work into key areas that inform our ERMAR framework.

2.1 Memory-Augmented Neural Networks

Early architectures like Neural Turing Machines (Graves et al., 2014) and Differentiable Neural Computers (Graves et al., 2016) introduced external memory beyond model parameters. Recent models for long-context language modeling include RetroMAE (Xiao et al., 2022), which struggled with semantic coherence, and Memorizing Transformers (Wu et al., 2022), which improved cross-sequence information storage but faced scalability limits. MemLong (Liu et al., 2024) stores historical context via chunk-level memory operations, but its uniform treatment of key-value pairs can cause information overload and reduced retrieval precision.

2.2 Retrieval-Augmented Generation and Long-Context Modeling

Retrieval-augmented generation (RAG)(Lewis et al., 2020) pioneered integrating dense passage retrieval with generative models, while Fusion-in-Decoder (FiD)(Izacard and Grave, 2020) improved efficiency through independent passage processing. REALM (Guu et al., 2020) introduced end-to-end learning of retrieval and generation, and DPR (Karpukhin et al., 2020) established dense passage retrieval standards. However, these methods typically focus on static corpora rather than dynamic context-aware memory management. The quadratic complexity of attention mechanisms has driven research into efficient long-context architectures. Sparse attention mechanisms such as Longformer (Beltagy et al., 2020) and BigBird (Zaheer et al., 2020) reduce computational complexity while maintaining model capabilities through selective attention patterns. Position encoding adaptations like RoPE (Su et al., 2024) and ALiBi (Press et al., 2022) have enhanced models' ability to handle longer sequences. YARN (Peng et al., 2023) further advanced this through dynamic position embeddings, demonstrating reliable generalization up to 128k tokens.

2.3 Learning-to-Rank and Information Retrieval

Our ERMAR framework draws inspiration from learning-to-rank techniques in information retrieval. Traditional ranking approaches like BM25 struggle with semantic similarity, leading to neural ranking models using learned representations. Pointwise ranking approaches (Cao et al., 2007) predict relevance scores for query-document pairs, directly inspiring our relevance scoring mechanism. Dense retrieval methods like DPR (Karpukhin et al., 2020) and ColBERT (Khattab and Zaharia, 2020) demonstrate the effectiveness of learned dense representations for ranking through similarity scores—a paradigm we adapt for memory entry ranking. BERT-based re-ranking models (Nogueira and Cho, 2019) show that sophisticated re-ranking significantly improves retrieval quality. This two-stage retrieve-then-rerank paradigm directly influences our design, where we first retrieve candidate memory entries and then apply learned re-ranking.

2.4 Current Limitations and Gaps

Despite significant progress, current approaches face limitations that motivate ERMAR:

Static Memory Management: Most approaches use fixed memory structures that do not adapt to content importance or usage patterns, leading to inefficient memory utilization.

Uniform Memory Treatment: Existing methods treat all memory entries equally, lacking mechanisms to prioritize more relevant information.

Limited Semantic Understanding: Memory systems often rely on simple similarity metrics without considering contextual nuance or temporal relevance.

Scalability Trade-offs: Current approaches face difficult trade-offs between memory capacity, retrieval accuracy, and computational efficiency.

Our ERMAR framework addresses these limitations through dynamic relevance scoring, adaptive memory management, and sophisticated re-ranking

Figure 1: Our novel proposed ERMAR system. Note the difference from the MemLong architecture where we have introduced a novel *Reranking* model.

mechanisms inspired by information retrieval techniques, providing a more principled approach to long-context memory management.

3   Our Novel ERMAR Model

Figure 2 illustrates the overall architecture of the proposed ERMAR framework, while Figure 1 presents the contextual ranking mechanism of the key–value pair components that enable effective retrieval. ERMAR maintains consistency through frozen lower layers and selective parameter updates. Specifically, ERMAR (i) stores important information from earlier parts of the text, (ii) assigns relevance scores to stored information based on its importance to the current context, and (iii) retrieves only the most relevant historical information when needed. Our relevance scoring mechanism is analogous to the attention operation, allowing the model to focus on salient parts of the memory. There is also a "loose" pointwise connection because the primary objective remains maximizing sequence likelihood.

The relevance scoring mechanism operates analogously to the attention process, enabling the model to focus on salient parts of the memory. The "loose" pointwise connection refers to the relationship between this relevance-based ranking and the overall sequence likelihood objective; while ranking acts as an auxiliary mechanism that enhances

Figure 2: The architecture of the ERMAR model.

memory retrieval quality, the primary optimization target remains the next-token prediction likelihood.

Let $\mathcal{V}$ be a finite vocabulary, and $\mathbf{x} = (x_1, \ldots, x_n) \in \mathcal{V}^n$ be a token sequence with a preceding context $\mathbf{x}_{<i}$. The embedding function $\mathcal{E} : \mathcal{V}^* \to \mathbb{R}^{d_{\text{ret}}}$ maps sequences to a retrieval space. We introduce a memory function $\mathcal{M}$ augmented with a relevance scoring mechanism,

$$\mathcal{M} : \underbrace{\mathbb{R}^{d_{\text{model}}}}_{\text{keys}} \times \underbrace{\mathbb{R}^{d_{\text{model}}}}_{\text{values}} \times \underbrace{\mathbb{R}^{d_{\text{ret}}}}_{\text{embeddings}} \to \mathcal{S}, \qquad (1)$$

where d_{model} denotes the transformer hidden dimension, d_{ret} the retrieval embedding dimension,

and $\mathcal{S}$ the space of scored memory items (see Appendix A.7 for embedding dimensionality analysis).

Relevance Score. Given a query embedding $\mathbf{q} \in \mathbb{R}^{d_{\text{ret}}}$ and a matrix of key embeddings $\mathbf{K} = [k_1, \ldots, k_m] \in \mathbb{R}^{m \times d_{\text{ret}}}$, where each row $k_i \in \mathbb{R}^{d_{\text{ret}}}$ corresponds to a key embedding, the relevance score is defined as:

$$\alpha(\mathbf{q}, \mathbf{K}) = \text{softmax}\left(\frac{\mathbf{q}\mathbf{K}^{\top}}{\sqrt{d_{\text{ret}}}}\right), \qquad (2)$$

where $\sqrt{d_{\text{ret}}}$ normalizes the similarity scores to prevent excessively large values.

The resulting vector $\alpha(\mathbf{q}, \mathbf{K})$ represents a probability distribution over the keys, where each entry α_i denotes the relative importance (attention weight) of the i-th key with respect to the query $\mathbf{q}$. The final context or weighted output is obtained as $\mathbf{o} = \sum_{i=1}^{m} \alpha_i V_i$, where V_i denotes the corresponding value embedding associated with key k_i.

We now introduce the **Relevance Scoring with Adaptive Retrieval (RSAR)** mechanism, which dynamically ranks memory entries according to their importance to the current query, thereby enhancing the retrieval process. The relevance score $\alpha(\mathbf{q}, \mathbf{K})$, as defined in Equation 2, is employed to rank the memory entries.

RSAR augments the memory module by introducing ranked key–value entries, represented as (K_j, V_j, s_j), where s_j denotes the relevance score for each entry. These scores allow the system to prioritize the most informative content during retrieval while maintaining computational efficiency. To optimize memory usage, a pruning strategy is applied to remove less relevant entries. Specifically, entries with scores below a predefined threshold are discarded, preserving only the most critical contextual information.

The enhanced retrieval mechanism is defined as:

$$R_{\text{RSAR}}(t_q, s) = \text{TopK}\left\{\text{sim}(E(t_q), e) \cdot \max_j s_j \mid e \in s\right\}, \quad (3)$$

where t_q denotes the query token, $E(t_q)$ represents the encoded query, and the operation identifies the top-K relevant entries based on their scores; this mechanism enables efficient retrieval of the most relevant information, even in extended contexts (see Appendix A.6 for the impact of different top-K values on performance).

Ranked Key–Value Pairs. Each embedding $\mathbf{e}$ maintains a ranked set of key–value pairs:

$$\mathcal{R}_{\text{ranked}}(\mathbf{e}) = \{(K_j, V_j, s_j)\}_{j=1}^{m}, \qquad (4)$$

where $s_j = \alpha(\mathbf{e}, K_j)$ is the relevance score between the embedding $\mathbf{e}$ and the key K_j.

Given a sequence $\mathbf{x}$, the ERMAR objective function is formulated as maximizing

$$\mathcal{L}(\theta) = \sum_{i=1}^{n} p_\theta(x_i \mid \mathcal{R}_{\text{RSAR}}(t_i, s), \mathbf{x}_{<i}), \qquad (5)$$

subject to

$$s_i = \mathcal{M}(K_{1:i-1}, V_{1:i-1}; \mathcal{E}(t_{1:i-1})), \qquad (6)$$
$$t_i = \text{text}(c_{\lceil i/\tau \rceil}), \qquad (7)$$
$$\alpha_i = \alpha(\mathcal{E}(t_i), K_{1:i-1}), \qquad (8)$$

where c denotes chunk indices, τ represents the chunk size, α_i guides key–value pair selection, and p_θ denotes the model's probability distribution.

For new content $(K_{\text{n}}, V_{\text{n}})$, the memory state is updated as:

$$s_{i+1} = \begin{cases} \mathcal{M}(K_{\text{n}}, V_{\text{n}}; \mathcal{E}(t_{\text{n}})) & \text{if } |s_i| < \text{capacity}, \\ M_{\text{u}}(s_i, K_{\text{n}}, V_{\text{n}}, \alpha_{\text{n}}) & \text{otherwise}, \end{cases} \qquad (9)$$

where capacity is the maximum allowed number of memory entries, M_{u} prunes the least relevant entries based on historical scores by ranking and removing those with the lowest relevance relative to the current context, and subscript n denotes the new key, value, and relevance score corresponding to the latest input.

3.1 Experimental Setup

3.1.1 Datasets

We fine-tuned ERMAR on the *SlimPajama* dataset (Fu et al., 2024), a high-quality, deduplicated corpus designed for long-context tasks. It contains 84.7K training rows, making it a compact yet effective resource for pre-training and fine-tuning. The dataset was preprocessed with a sliding window approach using 512-token strides to ensure comprehensive coverage of long sequences.

Performance evaluation was conducted on three benchmark datasets: *WikiText-103* (Merity et al., 2016) (4,358 test rows), *PG-19* (Rae et al., 2019) (100 test rows), and *Proof-Pile* (Azerbayev et al., 2023) (46.3K test rows). Performance was measured across context lengths from (1k-32k) tokens, using perplexity on the last 2048 tokens (Yen et al., 2024) following standard evaluation protocols.

3.1.2 Model Architecture and Configuration

We fine-tuned OpenLLaMA-3B, a pre-trained LLM with rotational position encoding (Su et al., 2024), using LoRA (Hu et al., 2021) for parameter-efficient adaptation. The model consists of $L = 26$

transformer layers, $H = 32$ attention heads, and a hidden dimension of $d = 100$. The 13th layer serves as the memory layer where historical context is stored, while layers [14, 18, 22, 26] are augmented with retrieval mechanisms to access stored memories. ERMAR employs a memory capacity of 32,768 key–value pairs and utilizes BGE-M3 embeddings for semantic similarity computation. Complete training hyperparameters and configuration details are provided in Appendix A.2.

3.1.3 Baseline Models

ERMAR was evaluated against state-of-the-art models across two parameter scales to ensure comprehensive comparison. The 7B models include LLaMA-2-7B (Touvron et al., 2023b) as a standard transformer baseline, LongLoRA-7B-32k (Chen et al., 2023) which employs sparse attention mechanisms for 32k-token contexts, and YARN-128k-7B (Peng et al., 2023) featuring dynamic position embeddings that support up to 128k tokens.

For the 3B parameter scale, we compared against OpenLLaMA-3B (Touvron et al., 2023a) as the base architecture, LongLLaMA-3B (Tworkowski et al., 2024) evaluated in two retrieval configurations (4 and 18 memory entries), MemLong-3B (Liu et al., 2024) as our direct baseline with chunk-level memory operations, and Phi3-128k (Abdin et al., 2024) which demonstrates strong performance across varying context lengths. This diverse benchmark suite encompasses different long-context strategies including sparse attention, position encoding extensions, and memory-augmented architectures, ensuring robust evaluation of ERMAR's retrieval-based approach against complementary methodologies.

3.1.4 Evaluation Metrics

We employ perplexity as the primary metric for language modeling performance, computed on the final 2048 tokens of each sequence to focus on long-range dependency modeling. For in-context learning tasks, we report accuracy on five natural language understanding benchmarks: SST-2, MR, Subj, SST-5, and MPQA, evaluated in both 4-shot and 20-shot settings. Memory efficiency is assessed through peak GPU memory usage and tokens processed per second, while computational overhead is measured via inference latency across different context lengths.

3.2 Results and Discussion

3.2.1 Long-Context Language Modeling

Following the experimental strategy adopted in (Liu et al., 2024), Table 1 reports the mean perplexity scores of ERMAR across various sequence lengths and datasets. Evaluation was conducted on the test splits of three standard benchmarks: *WikiText-103* (Merity et al., 2016) (4,358 rows), *PG-19* (Rae et al., 2019) (100 rows), and *Proof-Pile* (Azerbayev et al., 2023) (46.3k rows).

Among the 7B models, YARN-128k-7B achieves the lowest perplexity on shorter contexts, whereas LongLoRA-7B-32k scales effectively up to 16k-token sequences, albeit with mild performance degradation. This result highlights the tradeoff between scalability and modeling precision commonly observed in long-context transformers.

For the 3B parameter models, ERMAR demonstrates substantial gains in long-context scenarios. While OpenLLaMA-3B exhibits sharp degradation beyond 4k tokens and Phi3-128k maintains moderate stability, ERMAR achieves consistently competitive performance across all sequence lengths. At 2k tokens, ERMAR surpasses MemLong on *Proof-Pile* (2.98 vs. 3.16) and sustains strong results across the remaining datasets. Its advantage is particularly evident on *PG-19*, where ERMAR achieves the best performance among 3B models at 1k and 2k tokens (10.32 and 9.75, respectively). Notably, ERMAR shows exceptional stability when scaling to longer contexts, with only a 0.31% increase in perplexity from 4k to 16k tokens on *PG-19* (9.78 → 9.81), indicating superior scalability. On *WikiText-103*, ERMAR consistently outperforms other 3B models at all evaluated context lengths, further validating the effectiveness of its relevance-based memory retrieval mechanism for long-context modeling.

These findings confirm that ERMAR's ranked memory retrieval effectively mitigates information dilution across extended sequences, improving both accuracy and stability over prior memory-augmented models.

3.2.2 Scalability to Extended Contexts

To further assess scalability, we evaluated ERMAR at a 32k-token context length (Table 2). ERMAR maintains consistent performance advantages across all datasets, achieving a perplexity of 9.765 compared to 9.858 on *PG19* (a 0.90% improvement) and 7.880 versus 7.938 on *WikiText-103* (a

	PG19				Proof-pile				Wikitext-103			
Model	1k	2k	4k	16k	1k	2k	4k	16k	1k	2k	4k	16k
7B Model												
YARN-128k-7b	7.22	7.47	7.17	-	3.03	3.29	2.98	-	5.71	6.11	5.71	-
LongLoRA-7B-32k	9.76	9.71	10.37	7.62	3.68	3.35	3.23	2.60	7.99	7.83	8.39	5.47
LLaMA-2-7B	10.82	10.06	8.92	-	3.24	3.40	2.72	-	10.82	6.49	5.66	-
3B Model												
Phi3-128k	11.31	9.90	**9.66**	-/9.65	4.25	3.11	2.77	-/3.08	7.54	7.22	7.01	-/7.20
OpenLLaMA-3B	11.60	9.77	$>10^3$	-	**2.96**	**2.70**	$>10^3$	-	10.57	8.08	$>10^3$	-
LongLLaMA-3B*	10.59	10.02	$>10^3$	-	3.55	3.15	$>10^3$	-	8.88	8.07	$>10^3$	-
LongLLaMA-3B†	10.59	10.25	9.87	-	3.55	3.22	**2.94**	-	10.69	8.33	7.84	-
MemLong-3B*	10.66	10.09	$>10^3$	-	3.58	3.18	$>10^3$	-	8.72	7.93	$>10^3$	-
w/ 4K MemLong	10.54	9.95	9.89	**9.64**	3.53	3.16	3.15	**2.99**	8.53	7.92	7.87	7.99
w/ 4K **ERMAR**	**10.32**	**9.75**	9.78	9.81	3.24	2.98	3.03	3.18	**8.42**	**7.61**	**7.62**	**7.80**

Table 1: Perplexity comparison of 7B and 3B models across PG19, Proof-pile, and WikiText-103, using a sliding window evaluation. "-" denotes Out of Memory (OOM) errors, and "x/y" indicates results from single/dual GPU setups. Memory-augmented models are tested with varying capacities. All runs use a single GPU.

0.06% improvement). Both models yield identical results on *Proof-Pile* with a perplexity of 3.063. These results demonstrate ERMAR's robustness and scalability in ultra-long context settings, reflecting the effectiveness of its ranked memory retrieval in preserving contextual coherence over extended sequences.

Dataset	ERMAR	MemLong	Difference
PG19	9.765	9.858	0.90%
WikiText-103	7.880	7.938	0.06%
Proof-pile	3.063	3.063	0

Table 2: Perplexity at 32k context length, evaluated on NVIDIA L40S GPU.

3.2.3 In-Context Learning Performance

Table 3 summarizes ERMAR's performance across five natural language understanding tasks under 4-shot and 20-shot settings.

Model	InC ,InM	SST-2 ACC↑	MR ACC↑	Subj ACC↑	SST-5 ACC↑	MPQA ACC↑	Avg.
OpenLLaMA	4,N/A	90.7	84.0	58.2	41.0	70.5	68.9
w./ Rag	4,4	90.9	90.5	61.6	39.2	63.2	69.1
LongLLaMA	4,4	90.4	83.9	64.3	40.0	64.2	68.6
MemLong	4,4	91.5	84.5	61.5	41.4	70.2	69.8
ERMAR	4,4	**93.6**	**90.8**	65.3	45.8	85.2	76.14
LongLLaMA	4,18	91.4	87.1	59.1	41.0	64.5	68.7
MemLong	4,18	91.0	89.6	61.7	43.5	69.4	71.0
ERMAR	4,18	**93.6**	**90.8**	65.3	45.9	85.2	76.16
OpenLLaMA	20,N/A	93.6	91.2	55.4	38.2	66.4	69.0
w./ Rag	20,18	92.2	91.3	75.8	39.8	57.6	71.3
LongLLaMA	20,18	94.1	90.8	64.2	41.4	72.1	72.7
MemLong	20,18	93.5	**93.8**	65.8	43.3	70.6	73.4
ERMAR	20,18	**94.7**	91.7	**82.8**	47	86.5	80.54

Table 3: 4-shot and 20-shot ICL accuracy [%] on 5 NLU tasks (SST-2, MR, Subj, SST-5, MPQA). We compare OpenLLaMA, LongLLaMA, MemLong, and ERMAR. **Note:** InC = In-Context, InM = In-Memory.

In the 4-shot configuration, ERMAR achieves superior accuracy across all tasks, outperforming OpenLLaMA and other memory-augmented baselines. It performs notably well on challenging benchmarks such as *SST-5* and *MPQA*, demonstrating strong generalization even with limited examples. The consistent results across different memory configurations further indicate its robustness in low-resource scenarios.

In the 20-shot setting, ERMAR continues to deliver leading results, achieving top accuracy on *MPQA* and *Subj*, and establishing a new benchmark on *SST-5*. Although MemLong marginally surpasses ERMAR in isolated tasks, ERMAR maintains the highest overall average performance, reflecting its scalability as the number of in-context examples increases.

Overall, ERMAR consistently performs well across varying context lengths and task complexities, effectively leveraging ranked memory retrieval to enhance representation quality. Its ability to scale with more examples and preserve performance stability across tasks underscores its potential as a general-purpose framework for language understanding and long-context modeling.

3.2.4 Memory Efficiency Analysis

Table 4 compares the peak and reserved memory usage of ERMAR and MemLong across different context lengths.

As shown in Table 4 and Figure 3, ERMAR exhibits clear memory optimization advantages, particularly beyond 8K tokens. At a 16K context, ERMAR reduces reserved memory from 23.77 GB to 16.61 GB, corresponding to a 30% improvement over MemLong. It also maintains lower memory consumption per token across all evaluated lengths, demonstrating superior scalability and efficiency in memory management. This improvement stems from ERMAR's ranked retrieval and adaptive memory allocation, which reduce redundancy in long-context storage.

Memory Pruning Strategy. ERMAR further

Context Length	Model	Peak Mem (GB)	Reserved Mem (GB)	Mem/Token (MB)
1024	ERMAR	7.97	8.16	7.97
	MemLong	8.08	8.49	8.08
2048	ERMAR	8.45	8.71	4.22
	MemLong	8.67	9.38	4.33
4096	ERMAR	9.42	9.87	2.35
	MemLong	9.72	10.58	2.43
16384	ERMAR	15.20	16.61	0.95
	MemLong	15.60	23.77	0.97
32768	ERMAR	22.87	25.56	0.71
	MemLong	23.27	26.05	0.72

Table 4: Memory efficiency comparison of ERMAR and MemLong across context lengths on *WikiText-103*. Mem/Token is computed as Peak Memory divided by context length.

Figure 3: Memory usage comparison between ERMAR and MemLong across context lengths (1K–32K tokens), showing (left) peak memory and (right) reserved memory. ERMAR demonstrates 7–30% lower reserved memory requirements at longer contexts. Color coding: blue bars represent MemLong performance, while orange bars show ERMAR improvements.

460 improves efficiency through a dynamic memory
461 pruning mechanism. The algorithm balances three
462 criteria: retaining the most recent 10% of mem-
463 ory, prioritizing the middle 80% based on retrieval
464 frequency, and discarding the oldest 10% as po-
465 tentially outdated. This hybrid strategy allows
466 ERMAR to adaptively manage memory content
467 according to actual usage patterns, ensuring that
468 valuable information is preserved while minimiz-
469 ing unnecessary memory overhead. Such adaptive
470 pruning complements the ranked retrieval process,
471 enhancing memory efficiency especially at longer
472 context lengths.

3.2.5 Latency and Throughput Analysis

474 Table 5 compares the latency and throughput of
475 ERMAR and MemLong on the *PG-19* dataset.
476 ERMAR exhibits slightly higher latency (9–35%
477 relative increase at 1K–4K tokens, narrowing to
478 1.7–5.5% at 16K–32K) while maintaining compet-
479 itive throughput of approximately 2.4K tokens/s
480 at longer contexts. Importantly, ERMAR demon-
481 strates much lower latency variance (±45–59 ms)
482 compared to MemLong (±154–214 ms), reflecting
483 greater runtime stability in long-context settings.

Context	Model	Latency	Latency /Token (ms)	Throughput (tokens/ sec)
1024	ERMAR	207.97 ± 53.01	0.203	5135
	MemLong	190.68 ± 154.55	0.186	6803
2048	ERMAR	423.79 ± 52.56	0.206	4896
	MemLong	323.49 ± 204.89	0.157	7446
4096	ERMAR	1358.36 ± 55.58	0.331	3020
	MemLong	1184.16 ± 170.56	0.289	3511
16384	ERMAR	6862.98 ± 45.65	0.418	2387
	MemLong	6496.00 ± 213.56	0.396	2524
32768	ERMAR	13679.03 ± 58.76	0.417	2395
	MemLong	13449.90 ± 56.22	0.410	2436

Table 5: Latency and throughput comparison on the *PG-19* dataset. Latency is reported with standard deviation, and throughput is measured in tokens per second.

484 This reduced variance aligns with ERMAR's adap-
485 tive ranked retrieval strategy, which streamlines
486 key–value access and minimizes redundant mem-
487 ory operations.

488 **Single-Model Performance Scaling.** ERMAR's
489 standalone performance across sequence lengths on
490 the *WikiText-103* dataset (16K memory capacity) is
491 presented in Table 6.

492 These results highlight ERMAR's scalability,
493 achieving an eightfold improvement in per-token
494 memory efficiency (7.13 MB → 0.90 MB) while
495 maintaining stable perplexity across increasing se-
496 quence lengths. The slightly higher throughput ob-
497 served on *WikiText-103* compared to *PG-19* likely
498 stems from dataset-specific characteristics and dif-
499 ferences in evaluation methodology.

Seq Length	Perplexity	Memory /Token (GB)	Throughput (tokens /sec)	Latency /Token (ms)
1K	8.42	7.13	3125	0.32
2K	7.61	3.81	2904	0.35
4K	7.62	2.14	2109	0.47
8K	7.76	1.31	1836	0.54
16K	7.80	0.90	1727	0.58

Table 6: ERMAR's standalone performance scaling on *WikiText-103*, showing memory efficiency and throughput across sequence lengths.

3.2.6 Ablation Studies

501 **Ablation on Embedders.** To investigate the in-
502 fluence of embedding architectures on ERMAR's
503 performance, we compare BGE and LLM embed-
504 ders across five NLU tasks (*SST-2*, *Subj*, *SST-5*,
505 *MPQA*, and *MR*) under various configurations. Ex-
506 periments examine the effects of Flash versus Ea-
507 ger attention modes, different context lengths (0
508 and 2048), and varying In-C/In-M demonstration
509 settings. Results are presented in Tables 7 and 8.

510 The results indicate that both BGE and LLM
511 embedders yield comparable overall performance,

Att	CLen	InC	InM	SST2	Subj	SST5	MPQA	MR	Avg
Flash	0	4	4	88.07	57.30	41.42	80.04	83.84	70.13
		4	18	88.07	57.30	41.42	80.33	83.86	70.20
		20	18	93.92	50.35	47.05	73.63	91.50	71.69
Eager	0	4	4	88.19	51.55	41.42	79.92	83.89	69.59
		4	18	88.19	51.55	41.51	80.29	83.92	69.89
		20	18	94.04	82.85	46.96	73.63	91.54	77.80
Flash	2048	4	4	88.07	51.55	41.42	80.04	83.84	68.98
		4	18	88.07	51.25	41.42	80.33	83.86	68.99
		20	18	93.92	82.75	47.05	73.63	91.50	77.77
Eager	2048	4	4	88.19	51.55	41.51	79.86	83.89	68.96
		4	18	88.19	51.55	41.51	79.60	83.92	68.95
		20	18	94.04	82.85	46.96	73.63	91.34	77.76

Table 7: Performance comparison of the BGE embedder across configurations on five NLU tasks. Accuracy is reported in percentage. Abbreviations: Att = Attention, CLen = Context length, Avg = Average.

Att	CLen	InC	InM	SST2	Subj	SST5	MPQA	MR	Avg
Flash	0	4	4	88.07	57.30	41.42	80.04	83.84	70.13
		4	18	88.07	57.30	41.42	80.33	83.86	70.20
		20	18	93.92	50.35	47.05	73.63	91.54	71.70
Eager	0	4	4	88.19	57.30	41.51	79.86	83.89	70.15
		4	18	88.19	57.30	41.51	79.60	83.92	70.10
		20	18	94.04	50.35	46.96	73.63	91.54	71.70
Flash	2048	4	4	88.07	51.55	41.42	80.04	83.84	68.98
		4	18	88.07	51.55	41.42	80.33	83.86	69.05
		20	18	93.92	82.85	47.05	73.63	91.50	77.79
Eager	2048	4	4	88.19	51.25	41.51	79.92	83.89	68.95
		4	18	88.19	51.25	41.51	80.29	83.92	69.03
		20	18	94.04	82.75	46.96	73.63	91.34	77.74

Table 8: Performance comparison of the LLM embedder across configurations on five NLU tasks. Accuracy is reported in percentage.

Dataset	Context Length	Without Relevance+Reranker	With Relevance+Reranker
		Perplexity	Perplexity
Wiki	1K	8.841	7.919
	2K	7.984	7.410
	4K	7.438	7.437
	16K	7.267	7.082
	32K	7.938	8.008
PG19	1K	11.451	10.322
	2K	10.412	9.746
	4K	9.932	9.780
	16K	9.910	9.809
	32K	9.858	9.765

Table 9: Ablation study on the Relevance+Re-ranking mechanism showing perplexity differences for *WikiText-103* and *PG-19* across context lengths.

with BGE showing slight advantages under certain configurations. Notably, in the 20-shot, 18 in-memory setup with Eager attention and zero context length, BGE achieves a higher average accuracy (77.80%) compared to LLM (71.70%). The largest gap occurs in the *Subj* task, where BGE reaches 82.85% versus LLM's 50.35%, suggesting that BGE better captures fine-grained semantic representations. Nevertheless, both embedders remain broadly consistent, highlighting ERMAR's adaptability to different embedding backbones.

Ablation on Relevance and Re-ranking. We further evaluate the effect of the Relevance+Re-ranking mechanism on model perplexity across varying context lengths for *WikiText-103* and *PG-19*. Results are shown in Table 9.

The relevance scoring mechanism provides the greatest improvements at shorter context lengths—10.4% at 1K and 7.2% at 2K tokens on *WikiText-103*. The gains taper off beyond 4K tokens and become marginally negative at 32K, suggesting that the computational overhead of ranking may outweigh its benefits when sufficient memory capacity is available. In contrast, *PG-19* exhibits consistent improvements (1.0–9.9%) across all context lengths, indicating that narrative text benefits more from semantic ranking, where long-range dependencies and non-sequential references are frequent.

4 Conclusion

This paper introduced **ERMAR**, a Ranked Memory-Augmented Retrieval framework that enhances long-context language modeling through dynamic relevance scoring and adaptive memory management. By prioritizing semantically relevant information during retrieval, ERMAR improves contextual reasoning and scalability over extended sequences. Experimental results demonstrate that ERMAR achieves up to a **3.2% reduction in perplexity** compared to MemLong and maintains stable performance at **32K-token** contexts. In few-shot in-context learning tasks, ERMAR outperforms baselines by **6.1%** on average in 4-shot and **7.1%** in 20-shot settings, including substantial gains on MPQA (+21%) and Subj (+26%), confirming its effectiveness in retrieval precision and generalization.

ERMAR also exhibits strong computational efficiency, reducing reserved memory by up to **30%** at long contexts and sustaining a throughput of approximately **2.4K tokens/sec** with minimal latency variance. These results establish ERMAR as an efficient and scalable retrieval-augmented framework for long-context modeling. Future work will focus on optimizing ERMAR for specialized datasets and expanding its applicability to complex reasoning tasks.

5 Limitations

While ERMAR improves retrieval efficiency and context retention, it has certain limitations. Its reliance on ranked memory structures increases computational overhead compared to standard LLMs, particularly for large-scale retrieval, as discussed

in Subsections 3.2.4 and 3.2.5, as well as Appendix A.5. Additionally, performance variations across different task domains indicate the need for further tuning. The framework's effectiveness in real-world, noisy environments also requires further validation.

References

Marah Abdin, Jyoti Aneja, Hany Awadalla, Ahmed Awadallah, Ammar Ahmad Awan, Nguyen Bach, Amit Bahree, Arash Bakhtiari, Jianmin Bao, Harkirat Behl, et al. 2024. Phi-3 technical report: A highly capable language model locally on your phone. *arXiv preprint arXiv:2404.14219*.

Zhangir Azerbayev, Edward Ayers, and Bartosz Piotrowski. 2023. Proofpile: A pre-training dataset of mathematical texts.

Iz Beltagy, Matthew E Peters, and Arman Cohan. 2020. Longformer: The long-document transformer. *arXiv preprint arXiv:2004.05150*.

Zhe Cao, Tao Qin, Tie-Yan Liu, Ming-Feng Tsai, and Hang Li. 2007. Learning to rank: from pairwise approach to listwise approach. In *Proceedings of the 24th international conference on Machine learning*, pages 129–136.

Yukang Chen, Shengju Qian, Haotian Tang, Xin Lai, Zhijian Liu, Song Han, and Jiaya Jia. 2023. Longlora: Efficient fine-tuning of long-context large language models. *arXiv preprint arXiv:2309.12307*.

Yao Fu, Rameswar Panda, Xinyao Niu, Xiang Yue, Hannaneh Hajishirzi, Yoon Kim, and Hao Peng. 2024. Data engineering for scaling language models to 128k context. *arXiv preprint arXiv:2402.10171*.

Alex Graves, Greg Wayne, and Ivo Danihelka. 2014. Neural turing machines. *arXiv preprint arXiv:1410.5401*.

Alex Graves, Greg Wayne, Malcolm Reynolds, Tim Harley, Ivo Danihelka, Agnieszka Grabska-Barwińska, Sergio Gómez Colmenarejo, Edward Grefenstette, Tiago Ramalho, John Agapiou, et al. 2016. Hybrid computing using a neural network with dynamic external memory. *Nature*, 538(7626):471–476.

Kelvin Guu, Kenton Lee, Zora Tung, Panupong Pasupat, and Mingwei Chang. 2020. Retrieval augmented language model pre-training. In *International conference on machine learning*, pages 3929–3938. PMLR.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*.

Gautier Izacard and Edouard Grave. 2020. Leveraging passage retrieval with generative models for open domain question answering. *arXiv preprint arXiv:2007.01282*.

Vladimir Karpukhin, Barlas Oğuz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. Dense passage retrieval for open-domain question answering. *arXiv preprint arXiv:2004.04906*.

Omar Khattab and Matei Zaharia. 2020. Colbert: Efficient and effective passage search via contextualized late interaction over bert. In *Proceedings of the 43rd International ACM SIGIR conference on research and development in Information Retrieval*, pages 39–48.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in neural information processing systems*, 33:9459–9474.

Weijie Liu, Zecheng Tang, Juntao Li, Kehai Chen, and Min Zhang. 2024. Memlong: Memory-augmented retrieval for long text modeling. *arXiv preprint arXiv:2408.16967*.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. 2016. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*.

Rodrigo Nogueira and Kyunghyun Cho. 2019. Passage re-ranking with bert. *arXiv preprint arXiv:1901.04085*.

Bowen Peng, Jeffrey Quesnelle, Honglu Fan, and Enrico Shippole. 2023. Yarn: Efficient context window extension of large language models. *arXiv preprint arXiv:2309.00071*.

Ofir Press, Noah A. Smith, and Mike Lewis. 2022. Train short, test long: Attention with linear biases enables input length extrapolation. *Preprint*, arXiv:2108.12409.

Jack W Rae, Anna Potapenko, Siddhant M Jayakumar, and Timothy P Lillicrap. 2019. Compressive transformers for long-range sequence modelling. *arXiv preprint arXiv:1911.05507*.

Jianlin Su, Murtadha Ahmed, Yu Lu, Shengfeng Pan, Wen Bo, and Yunfeng Liu. 2024. Roformer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. 2023a. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023b. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288.*

Szymon Tworkowski, Konrad Staniszewski, Mikołaj Pacek, Yuhuai Wu, Henryk Michalewski, and Piotr Miłoś. 2024. Focused transformer: Contrastive training for context scaling. *Advances in Neural Information Processing Systems*, 36.

A Vaswani. 2017. Attention is all you need. *Advances in Neural Information Processing Systems.*

Yuhuai Wu, Markus N Rabe, DeLesley Hutchins, and Christian Szegedy. 2022. Memorizing transformers. *arXiv preprint arXiv:2203.08913.*

Shitao Xiao, Zheng Liu, Yingxia Shao, and Zhao Cao. 2022. Retromae: Pre-training retrieval-oriented language models via masked auto-encoder. *arXiv preprint arXiv:2205.12035.*

Howard Yen, Tianyu Gao, and Danqi Chen. 2024. Long-context language modeling with parallel context encoding. *arXiv preprint arXiv:2402.16617.*

Manzil Zaheer, Guru Guruganesh, Kumar Avinava Dubey, Joshua Ainslie, Chris Alberti, Santiago Ontanon, Philip Pham, Anirudh Ravula, Qifan Wang, Li Yang, et al. 2020. Big bird: Transformers for longer sequences. *Advances in neural information processing systems*, 33:17283–17297.

A Appendix

This appendix supplements the main text with detailed implementation and evaluation specifics for the Enhanced Ranked Memory Augmented Retrieval (ERMAR) framework. It includes comprehensive descriptions of dataset preprocessing, training configurations, hyperparameters, and key terminology, along with extended analyses of context-length performance and memory efficiency. The provided details ensure reproducibility and offer deeper insights into ERMAR's architectural and operational nuances.

A.1 Dataset Preprocessing

The *SlimPajama* dataset, used for fine-tuning ERMAR, underwent several preprocessing steps to ensure compatibility with long-context tasks. The dataset was tokenized using the OpenLLaMA tokenizer, with a maximum sequence length of 32768 tokens. Duplicate sequences were removed using a hash-based deduplication algorithm, reducing the dataset to 84.7K unique training rows. To handle variable context lengths, we applied a sliding window approach with a stride of 512 tokens, ensuring that the model could process contexts ranging from 1024 to 32768 tokens. Special tokens were added to denote document boundaries, and padding was applied to align sequences to the nearest multiple of 128 tokens for efficient batch processing.

A.2 Training Configuration

ERMAR was trained using a two-stage fine-tuning approach with the following configuration:

Model Parameters:

- Base model: OpenLLaMA-3B-v2 with LoRA adaptations

- Memory layer: Layer 13 for historical context storage

- Retrieval attention layers: [14, 18, 22, 26]

- Memory capacity: 32,768 key-value pairs

- Memory group size: 128 tokens per memory group

- Retrieval group size: 8 (TopK retrieval)

- Gate mechanism: Disabled (use_gate=False)

Training Hyperparameters:

- Learning rate: 5×10^{-5} with 1,000 warmup steps

- Weight decay: 1×10^{-4}

- Batch size: 1 per device (with gradient accumulation)

- Sequence length: 1,024 tokens

- Last context length: 1,024 tokens

- Training epochs: 1 epoch on SlimPajama 0.5B subset

- Training mode: LoRA-freeze (partial parameter updates)

LoRA Configuration:

- Target modules: q_proj, k_proj, v_proj, o_proj

- Trainable parameters: Layer normalization and embeddings

- Frozen layers: Layers 0-13 (up to memory layer)

- Position encoding: Zero position type for extended contexts

Embedder Setup:

- Embedder: BAAI/bge-m3 (BGE embedder)

- Embedding dimension: 1,024

- GPU-based similarity search for efficient retrieval

Hardware and Infrastructure:

- Primary training: Single NVIDIA 3090 24GB GPU

- Extended context (32k): NVIDIA L40S 44.4GB GPU

- Distributed training: ZeRO-2 optimization with Accelerate

- Memory optimization: Sequential batching and continual fine-tuning

A.3 Glossary of Terms

To aid understanding, we provide definitions for key terms used in the ERMAR framework:

- **Relevance Score** (α): A normalized score computed via softmax over the dot product of query and key embeddings, representing the contextual importance of a memory entry (see Equation 2).

- **Key-Value Pair**: A tuple (K_j, V_j) storing contextual information, where K_j is the key embedding and V_j is the corresponding value embedding in the memory bank.

- **RSAR (Relevance Scoring with Adaptive Retrieval)**: The mechanism that dynamically ranks key-value pairs based on their relevance to the query, incorporating historical usage patterns.

- **Memory Bank**: A non-trainable storage of pre-computed key-value embeddings, used to retain historical context without recomputation.

- **TopK Retrieval**: The process of selecting the top-K most relevant memory entries based on their relevance scores for use in the current context.

A.4 Fine-Grained Context Length Analysis

Figure 4: ERMAR perplexity performance across fine-grained context lengths for PG-19 and WikiText-103 datasets. The analysis reveals dataset-specific scaling patterns and validates performance stability across extended contexts.

Figure 4 presents detailed perplexity measurements across incremental context lengths from 1000 to 16000 tokens, providing fine-grained insights into ERMAR's scaling behavior. The fine-grained analysis reveals that WikiText-103 achieves optimal performance around 13K-16K tokens (perplexity 7.36), while PG-19 maintains consistent performance (9.74-9.97) across all context lengths. This validates ERMAR's robustness and suggests that factual content benefits more from extended context than narrative text.

A.5 Relevance+Reranker Visual Analysis

Figure 5: Visualization of Table 9, showing the relative impact of the Relevance+Reranker mechanism across context lengths. Color coding highlights: blue bars represent baseline performance, while orange bars show improvements with our full mechanism(ERMAR).

Figure 5 provides complementary visual evidence for the patterns discussed in Section 3.2.6. The stronger improvements at shorter contexts are visually apparent through the larger differentials between the orange and blue bars, while differences in mechanism effectiveness across datasets are immediately noticeable in the side-by-side comparisons. Additionally, the 32K edge case on

WikiText, where the mechanism underperforms, is clearly highlighted in the visualization, underscoring context-length sensitivities of the Relevance+Reranker mechanism.

A.6 Impact of Top-*K* on Performance

We conducted experiments to examine how varying the Top-*K* retrieval parameter affects system performance across different sequence lengths on the *WikiText-103* dataset. The Top-*K* values (1, 4, 8, 16, 32) were tested for sequence lengths of 1K–16K tokens, measuring latency, throughput, memory usage, and perplexity.

Results. Table 10 summarizes latency and memory results across all configurations. Increasing Top-*K* consistently reduces latency per token and improves throughput, particularly between $K = 1$ and $K = 4$, with diminishing gains beyond $K = 8$. Memory consumption (both peak and reserved) remains constant for a given sequence length, confirming that Top-*K* selection does not affect model footprint.

Seq Len	TopK	Latency/ Token (ms)	Latency (s)	Throughput (tokens/sec)	Peak Memory (GB)	Reserved Memory (GB)
1024	1	285.38 ± 54.98	0.279	3684.15	7.98	8.19
	4	277.15 ± 60.41	0.271	3810.19	7.98	8.21
	8	270.90 ± 57.72	0.265	3893.17	7.98	8.21
	16	268.60 ± 57.54	0.262	3928.15	7.98	8.21
	32	269.26 ± 56.84	0.263	3915.67	7.98	8.21
2048	1	630.68 ± 49.07	0.308	3264.37	8.46	8.83
	4	556.76 ± 51.17	0.272	3704.12	8.46	8.81
	8	555.35 ± 51.52	0.271	3714.39	8.46	8.81
	16	549.25 ± 50.81	0.268	3755.02	8.46	8.81
	32	549.17 ± 50.93	0.268	3756.11	8.46	8.81
4096	1	1873.54 ± 54.43	0.457	2187.96	9.43	9.89
	4	1804.90 ± 56.60	0.441	2271.53	9.43	9.91
	8	1759.28 ± 53.03	0.430	2330.24	9.43	9.89
	16	1738.93 ± 44.91	0.425	2356.96	9.43	9.90
	32	1719.64 ± 50.91	0.420	2383.85	9.43	9.90
8192	1	4264.45 ± 63.90	0.521	1921.41	11.36	12.16
	4	4116.54 ± 71.41	0.503	1990.60	11.36	12.18
	8	4094.69 ± 79.01	0.500	2001.35	11.36	12.16
	16	4107.60 ± 94.04	0.501	1995.37	11.36	12.16
	32	4098.25 ± 96.92	0.500	2000.00	11.36	12.16
16348	1	9136.22 ± 176.62	0.558	1793.95	15.21	16.69
	4	8965.27 ± 115.76	0.547	1827.79	15.21	16.71
	8	8961.31 ± 55.20	0.547	1828.37	15.21	16.69
	16	8945.37 ± 42.26	0.546	1831.60	15.21	16.70
	32	8843.33 ± 48.01	0.540	1852.75	15.21	16.70

Table 10: Performance metrics across Top-*K* values and sequence lengths on *WikiText-103*.

Constant Metrics. Table 11 reports memory-per-token and perplexity, which remain stable across Top-*K* variations. This indicates that increasing retrieval scope affects efficiency but not model quality.

Findings. Increasing Top-*K* from 1→4 yields the largest latency reduction (e.g., 285.4→277.1 ms at

Sequence Length	Memory/Token (MB)	Val Perplexity	Perplexity
1024	7.98	2.13	8.42
2048	4.23	2.03	7.61
4096	2.36	2.03	7.62
8192	1.42	2.05	7.76
16348	0.95	2.05	7.80

Table 11: Constant metrics across Top-*K* values for each sequence length.

1K; 9136.2→8965.3 ms at 16K), while further increases provide minimal additional gains. Throughput improvements are proportional, especially for longer sequences (e.g., 2188→2384 tokens/s at 4K). Memory and perplexity remain unaffected. Thus, $K = 4$–8 offers the best trade-off between efficiency and computational cost.

Embedder	In-C, In-M	Dim	MPQA	SST2	SST5	SUBJ	MR
BGE	4,4	512	88.28	93.00	45.96	94.90	97.15
		1024	87.93	91.51	46.32	94.65	97.09
		2048	87.99	91.51	46.14	94.35	97.08
	4,18	512	88.02	92.89	46.14	94.90	97.11
		1024	88.11	91.40	46.32	94.65	97.09
		2048	88.17	91.40	46.14	94.35	97.08
	20,18	512	91.23	94.50	52.59	95.55	97.83
		1024	91.26	93.35	49.41	96.60	97.44
		2048	91.29	93.23	49.68	96.75	97.40
LLM	4,4	512	88.65	93.00	46.32	89.05	97.62
		1024	88.76	92.20	46.32	88.15	96.65
		2048	88.76	92.20	46.32	88.15	96.65
	4,18	512	88.59	93.00	46.32	89.25	97.62
		1024	88.72	92.20	46.32	88.15	96.65
		2048	88.72	92.20	46.32	88.15	96.65
	20,18	512	90.35	92.78	50.32	95.15	98.08
		1024	91.01	93.35	48.14	94.85	98.04
		2048	91.01	93.35	48.14	94.85	98.04

Table 12: Accuracy results for embedding dimensionality experiments across datasets and settings.

A.7 Sensitivity to Embedding Dimensionality in ICL Retrieval

We analyzed how embedding dimensionality influences in-context retrieval performance using both BGE and LLM embedders. Experiments were conducted on *MPQA*, *SST-2*, *SST-5*, *SUBJ*, and *MR* datasets with in-context/in-memory settings of (4, 4), (4, 18), and (20, 18). Embedding dimensions of 512, 1024, and 2048 were evaluated.

Results. Table 12 reports results for both embedders. Overall, reducing the dimension to 512 (via PCA) maintains or slightly improves accuracy across most datasets compared to higher dimensions, suggesting redundancy in high-dimensional embeddings.

Findings. Reducing dimensionality to 512 preserves retrieval accuracy while slightly improving performance on *SST-5* (+3.2 pp) and *MPQA* (+0.3 pp). This indicates that lower dimensions suppress noise and redundancy. Dimensional padding to 2048 introduces negligible changes (<0.5 pp). Across both embedders, *SUBJ* shows minor degradation at high dimensionality, whereas *MR* remains stable. Overall, 512-dimensional embeddings offer the best trade-off between accuracy and efficiency.