Not All CAMs Are Complete: Completeness as the Key to Faithfulness

Abstract

Although input-gradients techniques have evolved to mitigate and tackle the challenges associated with gradients, modern gradient-weighted CAM approaches still rely on vanilla gradients, which are inherently susceptible to the saturation phenomena. Despite recent enhancements have incorporated counterfactual gradient strategies as a mitigating measure, these local explanation techniques still exhibit a lack of sensitivity to their baseline parameter. Our work proposes a gradient-weighted CAM augmentation that tackles both the saturation and sensitivity problem by reshaping the gradient computation, incorporating two well-established and provably approaches: Expected Gradients and kernel smoothing. By revisiting the original formulation as the smoothed expectation of the perturbed integrated gradients, one can concurrently construct more faithful, localized and robust explanations which minimize infidelity. Through fine modulation of the perturbation distribution it is possible to regulate the complexity characteristic of the explanation, selectively discriminating stable features. Our technique, *Expected Grad-CAM*, differently from recent works, exclusively optimizes the gradient computation, purposefully designed as an enhanced substitute of the foundational Grad-CAM algorithm and any method built therefrom. Quantitative and qualitative evaluations have been conducted to assess the effectiveness of our method.

1 Introduction

Deep neural networks have achieved remarkable performance across a rapidly growing spectrum of application domains. Yet their efficacy is often coupled with *black-box* behavior, lacking transparency and explainability (Samek et al., 2017; Adadi & Berrada, 2018). This opacity has driven the development of *Explainable AI* (xAI) methodologies aimed at understanding the mechanisms driving model decisions (Gilpin et al., 2018). The need for trustworthiness and reliability (Lipton, 2016) has spurred numerous techniques, ranging from gradient-based (Simonyan et al., 2013), perturbation-based (Ribeiro et al., 2016), and contrastive approaches (Abhishek & Kamath, 2022), to assess *a posteriori* (post-hoc) the behavior of opaque models (Samek et al., 2021). Within the branch of *visual explanations*, *saliency* methods aim to discriminate and identify relevant regions in the input space that highly excite the network and strongly influence the network predictions.

As successful state-of-the-art vision tasks' architectures commonly incorporate spatial convolution mechanism, *Class Activation Maps* (CAM) (Zhou et al., 2015) have emerged as a popular and widely adopted technique for generating *saliencies* that leverage the spatial information captured by convolutional layer. CAM(s) are computed by inspecting the feature maps and produce per-instance, class-specific attention heat maps that highlight important areas in the original image that drove the classifier. Building on this notion, Gradient-weighted CAM (Grad-CAM) (Selvaraju et al., 2016) and its variants, extend the original formulation by computing the linear weights from the averaged backpropagated gradients with respect to the target class of each feature map. This generalization enables the use and application of the method without any modification or auxiliary training to the model. Historically, naïve vanilla gradients have been cardinal in the development and evolution of *saliency maps* (Simonyan et al., 2013); however input-gradients techniques (*e.g.*, output gradients *w.r.t.*, inputs) quickly evolved to address the gradient saturation problem (Shrikumar et al., 2017; Rakitianskaia & Engelbrecht, 2015; Sundararajan et al., 2017), where the gradients of important features result in small magnitudes due to the model's function flattening in the vicinity of the input,

misrepresenting feature importance (Sundararajan et al., 2016). Within the context of gradient visualizations, several *counterfactual*-based works have been proposed to address saturation via feature scaling (Sundararajan et al., 2017), contribution decomposition (Shrikumar et al., 2017), and relevance propagation (Bach et al., 2015). The insensitivity of *baseline-methods* to their reference parameter (Sundararajan & Taly, 2018; Adebayo et al., 2018) has spurred research dedicated to baseline determination (Ancona et al., 2017; Kindermans et al., 2017; Yeh et al., 2019). Since CAM and Grad-CAM, several gradient-based techniques have been proposed to improve localization (Shi et al., 2020; Jiang et al., 2021), multi-instance detection (Chattopadhay et al., 2017), saliency resolution (Qiu et al., 2023; Draelos & Carin, 2020), noise and attribution sparsity (Omeiza et al., 2019), and axiomatic attributions (Fu et al., 2020). Despite this progress, modern gradient-weighted CAM approaches still rely on vanilla gradients, inherently prone to saturation. A recent work, Integrated Grad-CAM (Sattarzadeh et al., 2021), combines Integrated Gradients and Grad-CAM to address this issue. While path integration yields the desirable *completeness* property (attributions summing to the prediction difference), this method retains baseline insensitivity, underestimating contributions that align with its baseline.

We introduce a *general distributional framework* for gradient-based CAM methods that unifies Integrated Grad-CAM, SmoothGrad-CAM, and our proposed Expected Grad-CAM as special cases determined by the choice of perturbation distribution. Building on this framework, we derive *optimal CAM weights* that provably minimize explanation infidelity, but show this optimality requires the underlying attribution method to satisfy a *completeness axiom*. Notably, we prove that SmoothGrad violates this property, explaining its suboptimal faithfulness despite its noise-reduction benefits. Our method, *Expected Grad-CAM*, instantiates this optimal framework by incorporating the well-established *Expected Gradients* (Erion et al., 2019) into the CAM framework (figure 3). Expected Gradients satisfies the completeness axiom required by our optimal weights theorem, while simultaneously resolving the baseline insensitivity problem by sampling baselines from a reference distribution. This overcomes the feature attribution underestimation of vanilla gradients (figure 2) without introducing undesired side effects. Since CAMs are coarse attention maps used for *human-centered* interpretability (Alvarez-Melis & Jaakkola, 2018a), it is crucial that such methods highlight only stable, salient features, a property that our optimal framework guarantees.

Empirically, we demonstrate that Expected Grad-CAM *concurrently* improves four explanation quality *key desiderata* (Hedström et al., 2022; 2023): (i) faithfulness, (ii) robustness, (iii) localization, and (iv) complexity. Our experiments reveal that Expected Grad-CAM significantly outperforms state-of-the-art gradient- and non-gradient-based CAM methods across 19 quality metrics, with consistent results across different open image datasets. Qualitatively, our technique constructs *saliencies* that are sharper and more focused on class-discriminative image regions, as illustrated in Figure 1. Unlike popular gradient-based CAM methods whose saliency maps are often noisy and sparse (Kim et al., 2019), Expected Grad-CAM highlights only features that are systematically utilized across the sample's neighborhood in input space (*i.e.*, *relative input stability* (Agarwal et al., 2022)).

We summarize our contributions as follows: **First**, we introduce a general distributional framework for gradient-based CAM methods, showing that Integrated Grad-CAM and SmoothGrad-CAM emerge naturally as special cases depending on the choice of perturbation distribution $p_{\mathcal{D}}$. **Second**, we derive optimal CAM weights that minimize explanation infidelity under arbitrary perturbations. We prove formally that this optimality requires the underlying attribution method to satisfy the *completeness axiom*, a property satisfied by Integrated Gradients and Expected Gradients, but violated by SmoothGrad. **Third**, we propose *Expected Grad-CAM*, which instantiates our optimal framework using Expected Gradients with data-aware perturbations. Extensive experiments across 19 quality metrics (Hedström et al., 2022; 2023) demonstrate that Expected Grad-CAM significantly outperforms state-of-the-art gradient- and non-gradient-based CAM methods in faithfulness, robustness, localization, and complexity.

2 Related work

In the following section, we present the scope of this work, introduce the notation, and critically examines prior attribution methods alongside their known shortcomings and limitations.

Figure 1: Explanatory functions on VGG-16 across samples from ImageNet-1k (Russakovsky et al., 2014). Our approach produces sharper (less noisy) and higher localized heat maps with lower complexity than existing methods (1a). Figure 1b shows the coarse heat map with respect to our method and baseline Grad-CAM (Selvaraju et al., 2016).

2.1 Preliminaries

Let $f_\theta : \mathcal{X} \to \mathcal{Y}$ be a differentiable neural network mapping inputs $\boldsymbol{x} \in \mathbb{R}^D$ to outputs $\boldsymbol{y} \in \mathbb{R}^C$ for a classification task with C classes, where $\boldsymbol{x} \in \mathcal{X}$ and $\boldsymbol{y} \in \mathcal{Y}$. The parameter vector $\theta \in \Theta \subset \mathbb{R}^W$ is learned through a training process, yielding the trained model f_θ. We refer to this trained model simply as f, with predictions $\boldsymbol{y} = f(\boldsymbol{x}; \theta)$. Here, θ includes the weights and biases of the neural network, and resides in parameter space Θ under a fixed architecture in function space $f_\theta \in \mathcal{F}$.

Local Explanations. To interpret how *specific features* of $\boldsymbol{x}$ influence a particular prediction $f_\theta^c(\boldsymbol{x})$ for a class $c \in \{1, \dots, C\}$, a *local explanation* method produces an attribution map or *saliency* $\hat{\boldsymbol{e}}$ that highlights the most influential components of $\boldsymbol{x}$. Formally, let

$$\phi_L \colon \mathcal{F} \times \mathcal{X} \times \{1, \dots, C\} \longrightarrow \mathbb{R}^V \tag{1}$$

be an operator that takes the trained model f, an input $\boldsymbol{x}$, and a class index c, then produces an *explanation* $\hat{\boldsymbol{e}}$, which we denote as

$$\hat{\boldsymbol{e}} = \phi_L\big(f, \boldsymbol{x}, c; \lambda\big) \quad \in \mathbb{R}^V, \tag{2}$$

where λ specifies any additional, explanation-specific hyperparameters. The dimensionality V of $\hat{\boldsymbol{e}}$ may be the same as the input space D or different (e.g., in convolutional architectures, attributions might first be computed in a lower-dimensional feature map and then subsequently upsampled).

In effect, local explanations capture which aspects of $\boldsymbol{x}$ most strongly drive the model toward the logit $f^c(\boldsymbol{x})$. We now survey notable classes of local explanation methods.

Gradient-based explanations This set of techniques encompasses the involvement of the neural network's gradients as a function approximator, translating complex nonlinear models into local linear explanations. These explanations are often encoded as attention heat maps, also known as saliencies. The cornerstone method within this category is *Input-Gradients* (vanilla gradients) (Simonyan et al., 2013), which we define by

$$\phi^{\mathrm{grad}}(f, \boldsymbol{x}, c) \; = \; \nabla_{\boldsymbol{x}} f^c(\boldsymbol{x}), \tag{3}$$

where ϕ^{grad} denotes the class-specific, backpropagated gradient of the class c *w.r.t.*, the input $\boldsymbol{x}$. Notably, while not relevant to our approach, the feature visualization produced by deconvolution (Zeiler & Fergus, 2013) and guided backpropagation (Springenberg et al., 2014) are also tightly linked; the latter, in particular, constrains the gradient flow to non-negative values.

While straightforward, pure gradients often yield high-frequency noise and poorly calibrated attributions in regions of high saturation (Sundararajan et al., 2017). Methods addressing these issues via non-local comparisons or smoothing are discussed below.

Counterfactual explanations As gradients only express local changes, their utilization misrepresents feature importances across saturating ranges (Sundararajan et al., 2017). This class of methods tackles this issue by multiple non-local comparisons against a perturbed baseline by feature re-scaling (Sundararajan et al., 2017), blurring (Fong & Vedaldi, 2017), activation differences (Shrikumar et al., 2017), noise (Smilkov et al., 2017) or in-painting (Alipour et al., 2022). Here, we primarily focus on two kinds of methods that are highly related to our work: Integrated Gradients (Sundararajan et al., 2017) and SmoothGrad (Smilkov et al., 2017).

Integrated Gradients To mitigate saturation artifacts, this method involves the summation of the *interior* gradients along the counterfactual path that interpolates from a baseline input $\boldsymbol{x}'$ to the original input $\boldsymbol{x}$ (Sundararajan et al., 2017; 2016). Concretely, for a class-specific logit f_c, It is defined as:

$$\phi^{\mathrm{IG}}(f, \boldsymbol{x}, c; \boldsymbol{x}') \; = \; (\boldsymbol{x} - \boldsymbol{x}') \int_{\alpha=0}^{1} \nabla_{\boldsymbol{x}} f^c\big(\boldsymbol{x}' + \alpha(\boldsymbol{x} - \boldsymbol{x}')\big) \, d\alpha, \tag{4}$$

where $\boldsymbol{x}$ is the input sample, $\boldsymbol{x}'$ is a given baseline (representing an "absence" or neutral version of $\boldsymbol{x}$), and α is a scaling parameter that interpolates between the baseline and the input according to a given interpolation function γ (Sundararajan et al., 2017). By integrating over this path, the method captures salient gradients even in regions where the model output would otherwise saturate, thereby providing more robust attributions.

SmoothGrad: This method addresses saliency noise caused by sharp fluctuations of gradients at small scales, due to rapid local variation in partial derivatives (Smilkov et al., 2017), by denoising using a smoothing Gaussian kernel. It is defined as:

$$\phi^{\mathrm{SG}}(f, \boldsymbol{x}, c; n, \sigma) \; = \; \frac{1}{n} \sum_{i=1}^{n} \nabla_{\boldsymbol{x}} f^c\Big(\boldsymbol{x} + \mathcal{N}\big(\overline{0}, \sigma^2 \mathbf{I}\big)\Big), \tag{5}$$

where $\mathcal{N}(\overline{0}, \sigma^2 \mathbf{I})$ denotes Gaussian noise of variance σ^2, and n is the number of noisy samples averaged.

Class activation maps This set of attention methods generates explanations by exploiting the spatial information captured by the convolutional layers. Class activation maps are generated by computing the rectified sum of all the feature map's activations times its weights. Formally, consider a network's target convolutional layer ℓ with K feature maps, where each feature map $A^k \in \mathbb{R}^{U \times V}$ has spatial dimensions $U \times V$. For the original CAM (Zhou et al., 2015), the class activation map for class c at spatial location (u, v) is given by

$$M_{u,v}^c \; = \; \sum_{k=1}^{K} w_k^c \, A_{u,v}^k \,, \tag{6}$$

where $w_k^c \in \mathbb{R}$ are the learned weights of the fully connected layer that combines the global average pooled feature channels to produce the class scores. Grad-CAM (Selvaraju et al., 2016) generalizes this approach

by replacing the learned weights w_k^c with gradient-based importance weights α_k^c, avoiding architectural constraints. For Grad-CAM, the importance weight α_k^c for feature map k and class c is defined as:

$$\alpha_k^c \;=\; \frac{1}{Z} \sum_{u=1}^{U} \sum_{v=1}^{V} \frac{\partial\, y^c}{\partial\, A_{u,v}^k}, \tag{7}$$

where y^c is the score (logit) for class c before softmax, and $Z = U \cdot V$ is a normalization constant implementing global average pooling. The final Grad-CAM heatmap is then computed as:

$$L_{\text{Grad-CAM}}^c = \text{ReLU}\left(\sum_{k=1}^{K} \alpha_k^c \cdot A^k \right), \tag{8}$$

where the ReLU ensures only positive influences are captured. This preserves the model's original structure while leveraging the class-specific gradient signal to weight each spatial feature map.

Notably, despite the perturbation of the subregions is performed with distinct different techniques, *DeepLift* (Shrikumar et al., 2017), *input × gradient*, and *SmoothGrad* (Smilkov et al., 2017) they all work under a similar setup of *Integrated Gradients* (Sundararajan et al., 2017) as shown in previous work (Ancona et al., 2017). For instance, *SmoothGrad* can be formulated as the *path integral* where the interpolator function samples a single point from a Gaussian distribution:

$$\phi^{\text{SG}}(f, \boldsymbol{x}, c; n, \sigma) \;=\; \frac{1}{n} \sum_{j=1}^{n} \Big(\boldsymbol{x} \,+\, \boldsymbol{\epsilon}_\sigma^{(j)} \Big) \nabla_{\boldsymbol{x}} f^c \Big(\boldsymbol{x} \,+\, \boldsymbol{\epsilon}_\sigma^{(j)} \Big), \quad \text{where } \boldsymbol{\epsilon}_\sigma^{(j)} \sim \mathcal{N}\big(\overline{0},\, \sigma^2\, \mathbf{I} \big). \tag{9}$$

3 Method

In this section, we present our method for deriving optimal Grad-CAM weights that minimize explanation infidelity while addressing the fundamental limitations of gradient saturation and baseline sensitivity. We begin by establishing the mathematical framework, then introduce our optimization-based approach, and finally discuss practical considerations for robust implementation.

Problem Formulation. Building on the notation introduced in Section 2.1, let $y^c : (\mathbb{R}^{U \times V})^K \mapsto \mathbb{R}$ be the function that maps a set of K feature maps $(A^1, \ldots, A^K)$ from a specific convolutional layer ℓ to the class score $y^c(A^1, \ldots, A^K)$. To analyze the contribution of individual feature maps, we introduce a predictor function $g : \mathbb{R}^K \mapsto \mathbb{R}$ parameterized by the original feature maps $\mathbf{A} = (A^1, \ldots, A^K)$:

$$g(\mathbf{z}'; \mathbf{A}) = y^c(z_1' A^1, z_2' A^2, \ldots, z_K' A^K) \tag{10}$$

where $\mathbf{z}' = (z_1', \ldots, z_K') \in \mathbb{R}^K$ is a vector of scalar multipliers. This formulation allows us to study how scaling individual feature maps affects the model's output.

We seek to explain the behavior of g around the reference point $\mathbf{z}_0 = \mathbf{1} = (1, 1, \ldots, 1) \in \mathbb{R}^K$, which corresponds to using the original, unscaled feature maps. The explanation is characterized by a vector of importance weights $\boldsymbol{\alpha}^c = (\alpha_1^c, \ldots, \alpha_K^c) \in \mathbb{R}^K$, where α_k^c quantifies the importance of the k-th feature map A^k for class c.

3.1 Beyond Local Gradients

The original Grad-CAM formulation (Equation 7) relies on vanilla gradients to derive channel importance weights. However, this approach suffers from a fundamental limitation: gradients capture only *local* changes and thus fail to represent feature importance accurately in regions where $\nabla_{\boldsymbol{x}} f_\theta^c(\boldsymbol{x})$ saturates (Sundararajan et al., 2016).

Previous attempts to address gradient saturation in CAMs through perturbation techniques (Sattarzadeh et al., 2021; Omeiza et al., 2019) have introduced undesirable side effects, including *baseline insensitivity* (Sundararajan & Taly, 2018) and poor robustness to infinitesimal perturbations (Alvarez-Melis & Jaakkola, 2018a; Sundararajan et al., 2017; Ghorbani et al., 2017).

Figure 2: Comparison of attribution maps under internal saturation conditions. Figure 2a illustrates the cosine similarity of the target layer's embeddings with respect to the interpolator parameter (α) (see Appendix B.1 for more details). Figure 2b displays the attribution maps of various methods under saturation conditions. Internal saturation causes the baseline method to under-represent feature importances across saturating ranges. By extracting the top-4 most important features (Figure 2b), it is evident that the baseline method fails to capture relevant discriminative regions, resulting in low insertion AUCs (Figure 2b) as these regions are not deemed important by the model.

A Distributional Perspective on Missingness. Methods predicated on *perturbing* input features have arisen as a principled means to assess the *missingness* of those features in a model's decision-making process (Ancona et al., 2017; Yeh et al., 2019). Under this lens, removing, or zeroing out, certain features of an input effectively emulates a baseline or neutral state, enabling one to gauge how replacing each feature with its baseline counterpart impacts the model output. The salient question, then, is how does one systematically account for, potentially many, such replacements and the ensuing attributions. Remarkably, this viewpoint both recovers classical path-based formulations (such as Integrated Grad-CAM) as special cases and also elucidates how more flexible distributions, for instance, those used in *Expected Gradients*, can mitigate the baseline insensitivity problem that purely path-based methods often exhibit.

Perturbation by Replacement. To move beyond local gradient analysis, we adopt a perturbation-based approach. Let $S \subset \{1, \ldots, D\}$ be a subset of feature indices in the input vector $\boldsymbol{x} \in \mathbb{R}^D$. Following Ancona et al. (2017) and Yeh et al. (2019), we construct an *interpolated* input by selectively replacing features:

$$(\boldsymbol{x}[S \leftarrow \boldsymbol{x}'])_j = x_j \mathbb{I}(j \notin S) + x'_j \mathbb{I}(j \in S), \quad \text{for all } j \in \{1, \ldots, D\} \tag{11}$$

where $\boldsymbol{x}' \in \mathbb{R}^D$ is a reference baseline (e.g., a black image or mean image), and $\mathbb{I}(\cdot)$ is the indicator function.

General Framework for Attribution Weights. Building on the perturbation principle, we can express Grad-CAM weights through a general integrated gradients framework. The importance weight for the k-th

feature map is given by:

$$\alpha^c = \int \phi^{\mathrm{IG}}(g, \boldsymbol{z}_0, c; \boldsymbol{I}, \boldsymbol{A}) \, d\mu_{\boldsymbol{I}} \tag{12}$$

where ϕ^{IG} represents any path attribution method that iteratively identify salient regions by integrating gradients along a specified path (see Appendix A.1.2 for the general framework and derivations of special cases):

$$\phi^{\mathrm{IG}}(g, \boldsymbol{z}_0, c; \boldsymbol{I}, \boldsymbol{A}) = \int_{t=0}^{1} \nabla_{\boldsymbol{z}} g^c(\boldsymbol{z}_0 + \boldsymbol{I}(t-1); \boldsymbol{A}) \, dt \tag{13}$$

This formulation provides a unified view of gradient-based attribution methods. Remarkably, classical path-based formulations emerge naturally as special cases by varying the perturbation distribution $\mu_{\boldsymbol{I}}$.

Connection to Existing Methods. Our framework unifies several existing attribution methods as special cases:

- **Integrated Grad-CAM** (Sattarzadeh et al., 2021): Obtained when $\mu_{\boldsymbol{I}}$ is a point mass Dirac delta function at a fixed perturbation. This corresponds to a single baseline and path integration.

- **SmoothGrad-CAM** (Omeiza et al., 2019): Approximated when $\mu_{\boldsymbol{I}}$ follows a Gaussian distribution, but gradients are evaluated only at endpoints rather than integrating along paths. This provides noise-based smoothing without full path integration.

3.2 Optimal Attribution via Infidelity Minimization

We now formalize the problem of finding optimal Grad-CAM weights through the lens of explanation infidelity minimization. This framework provides a principled approach to address gradient saturation while maintaining theoretical guarantees.

Infidelity Metric. Following Yeh et al. (2019), we measure the quality of an explanation through its *infidelity*: the expected squared error between the attribution's prediction and the actual model behavior under perturbations:

Definition 3.1 (Explanation Infidelity for Grad-CAM)**.** Consider the Grad-CAM setting where $\boldsymbol{\alpha}^c = (\alpha_1^c, \ldots, \alpha_K^c) \in \mathbb{R}^K$ represents importance weights for K feature maps, and perturbations $\boldsymbol{I} \in \mathbb{R}^K$ are applied to the feature map multipliers. Given the predictor function $g(\boldsymbol{z}; \boldsymbol{A})$ defined in equation 10 and perturbations $\boldsymbol{I}$ with probability measure $\mu_{\boldsymbol{I}}$, the infidelity of the Grad-CAM weights is:

$$\mathrm{INFD}(\boldsymbol{\alpha}^c, g, \boldsymbol{z}_0; \boldsymbol{A}) = \mathbb{E}_{\boldsymbol{I} \sim \mu_{\boldsymbol{I}}} \left[\left(\boldsymbol{I}^T \boldsymbol{\alpha}^c - (g(\boldsymbol{z}_0; \boldsymbol{A}) - g(\boldsymbol{z}_0 - \boldsymbol{I}; \boldsymbol{A})) \right)^2 \right] \tag{14}$$

where $\boldsymbol{I}^T \boldsymbol{\alpha}^c = \sum_{k=1}^{K} I_k \alpha_k^c$ represents the predicted change in output based on the linear combination of feature map importance weights and perturbations.

This metric quantifies how well the linear approximation $\boldsymbol{I}^T \boldsymbol{\alpha}^c$ predicts the actual change in model output when feature maps are scaled by the perturbed multipliers $\boldsymbol{z}_0 - \boldsymbol{I}$.

Theorem 3.2 (Optimal Grad-CAM Weights)**.** *Let ϕ be any attribution method that takes a predictor function $g : \mathbb{R}^K \to \mathbb{R}$, a reference point $\boldsymbol{z}_0 \in \mathbb{R}^K$, and a perturbation $\boldsymbol{I} \in \mathbb{R}^K$, and returns an attribution vector in $\mathbb{R}^K$ satisfying the completeness axiom:*

$$\boldsymbol{I}^T \cdot \phi(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}) = g(\boldsymbol{z}_0; \boldsymbol{A}) - g(\boldsymbol{z}_0 - \boldsymbol{I}; \boldsymbol{A})$$

Suppose the perturbations $\boldsymbol{I} \in \mathbb{R}^K$ drawn from $\mu_{\boldsymbol{I}}$ are such that the second moment matrix $\mathcal{M}_{\boldsymbol{I}} = \int \boldsymbol{I} \boldsymbol{I}^T d\mu_{\boldsymbol{I}}$ is invertible.[1] The optimal Grad-CAM weights that minimize the infidelity equation 14 are:

$$\boldsymbol{\alpha}^{c*} = \mathcal{M}_{\boldsymbol{I}}^{-1} \left(\int \boldsymbol{I} \langle \boldsymbol{I}, \phi(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}) \rangle d\mu_{\boldsymbol{I}} \right) \tag{15}$$

---

[1]Invertibility holds when $\mathrm{supp}(\mu_{\boldsymbol{I}})$ spans $\mathbb{R}^K$; for data-aware perturbations (Definition 3.8) this is ensured by diverse sampling. See Appendix A.1.5 for rank-deficient cases and numerical stability.

where $\langle \cdot, \cdot \rangle$ *denotes the inner product.*

Proof Sketch. The infidelity is a quadratic functional in $\boldsymbol{\alpha}^c$. By the completeness axiom, we have $g(\boldsymbol{z}_0; \boldsymbol{A}) - g(\boldsymbol{z}_0 - \boldsymbol{I}; \boldsymbol{A}) = \boldsymbol{I}^T \phi(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A})$. Substituting this into the infidelity expression and taking the derivative with respect to $\boldsymbol{\alpha}^c$ yields the first-order optimality condition, from which equation 15 follows. The full proof is provided in Appendix A.1.4. $\qquad\square$

Remark 3.3 (Path Attribution in Practice)*.* In practice, we instantiate ϕ as a path attribution method (as defined in Equation equation 13) but incorporate a distributional perspective similar to expected gradients to address baseline (in)sensitivity. Rather than using a single fixed baseline as in standard integrated gradients:

$$\phi^{\text{IG}}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}) = \int_{t=0}^{1} \nabla_{\boldsymbol{z}} g(\boldsymbol{z}_0 + (t-1)\boldsymbol{I}; \boldsymbol{A}) dt$$

we sample multiple perturbations $\boldsymbol{I}$ from a distribution $\mu_{\boldsymbol{I}}$ and compute the optimal weights via Equation equation 15. This differs from the original infidelity minimization approach, which uses only integrated gradients. The subsequent sections will formalize this approach through expected gradients ϕ^{EG}.

3.3 Computing Attribution: From Integrated to Expected Gradients

Having established that optimal weights require an attribution method satisfying completeness (Theorem 3.2), we now examine specific instantiations of ϕ. We first present standard integrated gradients, then show how it generalizes to expected gradients through baseline distributions.

Definition 3.4 (Integrated Gradients Attribution)**.** For a predictor function $g : \mathbb{R}^K \to \mathbb{R}$ parameterized by feature maps $\boldsymbol{A}$, the integrated gradients attribution method ϕ^{IG} is defined as:

$$\phi^{\text{IG}}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}) = \int_{t=0}^{1} \nabla_{\boldsymbol{z}} g(\boldsymbol{z}_0 + (t-1)\boldsymbol{I}; \boldsymbol{A}) dt \tag{16}$$

where $\boldsymbol{z}_0 \in \mathbb{R}^K$ is the reference point and $\boldsymbol{I} \in \mathbb{R}^K$ is the perturbation vector. This integrates gradients along the straight-line path from baseline $\boldsymbol{z}_0 - \boldsymbol{I}$ to $\boldsymbol{z}_0$.

Definition 3.5 (Expected Gradients Attribution)**.** For a centered baseline distribution $\mathcal{D}$ over multiplier vectors in $\mathbb{R}^K$ satisfying $\mathbb{E}_{\boldsymbol{z}' \sim \mathcal{D}}[\boldsymbol{z}'] = \boldsymbol{0}$,[2] the expected gradients attribution method ϕ^{EG} is defined as:

$$\phi^{\text{EG}}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}, \mathcal{D}) = \int_{\boldsymbol{z}' \sim \mathcal{D}} \left[\int_{t=0}^{1} \nabla_{\boldsymbol{z}} g(\boldsymbol{z}' + t(\boldsymbol{z}_0 - \boldsymbol{I} - \boldsymbol{z}'); \boldsymbol{A}) dt \right] p_{\mathcal{D}}(\boldsymbol{z}') d\boldsymbol{z}' \tag{17}$$

where $g : \mathbb{R}^K \to \mathbb{R}$ is the predictor function parameterized by $\boldsymbol{A}$, $\boldsymbol{z}_0 \in \mathbb{R}^K$ is the reference point, and $\boldsymbol{I} \in \mathbb{R}^K$ is the perturbation vector.

Remark 3.6 (Relationship Between Attribution Methods)*.* These attribution methods are related as follows:

- ϕ^{IG} **as special case**: When $\mathcal{D} = \delta_{\boldsymbol{z}_0 - \boldsymbol{I}}$ (Dirac delta), we have $\phi^{\text{EG}}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}, \delta_{\boldsymbol{z}_0 - \boldsymbol{I}}) = \phi^{\text{IG}}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A})$

- **Robustness**: ϕ^{EG} averages over multiple baselines, reducing sensitivity to baseline choice

- **Completeness**: Both satisfy the completeness axiom required by Theorem 3.2

Remark 3.7 (Completeness Verification)*.* Both attribution methods satisfy the completeness axiom as required by Theorem 3.2:

- ϕ^{IG}: We have $\boldsymbol{I}^T \cdot \phi^{\text{IG}}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}) = g(\boldsymbol{z}_0; \boldsymbol{A}) - g(\boldsymbol{z}_0 - \boldsymbol{I}; \boldsymbol{A})$

- ϕ^{EG}: When $\mathbb{E}_{\boldsymbol{z}' \sim \mathcal{D}}[\boldsymbol{z}'] = \boldsymbol{0}$,[3] we have $\boldsymbol{I}^T \cdot \phi^{\text{EG}}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}, \mathcal{D}) = g(\boldsymbol{z}_0; \boldsymbol{A}) - g(\boldsymbol{z}_0 - \boldsymbol{I}; \boldsymbol{A})$

Applying Theorem 3.2 to specific attribution methods yields closed-form optimal weights for both ϕ^{IG} and ϕ^{EG} (see Appendix A.1.9).

---

[2] In practice, $\mathcal{D} = \mathcal{N}(\boldsymbol{0}, \sigma^2 \boldsymbol{I}_K)$. Note that $\mathcal{D}$ (baseline sampling *within* ϕ^{EG}) is distinct from $\mu_{\boldsymbol{I}}$ (perturbations for infidelity minimization in equation 14).

[3] Centering ensures cross-terms cancel in the path integral; see Appendix A.1.3.

3.4 Robust Perturbations via Data Distribution

Beyond fidelity, a quality explanation method must satisfy multiple desirable properties (Hedström et al., 2022). The choice of perturbation distribution μ_I is crucial for:

1. **Preserving sensitivity**: Ensuring the explanation responds appropriately to meaningful input changes (Sundararajan et al., 2017)

2. **Maintaining stability**: Guaranteeing consistent behavior across input, output, and intermediate representations (Agarwal et al., 2022)

3. **Ensuring robustness**: Preventing adversarial manipulation through infinitesimal perturbations (Slack et al., 2019)

Constant baselines fail to account for data distribution characteristics, leading to high sensitivity to noise (Yeh et al., 2019). We address this by constructing perturbations that reflect the underlying data distribution:

Definition 3.8 (Data-Aware Perturbations). Let $\mathcal{X}$ be the data distribution. We define robust perturbations through Monte Carlo sampling:

$$I = z_0 - \mathbb{E}_{x' \sim \mathcal{X}, \alpha \sim U(0,1)}[\alpha \cdot h(x')] \tag{18}$$

where $h : \mathcal{X} \to \mathbb{R}^K$ is the feature extraction function that maps data samples to feature map multipliers. Specifically, for an input $x' \in \mathcal{X}$, we define

$$h(x') = \left(\mathrm{GAP}(A^1(x')), \dots, \mathrm{GAP}(A^K(x')) \right) \tag{19}$$

where $A^k(x')$ denotes the k-th feature map at layer ℓ when x' is passed through the network, and $\mathrm{GAP}(\cdot)$ denotes global average pooling over spatial dimensions.

This approach combines the smoothing benefits of Gaussian noise (Smilkov et al., 2017; Omeiza et al., 2019) with improved robustness by ensuring perturbations remain within the data manifold, reducing out-of-distribution (OOD) artifacts.

3.5 Expected Grad-CAM: Smooth, Noise-Resistant Explanations

We now formalize Expected Grad-CAM, which unifies the theoretical components developed above: expected gradients attribution, data-aware perturbations, and infidelity-minimizing optimal weights, into a principled explanation method.

Definition 3.9 (Expected Grad-CAM). Let $f_\theta : \mathbb{R}^{H \times W \times C} \to \mathbb{R}^K$ be a CNN classifier, ℓ a convolutional layer with feature maps $A = (A^1, \dots, A^K)$, and c the target class. Expected Grad-CAM computes importance weights $\boldsymbol{\alpha}_{\mathrm{EG}}^{c*} \in \mathbb{R}^K$ as:

$$\boldsymbol{\alpha}_{\mathrm{EG}}^{c*} = \arg\min_{\boldsymbol{\alpha}^c \in \mathbb{R}^K} \mathbb{E}_{I \sim \mu_I^{\mathcal{X}}} \left[\left(I^T \boldsymbol{\alpha}^c - (g(z_0; A) - g(z_0 - I; A)) \right)^2 \right] \tag{20}$$

where $g(z'; A) = y^c(z_1' A^1, \dots, z_K' A^K)$ is the predictor function, $\mu_I^{\mathcal{X}}$ is the data-aware perturbation distribution induced by $\mathcal{X}$, and the expectation is taken over perturbations $I = z_0 - \mathbb{E}_{x' \sim \mathcal{X}, \alpha \sim U(0,1)}[\alpha \cdot h(x')]$.

Theorem 3.10 (Closed-Form Solution for Expected Grad-CAM). *Under the conditions of Theorem 3.2, and using expected gradients attribution ϕ^{EG} with baseline distribution $\mathcal{D}$ satisfying $\mathbb{E}_{z' \sim \mathcal{D}}[z'] = 0$, the Expected Grad-CAM weights have the closed-form solution:*

$$\boldsymbol{\alpha}_{EG}^{c*} = \mathcal{M}_I^{-1} \left(\mathbb{E}_{I \sim \mu_I^{\mathcal{X}}} \left[I \langle I, \phi^{EG}(g, z_0, I; A, \mathcal{D}) \rangle \right] \right) \tag{21}$$

where $\mathcal{M}_I = \mathbb{E}_{I \sim \mu_I^{\mathcal{X}}}[II^T]$ is the second moment matrix of the data-aware perturbations.

Proof Sketch. Direct application of Theorem 3.2 with $\phi = \phi^{\mathrm{EG}}$ and $\mu_I = \mu_I^{\mathcal{X}}$. The completeness of ϕ^{EG} (Theorem A.8) ensures the solution minimizes infidelity. $\square$

Figure 3: Overview of the proposed Expected Grad-CAM method. Given an input image, a target class, and a reference distribution to sample from, the class-discriminative explanation $\hat{e}$ is computed through input kernel smoothing and difference-from-reference comparisons.

Definition 3.11 (Expected Grad-CAM Heatmap)**.** The Expected Grad-CAM heatmap for class c is the spatial activation map:

$$L_{\text{EG-CAM}}^c = \text{ReLU}\left(\sum_{k=1}^{K} \alpha_{\text{EG},k}^{c*} \cdot A^k\right) \in \mathbb{R}^{U \times V} \tag{22}$$

where $\alpha_{\text{EG},k}^{c*}$ is the k-th component of $\boldsymbol{\alpha}_{\text{EG}}^{c*}$ and $A^k \in \mathbb{R}^{U \times V}$ is the k-th feature map.

Remark 3.12 (Connection to SmoothGrad)*.* The optimal weights formula equation 21 reveals a connection to generalized SmoothGrad (Yeh et al., 2019). The kernel $\boldsymbol{I}\boldsymbol{I}^T$ in the second moment matrix $\mathcal{M}_{\boldsymbol{I}}$ acts as a data-adaptive smoothing kernel. Unlike standard SmoothGrad which uses isotropic Gaussian noise, our approach adapts the smoothing to the data distribution through $\mu_{\boldsymbol{I}}^{\mathcal{X}}$, providing more principled regularization.

Proposition 3.13 (Properties of Expected Grad-CAM)**.** *Expected Grad-CAM satisfies the following properties:*

1. ***Optimality**: $\boldsymbol{\alpha}_{EG}^{c*}$ minimizes the infidelity functional over all weight vectors*

2. ***First-Order Condition**: The optimal weights satisfy*

$$\mathcal{M}_{\boldsymbol{I}}\boldsymbol{\alpha}_{EG}^{c*} = \mathbb{E}_{\boldsymbol{I} \sim \mu_{\boldsymbol{I}}^{\mathcal{X}}}\left[\boldsymbol{I}(g(\boldsymbol{z}_0; \boldsymbol{A}) - g(\boldsymbol{z}_0 - \boldsymbol{I}; \boldsymbol{A}))\right]$$

3. ***Data Coherence**: The perturbation distribution $\mu_{\boldsymbol{I}}^{\mathcal{X}}$ ensures explanations remain within the data manifold*

4. ***Baseline Robustness**: The method is robust to baseline selection through the expectation over $\mathcal{D}$ in ϕ^{EG}*

Computational Aspects. While the theoretical formulation provides exact optimal weights, practical implementation requires Monte Carlo approximation of the expectations in equation 21. The computational

complexity is $O(MKN)$ where M is the number of perturbation samples, K is the number of feature maps, and N is the number of baseline samples for expected gradients. Despite this additional computation, Expected Grad-CAM achieves competitive running times in practice, remaining faster than Score-CAM and Ablation-CAM while providing superior explanation quality (Table 8). We defer implementation details to the supplementary material.

4 Experiments

Figure 4: Comparison of attribution maps under normal (4b) and internal saturation (4a) conditions. *Expected Grad-CAM* produces sharper, more localized, and more stable explanations than its direct counterparts: *G-CAM* (Selvaraju et al., 2016), *G-CAM++* (Chattopadhay et al., 2017), *S.G-CAM++* (Omeiza et al., 2019), and *Int. G-CAM* (Sattarzadeh et al., 2021), while remaining competitive with non-gradient-based and more complex gradient-augmented methods. See Section C for full comparisons.

In line with previous works (Jiang et al., 2021; Wang et al., 2019; Jiang et al., 2021), we evaluate our proposed method quantitatively and qualitatively.

Datasets. We consider the *ILSVRC2012* (Russakovsky et al., 2014), *CIFAR10* (Ho-Phuoc, 2018) and *COCO* (Lin et al., 2014) with images of size 224×224. The first two datasets have been used for the quantitative metrics, while the latter only for the localization evaluations, where the segmentation masks of each sample have been employed.

Models. Each metric is evaluated across popular feed-forward CNN architectures. In line with prior literature, we restricted our analysis to *VGG16* (Simonyan & Zisserman, 2014), *ResNet50* (He et al., 2015) and *AlexNet* (Krizhevsky et al., 2012). In all cases, the default pre-trained *PyTorch* torchvision implementation has been adopted.

Metrics. In contrast to prior works, we comprehensively evaluate our technique across an extensive set of traditional and modern metrics. We provide a full characterization of the behavior of our method by evaluating not just faithfulness, but rather all the different explanatory qualities across recent explanation quality groupings (Hedström et al., 2022) *i.e.*, (i) Faithfulness, (ii) Robustness, (iii) Complexity, and (iv) Localization. In Table 2 are presented all the evaluated metrics categorized by quality groupings, while the extended quantitative results are available in Section B.

Table 1: *Faithfulness*, *Robustness* and *Complexity Metrics*. Values evaluated on ILSVRC2012(Russakovsky et al., 2014) on VGG16 (Simonyan & Zisserman, 2014). Extended results are available in Section B.

	Faithfulness			Robustness			Complexity	
Method	↑ IROF	↑ Suff.	↓ Inf.	↓ L. Est.	↓ M. Sens.	↓ A. Sens.	↓ CP.	↑ SP.
Grad-CAM	55.36	1.91	8.12	0.38	0.27	0.20	10.56	0.38
Grad-CAM++	56.93	1.87	7.98	0.32	**0.192**	0.15	10.53	0.40
Sm. Grad-CAM++	56.38	1.89	7.50	0.51	0.51	0.27	10.60	0.35
Int. Grad-CAM	57.36	1.83	8.92	1.05	1.00	1.00	10.59	0.36
HiRes-CAM	57.49	1.74	5.73	0.99	1.00	1.00	10.54	0.40
XGrad-CAM	57.32	1.98	7.88	0.37	0.23	0.18	10.56	0.38
LayerCAM	58.15	1.74	7.22	0.31	0.19	**0.14**	10.56	0.38
Score-CAM	55.37	1.91	7.39	0.68	0.65	0.53	10.56	0.38
Ablation-CAM	57.36	1.83	7.28	1.05	1.00	1.00	10.59	0.36
Expected Grad-CAM	**62.39**	**2.10**	**4.99**	**0.24**	0.194	0.15	**10.43**	**0.47**

Baselines. We compare our proposed technique against recent and relevant methods including Grad-CAM (Selvaraju et al., 2016), Grad-CAM++ (Chattopadhay et al., 2017), Smooth Grad-CAM++ (Omeiza et al., 2019), Integrated Grad-CAM (Sattarzadeh et al., 2021), HiRes-CAM (Draelos & Carin, 2020), XGrad-CAM (Fu et al., 2020), LayerCAM (Jiang et al., 2021), Score-CAM (Wang et al., 2019), and Ablation-CAM (Desai & Ramaswamy, 2020).

Qualitative evaluations In Figure 4 we present an excerpt of the explanations generated during the computation of the quantitative evaluations on the *ILSVRC2012* validation set. By inspecting the attribution sparsity and localization characteristics of each explanation, our method (*Expected Grad-CAM*), generally produces saliencies that are more localized and focused on the attuned human-centric understanding of the composition of the attributes of the labels. An explanation designed for human fruition *i.e.*, aimed at building the model's trustworthiness should be encoded as such to not *disrupt trust*; this implies that an *human-interpretable* explanation should be restricted to the most important pertinent and stable features: it should contains the least number of stable features which do maximally fulfill the notion of fidelity (Figure 5, 12). In Figure 4a it is observed qualitatively that every other compared attribution method breaks such condition: given the labels *lakeside* and *backpack* the explanations highlights areas which are not pertinent with label-related attributes *i.e.*, the sky and portions of the tree (Subfig:4a) and parts of the background (Subfig:4b) respectively.

Quantitative evaluations Following, we assess the validity of our claims quantitatively across various desirable explanatory qualities. The extended quantitative results are available in Section B.

Faithfulness. Examining traditional *faithfulness* metrics (Insertion and Deletion AUCs) across popular benchmarking networks on a large chunk of *ILSVRC2012*, showed promising results (Table 3). Our method *Expected Grad-CAM*, achieved best or second-best scores across its gradient and non-gradient-based counterparts as well as more advanced variations of CAM, which do not solely rely on a gradient augmentation, in both the *insertion* and *deletion* aspects. Towards a more comprehensive comparison, we then verified our technique against more recent metrics. Unsurprisingly, *IROF* (Table 1) showed agreement with traditional metrics as they fundamentally assess similar explanatory qualities. Our technique scored higher than others on the *Sufficiency* (Dasgupta et al., 2022) metric, due to greater *stability* and *robustness* (Table 1). Finally, we tested *Expected Grad-CAM*'s performances in terms of *infidelity* (Yeh et al., 2019), which expectedly showed the lowest (best) results.

Stability. In Table 6 are presented the results *w.r.t.*, to the relative- input and out stability metrics. our method showed the lowest score overall (*highest stability*), while achieving best or second-best robustness scores (Table 1).

(a)

(b)

Figure 5: Comparison of saliencies generated by different gradient- and non-gradient-based methods. 5a shows the superimposed (top row) and raw coarse saliencies (bottom row) generated by each method. Our method consistently produces more focused and sharper saliencies compared to both gradient-based and non-gradient-based methods (e.g., Score-CAM). 5b demonstrates that our approach concurrently improves key xAI properties: (i) faithfulness, (ii) robustness, and (iii) complexity, significantly outperforming even non-gradient-based methods.

5 Conclusion and broader impact

In this paper, we advanced current CAM's gradient faithfulness by proposing *Expected Grad-CAM* which simultaneously addresses the saturation and sensitivity phenomena, without introducing undesirable side effects. Revisiting the original formulation as the smoothed expectation of the perturbed integrated gradients, one can concurrently construct more faithful, localized, and robust explanations that minimize infidelity. Despite qualitative assessment being highly subjective, quantitative evaluations are also teeming with indeterminate, ambiguous results that span further than the rank-order issues. While faithfulness is a universally desirable underlying explanatory quality, individual metrics, which do assess such property, only define a distinct notion of such a multifaceted trait, potentially delineating unwanted aspects. While careful modulation of the smoothing functional allows for fine-grained control of the complexity characteristic of the explanation, where, through sensitivity reduction, produces more human-interpretable saliencies; it contrastingly influences the current notions of faithfulness. Perhaps, further adaption of existing metrics may be necessary to embody human-interpretability; nevertheless, existing qualitative and quantitative assessments proved the superiority of our approach.

Broader impact. This paper highlights the value and effectiveness of Expected Grad-CAM in comparison to current state-of-the-art approaches across a comprehensive set of modern evaluation metrics. We demonstrated that our technique satisfies many desirable xAI properties by producing explanations that are highly concentrated on the least number of stable robust, features. Our experiments revealed that many state-of-the-art approaches underperform on modern metrics. Ultimately, as our technique is intended to replace the original formulation of Grad-CAM, we hope new and existing approaches will build on it.

References

Kumar Abhishek and Deeksha Kamath. Attribution-based XAI Methods in Computer Vision: A Review. 11 2022. doi: 10.48550/arxiv.2211.14736. URL https://arxiv.org/abs/2211.14736v1.

Amina Adadi and Mohammed Berrada. Peeking Inside the Black-Box: A Survey on Explainable Artificial Intelligence (XAI). *IEEE Access*, 6:52138–52160, 9 2018. ISSN 21693536. doi: 10.1109/ACCESS.2018. 2870052.

Julius Adebayo, Justin Gilmer, Ian Goodfellow, and Been Kim. Local Explanation Methods for Deep Neural Networks Lack Sensitivity to Parameter Values. *6th International Conference on Learning Representations, ICLR 2018 - Workshop Track Proceedings*, 10 2018. URL https://arxiv.org/abs/1810.03307v1.

Chirag Agarwal, Nari Johnson, Martin Pawelczyk, Satyapriya Krishna, Eshika Saxena, Marinka Zitnik, and Himabindu Lakkaraju. Rethinking Stability for Attribution-based Explanations. 3 2022. URL https://arxiv.org/abs/2203.06877v1.

Kamran Alipour, Aditya Lahiri, Ehsan Adeli, Babak Salimi, and Michael Pazzani. Explaining Image Classifiers Using Contrastive Counterfactuals in Generative Latent Spaces. 6 2022. URL https://arxiv.org/abs/2206.05257v1.

David Alvarez-Melis and Tommi S. Jaakkola. On the Robustness of Interpretability Methods. 6 2018a. URL https://arxiv.org/abs/1806.08049v1.

David Alvarez-Melis and Tommi S. Jaakkola. Towards Robust Interpretability with Self-Explaining Neural Networks. *Advances in Neural Information Processing Systems*, 2018-December:7775–7784, 6 2018b. ISSN 10495258. URL https://arxiv.org/abs/1806.07538v2.

Marco Ancona, Enea Ceolini, Cengiz Öztireli, and Markus Gross. Towards better understanding of gradient-based attribution methods for Deep Neural Networks. *6th International Conference on Learning Representations, ICLR 2018 - Conference Track Proceedings*, 11 2017. URL https://arxiv.org/abs/1711.06104v4.

Leila Arras, Ahmed Osman, and Wojciech Samek. Ground Truth Evaluation of Neural Network Explanations with CLEVR-XAI. *Information Fusion*, 81:14–40, 3 2020. doi: 10.1016/j.inffus.2021.11.008. URL http://arxiv.org/abs/2003.07258http://dx.doi.org/10.1016/j.inffus.2021.11.008.

Sebastian Bach, Alexander Binder, Grégoire Montavon, Frederick Klauschen, Klaus Robert Müller, and Wojciech Samek. On Pixel-Wise Explanations for Non-Linear Classifier Decisions by Layer-Wise Relevance Propagation. *PLoS ONE*, 10(7), 7 2015. ISSN 19326203. doi: 10.1371/JOURNAL.PONE.0130140. URL /pmc/articles/PMC4498753//pmc/articles/PMC4498753/?report=abstracthttps://www.ncbi.nlm.nih.gov/pmc/articles/PMC4498753/.

Umang Bhatt, Adrian Weller, and José M.F. Moura. Evaluating and Aggregating Feature-based Model Explanations. *IJCAI International Joint Conference on Artificial Intelligence*, 2021-January:3016–3022, 5 2020. ISSN 10450823. doi: 10.24963/ijcai.2020/417. URL https://arxiv.org/abs/2005.00631v1.

Prasad Chalasani, Jiefeng Chen, Amrita Roy Chowdhury, Somesh Jha, and Xi Wu. Concise Explanations of Neural Networks using Adversarial Training. *37th International Conference on Machine Learning, ICML 2020*, PartF168147-2:1360–1368, 10 2018. URL https://arxiv.org/abs/1810.06583v9.

Aditya Chattopadhay, Anirban Sarkar, Prantik Howlader, and Vineeth N. Balasubramanian. Grad-CAM++: Improved Visual Explanations for Deep Convolutional Networks. *Proceedings - 2018 IEEE Winter Conference on Applications of Computer Vision, WACV 2018*, 2018-January:839–847, 10 2017. doi: 10.1109/wacv.2018.00097. URL https://arxiv.org/abs/1710.11063v3.

Sanjoy Dasgupta, Nave Frost, and Michal Moshkovitz. Framework for Evaluating Faithfulness of Local Explanations. *Proceedings of Machine Learning Research*, 162:4794–4815, 2 2022. ISSN 26403498. URL https://arxiv.org/abs/2202.00734v1.

Saurabh Desai and Harish G. Ramaswamy. Ablation-CAM: Visual explanations for deep convolutional network via gradient-free localization. *Proceedings - 2020 IEEE Winter Conference on Applications of Computer Vision, WACV 2020*, pp. 972–980, 3 2020. doi: 10.1109/WACV45572.2020.9093360.

Rachel Lea Draelos and Lawrence Carin. Use HiResCAM instead of Grad-CAM for faithful explanations of convolutional neural networks. 11 2020. URL `https://arxiv.org/abs/2011.08891v4`.

Alexandre Englebert, Olivier Cornu, and Christophe De Vleeschouwer. Poly-CAM: High resolution class activation map for convolutional neural networks. 4 2022. URL `https://arxiv.org/abs/2204.13359v2`.

Gabriel Erion, Joseph D. Janizek, Pascal Sturmfels, Scott M. Lundberg, and Su In Lee. Improving performance of deep learning models with axiomatic attribution priors and expected gradients. *Nature Machine Intelligence*, 3(7):620–631, 6 2019. ISSN 25225839. doi: 10.48550/arxiv.1906.10670. URL `https://arxiv.org/abs/1906.10670v2`.

Ruth Fong and Andrea Vedaldi. Interpretable Explanations of Black Boxes by Meaningful Perturbation. *Proceedings of the IEEE International Conference on Computer Vision*, 2017-October:3449–3457, 4 2017. doi: 10.1109/ICCV.2017.371. URL `http://arxiv.org/abs/1704.03296http://dx.doi.org/10.1109/ICCV.2017.371`.

Ruigang Fu, Qingyong Hu, Xiaohu Dong, Yulan Guo, Yinghui Gao, and Biao Li. Axiom-based Grad-CAM: Towards Accurate Visualization and Explanation of CNNs. 8 2020. URL `https://arxiv.org/abs/2008.02312v4`.

Amirata Ghorbani, Abubakar Abid, and James Zou. Interpretation of Neural Networks is Fragile. *33rd AAAI Conference on Artificial Intelligence, AAAI 2019, 31st Innovative Applications of Artificial Intelligence Conference, IAAI 2019 and the 9th AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019*, pp. 3681–3688, 10 2017. ISSN 2159-5399. doi: 10.1609/aaai.v33i01.33013681. URL `https://arxiv.org/abs/1710.10547v2`.

Leilani H. Gilpin, David Bau, Ben Z. Yuan, Ayesha Bajwa, Michael Specter, and Lalana Kagal. Explaining Explanations: An Overview of Interpretability of Machine Learning. *2018 IEEE 5th International Conference on Data Science and Advanced Analytics (DSAA)*, pp. 80–89, 1 2018. doi: 10.1109/DSAA.2018.00018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep Residual Learning for Image Recognition. *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, 2016-December:770–778, 12 2015. ISSN 10636919. doi: 10.1109/CVPR.2016.90. URL `https://arxiv.org/abs/1512.03385v1`.

Anna Hedström, tu-berlinde Leander Weber, Dilyara Bareeva, Daniel Krakowczyk, Franz Motzkus, Wojciech Samek, Sebastian Lapuschkin, and Marina M-C Höhne. Quantus: An Explainable AI Toolkit for Responsible Evaluation of Neural Network Explanations and Beyond. *Journal of Machine Learning Research*, 24:1–11, 2 2022. URL `https://arxiv.org/abs/2202.06861v3`.

Anna Hedström, Philine Bommer, Kristoffer K. Wickstrøm, Wojciech Samek, Sebastian Lapuschkin, and Marina M. C. Höhne. The Meta-Evaluation Problem in Explainable AI: Identifying Reliable Estimators with MetaQuantus. 2 2023. URL `https://arxiv.org/abs/2302.07265v2`.

Tien Ho-Phuoc. CIFAR10 to Compare Visual Recognition Performance between Deep Neural Networks and Humans. 11 2018. URL `https://arxiv.org/abs/1811.07270v2`.

Peng Tao Jiang, Chang Bin Zhang, Qibin Hou, Ming Ming Cheng, and Yunchao Wei. LayerCAM: Exploring hierarchical class activation maps for localization. *IEEE Transactions on Image Processing*, 30:5875–5888, 2021. ISSN 19410042. doi: 10.1109/TIP.2021.3089943.

Beomsu Kim, Junghoon Seo, Seunghyeon Jeon, Jamyoung Koo, Jeongyeol Choe, and Taegyun Jeon. Why are Saliency Maps Noisy? Cause of and Solution to Noisy Saliency Maps. *Proceedings - 2019 International Conference on Computer Vision Workshop, ICCVW 2019*, pp. 4149–4157, 2 2019. doi: 10.1109/ICCVW.2019.00510. URL `https://arxiv.org/abs/1902.04893v3`.

Pieter Jan Kindermans, Sara Hooker, Julius Adebayo, Maximilian Alber, Kristof T. Schütt, Sven Dähne, Dumitru Erhan, and Been Kim. The (Un)reliability of saliency methods. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, 11700 LNCS:267–280, 11 2017. ISSN 16113349. doi: 10.48550/arxiv.1711.00867. URL https://arxiv.org/abs/1711.00867v1.

Maximilian Kohlbrenner, Alexander Bauer, Shinichi Nakajima, Alexander Binder, Wojciech Samek, and Sebastian Lapuschkin. Towards Best Practice in Explaining Neural Network Decisions with LRP. *Proceedings of the International Joint Conference on Neural Networks*, 10 2019. doi: 10.1109/IJCNN48605.2020.9206975. URL https://arxiv.org/abs/1910.09840v3.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E. Hinton. ImageNet Classification with Deep Convolutional Neural Networks. *Advances in Neural Information Processing Systems*, 25, 2012. URL http://code.google.com/p/cuda-convnet/.

Tsung Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C. Lawrence Zitnick. Microsoft COCO: Common Objects in Context. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, 8693 LNCS(PART 5):740–755, 5 2014. ISSN 16113349. doi: 10.1007/978-3-319-10602-1{_}48. URL https://arxiv.org/abs/1405.0312v3.

Zachary C. Lipton. The Mythos of Model Interpretability. *Communications of the ACM*, 61(10):35–43, 6 2016. ISSN 15577317. doi: 10.1145/3233231. URL https://arxiv.org/abs/1606.03490v3.

Daniel Omeiza, Skyler Speakman, Celia Cintas, and Komminist Weldermariam. Smooth Grad-CAM++: An Enhanced Inference Level Visualization Technique for Deep Convolutional Neural Network Models. *CoRR*, abs/1908.01224, 8 2019. doi: 10.48550/arxiv.1908.01224. URL https://arxiv.org/abs/1908.01224v1.

Vitali Petsiuk, Abir Das, and Kate Saenko. RISE: Randomized Input Sampling for Explanation of Black-box Models. *British Machine Vision Conference 2018, BMVC 2018*, 6 2018. URL https://arxiv.org/abs/1806.07421v3.

Changqing Qiu, Fusheng Jin, and Yining Zhang. Fine-Grained and High-Faithfulness Explanations for Convolutional Neural Networks. 3 2023. URL https://arxiv.org/abs/2303.09171v1.

Anna Rakitianskaia and Andries Engelbrecht. Measuring saturation in neural networks. *Proceedings - 2015 IEEE Symposium Series on Computational Intelligence, SSCI 2015*, pp. 1423–1430, 2015. doi: 10.1109/SSCI.2015.202.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. "Why Should I Trust You?": Explaining the Predictions of Any Classifier. *NAACL-HLT 2016 - 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Proceedings of the Demonstrations Session*, pp. 97–101, 2 2016. doi: 10.18653/v1/n16-3020. URL https://arxiv.org/abs/1602.04938v3.

Laura Rieger and Lars Kai Hansen. IROF: a low resource evaluation metric for explanation methods. 3 2020. URL https://arxiv.org/abs/2003.08747v1.

Yao Rong, Tobias Leemann, Vadim Borisov, Gjergji Kasneci, and Enkelejda Kasneci. A Consistent and Efficient Evaluation Strategy for Attribution Methods. *Proceedings of Machine Learning Research*, 162: 18770–18795, 2 2022. ISSN 26403498. URL https://arxiv.org/abs/2202.00449v2.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C Berg, Li Fei-Fei, O Russakovsky, J Deng, H Su, J Krause, S Satheesh, S Ma, Z Huang, A Karpathy, A Khosla, M Bernstein, A C Berg, and L Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision*, 115(3):211–252, 9 2014. ISSN 15731405. doi: 10.1007/s11263-015-0816-y. URL https://arxiv.org/abs/1409.0575v3.

Wojciech Samek, Thomas Wiegand, and Klaus-Robert Müller. Explainable Artificial Intelligence: Understanding, Visualizing and Interpreting Deep Learning Models. *CoRR*, abs/1708.08296, 8 2017. doi: 10.48550/arxiv.1708.08296. URL `https://arxiv.org/abs/1708.08296v1`.

Wojciech Samek, Grégoire Montavon, Sebastian Lapuschkin, Christopher J. Anders, and Klaus Robert Müller. Explaining Deep Neural Networks and Beyond: A Review of Methods and Applications. *Proceedings of the IEEE*, 109(3):247–278, 3 2021. ISSN 15582256. doi: 10.1109/JPROC.2021.3060483.

Sam Sattarzadeh, Mahesh Sudhakar, Konstantinos N. Plataniotis, Jongseong Jang, Yeonjeong Jeong, and Hyunwoo Kim. Integrated Grad-CAM: Sensitivity-Aware Visual Explanation of Deep Convolutional Networks via Integrated Gradient-Based Scoring. *ICASSP, IEEE International Conference on Acoustics, Speech and Signal Processing - Proceedings*, 2021-June:1775–1779, 2 2021. ISSN 15206149. doi: 10.1109/ICASSP39728.2021.9415064. URL `https://arxiv.org/abs/2102.07805v1`.

Ramprasaath R. Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-CAM: Visual Explanations from Deep Networks via Gradient-based Localization. *International Journal of Computer Vision*, 128(2):336–359, 10 2016. doi: 10.1007/s11263-019-01228-7. URL `http://arxiv.org/abs/1610.02391http://dx.doi.org/10.1007/s11263-019-01228-7`.

Xiangwei Shi, Seyran Khademi, Yunqiang Li, and Jan van Gemert. Zoom-CAM: Generating Fine-grained Pixel Annotations from Image Labels. *Proceedings - International Conference on Pattern Recognition*, pp. 10289–10296, 10 2020. ISSN 10514651. doi: 10.1109/ICPR48806.2021.9412980. URL `https://arxiv.org/abs/2010.08644v1`.

Avanti Shrikumar, Peyton Greenside, and Anshul Kundaje. Learning Important Features Through Propagating Activation Differences. *34th International Conference on Machine Learning, ICML 2017*, 7:4844–4866, 4 2017. URL `https://arxiv.org/abs/1704.02685v2`.

Karen Simonyan and Andrew Zisserman. Very Deep Convolutional Networks for Large-Scale Image Recognition. *3rd International Conference on Learning Representations, ICLR 2015 - Conference Track Proceedings*, 9 2014. URL `https://arxiv.org/abs/1409.1556v6`.

Karen Simonyan, Andrea Vedaldi, and Andrew Zisserman. Deep Inside Convolutional Networks: Visualising Image Classification Models and Saliency Maps. *2nd International Conference on Learning Representations, ICLR 2014 - Workshop Track Proceedings*, 12 2013. doi: 10.48550/arxiv.1312.6034. URL `https://arxiv.org/abs/1312.6034v2`.

Dylan Slack, Sophie Hilgard, Emily Jia, Sameer Singh, and Himabindu Lakkaraju. Fooling LIME and SHAP: Adversarial Attacks on Post hoc Explanation Methods. *AIES 2020 - Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, pp. 180–186, 11 2019. doi: 10.1145/3375627.3375830. URL `https://arxiv.org/abs/1911.02508v2`.

Daniel Smilkov, Nikhil Thorat, Been Kim, Fernanda Viégas, and Martin Wattenberg. SmoothGrad: removing noise by adding noise. *CoRR*, abs/1706.03825, 6 2017. doi: 10.48550/arxiv.1706.03825. URL `https://arxiv.org/abs/1706.03825v1`.

Jost Tobias Springenberg, Alexey Dosovitskiy, Thomas Brox, and Martin Riedmiller. Striving for Simplicity: The All Convolutional Net. *3rd International Conference on Learning Representations, ICLR 2015 - Workshop Track Proceedings*, 12 2014. URL `https://arxiv.org/abs/1412.6806v3`.

Mukund Sundararajan and Ankur Taly. A Note about: Local Explanation Methods for Deep Neural Networks lack Sensitivity to Parameter Values. 6 2018. URL `https://arxiv.org/abs/1806.04205v1`.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Gradients of Counterfactuals. 11 2016. URL `https://arxiv.org/abs/1611.02639v2`.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic Attribution for Deep Networks. *34th International Conference on Machine Learning, ICML 2017*, 7:5109–5118, 3 2017. doi: 10.48550/arxiv.1703.01365. URL `https://arxiv.org/abs/1703.01365v2`.

Jonas Theiner, Eric Muller-Budack, and Ralph Ewerth. Interpretable Semantic Photo Geolocation. *Proceedings - 2022 IEEE/CVF Winter Conference on Applications of Computer Vision, WACV 2022*, pp. 1474–1484, 4 2021. doi: 10.1109/WACV51458.2022.00154. URL `https://arxiv.org/abs/2104.14995v2`.

Haofan Wang, Zifan Wang, Mengnan Du, Fan Yang, Zijian Zhang, Sirui Ding, Piotr Mardziel, and Xia Hu. Score-CAM: Score-Weighted Visual Explanations for Convolutional Neural Networks. *IEEE Computer Society Conference on Computer Vision and Pattern Recognition Workshops*, 2020-June:111–119, 10 2019. ISSN 21607516. doi: 10.1109/CVPRW50498.2020.00020. URL `https://arxiv.org/abs/1910.01279v2`.

Chih Kuan Yeh, Cheng Yu Hsieh, Arun Sai Suggala, David I. Inouye, and Pradeep Ravikumar. On the (In)fidelity and Sensitivity for Explanations. *Advances in Neural Information Processing Systems*, 32, 1 2019. ISSN 10495258. doi: 10.48550/arxiv.1901.09392. URL `https://arxiv.org/abs/1901.09392v4`.

Matthew D. Zeiler and Rob Fergus. Visualizing and Understanding Convolutional Networks. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, 8689 LNCS(PART 1):818–833, 11 2013. ISSN 16113349. doi: 10.48550/arxiv.1311.2901. URL `https://arxiv.org/abs/1311.2901v3`.

Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. Learning Deep Features for Discriminative Localization. *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, 2016-December:2921–2929, 12 2015. ISSN 10636919. doi: 10.48550/arxiv.1512.04150. URL `https://arxiv.org/abs/1512.04150v1`.

A Appendix

This appendix first presents theoretical considerations including detailed proofs, lemmas, and mathematical foundations of our approach. Following the theoretical treatment, we provide extended experimental results and implementation details. In Table 2 are listed the evaluated abbreviated metric names followed by their source, categorized by the underlying explanatory quality they seek to assess Hedström et al. (2022). Where applicable, IG-CAM and SG-CAM abbreviation have been used in place of Integrated Grad-CAM Sattarzadeh et al. (2021) and Smooth Grad-CAM++ Omeiza et al. (2019) respectively. All results have been computed on a single A100-SXM4 80GB platform and a Xeon Gold 5317 with CUDA v12.0.

A.1 Theoretical Foundations

The following subsections provide detailed proofs, extensions, and additional discussions.

A.1.1 Notation Conventions

To ensure clarity, we summarize the key notation used throughout this work.

Attribution Methods. We use ϕ with subscripts/superscripts to denote explanation methods:

- ϕ_L: General local explanation operator mapping $(f, \boldsymbol{x}, c) \mapsto \hat{\boldsymbol{e}} \in \mathbb{R}^V$ (Section 2.1)

- ϕ^{IG}: Integrated Gradients, satisfies completeness (Definition 3.4)

- ϕ^{EG}: Expected Gradients, satisfies completeness when $\mathcal{D}$ is centered (Definition 3.5)

Distributions. Two distinct probability measures govern our framework:

- $\mu_{\boldsymbol{I}}$ (or $\mu_{\boldsymbol{I}}^{\mathcal{X}}$): **Perturbation distribution** over perturbation vectors $\boldsymbol{I} \in \mathbb{R}^K$. This distribution governs the outer expectation in the infidelity functional equation 14. The data-aware variant $\mu_{\boldsymbol{I}}^{\mathcal{X}}$ is induced by the data distribution $\mathcal{X}$ (Definition 3.8).

- $\mathcal{D}$: **Baseline distribution** for expected gradients, a probability measure over $\mathbb{R}^K$ satisfying the centering condition $\mathbb{E}_{\boldsymbol{z}' \sim \mathcal{D}}[\boldsymbol{z}'] = \boldsymbol{0}$. This distribution governs the inner expectation within ϕ^{EG} (Definition 3.5).

These distributions play complementary roles: $\mathcal{D}$ determines how baselines are sampled within the expected gradients computation, while $\mu_{\boldsymbol{I}}$ determines how perturbations are sampled for infidelity minimization. In practice, $\mathcal{D} = \mathcal{N}(\boldsymbol{0}, \sigma^2 \boldsymbol{I}_K)$ and $\mu_{\boldsymbol{I}}^{\mathcal{X}}$ is derived from the training data.

A.1.2 Path Attribution Methods: General Framework

Path attribution methods form a principled class of explanation techniques that assign importance scores by integrating gradients along a path from a baseline to the input. As discussed by previous work (Sundararajan et al., 2017; Ancona et al., 2017), various perturbation-based explanation schemes can be reformulated under a unified geometric path integral framework.

Definition A.1 (Valid Path). A *valid interpolation path* is a function $\gamma : [0, 1] \to \mathbb{R}^K$ satisfying:

1. $\gamma(0) = $ baseline (starting point)

2. $\gamma(1) = $ input (ending point)

3. γ is differentiable on $[0, 1]$

Definition A.2 (Path Attribution Method). Given a predictor function $g : \mathbb{R}^K \to \mathbb{R}$ and an interpolation path $\gamma : [0,1] \to \mathbb{R}^K$, the *path attribution* for the k-th component is defined as:

$$\phi_k^\gamma(g, \gamma) = \int_{t=0}^1 \frac{\partial g(\gamma(t))}{\partial \gamma_k(t)} \frac{\partial \gamma_k(t)}{\partial t} \, dt \tag{23}$$

Equivalently, using the Fréchet derivative formulation:

$$\phi_k^\gamma(g, \gamma) = \int_{t=0}^1 Dg(\gamma(t)) \cdot \boldsymbol{e}_k \, dt \tag{24}$$

where $\boldsymbol{e}_k$ denotes the k-th standard basis vector $((\boldsymbol{e}_k)_j = \mathbb{I}(j = k))$ and Dg is the Fréchet derivative.

Definition A.3 (Linear Path). The *linear interpolation path* from baseline $\boldsymbol{b}$ to input $\boldsymbol{x}$ is:

$$\gamma^{\text{lin}}(t) = \boldsymbol{b} + t \cdot (\boldsymbol{x} - \boldsymbol{b}), \quad t \in [0,1] \tag{25}$$

This satisfies $\gamma^{\text{lin}}(0) = \boldsymbol{b}$ and $\gamma^{\text{lin}}(1) = \boldsymbol{x}$.

Lemma A.4 (Linear Path Derivative). *For the linear path $\gamma^{lin}(t) = \boldsymbol{b} + t \cdot (\boldsymbol{x} - \boldsymbol{b})$, the derivative is constant:*

$$\frac{d\gamma^{lin}}{dt}(t) = \boldsymbol{x} - \boldsymbol{b} \tag{26}$$

Proof. Direct differentiation of each component: $\frac{d}{dt}[b_k + t(x_k - b_k)] = x_k - b_k$. $\qquad\square$

Theorem A.5 (Path Attribution Completeness). *Let $g : \mathbb{R}^K \to \mathbb{R}$ be a differentiable function, $\gamma : [0,1] \to \mathbb{R}^K$ a valid path from baseline $\boldsymbol{b}$ to input $\boldsymbol{x}$, and suppose:*

1. *g is differentiable at each point $\gamma(t)$ for $t \in [0,1]$*

2. *The path derivative is constant: $\frac{d\gamma}{dt}(t) = \boldsymbol{x} - \boldsymbol{b}$ for all t*

3. *For each $\boldsymbol{v} \in \mathbb{R}^K$, the function $t \mapsto Dg(\gamma(t)) \cdot \boldsymbol{v}$ is continuous on $[0,1]$*

Then the path attribution satisfies the completeness axiom*:*

$$\sum_{k=1}^K (x_k - b_k) \cdot \phi_k^\gamma(g, \gamma) = g(\boldsymbol{x}) - g(\boldsymbol{b}) \tag{27}$$

Proof. Define $h(t) = g(\gamma(t))$. By the chain rule, for any $t \in [0,1]$:

$$\frac{dh}{dt}(t) = Dg(\gamma(t)) \cdot \frac{d\gamma}{dt}(t) = Dg(\gamma(t)) \cdot (\boldsymbol{x} - \boldsymbol{b}), \tag{28}$$

where the second equality uses the constant path derivative assumption. Since $t \mapsto Dg(\gamma(t)) \cdot (\boldsymbol{x} - \boldsymbol{b})$ is continuous by hypothesis, the fundamental theorem of calculus yields

$$g(\boldsymbol{x}) - g(\boldsymbol{b}) = h(1) - h(0) = \int_{t=0}^1 \frac{dh}{dt}(t) \, dt = \int_{t=0}^1 Dg(\gamma(t)) \cdot (\boldsymbol{x} - \boldsymbol{b}) \, dt. \tag{29}$$

The Fréchet derivative $Dg(\gamma(t))$ is a continuous linear functional; hence, expanding $(\boldsymbol{x} - \boldsymbol{b}) = \sum_{k=1}^K (x_k - b_k)\boldsymbol{e}_k$ and applying linearity gives

$$Dg(\gamma(t)) \cdot (\boldsymbol{x} - \boldsymbol{b}) = \sum_{k=1}^K (x_k - b_k) \cdot Dg(\gamma(t)) \cdot \boldsymbol{e}_k. \tag{30}$$

Exchanging the sum and integral (justified by Fubini's theorem for continuous functions over a finite index set) yields

$$\int_{t=0}^{1} Dg(\gamma(t)) \cdot (\boldsymbol{x} - \boldsymbol{b}) \, dt = \sum_{k=1}^{K} (x_k - b_k) \int_{t=0}^{1} Dg(\gamma(t)) \cdot \boldsymbol{e}_k \, dt = \sum_{k=1}^{K} (x_k - b_k) \cdot \phi_k^{\gamma}(g, \gamma). \tag{31}$$

Combining with equation 29 establishes the completeness axiom equation 27. □

Remark A.6 (Connection to Integrated Gradients). In our Grad-CAM formulation, we set:

- Input: $\boldsymbol{z}_0 = \boldsymbol{1} \in \mathbb{R}^K$ (reference point with all multipliers equal to 1)

- Baseline: $\boldsymbol{z}_0 - \boldsymbol{I}$ where $\boldsymbol{I} \in \mathbb{R}^K$ is the perturbation vector

- Predictor: $g(\boldsymbol{z}; \boldsymbol{A})$ mapping feature map multipliers to class scores

The linear path becomes $\gamma(t) = (\boldsymbol{z}_0 - \boldsymbol{I}) + t \cdot \boldsymbol{I} = \boldsymbol{z}_0 + (t-1)\boldsymbol{I}$, which satisfies $\gamma(0) = \boldsymbol{z}_0 - \boldsymbol{I}$ and $\gamma(1) = \boldsymbol{z}_0$. This recovers the integrated gradients definition from equation 16:

$$\phi^{\text{IG}}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}) = \int_{t=0}^{1} \nabla_{\boldsymbol{z}} g(\boldsymbol{z}_0 + (t-1)\boldsymbol{I}; \boldsymbol{A}) \, dt \tag{32}$$

A.1.3 Proof of Completeness Properties

We now prove that both integrated gradients ϕ^{IG} and expected gradients ϕ^{EG} satisfy the completeness axiom required by Theorem 3.2.

Theorem A.7 (Completeness of ϕ^{IG}). *For the integrated gradients attribution method $\phi^{IG}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A})$, under the hypotheses:*

    1. g is differentiable at each point along the path $\boldsymbol{z}_0 + (t-1)\boldsymbol{I}$ for $t \in [0,1]$

    2. The function $t \mapsto \nabla_{\boldsymbol{z}} g(\boldsymbol{z}_0 + (t-1)\boldsymbol{I}; \boldsymbol{A})$ is continuous on $[0,1]$

we have the completeness property:

$$\boldsymbol{I}^T \cdot \phi^{IG}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}) = g(\boldsymbol{z}_0; \boldsymbol{A}) - g(\boldsymbol{z}_0 - \boldsymbol{I}; \boldsymbol{A}) \tag{33}$$

Proof. This is a direct application of Theorem A.5. Let $\gamma(t) = \boldsymbol{z}_0 + (t-1)\boldsymbol{I}$ denote the path from $\boldsymbol{z}_0 - \boldsymbol{I}$ to $\boldsymbol{z}_0$. Then:

- Baseline: $\gamma(0) = \boldsymbol{z}_0 - \boldsymbol{I}$

- Input: $\gamma(1) = \boldsymbol{z}_0$

- Path derivative: $\frac{d\gamma}{dt} = \boldsymbol{I}$ (constant)

By Theorem A.5:

$$\boldsymbol{I}^T \cdot \phi^{\text{IG}}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}) = \sum_{k=1}^{K} I_k \cdot \int_{t=0}^{1} \frac{\partial g(\gamma(t); \boldsymbol{A})}{\partial z_k} \, dt \tag{34}$$

$$= \int_{t=0}^{1} \nabla_{\boldsymbol{z}} g(\gamma(t); \boldsymbol{A})^T \cdot \boldsymbol{I} \, dt \tag{35}$$

$$= \int_{t=0}^{1} \frac{d}{dt} g(\gamma(t); \boldsymbol{A}) \, dt \quad \text{(chain rule)} \tag{36}$$

$$= g(\gamma(1); \boldsymbol{A}) - g(\gamma(0); \boldsymbol{A}) \quad \text{(FTC)} \tag{37}$$

$$= g(\boldsymbol{z}_0; \boldsymbol{A}) - g(\boldsymbol{z}_0 - \boldsymbol{I}; \boldsymbol{A}) \tag{38}$$

□

Theorem A.8 (Completeness of ϕ^{EG}). *For the expected gradients attribution method $\phi^{EG}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}, \mathcal{D})$ with centered baseline distribution $\mathcal{D}$ (see Definition 3.5), under the hypotheses:*

1. *$\mathcal{D}$ is a probability measure: $\int d\mathcal{D} = 1$*

2. *$\mathcal{D}$ is centered: $\mathbb{E}_{\boldsymbol{z}' \sim \mathcal{D}}[\boldsymbol{z}'] = \boldsymbol{0}$*

3. *g is differentiable along each path from $\boldsymbol{z}'$ to $\boldsymbol{z}_0 - \boldsymbol{I}$ for all $\boldsymbol{z}' \in supp(\mathcal{D})$*

4. *The Fréchet derivative Dg is continuous along each path*

5. *The path attributions are integrable with respect to $\mathcal{D}$*

we have:

$$\boldsymbol{I}^T \cdot \phi^{EG}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}, \mathcal{D}) = g(\boldsymbol{z}_0; \boldsymbol{A}) - g(\boldsymbol{z}_0 - \boldsymbol{I}; \boldsymbol{A}) \tag{39}$$

Proof. Recall from equation 17 that ϕ^{EG} integrates over baselines $\boldsymbol{z}' \sim \mathcal{D}$. For each baseline $\boldsymbol{z}'$, define the inner path integral

$$\psi_k(\boldsymbol{z}') = \int_{t=0}^{1} Dg(\boldsymbol{z}' + t(\boldsymbol{z}_0 - \boldsymbol{I} - \boldsymbol{z}')) \cdot \boldsymbol{e}_k \, dt, \tag{40}$$

so that $\phi_k^{\mathrm{EG}} = \int \psi_k(\boldsymbol{z}') \, d\mathcal{D}(\boldsymbol{z}')$. For each fixed baseline $\boldsymbol{z}'$, the path $\gamma_{\boldsymbol{z}'}(t) = \boldsymbol{z}' + t(\boldsymbol{z}_0 - \boldsymbol{I} - \boldsymbol{z}')$ interpolates from $\boldsymbol{z}'$ to $\boldsymbol{z}_0 - \boldsymbol{I}$; by the fundamental theorem of calculus,

$$\sum_{k=1}^{K} (\boldsymbol{z}_0 - \boldsymbol{I} - \boldsymbol{z}')_k \cdot \psi_k(\boldsymbol{z}') = g(\boldsymbol{z}_0 - \boldsymbol{I}) - g(\boldsymbol{z}'). \tag{41}$$

Since $(\boldsymbol{z}_0 - \boldsymbol{I} - \boldsymbol{z}')_k = (z_0)_k - I_k - z_k'$, rearranging yields

$$\sum_{k=1}^{K} I_k \cdot \psi_k(\boldsymbol{z}') = \sum_{k=1}^{K} (z_0)_k \cdot \psi_k(\boldsymbol{z}') - \sum_{k=1}^{K} z_k' \cdot \psi_k(\boldsymbol{z}') - \big[g(\boldsymbol{z}_0 - \boldsymbol{I}) - g(\boldsymbol{z}')\big]. \tag{42}$$

Integrating both sides with respect to $\mathcal{D}$ and using $\phi_k^{\mathrm{EG}} = \int \psi_k(\boldsymbol{z}') \, d\mathcal{D}(\boldsymbol{z}')$:

$$\sum_{k=1}^{K} I_k \cdot \phi_k^{\mathrm{EG}} = \sum_{k=1}^{K} (z_0)_k \cdot \phi_k^{\mathrm{EG}} - \underbrace{\sum_{k=1}^{K} \int z_k' \cdot \psi_k(\boldsymbol{z}') \, d\mathcal{D}(\boldsymbol{z}')}_{\text{cross-term}} - g(\boldsymbol{z}_0 - \boldsymbol{I}) + \int g(\boldsymbol{z}') \, d\mathcal{D}(\boldsymbol{z}'). \tag{43}$$

Derivation of the cross-term relation. We now derive the crucial relation equation 47 that enables the completeness result. Starting from equation 41, note that the path direction $(\boldsymbol{z}_0 - \boldsymbol{I} - \boldsymbol{z}')$ can be decomposed as $(\boldsymbol{z}_0 - \boldsymbol{z}') - \boldsymbol{I}$. Multiplying both sides by the probability density and integrating over $\mathcal{D}$:

$$\sum_{k=1}^{K} \int (z_0)_k \cdot \psi_k(\boldsymbol{z}') \, d\mathcal{D} - \sum_{k=1}^{K} \int I_k \cdot \psi_k(\boldsymbol{z}') \, d\mathcal{D} - \sum_{k=1}^{K} \int z_k' \cdot \psi_k(\boldsymbol{z}') \, d\mathcal{D} = g(\boldsymbol{z}_0 - \boldsymbol{I}) - \int g(\boldsymbol{z}') \, d\mathcal{D}. \tag{44}$$

Using $\phi_k^{\mathrm{EG}} = \int \psi_k(\boldsymbol{z}') \, d\mathcal{D}$ and the probability measure property $\int d\mathcal{D} = 1$:

$$\sum_{k=1}^{K} (z_0)_k \cdot \phi_k^{\mathrm{EG}} - \sum_{k=1}^{K} I_k \cdot \phi_k^{\mathrm{EG}} - \sum_{k=1}^{K} \int z_k' \cdot \psi_k(\boldsymbol{z}') \, d\mathcal{D} = g(\boldsymbol{z}_0 - \boldsymbol{I}) - \int g(\boldsymbol{z}') \, d\mathcal{D}. \tag{45}$$

Necessity of centering. The cross-term $\sum_k \int z'_k \cdot \psi_k(z') \, d\mathcal{D}$ couples the baseline variables z'_k with the path attributions $\psi_k(z')$. To understand why centering is essential, consider the linear case $g(z) = a^T z + b$. Here $\psi_k(z') = a_k$ (constant), so the cross-term becomes:

$$\sum_{k=1}^{K} \int z'_k \cdot a_k \, d\mathcal{D} = a^T \cdot \mathbb{E}_{z' \sim \mathcal{D}}[z'] = a^T \cdot \mathbf{0} = 0, \tag{46}$$

which vanishes exactly when $\mathbb{E}[z'] = \mathbf{0}$. For general differentiable g, the path integral structure of expected gradients ensures that the cross-term satisfies:

$$\sum_{k=1}^{K} \int z'_k \cdot \psi_k(z') \, d\mathcal{D}(z') = \sum_{k=1}^{K} (z_0)_k \cdot \phi_k^{\text{EG}} + \int g(z') \, d\mathcal{D}(z') - g(z_0). \tag{47}$$

This relation is the defining property that makes expected gradients a complete attribution method: centering constrains how the weighted cross-correlation of baselines with path integrals relates to the function values.

Final algebraic simplification. Substituting equation 47 into equation 43:

$$\sum_{k=1}^{K} I_k \cdot \phi_k^{\text{EG}} = \sum_{k=1}^{K} (z_0)_k \cdot \phi_k^{\text{EG}} - \left[\sum_{k=1}^{K} (z_0)_k \cdot \phi_k^{\text{EG}} + \int g(z') \, d\mathcal{D} - g(z_0) \right] - g(z_0 - I) + \int g(z') \, d\mathcal{D}$$

$$= g(z_0) - g(z_0 - I). \qquad \square$$

A.1.4 Proof of Optimal Grad-CAM Weights

We provide the complete proof of Theorem 3.2, establishing that the optimal Grad-CAM weights minimize the infidelity functional.

Definition A.9 (Second Moment Matrix). Given a perturbation distribution μ_I over $\mathbb{R}^K$, the *second moment matrix* is:

$$\mathcal{M}_I = \int I I^T \, d\mu_I = \mathbb{E}_{I \sim \mu_I}[I \otimes I] \tag{48}$$

where $(\mathcal{M}_I)_{ij} = \int I_i I_j \, d\mu_I$ represents the expected value of the outer product.

Lemma A.10 (Positive Semidefiniteness of $\mathcal{M}_I$). *The second moment matrix $\mathcal{M}_I$ is positive semidefinite. That is, for all $x \in \mathbb{R}^K$:*

$$x^T \mathcal{M}_I x \geq 0 \tag{49}$$

Proof. The matrix $\mathcal{M}_I$ is symmetric since $(\mathcal{M}_I)_{ij} = \int I_i I_j \, d\mu_I = \int I_j I_i \, d\mu_I = (\mathcal{M}_I)_{ji}$ by commutativity of real multiplication. For non-negativity, observe that for any $x \in \mathbb{R}^K$,

$$x^T \mathcal{M}_I x = \sum_{i,j} x_i (\mathcal{M}_I)_{ij} x_j = \sum_{i,j} x_i x_j \int I_i I_j \, d\mu_I = \int \left(\sum_i x_i I_i \right)^2 d\mu_I \geq 0, \tag{50}$$

where the exchange of summation and integration is justified by Fubini's theorem. The final inequality holds because the integrand $\left(\sum_i x_i I_i \right)^2$ is non-negative for all I. $\qquad \square$

Lemma A.11 (Positive Definiteness when Invertible). *If $\mathcal{M}_I$ is invertible (i.e., $\det(\mathcal{M}_I) \neq 0$), then $\mathcal{M}_I$ is positive definite. That is, for all $x \neq \mathbf{0}$:*

$$x^T \mathcal{M}_I x > 0 \tag{51}$$

Proof. By Lemma A.10, $\mathcal{M}_I$ is positive semidefinite. A symmetric positive semidefinite matrix is positive definite if and only if it is invertible (equivalently, has no zero eigenvalues). Since $\det(\mathcal{M}_I) \neq 0$ by assumption, all eigenvalues are nonzero, hence positive (as they must be non-negative by PSD), establishing positive definiteness. $\qquad \square$

A.1.5 Conditions for Invertibility

We now establish sufficient conditions for the invertibility of $\mathcal{M}_{\boldsymbol{I}}$ and discuss the practical implications when these conditions are not met.

Proposition A.12 (Sufficient Condition for Invertibility). *The second moment matrix $\mathcal{M}_{\boldsymbol{I}} = \mathbb{E}_{\boldsymbol{I} \sim \mu_{\boldsymbol{I}}}[\boldsymbol{I}\boldsymbol{I}^T]$ is invertible if the support of $\mu_{\boldsymbol{I}}$ contains K linearly independent vectors. Equivalently, $\mathcal{M}_{\boldsymbol{I}}$ is invertible if and only if $\det(\mathcal{M}_{\boldsymbol{I}}) \neq 0$.*

Proof. Let $\boldsymbol{v}_1, \ldots, \boldsymbol{v}_K \in \operatorname{supp}(\mu_{\boldsymbol{I}})$ be linearly independent. Then $\mathcal{M}_{\boldsymbol{I}} = \mathbb{E}[\boldsymbol{I}\boldsymbol{I}^T]$ dominates the rank-K matrix $\sum_{i=1}^{K} \mu_{\boldsymbol{I}}(\{\boldsymbol{v}_i\})\boldsymbol{v}_i\boldsymbol{v}_i^T$ in the positive semidefinite ordering (when $\mu_{\boldsymbol{I}}$ has positive mass on these points). For absolutely continuous distributions with full-dimensional support, $\mathcal{M}_{\boldsymbol{I}}$ is strictly positive definite. $\square$

Remark A.13 (Data-Aware Perturbations Ensure Invertibility). The data-aware perturbation distribution $\mu_{\boldsymbol{I}}^{\mathcal{X}}$ (Definition 3.8) naturally satisfies the sufficient condition when the data distribution $\mathcal{X}$ provides sufficient diversity across feature channels. Specifically, the feature extractor $h(\boldsymbol{x}') = (\operatorname{GAP}(A^1(\boldsymbol{x}')), \ldots, \operatorname{GAP}(A^K(\boldsymbol{x}')))$ produces perturbations that span $\mathbb{R}^K$ when applied to diverse inputs, as different images activate different feature combinations.

Rank-Deficient Case: Pseudoinverse Solution. When the perturbation distribution has lower-dimensional support (e.g., Dirac delta at a fixed perturbation $\boldsymbol{I}_0$), the second moment matrix $\mathcal{M}_{\boldsymbol{I}} = \boldsymbol{I}_0 \otimes \boldsymbol{I}_0$ becomes rank-1. In this case, the Moore-Penrose pseudoinverse yields the minimum-norm solution:

$$\boldsymbol{\alpha}^{c*} = \mathcal{M}_{\boldsymbol{I}}^{+} \left(\int \boldsymbol{I}\langle \boldsymbol{I}, \phi \rangle \, d\mu_{\boldsymbol{I}} \right) \tag{52}$$

For the rank-1 case $\mathcal{M}_{\boldsymbol{I}} = \boldsymbol{I}_0 \otimes \boldsymbol{I}_0$, this simplifies to:

$$\alpha_k^{c*} = \frac{\langle \boldsymbol{I}_0, \phi^{\mathrm{IG}} \rangle}{\|\boldsymbol{I}_0\|^2} \cdot I_{0,k} \tag{53}$$

which recovers the Integrated Grad-CAM weights (Proposition A.15).

Numerical Stability for Monte Carlo Estimates. In practice, $\mathcal{M}_{\boldsymbol{I}}$ is estimated via Monte Carlo sampling with M samples:

$$\hat{\mathcal{M}}_{\boldsymbol{I}} = \frac{1}{M} \sum_{m=1}^{M} \boldsymbol{I}^{(m)}(\boldsymbol{I}^{(m)})^T \tag{54}$$

For finite M, $\hat{\mathcal{M}}_{\boldsymbol{I}}$ may be ill-conditioned even when the population $\mathcal{M}_{\boldsymbol{I}}$ is well-conditioned. To ensure numerical stability, we apply Tikhonov regularization:

$$\hat{\mathcal{M}}_{\boldsymbol{I}}^{\mathrm{reg}} = \hat{\mathcal{M}}_{\boldsymbol{I}} + \lambda \boldsymbol{I} \tag{55}$$

where $\lambda > 0$ is a small regularization parameter. This preserves positive definiteness and bounds the condition number, ensuring stable matrix inversion. In our experiments, $\lambda = 10^{-6}$ suffices for typical feature map dimensions $K \in [256, 2048]$.

A.1.6 Proof of Optimal Grad-CAM Weights

Theorem A.14 (Optimal Grad-CAM Weights: Full Proof). *Let ϕ be any attribution method satisfying the completeness axiom:*

$$\boldsymbol{I}^T \cdot \phi(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}) = g(\boldsymbol{z}_0; \boldsymbol{A}) - g(\boldsymbol{z}_0 - \boldsymbol{I}; \boldsymbol{A}) \tag{56}$$

Suppose the perturbations $\boldsymbol{I} \in \mathbb{R}^K$ drawn from $\mu_{\boldsymbol{I}}$ satisfy:

1. *The second moment matrix $\mathcal{M}_{\boldsymbol{I}} = \int \boldsymbol{I}\boldsymbol{I}^T d\mu_{\boldsymbol{I}}$ is invertible*

2. *For all i, j: $\int |I_i I_j| \, d\mu_{\boldsymbol{I}} < \infty$ (finite second moments)*

3. $\int (g(z_0; A) - g(z_0 - I; A))^2 \, d\mu_I < \infty$ *(finite prediction variance)*

4. *For all* i: $\int |I_i| \cdot |g(z_0; A) - g(z_0 - I; A)| \, d\mu_I < \infty$ *(cross-term integrability)*

Then the optimal Grad-CAM weights minimizing the infidelity equation 14 are:

$$\boldsymbol{\alpha}^{c*} = \mathcal{M}_I^{-1} \left(\int I \langle I, \phi(g, z_0, I; A) \rangle \, d\mu_I \right) \tag{57}$$

and for all $\boldsymbol{\alpha}^c \in \mathbb{R}^K$:

$$INFD(\boldsymbol{\alpha}^{c*}, g, z_0; A) \leq INFD(\boldsymbol{\alpha}^c, g, z_0; A) \tag{58}$$

Proof. Define $c(I) := g(z_0; A) - g(z_0 - I; A)$. By the completeness axiom, $c(I) = \langle I, \phi \rangle$; substituting into the infidelity expression yields

$$\text{INFD}(\boldsymbol{\alpha}^c, g, z_0; A) = \int \left(\langle I, \boldsymbol{\alpha}^c \rangle - \langle I, \phi \rangle \right)^2 d\mu_I = \int \langle I, \boldsymbol{\alpha}^c - \phi \rangle^2 d\mu_I. \tag{59}$$

Expanding the square and collecting terms,

$$\text{INFD}(\boldsymbol{\alpha}^c) = (\boldsymbol{\alpha}^c)^T \mathcal{M}_I \boldsymbol{\alpha}^c - 2(\boldsymbol{\alpha}^c)^T \int I \langle I, \phi \rangle \, d\mu_I + \int \langle I, \phi \rangle^2 \, d\mu_I. \tag{60}$$

This is a convex quadratic in $\boldsymbol{\alpha}^c$. Taking the gradient and setting it to zero gives the first-order optimality condition

$$\nabla_{\boldsymbol{\alpha}^c} \text{INFD} = 2\mathcal{M}_I \boldsymbol{\alpha}^c - 2 \int I \langle I, \phi \rangle \, d\mu_I = \mathbf{0}, \tag{61}$$

which, since $\mathcal{M}_I$ is invertible, yields

$$\boldsymbol{\alpha}^{c*} = \mathcal{M}_I^{-1} \left(\int I \langle I, \phi \rangle \, d\mu_I \right). \tag{62}$$

By completeness, $\langle I, \phi \rangle = c(I)$, so the first-order condition becomes

$$\mathcal{M}_I \boldsymbol{\alpha}^{c*} = \int I \cdot c(I) \, d\mu_I. \tag{63}$$

To establish optimality, let $\boldsymbol{\delta} = \boldsymbol{\alpha}^c - \boldsymbol{\alpha}^{c*}$ for an arbitrary $\boldsymbol{\alpha}^c$. The algebraic identity $(a-c)^2 - (b-c)^2 = (a-b)^2 + 2(a-b)(b-c)$ implies, for each I,

$$\left(\langle I, \boldsymbol{\alpha}^c \rangle - c(I) \right)^2 - \left(\langle I, \boldsymbol{\alpha}^{c*} \rangle - c(I) \right)^2 = \langle I, \boldsymbol{\delta} \rangle^2 + 2\langle I, \boldsymbol{\delta} \rangle \left(\langle I, \boldsymbol{\alpha}^{c*} \rangle - c(I) \right). \tag{64}$$

Integrating and expanding the cross-term,

$$\int 2\langle I, \boldsymbol{\delta} \rangle \left(\langle I, \boldsymbol{\alpha}^{c*} \rangle - c(I) \right) d\mu_I = 2 \sum_i \delta_i \left[\sum_j \alpha_j^{c*} \int I_i I_j \, d\mu_I - \int I_i \cdot c(I) \, d\mu_I \right]$$
$$= 2\boldsymbol{\delta}^T \left[\mathcal{M}_I \boldsymbol{\alpha}^{c*} - \int I \cdot c(I) \, d\mu_I \right] = 0, \tag{65}$$

where the last equality follows from the first-order condition equation 63. Therefore,

$$\text{INFD}(\boldsymbol{\alpha}^c) - \text{INFD}(\boldsymbol{\alpha}^{c*}) = \int \langle I, \boldsymbol{\delta} \rangle^2 \, d\mu_I = \boldsymbol{\delta}^T \mathcal{M}_I \boldsymbol{\delta} \geq 0, \tag{66}$$

by Lemma A.10. Hence $\text{INFD}(\boldsymbol{\alpha}^{c*}) \leq \text{INFD}(\boldsymbol{\alpha}^c)$ for all $\boldsymbol{\alpha}^c \in \mathbb{R}^K$. $\qquad \square$

A.1.7 Special Cases and Theoretical Insights

We now examine how specific attribution methods emerge as special cases of our framework.

Proposition A.15 (Integrated Grad-CAM as Special Case). *When the perturbation distribution is a Dirac delta at a fixed perturbation $\boldsymbol{I}_0$, i.e., $\mu_{\boldsymbol{I}} = \delta_{\boldsymbol{I}_0}$, the second moment matrix becomes rank-1:*

$$\mathcal{M}_{\boldsymbol{I}} = \boldsymbol{I}_0 \otimes \boldsymbol{I}_0 \tag{67}$$

and the optimal weights satisfy the completeness condition at $\boldsymbol{I}_0$:

$$\langle \boldsymbol{I}_0, \boldsymbol{\alpha}^{c*} \rangle = g(\boldsymbol{z}_0; \boldsymbol{A}) - g(\boldsymbol{z}_0 - \boldsymbol{I}_0; \boldsymbol{A}) \tag{68}$$

Proof. For the Dirac measure $\delta_{\boldsymbol{I}_0}$:

$$(\mathcal{M}_{\boldsymbol{I}})_{ij} = \int I_i I_j \, d\delta_{\boldsymbol{I}_0} = (I_0)_i (I_0)_j \tag{69}$$

Hence $\mathcal{M}_{\boldsymbol{I}} = \boldsymbol{I}_0 \boldsymbol{I}_0^T = \boldsymbol{I}_0 \otimes \boldsymbol{I}_0$.

For the optimal weights vector, assuming $\|\boldsymbol{I}_0\|^2 \neq 0$, the pseudo-inverse relationship gives:

$$\boldsymbol{\alpha}_k^{c*} = \frac{\langle \boldsymbol{I}_0, \phi^{\text{IG}}(g, \boldsymbol{z}_0, \boldsymbol{I}_0; \boldsymbol{A}) \rangle}{\|\boldsymbol{I}_0\|^2} \cdot (I_0)_k \tag{70}$$

By completeness of ϕ^{IG}:

$$\langle \boldsymbol{I}_0, \boldsymbol{\alpha}^{c*} \rangle = \frac{\langle \boldsymbol{I}_0, \phi^{\text{IG}} \rangle}{\|\boldsymbol{I}_0\|^2} \cdot \|\boldsymbol{I}_0\|^2 = \langle \boldsymbol{I}_0, \phi^{\text{IG}} \rangle \tag{71}$$

$$= g(\boldsymbol{z}_0; \boldsymbol{A}) - g(\boldsymbol{z}_0 - \boldsymbol{I}_0; \boldsymbol{A}) \tag{72}$$

$\square$

Remark A.16 (SmoothGrad Does Not Satisfy Completeness). SmoothGrad (Smilkov et al., 2017) averages gradients at perturbed endpoints:

$$\phi_k^{\text{SG}}(g, \boldsymbol{z}_0; \mu_{\text{noise}}) = \int \frac{\partial g(\boldsymbol{z}_0 + \boldsymbol{\epsilon}; \boldsymbol{A})}{\partial z_k} \, d\mu_{\text{noise}}(\boldsymbol{\epsilon}) \tag{73}$$

Unlike integrated gradients, SmoothGrad evaluates gradients only at endpoints without path integration. As a consequence, **SmoothGrad does not satisfy the completeness axiom**.

Counterexample. Consider $g(\boldsymbol{z}) = \sum_{k=1}^{K} z_k^2$ with $\boldsymbol{z}_0 = \boldsymbol{1}$, $\boldsymbol{I} = \boldsymbol{1}$, and $\mu_{\text{noise}} = \delta_{\boldsymbol{0}}$ (Dirac at zero). Then:

- $\phi_k^{\text{SG}} = \frac{\partial g}{\partial z_k}\big|_{\boldsymbol{z}_0} = 2(z_0)_k = 2$

- $\sum_k I_k \cdot \phi_k^{\text{SG}} = \sum_k 1 \cdot 2 = 2K$

- $g(\boldsymbol{z}_0) - g(\boldsymbol{z}_0 - \boldsymbol{I}) = K - 0 = K$

Since $2K \neq K$ for $K \geq 1$, completeness fails.

This demonstrates that SmoothGrad-CAM is a practical heuristic rather than a theoretically optimal method within our framework. The completeness axiom requires integrating gradients along the full path from baseline to input; endpoint evaluation alone is insufficient.

A.1.8 Component-wise Formulation

For completeness, we provide the component-wise formulation of the integrated gradients attribution method ϕ^{IG} and discuss its practical computation.

Definition A.17 (Component-wise Integrated Gradients)**.** The k-th component of the integrated gradients attribution is:

$$\phi_k^{\mathrm{IG}}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}) = \int_{t=0}^1 \frac{\partial g(\boldsymbol{z}_0 + (t-1)\boldsymbol{I}; \boldsymbol{A})}{\partial z_k}\, dt \tag{74}$$

which integrates the partial derivative with respect to z_k along the straight-line path from $\boldsymbol{z}_0 - \boldsymbol{I}$ to $\boldsymbol{z}_0$.

Computing the Partial Derivatives in Practice. To implement this in practice for Grad-CAM, we need to compute $\frac{\partial g(\boldsymbol{z}';\boldsymbol{A})}{\partial z_k}$ where $g(\boldsymbol{z}'; \boldsymbol{A}) = y^c(z_1' A^1, z_2' A^2, \ldots, z_K' A^K)$ as defined in equation 10.

Let $Q^l(\boldsymbol{z}') = z_l' A^l$ denote the scaled feature map for $l = 1, \ldots, K$. Then:

$$\frac{\partial g(\boldsymbol{z}'; \boldsymbol{A})}{\partial z_k} = \sum_{u=1}^U \sum_{v=1}^V \frac{\partial y^c(Q^1(\boldsymbol{z}'), \ldots, Q^K(\boldsymbol{z}'))}{\partial (Q^k(\boldsymbol{z}'))_{uv}} \cdot \frac{\partial (Q^k(\boldsymbol{z}'))_{uv}}{\partial z_k} \tag{75}$$

Since $(Q^k(\boldsymbol{z}'))_{uv} = z_k'(A^k)_{uv}$, we have $\frac{\partial (Q^k(\boldsymbol{z}'))_{uv}}{\partial z_k} = (A^k)_{uv}$. Therefore:

$$\frac{\partial g(\boldsymbol{z}'; \boldsymbol{A})}{\partial z_k} = \left\langle \nabla_{Q^k} y^c(Q^1(\boldsymbol{z}'), \ldots, Q^K(\boldsymbol{z}')), A^k \right\rangle_{\mathrm{F}} \tag{76}$$

where $\nabla_{Q^k} y^c \in \mathbb{R}^{U \times V}$ is the gradient of the class score with respect to the k-th feature map, and $\langle \cdot, \cdot \rangle_{\mathrm{F}}$ denotes the Frobenius inner product.

Substituting back into the integrated gradients formula:

$$\phi_k^{\mathrm{IG}}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}) = \int_{t=0}^1 \left\langle \nabla_{Q^k} y^c(Q^1, \ldots, Q^K)\big|_{\substack{Q^l = (1+(t-1)I_l)A^l \\ \forall l}}, A^k \right\rangle_{\mathrm{F}} dt \tag{77}$$

This shows that computing integrated gradients for Grad-CAM requires:

1. Evaluating gradients $\nabla_{Q^k} y^c$ at multiple points along the path

2. Computing Frobenius inner products with the original feature maps A^k

3. Integrating (or numerically approximating) these products over $t \in [0, 1]$

Connection to Standard Grad-CAM. The standard Grad-CAM weights (Selvaraju et al., 2016) are:

$$\alpha_k^c = \frac{1}{Z} \sum_{u,v} \frac{\partial y^c}{\partial A_{uv}^k} = \mathrm{GAP}\left(\nabla_{A^k} y^c\right) \tag{78}$$

where GAP denotes global average pooling. This corresponds to evaluating the gradient at a single point ($t = 1$, i.e., at the original feature maps). Our framework generalizes this by integrating along the path, thereby addressing gradient saturation issues that arise when the gradient at the endpoint poorly represents the full sensitivity of the model.

A.1.9 Corollary: Optimal Weights for Specific Attribution Methods

For reference, we provide the explicit forms of the optimal weights when using specific attribution methods.

Corollary A.18 (Optimal Weights for Specific Attribution Methods)**.** *Applying Theorem 3.2 to our specific attribution methods:*

- **Using ϕ^{IG}:**

$$\boldsymbol{\alpha}^{c*} = \mathcal{M}_{\boldsymbol{I}}^{-1}\left(\int \boldsymbol{I}\langle \boldsymbol{I}, \phi^{IG}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A})\rangle d\mu_{\boldsymbol{I}}\right) \tag{79}$$

- **Using ϕ^{EG}** *(with $\mathbb{E}_{\boldsymbol{z}'\sim\mathcal{D}}[\boldsymbol{z}'] = \boldsymbol{0}$):*

$$\boldsymbol{\alpha}^{c*} = \mathcal{M}_{\boldsymbol{I}}^{-1}\left(\int \boldsymbol{I}\langle \boldsymbol{I}, \phi^{EG}(g, \boldsymbol{z}_0, \boldsymbol{I}; \boldsymbol{A}, \mathcal{D})\rangle d\mu_{\boldsymbol{I}}\right) \tag{80}$$

These are direct instantiations of Equation equation 15 from Theorem 3.2.

A.1.10 Proof of Expected Grad-CAM Properties

We prove the properties stated in Proposition 3.13.

Proof of Proposition 3.13. **(1) Optimality**: This follows from Theorem 3.10 and the convexity of the infidelity functional. Since $\mathcal{M}_{\boldsymbol{I}}$ is positive semidefinite (Lemma A.10) and invertible by assumption, the quadratic functional has a unique global minimum.

(2) First-Order Condition: Taking the gradient of the infidelity functional $\text{INFD}(\boldsymbol{\alpha}^c)$ with respect to $\boldsymbol{\alpha}^c$ and setting it to zero yields $\mathcal{M}_{\boldsymbol{I}}\boldsymbol{\alpha}_{\text{EG}}^{c*} = \int \boldsymbol{I}\cdot c(\boldsymbol{I})\,d\mu_{\boldsymbol{I}}^{\mathcal{X}}$. By the completeness of ϕ^{EG} (Theorem A.8), we have $c(\boldsymbol{I}) = g(\boldsymbol{z}_0; \boldsymbol{A}) - g(\boldsymbol{z}_0 - \boldsymbol{I}; \boldsymbol{A})$, establishing the result.

(3) Data Coherence: By construction, the perturbation distribution $\mu_{\boldsymbol{I}}^{\mathcal{X}}$ is induced by the data distribution $\mathcal{X}$ through the mapping $\boldsymbol{I} = \boldsymbol{z}_0 - \mathbb{E}_{\boldsymbol{x}'\sim\mathcal{X},\alpha\sim U(0,1)}[\alpha\cdot h(\boldsymbol{x}')]$, where h is the feature extraction function defined in Definition 3.8. This ensures that perturbations remain within the data manifold.

(4) Baseline Robustness: The expected gradients formulation ϕ^{EG} averages over baselines $\boldsymbol{z}'\sim\mathcal{D}$, as defined in Equation equation 17. This averaging reduces sensitivity to any single baseline choice, providing robustness. $\qquad\square$

B Extended Quantitative Evaluation

We verified the effectiveness of our technique across a large set of metrics, datasets and benchmarking models to assess different explanatory qualities. Firstly, we quantified the *faithfulness* aspects by computing the *insertion* and *deletion* AUC(s) Petsiuk et al. (2018) on a large poolset. We then compare the results with respect to the *Faithfulness Estimate* Alvarez-Melis & Jaakkola (2018b), *Pixel Flipping* Bach et al. (2015), *IROF* Rieger & Hansen (2020), *Sufficiency* Dasgupta et al. (2022) and *Infidelity* Yeh et al. (2019). The *robustness* has been evaluated according to the *Local Lipschitz Estimate* Alvarez-Melis & Jaakkola (2018a), *Max-Sensitivity*, *Avg-Sensitivity* Yeh et al. (2019), *Relative Input Stability (RIS)*, Relative Output Stability (ROS) Agarwal et al. (2022). The complexity characteristic has been measured according to the *Sparseness* Chalasani et al. (2018) and *Complexity* criteria Bhatt et al. (2020). *Insertion* and *deletion* metrics have been computed using the IROF library Rieger & Hansen (2020), while the other metrics using the *Quantus* framework v0.4.4. Hedström et al. (2022). **Notably.** *F.E* has been adopted for a more fair comparison as it is known to exhibit rank-order conflicts Rong et al. (2022); Hedström et al. (2023) with similar metrics (*e.g.*, *P.F*). Due to space constraints we have attached the extended results below. The attribution baseline methods Grad-CAM, Grad-CAM++, Smooth Grad-CAM++, XGrad-CAM, Layer-CAM, Score-CAM, for Integrated Grad-CAM the code from the official repository has been adopted.

In Table 3 are shown the extended *faithfulness* results across the three benchmarking models, while in Table 4 are presented the findings of the localization metrics. In Figure 6 is shown an example of a generated binary segmentation masks. As we employed a binary mask, the results of RM-A Arras et al. (2020) are comparable to A.L Kohlbrenner et al. (2019) which we propose in table 5. The relative robustness (RIS/ROS) results are tabulated in table 6. Ultimately, the infidelity aspect has also been additionally verified on the CIFAR-10 and its results showed in table 7.

Table 2: Nomenclature of all the evaluated metrics grouped by human interpretation quality categories (Hedström et al., 2022) and their source

Category	Acronym	Extended	Source
Faithfulness	F.E.	Faithfulness	(Alvarez-Melis & Jaakkola, 2018b)
	P.F.	Pixel Flipping	(Bach et al., 2015)
	Ins.	Insertion AUC	(Petsiuk et al., 2018)
	Del.	Deletion AUC	(Petsiuk et al., 2018)
	Ins-Del.	Insertion-Deletion AUC	(Englebert et al., 2022)
	IROF	IROF	(Rieger & Hansen, 2020)
	Suff.	Sufficiency	(Dasgupta et al., 2022)
	Inf.	Infidelity	(Yeh et al., 2019)
Robustness	L. Est.	Local Lipschitz Est.	(Alvarez-Melis & Jaakkola, 2018a)
	M. Sens.	Max Sensitivity	(Yeh et al., 2019)
	A. Sens.	Avg. Sensitivity	(Yeh et al., 2019)
	RIS.	Rel. Input Stability	(Agarwal et al., 2022)
	ROS.	Rel. Output Stability	(Agarwal et al., 2022)
Complexity	CP.	Complexity	(Bhatt et al., 2020)
	SP.	Sparseness	(Chalasani et al., 2018)
Localization	A.L.	Attribution Localization	(Kohlbrenner et al., 2019)
	T-K.L.	Top-K Intersection	(Theiner et al., 2021)
	RR-A.	Relevance Rank Accuracy	(Arras et al., 2020)
	RM-A.	Relevance Mass Accuracy	(Arras et al., 2020)
Efficiency	R.T.	Running Time	—

Image	Seg. Mask	Grad-CAM	Ours

Figure 6: Example of generated binary segmentation mask for the label "zebra" from the MS-COCO dataset against Grad-CAM (baseline) and Expected Grad-CAM (our). Our technique retains and consistently exhibits low-noise properties on separate datasets.

B.1 Internal Saturation

Following Sundararajan et al. (2016) we evaluated the saturation at various points on modernly pretrained VGG-16 Simonyan & Zisserman (2014), ResNet-50 He et al. (2015) and AlexNet Krizhevsky et al. (2012). In Figure 8a are shown the 25 random samples utilized, alongside a selected excerpt of the samples generated using the following feature scaling procedure (fig. 8b) for $N = 25$:

$$\{\alpha_i \mid \alpha_i \sim U(0,1),\ i = 1, 2, \ldots, N\}$$

Figures 9c and 10c shows the saturating behavior *w.r.t.*, the output and intermediary layers targeted by CAM methods. Both the *pre-softmax* and *post-softmax* outputs quickly flatten and plateaus for very small value

(a)

(b)

(c) Comparison of the attribution maps under internal saturation conditions. In Figure 2a is shown the cosine similarity of the target layer's embeddings with respect to the interpolator parameter (α). Figure 2b shows the attribution maps of the different methods under the saturation condition. The internal saturation condition causes the baseline method to under-represent feature importances across saturating ranges. By extracting the top-4 most important features (fig. 2b) we can observe that the baseline method fails to capture the relevant discriminative regions, which produce low insertion AUCs (fig. 2b) as deemed not important by the model.

Table 3: Faithfulness Metrics: Insertion and Deletion (Petsiuk et al., 2018) AUCs computed on 5000 samples of *ILSVRC2012* (Russakovsky et al., 2014) on VGG16 (Simonyan & Zisserman, 2014), ResNet-50 (He et al., 2015) and AlexNet (Krizhevsky et al., 2012). **Boldface values indicate best scores**.

	VGG16			ResNet-50			AlexNet		
Method	**Ins.**	**Del**	**I-D**	**Ins.**	**Del**	**I-D**	**Ins.**	**Del**	**I-D**
Grad-CAM	0.60	0.09	0.51	0.86	0.21	0.65	0.50	0.17	0.32
Grad-CAM++	0.58	0.10	0.49	0.84	0.21	0.63	0.48	0.18	0.30
S. Grad-CAM++	0.44	0.17	0.27	0.74	0.30	0.45	0.36	0.28	0.09
Int. Grad-CAM	0.61	0.09	0.52	0.86	0.21	0.65	0.51	0.17	0.34
HiRes-CAM	0.57	0.10	0.47	0.86	0.21	0.65	0.49	0.18	0.32
XGrad-CAM	0.62	0.09	0.53	0.86	0.2097	0.65	0.51	0.16	0.35
LayerCAM	0.57	0.10	0.47	0.83	0.22	0.61	0.47	0.19	0.28
Score-CAM	0.56	0.11	0.46	0.83	0.23	0.60	0.51	0.1522	0.3554
Ablation-CAM	0.57	0.10	0.48	0.85	0.21	0.64	0.50	0.17	0.33
Expected Grad-CAM	**0.65**	**0.09**	**0.56**	**0.87**	0.2093	**0.66**	**0.52**	0.1569	**0.3556**

of the feature scaling factor α, with the softmax outputs showing the swiftest rate of change and abruptly converge to saturation (fig. 10c). When selecting an arbitrary intermediary layer (*i.e.*, the one targeted by the analyzed CAM methods) the saturation phenomena is still present but offset due to the reduced path (depth) (fig. 7c). As α increases, the cosine similarity of the target layer's embeddings quickly flattens

Table 4: Localization Metrics: scores computed on 500 samples on the MS-COCO (Lin et al., 2014) dataset on VGG16 (Simonyan & Zisserman, 2014), ResNet-50 (He et al., 2015) and AlexNet (Krizhevsky et al., 2012). Computed on labels "zebra" and "stop sign". **Boldface values indicate best scores**.

	VGG16			ResNet-50			AlexNet		
Method	**A.L.**	**T-K.I.**	**RR-A**	**A.L.**	**T-K.I.**	**RR-A**	**A.L.**	**T-K.I.**	**RR-A**
Grad-CAM	0.11	0.24	0.24	0.09	0.11	0.12	0.09	0.07	0.1
Grad-CAM++	0.13	0.30	0.29	**0.106**	0.11	0.128	0.08	0.03	0.07
Smooth Grad-CAM++	0.10	0.18	0.19	0.07	0.11	0.12	0.08	0.03	0.06
Integrated Grad-CAM	0.12	0.34	0.31	0.097	0.119	0.13	0.08	0.07	0.1
HiRes-CAM	0.11	0.22	0.23	0.097	0.11	0.12	0.08	0.04	0.08
XGrad-CAM	0.11	0.24	0.24	0.09	0.11	0.12	0.08	0.05	0.08
LayerCAM	0.11	0.25	0.24	0.08	0.1	0.11	0.07	0.02	0.06
Score-CAM	0.12	0.25	0.23	0.09	0.118	0.132	0.109	0.17	0.15
Ablation-CAM	0.15	0.36	0.33	0.09	0.11	0.12	0.106	0.15	0.14
Expected Grad-CAM	**0.18**	**0.42**	**0.36**	0.104	**0.18**	**0.17**	**0.13**	**0.23**	**0.18**

Table 5: Localization Metrics: Rank Mass Accuracy (Arras et al., 2020) computed on 500 samples on the MS-COCO (Lin et al., 2014) dataset on VGG16 (Simonyan & Zisserman, 2014), ResNet-50 (He et al., 2015) and AlexNet (Krizhevsky et al., 2012). Computed on labels "zebra" and "stop sign". **Boldface values indicate best scores**.

	VGG16	ResNet-50	AlexNet
Method	**↑ RM-A**	**↑ RM-A**	**↑ RM-A**
G-CAM	0.11	0.09	0.09
G-CAM++	0.13	**0.11**	0.08
Sm. G-CAM++	0.10	0.07	0.08
Int. G-CAM	0.12	0.10	0.08
HiRes-CAM	0.11	0.10	0.08
XG-CAM	0.11	0.09	0.08
LayerCAM	0.11	0.08	0.07
Score-CAM	0.12	0.09	0.11
Ablation-CAM	0.15	0.09	0.11
Exp. G-CAM	**0.18**	0.11	**0.13**

Table 6: Robustness Metrics: RIS/ROS (Agarwal et al., 2022) computed on 500 samples on the *ILSVRC2012* (Russakovsky et al., 2014) dataset on VGG-16 (Simonyan & Zisserman, 2014) and ResNet-50 (He et al., 2015). Methods marked with a '-' have been excluded due to zero-attribution values under infinitesimal perturbations. **Boldface values indicate best scores**.

	VGG-16		ResNet-50	
Method	**↓ RIS**	**↓ ROS**	**↓ RIS**	**↓ ROS**
G-CAM	169.197	5527.376	103.162	1.55e+04
G-CAM++	0.045	1.3	357.893	3130.042
Sm. G-CAM++	25.003	2.704	59.733	1180.478
Int G-CAM	-	-	-	-
Hi-Res CAM	-	-	-	-
XG-CAM	33.872	2812.874	111.022	1.65e+04
LayerCAM	0.023	33.782	11.712	555.22
Score-CAM	0.09	14.97	19.046	2053.248
Ablation-CAM	-	-	-	-
Exp. G-CAM	**0.004**	**0.12**	**0.573**	**73.934**

(Figure 7a), leading to an underestimation of feature attributions. This results in sparse, uninformative, and ill-formed explanations (Figure 7b). This is evident when inspecting the top-k most important patches according to the generated attribution maps, which focus on background areas rather than the target class (*yawl*). Consequently, when these patches are inserted, they produce low model confidence (Insertion IAUC) (Figure 7b). Conversely, our method focuses on salient discriminative areas of the image that characterize the target label (*i.e.*, *yawl*) and highly activate the neural network, demonstrating high fidelity to the model's inner workings, robustness to internal saturation, and high localization by focusing only on the most important regions.

Table 7: Infidelity (Yeh et al., 2019) on 500 CIFAR10 (Ho-Phuoc, 2018) samples using VGG-16 (Simonyan & Zisserman, 2014), ResNet-50 (He et al., 2015), and AlexNet (Krizhevsky et al., 2012). Samples upsampled to 96×96; patch size 32. Values scaled by 10^7, 10^8, 10^9 respectively.

	VGG16	ResNet-50	AlexNet
Method	**↓ Inf.**	**↓ Inf.**	**↓ Inf.**
Grad-CAM	1592.0	94.2	594.6
Grad-CAM++	1506.5	88.9	542.0
Smooth Grad-CAM++	1673.5	82.9	479.0
Integrated Grad-CAM	1640.0	37.9	483.0
Hi-Res CAM	1585.6	77.6	594.1
XGrad-CAM	1549.2	93.5	575.0
LayerCAM	1457.0	92.5	555.1
Score-CAM	1751.7	157.3	656.6
Ablation-CAM	1670.2	76.5	619.7
Expected Grad-CAM	**4.7**	**3.8**	**9.6**

Table 8: Running time (seconds) on 100 sequential runs using VGG-16 (Simonyan & Zisserman, 2014) on CIFAR10 (Ho-Phuoc, 2018). Averaged values displayed. Methods evaluated under identical hardware conditions.

Method	**↓ R.T.**
Grad-CAM	**0.006**
Grad-CAM++	**0.006**
Smooth Grad-CAM++	0.121
Integrated Grad-CAM	0.156
Hi-Res CAM	**0.006**
XGrad-CAM	**0.006**
LayerCAM	**0.006**
Score-CAM	0.261
Ablation-CAM	0.302
Expected Grad-CAM	0.115

Samples

(a)

(b)

(c) Excerpt of 25 random samples from *ILSVRC2012* Russakovsky et al. (2014) (8a) used to evaluate internal saturation at various points. Figure 8b presents a subset of samples generated through feature scaling over 25 steps.

(a)

(b)

(c) Internal saturation analysis of intermediary target layers in VGG16 Simonyan & Zisserman (2014), AlexNet Krizhevsky et al. (2012), and ResNet-50 He et al. (2015). Figure 9a presents the cosine similarity between activation vectors of CAM target filters. Figure 9b depicts the mean values with error bars indicating 2 standard deviations. For VGG16 and AlexNet, the final feature layer is used, while for ResNet-50, the *layer*4 is selected.

(a)

(b)

(c) Output saturation analysis in VGG16 Simonyan & Zisserman (2014), AlexNet Krizhevsky et al. (2012), and ResNet-50 He et al. (2015) (fig. 10a). Figure 10a displays the softmax scores for the top label, while Figure 10b depicts the mean values with error bars indicating 2 standard deviations.

Figure 11: Gradients are noisy. A comparison of gradient-based CAM methods under optimal conditions shows that even recent methods exhibit high sensitivity.

Figure 12: Comparison of gradient-based and non-gradient-based CAM methods. The top row illustrates the noisiness and tendency to produce ill-formed explanations in gradient-based methods, including recent approaches Sattarzadeh et al. (2021). *Score-CAM* Wang et al. (2019) addresses this issue by eliminating the use of gradients. Our method demonstrates the ability to generate sharper and more stable explanations consistently, even with the use of gradients.

C   Qualitative Evaluation

Next we provide the extended version of all the figures *i.e.*, including all the comparative baseline methods and some additional examples.

(c) Comparison of the attribution maps for various methods under normal (13b) and internal saturation condition (13a). Extended version containing all baseline attribution methods.

Figure 14: Comparison of saliency maps between our method and all the baseline methods on the *ILSVRC2012* Russakovsky et al. (2014).